

INTERNATIONAL JOINT COMMISSION  
**MENOMONEE RIVER**  
PILOT WATERSHED STUDY

---

DRAFT  
FINAL REPORT  
VOLUME 5

SIMULATION OF POLLUTANT LOADINGS  
AND RUNOFF QUALITY

COOPERATING AGENCIES

WISCONSIN DEPARTMENT OF  
NATURAL RESOURCES  
JOHN G. KONRAD


UNIVERSITY OF WISCONSIN SYSTEM  
WATER RESOURCES CENTER  
GORDON CHESTERS

SOUTHEASTERN WISCONSIN REGIONAL  
PLANNING COMMISSION  
KURT W. BAUER

Sponsored by

INTERNATIONAL JOINT COMMISSION  
POLLUTION FROM LAND USE  
ACTIVITIES REFERENCE GROUP

UNITED STATES ENVIRONMENTAL  
PROTECTION AGENCY



November 1979



by

D. BALSIGER\*  
WISCONSIN DEPARTMENT OF NATURAL RESOURCES

G. V. SIMSIMAN  
G. CHESTERS  
WISCONSIN WATER RESOURCES CENTER

R. BANNERMAN  
J. G. KONRAD  
WISCONSIN DEPARTMENT OF NATURAL RESOURCES

Grant Number: R005142

THIS STUDY WAS CONDUCTED IN COOPERATION WITH:

WISCONSIN DEPARTMENT OF NATURAL RESOURCES  
UNIVERSITY OF WISCONSIN SYSTEM WATER RESOURCES CENTER  
SOUTHEASTERN WISCONSIN REGIONAL PLANNING COMMISSION

\*CURRENTLY IN THE DEPARTMENT OF STATISTICS, UNIVERSITY  
OF WISCONSIN-MADISON

U.S. Environmental Protection Agency  
GLNPO Library Collection (PL-12J)  
77 West Jackson Boulevard,  
Chicago, IL 60604-3590

#### DISCLAIMER

This report has been reviewed by the Great Lakes National Program Office of the U.S. Environmental Protection Agency, Region V Chicago, and approved for publication. Mention of trade names of commercial products does not constitute endorsement or recommendation for use.

## PREFACE

Prediction of pollutant loadings from non-point sources is an important aspect of water quality management. A well-calibrated mathematical model verified with extensive monitoring data may be applied to other watersheds for predictive purposes. This volume contains two reports on the application of the LANDRUN model and a discussion of a simple, empirical model for predicting runoff quality. The LANDRUN model is utilized to 1. assess sediment loadings from 48 subwatersheds in the Menomonee River Watershed in an attempt to identify critical areas that are most cost-effective in terms of pollution control and 2. obtain unit pollutant loadings for typical land uses to better understand the processes involved in pollution generation and transport from urban and non-urban areas.

## CONTENTS

Title Page .....	i
Disclaimer .....	ii
Preface .....	iii
Contents .....	iv
*Part I     Assessing Pollutant Loadings from Subwatersheds with Mixed Land Uses .....	I-i
*Part II    Model Enhanced Unit Loading (MEUL) - A Method of Assessing Pollutant Loadings from a Single Land Use .....	II-i
*Part III   A Simple, Empirical Model for Predicting Runoff Quality from Small Watersheds .....	III-i

---

\*Detailed contents are presented at the beginning of each part.

PART I

ASSESSING POLLUTANT LOADINGS FROM  
SUBWATERSHEDS WITH MIXED LAND USES

by

D. BALSIGER  
R. BANNERMAN  
G. V. SIMSIMAN  
J. G. KONRAD  
G. CHESTERS

#### ABSTRACT

Simulations of sediment loadings for various land uses in 48 subwatersheds of the Menomonee River Watershed are performed using the LANDRUN model. In order to determine critical source areas, simulated loadings are adjusted based on delivery ratios estimated for pervious areas in each subwatershed. Nine subwatersheds, consisting of 16% of the total area of the Watershed, are identified as critical source areas with developing lands being the primary contributors of sediments. The criticality of a subwatershed in terms of nonpoint source pollution appears to be enhanced by the extent of connected imperviousness and proximity to the stream of that area.

## CONTENTS - PART I

Title Page .....	I-i
Abstract .....	I-ii
Contents .....	I-iii
Figures .....	I-iv
Tables .....	I-v
I-1. Introduction .....	I-1
I-2. Conclusions .....	I-2
I-3. Methodology .....	I-3
Source and Form of Data for LANDRUN Simulation .....	I-3
Manipulation of Land DMS Data Prior to Calibration .....	I-3
Calibration, Verification and Determination of Degree of Connected Imperviousness .....	I-6
Simulations for 48 Subwatersheds and Determination of Sediment Delivery Ratios .....	I-7
I-4. Results and Discussion .....	I-10
References .....	I-15
Appendix	
I-A. Simulated Loadings for 48 Subwatersheds .....	I-16

# FIGURES

<u>Number</u>		<u>Page</u>
I-1	The 48 subwatersheds in the Menomonee River Watershed ...	I-4
I-2	Simulated (S) and monitored (M) sediment loadings (kg/ha) from area adjacent to mainstem monitoring stations--summer, 1977 .....	I-11
I-3	Distribution of simulated sediment loadings in the Menomonee River Watershed--summer, 1977 .....	I-12

# TABLES

<u>Number</u>		<u>Page</u>
I-1	Land use categories (1975) in the 48 subwatersheds of the Menomonee River Watershed .....	I-5
I-2	Estimated sediment delivery ratios for various land uses (LU) in the 48 subwatersheds of the Menomonee River Watershed .....	I-9
I-3	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in the Menomonee River Watershed--summer, 1977 .....	I-14
I-A-1	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 12A--summer, 1977 .....	I-16
I-A-2	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 12B--summer, 1977 .....	I-16
I-A-3	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 12C--summer, 1977 .....	I-17
I-A-4	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 12D--summer 1977 .....	I-17
I-A-5	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 12E--summer 1977 .....	I-18
I-A-6	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10A--summer 1977 .....	I-18
I-A-7	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10B--summer 1977 .....	I-19
I-A-8	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10C--summer 1977 .....	I-19

I-A-9	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10D--summer 1977 .....	I-20
I-A-10	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10E--summer 1977 .....	I-20
I-A-11	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7A--summer 1977 .....	I-21
I-A-12	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7B--summer 1977 .....	I-21
I-A-13	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7C--summer 1977 .....	I-22
I-A-14	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7D--summer 1977 .....	I-22
I-A-15	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7E--summer 1977 .....	I-23
I-A-16	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7F--summer 1977 .....	I-23
I-A-17	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7G--summer 1977 .....	I-24
I-A-18	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7H--summer 1977 .....	I-24
I-A-19	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 11A--summer 1977 .....	I-25
I-A-20	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 11B--summer 1977 .....	I-25
I-A-21	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 11C--summer 1977 .....	I-26

I-A-22	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 8A--summer 1977 .....	I-26
I-A-23	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 8B--summer 1977 .....	I-27
I-A-24	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 8C--summer 1977 .....	I-27
I-A-25	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 9--summer 1977 .....	I-28
I-A-26	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 6A--summer 1977 .....	I-28
I-A-27	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 6B--summer 1977 .....	I-29
I-A-28	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 6C--summer 1977 .....	I-29
I-A-29	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 6D--summer 1977 .....	I-30
I-A-30	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 6E--summer 1977 .....	I-30
I-A-31	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 6F--summer 1977 .....	I-31
I-A-32	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 4A--summer 1977 .....	I-31
I-A-33	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 4B--summer 1977 .....	I-32
I-A-34	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 4C--summer 1977 .....	I-32

I-A-35	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3D--summer 1977 .....	I-33
I-A-36	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3A--summer 1977 .....	I-33
I-A-37	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3B--summer 1977 .....	I-34
I-A-38	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3C--summer 1977 .....	I-34
I-A-39	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3D--summer 1977 .....	I-35
I-A-40	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3E--summer 1977 .....	I-35
I-A-41	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3F--summer 1977 .....	I-36
I-A-42	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3G--summer 1977 .....	I-36
I-A-43	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3H--summer 1977 .....	I-37
I-A-44	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 5--summer 1977 .....	I-37
I-A-45	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 7--summer 1977 .....	I-38
I-A-46	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 1A--summer 1977 .....	I-38
I-A-47	Water ( $m^3$ ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 1B--summer 1977 .....	I-39

I-A-48	Water (m <sup>3</sup> ) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 19--summer 1977 .....	I-39
--------	---	------

## I-1. INTRODUCTION

Identifying critical source areas of nonpoint pollution in a watershed is imperative if economical means of remedial control measures are to be adopted. Because monitoring of all potential source areas in relatively large watersheds, like the Menomonee River Watershed (35,000 ha), incurs extremely large expense and time, a model capable of predicting pollutant loads from smaller components of the total watershed is very useful.

LANDRUN, a dynamic runoff-sediment overland transport model, after initial calibration and verification, has demonstrated its capability of simulating field data for such parameters as runoff, sediment and adsorbed phosphorus (1). One application of LANDRUN is the prediction of pollutant loadings from subwatersheds of diverse land uses and physical characteristics. An attempt was made to use LANDRUN in simulating runoff and sediment loadings from 48 subwatersheds in the Menomonee River Watershed. Such application of the model is described in this report and results obtained should aid in demonstrating what land features, land uses or land activities contribute to high pollutant loadings. Water and sediment loadings were simulated during the summer of 1977.

## I-2. CONCLUSIONS

The LARPRON model was capable of simulating water and sediment loadings for various land uses in 48 subwatersheds. Delivery ratio for each land use was necessary to adjust sediment loadings from pervious areas. Simulated sediment loadings were found to compare reasonably well with monitored data from the mainstem stations.

Nine critical nonpoint source subwatersheds, constituting 16% of the total area of the Watershed, were identified and contributed about 50% of the total sediment loadings. Developing areas were the primary contributor of sediments. Although developing lands occupy a small portion of the subwatershed (1 to 5%), they contributed high amounts (50 to 85%) of sediment loadings. The criticality of a source area can be enhanced by the extent of connected imperviousness and proximity to the stream of that subwatershed. It appears that developing areas in urbanizing subwatersheds are the best cost-effective in terms of management.

### I-3. METHODOLOGY

#### Source and Form of Data for LANDRUN Simulation

LANDRUN is a mathematical model developed as a method of analysis for estimating the quantity and quality of runoff and eroded particulates emanating from watersheds having mixed land uses. The description of this model and the discussion of its initial calibration and verification are given in (1).

To perform LANDRUN simulations for the 48 subwatersheds in the Menomonee River Watershed (Fig. I-1.) two types of data are needed, namely, 1. land use and associated characteristics in each subwatershed and 2. meteorological information obtained within and near the Watershed. Data on land use, soils, slope and degree of imperviousness on the 48 subwatersheds were provided by the Land Data Management System (Land DMS) described in (2). The 79 land use descriptions were consolidated into 14 land use categories (Table I-1). The consolidation grouped similar land uses and land uses that have similar potential for non-point pollution (3). Data obtained from the Land DMS were in the form of area of each slope category for each soil type found for each of the 14 land uses in each subwatershed. The Land DMS also provided the degree of imperviousness for each land use for each of the subwatersheds.

Meteorological data were obtained from two sources. Precipitation data, in the form of hourly precipitation totals, were furnished by the U.S. Geological Survey (USGS) from eight precipitation gauges located throughout the Watershed. Maximum and minimum daily temperatures, as well as daily evaporation values, were obtained from the National Weather Service at Mitchell Field.

Dust and dirt data which include dust and dirt fallout, washout coefficient and sweeping efficiency were obtained from the Chicago study on pollution from urban areas (4). Information on sweeping frequency was provided by the Engineering Office of the cities in the Watershed.

#### Manipulation of Land DMS Data Prior to Calibration

LANDRUN, like other similar overland flow models, is sensitive to the degree of imperviousness connected directly to storm sewers and streams, and for pervious areas, to soil permeability, interception and depression storage. The model requires dividing the Watershed into uniform areas based on land use and soil characteristics. A land use with two different soil groups was considered as two sub-areas. For a single land use in a subwatershed, the many soil types were grouped into hydrologic soil groups B, C and D (soils under group A are insignificant in the Watershed). An area-




Fig. I-1. The 48 subwatersheds in the Menomonee River Watershed.

Table 1. Land use categories (1975) in the 49 subwatersheds of the Monumee River watershed

Subwatershed	Area, ha	Land use distribution, %														Total area, ha	Total area, km <sup>2</sup>
		1	2	3	4	5	6	7	8	9	10	11	12	13	14		
12A	429	0.4	3.3	0	6.7	3.7	0.1	7.8	17	48	2.6	0.4	0	0	0	0	0
12B	1,200	4.3	3.2	1.9	0.3	6.2	1.6	3.6	36	29	6.2	7.6	0.2	0	0	0	0
12C	571	0.6	1.8	0	0	9.6	1.9	1.5	11	43	1.4	4.8	0.5	0	0	0	0
12D	681	0	2.4	0	0	3.5	1.5	0.1	17	47	1.2	3.2	0	0	0	0	0
12E	1,593	0	0.7	0	0	4.3	1.4	2.1	31	30	1.4	8.8	0.1	0	0	0	0
10A	399	0.2	5.0	0	2.0	37	0.2	6.4	14.3	21	1.5	2.4	0	0	0.1	23	1
10B	459	1.1	4.6	5.9	1.8	36	2.5	1.2	15	25	0.2	0	0	0	0	0	0
10C	507	0.1	3.1	2.7	0	9.6	1.4	1	34	22	23	3.2	0	0	0	0	0
10D	1,610	1.8	1.1	2.2	0.1	12	1.6	5.9	19	48	1.1	5	0.2	0	0.5	2	0
10E	353	0	0.1	0.8	0	14	1.2	1.7	7	26	8.5	1.1	0	0	0.1	0	0
7A	981	3.1	5.2	8.0	0	18	0.6	5.0	8.9	40	0	2.2	0	0	1.7	2	13
7B	820	5.9	5.9	2.7	0.4	6.8	1.3	1.3	18	51	2.8	6.8	0	0	0.6	0	0
7C	515	0	3.1	0	0.2	48	0.1	6.7	9.0	28	2.6	0.7	0	0	0	0	0
7D	1,406	1.1	3.2	0	0.1	56	0.4	6.5	5.1	39	3.8	2.0	0	0	0.3	0	0
7E	307	2.7	8.2	3.5	0	28	1.0	3.0	5.3	41	5.2	0	0	0	0	0	0
7F	832	1.4	6.6	0	0	24	0.9	4.9	11	37	3.4	0.4	0	0	0.2	0	0
7G	1,354	2.7	4.9	2.4	0.2	8.3	1.5	6.5	28	32	8.4	1.1	0	0	0.2	0	0
7H	251	0.2	8.3	0	4.5	65	0	4.8	0.1	16	9.4	1.3	0.1	0	0	0	0
1A	527	0	1.2	0	0	2.4	2.5	0.2	1.8	15	6.2	1.5	0	0	0	0	0
12F	657	0	0.2	0	0.2	7.6	1.4	7	12	38	10	1.2	0.4	0	0.1	0	0
11C	765	0	1.3	0	0	12	1.3	1.1	29	31	12	0.8	0.7	0	0	0	0
2	555	3.4	15	1.6	6.8	41	0.1	3.9	0.1	5	0.5	0.1	0	0	0.6	0	0
8A	294	0.1	2.6	7.7	2.9	36	0.4	4.5	2.6	16	1.2	0.6	0	0	0.5	26	2
8B	853	1.3	7.8	0	2.9	13	0.4	3.8	1.7	15	5.5	2.9	0	0	1.6	0	0
8C	1,011	2.2	9.8	0	1.9	4.3	1.6	6.2	26	17	13	6.9	0	0	0.7	0	0
6A	9.0	2.0	8.9	5.1	2.9	47	0	1.9	0	27	6.4	0	0	0	0.2	0	0
6B	1,111	4.5	15	5.7	2.6	41	0	2.8	0	26	6.8	2.0	0	0	0.5	0	0
6C	717	0.3	6.9	0	1.8	58	0.1	4.7	0	20	6.3	1.0	0	0	0	0	0
6D	662	0.1	1.0	0	1.3	53	0.1	4.4	0	24	5.4	6.2	0	0	0	0	0
6E	6.4	0	8.3	0	0	55	0.1	5.3	3.0	26	7.1	4.5	0	0	0	0	0
6F	295	6.3	4.3	0	0	23	0.1	0.1	3	50	10	10	0	0	0	0	0
4A	535	4.6	11	0.0	5.4	47	0	0.2	0	26	0	0	0	0	0	0	0
4B	752	2.5	9.1	0.4	2.3	69	0	4.4	0	16	0	0	0	0	0.3	0	0
4C	757	0.1	5.5	0	11	67	0	3.5	0	13	0	0	0	0	0.1	0	0
4D	749	0	6.4	2.7	5.1	49	0.1	1.2	1.2	23	1	0	0	0	0.6	0.1	0
3A	17	0.2	5.8	3	4.1	42	0	0.1	1.5	43	2.1	0	0	0	0.2	0	0
3B	97.0	1.1	4.2	0.2	5.0	69	0	0.3	0	19	0	0	0	0	0.2	0	0
3C	2.1	0	2.3	4.7	8.4	21	0	0.8	0	39	2.5	0	0	0	0	0	0
3D	665	15	24	7.1	0.5	26	0	1.4	0	30	1.1	0	0	0	0.6	0	0
3E	230	7.9	34	7.9	3.7	11	0	0.4	0	23	0.3	1	0	0	0.3	0	0
3F	446	3.7	17	1.9	0.1	32	0.1	2.4	0.6	33	0	0	0	0	0.2	0	0
3G	151	0.2	85	0	4.4	8.6	0	0	6	1.2	0	0	0	0	0	0	0
3H	652	8.1	15	1.2	5.4	32	0	1.8	0	17	3	0	0	0	0.2	0	0
5	1.5	0	5.6	0	0.4	87	0	2.0	0	5.3	0	0	0	0	0	0	0
1	132	0	7.2	0	3.3	77	0	0.2	0	13	0	0	0	0	0	0	0
1A	1,143	1.1	25	3.8	2.3	31	0.1	0	0	18	0	0	0	0	0.2	0	0
1B	380	6.3	18	5.9	5.5	40	0	0.2	0	18	0	0	0	0	0	0	0
1C	105	5.0	12	0	2.5	65	0	1.1	0	13	0	0	0	0	0	0	0
Total	39,397	2.6	7.2	1.8	1.9	29	0.7	3.1	15	4	5	2.1	0.1	0.3	0	27	24

Land use categories are: 1-industrial, 2-commercial, 3-farm (other lands are proportionately distributed among the other land uses), 4-low density residential, 5-medium density residential, 6-low density residential, 7-land under development, 8-row crops, 9-pasture and small grains, 10-forest, 11-wetlands, 12-feedlots, 13-landfill and dumps, 14-water areas (land use categories are described in Table III-5 found in Appendix A).

weighted mean slope was calculated for each land use-soil group sub-area (e.g., the row crop land use in a subwatershed was computed as Row Crop B, Row Crop C and Row Crop D; and having an associated area and mean slope). Saturation permeability and other soil characteristics could be inputted for each of the 3 soil groups within a particular land use.

Land DMS-land use data segregated all streets, freeways and off-street parking areas from other land uses into a transportation land use. In order to represent accurately the nature of urban land uses, it was necessary to integrate these impervious areas back into the various land uses. Total area and degree of imperviousness data were adjusted to account for this additional area. Freeways were retained as a separate land use.

#### Calibration, Verification and Determination of Degree of Connected Imperviousness

Starting with values used in the initial calibration and verification of the model (5), individual events, sequences of events and eventually the entire 1977 summer season were simulated for subwatersheds in which good monitored data were available for comparison.

The hydrology portion of the model was first calibrated on subwatersheds 5 and 9 (Schoonmaker Creek-413010 and Noyes Creek-413011), each of which had water quality data and flow information from a sampling site which monitored only that subwatershed. Both subwatersheds are predominantly medium density residential although the Noyes Creek area is a newer development. Additional calibration was performed on the 3 subwatersheds (11A, 11B and 11C) which comprise the area monitored by the Donjes Bay Road station (463001) and the 4 subwatersheds (4A, 4B, 4C and 4D) monitored by the Honey Creek sampling site (413006). The Donjes Bay Road subwatersheds are predominantly rural while the Honey Creek subwatersheds are mostly residential, but with significant pervious areas on the southernmost subwatershed (4D). Simulation of these urban, rural and mixed land use areas and comparisons of simulated flows with monitored flows led to the determination of connected imperviousness values for the calibration subwatersheds. Calibration of the sediment portion of the model was done on the Noyes and Schoonmaker Creeks subwatersheds as these small urban areas were expected to have a delivery ratio much closer to unity than the larger subwatersheds or rural areas.

Simulations on other subwatersheds for verification showed that the degree of connected imperviousness could be described as a function of the extent of storm sewerage in a subwatershed. The degree of directly connected imperviousness is the single most important factor influencing simulated runoff from urban areas. For this reason, it was necessary to obtain detailed information from maps, conversation with city engineers, etc. concerning the extent of storm sewerage, the precise location of new residential developments, the usage of grass ditches for drainage, etc. The result of this exercise was a set of connected imperviousness values for the land uses modified according to individual differences in each subwatershed. The area of directly connected impervious surfaces was calculated for each land use in each subwatershed in the following manner. The model was used to determine percentages of directly connected imperviousness for completely sewerage and

unsewered subwatersheds. Values for partially sewerd subwatersheds were derived by prorating on the basis of the land use which was in the sewerd area of that subwatershed. Examples of percentages of directly connected imperviousness are shown below.

Land use	Completely sewerd	Partially sewerd (~60%)	Unsewerd
Industrial	80	45	8
Medium density residential	60	35	3
Low density residential	20	5	1
Parks/recreation	30	15	1

#### Simulations for 48 Subwatersheds and Determination of Sediment Delivery Ratios

After calibration and verification was completed, simulations were run on all subwatersheds. Simulated flow values from the individual subwatersheds were summed accordingly and were found to compare favorably with measured flows at the several mainstem river sampling stations. Simulated sediment values corresponded reasonably well with loading estimates calculated from monitored values for urban areas where a large part of the sediment originates from impervious surfaces and the degree of connected imperviousness is high. Calibration in these areas is accomplished by manipulation of the cropping management factor for developing areas and doubling the literature values for dust and dirt accumulation values. In more pervious areas and rural areas, simulated sediment values were much higher than monitored loading estimates (e.g., as much as 20 to 30 times higher in Donges Bay Road). Thus, there was a need to develop a series of sediment delivery ratios for the land uses in each subwatershed.

Proceeding as in the runoff calibration process, it was determined that sediment delivery ratios were dependent on the extent of storm sewerding (connected imperviousness) in the subwatersheds. Other important factors are proximity to runoff channels and characteristics of the land use (e.g., parks vs. small grains, airport vs. shopping center). Again, it was necessary to collect detailed information to characterize the land uses in each watershed.

Land uses were grouped into three categories and each category was assigned a sediment delivery ratio for each subwatershed. "Urban" land uses included industrial, commercial, medium and high density residential. "Rural" land uses included agricultural areas, parks, low density residential and landfills. Developing lands (construction), the third category, had such a high sediment yield compared to the other land uses that it was assigned its own delivery ratio. Resulting delivery ratios ranged from 1.0 for "urban" land uses in completely storm sewerd urban areas to 0.01 for developing lands

in non-sewered areas. Table I-2 shows the sediment delivery ratios for the subwatersheds for the 1977 summer simulations.

Table I-2. Estimated sediment delivery ratios for various land uses (LU) in the 48 subwatersheds of the Menomonee River Watershed

STORLT No.	Monitoring station Location	Adjacent subwatershed	Delivery ratios*		
			LU 1-5	LU 7	LU 6,8-13
673001	MR at River Lane Rd. (Hwy. F)	12A, 12L 12B, 12C, 12D	0.34 0.03	0.02 0.015	0.03 0.03
683002	MR at Pilgrim Rd. (Hwy. YY)	10A 10B, 10C, 10D 10E	0.80 0.03 0.60	0.02 0.015 0.02	0.03 0.03 0.03
683001	MR at 124th St. (Hwy. M)	7A 7B, 7D, 7F, 7G 7C 7E 7H	1.0 0.03 0.15 0.53 0.81	0.30 0.03 0.04 0.15 0.30	0.06 0.03 0.03 0.03 0.06
463001	Donges Bay Rd., Mequon	11A, 11B, 11C	0.03	0.03	0.03
413011	Noyes Creek at 91st St.	9	1.0	0.70	0.06
413008	Little MR at Appleton Ave. (Hwy. 175)	8A 8B 8C	1.0 1.0 0.03	0.40 0.10 0.07	0.06 0.03 0.03
413007	Underwood Creek above Hwy. 45 off North Ave.	6A 6B 6C, 6D, 6F 6E	0.35 0.25 0.03 0.03	0.10 0.04 0.015 0.01	0.10 0.05 0.03 0.03
413006	Honey Creek 140 m above confluence with MR	4A, 4B, 4C 4D	1.0 1.0	0.70 0.50	0.30 0.30
413005	MR at 70th St. Bridge	3A, 3B, 3C, 3E, 3F, 3H 3D 3G	1.0 0.52 0.60	0.70 0.30 0.70	0.30 0.10 0.15
413010	Schoonmaker Creek at Vliet St.	5	1.0	0.70	0.30
413009	MR at Hawley Rd.	2	1.0	0.70	0.30
413004	MR above 27th St. at Falk Corp.	1A, 1B, 19	1.0	1.0	1.0

\*For pervious areas only; delivery of dust and dirt from impervious areas is assumed to be 1.0.

#### I-4. RESULTS AND DISCUSSION

Extensive monitoring at the mainstem of the Menomonee River reveals that the more urbanized areas in the lower portion of the Watershed contributed greater sediment loadings than the rural upper portion (Fig. I-2). Mainstem monitoring could show general areas of nonpoint sources of pollutants, however, identification of critical areas is quite difficult because adjacent areas monitored by the major stations are too large (3,000 to 7,000 ha). Estimation of pollutant loadings on smaller units should provide reasonable precision for identifying critical source areas where best management practices can be applied.

Water and sediment loadings simulated by LANDRUM during the summer of 1977 for the 48 subwatersheds (200 to 1,600 ha) of the Menomonee River Watershed are shown in Tables I-A-1 to I-A-48. Loadings are given for all land uses identified in a particular subwatershed. The sediment data were adjusted accordingly taking into account delivery ratios (Table I-2) for pervious areas in the various land uses. Dust and dirt accumulations on impervious surfaces were assumed to have 100% delivery. Delivery ratio for a land use was estimated based on its physical characteristics, extent of connected imperviousness and proximity to the stream.

Simulated sediment loadings were found to compare reasonably well with those monitored at all but one of the mainstem stations (Fig. I-2). At station 673001, the simulated data was almost 3 times as high as the monitored data. The extremely low sediment loading measured at this station could be due to the trapping effect of a large pond just upstream of the station. The close agreement between the simulated and monitored data indicates the validity of the delivery ratios used for each land use and the integrity of the sediment estimates for each subwatershed.

Results of simulations showed that nine subwatersheds (7H, 7A, 8A, 9, 3F, 3H, 3C, 4C and 4D) contributed significant amounts of sediments (Fig. I-3). These high source areas, located in the urbanized lower portion of the Watershed, constitute 16% of the total area (calculated up to station 413005) but contributed almost 50% of the total sediment loadings. The high sediment yields from these subwatersheds can be ascribed mainly to developing areas and---to a certain degree---to medium density residential areas. Developing areas were present in almost all of the subwatersheds. However, high amounts of sediments were transported from developing areas in the critical subwatersheds essentially because of their short distances to the stream and extensive connected imperviousness. Although high amounts of sediment can be eroded in other subwatersheds particularly those in the rural portion of the Watershed, delivery of sediment to the stream could be impeded as a result of low connected imperviousness and/or greater distance to the stream. Medium density residential areas, the predominant land use in the critical subwatersheds, were significant sources of sediment loadings. Due to extensive impervious surfaces in these areas, dust and dirt washoff was prevalent.




Fig. I-2. Simulated (S) and monitored (M) sediment loadings (kg/ha) from area adjacent to mainstem monitoring stations--summer, 1977 (monitored data taken from (6)).



It is evident from the critical subwatersheds (Tables I-A-11, I-A-18, I-A-22, I-A-25, I-A-34, I-A-35, I-A-38, I-A-41 and I-A-43) that the majority of the sediment loadings (50 to 85%) originated from small areas (1 to 5%) that were under development. This also can be seen in Table I-3, which is an integration of the loadings from various land uses in the entire Watershed. Over 50% of the total sediment loadings was contributed by developing areas occupying just 3% of the total area of the Watershed.

It has been shown that the model is a useful tool in identifying critical nonpoint source areas of sediment in the Menomonee River Watershed. Results indicate that developing areas in urbanizing subwatersheds are the most cost-effective to manage. The method is applicable to other watersheds. However, the difficulty of simulating sediment loadings on pervious areas requires some recalibration and reverification of the model in other watersheds using monitored data.

Table 1-1. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by land use in the Menominee River Watershed (area in ha)--Summer 1977

LAND USE	WATER PERV	WATER IMPR	WATER TOTAL	SEDIMENT IMPR	SEDIMENT TOTAL	AREA IMPR	AREA TOTAL
INDUSTRIAL	108653. 2.3%	398707. 7.5%	1107365. 6.2%	5440. .1%	122654. 7.2%	449. 6.4%	635. 7.0%
COMMERCIAL	530245. 11.4%	3023755. 6.1%	3554010. 20.1%	10976. 1.4%	40115. 7.1%	1334. 19.0%	1041. 1%
MED/DENS/RES	1316740. 26.4%	5313647. 44.5%	131387. 40.2%	37266. 14.8%	1253462. 27.9%	3071. 43.3%	3110. 28.5%
LO/DENS/RES	32057. .7%	4459. .0%	3510. .2%	1841. .1%	410. .1%	2. .4%	247. .8%
HI/DENS/RES	139462. 3.0%	972418. 7.4%	1112280. 5.3%	40810. .5%	141118. 6.5%	359. 5.1%	634. 1.3%
DEVELOPING	1987323. 25.4%	22587. .1%	136115. .7%	10000. .1%	222004. 7.7%	272. .8%	1003. 3.2%
ROW CROPS	7716. .1%	1. .0%	545. .0%	1000. .0%	33303. .7%	0. .0%	453. 1.4%
PA/REC/PASTR	394923. 7.9%	57021. .1%	1770930. 10.0%	14420. .4%	256651. 4.7%	213. 1.5%	455. .8%
FORESTS	42269. 1.1%	7. .0%	43089. .6%	433. .1%	490. .2%	0. .0%	109. .2%
WETLANDS	170156. 3.4%	0. .0%	170156. 7.6%	6695. .8%	1195. .3%	0. .0%	105. .2%
FIELDPTS	16278. .3%	0. .0%	16278. .3%	1009. .5%	13266. .3%	7. .0%	37. .1%
LANDFILL	7009. .1%	0. .0%	2135. .1%	100. .0%	10. .0%	0. .0%	106. .1%
WATER	0. .0%	655334. 6.6%	655334. 3.2%	0. .0%	2314. .1%	147. .2%	147. .1%
FREEWAYS	0. .0%	67667. .1%	67667. .3%	0. .0%	1003. .1%	0. .0%	0. .0%
RAVINES	444770. 9.1%	1305935. 10.0%	1770543. 10.0%	4132. .1%	14. .0%	100. .1%	34. .0%

#### REFERENCES - I

1. Novotny, V., M. A. Chin and H. Tran. Description and Calibration of a Pollutant Loading Model-LANDPUN. Final Report of the Menomonee River Pilot Watershed Study, Vol. 4, Environmental Protection Agency, 1979.
2. Walesh, S. G. Land Use, Population and Physical Characteristics of the Menomonee River Watershed. Part I: Land Data Management System. Final Report of the Menomonee River Pilot Watershed Study, Vol. 2, U.S. Environmental Protection Agency, 1979.
3. Simsiman, G. V., J. Goodrich-Mahoney, G. Chesters and R. Bannerman. Land Use, Population and Physical Characteristics of the Menomonee River Watershed. Part III. Description of the Watershed. Final Report of the Menomonee River Pilot Watershed Study, Vol. 2, U.S. Environmental Protection Agency, 1979.
4. American Public Works Association. Water Pollution Aspect of Urban Runoff. Water Pollution Control Research Journal WP-20-15, Washington, D.C., 1969.
5. Novotny, V., M. A. Chin and H. Tran. Description and Calibration of a Pollutant Loading Model-LANDRUN. Part II: Calibration and Verification of the Model. Final Report of the Menomonee River Pilot Watershed Study, Vol. 4, U.S. Environmental Protection Agency, 1979.
6. Bannerman, R., J. G. Konrad, D. Becker and G. V. Simsiman. Surface Water Monitoring Data. Part II: Quality of Runoff from Mixed Land Uses. Final Report of the Menomonee River Pilot Watershed Study, Vol. 3, U.S. Environmental Protection Agency, 1979.

# APPENDIX I-A. SIMULATED LOADINGS FOR 48 SUBWATERSHEDS

Table I-A-1. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LAIN (IN for each land use in Subwatershed 12A (Area = 1 ha) -- Summer 1997.

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	215. 2%	2125. 1.7%	2400. 1.0%	32. .1%	213. 1.7%	245. .5%	0 0%	2 2.3%	2 .4%
COMMERCIAL	12615. 10.4%	10260. 8.1%	22875. 9.2%	1107. 2.7%	1028. 8.1%	2135. 3.9%	6. 1.7%	2. 11.4%	14 3.3%
MED/DENS/RFS	12950. 10.6%	11711. 9.2%	24561. 9.9%	2610. 6.3%	1173. 9.2%	3783. 7.0%	25. 7.1%	12. 16.2%	37. 8.7%
LO /DENS/RFS	632. .5%	102. .1%	735. .3%	59. .2%	10. .1%	109. .2%	3. 7%	0. .5%	3. .7%
HI /DENS/RFS	16177. 13.3%	11611. 9.2%	27788. 11.2%	1927. 4.8%	1163. 9.2%	3150. 5.9%	17. 4.7%	12. 16.1%	29. 6.7%
LIVELCPING	41940. 35.4%	3922. 3.1%	46842. 18.9%	30744. 74.3%	290. 3.1%	31134. 57.6%	25. 7.1%	8 10.8%	33. 7.5%
ROW CROPS	534. .4%	0. 0%	534. .2%	2005. 4.8%	0. .0%	2005. 3.7%	74 20.9%	0. 0%	74. 17.3%
PK/HC/PASTR	34313. 28.3%	2816. 2.2%	37134. 15.0%	2740. 6.6%	283. 2.2%	3023. 5.5%	192. 54.1%	14 19.5%	207 48.1%
FORESTS	407. .4%	0. 0%	452. .2%	22. .1%	0. .0%	22 0%	11. 3.1%	0 .0%	11. 2.6%
WETLANDS	587. .5%	0. 0%	587. .2%	44. .1%	0. .0%	44. .1%	2. 4%	0. 0%	2 .4%
WATER	0 .0%	84111. 66.4%	84111. 33.9%	0 0%	8426. 66.4%	8426. 15.6%	0 0%	17 23.3%	17. 4.0%
TOTALS	21384. 17.6%	126638. 100.0%	248019. 100.0%	41790. 100.0%	12686. 100.0%	51076. 100.0%	755 100.0%	74 100.0%	429. 100.0%

Table I-A-2. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LAIN (IN for each land use in Subwatershed 12B (Area = 1 ha) -- Summer 1997.

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	11314. 7.6%	5189. 18.5%	16503. 9.3%	607. 1.2%	520 18.5%	1127 2.0%	39. 3.5%	13 15.5%	52 4.3%
COMMERCIAL	15275. 10.2%	4662. 11.2%	19937 11.2%	275. .5%	466. 16.5%	741. 1.3%	26 2.3%	13.9%	38 3.2%
MED/DENS/RFS	20223 13.5%	2542. 9.0%	22765 12.8%	520. 1.0%	256. 9.1%	776. 1.4%	57 5.1%	17 20.2%	75 6.2%
LO /DENS/RFS	1666 1.1%	103. .4%	1769. 1.0%	46. .1%	10. .4%	56 .1%	17. 1.5%	2 2.4%	19. 1.6%
HI /DENS/RFS	1850 1.2%	426. 1.5%	2282 1.3%	31 .1%	43 1.5%	74. .1%	2. 2%	1 1.7%	4. 3%
DEVELOPING	46213 30.8%	963 3.4%	47176 26.5%	37308 71.4%	97. 3.4%	37455 68.0%	37 3.3%	7 7.7%	44. 5.6%
ROW CROPS	2611 1.7%	0 .0%	2611 1.5%	5787. 11.1%	0. .0%	5787. 10.5%	432 38.3%	0 .0%	432. 36.0%
PK/HC/PASTR	29825 19.9%	412 1.5%	30237. 17.0%	5153. 9.7%	41. 1.5%	5194 9.4%	347. 30.4%	8 9.8%	351. 24.3%
FORESTS	2344 1.6%	0 0%	2344 1.3%	187. .4%	0. .0%	187 .3%	72. 6.4%	0 .0%	72 6.1%
WETLANDS	16410. 11.0%	0 .0%	16410. 9.2%	652. 1.2%	0 .0%	652 1.2%	84. 7.5%	0 .0%	84. 7.5%
FEEDLOTS	2102. 1.4%	0 .0%	2102. 1.2%	1688. 3.2%	0. .0%	1688 3.1%	6. 5%	0 0%	6. 5%
WATER	0 0%	9370. 33.3%	9374. 5.3%	0 0%	939. 33.3%	939 1.7%	0 0%	2.2%	2. 2%
FREEWAYS	0 .0%	4452. 15.8%	4452. 2.5%	0 .0%	446 15.8%	446 .8%	0 0%	22 26.6%	4. 1.3%
TOTALS	149839	28123.	177962.	52314.	2818	5532	1114.	20	1214.

Table I-A-3 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 1-B (area in ha) -- Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	2687. 2.9%	852. 4.7%	3539 3.2%	12. .1%	85 4.6%	97. .7%	1. 3%	2. 4.4%	4 .0%
COMMERCIAL	7356. 7.9%	1761 9.6%	9117. 8.1%	57 .5%	176. 9.6%	233. 1.7%	5. 1.0%	5. 4.8%	10. 1.8%
MED/DENS/RES	22955. 24.5%	2742 15.0%	25697 22.9%	468. 4.0%	274. 15.0%	742. 5.5%	36 6.9%	19. 40.5%	55. 9.5%
LO /DENS/RES	1324. 1.4%	83. .5%	1407. 1.3%	32. .3%	8. .4%	40. .3%	9 1.4%	2. 3.7%	11. 1.9%
DEVELOPING	14661. 15.6%	489. 2.7%	15150 13.5%	3955 33.3%	48. 2.6%	3903 29.1%	5 9%	3. 7.3%	8. 1.4%
ROW CROPS	865. .9%	0. .0%	865. .8%	2148 18.5%	0 0%	2148. 16.0%	178 33.8%	0. .0%	178. 31.1%
PK/REC/PASTR	35685 38.1%	637. 3.5%	36322. 32.4%	3007. 26.0%	64. 3.5%	3071. 24.9%	207. 39.1%	13 23.4%	220. 38.5%
FORESTS	2624. 2.8%	0. .0%	2624. 2.3%	199 1.7%	0 .0%	199 1.5%	54. 10.3%	0. .0%	54. 9.4%
WETLANDS	4040. 4.3%	0. .0%	4040. 3.6%	118 1.0%	0. .0%	118 9%	27. 5.3%	0. .0%	27. 4.8%
FEEDLOTS	1495. 1.6%	0. .0%	1495. 1.3%	1686. 14.6%	0 0%	1686. 12.6%	3. .5%	0. .0%	3. .5%
WATER	0. .0%	11719 64.1%	11719. 10.5%	0. 0%	1174 64.2%	1174. 8.8%	0 .0%	2. 5.2%	2. .4%
TOTALS	93692.	18283.	111975.	11582.	1829.	13411.	526.	46.	571.

Table I-A-4. Water (m<sup>3</sup>) and sediment (kg) loading estimated by LANDRUN for each land use in Subwatershed 1-B (area in ha) -- Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	6896. 8.6%	1771. 47.9%	8667. 10.4%	84. .5%	178. 47.3%	262. 1.7%	19. 2.0%	5 19.5%	24. 2.4%
MED/DENS/RES	10928. 13.7%	1395. 37.7%	12323 14.7%	207. 1.3%	139. 37.4%	346 2.2%	24. 2.5%	10. 41.1%	34. 3.5%
LO /DENS/RES	1965. 2.5%	102. 2.8%	2067. 2.5%	52. .3%	10. 2.7%	62. .4%	13 1.4%	2. 3.9%	15. 1.5%
DEVELOPING	5079. 6.4%	135. 3.6%	5214 6.2%	921. 6.0%	14. 3.8%	935 5.9%	3 .3%	1 4.0%	3. .3%
ROW CROPS	3395. 4.3%	0. .0%	3395. 4.1%	8730. 56.8%	0. .0%	8730. 55.5%	444. 46.4%	0 .0%	444. 45.3%
PK/REC/PASTR	38135 47.7%	300. 8.1%	38435. 46.0%	3947. 25.7%	31. 8.3%	3978. 25.3%	305. 31.8%	6. 26.0%	311. 31.7%
FORESTS	6381. 8.0%	0. .0%	6381 7.6%	596. 3.9%	0. .0%	596. 3.8%	116. 12.1%	0. .0%	116. 11.8%
WETLANDS	5922. 7.4%	0 .0%	5922. 7.1%	166. 1.1%	0. .0%	166. 1.1%	31 3.2%	0. .0%	31 3.2%
FEEDLOTS	1168 1.5%	0. .0%	1168. 1.4%	664. 4.3%	0. .0%	664. 4.2%	3. .3%	0. .0%	3 .3%
TOTALS	79869.	3703.	83572.	15367.	372.	15739.	958.	23.	981.

TABLE 1-4-10: Wetland (ha) and Water Impervious (kg) Loadings (kg/ha) for the 1990-2000 Period (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000)

LAND USE	WATER PERCENT	WATER IMPERV	WATER TOTAL	WATER PERCENT	WATER IMPERV	WATER TOTAL	WATER PERCENT	WATER IMPERV	WATER TOTAL
CONCRETE/PAVEMENT	27.0%	10.5%	10.5%	4.0%	10.5%	10.5%	6.0%	10.5%	10.5%
MEADOWS/GRASS	20.1%	11.0%	11.0%	10.5%	11.0%	11.0%	10.5%	11.0%	11.0%
FOREST/SHRUBS	24.7%	5.7%	5.7%	10.5%	5.7%	5.7%	10.5%	5.7%	5.7%
DEVELOPING	7.7%	5.3%	5.3%	4.3%	5.3%	5.3%	4.3%	5.3%	5.3%
ROW CROPS	9.1%	0.0%	0.0%	11.0%	0.0%	0.0%	11.0%	0.0%	0.0%
PERMANENT PASTURE	10.1%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%
FORESTS	10.1%	0.0%	0.0%	10.5%	0.0%	0.0%	10.5%	0.0%	0.0%
WETLANDS	20.1%	0.0%	0.0%	10.5%	0.0%	0.0%	10.5%	0.0%	0.0%
DEVELOPING	7.7%	0.0%	0.0%	4.3%	0.0%	0.0%	4.3%	0.0%	0.0%
WATER	0.0%	10.5%	10.5%	0.0%	10.5%	10.5%	0.0%	10.5%	10.5%
TOTALS	140.7%	21.5%	162.2%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%

TABLE 1-4-11: Wetland (ha) and Water Impervious (kg) Loadings (kg/ha) for the 1990-2000 Period (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000) (1990-2000)

LAND USE	WATER PERCENT	WATER IMPERV	WATER TOTAL	WATER PERCENT	WATER IMPERV	WATER TOTAL	WATER PERCENT	WATER IMPERV	WATER TOTAL
INDUSTRIAL	8.3%	11.0%	11.0%	10.5%	11.0%	11.0%	10.5%	11.0%	11.0%
COMMERCIAL	4.0%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%
MEADOWS/GRASS	14.3%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%
FOREST/SHRUBS	14.3%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%
DEVELOPING	24.3%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%
ROW CROPS	3.0%	0.0%	0.0%	10.5%	0.0%	0.0%	10.5%	0.0%	0.0%
PERMANENT PASTURE	20.1%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%
FORESTS	0.0%	0.0%	0.0%	10.5%	0.0%	0.0%	10.5%	0.0%	0.0%
WETLANDS	21.2%	0.0%	0.0%	10.5%	0.0%	0.0%	10.5%	0.0%	0.0%
LANDFILL	3.0%	0.0%	0.0%	10.5%	0.0%	0.0%	10.5%	0.0%	0.0%
WATER	0.0%	10.5%	10.5%	0.0%	10.5%	10.5%	0.0%	10.5%	10.5%
TOTALS	113.7%	30.6%	44.3%	10.5%	10.5%	10.5%	10.5%	10.5%	10.5%

Table I-A-7. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in S. Watershed, 1000 ft<sup>2</sup> cell, Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	499. .5%	1649. 3.9%	2148. 1.5%	2. .0%	181 3.4%	183. 1.1%	0. 1%	5 2.4%	5. 4.5%
COMMERCIAL	6230 6.2%	5872. 14.1%	12102. 8.5%	73 .6%	645 14.0%	718 4.1%	4. 1.3%	17 12.7%	21 4.4%
MFD/DENS/RES	55286 55.2%	7904. 18.9%	63190 44.5%	1627 12.7%	969 18.9%	2496. 14.3%	107 32.5%	67 45.7%	174. 36.4%
LO /DENS/RES	1873. 1.9%	68. .2%	1941 1.4%	63. .5%	8 .2%	71. .4%	10 3.0%	2 1.2%	12 2.5%
HI /DENS/RES	5194. 5.2%	1245 3.0%	6438. 4.5%	30 .2%	147 3.0%	167 1.0%	4 1.1%	5 3.6%	8 1.6%
DEVELOPING	14019. 14.0%	648. 1.6%	14667. 10.3%	2823. 2.0%	71. 1.5%	2894 1.6%	4. 1.1%	5. 2.7%	9. 4.4%
ROW CROPS	2315 2.3%	0. 0%	2315. 1.6%	6365. 49.7%	0. 0%	6365 26.6%	27 21.2%	0 0%	27 15.2%
PK/REC/PASTR	14583. 14.6%	323. .8%	14906. 10.5%	1917 14.2%	36 .8%	1853. 10.7%	127 4.7%	7 5.6%	134. 20.2%
FORESTS	0. 0%	0. .0%	0. .0%	0. .0%	0. .0%	0. .0%	0 0.3%	0. 0%	0. 4.5%
WETLANDS	187 .2%	0. 0%	187. 1%	2 0%	0 .0%	2. .0%	2 0%	0 0%	2 4%
WATER	0. .0%	19302. 46.2%	19302. 13.6%	9 .0%	2122 46.2%	2122 12.2%	0 0%	4 3.3%	4 1.7%
FREEWAYS	0. 0%	4753 11.4%	4753 3.3%	0 0%	522. 11.4%	522. 3.0%	0 0%	27 20.4%	27 5.7%
TOTALS	100185.	41764.	141949.	12205	4591	17396	2.8.	131.	454

Table I-A-8. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in D. Watershed, 1000 ft<sup>2</sup> cell, Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	84 .1%	145. 1.9%	229 .3%	0 .0%	15. 1.9%	15 .1%	0. 0%	1.1%	1.1%
COMMERCIAL	9362. 13.4%	2105. 27.2%	11467. 14.8%	97. .5%	211 27.2%	208. 1.6%	4. 2.7%	5 15.4%	16. 3.1%
MFD/DENS/RES	15113. 21.7%	1459. 18.8%	16572 21.4%	344 1.8%	146. 18.8%	440 2.5%	37 6.1%	10 29.1%	47 24.9%
LO /DENS/RES	966. 1.4%	32. .4%	998 1.3%	22 .1%	3. .4%	25. 1%	10 1.4%	1 1.5%	11 1.4%
DEVELOPING	12810. 18.4%	294 3.8%	13104. 16.9%	6793 36.4%	29. 3.7%	6822. 35.1%	7. 1.5%	2 5.4%	9 1.4%
ROW CROPS	2985. 4.3%	0 0%	2985. 3.9%	8577 46.0%	0. 0%	8577. 44.2%	157 33.3%	0 0%	157 2%
PK/REC/PASTR	18555 26.7%	100 1.3%	18655. 24.1%	2307 12.4%	10 1.3%	2317 11.9%	159 34.0%	2 6.3%	161 40.2%
FORESTS	4114 5.9%	0. 0%	4114 5.3%	351. 1.9%	0 .0%	351 1.8%	1. 13.7%	0 0%	1. 12.7%
WETLANDS	5628. 8.1%	0. 0%	5628. 7.3%	159 1.9%	0. .0%	159. 0%	26 4.6%	0 0%	26 2.4%
WATER	0 .0%	980. 12.6%	980. 1.3%	0 .0%	95 12.6%	95. .5%	0 0%	0 1.6%	0 1.6%
FREEWAYS	0. 0%	2635. 34.0%	2635 3.4%	0. 0%	264 34.0%	264. 1.4%	0 0%	14 23.7%	14 2.7%
TOTALS	69617.	7750	77367.	18650.	776	14426.	467	44.	511

Table 1'-9. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10 (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	9126. 3.7%	3674. 2.9%	12870. 3.4%	165. .1%	368. 2.9%	533. .3%	19. 1.3%	9. 6.5%	28. 1.3%
COMMERCIAL	17505. 6.9%	2673. 2.9%	20908. 5.6%	187. .1%	361. 2.9%	548. .4%	9. .5%	9. 6.5%	18. 1.1%
MEADOWS/PASTURE	4874. 1.4%	6654. 4.8%	54758. 14.6%	2292. 2.3%	605. 4.8%	3298. 2.6%	112. 10.2%	41. 37.5%	153. 137.2%
ROADS/PAVEMENT	1114. .8%	113. .1%	2227. .6%	102. .1%	11. .1%	113. .1%	1.3%	2. 1.7%	32. 1.4%
WETLANDS	237. .1%	61. .4%	292. .1%	7. .4%	3. .3%	11. .0%	1. .3%	0. .2%	1. .1%
DEVELOPING	52225. 33.0%	17689. 55.3%	151914. 40.5%	88698. 63.3%	6081. 5.3%	95679. 62.6%	75. 5.1%	20. 15.0%	96. 5.9%
ROW CROPS	3345. 1.3%	0. 0%	3345. .9%	9194. 20.8%	0. 0%	29194. 19.1%	313. 21.2%	0. .0%	313. 19.4%
PK/REC/PASTURE	64925. 26.1%	492. .4%	65418. 17.4%	15516. 11.1%	49. .4%	15565. 10.2%	609. 41.3%	10. 7.4%	619. 38.5%
FORESTS	5362. 2.2%	0. .0%	5362. 1.5%	597. .4%	0. .0%	597. .4%	203. 13.8%	0. .0%	203. 12.6%
WETLANDS	12998. 5.6%	0. 0%	13998. 3.7%	832. .6%	0. .0%	832. .5%	72. 4.9%	0. .0%	72. 4.4%
FEEDLOTS	1594. .6%	0. 0%	1594. .4%	1603. 1.1%	0. .0%	1603. 1.0%	3. .2%	0. .0%	3. .2%
WATER	0. .0%	35385. 28.1%	35385. 9.4%	0. 0%	3545. 28.1%	3545. 2.3%	0. 0%	7. 5.3%	7. .5%
FREEWAYS	0. .0%	6920. 5.5%	6920. 1.8%	0. .0%	693. 5.5%	693. .5%	0. 0%	35. 26.1%	35. 22.2%
TOTALS	249197	125991.	375178.	140191.	12620.	152811.	1475.	136	1610.

Table 1'-10. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10E (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	442. .5%	4718. 6.6%	5160. 3.1%	33. .1%	472. 6.6%	505. .8%	0. .0%	2. 4.1%	2. .2%
MED/DENS/RES	23418. 25.4%	54309. 75.5%	77727. 47.4%	16736. 28.4%	5440. 75.5%	22176. 33.6%	68. 10.9%	28. 59.0%	116. 13.6%
LOW DENS/RES	1658. 1.8%	585. .8%	2243. 1.4%	826. 1.4%	58. .8%	884. 1.3%	9. 1.1%	1. 2.5%	10. 1.2%
DEVELOPING	20250. 22.0%	3689. 5.1%	23939. 14.6%	12386. 21.0%	370. 5.1%	12756. 19.3%	11. 1.3%	4. 8.0%	14. 1.7%
ROW CROPS	5060. 5.5%	0. .0%	5060. 3.1%	24973. 42.4%	0. .0%	24973. 37.8%	317. 39.3%	0. .0%	317. 37.1%
PK/REC/PASTURE	15328. 21.0%	2475. 3.4%	21803. 13.3%	2966. 5.0%	248. 3.4%	3214. 4.9%	218. 27.1%	5. 10.8%	224. 26.2%
FORESTS	3264. 3.5%	0. .0%	3264. 2.0%	272. .5%	0. .0%	272. .4%	73. 9.0%	0. .0%	73. 8.5%
WETLANDS	18737. 20.3%	0. .0%	18737. 11.4%	677. 1.2%	0. .0%	677. 1.0%	90. 11.2%	0. .0%	90. 10.6%
WATER	0. .0%	4582. 5.4%	4582. 2.8%	0. .0%	459. 6.4%	459. .7%	0. .0%	1. 2.0%	1. .1%
FREEWAYS	0. .0%	1562. 2.2%	1562. 1.0%	0. .0%	156. 2.2%	156. .2%	0. .0%	6. 13.6%	6. .8%
TOTALS	92157.	71920.	164077.	58869.	7203.	66072.	806	47.	853.

Table I-A-11. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10 (0.000000) - Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	3395. 6.9%	97857. 20.0%	101252. 18.8%	325. 1%	11752 20.0%	12077. 3.1%	1.3%	12.3%	13.6%
COMMERCIAL	7574. 15.5%	148520. 30.3%	156094. 29.0%	1707. 5%	17835 30.3%	19542. 5.0%	14. 1.0%	19.7%	33.7%
MED/DENS/RES	546. 1.1%	110435 22.5%	110981 20.6%	529 1%	13261. 22.5%	13790. 3.5%	135. 17.9%	42. 18.4%	177. 17.5%
LO /DENS/RES	0. 0%	523. 1%	523. 1%	0. 0%	63. 1%	63. 0%	5 7%	1 4%	6 1.5%
HI /DENS/RES	5. 0%	399. 1%	404. 1%	1 0%	48. 1%	49 0%	5. 0%	1. 1%	6. 1.2%
DEVELOPING	36366. 74.3%	16232. 3.3%	52598 9.8%	328394. 99.3%	1944. 3.5%	330343. 84.9%	39. 5.1%	11. 4.1%	50. 4.5%
ROW CROPS	0 0%	0. 0%	0. 0%	0 0%	0. 0%	0 0%	20 11.5%	0 0%	20 1.0%
PK/REC/PASTURE	861. 1.8%	9440. 1.9%	10301 1.9%	30. 0%	1134. 1.9%	1164 3%	144 57.8%	7. 3.0%	151 14.8%
FORESTS	0. 0%	0. 0%	0. 0%	0. 0%	0. 0%	0. 0%	68 2.1%	0 0%	68 7.0%
WETLANDS	197. 0.4%	0 0%	197. 0%	7. 0%	0 0%	7 0%	21 2.1%	0 0%	21 2.0%
FEEDLOTS	25. 1%	0. 0%	25. 0%	22. 0%	0. 0%	22. 0%	0. 0%	0 0%	22 0%
WATER	0 0%	72114. 14.7%	72114 13.4%	0 0%	8660 14.7%	8660. 2.2%	0. 0%	16. 7.1%	16 1.0%
FREeways	0. 0%	34546. 7.0%	34546. 6.4%	0. 0%	4148. 7.0%	4148. 1.1%	0 0%	34.9%	34.9 4.1%
TOTALS	48969	490066.	539035.	330715	58850	389565.	756	225	981

Table I-A-12. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 11 (0.000000) - Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	7325. 6.1%	2606. 6.1%	9931 6.1%	24 0%	246. 6.1%	370 1.1%	41. 0.6%	7. 5.4%	48. 5.4%
COMMERCIAL	28819 23.8%	10340. 24.2%	39159. 23.9%	255 0%	1126. 24.2%	1391. 4.1%	14 0.6%	24. 33.3%	38 9%
MED/DENS/RES	12150. 10.0%	1658. 3.9%	13808 8.4%	286 0%	181. 3.9%	467 1.4%	44 0.0%	13. 14.2%	58 5.5%
LO /DENS/RES	1433 1.2%	36. 1%	1469. 1%	42 1%	4. 1%	46 1%	1. 0%	1 0%	2 1.1%
HI /DENS/RES	905. 7%	190. 4%	1095 7%	0 0%	21. 4%	27 1%	2 3%	1 1%	3 4%
DEVELOPING	12722. 19.5%	440. 1.0%	13162. 8.0%	5737. 19.6%	49 1.0%	5786 17.1%	9 1.3%	4 3.0%	13 7.5%
ROW CROPS	4860. 4.0%	0. 0%	4860 3.0%	14809. 50.6%	0 0%	14809. 43.6%	144 12.4%	0 0%	144. 17.5%
PK/REC/PASTURE	45794. 37.8%	291. 0.7%	46085. 28.1%	7440 21.2%	22. 0.7%	7472. 22.0%	412 36.0%	7 0.0%	419. 5.1%
FORESTS	0 0%	0 0%	0. 0%	0 0%	0 0%	0. 0%	0 0%	0 0%	0 0%
WETLANDS	958 8%	0. 0%	958. 6%	19 1%	0 0%	19 1%	6. 1.0%	0 0%	6 0%
LANDFILL	6062. 5.0%	0 0%	6062. 3.7%	63. 2%	0 0%	63 2%	26 1.9%	0 0%	26 2.0%
WATER	0. 0%	23219. 54.4%	23219 14.2%	0 0%	2552. 54.4%	2552 7.5%	0 0%	5. 6.1%	5 7%
FREeways	0. 0%	3904. 9.1%	3904. 2.4%	0 0%	429. 9.1%	429 1.3%	0 0%	26.1%	26.1 2.7%
TOTALS	121033.	42684.	163717.	29240	4691.	33931.	723.	86	809

Table 1-4-14 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDPUN for each land use in Subwatershed 7C (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	3701. .4%	8654. 26.0%	12355 6.7%	273. .3%	951. 26.0%	1224. 1.4%	2. .4%	20. 16.3%	22. 3.1%
MED/DENS/RES	12220 46.2%	20338 60.7%	90464. 48.8%	20207. 24.2%	2225. 60.7%	22432. 25.8%	272. 45.5%	76. 63.4%	348. 48.5%
LO /DENS/RES	713 .5%	40 .1%	753 .4%	108. 1%	4. .1%	112 .1%	4. .7%	0. .4%	5. .7%
HI /DENS/RES	504. .3%	135. 1.0%	839. .5%	18. .0%	37. 1.0%	55 .1%	0. .1%	1. .8%	1. .2%
DEVELOPING	47753. 31.4%	2022 6.1%	49775. 26.9%	51264. 61.5%	222. 6.1%	51486 59.1%	37. 6.2%	11. 9.5%	48. 6.7%
ROW CROPS	2292. 1.5%	0. .0%	2292 1.2%	6554 7.9%	0. .0%	6554 7.5%	65. 10.8%	0. .0%	65. 9.0%
PK/RFC/PASTR	25890. 17.0%	1049. 6.1%	27931 15.1%	4912. 5.9%	225. 6.1%	5137. 5.9%	193 32.2%	12. 9.6%	204. 28.5%
FORESTS	11 0%	0. .0%	11. .0%	31. 0%	0 0%	31. .0%	19. 3.1%	0. .0%	19 2.6%
WETLANDS	794. .5%	0. .0%	794. .4%	20 .0%	0. .0%	20. .0%	5. .9%	0. .0%	5. .7%
TOTALS	151876.	33338.	185214.	83387.	3664.	87051.	598.	120.	718.

Table 1-4-14 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDPUN for each land use in Subwatershed 7D (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	7258. 5.6%	3098. 5.4%	10356. 5.5%	24 .0%	373. 5.4%	397. .4%	6. .5%	9. 3.5%	15. 1.1%
COMMERCIAL	6574. 5.0%	14169. 24.6%	20743. 11.0%	79. .1%	1701. 24.6%	1779. 1.9%	5. .4%	40. 15.9%	45. 3.2%
MED/DENS/RES	27006. 20.7%	20569. 35.7%	47575. 25.3%	1677. 1.9%	2470. 35.7%	4147. 4.4%	626. 54.3%	156. 61.7%	782. 55.6%
LO /DENS/RES	0 .0%	16. .0%	16. .0%	0. .0%	2. .0%	2. .0%	5. .4%	0. .1%	5. .4%
HI /DENS/RES	344. .3%	109 .2%	453 .2%	2 .0%	13. 2%	15. .0%	1. .0%	0. .2%	1. .1%
DEVELOPING	88197. 67.5%	2595. 4.5%	90792. 48.2%	86153 97.9%	312 4.5%	86465. 91.1%	71. 6.2%	20. 7.8%	91. 6.5%
ROW CROPS	0 .0%	0. .0%	0. 0%	0 .0%	0. 0%	0. .0%	71. 6.2%	0. .0%	71. 5.1%
PK/RFC/PASTR	0 .0%	1034. 1.8%	1034. .5%	0. .0%	124. 1.8%	124. .1%	247. 21.4%	23. 9.3%	271. 19.3%
FORESTS	0. 0%	0. .0%	0. 0%	0. .0%	0. .0%	0. .0%	50. 4.4%	0. .0%	50. 3.6%
WETLANDS	1257 1.0%	0. .0%	1257. .7%	38. .0%	0 0%	38. .0%	70. 6.1%	0. .0%	70. 5.0%
LANDFILL	21. .0%	0. .0%	21. .0%	0 0%	0. 0%	0. .0%	0. .0%	0. .0%	0. .0%
WATER	0. .0%	16086. 27.9%	16086. 8.5%	0. .0%	1932. 27.9%	1932. 2.0%	0 .0%	4. 1.4%	4. .3%
TOTALS	130657.	57676.	188333.	87972.	6927.	94899.	1154.	253.	1406.

Table I-A-15. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Flowweighted 5 (km<sup>2</sup> x 5) -- Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	562 1.0%	13748. 14.8%	14310. 9.8%	64 1%	1511. 14.8%	1554. 1.8%	0. 2%	8 10.4%	8 2.7%
COMMERCIAL	10031. 18.7%	25003. 27.0%	35034. 23.9%	2011. 2.6%	2749. 27.0%	4760. 5.4%	11 4.4%	14. 19.3%	25. 8.2%
MED/DENS/RES	16385. 30.6%	36544. 39.4%	52929. 36.2%	8711. 11.7%	4017. 39.4%	12728. 14.5%	32. 26.2%	28. 38.7%	85. 28.4%
LO /DENS/RES	445. 8%	66 .1%	511 .3%	145 2%	7. 1%	153. .2%	2 1.7%	0. .4%	3 1.0%
DEVELOPING	11452. 21.4%	1426. 1.5%	12878. 8.8%	6377. 82.6%	157. 1.5%	63885. 72.6%	6 2.5%	3. 4.5%	9. 3.7%
ROW CROPS	446. .9%	0. .0%	446 .3%	936 1.2%	0 .0%	936. 1.1%	16 7.2%	0. 0%	16. 5.5%
PK/REC/PASTR	14778. 26.6%	1189. 1.3%	15467. 10.6%	1714. 2.5%	130 1.3%	2073. 2.4%	118 51.1%	5 7.6%	123. 40.4%
FORESTS	0. .0%	0. .0%	0 .0%	0 0%	0 0%	0 .0%	12. 7.7%	0. 0%	12. 5.9%
WATER	0. 0%	11040 11.4%	11040 7.5%	0 0%	1214. 11.9%	1214 1.4%	0 1.1%	3. 3.7%	3. 1.2%
FREEWAYS	0 0%	3682 4.0%	3682. 2.5%	0 0%	405. 4.0%	405. .5%	0 0%	10. 14.6%	10. 3.5%
TOTALS	53599	92698	146297.	77518	10170	87708	229.	73	31.

Table I-A-16. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Flowweighted 5 (km<sup>2</sup> x 5) -- Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1028 1.3%	2827. 9.7%	3855. 3.5%	2. 3%	340. 2.7%	342. 1.6%	1 1%	8. 8.1%	9. 1.1%
COMMERCIAL	29641. 37.0%	11915. 40.8%	41556. 38.0%	130. 1.1%	1430 40.7%	1620 7.6%	21 2.5%	34 34.1%	55 6.6%
MED/DENS/RES	9619 12.0%	5561. 19.0%	15180 13.9%	233 1.3%	668. 19.0%	901 4.2%	157. 21.4%	42 42.5%	199. 24.7%
LO /DENS/RES	3 0%	34 .1%	37. 0%	0. 0%	4. 1%	4 0%	7. 1.0%	1. 2%	4 9%
DEVELOPING	39379. 49.1%	972 2.3%	40351. 36.9%	16675 92.8%	117 3.3%	16792 72.9%	34 4.6%	7. 7.4%	41 4.9%
ROW CROPS	0 0%	0 0%	0 .0%	0 0%	0. 0%	0 .0%	0 0%	0 0%	0 0%
PK/REC/PASTR	0 0%	233. .8%	233 2%	0 0%	22 2%	22. .1%	204 41.4%	5. 5.0%	379. 37.1%
FORESTS	0. 0%	0. .0%	0. 0%	0. 0%	0 0%	0 0%	42 4.9%	0. 0%	33. 3.9%
WETLANDS	15. .0%	0 .0%	15 .0%	0 0%	0. 0%	0 0%	2 1%	0 0%	2 4%
FREELOTS	463. .6%	0 0%	468 .4%	675. 3.8%	0 .0%	675 3.2%	1 0%	0. 0%	1 3%
WATER	0 0%	7692 26.3%	7692 7.0%	0 0%	924. 26.3%	924 4.2%	0 0%	2 1.4%	2 1.2%
TOTALS	80153	29234.	109387.	17776.	3511.	21287.	733	99.	832.

Table 1-A-17. Water (m<sup>3</sup>) and Sediment (kg) Loadings Estimated by LULU for 1990 and 1991  
 Summary 1990

LAND USE	WATER PERFECT	WATER IMPERFECT	WATER TOTAL	SEDIMENT PERFECT	SEDIMENT IMPERFECT	SEDIMENT TOTAL	PERFECT LOADING	IMPERFECT LOADING	PERFECT LOADING
INDUSTRIAL	5, 1.1%	11938, 11.1%	10716, 6.9%	21, 0%	1312, 31.3%	1333, 1.2%	5	1338	1343
COMMERCIAL	21,000, 14.0%	4709, 4.3%	41017, 11.4%	73, 0%	1,672, 46.4%	1745, 1.1%	2	1747	1749
RESIDENTIAL/RECREATION	3603, 12.0%	7820, 8.9%	2703, 11.5%	1,531, 3%	472, 3.9%	1009, 1.7%	1	1010	1011
EDUCATION/RESEARCH	5074, 1.5%	0, 0%	3101, 1.3%	130, 1%	3, 0%	133, 0%	1	134	135
HEALTHCARE/RESEARCH	1475, 1.0%	422, 1.1%	2295, 1.7%	5, 0%	17, 1.1%	22, 0%	1	23	24
DEVELOPING	6305, 26.3%	1552, 4.0%	64357, 24.7%	4,462, 19.3%	171, 4.0%	66144, 46.7%	7	66151	66158
ROW CROPS	12778, 6.5%	0, 0%	12778, 5.4%	64748, 4.9%	0, 0%	64748, 34.3%	11.8%	0	11.8%
PAVED/PAVING	4,000, 24.4%	0, 0%	45215, 20.0%	1,110, 0.4%	32, 0%	16127, 7.1%	4.1%	4.1%	4.1%
WATERWAYS	0, 0%	0, 0%	0, 0%	0, 0%	0, 0%	0, 0%	0	0	0
WETLANDS	170, 1.0%	0, 0%	707, 2.1%	27, 0%	0, 0%	297, 0%	0	297	297
FORESTED	507, 0.1%	0, 0%	707, 0.2%	774, 0%	0, 0%	774, 0%	0	774	774
WATER	0, 0%	5345, 3.9%	5345, 2.3%	0, 0%	588, 13.9%	588, 0.4%	0	588	588
FREEWAYS	0, 0%	5654, 14.7%	5654, 2.4%	0, 0%	621, 14.7%	621, 0.4%	0	621	621
TOTALS	70800, 1.1%	33431, 3.3%	235275, 13.5%	13522, 0.9%	4020, 13.2%	137195, 13.2%	1.1%	137195	137195

Table 1-A-18. Water (m<sup>3</sup>) and Sediment (kg) Loadings Estimated by LULU for 1990 and 1991  
 Summary 1991

LAND USE	WATER PERFECT	WATER IMPERFECT	WATER TOTAL	SEDIMENT PERFECT	SEDIMENT IMPERFECT	SEDIMENT TOTAL	PERFECT LOADING	IMPERFECT LOADING	PERFECT LOADING
INDUSTRIAL	27, 1.1%	1097, 5.5%	1124, 5%	5, 0%	121, 6%	126, 1%	5	126	131
COMMERCIAL	5715, 11.2%	48920, 20.7%	54635, 20.7%	1440, 1.2%	5372, 15.7%	6812, 4.4%	1	6813	6814
RESIDENTIAL/RECREATION	25676, 50.3%	11543, 21.2%	142119, 55.4%	1,111, 2.4%	12011, 11.2%	13122, 9.8%	1	13123	13124
HEALTHCARE/RESEARCH	2358, 6.7%	16176, 8.4%	13474, 8.1%	20, 0%	47, 0.4%	67, 0%	1	68	69
DEVELOPING	16610, 20.8%	4760, 2.0%	14370, 6.0%	64748, 72.2%	813, 2.0%	65561, 62.7%	4.3%	65565	65569
ROW CROPS	0, 0%	0, 0%	0, 0%	0, 0%	0, 0%	0, 0%	0	0	0
PAVED/PAVING	5119, 10.1%	3913, 2.1%	9031, 3.7%	577, 0%	430, 1.1%	1007, 0%	1	1007	1007
WATERWAYS	0, 0%	0, 0%	0, 0%	0, 0%	0, 0%	0, 0%	0	0	0
WETLANDS	390, 0%	0, 0%	390, 0%	0, 0%	0, 0%	0, 0%	0	0	0
TOTALS	50902, 1.1%	143309, 14.3%	241217, 13.8%	7085, 0.5%	27905, 27.9%	141710, 14.1%	1.1%	141710	141710

Table I-A-19. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUM for each land use in the watershed for the summer of 1977.

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	1113. 2.5%	249. 4.0%	1362. 2.7%	22. .1%	24 3.9%	46 .1%	6 1.1%	1 2.7%	7. 1.2%
MED/DENS/RES	6985. 15.5%	627. 10.2%	7612. 14.9%	104 .3%	63. 10.2%	157 .5%	8. 1.7%	4. 18.0%	13 2.4%
LO/DENS/RES	4194. 9.3%	115. 1.9%	4309. 8.4%	79. .3%	12. 1.9%	91. .3%	11. 2.1%	2. 10.0%	13 2.5%
DEVELOPING	1595. 3.5%	45. .7%	1640. 3.2%	978 3.2%	5. .8%	983. 3.2%	1. .1%	5. 1.3%	6. 1.3%
ROW CROPS	6122. 13.6%	0. .0%	6122. 12.0%	27093. 89.9%	0. .0%	27093. 88.1%	358. 71.3%	0. .0%	358. 66.1%
PK/REC/PASTURE	22187 49.3%	744 12.1%	22931. 44.8%	1745 5.8%	75 12.0%	1720. 5.9%	79. 15.7%	15. 64.2%	94. 17.3%
FORESTS	1092 2.4%	0 .0%	1092 2.1%	67. .2%	0 .0%	67 .2%	32. 6.4%	0. .0%	32 6.2%
WETLANDS	1761 3.9%	0 .0%	1761. 3.4%	36. .1%	0 .0%	36. .1%	8. 1.5%	0. .0%	8 1.5%
WATER	0. .0%	4370. 71.1%	4370 8.5%	0. .0%	478. 71.0%	438. 1.4%	0. 0%	1. 3.8%	1 1.2%
TOTALS	45049.	6150.	51199	30124.	617.	30741.	579	24	527.

Table I-A-20. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUM for each land use in the watershed for the summer of 1977.

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	378. 4%	698. 1.1%	1076. 6%	2 .0%	70 1.1%	72. .1%	0 0%	2. 4.4%	2 2%
MED/DENS/RES	20420. 19.5%	1907. 2.9%	22327 13.1%	953. 1.3%	191 2.9%	1144 1.4%	51 1.3%	13. 32.5%	64. 7.6%
LO/DENS/RES	1759. 1.7%	64. .1%	1853 1.1%	35 .0%	7 .1%	42. .1%	11 1.3%	1. 3.3%	12 1.4%
HI/DENS/RES	803 8%	176. .3%	979. .6%	3 .0%	18 3%	21. .0%	1 1%	1 1.5%	1. 1.2%
DEVELOPING	33164. 31.6%	725. 1.1%	33889. 19.9%	43988 58.3%	72. 1.1%	44061. 53.7%	18. 2.2%	6. 12.2%	23 2.7%
ROW CROPS	4925 4.7%	0. .0%	4925 2.9%	21743. 28.9%	0 .0%	21743. 25.6%	281 44.6%	0. 0%	281 33.7%
PK/REC/PASTURE	33414. 31.7%	296 4%	33710 19.8%	6028. 8.0%	30. 5%	6058. 7.4%	321 39.5%	6 15.1%	327. 39.4%
FORESTS	1298 1.2%	0. .0%	1298. .8%	83. .1%	0 0%	83. .1%	58 1.1%	0. 0%	58. 1.1%
WETLANDS	5391 5.1%	0. 0%	5391 3.2%	184. .2%	0 .0%	184 .2%	34 4.0%	0 0%	34. 4.0%
FFFLOTS	3204. 3.1%	0 .0%	3204. 1.9%	2347 3.1%	0 .0%	2347 2.9%	7 .9%	0 0%	7. .9%
WATER	0. .0%	61998. 94.1%	61998. 36.3%	0. .0%	6210 94.1%	6210 7.6%	0. 0%	13 31.4%	13 1.5%
TOTALS	104786.	65864.	170650.	75416.	6599	82015.	812	47.	859.

Table 1-10: Water (kg) and Sediment (kg) loading from all sources by FAIRWAY for all years

FAIRWAY USE	WATER CORV	WATER IMPER	WATER TOTAL	SEDIMENT CORV	FUST/PLANT IMPER	SEDIMENT TOTAL	WATER IMPER	SEDIMENT IMPER	WATER TOTAL
COMMERCIAL	2411 2.7%	2671 1.0%	3498.1 2.7%	5 0.0%	1394 0.5%	1399 0.5%	12	10	22
MED. DENS. RES.	20714 29.1%	24181 43.4%	32163 29.5%	100 0.1%	242 0.0%	342 0.1%	100	242	342
LC / DENS. RES.	1814 0.0%	0 0%	1567 1.4%	0 0%	0 0%	57 0.0%	10	0	10
DEVELOPMENT	2494 4.0%	456 1.2%	25303 22.3%	1031 0.1%	10 0.0%	1031 0.1%	10	10	20
LOW DENS. RES.	6501 6.4%	0 0%	6501 5.7%	0 0.0%	0 0%	0 0%	0	0	0
IR/RUC/FAIR	2851 2.1%	115 0.1%	23666 20.6%	0 0.0%	10 0.0%	10 0.0%	0	10	10
RESIDENTS	51 0.0%	0 0%	113 0.0%	0 0.0%	0 0%	0 0%	0	0	0
WETLANDS	17 0.0%	0 0%	145 1.2%	0 0%	0 0%	0 0%	0	0	0
FAIRWAY	28 0.0%	0 0%	28 0.0%	0 0.0%	0 0%	0 0%	0	0	0
TOTAL	1031 1.3%	574 0.2%	17954 15.9%	0 0.0%	10 0.0%	10 0.0%	0	10	10

Table 1-11: Water (kg) and Sediment (kg) loading from all sources by FAIRWAY for all years

FAIRWAY USE	WATER CORV	WATER IMPER	WATER TOTAL	SEDIMENT CORV	FUST/PLANT IMPER	SEDIMENT TOTAL	WATER IMPER	SEDIMENT IMPER	WATER TOTAL
COMMERCIAL	51 0.0%	204 0.5%	204 0.2%	0 0.0%	0 0%	0 0%	0	0	0
COMMERCIAL	10 0.1%	14916 6.7%	14926 12.9%	0 0.0%	0 0%	0 0%	0	0	0
MED. DENS. RES.	14111 25.1%	18217 13.6%	19724 17.7%	100 0.1%	242 0.0%	342 0.1%	100	242	342
LC / DENS. RES.	116 0.0%	121 0.1%	477 0.4%	0 0%	0 0%	0 0%	0	0	0
DEVELOPMENT	18 0.0%	31127 10.5%	3114 9.4%	0 0%	10 0.0%	10 0.0%	0	10	10
LOW DENS. RES.	14024 42.7%	12962 8.5%	3707 10.6%	1031 0.1%	10 0.0%	1031 0.1%	10	10	20
FAIRWAY	10 0.0%	0 0%	0 0%	0 0.0%	0 0%	0 0%	0	0	0
WETLANDS	85 0.2%	0 0%	85 0.0%	0 0%	0 0%	0 0%	0	0	0
WATER	0 0%	12644 4.0%	12644 10.9%	0 0%	10 0.0%	10 0.0%	0	10	10
FAIRWAY	0 0%	11525 7.5%	11525 10.2%	0 0%	2374 0.0%	2374 0.0%	0	2374	2374
TOTAL	6294 6.2%	28799 2.8%	344194 34.4%	24864 2.4%	31751 3.1%	27970 2.7%	24864	31751	344194

Table 1-A-23 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDSLN for each land use in the watershed for the year 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1878 2.6%	31352 9.6%	33230. 8.3%	342. .2%	3457 9.6%	3799. 1.7%	2. .3%	5. 7.4%	7.4%
COMMERCIAL	4152. 5.7%	147919. 45.1%	152071. 37.9%	1793 1.0%	16312. 45.1%	18106. 8.1%	27. 3.6%	35.7%	62.7%
MED/DENS/RES	7522. 10.3%	86638. 26.4%	94160. 23.5%	4303. 6.3%	9555 26.4%	13858 6.2%	81. 10.9%	31. 27.4%	112. 13.1%
LO /DENS/RES	362. .5%	753. .2%	1115. .3%	430. .2%	83. .2%	413. .2%	7. .9%	1. .7%	8. 9%
HI /DENS/RES	1867. 2.6%	40752. 12.4%	42619. 10.6%	797. .4%	4494. 12.4%	5291 2.4%	12 1.6%	13. 11.7%	25 2.3%
DEVELOPING	40988. 56.2%	18633. 5.7%	59621. 14.9%	177748. 95.4%	2055. 5.7%	179803 80.8%	38. 6.1%	11. 9.3%	50. 5.8%
ROW CROPS	0. .0%	0. .0%	0 0%	0 .0%	0 0%	0. 0%	116 15.6%	0 0%	116. 13.6%
PK/REL/PASTR	13634. 18.7%	1713. .5%	15347. 3.8%	839. .5%	189. .5%	1028. .5%	373 50.3%	7. 6.6%	381. 44.6%
FORESTS	0. .0%	0. 0%	0. .0%	0. 0%	0. .0%	0. .0%	47 6.3%	0 0%	47 5.5%
WETLANDS	655. .9%	0. .0%	655. .2%	34. .0%	0. .0%	34. .0%	25 3.3%	0 0%	25 2.9%
LANDFILL	1905. 2.6%	0. .0%	1905 .5%	39. .0%	0 0%	39. .0%	13 1.8%	0 0%	13 1.6%
WATER	0. .0%	396. .1%	396 .1%	0. 0%	44 1%	44. .0%	0. 0%	0 1%	0. .0%
TOTALS	72963.	328156.	401119	186225	36190.	222415.	741	112.	853

Table 1-A-24 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDSLN for each land use in the watershed for the year 1978

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	8425. 4.4%	3214. 6.5%	11639. 4.8%	40. .1%	354. 6.5%	414. .4%	13. 1.4%	9 7.4%	22. 2.2%
COMMERCIAL	53642. 27.9%	22036. 44.4%	75678. 31.3%	698 .7%	2422. 44.4%	3120. 3.1%	37. 4.1%	62. 54.0%	99. 9.8%
MED/DENS/RES	8329. 4.3%	1205 2.4%	9534. 3.9%	349. .4%	132. 2.4%	481 .5%	34 3.8%	9. 7.9%	43. 4.3%
LO /DENS/RES	1388. .7%	40 1%	1428. .6%	30 0%	4. .1%	34. .1%	9. 1.0%	1. .9%	10. 1.0%
HI /DENS/RES	12913 6.7%	2540. 5.1%	15453. 6.4%	111. .1%	279. 5.1%	390. .4%	17. 1.1%	10 8.5%	19 1.9%
DEVELOPING	62075. 32.3%	2096 4.2%	64171 26.5%	68941 72.1%	230 4.2%	69171 63.4%	47 5.2%	16. 13.7%	63 6.2%
ROW CROPS	6084. 3.2%	0 0%	6084. 2.5%	21010. 21.0%	0. .0%	21010 20.8%	258 24.8%	0 0%	258. 25.5%
PK/REC/PASTR	29966 15.6%	202. .4%	30168. 12.5%	4237. 4.4%	23 .4%	4260 4.2%	284 31.7%	5. 3.9%	289 29.5%
FORESTS	0. .0%	0. .0%	0. 0%	0. 0%	0 0%	0. .0%	135. 15.0%	0 0%	135 13.5%
WETLANDS	9294. 4.8%	0. .0%	9294. 3.8%	199. .2%	0. .0%	199 .2%	70. 7.8%	0 0%	70 6.4%
FEEDLOTS	71. .0%	0 .0%	71 .0%	24. .0%	0. .0%	24 .0%	0. .0%	0 0%	24 0%
WATER	0. .0%	18335. 36.9%	18335 7.6%	0. .0%	2015. 26.9%	2015 2.0%	0 0%	4 3.6%	4. 4%
TOTALS	192187.	49668.	241855	95659.	5459.	101118.	896	110.	1011

Table 1-A-26 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LINDBURN for each land use category in the watershed for the summer of 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1811 5.7%	662261 9.6%	664072 8.8%	2411 1.1%	1313 9.6%	7524 2.1%	1000	1000	2000
COMMERCIAL	48921 5.9%	151926 20.0%	156818 20.2%	1111 7%	16754 22.0%	17865 5.9%	1000	1000	2000
REF/DENS/RES	26697 32.1%	297535 43.0%	324232 41.9%	11117 9.2%	22511 43.0%	47718 13.1%	1000	1000	2000
IND/DENS/RES	111 .1%	202 0%	203 .0%	10 0%	10 .0%	20 0%	1000	1000	2000
HI/DENS/RES	4736 5.7%	76361 11.0%	81097 10.5%	1261 4%	5415 11.0%	6676 2.1%	1000	1000	2000
DEVELOPING	30852 37.1%	19112 2.0%	50264 6.4%	6917 9.2%	21401 7.1%	27318 7.4%	1000	1000	2000
ROW/CRIP	0 0%	0 0%	0 0%	0 0%	0 0%	0 0%	1000	1000	2000
PK/REC/PASTR	11220 1.4%	28837 4.2%	40057 5.2%	1113 1%	5121 4.2%	6234 1.8%	1000	1000	2000
FORESTS	11 0%	0 0%	11 0%	1 0%	1 0%	2 0%	1000	1000	2000
WETLANDS	11 0%	0 0%	11 0%	1 0%	1 0%	2 0%	1000	1000	2000
LANDFILL	112 .1%	0 0%	112 .1%	11 .1%	0 0%	11 .1%	1000	1000	2000
WATER	0 0%	9531 1.4%	9531 1.2%	0 0%	1351 1.4%	1351 .3%	1000	1000	2000
FREEWAYS	11 .0%	41469 6.7%	41480 5.4%	1 0%	4142 6.7%	4143 1.4%	1000	1000	2000
TOTALS	83211	671441	754652	159101	76243	185577	1000	1000	2000

Table 1-A-26 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LINDBURN for each land use category in the watershed for the summer of 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1705 .9%	512651 6.9%	529706 5.6%	111 .1%	1442 0.8%	6053 3.1%	1000	1000	2000
COMMERCIAL	23099 11.9%	117243 25.5%	215342 22.7%	4773 4.5%	22246 25.5%	26019 13.4%	1000	1000	2000
REF/DENS/RES	64027 33.0%	380539 50.6%	444566 47.0%	67905 6.2%	44034 50.4%	111939 57.0%	1000	1000	2000
IND/DENS/RES	34 0%	19 0%	53 0%	1 0%	1 0%	2 0%	1000	1000	2000
HI/DENS/RES	6022 3.1%	39414 5.2%	45436 4.8%	1111 1.1%	4511 5.2%	5722 2.1%	1000	1000	2000
DEVELOPING	10873 5.6%	4160 .6%	15033 1.6%	24114 22.1%	482 .6%	24646 12.4%	1000	1000	2000
PK/REC/PASTR	75983 39.7%	10642 8.1%	127625 14.5%	11102 10.4%	7017 8.1%	18619 9.4%	1000	1000	2000
FORESTS	0 0%	0 0%	0 0%	0 0%	0 0%	0 0%	1000	1000	2000
LANDFILL	11313 .8%	0 0%	11313 1.2%	502 .5%	0 0%	502 .2%	1000	1000	2000
WATER	0 0%	5867 .6%	5867 .6%	0 0%	579 .6%	679 .3%	1000	1000	2000
FREEWAYS	0 0%	18458 2.5%	18458 1.9%	0 0%	2136 2.5%	2136 1.1%	1000	1000	2000
TOTALS	194036	752607	946643	109246	87089	196335	1000	1000	2000

Table I-A-27. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in the watershed for Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	13839 4.5%	100737. 13.3%	114576. 10.7%	575. .5%	11657. 13.3%	12232. 6.5%	11 1.1%	43 4.3%	54 4.5%
COMMERCIAL	74212 23.9%	247597 32.7%	321809 30.2%	7268 7.3%	28651. 31.7%	35919. 19.2%	21. 1.0%	118. 23.0%	139. 16.1%
MED/DENS/RES	110468. 35.6%	276116. 36.5%	386584. 36.2%	43486. 43.7%	31950 36.5%	75436. 40.3%	141. 4.0%	198. 39.4%	339. 40.7%
HI /DENS/RES	17422. 5.6%	33409. 4.4%	50831. 4.8%	1416. 1.4%	3865. 4.4%	5281. 2.8%	14 1.7%	21 4.0%	35 3.6%
DEVELOPING	39526 12.7%	10506 1.4%	50032 4.7%	43354. 43.5%	1216. 1.4%	44570 23.8%	25 2.1%	11. 2.2%	36 2.8%
PK/REC/PASTR	51656. 16.6%	25094. 3.3%	76750. 7.2%	3400. 3.4%	2904. 3.3%	6304 3.4%	308 3.0%	36 7.0%	744 26.0%
FORESTS	0. 0%	0. 0%	0. 0%	0. 0%	0 0%	0 0%	11 1.4%	0. 0%	11. 0.8%
WETLANDS	2569. .8%	0. 0%	2569. .2%	95. 1%	0. 0%	95. 1%	13. 1.6%	0 0%	13. 1.0%
LANDFILL	950. .3%	0. 0%	950. .1%	11 0%	0. 0%	11. 0%	3. 4%	0. 0%	3. 0%
WATER	0. 0%	35077. 4.6%	35077 3.3%	0. 0%	4059. 4.6%	4059. 2.2%	0. 0%	8. 1.5%	8. 0%
FREWAYS	0. 0%	28110 3.7%	28110 2.6%	0 0%	3253. 3.7%	3253. 1.7%	0. 0%	14.7 14.7%	76. 5.7%
TOTALS	310642.	756646.	1067288.	99605	87555.	187160.	208.	516	1323.

Table I-A-28. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by ANDRIN for each land use in the watershed for Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	281. .2%	1246. 3.6%	1527. .7%	1. 0%	144. 3.6%	145 3%	0. 0%	3 2.0%	4 5%
COMMERCIAL	26751. 15.1%	11903. 34.4%	38654. 18.2%	397. 1.0%	1378. 34.4%	1775. 4.2%	20. 3.4%	32. 18.7%	52. 6.9%
MED/DENS/RES	75625. 42.5%	13347. 38.5%	88972. 41.9%	7149. 19.8%	1545. 38.5%	8694. 20.7%	339. 59.3%	96 56.0%	435 55.5%
LO /DENS/RES	103. .1%	5. 0%	108. 1%	3. 0%	1. 0%	4 0%	1. 1%	1. 1%	2. 0%
HI /DENS/RES	8697 4.9%	1968. 5.7%	10665. 5.0%	91 2%	227. 5.7%	318 1.9%	6 1.1%	7. 4.1%	13 1.0%
DEVELOPING	37125 20.9%	1179. 3.4%	38304 18.0%	27353. 77.2%	137. 3.4%	29490. 70.1%	27 4.7%	4. 4.9%	31. 4.1%
PK/REC/PASTR	27721. 15.6%	2176. 6.3%	29897 14.1%	1016. 2.7%	251 6.3%	1267 3.0%	125 21.7%	23 14.7%	149. 10.7%
FORESTS	0. 0%	0. 0%	0. 0%	0. 0%	0. 0%	0. 0%	47. 2.2%	0 0%	47. 0.4%
WETLANDS	1382 8%	0 0%	1382 7%	21. 1%	0 0%	21. 0%	7 1.3%	0 0%	7 1.0%
WATER	0. 0%	2766. 8.0%	2766 1.1%	0. 0%	320 8.0%	320 8%	0 0%	0 0%	0 0%
FREWAYS	0. 0%	55. 2%	55. 0%	0 0%	6. 1%	6. 0%	0 0%	0 0%	0 0%
TOTALS	177685.	34645.	212330.	38031.	4009.	42040.	572	171	743

TABLE 1-10. Water quality and sediment (kg) loadings estimated for the upper portion of the river, 1977

LAND USE	WATER LOAD	WATER IMPER	WATER TOTAL	SEDIMENT TOTAL	DUST/DIRT IMPER	SEDIMENT TOTAL	WATER LOAD	WATER TOTAL	APR TOTAL
INDUSTRIAL	6,417 1.4%	3214. 17.0%	9231 6.1%	52. %	370 17.0%	422 1.6%	1.4%	1.4%	1.4%
COMMERCIAL	3,450 0.8%	136 0.7%	4594. 3.1%	42. %	131. 6.0%	173 0.7%	0.8%	0.8%	0.8%
MEADOWS/PASTURE	7,843. 4.1%	8563. 45.0%	63402 4.1%	4554 16.0%	931. 15.2%	5540 2.1%	4.1%	4.1%	4.1%
FORESTS/RES.	3,112 0.7%	16 0.0%	333 0.2%	1. %	0. %	16 0.0%	0.7%	0.7%	0.7%
ROADS/RES.	10,000 0.0%	241 0.0%	2569 0.1%	45 0.0%	0. %	10 0.0%	0.0%	0.0%	0.0%
DEVELOPING	3,113 0.7%	16 0.0%	333 0.2%	1. %	0. %	16 0.0%	0.7%	0.7%	0.7%
FORESTS/RES.	3,450 0.8%	136 0.7%	4594. 3.1%	42. %	131. 6.0%	173 0.7%	0.8%	0.8%	0.8%
WATER	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0.0%	0.0%	0.0%
WATER	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0.0%	0.0%	0.0%
WATER	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0.0%	0.0%	0.0%
TOTAL	11,111 1.1%	4,960 4.9%	15,111 1.1%	10 0.0%	1,444 1.4%	1,111 0.1%	1.1%	1.1%	1.1%

TABLE 1-11. Water quality and sediment (kg) loadings estimated for the lower portion of the river, 1977

LAND USE	WATER LOAD	WATER IMPER	WATER TOTAL	SEDIMENT TOTAL	DUST/DIRT IMPER	SEDIMENT TOTAL	WATER LOAD	WATER TOTAL	APR TOTAL
COMMERCIAL	1,450 0.4%	24818 17.6%	13741 10.4%	10. %	2574 47.4%	3100 1.4%	0.4%	0.4%	0.4%
MEADOWS/PASTURE	7,843. 4.1%	13700 26.3%	91310 34.1%	4554 16.0%	1510 26.4%	6800 2.1%	4.1%	4.1%	4.1%
FORESTS/RES.	3,112 0.7%	16 0.0%	333 0.2%	1. %	0. %	16 0.0%	0.7%	0.7%	0.7%
DEVELOPING	3,113 0.7%	16 0.0%	333 0.2%	1. %	0. %	16 0.0%	0.7%	0.7%	0.7%
ROADS/RES.	2,116 0.1%	0. 0.0%	2276 0.2%	1444 0.4%	0. 0.0%	1444 0.4%	0.1%	0.1%	0.1%
FORESTS/PARK	14663 20.1%	2451. 5.1%	47314 17.1%	145 0.4%	376 5.1%	1911 0.7%	20.1%	20.1%	20.1%
FORESTS	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0. 0.0%	0.0%	0.0%	0.0%
WETLANDS	3602 4.0%	0. 0.0%	8682. 3.0%	311 1.1%	0. 0.0%	311 0.4%	4.0%	4.0%	4.0%
WATER	0. 0.0%	9063. 17.4%	9063. 3.4%	0. 0.0%	1049. 1.1%	1049 0.4%	0.0%	0.0%	0.0%
TOTALS	11,111 1.1%	5,217 5.2%	26777.9 1.9%	2729 0.0%	6137 6.1%	3375.6 0.1%	1.1%	1.1%	1.1%

Table I-A-31 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Cook County, Illinois--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	65. .1%	288. 5.3%	353 7%	0. .0%	33. 5.2%	33 1.3%	0 0%	1 2.7%	1. .3%
COMMERCIAL	7721. 16.3%	2603. 47.7%	10324 19.5%	88 .6%	301. 47.7%	389. 15.3%	6. 2.1%	7. 24.3%	13. 4.3%
MED/DENS/RES	11322. 23.9%	1814. 33.2%	13136. 24.8%	641. 31.5%	210 33.3%	851 32.4%	29. 22.4%	13. 45.1%	72. 21.7%
LO /DENS/RES	140 .3%	3. .1%	143 .3%	2 .1%	0 .0%	2. .1%	1. 3%	0. 2%	1. 3%
DEVELOPING	346. .7%	10. .2%	356. .7%	95. 5.0%	1. .2%	96 3.8%	0. 1%	0. .2%	1. 1%
PK/REC/PASTH	22125. 46.6%	739. 13.5%	22864. 43.2%	902. 47.1%	76. 13.6%	988. 38.8%	138 52.3%	3 27.5%	146. 49.9%
FORESTS	0 .0%	0. .0%	0. .0%	0. .0%	0 0%	0. .0%	29. 11.1%	0. 0%	29. 10.0%
WETLANDS	5749. 12.1%	0. .0%	5749 10.9%	186. 9.7%	0. .0%	186. 7.4%	31 11.6%	0. 0%	31. 10.5%
TOTALS	47468.	5457.	52925.	1914.	531	2545.	265.	29.	294

Table I-A-32 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Cook County, Illinois--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1698. 2.2%	74106. 8.9%	75804. 8.4%	159 7%	8768. 8.9%	8927. 7.4%	1 .5%	20 7.3%	21. 4.7%
COMMERCIAL	5816. 7.6%	118811. 14.3%	124627 13.8%	1619. 7.0%	14637. 14.3%	15676. 13.0%	24. 10.8%	32 11.6%	61. 11.2%
MED/DENS/RES	33928 44.4%	337468. 40.8%	371396. 41.1%	14453. 62.8%	39926. 40.8%	54379. 44.9%	132. 49.3%	122 44.1%	254. 46.9%
HI /DENS/RES	4150 5.4%	57191. 6.9%	61341 6.8%	847 3.7%	5766 6.9%	7613. 6.3%	12 4.3%	14 6.1%	26 5.4%
DEVELOPING	1160 1.5%	837. .1%	1997 .2%	2116. 9.2%	99 .1%	2209. 1.8%	1 .2%	1. .2%	1. .3%
PK/REC/PASTH	29654. 38.8%	63670. 7.7%	93324. 10.3%	3821. 16.6%	7533. 7.7%	11354. 9.4%	43 34.3%	46 16.6%	109 22.5%
WATER	0. 0%	752. .1%	752. .1%	0 0%	89. 1%	89. 1%	0 .1%	0. 1%	0. .1%
FREEWAYS	0. 0%	175253. 21.2%	175253 19.4%	0 .0%	20735. 21.2%	20735. 17.1%	0 .1%	3. 11.7%	3. 7.6%
TOTALS	76406.	828088	904494.	23009.	97973	126982.	267	277	545

Table I-A-55. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 4B (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1491. 1.4%	64054. 6.1%	65545. 5.7%	134. .3%	7578. 6.1%	7712. 4.4%	1. .3%	17. 4.8%	19. 2.5%
COMMERCIAL	9433. 9.1%	221850 21.0%	231283 20.0%	1238. 2.5%	26248. 21.0%	27486. 15.7%	8. 2.0%	60. 16.6%	68. 9.1%
MED/DENS/RES	69784. 67.5%	679667. 64.4%	749451. 64.7%	37991. 75.5%	80413. 64.4%	118404. 67.6%	276 70.8%	246. 67.9%	522. 69.4%
LD /DENS/RES	21. .0%	30. .0%	51. .0%	1. .0%	4. .0%	5. 0%	0. .0%	0. .0%	0. .0%
HI /DENS/RES	2381. 2.3%	34448. 3.3%	36829. 3.2%	450. .9%	4076. 3.3%	4526. 2.6%	7. 1.8%	11. 2.9%	18. 2.3%
DEVELOPING	3300. 3.2%	2374. .2%	5674. .5%	8345 16.6%	281 .2%	8626. 4.9%	2. .5%	1. .4%	3. .4%
PK/REC/PASTR	16963. 16.4%	30326. 2.9%	47289 4.1%	2165. 4.3%	3588. 2.9%	5753. 3.3%	96. 24.6%	22. 6.1%	118. 15.6%
WATER	0. .0%	9353. .9%	9353. .8%	0. .0%	1107. 9%	1107. .6%	0. .0%	2. .6%	2. .3%
FREEWAYS	0. .0%	12617 1.2%	12617. 1.1%	0. .0%	1516. 1.2%	1516. .9%	0. .0%	3. .8%	3. .4%
TOTALS	103373	1054919.	1158292.	50324.	124811	175135.	390.	363.	752.

Table I-A-54. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 4C (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	28 .0%	1447. .1%	1475. .1%	4. .0%	154. .1%	158. .0%	0. .0%	0. .1%	0. .1%
COMMERCIAL	3310. 3.4%	101502. 10.2%	104812. 9.6%	1093. .5%	10815 10.2%	11908. 3.7%	11. 3.2%	28. 7.7%	39. 5.5%
MED/DENS/RES	54162. 55.2%	680729. 68.5%	734881. 67.3%	53313. 24.5%	72529. 68.5%	125842. 38.9%	223. 65.6%	254. 69.0%	476. 67.3%
HI /DENS/RES	9673. 9.9%	158747. 16.0%	168420 15.4%	4248. 1.9%	16914. 16.0%	21162. 6.5%	27. 8.1%	51. 13.8%	78. 11.0%
DEVELOPING	21676 22.1%	15006. 1.5%	36682. 3.4%	157641. 72.3%	1599 1.5%	159240. 49.2%	8. 2.5%	10. 2.6%	18. 2.5%
PK/REC/PASTR	9314. 9.5%	32350. 3.3%	41674. 3.8%	1657 .8%	3448. 3.3%	5105. 1.6%	70. 20.7%	24. 6.6%	95. 13.4%
WATER	0. .0%	4436. .4%	4436. .4%	0. .0%	473. .4%	473. .1%	0. .0%	1. .3%	1. .1%
TOTALS	98153.	994227.	1092380.	217956.	105932.	323883.	340.	368.	707.

Table I-A-35. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 10 (for area 10)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	2556. 2.7%	108888. 15.4%	111444. 13.9%	1088. 3%	11602. 15.4%	12690. 2.8%	31 3.8%	31 11.9%	62 6.4%
MED/DENS/RES	25229. 26.3%	361725. 51.1%	386954. 48.1%	31430. 8.1%	38541. 51.1%	69971. 15.2%	264 47.6%	135. 52.6%	399 49.2%
LO /DENS/RES	50. .1%	48. .0%	98. .0%	22. .0%	5. .0%	27. .0%	0. .1%	0. .0%	0. .1%
HI /DENS/RES	3735. 3.9%	76399. 10.8%	80134. 10.0%	1743. .5%	8140. 10.8%	9883. 2.1%	16 3.0%	24. 9.5%	41. 5.1%
DEVELOPING	37596 39.2%	23520. 3.3%	61116. 7.6%	34304. 88.9%	2506. 3.3%	34555. 74.9%	26. 4.9%	15. 5.9%	41. 5.1%
ROW CROPS	0. .0%	0. .0%	0. .0%	0. .0%	0 0%	0. .0%	15 2.8%	0 0%	15. 1.9%
PK/REC/PASTR	23121. 24.1%	40190. 5.7%	63311. 7.9%	8163. 2.1%	4282. 5.7%	12445. 2.7%	173 31.2%	27. 11.7%	200 25.4%
FORESTS	54. .1%	0 0%	54. 0%	45 .0%	0. 0%	45 0%	14. 2.9%	0 0%	14. 1.7%
WETLANDS	516. .5%	0 .0%	516. .1%	113 0%	0 .0%	113. 0%	0 1.6%	0 0%	0 1.1%
LANDFILL	2970 3.1%	0. .0%	2970. .4%	322. .1%	0 .0%	332. .1%	13 2.4%	0. 0%	13 1.6%
WATER	0. .0%	2145. .3%	2145. .3%	0 0%	229. .3%	229 .0%	0. 0%	0. 0%	0. 0%
FREEWAYS	0 0%	95117. 13.4%	95117. 11.8%	0. .0%	10134. 13.4%	10134. 2.2%	0. 0%	21 8.3%	21. 2.7%
TOTALS	95827.	708032.	803859.	385985	75430.	461424.	542.	255.	797.

Table I-A-36. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 11 (for area 11)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	95 1%	4357. 7%	4452. .6%	5 0%	515. 7%	520 .4%	1 1%	1. 4%	2 2%
COMMERCIAL	5206. 4.6%	89686. 15.4%	94892. 13.6%	1023 2.1%	10611. 15.4%	11634 9.9%	5 2.1%	24. 10.1%	29. 5.9%
MED/DENS/RES	28878 25.3%	279175. 47.9%	308053. 44.2%	12363. 25.5%	33030. 47.9%	45393 38.7%	119. 41.8%	101 40.1%	220 41.9%
HI /DENS/RES	3633 3.2%	41919 7.2%	45552 6.5%	3392 7.0%	4454. 7.2%	8351. 7.1%	9 2.4%	13 5.4%	22 4.1%
DEVELOPING	348. .3%	250. .0%	598 .1%	612 1.3%	30 .0%	642 5%	0 1%	0 1%	0 1%
ROW CROPS	444. .4%	0 .0%	444. .1%	5015. 10.3%	0. 0%	5015 4.3%	8 2.7%	0 0%	8 1.5%
PK/REC/PASTR	75725. 66.2%	126602. 21.7%	202327 29.0%	26053 53.8%	14978 21.7%	41031 34.9%	124 45.7%	52 35.1%	200 41.9%
FORESTS	0. .0%	0. .0%	0 0%	0. .0%	0 0%	0 0%	11 4.9%	0 0%	11. 2.1%
LANDFILL	14 0%	0 0%	14 0%	0. .0%	0. 0%	0 0%	0 0%	0 0%	0 0%
WATER	0. .0%	40730. 5.8%	40730. 5.8%	0. .0%	4819 7.0%	4819. 4.1%	0 5%	0. 3.7%	0 1.7%
FREEWAYS	0 0%	230. .0%	230 .0%	0. .0%	27. 0%	27. .0%	0 0%	0 0%	0 0%
TOTALS	114343	582949.	697292.	48463.	68969.	117432	226.	240.	507.

Table I-A-3/ Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3B (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1849. 1.2%	39057. 2.9%	40906. 2.7%	157. 1%	4519. 2.9%	4676. 1.7%	1. .3%	10. 2.2%	12. 1.3%
COMMERCIAL	4542 3.0%	144870. 10.8%	149412 10.1%	748 6%	16764. 10.8%	17512. 6.3%	4. .8%	39. 8.2%	43. 4.5%
MED/DENS/RFS	103569. 69.4%	959344. 71.5%	1062913. 71.3%	100494. 81.4%	111011. 71.5%	211505. 75.8%	305. 65.5%	344. 72.5%	649. 69.0%
LO /DENS/PES	11. .0%	10 .0%	21. 0%	1. .0%	1. .0%	2. .0%	0 .0%	0. .0%	0. .0%
HI /DENS/RFS	7072. 4.7%	99972. 7.4%	107044. 7.2%	1952. 1.6%	11568. 7.4%	13520. 4.8%	17. 3.6%	31. 6.5%	47. 5.0%
DEVELOPING	3940. 2.6%	2809. .2%	6749. .5%	10443. 8.5%	325. .2%	10768. 3.9%	1. 3%	2. .4%	3. .3%
PK/REC/PASIR	28171. 18.9%	55442. 4.1%	83613. 5.6%	9713. 7.9%	6415. 4.1%	16128. 5.8%	137. 29.5%	40. 8.4%	177. 18.8%
WATER	0 .0%	31053. 2.3%	31053. 2.1%	0 .0%	3593. 2.3%	3593. 1.3%	0. .0%	7. 1.4%	7. .7%
FREEWAYS	0 .0%	9972. .7%	9972. .7%	0 .0%	1154. .7%	1154. .4%	0 .0%	2. .5%	2. .2%
TOTALS	143154.	1342529.	1491683.	124508	155350.	278858.	406	475.	940.

Table I-A-4. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3C (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	5463 16.7%	149847. 44.0%	155310. 41.6%	1481. 3.6%	17340. 44.0%	18821. 23.5%	4. 3.5%	40. 38.5%	45. 19.8%
MED/DENS/RES	8632. 20.3%	58368. 17.1%	65000. 17.4%	8824. 21.6%	6754. 17.1%	15578. 19.4%	31. 26.1%	21 20.0%	52. 23.3%
HI /DENS/RFS	5665. 17.3%	47413. 13.9%	53078 14.2%	1939. 4.7%	5486. 13.9%	7425. 9.3%	4. 3.6%	15. 13.9%	19. 8.4%
DEVELOPING	2044. 6.3%	1301. .4%	3345. .9%	22458. 55.0%	150. .4%	22608. 28.2%	1. .9%	1. .8%	2. .8%
PK/REC/PASTR	12858. 39.4%	18833. 5.5%	31691. 8.5%	6123. 15.0%	2179. 5.5%	8302. 10.3%	74. 61.2%	14 12.9%	87. 38.7%
FORESTS	0 .0%	0 .0%	0 .0%	0 .0%	0 .0%	0 .0%	6 4.7%	0. .0%	6. 2.5%
WATER	0 .0%	18301. 5.4%	18301. 4.9%	0 .0%	2118. 5.4%	2118. 2.6%	0 0%	4. 3.2%	4. 1.8%
FREEWAYS	0 .0%	46396. 13.6%	46396. 12.4%	0 .0%	5369. 13.6%	5369. 6.7%	0 .0%	11. 10.1%	11. 4.7%
TOTALS	32662.	340459.	373121.	40825.	39396.	80221.	120.	105.	225.

Table I-A-39. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in the watershed for the summer of 1977.

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	7830. 10.5%	147027. 31.0%	154857. 28.2%	804 1.9%	17656. 31.0%	18460. 18.4%	6. 1.9%	94. 7.2%	100. 10.1%
COMMERCIAL	38359. 51.7%	210840. 44.5%	249199. 45.4%	6172. 14.2%	25219. 44.5%	31491. 31.4%	28. 9.2%	170. 24.1%	198. 24.4%
MED/DENS/RES	12366. 16.7%	69639. 14.7%	82005. 15.0%	6867. 15.8%	8363. 14.7%	15230. 15.2%	102. 34.1%	53. 17.2%	155. 19.1%
LO/DENS/RES	23. .0%	11. .0%	34. .0%	1. .0%	1. .0%	2. .0%	0. .0%	0. .0%	0. .0%
HI/DENS/RES	1175. 1.6%	2470. .5%	3645. .7%	159. .4%	297. .5%	456. .5%	1. .4%	0. .5%	1. .6%
DEVELOPING	9876. 13.3%	2633. .6%	12509. 2.3%	29204. 67.2%	316. .6%	29522. 29.4%	6. 1.9%	9. 1.0%	15. 1.4%
PK/REC/PASTR	4383. 5.9%	19262. 4.1%	23645. 4.3%	246. .6%	2313. 4.1%	2559. 2.5%	104. 3.4%	24. 2.5%	128. 25.5%
FORESTS	0. .0%	0. .0%	0. .0%	0. .0%	0. .0%	0. .0%	7. 2.3%	0. .0%	7. 1.1%
LANDFILL	219. .3%	0. .0%	219. .0%	2. .0%	0. .0%	2. .0%	1. .0%	0. .0%	1. .1%
WATER	0. .0%	16760. 3.5%	16760. 3.1%	0. .0%	2013. 3.5%	2013. 2.0%	0. .0%	4. 1.2%	4. 2%
FREEWAYS	0. 0%	5454. 1.2%	5454. 1.0%	0. .0%	655. 1.2%	655. 1%	0. .0%	12. 1.0%	12. 1.1%
TOTALS	74230	474096.	548326.	42457	56933.	100390.	274.	308.	582.

Table I-A-40. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in the watershed for the summer of 1977.

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	2069 21.4%	58748. 16.0%	60817. 16.1%	217 3.5%	7055. 16.0%	7272. 14.5%	1. 1.1%	17. 15.9%	18. 17.9%
COMMERCIAL	4829. 49.8%	175151. 47.7%	179979. 47.8%	1121. 18.0%	21033. 47.7%	22154. 44.0%	24. 20.8%	50. 47.2%	74. 54.2%
MED/DENS/RES	855. 8.8%	24561. 6.7%	25416. 6.7%	214 3.4%	2950. 6.7%	3164. 6.3%	17. 15.2%	0. 5.6%	26. 17.2%
HI/DENS/RES	428. 4.4%	13638. 3.7%	14066. 3.7%	107. 2.6%	1638. 3.7%	1745. 3.6%	4. 3.2%	4. 4.2%	8. 7.2%
DEVELOPING	1017. 10.5%	565. .2%	1582. .4%	4510. 72.2%	68. .2%	4578. 9.1%	0. .0%	0. .4%	0. 4%
PK/REC/PASTR	151 1.6%	4501. 1.2%	4652. 1.2%	10. .2%	541 1.2%	551. 1.1%	7. 57.6%	0. 3.0%	7. 32.6%
FORESTS	0. .0%	0. .0%	0. .0%	0. .0%	0. .0%	0. .0%	1. .0%	0. .0%	1. .0%
LANDFILL	341. 3.5%	0. .0%	341. .1%	12 .2%	0. .0%	12. .0%	1. 1.3%	0. .0%	1. 1.0%
WATER	0. .0%	13654. 3.7%	13654. 3.6%	0. .0%	1640. 3.7%	1640. 3.3%	0. .0%	0. 2.7%	0. 4%
FREEWAYS	0. .0%	76097. 20.7%	76097. 20.2%	0. .0%	9138. 20.7%	9138. 18.2%	0. 14	12. 17.1%	12. 17.1%
TOTALS	9689.	366915.	376604.	6245.	44063.	50309	174.	1	175.

Table I-A-41. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3F (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1184. 2.5%	49650 7.5%	50834 7.2%	183. .1%	5962. 7.5%	6145. 2.1%	1. .3%	14. 6.1%	15. 3.0%
COMMERCIAL	4288. 9.2%	195991. 29.8%	200279. 28.4%	2950. 1.4%	23536. 29.8%	26486. 8.9%	30. 11.4%	56. 24.2%	86. 17.3%
MED/DENS/RES	14920. 32.1%	218233. 33.2%	233153. 33.1%	18149. 8.4%	26207. 33.2%	44356. 15.0%	75. 28.1%	83. 35.9%	157. 31.8%
LOW DENS/RES	1. .0%	60. .0%	61. .0%	2. .0%	7. .0%	9. .0%	0. .1%	0. .0%	0. .1%
HIGH DENS/RES	7639. 16.4%	95226. 14.5%	102865. 14.6%	3213. 1.5%	11435. 14.5%	14648. 4.9%	14. 5.4%	31. 13.4%	45. 9.1%
DEVELOPING	13459. 28.9%	8355. 1.3%	21814. 3.1%	191532. 88.3%	1003. 1.3%	192535. 65.0%	6. 2.4%	5. 2.4%	12. 2.4%
ROW CROPS	0. .0%	0. 0%	0. .0%	0. 0%	0. .0%	0. .0%	3. 1.1%	0. .0%	3. .6%
PK/REC/PASTURE	5017. 10.8%	37841. 5.8%	42858. 6.1%	934. 4%	4544. 5.8%	5478. 1.9%	136. 51.2%	29. 12.5%	165. 33.2%
WATER	0. .0%	13523. 2.1%	13523. 1.9%	0. 0%	1624. 2.1%	1624. .5%	0. .0%	3. 1.3%	3. .6%
FREEWAYS	0. 0%	39161. 6.0%	39161. 5.6%	0. .0%	4703. 6.0%	4703. 1.6%	0. .0%	9. 4.1%	9. 1.9%
TOTALS	46508.	658040.	704548.	216953.	79021	295984.	265.	230.	496.

Table I-A-42. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 3G (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	12. .2%	922. 1.3%	934. 1.2%	1. .1%	111. 1.3%	112. 1.2%	0. .0%	0. .8%	0. .2%
COMMERCIAL	573. 10.5%	31559. 45.0%	32132. 42.5%	466. 39.6%	3790. 45.0%	4256. 44.3%	111. 93.2%	18. 55.9%	129. 85.3%
MED/DENS/RES	2852. 52.4%	21678. 30.9%	24530. 32.4%	555. 47.2%	2603. 30.9%	3158. 32.9%	5. 4.1%	8. 25.6%	13. 8.6%
HIGH DENS/RES	1668. 30.6%	14933. 21.3%	16601. 22.0%	144. 12.2%	1793. 21.3%	1937. 20.2%	2. 1.4%	5. 15.1%	7. 4.4%
PK/REC/PASTURE	338. 6.2%	1075. 1.5%	1413. 1.9%	11. .9%	129. 1.5%	140. 1.5%	1. 1.2%	1. 2.5%	2. 1.5%
TOTALS	5443.	70167.	75610.	1177.	8426.	9603.	119.	32.	151.

Table I-A-43 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUM for all land use categories, summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	SEDIMENT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	10322 15.9%	149535 17.5%	159857 17.4%	1066 6%	17957 17.5%	19023 6.4%	10 2.3%	42 14.1%	52 16.1%
COMMERCIAL	18402. 28.4%	272042. 31.9%	290444 31.6%	5227. 2.7%	32669 31.9%	37896 12.8%	16. 5.4%	77 25.5%	93 15.1%
MED/DENS/RES	9748 13.5%	242300. 28.4%	251948 27.3%	6042. 3.1%	29096 28.4%	35138 11.9%	112. 32.5%	32 30.3%	144 11.5%
HI /DENS/PES	2395. 3.7%	53684. 6.3%	56079. 6.1%	746. 4%	6440. 6.3%	7192. 2.4%	11. 3.2%	11 3.4%	22 4.4%
DEVELOPING	12800. 19.7%	7902. .9%	20702 2.3%	177402. 91.0%	949. 9%	178351. 60.3%	5 1.4%	5 1.7%	10 1.2%
PK/REC/PASTR	12170 18.9%	74879. 8.8%	87049. 9.5%	2626 1.4%	8943 8.8%	11619. 3.9%	160 33.3%	57. 12.7%	177 14.9%
WATER	0. 0%	20609 2.4%	20609. 2.2%	0. 0%	2475. 2.4%	2475 8%	0 0%	5 1.5%	5 .7%
FRESHWATER	0. 0%	32451 3.8%	32451. 3.5%	0. 0%	3097 3.8%	3897 1.3%	0. 0%	3 2.4%	3 1.1%
TOTALS	64837	853402.	918239.	193109	172482.	295491.	735.	373.	642

Table I-A-44 Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUM for all land use categories, winter 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	SEDIMENT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
COMMERCIAL	246 2.9%	33039 12.3%	33985. 11.3%	66 .4%	3900. 12.3%	3975 9.4%	1. 1.7%	9 4.2%	10 1.4%
MED/DENS/RES	24204 74.4%	204904 83.8%	249108. 82.8%	7990 48.1%	26609 83.8%	34594 72.2%	1. 5.1%	11. 44.0%	12. 47.7%
HI /DENS/PES	115. .4%	1578 6%	1693. .6%	2. 1%	187 6%	195. .4%	0 4%	0 5%	0 1.4%
DEVELOPING	4412 12.6%	3117. 1.2%	7529. 2.5%	7900. 50.1%	269 1.2%	927. 17.4%	0 2.0%	0 2.0%	0 2.0%
PK/REC/PASTR	2851. 8.0%	5614 2.1%	8465. 2.8%	107 .7%	664 2.1%	771. 1.6%	0 5%	0 1.7%	0 1.1%
TOTALS	33528	268252	300780	15773	31738.	47511	7%	47.	54

Table 1-A-56. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Colwatershed 13 (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	11 .0%	234. .1%	245. .1%	0 .0%	28 .1%	28. .1%	0 .0%	0. .1%	0. .0%
COMMERCIAL	2545. 7.5%	39918. 13.9%	42463. 13.2%	180 2.3%	4723. 13.9%	4903. 11.7%	2 2.7%	11. 10.6%	13. 12.6%
MED/DENS/RES	25433 77.6%	225880 78.7%	252313. 78.6%	6915 87.7%	26724 78.7%	33639 80.4%	58. 72.3%	92 80.0%	139. 75.6%
LO/DENS/RES	1069 3.1%	13224. 4.6%	14293 4.5%	105 1.3%	1565 4.6%	1670 4.0%	2. 2.3%	4. 4.0%	6. 3.3%
DEVELOPING	491 1.4%	334 .1%	815 .3%	430 5.5%	40. 1%	470. 1.1%	0. 2%	0 2%	0. 2%
PK/REC/PASTR	3536. 10.4%	7257. 2.5%	10793 3.4%	259 3.3%	859 2.5%	1118. 2.7%	18. 22.5%	5. 5.1%	23. 12.7%
TOTALS	34075.	286847.	320922.	7889	33939	41823.	80.	102.	182.

Table 1-A-56. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Colwatershed 13 (area in ha)--  
Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	14695. 9.1%	630223. 26.1%	694918. 25.1%	2122 4.4%	80479 26.1%	82601. 23.2%	13. 3.7%	185. 23.0%	197. 17.3%
COMMERCIAL	26788. 16.6%	963993. 37.0%	990781. 35.8%	4259. 8.9%	114052. 37.0%	118311. 33.2%	23 6.7%	262. 32.6%	285. 24.9%
MED/DENS/RES	60096 37.3%	557160 21.4%	617256 22.3%	23628 49.2%	65919. 21.4%	89547. 25.1%	173. 50.8%	202. 25.1%	375. 32.8%
LO/DENS/RES	252. .2%	306. 0%	558 0%	15. 0%	36. 0%	51. 0%	0. .1%	0 .0%	1. .1%
HI/DENS/RES	4203. 2.6%	55930. 2.1%	60133. 2.2%	685. 1.4%	6617. 2.1%	7302. 2.0%	9. 2.7%	17. 2.2%	27 2.3%
DEVELOPING	713. 4%	505. 0%	1218 .0%	1147 2.4%	60. 0%	1207. 3%	0 .1%	0 .1%	1. 0%
PK/REC/PASTR	54411. 33.8%	114714. 4.4%	169125 6.1%	16195. 33.7%	13572 4.4%	29767 8.3%	122. 35.0%	83 10.4%	205. 18.0%
WATER	0. 0%	44208. 1.7%	44208. 1.6%	0 0%	5230. 1.7%	5230. 1.5%	0. 0%	10. 1.2%	10. 0.9%
FREEWAYS	0 0%	190488. 7.3%	190488. 6.9%	0. 0%	22537. 7.3%	22537. 6.3%	0 0%	44 5.4%	44 3.9%
TOTALS	161158	2607527.	2768685.	48051.	308502.	356553.	340.	833.	1173.

Table I-A-47. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 14 (area in ha) -- Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	2386. 4.0%	111205. 15.0%	113591 14.2%	222 1.3%	13157 15.0%	13379. 12.8%	2. 1.3%	31. 13.2%	33. 4.5%
COMMERCIAL	10073 16.9%	200742. 27.1%	210815. 26.3%	1540. 9.3%	23750. 27.1%	25290. 24.2%	15. 9.3%	55. 23.9%	70. 17.7%
MED/DENS/RES	29273. 49.2%	252247. 34.0%	281520. 35.2%	7811. 47.0%	29844. 34.0%	37655. 36.1%	55. 40.9%	91. 40.9%	157. 47.3%
HI /DENS/RES	3551. 6.0%	46094. 6.2%	49645. 6.2%	527. 3.2%	5454. 6.2%	5981. 5.7%	7. 4.5%	14. 6.3%	22. 6.5%
DEVELOPING	1368. 2.3%	949. .1%	2317. 3%	2204. 13.3%	112. .1%	2316. 2.2%	0. .2%	1. .3%	1. 2%
PK/REC/PASTR	9553. 16.0%	15742. 2.1%	25295 3.2%	3362. 20.2%	1863. 2.1%	5225. 5.0%	58 36.0%	11. 5.0%	69. 17.8%
LANDFILL	3354. 5.6%	0. .0%	3354 .4%	965. 5.8%	0. .0%	965. .9%	13. 7.9%	0. 0%	13. 3.2%
WATER	0. .0%	13422. 1.8%	13422 1.7%	0. .0%	1588. 1.8%	1588. 1.5%	0. .0%	3. 1.3%	3. 8%
FREEWAYS	0. .0%	100814. 13.6%	100814. 12.6%	0. 0%	11928. 13.6%	11928. 11.4%	0 .0%	23. 10.1%	23 5.9%
TOTALS	59558.	741215.	800773.	16631.	87696.	104327	160.	229.	389.

Table I-A-48. Water (m<sup>3</sup>) and sediment (kg) loadings estimated by LANDRUN for each land use in Subwatershed 15 (area in ha) -- Summer 1977

LAND USE	WATER PERV	WATER IMPER	WATER TOTAL	SEDIMENT PERV	DUST/DIRT IMPER	SEDIMENT TOTAL	AREA PERV	AREA IMPER	AREA TOTAL
INDUSTRIAL	1176. 2.3%	52664. 10.5%	53840 9.8%	91. .4%	6231. 10.5%	6322. 7.6%	1. 7%	14. 6.4%	15. 5.0%
COMMERCIAL	7026. 13.8%	114516. 22.9%	121542. 22.1%	680. 2.8%	13549. 22.9%	14229. 17.1%	7. 4.9%	31 18.4%	38 12.4%
MED/DENS/RES	30675. 60.1%	288972. 57.8%	319647. 58.0%	10718. 44.4%	34189. 57.8%	44907. 53.9%	93. 68.6%	105. 61.7%	197 64.6%
HI /DENS/RES	1139. 2.2%	15529. 3.1%	16668. 3.0%	142 .6%	1837. 3.1%	1979. 2.4%	3. 2.0%	5. 2.8%	8 2.5%
DEVELOPING	4316. 8.5%	3046. .6%	7362. 1.3%	10771. 44.6%	360 .6%	11131. 13.4%	1. 1.1%	2. 1.1%	3. 1.1%
PK/PAC/PASTR	6389 12.5%	14238. 2.8%	20627 3.7%	1695. 7.0%	1685. 2.8%	3380 4.1%	30. 21.8%	10 5.1%	40. 13.1%
LANDFILL	292. .6%	0. .0%	292 .1%	45. .2%	0. .0%	45. .1%	1. .8%	0. .0%	1 .4%
WATER	0 0%	11225. 2.2%	11225. 2.0%	0. .0%	1328. 2.2%	1328. 1.6%	0. .0%	2. 1.4%	2. .8%
TOTALS	51013	500190.	551203.	24142	59179.	83321.	135.	170	305.

PART II

MODEL ENHANCED UNIT LOADING (MEUL) - A METHOD  
OF ASSESSING POLLUTANT LOADINGS FROM A  
SINGLE LAND USE

by

V. NOVOTNY  
G. CHESTERS  
G. V. SIMSIMAN

## ABSTRACT

The Model Enhanced United Loading (MEUL) method utilizing the LANDRUN model has been developed to simulate potential pollutant loadings from urban and non-urban land uses. The simulations for typical land uses are evaluated as if the land uses are located on hydrologically different soils representative of standard hydrologic categories. Pollutant loadings vary considerably among land uses. Sensitivity analyses indicate that the most significant factors affecting such differences are extent of imperviousness of urban areas, portion of the impervious areas directly connected to runoff channels, depression and storage, length of dry period between rainfall, curb height for urban areas and soil type, slope and vegetative cover for pervious urban and non-urban areas. The applicability of the unit loading data obtained by the MEUL method has been tested on several well-monitored subwatersheds in the Menomonee River Watershed. The simulated unit loadings for sediment and phosphate-P are of the same order of magnitude as the measured values.

## CONTENTS - PART II

Title Page .....	II-i
Abstract .....	II-ii
Contents .....	II-iii
Figures .....	II-iv
Tables .....	II-vi
II-1. Introduction .....	II-1
II-2. Conclusions .....	II-3
II-3. Methodology .....	II-4
Pollutant Transport Process from Non-point Sources .....	II-4
Pollutant Loadings and Transport from Impervious Urban Areas .....	II-4
Unit Loadings from Pervious Areas .....	II-5
Rainfall factor, R .....	II-6
Soil erodibility factor, K .....	II-7
Slope-length factor, LS .....	II-7
Vegetative cover factor, C .....	II-7
Erosion control practice factor .....	II-7
Delivery ratio factor, D .....	II-8
Application of LANDRUN Model - Model Enhanced Unit Loading (MEUL) Simulations Based on Land Use .....	II-8
Surface characteristics .....	II-9
Soils .....	II-10
Soil erosion data .....	II-18
Pollutant accumulation in urban areas .....	II-22
Atmospheric pollutant deposition .....	II-22
Wind erosion .....	II-29
Motor vehicles .....	II-29
Litter deposition .....	II-29
Effect of vegetation .....	II-29
Pollutant washout .....	II-30
Street sweeping practices .....	II-32
Meteorological inputs .....	II-32
II-4. Results and Discussion .....	II-39
Simulated Loadings .....	II-39
Comparison of Measured Loadings with Estimates Obtained by the MEUL Method .....	II-44
References .....	II-50
Appendices	
II-A. Detailed Statistical Evaluation of Street Litter Accumulation .....	II-53
II-B. Simulated Loading Diagrams .....	II-61
II-C. Remedial Measures and Non-Point Pollution Control .....	II-76

## FIGURES

<u>Number</u>		<u>Page</u>
II-1	Depression storage capacity in relation to degree of land slope .....	II-11
II-2	Fraction of impervious areas not directly connected to channel .....	II-12
II-3	Moisture characteristics of selected soils .....	II-15
II-4	Soil particle size distribution accepted by USDA-SCS .....	II-16
II-5	Relationship between soil permeability and soil texture ...	II-17
II-6	Determination of soil K factor .....	II-19
II-7	Pollutant accumulation schematic model .....	II-23
II-8	Curb length-imperviousness relationship .....	II-25
II-9	Seasonal cumulative frequency of precipitation .....	II-35
II-10	Seasonal cumulative frequency of R-factor .....	II-36
II-11	Slope correction factor for sediment and phosphate loadings from pervious urban areas .....	II-41
II-12	Loading multiplier for different slope categories .....	II-42
II-13	Relationship of the size of the area to sediment loading .....	II-43
II-14	Sediment delivery ratio versus drainage area .....	II-47
II-A-1	Effect of dry periods on the quantity of street litters ...	II-59
II-B-1	Sediment loadings from residential areas .....	II-62
II-B-2	Sediment loadings from commercial areas .....	II-63
II-B-3	Sediment loadings from industrial areas .....	II-64
II-B-4	Phosphate-P loadings from residential areas .....	II-65

II-B-5	Phosphate-P loadings from commercial areas .....	II-66
II-B-6	Phosphate-P loadings from industrial areas .....	II-67
II-B-7	Relationship of sediment loadings and R-factor in row crop-woodland areas .....	II-68
II-B-8	Probability distribution of sediment loadings in row crop-woodland areas .....	II-69
II-B-9	Relationship of sediment loadings and R-factor in feedlots .....	II-70
II-B-10	Probability distribution of sediment loadings in feedlots .....	II-71
II-B-11	Relationship of sediment loadings and R-factor in pastures .....	II-72
II-B-12	Probability distribution of sediment loadings in pastures .....	II-73
II-B-13	Relationship of sediment loadings and R-factor in wetlands .....	II-74
II-B-14	Probability distribution of sediment loadings in wetlands .....	II-75
II-C-1	Effect of sweeping interval on pollutant loadings (sweeping efficiency = 50%) .....	II-78
II-C-2	Effect of sweeping efficiency on pollutant loadings (sweeping interval = 7 days) .....	II-79
II-C-3	Effect of curb (median barrier) height on street litter accumulation .....	II-80

## TABLES

<u>Number</u>		<u>Page</u>
II-1	Properties of soils used in the simulation .....	II-13
II-2	Properties of the major soil types surrounding the Donges Bay station (463001), Menomonee River Watershed .....	II-14
II-3	C-value used to compute erosion .....	II-20
II-4	Metal concentrations of surficial materials of the U.S.A. ...	II-21
II-5	Street refuse accumulation .....	II-24
II-6	Pollutants associated with street refuse .....	II-26
II-7	Metal contamination of street refuse .....	II-27
II-8	Annual and monthly mean deposition rates of particulate material in Milwaukee County .....	II-28
II-9	Daily leaf fall .....	II-31
II-10	Pollutant distribution in various particle sizes .....	II-33
II-11	Interrelationship of sweeper efficiency and particle size ...	II-33
II-12	Street sweeping removal efficiency of pollutants .....	II-33
II-13	Urban land use information .....	II-37
II-14	Non-urban land use information .....	II-38
II-15	Simulated pollutant loadings for urban land uses under slope category B (2 to 6%) during an average year (1968) ....	II-40
II-16	Simulated pollutant loadings for land uses on essentially pervious areas .....	II-45
II-17	Comparison of simulated and measured sediment and phosphate loadings in subwatersheds with mixed land uses .....	II-48
II-18	Comparison of simulated and measured sediment and phosphate loadings in predominantly single land use areas .....	II-49

II-A-1      Partial and multiple correlation coefficients between dust  
and dirt pollutants and factors affecting their accumulation. II-57

## II-1. INTRODUCTION

The International Joint Commission, through the Great Lakes Water Quality Board, established the International Reference Group on Great Lakes Pollution from Land Use Activities (PLUARG) to study and report the effects of land use on water quality and recommend remedial measures. Several pilot watersheds subjected to detailed monitoring were selected throughout the Great Lakes Basin in Canada and the United States. The Menomonee River Watershed located in the southeastern part of Wisconsin in the Milwaukee metropolitan area was one of the watersheds selected. The primary task was to establish pollutant loadings from various land uses and extrapolate these findings to the entire Great Lakes region.

The investigation discussed in this report presents an effort to develop unit loadings for typical urban and suburban land uses using a combination of modeling techniques with measured monitored data. It is true that the best information on actual loadings can be obtained only from direct field measurements. However, the applicability of such information is limited by time and location at which the data were gathered and sometimes by the sparsity of data. On the other hand, even the most effective models may fail to provide reliable results if proper calibration and verification is not guaranteed. Thus, a combination of simulated loadings using a mathematical model, calibrated and verified by extensive monitoring data and applied to several hydrologically different seasons and soils, may provide a better understanding of the variability of the loading figures, their dependence on meteorological, pedological and environmental factors and may reveal a possible impact of some remedial measures suggested for reducing pollutant impact.

Pollution from non-point or diffuse sources originates either from weathering of minerals, erosion of virgin and forest lands including residues of natural vegetation, or from artificial or semi-artificial sources. The latter sources can be related directly to human activities such as fertilizer application or use of agricultural chemicals for controlling weeds and pests, erosion of soil materials from agricultural farming areas and animal feedlots, erosion occurring in urban developments, transportation, atmospheric fallout, etc. With the gradual elimination of point sources including sewage and industrial wastewater outfalls, it is becoming obvious that a substantial portion of surface waters pollution originates from the use of land by man, i.e. from diffuse sources.

A tendency exists to relate pollutant loadings from non-point sources to type of land use. In this approach, pollution from diffuse sources is expressed simply as a value or range of unit loadings (loadings/unit area/unit time) for the land use. This approach, though justified as an initial rough approximation may lead to results which deviate markedly from measured values. More appropriately, it is important to examine and analyze the basic processes and factors involved in pollutant generation from diffuse sources.

The Model Enhanced Unit Loading (MEUL) analysis is a method which assesses pollutant loadings from various land uses on a directly comparative basis. The loadings are generated by a hydrologic overland pollution transport model calibrated and verified by extensive field measurements and monitoring. The loadings generated in this way are abstracted from a particular location at a particular time and reflect for a typical area mean pollutant accumulation characteristics and statistically averaged meteorological conditions subjected to certain land uses. The pollutant loadings developed in this report do not include background or natural composition of surface waters caused by its contact with geological layers, undisturbed soils and natural vegetation.

Limitations of the MEUL method include:

1. The method is intended basically for comparative assessment of loadings among various land uses.
2. The loadings are related to a few primary variables such as degree of imperviousness of the area, cleanliness of the area, soil characteristics and type of land use.
3. The meteorological inputs represent a typical average meteorological year for the Midwest (Milwaukee). The accuracy of the estimates for pervious areas was improved by considering the 10 and 90 percentile meteorological seasons selected from 30 years of weather observations in southeastern Wisconsin.
4. The pollutant accumulation rates on impervious areas represent average U.S. rates as reported by Sartor and Boyd (1).
5. The loading figures were computed for five typical urban land uses (residential, commercial, industrial, developing and parks) and five typical non-urban land uses (row crops, pastures, woodland, wetland and feedlots).
6. The loading figures are not intended to be used for estimating accurate loadings in areas where no historical or monitoring data are available.
7. No monitored pollutant loadings from pervious areas and only limited loadings from impervious areas during winter conditions in Midwestern areas are available.

## II-2. CONCLUSIONS

Large amounts of pollutants are washed into surface waters from non-point sources. The factors contributing to non-point pollution from various urban and non-urban land uses have been investigated using a calibrated and verified hydrologic transport model capable of simulating overland pollutant loading and transport. The simulated seasonal loadings provide a comparison of the variability and potential danger to surface waters of typical land use activities. The model was calibrated and verified using field data from the Menomonee River Pilot Watershed Study. The simulated loadings for typical land use areas were evaluated as if the land uses were located on four hydrologically different soils representative of standard hydrologic categories. Developing urban, high density urban areas with no cleaning practices, livestock feedlots and steep-sloped crop lands yield the highest pollutant potential while parks and recreational areas, low density residential and most urban areas with good cleaning practices produce much less pollutants. The differences in pollution potential among the land uses were several orders of magnitude. Summer rains in Midwestern areas have the highest erosion potential; however, spring rains on bare soils with frozen subsurface generate the highest sediment runoff on row cropland. By sensitivity analyses, various parameters have been tested as to their effect on loadings. The most significant parameters are extent of imperviousness of urban areas, fraction of impervious areas directly connected to surface runoff, depression and interception storage, average length of the dry period preceding a rain, curb height for urban areas and soil type, slope and vegetative cover for pervious urban and non-urban areas.

Various control techniques and their impact on non-point sources pollutant generation have been discussed.

The loading diagrams which relate sediment and phosphate-P unit loadings to the most important causative factors have been developed and their applicability tested on several subwatersheds in the Menomonee River Basin. Estimated and measured loading values were of the same order of magnitude.

### II-3. METHODOLOGY

#### Pollutant Transport Process From Non-Point Sources

Water is the primary mover of pollutants through the environment from their sources to the place of final disposal. Unlike pollutants from point sources which enter the hydrologic transport route during a late stage of the hydrologic cycle (channel or estuary flow), non-point source pollutants enter the hydrologic route during its early stage, i.e., in precipitation or by overland flow. The point where the pollutants enter the hydrologic transport process depends not only on the type and location of the source but also on the physical form in which the pollutant occurs. Gaseous, emulsified and dispersed airborne pollutants enter the water transport route following deposition on the surface by wet or dry fallout. Soluble pollutants mix with water directly. Relatively insoluble pollutants either are dispersed and picked up during rain or snowmelt events through subsequent surface runoff, or are transported by wind and subsequently redeposited. Furthermore, pollutants can be adsorbed by soil and dust particles and transported by water in the particulate phase.

It is anticipated that non-point pollutant transport processes in urban areas may be different from those in non-urban areas because:

1. Large portions of urban areas are impervious resulting in much higher hydrological activity.
2. With the exception of construction sites most of the pervious surfaces in residential or city areas are well protected by lawns and are subject to less erosion.
3. Pollutant loadings in urban areas are affected mainly by litter accumulation, dry or wet fallout and traffic while in non-urban areas most of the pollution is due to erosion of soils and soil-adsorbed pollutants.
4. Over a large period of time (season) almost all of the pollutants deposited on impervious surfaces which have not been removed by street cleaning practices, wind or decay, eventually end up in surface runoff. On the other hand, in non-urban areas soil represents an extensive pool of sediments and pollutants adsorbed by soil and their removal rate depends then on the energy of rain or runoff which liberates the soil particles and eliminates surface protection.

#### Pollutant Loadings and Transport From Impervious Urban Areas

Pollutant accumulation on ground surfaces in urban areas and subsequent washout by runoff represents a major pollutant contribution from non-point

urban sources. Since impervious areas are almost fully hydrologically active, most of the runoff and associated pollutants in highly urbanized areas originate from these surfaces. The amount of deposited pollutants depends on various factors and inputs. The major inputs are atmospheric fallout, street litter deposition, animal and bird fecal wastes, dead vegetation, and road traffic impacts. The factors which affect the quality of street refuse washed out to surface waters include land use, population density, traffic flow and frequency, effectiveness of street cleaning, type of street surface and condition.

It has been realized that a simple unit loading value related to land use may not provide an adequate estimation. Instead, the loading values should be correlated to major causative factors which for various urban land uses can be listed as follows:

- a. Percent impervious area directly connected to a channel (a function of land use or percent of imperviousness).
- b. Population density (a factor related to land use).
- c. Dry and wet atmospheric fallout.
- d. Litter accumulation (a factor related to population density and land use).
- e. Traffic density (a factor related to land use).
- f. Curb height and length/unit area (factors related to land use).
- g. Percent open area (a factor related to land use).
- h. Average wind velocity.
- i. Street cleaning practices and effectiveness.
- j. Average number of dry days preceding a rain or rain intensity.
- k. Depression and interception storage (a factor related to land use).

With the exception of low density residential areas, other factors such as slope, soil type, are expected to have little effect on pollutant loads from urban areas because most of the loading originates from impervious areas.

It can be seen that most--but not all--of the above listed factors are indeed related to land use. Thus, it may be possible to develop a multi-dimensional loading factor for various urban land uses which would be a function of:

- a. Dry fallout (primary independent variable).
- b. Street cleaning frequency and efficiency. ) parametric
- c. Average wind velocity. ) independent variable
- d. Average number of dry days preceding a rain. )

#### Unit Loadings From Pervious Areas

Urban or suburban pervious areas with the exception of those overlain with heavy clay soils or areas with a very high groundwater table are hydrologically active only during extreme storms or during spring melt or rain events when the ground is frozen. Freezing of the surface layers in Midwestern areas of the United States also provides protection against erosion and groundwater contamination.

Sediment and soil-adsorbed pollutants (e.g., P, heavy metals and most pesticides) can be modeled by the Universal Soil Loss Equation (USLE). The equation in its original form (2) can be written as:

$$A = (R) (K) (LS) (C) (P) \quad \text{Eq. (1)}$$

where

A is amount of sediment generated/storm  
 R is the rainfall energy factor of the storm  
 K is the soil erodibility factor  
 LS is the length-slope factor  
 C is the vegetative cover factor  
 P is the erosion control factor

In this form the equation represents the amount of soil particles liberated by rain energy impact. In order to obtain the sediment load to receiving waters the equation must be multiplied by a delivery ratio:

$$AS = D * A \quad \text{Eq. (2)}$$

where AS is the sediment load and D is the sediment delivery ratio.

Loadings of some pollutants other than sediment are then estimated by

$$PL = AS * CP * RP \quad \text{Eq. (3)}$$

where

PL is pollutant loading  
 CP is pollutant content of the soil  
 RP is the enrichment factor accounting for the difference in pollutant content in soil and the sediment suspended in water

It is possible now to estimate which of the above variables is land use related.

#### Rainfall factor, R

This is a function of storm intensity and volume and is not related to any land use activity.

The rainfall energy factor, R, is computed according to the equation:

$$R = \sum_i \{[(2.29 + 1.15 \log X_i)] D_i\} I \quad \text{Eq. (4)}$$

where

$X_i$  is rainfall intensity, cm/hr

$\Sigma_i$  is rainfall hydrograph time interval

$D_i$  is rainfall depth during time interval  $i$

$I$  is the maximum 30 min rainfall intensity of the storm in cm/hr

It is evident that the rain energy input/season reduced by the amount of snowpack on the surface is the major independent variable affecting the soil loss estimation.

#### Soil erodibility factor, K

This is purely a function of soil characteristics (2,3). For most Midwestern soils the K factor is in the range 0.1 to 0.4.

#### Slope-length factor, LS

This is based on formula (2):

$$LS = L^{1/2} (0.0138 + 0.00974S + 0.001385^2) \quad \text{Eq. (5)}$$

where

$L$  is length from the point of origin of the overland flow, m

$S$  is the average slope over the given overland flow length, %

The equation indicates that soil loss is more sensitive to slope changes than to the size of the area.

#### Vegetative cover factor, C

This variable depends on the crop or vegetative cover and the season. It varies from 0.005 for heavily wooded areas to 1.0 for bare soils. Besides the rain energy factor and slope this is a variable to which soil loss is very sensitive.

#### Erosion control practice factor, P

This factor depends on erosion practices implemented in the Watershed. In the absence of such practices the value assigned to this factor is unity.

### Delivery ratio factor, D

This is probably the most difficult factor to estimate. For larger watersheds the delivery ratio seems to be a function of watershed size and configuration. For smaller areas it may be a function of the lot roughness (depression and interception storage) and, mainly, permeability. For relatively homogeneous sites, a study by the Midwest Research Institute (4) related delivery ratio to soil texture and drainage density which is defined as the ratio of total channel-segment lengths to the basin area.

If a loading function is to be developed it should be related to the rainfall energy factor as a primary independent variable, with soil type, slope and depression storage as parametric variables

### Application of LANDRUN Model - Model Enhanced Unit Loading (NEUL) Simulations Based on Land Use

This method used in the study to develop loading functions relied on field data and system simulation. It has been realized that although the field data provide the best information on pollutant loadings from a particular site the information is limited by time and location at which the data were gathered. On the other hand, even the most complex simulation model of a watershed can provide results quite far from reality if the model is not properly calibrated or verified.

A model developed for this study has the code name LANDRUN (5). It is a deterministic watershed model capable of simulating the following processes:

- a. Snowpack-snowmelt by the Holtan or Philip Models.
- b. Infiltration by the Holtan or Philip Models.
- c. Excess rain can be computed as the difference between precipitation and evaporation, evapotranspiration, infiltration and surface storage.
- d. Routing of excess rain by an Instantaneous Unit Hydrograph Method.
- e. Dust and dirt accumulation in urban areas and washout.
- f. Removal of accumulated pollutants on impervious areas by cleaning practices.
- ✓ g. Surface erosion by a modified quasi-dynamic USLE which includes effects of rainfall energy and sheet runoff.
- h. Routing of the sediment and sediment-adsorbed pollutants.

The model takes into consideration several parameters including:

- a. Land use data.
- b. Meteorological parameters.
- c. Pollutant input.

The computer model is capable of estimating:

- a. Storm water hydrographs and volume.
- b. Sediment transport from pervious areas.
- c. Dust and dirt washout from urban impervious areas.
- d. Volatile suspended solids in the runoff.
- e. Adsorbed pollutant loadings.

A dynamic soil adsorption segment is an optional feature of the model which enables detailed study of pollutant-soil interactions (6).

Following calibration and verification of the LANDRUN model (7), pollutant loading simulations were conducted for the land uses agreed upon by PLUARG. The land uses were grouped into urban and non-urban categories:

<u>Urban uses</u>	<u>Non-urban uses</u>
Low density residential	Row crops
Medium density residential	Pasture
High density residential	Livestock feedlots
Commercial	Woodlands
Industrial	Wetlands
Park and recreation	
Developing	

To simulate pollutant loadings, each land use was assigned typical values for such variables as degree of imperviousness, fraction of impervious areas directly connected to a channel, depression storage, permeability of pervious areas, slope, soil moisture characteristics, etc. In addition, other variables describing atmospheric fallout, litter accumulation, street sweeping practices and the USLE inputs were selected. The values were based on Menomonee River Pilot Watershed data or on literature values typical of Midwestern urban areas.

#### Surface characteristics

The model requires a detailed description of the hydrologic characteristics of the subwatershed surface. Included are: Degree of imperviousness, depression and interception (surface) storage, subwatershed slope, surface roughness and extent of impervious areas directly connected to a channel.

Most of the land surface data was obtained from the SEWRPC Land Data Management System (Land DMS) (8). Unless otherwise specified default values were substituted in the model for depression and interception storage and surface roughness. For combined depression and interception storage characteristics, default values used are: 6.35 mm (1/4 inch) for pervious areas and 1.58 mm (1/16 inch) for impervious areas. These values are similar to those used in the Chicago study (9) and other urban studies. For non-urban pervious areas a graph developed by Hiemstra (10) served as a guide to selection of the storage characteristics (Fig. II-1).

Surface roughness characteristics are necessary if routing of pollutants is required. The value of the Manning roughness factor for pervious areas is 0.25 and for impervious areas is 0.012.

The impervious areas not directly connected to the surface runoff channels include rooftops discharging through underground drains, paved areas overflowing on adjacent pervious surfaces, etc. This factor can be related approximately to the total imperviousness of the area as shown in Fig. II-2. The simulated areas were 1 km<sup>2</sup> for each land use.

### Soils

For simulation purposes, four soils typical of the Menomonee River Watershed or immediate vicinity were selected. These soils are representative of each basic hydrologic group ranging from the most permeable hydrologic group A to the least permeable group D (11).

Table II-1 shows the basic soil data used in the simulation; these data reflect typical values for soils given in SCS soil maps. More exactly measured values for ten major soil types in the Donges Bay Road subwatershed (station 463001) are reported in Table II-2.

Some of the data such as 0.3-bar moisture tension (field moisture capacity) and 15-bar moisture tension (wilting coefficient) are unavailable from soil maps. In this case, a graph relating moisture characteristics to median particle diameter of the soils was prepared using data from the Menomonee River Watershed and literature values (Fig. II-3). The median particle diameter in mm was computed using a formula suggested by Horn (13):

$$d_m = \frac{1}{100} [0.3 (\% \text{ sand}) + 0.01 (\% \text{ silt}) + 0.002 (\% \text{ clay})] \quad \text{Eq. (6)}$$

The particle sizes (Fig. II-4) are the averages of the particle size ranges recommended by the U.S. Department of Agriculture (USDA).

The permeability ranges related to soil mean particle diameter are shown in Fig. II-5. Known and measured data for some Wisconsin soils indicate that a lower range of permeability seems to be typical for Wisconsin rather than an average theoretical curve. However, data measured by Bouma et al. (14) represent permeabilities of septic tank seepage fields after several years of operation and may not provide a good approximation of permeability of typical undisturbed soils. Such values confirm the lower limits of the permeability-texture relationship.

### Soil erosion data

Use of the USLE requires a knowledge of: the rainfall energy factor (R), soil erodibility factor (K), cropping management factor (C), erosion control practice factor (P) and the slope-length factor (LS).




Fig. II-1. Depression storage capacity in relation to degree of land slope (10).




Fig. II-2. Fraction of impervious areas not directly connected to channel (12).

Table II-1. Properties of soils used in the simulation

Property	Soil type			
	Boyer ls	Hochheim l	Ozaukee sil	Ashkun sicl
Hydrologic group	A	B	C	D
Depth of A-horizon, cm	41	20	28	28
Sand, %	80	45	15	5
Silt, %	15	39	55	56
Clay, %	5	16	20	39
Mean diameter, mm	0.415	0.138	0.051	0.021
Organic matter, %	0.5	2.0	3.0	8.0
Permeability of A-horizon, cm/hr	40	10	3.0	0.5
0.3 bar H <sub>2</sub> O content, %	8	20	30	36
15 bar H <sub>2</sub> O content, %	0	7	17	24
Porosity, %	30	34	43	46
K factor*	0.09	0.24	0.31	0.15
PO <sub>4</sub> -P adsorption,** ug/g	243	346	403	697
Total P content, ug/g	1,000	1,500	1,800	3,100

\*K is the soil erodibility factor used in USLE.

\*\*Soil adsorption maximum obtained from the Langmuir isotherm.

Table II-2. Properties of the major soil types surrounding the Donges Bay station (463001), Menomonee River Watershed

Property	Soil type									
	Ozaukee sil	Mequon sil	Ogden muck	Pella sil	Theresa sil	Sesewa sil	Belwood sil	Ashtun silt	For 1	Lib 1
Area, ha	1,018	182	162	101	73	47	56	50	39	31
% of total area*	47.5	8.5	7.6	4.7	3.4	2.2	2.6	2.4	3.8	...
Depth of A-horizon, cm	18	28	90	30	40	40	23	25	13	...
Hydrologic group	C	C	D	B	D	D	D	D	B	B
pH	6.6 to 7.3	7.4 to 7.8	6.6 to 7.8	6.6 to 7.3	6.6 to 7.8	7.4 to 7.8	7.4 to 7.8	7.4 to 7.3	6.1 to 7.3	7.1
Clay, %	20.3 to 20.8				11.7 to 13.1			39.7		
Organic C, ** %	1.52 to 1.70				3.89 to 4.30			3.06 to 3.38		
0.3 bar H <sub>2</sub> O content, %					34.6			1.02 to 1.92		
15 bar H <sub>2</sub> O content, %	7.8 to 8.1				10.5					
Available H <sub>2</sub> O, cm/cm	0.20	0.20	>0.20	0.24	0.20	0.20	0.20	0.20	0.16	0.11
Extractable Fe, %	1.2 to 1.3							1.1 to 1.2		
Bulk density, g/cm <sup>3</sup>	1.44 to 1.55				1.20 to 1.31			1.50 to 1.85		
Permeability, cm/hr	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1	1.6 to 5.1
Porosity, %	41.5 to 45.7									
Cation exchange capacity, me/100 g	14.0 to 14.4				21.2 to 23.9			33.2 to 33.9		

\*Total area of Donges Bay station watershed is 2,144 ha.

\*\*To convert organic C to organic matter divide organic C by 0.60




Fig. II-3. Moisture characteristics of selected soils.




Fig. II-4. Soil particle size distribution accepted by USDA-SCS.




Fig. II-5. Relationship between soil permeability and soil texture (13).

The value of R is computed by the LANDRUN model from the rainfall data and the LS factor is estimated from average slope and area of the subwatershed for each land use. However, the remaining three factors must be inputted for each soil and land cover. Figure II-6 is a nomograph for estimating K. The factor K is determined from the contents of silt and very fine sand (particle size 0.01 to 0.1 mm), sand (0.1 to 2 mm), organic matter, soil structure and permeability. The K factors for the selected four soils are:

<u>Soil</u>	<u>K factor</u>
Boyer ls	0.09
Hochheim sil	0.24
Ozaukee sil	0.31
Ashkum sicl	0.15

The factor, C, is dependent on type of groundcover, general management practices and composition of the soil. For simulation purposes, the values suggested by Brandt (15) were used (Table II-3). For agricultural cultivated lands C was 1 during the spring season and adjusted to its tabular value for summer and fall.

The P factor was 1 for most land uses. Some erosion control was assumed on croplands.

Organic matter content of soils was selected to reflect typical values in the Watershed.

Phosphate-P content of soils was based on the known range of P content of the Ozaukee sil ( $P \approx 0.18\%$ ) which was determined from the measured total P-suspended solids relationship from the spring runoff at the Donges Bay Road station. The phosphate-P content for other soils was adjusted according to their adsorption characteristics,  $Q^0$  (6).

The lead content of average soils is very low. The U.S. Geological Survey (USGS) has undertaken an in-depth study (16) to determine the elemental composition of surficial materials in the United States. Soil samples were collected from 863 sites throughout the 48 conterminous states and analyzed for 44 elements. The average values for eastern and western parts of the United States are presented in Table II-4.




Fig. II-6. Determination of soil K factor (3).

Table II-3. C-value used to compute erosion (15)

Land use	C-value
Cropland	0.08
Grassland	0.01
Woodland	0.05
Construction	1.00
Urban	0.01

Table II-4. Metal concentrations of surficial materials of the U.S.A. (16)

Element	Average, $\mu\text{g/g}$	Range, $\mu\text{g/g}$	Geometric means, $\mu\text{g/g}$		
			Conterminous U.S.A.	West of 97th meridian	East of 97th meridian
As	--*	< 1,000	--	--	--
Ba	554	15 to 5,000	430	560	300
Cd	--	< 20	--	--	--
Ce	86	<150 to 300	75	74	78
Cr	53	1 to 1,500	37	38	36
Co	10	<3 to 70	7	8	7
Cu	25	<1 to 300	18	21	14
Fe	25,000	100 to 100,000	18,000	20,000	15,000
Ga	19	<5 to 70	14	18	10
Ge	--	< 10	--	--	--
Au	--	< 20	--	--	--
Hf	--	< 100	--	--	--
In	--	< 10	--	--	--
La	41	<30 to 200	34	35	33
Pb	20	<10 to 700	16	18	14
Mn	560	<1 to 7,000	340	389	285
Mo	3	<3 to 7	--	--	--
Nd	45	<70 to 300	39	36	44
Ni	20	<5 to 700	14	16	13
Nb	13	<10 to 100	12	11	13
Pd	--	< 1	--	--	--
Pt	--	< 30	--	--	--
Re	--	< 30	--	--	--
Sc	10	<5 to 50	8	9	7
St	240	<5 to 3,000	120	210	51
Ta	--	< 200	--	--	--
Te	--	< 2,000	--	--	--
Tl	--	< 50	--	--	--
Th	--	< 200	--	--	--
Ti	3,000	300 to 15,000	2,500	2,100	3,000
U	--	< 500	--	--	--
V	76	<7 to 500	56	66	46
Yb	4	<1 to 50	3	3	3
Y	29	<10 to 200	24	25	23
Zn	54	<25 to 2,000	44	51	36
Zr	240	<10 to 2,000	200	170	250
Total	30,100		2,990	23,858	19,263

\* Below detection limit.

### Pollutant accumulation in urban areas

The basic feature of urban areas is the extent of imperviousness of the land surface. Besides the hydrological significance of impervious areas (higher runoff, shorter duration of high pollutant concentrations, higher flood peaks), essentially all pollutants are flushed into the receiving waters whenever runoff takes place.

Pervious urban areas produce pollutant loadings of lesser magnitude provided that these areas are not steep and are well protected by lawns, shrubbery and trees. The amount of pollutants deposited on impervious areas depends on various factors and inputs as mentioned earlier. Pollutants transported from impervious areas can be carried by wind and traffic impact and they accumulate near the curb. Thus, it has been reported that street pollution accumulation rates are related to the unit length of curb (Fig. II-7; Table II-5). Reporting street refuse loadings/unit length of curb, instead of a more meaningful area loading, seems to be justified since it has been observed that almost 80% of refuse can be found within 15 cm and 97% within 1 m of the curb (17). The strong correlation existing between curb length density and degree of imperviousness of residential areas (Fig. II-8) can be utilized for simulation purposes.

A recently-developed regression formula (9) between curb length of urban areas and population density is:

$$CL = 311.67 - (266.07) (0.839)^{(2.48 PD)} \quad \text{Eq. (7)}$$

where

CL is curb length in m/ha

PD is population density, persons/ha

Refuse washed from streets by runoff contains many hazardous contaminants. Significant organic pollutants, toxic metals, pesticides and bacteria are associated commonly with the dust and dirt fraction (Tables II-6 and II-7). It should be noted that these values, though typical, are not uniform but represent averages from a wide range of refuse deposition and contamination from a limited number of municipalities which have been studied.

### Atmospheric pollutant deposition

Deposition of atmospheric pollutants occurs as dry or wet fallout. The deposition rates of particulate atmospheric pollutants in United States cities vary from 3.5 to >35 Tonnes/km<sup>2</sup>/month. Higher deposition rates can be expected in congested industrial areas or business districts while lower deposition rates are common in residential and rural suburban zones (Table II-8).

DUST FALLOUT FROM INDUSTRIAL  
AND STATIONARY FUEL COMBUSTION PROCESSES




Fig. II-7. Pollutant accumulation schematic model.

Table II-5. Street refuse accumulation

Land use	Solids accumulation, g/curb m/day	
	Chicago*	Eight U.S. cities**
Single family	10.4	48
Multiple family	34.2	66
Commercial	49.1	69
Industrial	68.4	127
Weighted average	22.3	

\*Taken from (9); data is for dust and dirt only.

\*\*Taken from (1); data is for total solids which contain  
75% dust and dirt.




Fig. II-8. Curb length-imperviousness relationship.

Table II-6. Pollutants associated with street refuse (1)

Pollutant	Concentration, ug/g total solids			
	Residential	Industrial	Commercial	Total
BOD <sub>5</sub> *	5,000	3,000	7,700	5,000
COD	33,800	59,000	31,500	--
Volatile solids	78,000	56,500	77,000	71,400
Total nitrogen	1,020	870	600	1,570
Nitrate-N	32	41	314	67
Phosphate-P	600	800	550	780
Total metals	2,040	1,150	1,900	--
Zn				460
Cu				140
Pb				410
Ni				36
Hg				52
Cr				78
p,p'-DDD, ng/g				48
p,p'-DDT, ng/g				43
Total coliforms, organisms/g				71x10 <sup>6</sup>
Fecal coliforms, organisms/g				40x10 <sup>6</sup>

\*Taken from (9).

Table II-7. Metal contamination of street refuse (19)

Contaminant	Concentration, $\mu\text{g/g}$ total solids			
	Residential	Industrial	Commercial	Total
Cd	3.45	2.83	3.92	2.82
Cr	186	208	241	183
Cu	95	55	126	101
Ni	22	59	59	31
Pb	1,468	1,339	3,924	1,324
Sr	23	134	151	177
Zn	397	283	506	338

Table II-8. Annual and monthly mean deposition rates of particulate material in Milwaukee County (20)

Land use	Annual deposition rate, Tonnes/km <sup>2</sup> /yr									
	1951	1957	1963	1965	1966	1967	1968	1969		
Agricultural and rural suburbs	58.4	64.3	85.2	102.1	114.5	129.5	98.5	80.4		
Residential	93.6	82.7	88.5	99.4	97.7	95.2	94.0	81.0		
Local business	152.4	113.2	124.4	102.5	109.0	121.9	123.6	96.5		
Commercial	191.3	200.0	153.7	173.8	153.7	190.4	169.6	146.5		
Industrial	342.8	235.1	172.4	189.6	174.1	180.0	177.1	170.4		

Monthly deposition rate (1951 to 1969), Tonnes/km <sup>2</sup> /mo											
Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec
9.85	10.4	12.9	14.1	14.5	12.8	10.5	10.6	10.6	10.2	9.71	8.09

### Wind erosion

The effect of wind erosion on surface particulate pollutant loadings seems to be significant only occasionally. Factors important in the assessment are: climate, soil characteristics, surface roughness, vegetative cover and length of the eroding surface (21). In urban areas the primary source of wind eroded materials are open, ungrassed areas and construction sites.

### Motor vehicles

Traffic can contribute significantly to pollutant deposition in urban areas. High amounts of some metals in storm water runoff are attributed to motor vehicle emissions and to the breakdown of road surface materials and vehicular parts. Motor vehicle usage can influence pollutant accumulation in urban areas and near high density traffic lanes by emission of pollutants, oil and gasoline spillage, mechanical impact of traffic, tire abrasion, etc. Therefore, in addition to traffic density, the pavement composition and conditions are significant in determining traffic impact on pollution. Streets paved entirely with asphalt have provided total solids loadings of about 80% higher than all-concrete streets (17). Streets where conditions were rated "fair to poor" were found to have total solids loadings ~2.5 times greater than those rated "good to excellent" (1).

### Litter deposition

Litter deposits in urban areas include solid wastes dropped from garbage collectors, animal and bird fecal droppings, fallen tree leaves, grass clippings, etc. The dust and dirt component of litter (material <3.5 mm) is regarded as having greatest pollution potential; although most of the litter is originally larger in size than dust and dirt, the mechanical fracture of litter increases the amount of dust and dirt. It has been reported that residential areas had greater amounts of street surface dust and dirt as population density increased, reflecting increased pedestrian and roadway traffic (9). It is also expected that the higher the population density, the greater the street deposition from garbage collections.

### Effect of vegetation

Leaf fall and grass clippings in urban areas contribute significantly to dust and dirt accumulation. For most of the year, the accumulation on impervious areas arises from erosion of soils from surrounding pervious areas, atmospheric pollution and litter accumulation and during the fall season, leaf fall increases the organic solids accumulated at the surface.

Heaney and Huber (22) estimated from the study of Carlisle et al. (23) that average leaf fall was 14 to 26 kg/tree/year. The area investigated was stocked with trees ranging in age from 40 to 120 years with a 90 to 95% closed canopy, and 155 trees/ha; species were mainly oak and birch. Typical values for leaf fall in Minnesota are ~380 Tonnes/km<sup>2</sup>/year in a forested area with ~420 trees/ha with 65% occurring during the fall season. Fallen leaves are 90 to 97% organic matter and contain about 0.04 to 0.28% P (24).

For loading simulations, values of leaf fall for various land uses were estimated (Table II-9). Organic and P contents of leaves were assumed to be 90 and 0.1%, respectively.

A detailed statistical evaluation of street litter accumulation is contained in Appendix II-A.

#### Pollutant washout

Not all pollutants accumulated during a period preceding a rainfall are washed off the impervious surface during the initial moments of the rain. The rate at which loose particulate matter is washed from street surfaces depends on three factors, namely, rainfall intensity, street surface characteristics and particle size (17). It can be expected that the amount of pollutants washed off generally will follow the equation:

$$PL = \frac{dL}{dt} = - K_p L \quad \text{Eq. (8)}$$

where

PL is pollutant washout rate  
 L is amount of pollutant present on the surface  
 $K_p$  is a coefficient depending on rain intensity and street surface characteristics

The coefficient,  $K_p$ , which was found to be independent of particle size in the range of 10 to 1000  $\mu\text{m}$  is approximated as follows:

$$K_p = E_u R \quad \text{Eq. (9)}$$

where

$E_u$  is urban washout coefficient  
 R is the surface runoff rate, cm/hr

Table II-9. Daily leaf fall

Land use	Leaf fall, Tonnes/km <sup>2</sup> /day	
	Spring-Summer	Fall
Forest	2.45	7.0
Parks	1.22	3.5
Low density residential	0.17	0.35
Medium density residential	0.08	0.18
High density residential, commercial and industrial	0.016	0.036

values close to  $1.81^{-1}$  have been reported for the washout coefficient  $A_s$  (25).

Not all litter is available for transport by surface runoff. Therefore sediment washout rate should be multiplied by an availability factor (25) as:

$$A_s = 0.57 + 0.5 R^{1.1} \quad \text{Eq. (10)}$$

It is obvious that a limit must be placed on the availability factor as runoff rate increases. A suggested value for the maximum  $A_s$  is 0.75, which implies that about 25% of urban litter is unavailable for transport.

### Street sweeping practices

Street sweeping is a common practice in American cities whereas in European cities streets are washed. Most of street sweeping is done mechanically either by brush or vacuum. Removal efficiencies with brush sweepers are shown in Table II-10; removal of deposited suspended solids is ~50% with one pass of a sweeper. Some pollutants are associated more with finer particle fractions (Table II-11). By cumulative multiplication of sweeping efficiency for each fraction and pollution concentrations on particles of the fraction, overall efficiency can be estimated (Table II-12), e.g., the efficiency of sweeping for P control would be 22% compared to 50% for total solids. Street washing is more effective for fine materials.

### Meteorological inputs

The climate of the Milwaukee area is influenced by the general storms which move eastward across the upper Ohio River valley and the Great Lakes region.

Annual precipitation is about 762 mm (30 in); two-thirds of which occurs during the growing season. Thunderstorms, which carry the highest erosion potential, occur less frequently and with less severity than in areas to the south and west. The maximum rainfall which occurred in a 24-hr period is 172 mm (5.76 in) in June 1917. As much as 20 mm (0.79 in) has fallen in 5 min, 28 mm (1.11 in) in 10 min, 34 mm (1.34 in) in 15 min, 42 mm (1.86 in) in 30 min, and 57 mm (2.25 in) in 1 hr.

The average yearly rainfall energy factor,  $R$ , for sediment loss estimation by the USLE assigned for the Milwaukee area is  $R = 125$  (2).

It has been realized that pollutant loadings shall be representative of an average season, i.e., they express loadings which would be a mathematical average over a long time period. In order to obtain such averages, at least 20 to 30 yr of data is necessary. In the absence of such a data base, as is almost always the case, water quality (loading) data time series can be generated by a properly calibrated and verified model using a measured meteorological time series as input. Hourly precipitation data for the

Table II-10. Pollutant distribution in various particle sizes (17)

Particle size, $\mu\text{m}$	Pollutant distribution, %				
	Total solids	Volatile solids	COD	TKN	$\text{PO}_4\text{-P}$
>2000	24.9	11.0	2.9	9.9	0
840-2400	7.6	17.4	4.5	11.6	0.9
246-840	24.6	12.0	13.0	20.0	6.9
104-246	27.8	16.1	12.4	20.2	6.4
43-104	9.7	17.9	45.0	19.6	29.6
<43	5.9	25.6	22.7	18.7	56.2

Table II-11. Interrelationship of sweeper efficiency and particle size (17)

Particle size, $\mu\text{m}$	Sweeper efficiency, %
>2000	79
840-2000	66
246-840	60
104-246	48
43-104	20
<43	50
Overall	18

Table II-12. Street sweeping removal efficiency of pollutants (17)

Pollutant	Removal efficiency, %
Total solids	50.0
Volatile solids	42.5
COD	31.0
TKN	43.9
$\text{PO}_4\text{-P}$	22.2

Milwaukee area are available and a 37 yr series covering 37 yr was prepared.

In an ideal case, the simulation period would cover an entire 37 yr of data, but with more complex models such simulation periods may prove to be prohibitively expensive requiring considerable computer time and storage capacity.

To avoid the expensive, long simulation runs, the 37 yr series of meteorological data was analyzed as to its distribution of seasonal wetness and erosion potential.

The wetness analysis utilized a simple summation of precipitation per calendar season; the seasonal erosion potential is based on the USLE R factor as expressed by Eq. (4). In analyzing the erosion potential, only rain events were counted, snowfall was omitted.

The probabilistic distributions of seasonal wetness and erosion potential are shown in Figs. II-9 and II-10. The arrows indicate the probabilistic expectancy of season from the monitoring period 1975-1977. It should be pointed out that the graphs are typical for the storm patterns in the Milwaukee area and should not be generalized to other areas.

Summaries of the final land data used for simulation are in Tables II-13 and II-14.




Fig. II-9. Seasonal cumulative frequency of precipitation.




Fig. II-10. Seasonal cumulative frequency of R factor .

Table II-13. Urban land use information

Category	Land use						
	Residential			Land use			
	Low density	Medium density	High density	Commerical	Industrial	Park and recreation	Developing
Housing, dwelling/ha	0.3 to 5	5 to 16	>16				
Curb, m/ha	95	270	300	300	300		
Impervious area, %	25	60	95	90	90	2.0	3.0
Impervious area not connected, %	90	55	10	10	10	90	90
Street litter accumulation, g/m/day	45	66	60	65	100		
Dust and dirt fallout, tonnes/km <sup>2</sup> /day							
Spring and summer	0.25	0.25	0.28	0.46	0.50	1.4**	0.5
Fall	0.6	0.5	0.3	0.48	0.5	3.5**	0.5
Sweeping frequency, days							
Well maintained	7	7	7	7	7	30	1000 <sup>+</sup>
Poorly maintained	1000 <sup>+</sup>	1000 <sup>+</sup>	1000 <sup>+</sup>	1000 <sup>+</sup>	1000 <sup>+</sup>	)	)
Sweeping efficiency, %							
Solids	50	50	50	50	50	50	50
PO <sub>4</sub> -P	22	22	22	22	22	22	22
Impervious area affected by sweeping, %	50	50	50	50	50	50	50
C factor for pervious area*	0.01	0.01	0.01	0.01	0.01	0.01	0.01

\*C is the cropping factor used in USLE.

\*\*Includes leaf fall and vegetation.

+Denotes the absence of maintenance.

Table II-14. Non-urban land use information

Category	Row crop	Land use			
		Feedlots	Pasture	Wetlands	Woodlands
Impervious area, %	1.0	1.0	1.0	1.0	1.0
Litter and atmospheric fallout, tonnes/km <sup>2</sup> /day					
Spring and summer	0.2	0.2	0.2	0.2	2.4
Fall	0.2	0.2	0.2	0.2	7.0
C factor*					
Spring	1.0	1.0	0.03	0.5	0.005
Summer and fall	0.08	1.0	0.03	0.2	0.005
P factor**	0.8	1.0	1.0	1.0	1.0
Soil	average	compacted; high organic matter and P contents	average	average; high water table	average

\*C is the cropping factor in USLE.

\*\*P is the conservation factor in USLE.

## RESULTS AND DISCUSSION

### Simulated Loadings

The simulation results for each land use and characteristic season produced loading diagrams which related loadings of pollutants (sediment, volatile suspended solids and phosphate-P) to the R-factor for mostly pervious areas and to atmospheric fallout for impervious areas. These loading diagrams are presented in Appendix II-B.

Loadings for urban areas were related to the degree of imperviousness and accumulation rates established for relatively clean areas (i.e., areas which are swept about once a week) and areas with on cleaning. The upper curves represent loadings from poorly-maintained areas based on a uniform daily rate of pollutant accumulation which decreases with prolonged dry periods similar to the rates reported (1,17). The loadings for urban land uses were plotted separately for impervious and pervious areas. It should be remembered that the loading from the impervious areas was estimated assuming an atmospheric fallout rate of 0.8 Tonnes/km<sup>2</sup>/day and curb litter loadings similar to those obtained by Sartor and Boyd (1) and Sartor et al. (17). If significantly different accumulation rates are anticipated the loadings from impervious areas should be adjusted accordingly to reflect the change in curb loading rate due to increased or decreased atmospheric fallout.

Since impervious urban areas were simulated for an average year and the loadings appear to have no correlation with rainfall intensity, the average loading values can be read directly from the diagram and values are presented in Table II-15. In order to obtain average loadings for pervious areas, the loading diagram related to the R-factor must be transformed to a probability distribution loading plot using the cumulative frequency chart of the R-factor as given in Fig. II-10. The area under the R-factor-probability curve can be graphically or numerically integrated according to the equation:

$$I = \int_0^1 L_i p_i dp \quad \text{Eq. (11)}$$

I is the average loading, kg/ha

$L_i$  is the loading function

$p_i$  is the assigned probability of  $L_i$  being less or equal.

It also should be noted that the loading diagrams in Appendix II-B reflect loadings from a 1 km<sup>2</sup> area under slope category B (2 to 6%) for the impervious urban areas and slope category C (6 to 12%) for pervious areas. To transform these values to other slopes and areal units, the loadings corresponding to pervious areas should be multiplied by slope or area correction factors presented in Figs. II-11, II-12 and II-13. It is clear

Table II-15. Simulated pollutant loadings\* for urban land uses under slope category B (2 to 6%) during an average year (1968)

Soils and maintenance	Imperv., %	Sediment, kg/ha				Volatile susp. solids, kg/ha				Pb, kg/ha							
		Winter	Spring	Summer	Fall	Winter	Spring	Summer	Fall	Winter	Spring	Summer	Fall				
Poor soils, poorly maintained area	25	24	300	450	150	2.0	19.0	22.0	**	0.016	0.44	1.10	0.34	0.035	0.29	0.25	0.24
	25	16	130	365	100	1.25	5.0	13.0	**	0.01	0.36	1.00	0.20	0.035	0.036	0.037	0.017
	25	24	225	240	130	2.0	15.0	13.0	**	0.016	0.15	0.12	0.12	0.23	0.29	0.25	0.24
	25	16	55	180	35	1.25	3.0	4.0	**	0.01	0.04	1.1	0.03	0.023	0.036	0.056	0.012
Poorly maintained area	60	221	900	1,100	600	17	70	80	98	0.14	1.25	1.36	0.98	0.32	1.31	1.13	0.90
	60	141	275	540	120	11	19	34	19	0.09	1.10	1.60	0.13	0.21	0.31	0.30	0.11
	95	294	2,090	2,040	1,700	22	180	158	498	0.20	1.62	1.44	1.50	0.43	2.40	2.8	2.30
	95	187	304	800	200	14	20	60	28	0.13	0.33	0.70	0.16	0.27	0.49	0.57	0.28
Poorly maintained area	90	264	1,950	1,920	1,720	16	121	115	287	0.11	1.00	1.50	1.00	1.00	3.16	7.38	6.13
	90	167	283	516	200	10	17	23	34	0.07	0.30	0.60	0.20	0.66	1.03	1.50	0.15
	90	403	2,970	2,770	2,600	29	259	203	520	0.21	2.00	2.40	2.18	0.54	4.25	3.71	3.48
	90	256	420	1,270	330	18	298	83	65	0.13	0.60	1.10	0.30	0.33	0.54	1.50	0.40

\*Simulated loadings were obtained assuming dust fallout rates of 0.8 tonnes/km<sup>2</sup>/day except for park and recreational areas where the value was increased to 1.4 in the Spring and to 3.5 tonnes/km<sup>2</sup>/day in the Fall because of the effect of leaf vegetation.

\*\*60 to 85% of the total sediment was in the form of vegetation.




Fig. II-11. Slope correction factor for sediment and phosphate loadings from pervious urban areas (use with Table II-15).




Fig. II-12. Loading multiplier for different slope categories (for use with Table II-16).




Fig. II-13. Relationship of the size of the area to sediment loading.

that erosion potential of soils in the slope category D (12 to 20%) is about 20 times greater than that for soils in slope category A (0 to 2%).

Table II-16 shows the average potential loading values for typical pervious land (non-urban) uses situated on the four hydrologic soil groups. The loadings for each land use, soil and season are long-term average simulation results.

It is seen from Tables II-15 and II-16 that developing urban, industrial, commercial and high density residential land uses with poor maintenance and street cleaning practices, produce the highest potential loadings in urban areas while low density residential and park and recreation land uses contribute the least. For non-urban land uses, livestock feedlots are expected to have the highest pollution potential and woodlands the lowest. However, simulated loadings for feedlots may be unrealistic and are not reported because of the impossibility of arriving at reasonable values for the soil erodibility factor, K, due to the unusually high organic matter content and unknown compactness of feedlot soils.

Differences between the pollution potentials for various land uses indicate that pollution control measures should be concentrated intensively on hazardous land uses; i.e., developing and high density residential areas, unprotected non-urban areas located on soils with low permeability and steep slopes and feedlots. Discussion of remedial measures are given in Appendix II-C.

#### Comparison of Measured Loadings with Estimates Obtained by the MEUL Method

One purpose of the Menomonee River pilot project was to establish loadings from various land use activities. Although at the conclusion of the research it can be stated that the loadings should be related to various causative factors such as imperviousness of the area, type and slope of the soils, vegetative factors etc., some of these factors may indeed be related to land use. For example, the imperviousness of the area which is one of the primary factors defining residential land uses can be correlated with housing density. However, it must be realized that great loading variations should be expected within one particular land use based upon soil type and slope category, atmospheric fallout and litter accumulation and type of activities taking place in the area. This is especially true for such land uses as low density residential where most of the loadings originate from pervious areas thereby involving soil type and slope as principal causative factors. Furthermore, commercial and industrial land categories seem to be too broadly-defined and need further subcategorization (e.g., type of industry or type of commercial activities, degree of imperviousness).

Another problem which can arise when comparing estimated and measured loadings is that each season has a different erosion potential. This is shown in Fig. II-10 where cumulative rainfall energy factors defined by the USLE were arranged on a probabilistic scale of seasons. More than one order of magnitude of sediment loss can be expected based on whether the season is dry or has a significant number of high intensity storms. The measured values

Table II-16. Simulated pollutant loadings for land uses on essentially pervious areas

Soil and slope*	Sediment, kg/ha			PO <sub>4</sub> -P			Sediment, kg/ha			PO <sub>4</sub> -P		
	Spring	Summer	Fall	Spring	Summer	Fall	Spring	Summer	Fall	Spring	Summer	Fall
<u>Park and Recreation--SC<sup>†</sup> = 0.01</u>												
BMA	18	23	17	0.02	0.03	0.02	25	54	21	0.02	0.05	0.02
BMB	44	64	26	0.04	0.07	0.03	102	178	47	0.10	0.17	0.05
BMC	120	186	82	0.12	0.10	0.07	330	543	216	0.33	0.54	0.22
HMA	30	52	26	0.04	0.08	0.03	60	142	48	0.09	0.21	0.07
HMB	94	160	46	0.14	0.24	0.06	252	466	107	0.36	0.68	0.16
HMC	275	477	174	0.41	0.72	0.25	795	1,420	492	1.19	2.12	0.73
OUA	55	64	30	0.09	0.13	0.05	134	206	60	0.23	0.37	0.11
OUB	172	235	55	0.30	0.42	0.09	487	690	135	0.87	1.22	0.24
OUC	501	692	217	0.80	1.25	0.38	1,470	2,060	620	2.65	3.71	1.11
ODD	1,290	1,770	599	2.31	3.19	1.07	3,830	5,300	1,770	6.89	9.53	3.18
ASA	61	115	31	0.17	0.35	0.08	152	330	62	0.41	1.03	0.19
ASB	184	340	57	0.55	1.05	0.15	522	1,000	140	1.60	3.11	0.43
ASC	532	1,010	225	1.63	3.11	0.68	1,560	3,000	645	4.85	9.30	1.99
<u>Woodland--SC = 0.005</u>												
BMA	<1	<1	<1	<0.001	<0.001	<0.001	26	45	4	0.03	0.05	<0.001
BMB	1.5	1.0	<1	0.0015	0.001	<0.001	97	144	12	0.10	0.14	0.01
BMC	14	35	9.4	0.014	0.035	0.010	**	**	**	**	**	**
HMA	<1	<1	<1	<0.001	<0.001	<0.001	69	124	11	0.10	0.19	0.02
HMB	3.3	2.2	<1	0.005	0.003	<0.001	256	395	34	0.38	0.59	0.05
HMC	28	80	19	0.041	0.012	0.027	**	**	**	**	**	**
OUA	<1	<1	<1	<0.001	<0.001	<0.001	119	248	19	0.21	0.45	0.03
OUB	8.3	6.2	<1	0.015	0.011	<0.001	441	655	58	0.79	1.18	0.11
OUC	85	150	32	0.153	0.270	0.059	**	**	**	**	**	**
ODD	1,400	1,300	2,850	2.52	2.34	0.52	**	**	**	**	**	**
ASA	<1	2.9	<1	<0.001	0.009	<0.001	140	350	25	0.43	1.09	0.08
ASB	7.1	32	2.1	0.022	0.098	0.007	519	1,090	80	1.61	3.37	0.25
ASC	94	334	50	0.28	1.35	0.16	**	**	**	**	**	**
<u>Row Crops--SC = 1.0 or 0.08</u>												
BMA	<10	<10	<10	<0.01	<0.01	<0.01	830	1,800	700	0.83	1.80	0.70
BMB	303	16	<10	0.30	0.02	<0.01	3,400	5,900	1,600	3.40	5.90	1.60
BMC	2,800	560	150	2.8	0.56	0.15	11,000	18,100	7,200	11.0	18.1	7.20
HMA	<10	<10	<10	<0.01	<0.01	<0.01	2,000	4,700	1,600	3.00	7.05	2.40
HMB	655	36	<10	0.98	0.05	<0.01	8,400	15,500	3,600	12.6	23.3	5.40
HMC	5,500	1,280	296	8.25	1.92	0.44	26,500	47,200	16,400	39.7	71.0	24.6
OUA	<10	10	<10	<0.01	0.02	<0.01	4,500	6,900	2,000	8.10	12.4	3.60
OUB	1,665	100	<10	3.00	0.18	<0.01	16,200	23,000	4,500	29.2	41.4	8.10
OUC	17,000	2,400	518	30.6	4.31	0.94	49,100	68,700	20,700	88.4	123	37.3
ODD	280,000	20,900	4,565	505	37.5	8.28	128,000	177,000	59,000	229		166
ASA	<10	46	<10	<0.01	0.14	<0.01	5,100	11,000	2,100	15.8	34.1	6.51
ASB	1,420	505	34	4.39	1.56	0.11	17,400	33,500	4,700	54.0	104	14.6
ASC	18,700	5,340	800	57.9	16.9	2.50	52,200	100,000	21,500	161	310	66.7
<u>Feedlots--SC = 1.0</u>												
BMA	936	1,490	452	1.82	2.97	0.90						
BMB	2,450	3,240	1,360	5.89	6.48	2.71						
BMC	7,200	8,750	5,430	14.4	17.4	10.9						
HMA	2,440	3,600	1,130	7.33	10.8	3.39						
HMB	6,390	7,860	3,395	19.2	23.6	10.2						
HMC	18,800	21,200	13,600	56.4	63.8	40.7						
OUA	8,200	18,200	3,000	29.5	65.5	10.8						
OUB	21,000	39,600	9,000	75.6	142	32.4						
OUC	61,400	107,000	36,000	221	385	129						
ODD	142,000	245,000	100,000	511	882	360						
ASA	3,380	8,700	1,380	21.0	52.1	8.53						
ASB	8,840	18,900	4,130	54.8	117	25.6						
ASC	26,000	51,200	16,500	161	317	102						

\*BM is Boyer ls, HM is Hochheim 1, OU is Ozaukee sil, and AS is Ashkum sil; A is 0 to 2%, B is 2 to 6%, C is 6 to 12% and D is 12 to 20% slope.

\*\*Not applicable.

+SC is the cropping factor used in USLE.

should be adjusted according to the R-factor for pervious areas to reflect the average meteorological conditions on which the MEUL method is based.

The following correction factors based on Fig. II-10 should be applied to sediment loadings from pervious areas.

<u>Season</u>	<u>Erosion Correction Factor</u>
Spring 1975	0.44
Summer 1975	4.00
Fall 1975	1.25
Spring 1976	0.31
Summer 1976	2.3
Fall 1976	5.0
Spring 1977	1.0
Summer 1977	0.66

The loading values must be further adjusted by the delivery ratio (DR) relating loadings at the watershed outlet to those potentially liberated from the source area. The DR is still an unknown quantity which includes such factors as sedimentation and resettling during overland and channel flow, flocculation and agglomeration of suspended particles and removal of pollutants by infiltration during overland flow. An inaccurate method of DR estimation relates DR to the areal size of the watershed as shown in Fig. II-14. Although the method is inaccurate it is as good as any other available. Another factor which must be included is type of drainage. Natural drainage systems with low or no curbs will yield low delivery ratios approximately proportional to the fraction of impervious (e.g., storm sewer) and pervious drainage ditches. Areas with no curbs may show loadings reduced as much as 50% or more as compared to typical urban landscapes of impervious areas (i.e., streets draining into impervious drainage gutters). The loading figures presented in this report are based on the assumption that most of the street pollutants will accumulate near the curb.

Tables II-17 and II-18 present a comparison of measured and estimated sediment and phosphate-P loadings for some major pilot subwatersheds and for areas in a predominantly single land use in the Menomonee River Watershed. In almost all cases the estimated values were higher than the measured ones, a fact partially attributable to assigning a DR-value. For most of the simulated land uses the DR (ratio of measured:estimated loadings) is within the ranges indicated in Fig. II-14. The measured loadings for the fall seasons were low and do not conform to estimated values. It should be noted that Fall 1975 and 1976 seasons were very dry with minimal runoff.

It can also be expected that DR for highly impervious areas will be higher than for largely pervious areas of the same size and DR will be higher in sewered than in unsewered areas with natural drainage ditches.

Simulated unit loadings agree fairly well with measured values under similar meteorological conditions and land use characteristics. An exception has been noted for livestock feedlots where it was impossible to arrive at reasonable values of the soil erodibility factor, K, due to unusually high organic content of feedlot soils and unknown degree of compactness. Available measured loading values from feedlots (28,29) deviate significantly from simulated ranges; however, more research is necessary to obtain more realistic data.




Fig. II-14. Sediment delivery ratio versus drainage area (% of eroded soil material transported to the downstream outlet of streams based upon their drainage area) (27).

Table II-17. Comparison of simulated and measured sediment and phosphate loadings in subwatersheds with mixed land uses (measured loadings are taken from (26))

Land Use	Area, %	Impervious areas, %	Sediment, kg/ha			PO <sub>4</sub> -P, kg/ha		
			Spring	Summer	Fall	Spring	Summer	Fall
<u>Donges Bay Rd. (463001), 2144 ha</u>								
Commercial	2.6		200	400	200	0.30	0.70	0.25
High density residential	0.05		400	800	60	0.60	0.80	0.70
Medium density residential	3.9		200	400	150	0.50	0.80	0.40
Low density residential	4.7		120	250	50	0.35	0.50	0.10
Row crops	74							
Contributing	32		1,655	100	10	3.0	0.18	0.00
Pasture A	5		134	206	60	0.23	0.37	0.11
Pasture B	5		487	690	135	0.87	1.22	0.24
Wetlands	2.3		119	248	18	0.21	0.45	0.03
Feedlots	0.5		2,100	4,525	750*	5.90	12.89	2.0
Developing	1.6		2,800	4,150	1,200*	5.67	7.45	2.5
Estimated mean			597	212	50	1.18	0.40	0.09
Measured, arithmetic mean			304	39		0.61	0.07	
weighted mean			107	62		0.20	0.06	
Delivery ratio, weighted			0.18	0.29		0.17	0.15	
<u>Noyes Creek** (413011), 552 ha</u>								
Industrial	1.8	60	880(80)***	1,020(220)	460(60)	0.70	1.1	0.30
Commercial	35	60	700(100)	650(150)	250(50)	0.50	0.60	0.16
High density residential	3.8	70	730(130)	820(170)	350(50)	0.60	0.80	0.16
Medium density residential	15.8	40	260(160)	470(270)	140(60)	0.45	0.60	0.15
Low density residential	14.6	10	180(160)	290(270)	70(60)	0.30	0.45	0.12
Park and recreation A	23	2	55	64	30	0.09	0.13	0.09
Woodlands A	-	-	-	-	-	-	-	-
Developing A	2.7	2	3,000	6,600	1,260*	4.1	6.2	3.6
Landfill A	2.7	2	3,000	6,600	1,260*	4.1	6.2	3.6
Water	0.3							
Estimated mean		35	547	762	155	0.56	0.78	0.32
Measured, arithmetic mean			840	389	136++	0.61	0.36	0.01
weighted mean			566	566	153			
Delivery ratio, weighted			1.0	0.74	0.49			
<u>Honey Creek (413006), 2,803 ha</u>								
Industrial	0.9		855(55)	564(64)	460(60)			
Commercial	27.9		655(55)	544(64)	250(50)			
High density residential	3.3		655(55)	714(64)	350(50)			
Medium density residential	24.2		255(55)	264(64)	115(35)			
Low density residential	15.6		75(55)	84(64)	45(45)			
Developing A	1.8		3,500	7,000	1,200			
Row crops	0.07		-	-	-			
Parks and recreation A	18.6		55	64	30			
Woodlands	0.6		-	-	-			
Wetland	0.3		-	-	-			
Landfill	0.5		2,500	5,500	1,050**			
Estimated mean			368	425	258			
Measured, arithmetic mean			417	225	28			
weighted mean			294	287	41			
Delivery ratio, weighted			0.80	0.66	0.16			
<u>Schoonmaker Creek+++ (413010), 179 ha</u>								
Commercial	26.6	90	350(50)	500(50)	190(10)			
High density residential	0.5	90	350(50)	800(50)	210(30)			
Medium density residential	39.1	60	200(50)	600(200)	160(60)			
Low density residential	27.2	25	200(170)	280(200)	75(60)			
Developing A	3.0	1.6	1,500	2,300	660*			
Parks and recreation	9.0	5.0	27	32	15*			
Estimated mean		54	277	531	120			
Measured, arithmetic mean			157	147	33			
weighted mean			120	210	45			
Delivery ratio			0.43	0.40	0.38			

\*Corrected for the area used.

\*\*No cleaning in spring, medium maintenance in summer and fall.

\*\*\* ( ) amount contributed by pervious areas.

+Assume that 50% originated from pervious areas.

++Data for Fall 1976 excluded due to unusually dry weather.

+++Assume good cleaning.

Table II-18. Comparison of simulated and measured sediment and phosphate loadings in predominantly single land use areas (measured loadings are taken from (26))

Type of loading	Sediment, kg/ha		PO <sub>4</sub> -P, kg/ha	
	Spring	Summer	Spring	Summer
				Fall
<u>Timmerman Airport (413614):</u>				
140 ha, 1% mean slope, 18% impervious, commercial				
Estimated mean	36	55	15	0.06
Measured, arithmetic mean	16	68	4.2	0.10
weighted mean	16	55	6	0.09
Delivery ratio	0.44	1.0	0.40	0.05
				0.03
<u>Brookfield Square (6830089):</u>				
61 ha, 2% mean slope, 50.4% impervious, commercial				
Estimated mean	200	310	120	0.3
Measured, arithmetic mean	350	136	5	0.3
weighted mean	350	180		0.26
				0.16
				0.1
				0.02
<u>Stadium Interchange (413615):</u>				
64 ha, 2% mean slope, 44.6% impervious, transportation				
Estimated mean	250	450	100	0.42
Measured, arithmetic mean	230	353	28	0.60
				0.32
				0.04
				0.15
<u>Allis Chalmers (413616):</u>				
49 ha, 89.9% impervious, industrial				
Estimated mean	1,200	1,600	1,600	0.9
Measured, arithmetic mean	79	913	--	0.45
				1.3
				2.38
				0.5
				0.08

## REFERENCES-II

1. Sartor, J. D. and G. B. Boyd. Water Pollution Aspects of Street Surface Contaminants. U.S. Environmental Protection Agency Report No. EPA-R2-72-081, Washington, D.C., 1972.
2. Wischmeier, W. H. and D. D. Smith. Predicting Rainfall-Erosion Losses from Cropland East of the Rocky Mountains. U.S. Dept. of Agriculture Handbook 282. Washington, D.C., 1965. 47 pp.
3. Wischmeier, W. H., C. B. Johnson and B. V. Cross. A Soil Erodibility Nomograph for Farmland and Construction Sites. J. Soil and Water Conserv. 26(5):189-193, 1971.
4. Midwest Research Institute. Loading Functions for Assessment of Water Pollution from Non-point Sources. U.S. Environmental Protection Agency Report No. EPA-600/2-76/151, Washington, D.C., 1976.
5. Novotny, V., M. A. Chin and H. Tran. Description and Calibration of a Pollutant Loading Model-LANDRUN. Part I: Description of the Model. Final Report of the Menomonee River Pilot Watershed Study, Vol. 4, U.S. Environmental Protection Agency, 1979.
6. Novotny, V., H. Tran, G. Simsiman and G. Chesters. Mathematical Modelling of Land Runoff Contaminated by Phosphorus. J. Water Pollution Control Fed. 50(1):101-112, 1978.
7. Novotny, V., M. A. Chin and H. Tran. Description and Calibration of a Pollutant Loading Model-LANDRUN. Part II: Calibration and Verification of the Model. Final Report of the Menomonee River Pilot Watershed Study, Vol. 4, U.S. Environmental Protection Agency, 1979.
8. Walesh, S. G. Land Use, Population and Physical Characteristics of the Menomonee River Watershed. Part I: Land Data Management System. Final Report of the Menomonee River Pilot Watershed Study, Vol. 2, U.S. Environmental Protection Agency, 1979.
9. American Public Works Association. Water Pollution Aspect of Urban Runoff. Water Pollution Control Research Journal WP-20-15, Washington, D.C., 1969.
10. Hiemstra, L. Frequencies of Runoff for Small Basins. Ph.D. Thesis, Colorado State University, Fort Collins, Colorado, 1968. 151 pp.
11. Simsiman, G. V., J. Goodrich-Mahoney, G. Chesters and R. Bannerman. Land Use, Population and Physical Characteristics of the Menomonee River Watershed. Part III: Description of the Watershed. Final Report of the Menomonee River Pilot Watershed Study, Vol. 2, U.S. Environmental Protection Agency, 1979.

12. Hydrocomp International. Hydrocomp Simulation Programming Operation Manual. Hydrocomp International, Palo Alto, California, 1972.
13. Horn, M. E. Estimating Soil Permeability Rates. J. Irrigation and Drainage Div. Proc., Amer. Soc. Civil Engineers 97(IR2):263-274, 1971.
14. Bouma, J., W. A. Ziebell, W. G. Walker, D. G. Olcott, E. McCoy and F. D. Hole. Soil Absorption of Septic Tank Effluents. University of Wisconsin Extension, Geological and Natural History Survey Information Circular No. 20, Madison, Wisconsin, 1972.
15. Brandt, G. H., E. S. Conyers, M. B. Ettinger, F. J. Lowes, J. W. Mighton and J. W. Pollack. An Economic Analysis of Erosion and Sediment Control Methods for Watersheds Undergoing Urbanization. Final Report, OWRR Contract No. 14-31-001-3392, Dow Chemical Co., Midland, Michigan, 1972.
16. Shacklette, H. T., J. C. Hamilton, J. G. Boernagen and J. M. Bowles. Elemental Composition of Surficial Materials in the Conterminous United States. U.S. Geological Survey Proc. Paper 574-P, Washington, D.C., 1971.
17. Sartor, J. D., G. B. Boyd and F. J. Agardy. Water Pollution Aspects of Street Surface Contaminants. J. Water Pollution Control Fed. 46(3):458-467, 1974.
18. Graham, D. H., L. S. Costello and H. J. Mallon. Estimation of Imperviousness and Specific Curb Length for Forecasting Storm Quality and Quantity. J. Water Pollution Control Fed. 46(4):717-725, 1974.
19. Pitt, R. and G. Amy. Toxic Material Analysis of Street Surface Contaminants. U.S. Environmental Protection Agency Rep. No. EPA-R2-73-283, Washington, D.C., 1973.
20. Milwaukee County Department of Air Pollution. Ambient Air Quality (Particulates and Sulfur Dioxides) in Milwaukee County. Milwaukee County Department of Air Pollution, Milwaukee, Wisconsin, 1970.
21. Beaseley, R. B. Erosion and Sediment Pollution Control. The Iowa State University Press, Ames, Iowa, 1972.
22. Heaney, J. P. and W. C. Huber. Storm Water Management Model: Refinements, Testing and Decision-making. Department of Environmental Engineering Sciences, University of Florida, Gainesville, Florida, 1973.
23. Carlisle, A. A., H. F. Brown and E. J. White. Litter Fall Leaf Production and the Effects of Defoliation by Tortrix viridana in a Sissile Oak (Quercus petraea). Woodland J. Ecology 54:65-98, 1966.
24. Lutz, H. J. and R. I. Chandler. Forest Soils. John Wiley and Sons, New York, N.Y., 1976.
25. U.S. Army Corps of Engineers. Urban Storm Water Runoff Model STORM. The Hydrologic Engineering Center, U.S. Army Corps of Engineers, Davis, California, 1975.

26. Konrad, J. G. and G. Chesters. Menomonee River Pilot Watershed Study; Summary Pilot Watershed Report. Submitted to PLUARG Task Group C (U.S.), Activity 2. Windsor, Ontario, May 1978. 77 pp.
27. Roehl, J. W. Sediment Source Areas, Delivery Ratios and Influencing Morphological Factors. J.A.S.H. Commission on Land Erosion Publ. No. 59, 1962.
28. Daniel, T. C., W. Wendt and P. E. McGuire. Pollutant Loadings from Selected Rural Land Uses. Trans. Amer. Soc. Ag. Eng. (submitted for publication), 1979.
29. Coote, D. R. and F. R. Hore. Pollution Potential of Cattle Feedlots and Manure Storages in the Canadian Great Lakes Basin. Final Report Agricultural Watershed Studies Project 21. Submitted to PLUARG, Windsor, Ontario, 1978.

## APPENDIX II-A

### DETAILED STATISTICAL EVALUATION OF STREET LITTER ACCUMULATION

It has been realized that a simple unit loading value may not be representative of the surface pollution accumulation process. Instead, a mass balance model can be developed which may better represent the dynamic character of the street refuse accumulation. The model is based on the following simple mass balance equation (see Fig. II-7 for more detail):

$$\frac{dl}{dt} = L_D - L_R \quad \text{Eq. (A-1)}$$

$L$  is the pollutant accumulation on the surface, g/curb m/day

$L_D$  is the pollutant deposition rate, g/curb m/day

$L_R$  is the pollutant removal rate from the surface, g/curb m/day

The simple mass balance equation presented above can be expanded by identifying the significant factors which affect deposition and removal from street surfaces. The primary sources can be related to fallout of atmospheric pollutants, motor vehicle usage and deposition of street litter.

Traffic can contribute significantly to pollutant deposition in urban areas. Large amounts of toxic metals in storm water runoff are often attributed to motor vehicle emissions and to the breakdown of road surface materials and vehicle parts.

The variables affecting the pollutant deposition rate on impervious urban areas can be combined to yield the following equation:

$$L_D = (ATFL) (SW/2) + A_1 A (SW/2) (POA) + A_2 (RD) + A_3 (TD) (RCC)$$

Eq. (A-2)

where

ATFL is a coefficient reflecting deposition from stationary combustion processes and atmospheric fallout, g/ha/day

SW is the street width, m

$A_1$  is a coefficient reflecting the effect of open areas on pollutant deposition

POA is % open area in the vicinity of the site

$A_2$  is a coefficient reflecting the effect of residential density on pollutant accumulation

RD is the residential density, dwelling units/ha

$A_3$  is a coefficient reflecting the effect of traffic on pollutant accumulation  
 TD is traffic density, thousand axles/day  
 RCC is road composition and conditions which is a value based on scale determined from regression analysis

At the same time that pollutants are being deposited on the surface they are being removed. Factors which should be investigated as affecting the removal rate include wind speed, traffic speed, and curb and average height of buildings. The equation for street surface refuse removal can be formulated as:

$$L_R = A_4 [f_1(H) f_2(WS, TS)] L \quad \text{Eq. (A-3)}$$

where

$A_4$  is a coefficient reflecting the rate of pollutant removal due to the combined effect of wind and traffic speed  
 H is curb height, cm  
 WS is average wind speed, km/hr  
 TS is average traffic speed, km/hr

The function  $f_1(H)$ , describes the effect of curb height on pollutant removal and can be modeled as:

$$f_1(H) = e^{-\beta H} \quad \text{Eq. (A-4)}$$

where  $\beta$  is a statistical coefficient.

The above model was applied to a set of field data. Since the Menomonee River Watershed data do not yet provide a representative data sample, the data sample was supplemented by field measurements of street refuse accumulation in the Washington, D.C. area (A-1).

The solution to Eq. 12 will yield the following formula:

$$L = \frac{A}{B} (1 - e^{-Bt}) + C \quad \text{Eq. (A-5)}$$

where

t is time from last street cleaning or rain  
 A and B are variables determined for each constituent  
 C is a constant

The Washington, D.C. data (A-1), contain about 73 measurements on 7 different sites. Although the number of sites is probably too low to provide a sufficient spread of independent variables the statistical analysis did provide some answers as to the significance of the variables involved.

The best fit equations for four typical constituents, i.e., which were statistically significant are as follows:

Dust and dirt suspended solids -

$$DDSS = \frac{A}{B}(1 - e^{-Bt}) + C \quad \text{Eq. (A-6)}$$

$$A = ATFL\left(\frac{SW}{2}\right) - 5.02(RD) - 6.29(POA) + 1.15(TD)$$

$$B = 0.0116e^{-0.088H} (TS + WS)$$

$$C = 0.0$$

Multiple correlation coefficient  $R = 0.86$

Similarly:

Dust and dirt chemical oxygen demand -

$$DDCOD = \frac{A}{B}(1 - e^{-Bt}) + C \quad \text{Eq. (A-7)}$$

$$A = 2.60\left(\frac{SW}{2}\right) - 0.28(RD) - 0.51(POA) + 0.52(TD)$$

$$B = 0.142e^{-0.98H} (TS + WS)$$

$$C = 0$$

Multiple correlation coefficient  $R = 0.71$

Dust and dirt volatile suspended solids -

$$DDVSS = \frac{A_1}{B_1}(1 - e^{-B_1 t}) - \frac{A_2}{B_2}(1 - e^{-B_2 t}) + \frac{A_3}{B_3}(1 - e^{-B_3 t}) + C \quad \text{Eq. (A-8)}$$

$$A_1 = 1.46\left(\frac{SW}{2}\right)$$

$$B_1 = 0.024 e^{-0.05H} (TS + WS)$$

$$A_2 = 0.25(RD) + 0.31(POA)$$

$$B_2 = 0.048 e^{-0.05H} (TS + WS)$$

$$A_3 = 0.069(TD)$$

$$B_3 = 0.105 e^{-0.05H} (TS + WS)$$

$$C = 0$$

Multiple correlation coefficient  $R = 0.65$

Dust and dirt lead -

$$DD \text{ Lead} = \frac{A_1}{B_1}(1 - e^{-B_1 t}) - \frac{A_2}{B_2}(1 - e^{-B_2 t}) + \frac{A_3}{B_3}(1 - e^{-B_3 t}) + C$$

$$A_1 = 0.131 \frac{SW}{I}$$

$$B_1 = 0.036 e^{-0.03H} (TS + WS)$$

$$A_2 = 0.027(RD)$$

$$B_2 = 0.026 e^{-0.03H} (TS + WS)$$

$$A_3 = 0.013 (TD)$$

$$B_3 = 0.053 e^{-0.03H} (TS + WS)$$

$$C = -0.825$$

Multiple correlation coefficient  $R = 0.80$

Table II-A-1 lists the partial correlation coefficients for the above variables. From the table it can be seen that in all four cases the overall functional relationship is at a significant level. The dependent variables which have the most significant effect on the independent variables vary with the character of the variables. As might be expected, traffic density may have a very significant effect on the magnitude of the accumulation of dust and dirt constituents, particularly lead. On initial inspection it may seem surprising that the regression coefficients have a negative value for POA and RD. One would expect that quantity of street refuse would increase with increasing housing density or open area (i.e., area without significant vegetation). On the other hand, just the opposite can be true if one realizes that a significant portion of street refuse originates from vegetation--lawns, trees and shrubs--which are inversely proportional to housing density (RD) or open area (POA). Thus, it seems that trees and vegetation near impervious areas may contribute significantly (especially during the fall season) to pollutant loading.

The above equations represent the best combination of variables which

Table II-A-1. Partial and multiple correlation coefficients between dust and dirt pollutants and factors affecting their accumulation

Independent variable	Partial r of dependent variable*			
	SW	RD	POA	TD
Suspended solids	0.28	-0.30	-0.34	0.34
COD	0.26	-0.16	-0.27	0.15
Volatile suspended solids	0.13	-0.23	-0.20	0.26
Lead	0.067	-0.113	0.0018	0.40
				0.86
				0.71
				0.65
				0.80

\*SW is street width, RD is residential density, POA is percent of open area, TD is traffic density, H is curb height, TS is traffic speed and WS is wind speed.

were investigated. Other combinations which yielded lower statistical correlations included the effect of traffic speed on pollutant accumulation (as in the form of  $TD \times TS$  or  $TD \times TS^2$ ), excluding some insignificant variables and others.

Equations (A-6) to (A-9) indicate that as the quantity of deposited pollutants increases with prolonged dry periods, more particles can be removed by wind and traffic and the actual differential deposition rate decreases. This fact was also observed by Sartor et al. (A-2) and is documented in Fig. II-A-1.




Fig. II-A-1. Effect of dry periods on the quantity of street litters.

#### REFERENCES-APPENDIX II-A

- A-1. Shaheen, D. Contribution of Roadway Usage to Water Pollution. U.S. Environmental Protection Agency Report No. EPA 600/2-75-004, Washington, D.C., 1975.
- A-2. Sartor, J. D. and G. B. Boyd. Water Pollution Aspects of Street Surface Contaminants. U.S. Environmental Protection Agency Report No. EPA-R2-72-081, Washington, D.C., 1972.
- A-3. Sartor, J. D., G. B. Boyd and F. J. Agardy. Water Pollution Aspects of Street Surface Contaminants. J. Water Pollution Control Fed. 46(3):458-467, 1974.

## APPENDIX II-B

### SIMULATED LOADING DIAGRAMS

Loadings for impervious urban land uses (Figs. II-B-1 to II-B-6) reflect values from areas under slope category B (2 to 6%). Average loadings can be read directly from the loading diagrams. Loading diagrams for volatile suspended solids and Pb are available but are not presented in this report.

Loadings from pervious areas shown in Figs. II-B-7 to II-B-16 reflect values from a 1 km<sup>2</sup> area under soil slope category C (6 to 12%). To obtain average loadings, loading diagram related to the R-factor must be transformed to a probability distribution loading plot using the cumulative frequency chart in Fig. II-10. The cropping factor, SC, on all loading diagrams is 0.01. To obtain loadings for each land use with SC other than 0.01 multiply the values from the graph by 100 and SC factors in Table II-16. To transform loadings to other slopes and areal units, values should be multiplied by slope or area correction factors presented in Figs. II-11 to II-13. Loading diagrams for phosphate-P are available but are not given in this report.




Fig. II-B-1. Sediment loadings from residential areas.




Fig. II-B-2. Sediment loadings from commercial areas.




Fig. II-B-3. Sediment loadings from industrial areas.




Fig. II-B-4. Phosphate-P loadings from residential areas.




Fig. II-B-5. Phosphate-P loadings from commercial areas.




Fig. II-B-6. Phosphate-P loadings from industrial areas.




Fig. II-B-7. Relationship of sediment loadings and R-factor in row crop-woodland areas.




Fig. II-B-8. Probability distribution of sediment loadings in row crop-woodland areas.




Fig. II-B-9. Relationship of sediment loadings and R-factor in feedlots.




Fig. II-B-10. Probability distribution of sediment loadings in feedlots.




Fig. II-B-11. Relationship of sediment loadings and R-factor in pastures.




Fig. II-B-12. Probability distribution of sediment loadings in pastures.




Fig. II-B-13. Relationship of sediment loadings and R-factor in wetlands.




Fig. II-B-14. Probability distribution of sediment loadings in wetlands.

## APPENDIX II-C

### REMEDIAL MEASURES AND NON-POINT POLLUTION CONTROL

Remedial measures can be categorized using a macro or micro scale. The former may result in better land use practices and zoning, legislation limiting marketing certain potentially-hazardous pollutants or better farming practices. These measures are usually long-term remedies and take longer periods of time to implement. Micro-scale remedial measures include better management and control of existing land uses. In urban settings, limiting the non-point pollution can take place either at the source (maintenance and cleaning) or at the area outlet (storage and treatment). In non-urban settings, the control is limited to better farming practices and erosion control.

A literature review by the Wisconsin Department of Natural Resources (C-1) compiled and presented possible management practices to control water quality of urban runoff. The control techniques mentioned included:

#### Source control

- Increased infiltration
- Retention of runoff
- Reduction of erosion
- Reduction of contaminant deposition
- Street sweeping

#### Outfall treatment and collection control

- Reduction in channel erosion
- Infiltration and sedimentation basins
- Storage basins to equalize flow
- Physical, chemical and biological treatment

The study concluded that in low density urbanizing areas the quality of stormwater runoff is most efficiently handled by systems incorporated into the development stage such as zoning, control of developing areas, increased perviousness and optimal design of stormwater conveyance systems. In high density, developed areas, runoff is handled by good street cleaning practices and through one of a series of treatment methods subsequent to collection.

Source control of urban-related pollution, which reduces on-site pollutant generation or prevents pollutants from leaving the small drainage areas at which a disturbance occurs, is less expensive and more effective than remedial measures once the pollutants leave the site and move downstream. Control of runoff pollution by collection systems is more expensive than on-site source control but less costly than treatment at the outfall.

Treatment of urban runoff may be feasible only for highly developed areas where source control and collection control are not possible.

The difference between frequently cleaned and poorly maintained (no cleaning) urban areas can be seen in Table II-15. Although Table II-15 represents simulated pollutant loadings the importance of street cleaning is evident. Figures II-C-1 and II-C-2 show the simulated effect of street cleaning frequency and efficiency on sediment loadings. The average efficiency of street sweepers for the suspended particulate materials (dust) is about 50% (C-2) but due to the fact that P is associated mostly with the fine fractions of street dust and dirt the expected efficiency of P removal is only about 22%. The effects of street sweeping are much higher during a dry season and when a linear accumulation of street pollutants is assumed.

Other remedial measures include increasing pervious areas within urban settings and reducing impervious areas directly connected to surface runoff channels. Installing pervious parking areas, introducing seepage beds and basins, and disconnecting roof drains from storm sewers can be listed as possible examples. These measures can be ineffective if the area is located on impermeable soils or on steep slopes since the conveyance of runoff from the pervious area would create more erosion and pollutant washout from these soils. Pervious areas should not be left bare. Permanent or temporal surface protection, such as lawns, temporary seeding, or application of mulch or chemicals should be practiced to control erosion and pollutant washout.

Street curbs and highway barriers represent obstacles at which surface suspended pollutants (dust) can accumulate. Studies by Sartor et al. (C-2) and Sartor and Boyd (C-3) indicated that 90% of surface suspended pollutants are located within 1 m of the curb. One would suspect that the curb height can--to some degree--affect the amount of pollutants accumulated. To provide some insight into the validity of this hypothesis, a sensitivity analysis of Eq. (A-6) was performed (Fig. II-C-3). Thus, lower curb heights may result in less pollutant accumulation near the curb since some of the deposits can be removed by wind and traffic and deposited in adjacent pervious areas where they are less available for transport. Obviously, lowering curb sizes would be effective only if the streets are surrounded by pervious areas.




Fig. II-C-1. Effect of sweeping interval on pollutant loadings (sweeping efficiency = 50%).




Fig. II-C-2. Effect of sweeping efficiency on pollutant loadings (sweeping interval = 7 days)




Fig. II-C-3. Effect of curb (median barrier) height on street litter accumulation.

#### REFERENCES-APPENDIX II-C

- C-1. Oberts, G. L. Water Quality Effects of Potential Urban Best Management Practices. Dept. of Natural Resources Tech. Bull. No. 97, Madison, Wisconsin, 1977.
- C-2. Sartor, J. D., G. B. Boyd and F. J. Agardy. Water Pollution Aspects of Street Surface Contaminants. J. Water Pollution Control Fed. 46(3):458-467, 1974.
- C-3. Sartor, J. D. and G. B. Boyd. Water Pollution Aspects of Street Surface Contaminants. U.S. Environmental Protection Agency Report No. EPA-R2-72-081, Washington, D.C., 1972.

PART III

A SIMPLE, EMPIRICAL MODEL FOR PREDICTING  
RUNOFF QUALITY FROM SMALL WATERSHEDS

by

D. S. CHERKAUER

## ABSTRACT

A single model for calculating the time distribution of suspended solid loads in a runoff event is presented. Instantaneous solids concentrations are related to discharge per unit drainage area, rainfall intensity, antecedent dry period, and stage of urban development. A set of empirical curves developed from observations on small watersheds within the Menomonee and Milwaukee River watersheds allows calculation of suspended solids concentrations for any percentage of urbanization. These concentrations can then be combined with discharges predicted by some standard means to provide loading. The model has been tested in watersheds from a variety of climatic, geologic and topographic regions. For storms within the calibration limits of the model, it predicts loads with reasonable accuracy.

## CONTENTS - PART III

Title Page . . . . .	III-i
Abstract . . . . .	III-ii
Contents . . . . .	III-iii
Figures . . . . .	III-iv
Tables . . . . .	III-vi
III-1. Introduction . . . . .	III-1
III-2. Conclusions . . . . .	III-2
III-3. Methods and Procedures . . . . .	III-6
III-4. Results and Discussion . . . . .	III-9
References . . . . .	III-22

## FIGURES

<u>Number</u>		<u>Page</u>
III-1	Regression coefficients for model for total suspended solids . . . . .	III-5
III-2	Comparison of observed and predicted suspended solids concentrations for Brown Deer Creek on 6/8/77. Total precipitation was 1.32 cm, the antecedent dry period was 3 days and rainfall intensity was 0.25 cm/hr . . . . .	III-10
III-3	Comparison of observed and predicted suspended solids loads for Brown Deer Creek on 6/8/77. Total precipitation was 1.32 cm, antecedent dry period was 3 days and rainfall intensity was 0.25 cm/hr. . . . .	III-11
III-4	Comparison of observed and predicted suspended solids loads for Underwood Creek on 4/23/76. Total precipitation is 5.4 cm, antecedent dry period was 1 day and rainfall intensity was 0.30 cm/hr . . . . .	III-12
III-5	Comparison of observed and predicted suspended solids loads for Event 32 at Third Fork Creek, Durham, North Carolina. Total precipitation was 2 cm, the antecedent dry period was 2.5 days and rainfall intensity was 0.48 cm/hr . . . . .	III-14
III-6	Comparison of observed and predicted suspended solids loads for Event 29, at Third Fork Creek, Durham, North Carolina. Total precipitation was 6 cm, the antecedent dry period was 5 days and rainfall intensity was 0.86 cm/hr . . . . .	III-15
III-7	Comparison of observed and predicted suspended solids loads for Event 27 at Third Fork Creek, Durham, North Carolina. Total precipitation was 3.8 cm, the antecedent dry period was 11.3 days and rainfall intensity was 1.14 cm/hr . . . . .	III-16
III-8	Comparison of observed and predicted suspended solids loads for Bloody Run, Cincinnati, Ohio on 9/25/70. Total precipitation was 1.7 cm, antecedent dry period was 1 day and rain fall intensity was 0.73 cm/hr . . . . .	III-17

<u>Number</u>		<u>Page</u>
III-9	Comparison of observed and predicted suspended solids loads for Bloody Run, Cincinnati, Ohio on 10/20/70. Total precipitation was 2.3 cm, antecedent dry period was 6 days and rainfall intensity was 0.45 cm/hr . . . . .	III-18
III-10	Comparison of observed and predicted suspended solids loads for Baker Street Basin, San Francisco, California on 11/5/69. Loads have been predicted using the general model (x) and also a modified model which reduces the importance of antecedent conditions (o). Total precipitation was 1.6 cm, antecedent dry period was 19 days and rainfall intensity was 0.33 cm/hr . . . . .	III-19
III-11	Comparison of observed and predicted suspended solids concentrations and flow for Baker Street Basin, San Francisco, California. Total rainfall was 1.6 cm, antecedent dry period was 19 days and rainfall intensity was 0.33 cm/hr . . . . .	III-20

## TABLES

<u>Number</u>		<u>Page</u>
III-1	Comparisons of predictive capabilities of model for suspended solids loads . . . . .	III-3
III-2	Coefficients for final regression equations for various degrees of urbanization . . . . .	III-8

### III-1. INTRODUCTION

One of the objectives of the Menomonee River Pilot Watershed Project was to synthesize the collected data into a form useful to planners and others concerned with the effects of runoff quality from future urban development. Models, calibrated with data gathered from the Menomonee River Study can be extrapolated to project the effects of development. The LANDRUN digital model represents the primary modeling effort and like most available digital runoff models for calibration, it requires detailed input of the hydraulics of the Watershed and its channels. When precise inputs can be provided, the model produces precise results. However, in many urban areas in the Great Lakes Watershed, either the necessary input data is not available or time and budget constraints do not allow development and/or calibration of a digital model.

With these concerns in mind, a methodology is presented for development of a simple empirical model for predicting runoff quality from small watersheds. This model is less precise than LANDRUN in its final product, but it is one which can be calibrated for a particular urban area with data which is easily obtainable.

### III-2. CONCLUSIONS

Table III-1 summarizes the investigation and provides a comparison of the observed and predicted suspended solids loads for each event discussed. After calibration in an area, the model is able to predict suspended solids loads to about  $\pm 20\%$ . It cannot be used on watersheds (such as Underwood Creek) which are substantially larger than those used for calibration without introducing a substantial error (Table III-1). In addition, the model is valid only for the range of rainfall intensities and totals for which it is calibrated. It would probably be advisable to calibrate it locally for small, intermediate and large storms, but insufficient data has been analyzed to determine the value of multiple calibrations.

Extrapolation of the model to areas of vastly different climatic, geologic and topographic conditions produced surprisingly good results. Admittedly, predicted solids loads were generally substantially different from the observed ones (error range of 8 to 80%, Table III-1). However, within the constraints of its calibration, the model was always within the proper order of magnitude for watersheds and events that produced from 1,100 to 46,000 kg suspended solids/km<sup>2</sup>. In addition, it cannot be determined from the published watershed descriptions the extent of active construction in these areas. Such construction is not accounted for in the model.

Two conclusions can be drawn from the apparent flexibility of this statistical model. First, the regression coefficients developed for the Menomonee River Watershed are valid for a wide range of conditions. Local calibrations should be made to refine the coefficients for local conditions. Secondly, it can be inferred that rainfall conditions (intensity and duration of antecedent dry conditions), amount of runoff and degree of urbanization are much more important in determining suspended solids in urban areas than are such local conditions as topography, geology and vegetation. If this were not the case, the regression information transferred from one area to another would bear no relationship with reality.

Furthermore, it has been suggested that the model produces reasonably accurate estimations of suspended solids loads after it has been calibrated for local conditions. The principal value of the model is the ease with which it can be calibrated. Runoff samples must be collected from a variety of small streams for which the following is known:

- a. Intensity and quantity of rainfall capable of producing runoff.
- b. antecedent rainfall conditions,
- c. discharge at the time of sample collection, and
- d. land usage information for the sampled watersheds.

Multiple regression relations are then developed for suspended solids concentrations and Items a. and c. for each stream. The regression coefficients are plotted as functions of urban development (Fig. III-1). The

Table III-1. Comparisons of predictive capabilities of model for suspended solids loads

Date or event no.	Drainage basin		Rainfall		Loads			Comments
	Area, km <sup>2</sup>	Urban, %	Amount, cm	Intensity, cm/hr	Antecedent dry period, days	Observed, kg/km <sup>2</sup>	Predicted, kg/km <sup>2</sup>	Difference, %
6/8/77	7.5	65	1.3	0.25	3	2,900	2,290	-21
								Meets all conditions of calibration
4/23/76	49.7	54	5.4	0.30	1	2,100	850	-60
								In calibration watershed but too large
27*	4.3	80	3.8	1.14	11	46,200	27,400	-41
29*			6.0	0.86	5	14,300	19,300	+35
32*			2.0	0.48	2.5	3,800	3,500	+8
								Outside calibration area
9/25/70	9.6	77	1.7	0.73	1	3,220	5,280	+64
10/20/70			2.3	0.45	6	2,800	5,000	+79
								Outside calibration area
11/5/69	0.73	100	1.6	0.33	19	1,130	6,765	+500
11/5/69			1.6	0.33	1**	1,130	1,730	+53
								Outside calibration area

\*Taken from Colston (1).

\*\*Antecedent dry period of 1 day was substituted for the 19 days.

suspended solids concentration model is then interfaced with whatever method is used locally to predict runoff quantities.

Relatively few samples are needed; only 15 to 20 from each of 5 to 8 watersheds as a minimum should be collected from a range of storm events. However, it is unnecessary to monitor the runoff events continuously. As long as discharge is known spot sampling is adequate because each sample is treated independently by the model. If continuous monitoring data is available, the precision of the model should be markedly enhanced by separate consideration of the rising and falling limbs of the hydrograph.

Location coding: BD - Brown Deer; BV - Beaver; DB - Donges Bay; HO - Honey,  
 NO - Noyes; SC - Schoonmaker; T - Trinity




Fig. III-1. Regression coefficients for model for total suspended solids.

### III-3. METHODS AND PROCEDURES

Efforts have been concentrated on small watersheds ( $<28 \text{ km}^2$ ) tributary to the Menomonee and Milwaukee Rivers. The watersheds are small enough to have simple hydraulic responses to precipitation events and these responses are amenable to the type of analysis proposed. Also, small streams are more dramatically affected by the processes of urbanization than larger receiving streams, because urban development will occupy a greater percentage of the watershed. Furthermore, concentration on small watersheds provides flexibility in the model, because larger watersheds can be modeled as the composites of the small ones. On the other hand, a model developed for large watersheds is not easily adapted to smaller watersheds.

The Menomonee River monitoring stations used for development of this model were Noyes, Schoonmaker and Honey Creeks and the Little Menomonee River at Donges Bay Road. In addition, three tributaries to the Milwaukee River, which are adjacent to the Little Menomonee at Donges Bay Road and Noyes Creek, were used (2,3). Water quality and flow in these watersheds were monitored manually from 1974 until 1977.

The initial step in the data analysis was to determine what independent factors most closely control the quality of water in surface runoff. Data were handled independently for each stream. Furthermore, analysis was restricted to rainfall runoff events and each sample for a particular stream was treated as an independent input and were all combined in a multiple regression analysis. A variety of rainfall and watershed parameters were tested as independent variables in the regression to determine whether they were statistically related to the dependent variable, i.e., the concentration of the chemical of interest. Only the procedure used in establishing and testing a model for total suspended solids is described here. However, similar development could be done for other water quality parameters.

With suspended solids concentration as dependent variable, total precipitation, rainfall intensity and duration, precipitation event recurrence interval, antecedent rainfall, instantaneous runoff/unit area of drainage, and temporal position of the sample within a runoff event were all tried as independent variables in a multiple regression analysis. Consistently, for the watersheds considered, the most important independent variables proved to be instantaneous runoff/unit area of drainage, rainfall intensity and antecedent rainfall conditions, in order of descending correlation. For comparison, the significant independent variables for total P concentration were total precipitation, instantaneous runoff and antecedent rainfall, again in descending order of importance.

It should also be pointed out that the position of the sample within the time framework of the runoff event may merit further attention. A relative time parameter was used, namely, a ratio of elapsed time since the

start of runoff to an average response time for the watershed. Response time was defined as the time elapsed between the start of runoff and the crest of the hydrograph. As a result, samples on the rising limb had relative time ratios  $< 1.0$ , those on the descending limb were  $> 1.0$ . Separation of samples into rising and falling limb categories improves the statistical significance of the multiple regressions. However, this separation has not been included in the model because it may reduce the availability of data for calibration at other sites.

After the initial determination of primary independent variables, multiple regressions were run in each watershed. The regression coefficients for each independent variable were plotted as a function of the extent of the watershed which was urbanized (Fig. III-1). The extent of urbanization is the sum of residential, commercial, industrial and transportation land uses. This factor was used--rather than extent of imperviousness--because it is more readily obtainable from literature or from local or regional planning agencies.

The graphs in Fig. III-1 can be used to create a multiple regression equation for a small watershed for which degree of urbanization is known. Table III-2 lists equations for several levels of urban development. Thus a user need know only the following to operate the model:

- a. Watershed drainage area ( $\text{km}^2$ ),
- b. area urbanized (%),
- c. instantaneous discharge for the time suspended solids concentration is desired ( $\text{m}^3/\text{sec}$ ),
- d. rainfall intensity ( $\text{cm/hr}$ ), and
- e. antecedent rainfall period, i.e., number of days since preceding rain which produced runoff rain (days).

The degree of urbanization determines which equation to use (Table III-2; Fig. III-1), and the equation provides the instantaneous suspended solids concentration after Items a, c, d and e are entered in the model. The instantaneous discharge values can be obtained from any runoff predicting system available to the user, from the basic "Rational Method" to the more sophisticated digital models. Any error inherent in discharge prediction will be additive in this water quality model.

However, a word of caution is essential for developing the suspended solids model. It has been found that the regression coefficient for instantaneous discharge is sensitive to active construction. For those watersheds where construction is underway (Brown Deer) coefficients are produced which fall above the line in Fig. III-1a. Data were insufficient to determine the extent to which construction activity affects the coefficient, but it is known that the model will produce erroneous results under such conditions.

Table III-2. Coefficients for final regression equations for various degrees of urbanization:

Watershed urbanized, %	Coefficient for QA, $\text{m}^3/\text{sec}/\text{km}^2$ (a)	Coefficient for I, cm/hr (b)	Coefficient for A, days (c)	Regression constant (d)
0	+700	0	-12	+160
20	+550	+80	-3.5	+80
40	+400	+200	-4.5	0
60	+250	+520	+12.5	-120
80	+100	+1420	+21	-400
100	-50	+3000	+29	-820

\*SS =  $a(QA) + b(I) + c(A) + d$ , where SS is suspended solids concentration (mg/L), QA is discharge/unit drainage area ( $\text{m}^3/\text{sec}/\text{km}^2$ ), I is rainfall intensity (cm/hr), A is antecedent dry period (days).

#### III-4. RESULTS AND DISCUSSION

In an attempt to determine the reliability of the model and limitations of its use, several tests have been tried. The model has been used to predict suspended solids loads for streams in the study area, one of which was used in calibrating the model. Also, it was tested against published data for small watersheds outside the Great Lakes Watershed. It would have been desirable to also test in the Great Lakes area outside of southeastern Wisconsin, but data for small watersheds were not available. The model also was tested on watersheds having different geological and hydraulic conditions from those used to calibrate it and for storms of different magnitudes and intensities from the studied storms.

For each test, measured flow rather than predicted flow was used because the model provides no method of flow prediction, and the use of any runoff predictor introduces an error in the final load calculations. That error compounds with any error due to the suspended solids prediction. Separation of these two errors is difficult and clouds the validity of the test of the empirical model. Thus, it is assumed that each user will interface the suspended solids model with his own method of obtaining flow.

Comparison of observed suspended solids loads with those predicted by the model for the Brown Deer Watershed for a storm event on 6/8/77 is shown in Fig. III-2. The Watershed is one used for calibration of the model, but data from this event were not used in the calibration. The Watershed is 65% urbanized and the equation derived from Fig. III-1 is:

$$SS = 200 QA + 680I + 14.5A - 170,$$

where:

SS is suspended solids concentration (mg/L)  
QA is discharge/unit area ( $m^3/sec/km^2$ )  
I is rainfall intensity (cm/hr)  
A is antecedent dry period (days)

The agreement is obviously good. The comparative suspended solids loads/unit area (QA x SS) are shown in Fig. III-3, and agreement again is good. All further tests compare loads because they are more reliable indicators of average stream conditions during an event. Concentrations tend to fluctuate dramatically in the early and late stages of an event when discharge is very low. However, these fluctuations are of little importance because the stream does not carry large quantities of suspended solids at these times. Comparison of loads attaches more importance to the bulk of the sediment transported.

A second test (Fig. III-4) was run on Underwood Creek, one of the larger ( $49.7 km^2$ ) tributaries to the Menomonee River. In this case, agreement is poor likely because the Watershed is outside the size range of watersheds for which the model was calibrated. Because of its size, Underwood Creek is not simply a single stream with ephemeral tributaries, but has two main branches which complicate its hydraulics. The model does not work well on complex or large stream systems.




Fig. III-2. Comparison of observed and predicted suspended solids concentrations for Brown Deer Creek on 6/8/77. Total precipitation was 1.32 cm, the antecedent dry period was 3 days and rain fall intensity was 0.25 cm/hr.




Fig. III-3. Comparison of observed and predicted suspended solids loads for Brown Deer Creek, Milwaukee, Wisconsin on 6/8/77. Total precipitation was 1.32 cm, antecedent dry period was 3 days and rainfall intensity was 0.25 cm/hr.




Fig. III-4. Comparison of observed and predicted suspended solids loads for Underwood Creek on 4/23/76. Total precipitation is 5.4 cm, antecedent dry period was 1 day and rainfall intensity was 0.30 cm/hr.

Other tests were run using data from Durham, North Carolina (1), San Francisco, California (4) and Cincinnati, Ohio (5). The purpose of these tests was to determine whether the coefficients established in Wisconsin could be transferred to other urban areas where topographic, climatic and geologic conditions were different. It was anticipated that these conditions would each play major roles in defining the coefficients and consequently the degree of transferability that could be achieved.

The Durham, North Carolina data is most complete, providing runoff and suspended solids for a wide range of rainfall events on a 4.3 km<sup>2</sup> watershed which is 80% urban. The terrain is steeper than that in Milwaukee (average land slope of 6 to 7% in Durham, 2% in Milwaukee) and geologic conditions are entirely different. However, for storms which fall within the range of intensity and total precipitation of storms used to calibrate the model, there is remarkably good agreement (Figs. III-5 to III-7).

The model was calibrated in the Menomonee River Watershed using storms which had intensities > 0.25 cm/hr and total precipitation > 1.0 cm. With the Durham data, the model was used to predict suspended solids for each of the 34 events for which rainfall data was available (1). It was found that the model did not agree with observed data for events of intensity < 0.25 cm/hr (19 events). Of the remaining 15 events, 7 had precipitation of < 1.0 cm, and were not handled well by the model. However, for the 8 events which had intensity > 0.25 cm/hr and total precipitation > 1.0 cm, the model worked well (Figs. III-5 to III-7). It seems that rainfall conditions and percentage development may play a larger role in controlling the sediment regression coefficients than local topography and geology.

Data from the Bloody Run Watershed in Cincinnati (5) also provided an opportunity for investigating the transferability of the model. This Watershed is 9.63 km<sup>2</sup> in size, is 80% urban and has an average slope of about 5%. Again it is topographically and geologically different from the Menomonee Watershed. Data for several events are published, but only four fall within the total precipitation and intensity range valid for the model. Use of the model to predict suspended solids loads for Bloody Run, Cincinnati are shown in Figs. III-8 and III-9. Agreement with observed values is not particularly good. The results for the 9/25/70 event (Fig. III-8) reveal a major shortcoming of the model, i.e., the model is extremely insensitive to changes in suspended solids during events when discharge remains relatively constant. The Bloody Run flow response to a rainfall of 1.65 cm (intensity of 0.73 cm/hr) on 9/25/70, varied only from 0.27 m<sup>3</sup>/sec/km<sup>2</sup> to 0.30 m<sup>3</sup>/sec/km<sup>2</sup> over a 3.5 hr period. Consequently, the model, which is discharge dependent, predicted a relatively constant solids load while observed values were variable. Such a response from an urban watershed is probably anomalous, but nonetheless, the model does not handle it well.

The San Francisco data (4) provides a less comprehensive test than Durham or Cincinnati. Only one storm fits in the intensity and total rainfall conditions for the model, and it has an anomalous antecedent dry period of 19 days. For a watershed of 0.73 km<sup>2</sup> which is 100% developed, the model greatly overpredicted suspended solids (Fig. III-10). However, it does properly predict for this Watershed the unusual conditions where suspended solids concentrations increase when runoff decreases (Fig. III-11). This dilution effect is anomalous for suspended solids. In fact, if an antecedent




Fig. III-5. Comparison of observed and predicted suspended solids loads for Event 32 at Third Fork Creek, Durham, North Carolina. Total precipitation was 2 cm, the antecedent dry period was 2.5 days and rainfall intensity was 0.48 cm/hr.




Fig. III-6. Comparison of observed and predicted suspended solids loads for Event 29, at Third Fork Creek, Durham, North Carolina. Total precipitation was 6 cm, the antecedent dry period was 5 days and rainfall intensity was 0.86 cm/hr.




Fig. III-7. Comparison of observed and predicted suspended solids loads for Event 27 at Third Fork Creek, Durham, North Carolina. Total precipitation was 3.8 cm, the antecedent dry period was 11.3 days and rainfall intensity was 1.14 cm/hr.




Fig. III-8. Comparison of observed and predicted suspended solids loads for Bloody Run, Cincinnati, Ohio on 9/25/70. Total precipitation was 1.7 cm, antecedent dry period was 1 day and rainfall intensity was 0.73 cm/hr.




Fig. III-9. Comparison of observed and predicted suspended solids loads for Bloody Run, Cincinnati, Ohio on 10/20/70. Total precipitation was 2.3 cm, antecedent dry period was 6 days and rainfall intensity was 0.45 cm/hr.




Fig. III-10. Comparison of observed and predicted suspended solids loads, Baker Street Basin, San Francisco, California on 11/5/69. Loads have been predicted using the general model (x) and also a modified model which reduces the importance of antecedent conditions (o). Total precipitation was 1.6 cm, antecedent dry period was 19 days and rainfall intensity was 0.33 cm/hr.




Fig. III-11. Comparison of observed and predicted suspended solids concentrations and flow for Baker Street Basin, San Francisco, California. Total rainfall was 1.6 cm, antecedent dry period was 19 days and rainfall intensity was 0.33 cm/hr.

dry period of 1 day is entered into the equation, the model produces very reasonable results. Exactly what this means is not understood. Perhaps the model does not work for such a steep (average slope 8 to 10%) watershed or for such long antecedent dry periods. Or perhaps on steep watersheds, the antecedent dry conditions become unimportant or the model is unaffected after 1 or 2 days. The interpretation of the test remains unresolved.

### REFERENCES-III

1. Colston, N. V. Jr. Characterization and Treatment of Urban Land Runoff. U.S. Environmental Protection Agency Report No. EPA 670/2-74-096, 1974. 157 pp.
2. Konrad, J. G., G. Chesters and K. W. Bauer. Menomonee River Pilot Watershed Study: Semi-Annual Report. IJC-Pollution from Land Use Activities Reference Group. Sponsored by U.S. Environmental Protection Agency. April 1976. 135 pp.
3. Cherkauer, D. S. The Hydrologic Response of Small Watersheds to Suburban Development: Observations and Modeling. In: Urbanization and Water Quality Control, W. Whipple Jr., ed., American Water Resources Association, Minneapolis, Minn., 1975. pp. 110-119.
4. Yen, B. C., V. T. Chow and A. O. Akran. Stormwater Runoff on Urban Areas of Steep Slope. U.S. Environmental Protection Agency Report No. EPA 600/2-77-168, 1977. 91 pp.
5. University of Cincinnati, Department of Civil Engineering. Urban Runoff Characteristics. U.S. Environmental Protection Agency Report No. EPA 11024 DQU 10/70, 1970. 340 pp.