EPA/540/2-91/011, No.2 June 1992

SEPA Vendor Information Form

To be completed for participation in the:

Vendor Information System for Innovative Treatment Technologies (VISITT) Version 2.0

NOTE: You may submit data electronically instead of typing or writing responses on the enclosed Vendor Information Form. Each Form is accompanied by one 3.5" IBM-compatible diskette. If you need additional diskettes, call the VISITT Hotline.

Completion of this form is voluntary. Any questions, call VISITT Hotline: 800/245-4505 or 703/883-8448.

Vendor Information Form

To be completed for participation in the:

U.S. Environmental Protection Agency
Office of Solid Waste and Emergency Response
Technology Innovation Office
Washington, DC 20460



A Letter to Technology Vendors

One of this country's greatest challenges is cleaning up its many hazardous waste sites. The nature and extent of contamination varies widely at these sites, and it is becoming increasingly clear that acceptable and cost-effective remedies will require the expedited development of new treatment technologies. EPA established the Technology Innovation Office (TIO) within the Office of Solid Waste and Emergency Response to promote greater development and use of these new remediation methods.

A serious obstacle to technology development and use is the lack of readily available and current technology information. To address this problem, TIO has developed an automated database - the *Vendor Information System for Innovative Treatment (VISITT)* - for use by state, federal, and private sector professionals responsible for cleanup of hazardous waste sites. *VISITT Version 1.0*, which we made available this June, contains detailed information on the availability, performance, and cost of 155 innovative technologies offered by 97 vendors. The database is available free of charge to the public, and we announced its availability to over 17,000 people who have expressed an interest in remediation technologies.

Although we've made a good start, we know that the initial version of VISITT did not include some of the companies in this growing industry. This booklet describes the types of technologies that we are including in the database. If you offer one of these technologies, I encourage you to complete the Vendor Information Form in Appendix D, and submit it by the October 1, 1992 deadline. Submittals received by that date will be considered for inclusion in the second release of VISITT in early 1993.

EPA believes that VISITT offers an unprecedented opportunity for developers and vendors of innovative treatment technologies to showcase their capabilities and to improve communication among technology developers, users, and the investment community. To fully appreciate the advantages of participating in VISITT, you must see it for yourself. IBM-compatible diskettes and a user manual are available free of charge from the VISITT Hotline (800/245-4505 or 703/883-8448). I invite you to order the system, and see how easy it is for a user to access information serving a wide variety of needs.

Submittal of the information requested in this form is completely optional. We do, however, urge all vendors who offer (or are developing) relevant innovative treatment technologies to respond. With your help, we expect that this cooperative EPA/industry effort will play a significant role in making new technologies available to remediate our nation's hazardous waste sites.

Walter W. Kovalick, Jr., Ph.D.

Director

Technology Innovation Office

TABLE OF CONTENTS

Section	<u>on</u>		Page
LET	ER TO	O TECHNOLOGY VENDORS	i
GEN	ERAL	INFORMATION	
	I.	Synopsis	. 1
	II.	Contents of This Booklet	. 2
	III.	Why is This Database Needed?	. 3
	IV.	Why Should You Participate?	. 3
	V.	What Innovative Technologies are Eligible for Inclusion?	. 4
	VI.	Should Confidential Business Information (CBI) be Submitted?	. 4
	VII.	How Much Documentation is Required Regarding Performance and C Technology Claims?	
Appe	ndices		
Α	INST	RUCTIONS	A-1
В	DEFI	NITIONS	B-1
	1. 2.	Technology Types	B-1 B-5
C	KEY	TO CONTAMINANT GROUPS	C-1
D	VENI	DOR INFORMATION FORM	D-1
	Part 2 Part 3 Part 4 Part 5 Part 6	1: General Information and Technology Overview 2: Full-Scale Equipment/Capabilities 3: Pilot-Scale Equipment/Capabilities 4: Treatability Study Capabilities (Bench Scale) 5: Summary of Performance Data 6: Representative Applications and Client References 7: Literature and Technical References	D-10 D-13 D-15 D-16 D-19

GENERAL INFORMATION

I. **Synopsis**

The U.S. Environmental Protection Agency (EPA) has recently developed an automated database, the Vendor Information System for Innovative Treatment Technologies (VISITT), for use by state, federal, and private sector professionals responsible for cleanup of the nation's hazardous waste sites. VISITT Version 1.0, which was made available in June 1992, contains 155 innovative technologies offered by 97 vendors. IBM-compatible diskettes and a user manual are available free of charge from the VISITT Hotline (800/245-4505 or 703/883-8448).

VISITT contains information on innovative treatment technologies, those for which a lack of cost and performance data inhibit their routine use to cleanup hazardous waste sites. Exhibit 1 gives a partial list of innovative technologies eligible for

EXHIBIT 1

PARTIAL LIST OF INNOVATIVE TREATMENT TECHNOLOGIES OF INTEREST

Acid Extraction Adsorption - In Situ*

Air Sparging - In Situ Ground Water*

Bioremediation - General*

Bioremediation - In Situ Ground Water*

Bioremediation - In Situ Lagoon Bioremediation - In Situ Soil*

Bioremediation - Slurry Phase*

Bioremediation - Solid Phase Bioventing*

Chemical Treatment - Dechlorination*

Chemical Treatment - Other

Chemical Treatment - In Situ Ground Water*

Delivery/Extraction Systems*

Electrical Separation

Magnetic Separation*

Materials handling Off-Gas Treatment

Pyrolysis

Slagging - Off-Gas Treated*

Soil Flushing - In Situ*

Soil Vapor Extraction

Soil Vapor Extraction - Thermally Enhanced

Soil Washing

Solvent Extraction*

Thermal Desorption*

Thermal Desorption - Off-Gas Treated*

Vitrification*

Vitrification - Off-Gas Treatment*

inclusion in VISITT. The database is designed to serve as a tool to screen these technologies for remediation of contaminated hazardous waste sites, and to direct users to more complete information. The investment community may also use this database to identify potential investment opportunities.

The Technology Innovation Office (TIO) of the Office of Solid Waste and Emergency Response (OSWER) is conducting this Second Invitation for Submittals for developers and providers of innovative treatment technologies. The information

Category included in VISITT Version 1.0.

submitted by applicants on the *Vendor Information Form (VIF)* (Appendix D) will be considered for inclusion in the second version of the database.

EPA believes that VISITT offers an unprecedented opportunity for developers and purveyors of innovative treatment technologies to showcase their capabilities. Innovative technologies are undergoing rapid change, which makes it difficult to maintain current information on their developmental status and commercial availability. We anticipate that this database will play an important role in the efficient expansion of this industry by tracking this changing market and improving communication between technology developers and users.

One of EPA's highest priorities is the generation of new methods to treat contaminated soil, sludge, solids, sediments, and solid-matrix waste and to treat ground water in situ. VISITT applies to only innovative treatment technologies that address these media/wastes. EPA will not accept information on the more widely available technologies: incineration, solidification/stabilization, and above-ground groundwater treatment. Technologies must address remediation of contaminated sites, not industrial wastes generated on an ongoing basis. Nor does this database address innovative measurement, monitoring, or containment technologies.

The purpose of *VISITT* is to facilitate the increased domestic use of innovative treatment technologies. Firms that respond may be located either inside or outside the United States; however, non-U.S. firms should intend to operate commercially within the U.S.

Technologies of interest include those at any stage of development, from bench to pilot to full scale. However, EPA desires information only on those technologies that respondents intend to commercialize, rather than those on which they are conducting academic research only.

Information submitted by applicants on the VIF by October 1, 1992, will be considered for inclusion in the second release of VISITT in early 1993. After October 1, EPA will review applications as time and resources permit. To remain in the database, all vendors must verify or update submitted information during the update cycle.

II. Contents of This Booklet

This booklet contains three sections. General Information gives background to VISITT and this Second Invitation for Submittals. Appendix A contains instructions for completing the *Vendor Information Form (VIF)*, definitions of terms used in the form, and a key to contaminant groups. Appendix B contains the blank *VIF* to be submitted.

The VIF consists of seven parts, which are listed in Exhibit 2. Part 1 must be completed in order for the vendor to be included in VISITT. This part contains questions on the name and location of the vendor and on the description, status, and application of the technology. Part 2 is required for applicants with full-scale technologies; Part 3 is required for applicants with pilot-scale technologies. Parts 4

EXHIBIT 2

CONTENTS OF VENDOR INFORMATION FORM

Part 1: General Information and Technology Overview

Part 2: Full-Scale Equipment/Capabilities

Part 3: Pilot-Scale Equipment/Capabilities

Part 4: Bench-Scale Treatability Study Capabilities

Part 5: Summary of Performance Data

Part 6: Representative Applications

Part 7: Literature and Technical References

through 7 are optional, and apply to technologies at any scale of development. Lastly, this submittal package includes an IBM-compatible computer diskette, which contains an automated version of the blank VIF.

III. Why Is This Database Needed?

The impetus for VISITT is the Agency's need to increase the availability and use of treatment technologies that can cost effectively clean up hazardous waste sites. The database provides a service to vendors who are developing and applying new technology by creating a vehicle to make known the application and performance of their technologies to the full range of users. The Agency anticipates that VISITT will be used by the thousands of professionals responsible for the cleanup of Superfund sites, RCRA corrective actions, State-led cleanups, Federal facility restoration programs, and remedial actions at leaking underground storage tank (UST) sites. The database allows users to screen technologies for engineering feasibility studies, and to identify vendors who provide treatability studies and cleanup services.

IV. Why Should You Participate?

EPA expects that VISITT will prove to be an excellent opportunity for vendors to promote their capabilities. The system allows the vendor to provide substantial information on the applicability, performance, and current use of their technologies. The database is publicly available free-of-charge on computer diskette, and EPA is studying online access. We reach cleanup personnel and investors throughout the U.S. and abroad by widely advertising VISITT in trade journals, at conferences, and

through direct mailings to an extensive list of potential users. Prior to the database's release, over 1,500 people requested order information.

V. What Innovative Technologies Are Eligible for Inclusion?

EPA includes only certain innovative treatment technologies in VISITT. These are technologies to treat the particular remedial problems identified earlier: treatment of contaminated soil, sludge, sediments, and solid-matrix wastes; and treatment of ground water in place. Innovative treatment technologies that treat off-gases generated from a primary treatment technology also are included in VISITT. Exhibit 1 contains a partial list of eligible innovative technologies. EPA will continue to expand this list to include additional innovative technologies submitted.

Incineration, solidification/stabilization, and above-ground groundwater treatment technologies will not be accepted. EPA recognizes that these technologies are vital to the clean up of hazardous waste sites, and that some innovative approaches utilizing these technologies are being developed and used. However, the Agency believes that, for the most part, information on these technologies is readily available and that there is a greater need to disseminate information on technologies for which there is far less information.

As noted earlier, this *VISITT* submittal also does not apply to technologies related to (1) treatment of industrial wastes generated on an ongoing basis, (2) measurement, (3) monitoring, or (4) containment.

VI. Should Confidential Business Information (CBI) Be Submitted?

Confidential business information should <u>not</u> be submitted, because EPA plans to make all submitted information available to the public. However, applicants may write "available on a case-by-case basis" as their response to those questions for which they have information, but would prefer not to make this information generally available.

Applicants are encouraged to provide "sanitized" or masked information that will allow users to review general information on a vendor's experience, without revealing confidential information. For instance, in Part 6, which details project experience, you may provide a generic industry name, such as "organic chemical manufacturer" instead of the actual site name. A lack of information may discourage users from considering the technology further.

VII. How Much Documentation is Required Regarding Performance and Other Technology Claims?

VISITT is intended to be a showcase for technology vendors. To optimize the usefulness of the data, EPA will review each submittal for clarity, completeness, and adherence to instructions. It is in the applicant's best interest to fill out each part of VIF as completely as possible since incomplete information may discourage users from considering the technology further.

EPA reserves the right to clarify or question information submitted. The respondent will be given the opportunity to review any substantive changes to the submittal that the Agency wishes to make, with two exceptions: (1) EPA may list Superfund sites or Federal facilities at which the vendor's technology has been used, and (2) EPA may add publicly-available references of which EPA is aware.

The Agency will not review submitted data for accuracy or quality; to do so would be too resource intensive and subjective, and would substantially delay dissemination. VISITT clearly states that vendors have supplied the information, and that the data have not been verified by the Agency. Applicants should expect that interested users will request additional information regarding applicability and performance of a particular treatment technology. The database contains the following disclaimer:

Inclusion in the U.S. Environmental Protection Agency's Vendor Information System for Innovative Treatment Technologies does not mean that the Agency approves, recommends, licenses, certifies, or authorizes the use of any of the technologies. Nor does the Agency certify the accuracy of the data. This listing means only that the vendor has provided information on a technology that EPA considers to be eligible for inclusion in this database.

EPA includes abstracts of all references cited in Part 7 of the VIF, and includes the abstracts in the Alternative Treatment Technology Information Center (ATTIC), an online service operated by EPA's Office of Research and Development. For this reason, we request that copies of references be included in the submittal.

VIII. EPA's Authority for Submittal and Burden Statement

EPA's authority for conducting this Second Invitation for Submittals is Section 311 of the Superfund Amendments and Reauthorization Act of 1986 (42 U.S.C. 9601 et seq.). Under Section 311, EPA may collect and disseminate information related to the use of innovative treatment technologies for remediation of hazardous waste sites.

EPA estimates that the vendor reporting burden for this collection of information will average 12 hours per response for completion of Part 1, and 28 hours for completion of the entire form. These estimates include the time applicants will require to review and maintain the data needed, and to complete and review the VIF. Send comments regarding this burden estimate, or any other aspect of reducing the burden, to Chief, Information Policy Branch, PM-223, U.S. Environmental Protection Agency, 401 M Street, S.W. Washington, D.C. 20460; and to Paperwork Reduction Project (OMB #2050-0114), Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, D.C. 20503.

IX. When and Where to File

EPA will review *Vendor Information Forms* received by October 1, 1992, for inclusion in the second release of *VISITT* in early 1993. EPA will review responses received after October 1 as time and resources permit.

Vendors already included in VISITT Version 1.0 will be contacted by EPA to verify or update submitted information. VISITT participants may also submit further technologies for consideration.

Send completed VIFs and diskettes to:

System Operator, VISITT PRC Environmental Management, Inc. 1505 PRC Drive McLean, VA 22102

EPA may need to contact respondents for further information or to clarify information submitted, prior to inclusion in VISITT.

APPENDIX A INSTRUCTIONS

INSTRUCTIONS

- 1. Part 1 must be completed in its entirety in order to be considered for inclusion in VISITT. A clear and concise technology description is particularly important, since this may be the first information reviewed by the user.
- 2. Provide your Vendor Name on each page in upper right corner; you need provide Technology Type on each page only if you are submitting more than one form.
- 3. Applicants with full-scale technologies (Question 17a checked) must fill out *Part 2*. You may also complete this part if the technology is at pilot scale.
- 4. Applicants with pilot-scale technologies (Question 17b checked) must fill out *Part 3*. You may also complete this part if the technology is at full scale or bench scale.
- 5. Parts 4 through 7 are optional, but it is in the applicant's best interest to complete these sections as thoroughly as possible. Incomplete information may discourage users from considering the technology further.
- 6. To answer *Part 1, Question 9*, refer to the definitions of Technology Types provided in Appendix B. Appendix B also contains other useful definitions of terms used in the *VIF*.
- 7. In Part 7, cite only references that you can provide with your application. If you are a participant in VISITT Version 1.0, you need not provide references submitted to EPA earlier.
- 8. You may submit responses on the computer diskette provided. A printed hard copy of the form should accompany the diskette, in case the latter is damaged in transit.
- 9. Submit one copy each completed VIF, references, and the computer diskette (if appropriate) to the System Operator, VISITT, PRC Environmental Management, Inc., 1505 PRC Drive, McLean, VA 22102.
- 10. Questions regarding the VIF should be addressed to the VISITT Hotline at 800/245-4505 or 703/883-8448.
- 11. EPA welcomes any comments on the contents of this form. You may provide comments in writing to the address given in No. 9, above, or by calling the VISITT Hotline.

APPENDIX B DEFINITIONS

DEFINITIONS

I. Technology Types

Acid Extraction - This technology is used to remove hazardous metals from excavated soils and sludges through the application of an acidic solution. It is a liquid-solid extraction technology that operates on the principle that the metals of concern will be preferentially solubilized and thereby removed from the waste. Further treatment will be required of the metal-containing acid solution.

Adsorption - In Situ - In this technology, containerized adsorptive materials (for example, various organic polymers, activated carbon, and sponge material) are placed directly in ground water to remove various hazardous compounds. This technology also would include systems that drill wells and place adsorptive materials in the air space above the ground water, in order to achieve reductions of relatively volatile compounds. The use of this technology will depend to a large extent on site-specific soil and ground-water characteristics.

Air Sparging - In Situ Ground Water - This technology reduces concentrations of hazardous compounds in ground water by injecting air below the water table. The injected air creates air bubbles in the ground water. The air bubbles contact dissolved/adsorbed-phase contaminants and non-aqueous phase liquids (NAPLs) in the aquifer, causing contaminants to volatilize. The volatilized contaminants are transported by the air bubbles into the vadose zone. Removal of the contaminants transferred to the vadose zone would be accomplished by another technology, usually soil vapor extraction. The application and effectiveness of this technology will depend to a large extent on site-specific soil and ground-water conditions.

Bioremediation - General - This technology uses microorganisms to degrade organic contaminants. The microorganisms breakdown the organic contaminants by using them as a food source. End products of the degradation are typically CO_2 and H_2O . Nutrients such as phosphorous, nitrogen, or oxygen may be added to enhance the biodegradation process. The VISITT database identifies FIVE subcategories of this technology, based on the type and media treated. The technologies listed in this category are those that did not specify one of the processes listed in the subcategories or were not described in enough detail to be included into one of the four subcategories.

Bioremediation - In Situ Ground Water - The defining characteristic of this technology is an injection system (typically injection wells) to circulate microorganisms, nutrients, and oxygen through contaminated aquifers. In most instances ground water is pumped, treated to some extent, and then reinjected with additives that enhance biodegradation. Common system design consists of a central withdrawal of ground water and reinfiltration upgradient of the treated area. Biodegradation relies on contact between contaminants in the ground water and microorganisms.

Bioremediation - In Situ Lagoon - This technology is similar to Bioremediation - Slurry Phase. However, it is in situ. The target media has a considerably higher moisture content. It may be close to a slurry in consistency. The various microbes and nutrients may be added by injection, sprayed on top of lagoon and mixed or applied in another manner. In many situations the media may also be stirred or aerated to promote bioremediation. Applications for this technology would include hazardous waste sludge lagoons.

Bioremediation - In Situ Soil - The target media for this technology are subsurface soils and the vadose zone above the water table. In this technology, various microbes, nutrients and an oxygen source are injected through injection wells into the soil. In general, subsurface soil moisture is required, and soils must be relatively permeable.

Bioremediation - Slurry Phase - This technology mixes excavated soil, sludge, or sediment with water to form a slurry that is mechanically agitated in an environment (usually a tank or reactor vessel, although in situ lagoon applications are possible) with appropriate ambient conditions of nutrients, oxygen, pH, and temperature. Upon completion of the process, the slurry is dewatered and the treated material disposed.

Bioremediation - Solid Phase - In this system, excavated soils are placed in a tank, building, or on a lined treatment bed. Nutrients and other additives are tilled into the soil using conventional equipment to facilitate microbial growth. The tillage equipment may provide aeration for the soil as well. Water is provided via a sprayer or sprinkler system. The VISITT system includes composting and land farming in this category.

Bioventing - This technology combines soil vapor extraction with bioremediation. It involves a system of vapor extraction wells that induce air flow in the subsurface through air injection or through the use of a vacuum. The increased air flow increases the amount of oxygen available for microbial degradation. A nutrient solution may be injected with the air or percolated into the soil to enhance biodegradation.

Chemical Treatment - Dechlorination - This category includes any chemical treatment technology that results in the removal or replacement of chlorine atoms bonded to hazardous compounds. Further treatment of the newly formed chlorinated compounds may be required.

Chemical Treatment - In Situ Ground Water - This technology treats ground water in situ through chemical treatment technology. In this technology chemicals may be injected into the ground water to convert hazardous compounds to less hazardous compounds. This technology is different from conventional pump and treat technologies in that the ground water is treated in situ and not pumped above ground, treated, and then reinjected.

Chemical Treatment - Other - Hazardous compounds are converted to less hazardous or nonhazardous compounds through chemical reactions. The chemical reactions may be induced through the addition of other compounds or through exposure of the contaminant to light (photo-initiated reactions). Treatment technologies that fall under this classification operate at moderate temperatures and pressure.

Delivery/Extraction Systems - These technologies do not treat hazardous wastes directly but facilitate the use of other waste treatment technologies. Such technologies may provide a means of in situ treatment in cases in which such treatment previously was not feasible. Such VISITT technologies include horizontal wells and other in situ delivery systems. In cases in which the delivery and extraction technology is integrally linked to the use of a particular treatment, the technology has been placed in the same technology category as the technology to which it is linked.

Electrical Separation - The operating principle of this technology is the establishment of an electric field that will allow positive and negative ions to migrate through the contaminated material and thereby be removed. The effectiveness of this technology will depend to a great extent on the electrolytic nature of the waste.

Soil Flushing - In Situ - This technology consists of recycling substantial volumes of water through a contaminated area for the purpose of flushing hazardous waste compounds from the contaminated site. Water is injected into the soil through injection wells, flows through the contaminated soil and is extraction through extraction wells. The principal defining characteristic of this technology is the ability to essentially isolate the injected water from any aquifer, and then to recover the water for aboveground treatment. The treated water is recycled through the contaminated area. Treatment chemicals maybe added to the water to help remove the hazardous constituents of concern (for example, water can be slightly acidified to help flush toxic metals from the waste site). As is the case in air sparging in situ ground-water, the use of this technology depends to a great extent on site-specific soil and ground-water conditions.

Materials Handling - These technologies do not treat hazardous waste directly but facilitate the use of other hazardous waste treatment technologies. Such VISITT technologies include innovative technologies to dewater waste, and remove debris. In cases in which material handling technology is integrally linked to the use of a particular treatment (for example, a specialized reactor for bioremediation), the technology also has been placed in the same technology category as the technology to which it is linked.

Off-Gas Treatment - This technology is specifically designed to treat the off-gas generated by another treatment technology such as thermal desorption or soil vapor extraction. Treatment of the gases may involve a chemical reaction to convert the gases to less hazardous compounds. Other treatments may involve a physical process such as absorption of the gases onto a substrate where they can be further treated. The VISITT database contains only innovative off-gas treatment technologies.

Pyrolysis - This technology, also referred to as cracking, breaks down large hydrocarbon molecules into molecules with lower molecular weight. This is achieved in the absence of oxygen (i.e. no oxidation) by high temperature alone. The process often takes place in a fluidized bed reactor. The products of the process include low molecular weight hydrocarbons and stack gases. Catalysts may be used to promote the pyrolysis process. Some pyrolysis systems may required air emission control systems for gases generated.

Slagging - This technology applies to hazardous wastes that contain substantial concentrations of metals (approximately 5 percent or greater). This system operates in an oxygen environment at temperatures of 3900°F (2150°C) or greater. Metal compounds are converted into a molten slag. Some slagging systems may require air emission control systems for acid gas, metal vapors, and particulate. The VISITT database identifies a separate subcategory of this technology if treatment of the off-gas generated by this process was specified. Slagging technologies listed under this category did not specify any type of off- gas treatment.

Slagging - Off-Gas Treated - This technology applies to hazardous wastes that contain substantial concentrations of metals (approximately 5 percent or greater) and organic compounds. This system operates in an oxygen environment at temperatures of 3900°F (2149°C) or greater. Organics are treated by combustion or other off gas treatment technology and metal compounds are converted into a molten slag. The off gas treatment systems may consist of air emission control systems for acid gas, metal vapors, and particulates.

Soil Vapor Extraction - This technology applies a vacuum to a series of extraction wells to create an air flow through the vadose zone. Air also may be injected through injection wells to enhance air flow. As air moves through the soil, volatile contaminants move from the soil and pore water to the air. The contaminated air is withdrawn often with entrained water. This technology typically strips volatile organic compounds from the soil. Further treatment of the extracted vapors usually is required.

Soil Vapor Extraction - Thermally Enhanced - This technology typically injects hot air or steam directly into the soil to induce vaporization of various volatile and semivolatile organic compounds. Injection of the hot air or steam may occur either through injection wells or by other devices such as hollow stem augers. The vaporized compounds are extracted directly from the soil through the use of vapor extraction wells. The hot air or steam (thermal treatment) enhances volatilization of the contaminant, thus increasing removal rates and the volatilization of less volatile compounds that would not have been extracted with non-thermally enhanced soil vapor extraction. Further treatment of the extracted vapors usually is required.

Soil Washing - This ex situ technology uses water and mechanical action to remove hazardous constituents that adhere physically to soil particles. It makes use of the fact that contaminants have a tendency to adhere to the organic carbon and fine-grained soil fraction (silt and clay) as opposed to the coarse grain mineral fraction (sand and gravel). Surficial contamination is removed from the coarse fraction of the soils by abrasive scouring. The wash water may be augmented with a leaching agent, surfactant, pH adjustment, or chelating agent to help remove organics or heavy metals. The spent wash water will require further treatment and most likely will be recycled back to the treatment unit.

Solvent Extraction - Similar to acid extraction, this technology focuses on the removal of organic compounds, from contaminated material instead of on the removal of metals. This is an ex situ liquid-solid and liquid-liquid extraction that operates on the principle that the organic constituents of concern can be preferentially removed from the waste to the solvent phase. The solvent used can be varied depending on the organic compounds to be treated. As with acid extraction, the contaminated solvent solution will require further treatment.

Thermal Desorption - This technology uses heat in a controlled environment to cause various organic compounds to volatilize and thereby be removed from contaminated material. In some cases an inert gas is used to carry the desorbed organics. The processes are planned and designed to avoid combustion (that is, not conducted in the presence of oxygen) in the primary unit. This technology differs from incineration in that the temperature range is usually 300°F - 1200°F (150°C - 650°C). Higher temperatures may be used when there is no oxygen present in the desorption chamber. Constituents that are volatilized will require further control. The VISITT database identifies a separate subcategory of this technology if treatment of the off-gas generated by this process was specified. Technologies listed under this category did not specify any type of off-gas treatment.

Thermal Desorption - Off-Gas Treated - As defined here, this technology includes all thermal desorption systems that are followed by some type of off-gas treatment system such as systems that liquify and recover volatilized constituents, adsorb off-gas with carbon, use a non-flame low temperature catalytic destruction process, or use incineration (that is, destruction of organic constituents in a controlled flame combustion process).

Vitrification - This technology treats wastes containing primarily metals and high concentrations of silicates (soil-like material). This technology uses heat usually applied through electrical power to melt contaminated soils and sludges to form a stable glass and crystalline structure with very low leaching characteristics. The contaminated waste is typically heated to a range of 2900°F to 3600°F (1600°C to 2000°C) well above the soil's melting point. In some cases vitrifying agents may be added. Metals are encapsulated in the glass-like structure of the melted silicate compounds. As used here, this technology also includes systems where treated wastes are ceramic-like in nature. Constituents that are volatilized will require further control. The VISITT database identifies a separate subcategory of this technology if treatment of the off-gas generated by this process was specified. Technologies listed under this category did not specify any type of off-gas treatment.

Vitrification - Off Gas-Treated - As defined here, this technology includes all vitrification systems that include some type of off-gas treatment such as systems that liquefy and recover volatilized constituents, adsorb off-gas with carbon, use a non-flame low temperature catalytic destruction process, or use incineration (that is, destruction of organic constituents in a controlled flame combustion process). This technology is useful for wastes containing both metals and organic wastes containing high concentrations of silicates (soil-like material). As used here, this technology also includes systems where treated wastes are ceramic-like in nature. As with Slagging and Thermal Desorption, this technology may require air emission controls for acid gas, metal vapors, and particulates.

II. Other Definitions

Batch Process - Processing of the waste occurs without any waste entering or leaving the process vessel during treatment. An example of a batch treatment process would be a solvent extraction system where a fixed amount of solvent and waste are mixed for a given period of time prior to transfer to another treatment operation.

Continuous Process - Untreated and treated wastes are simultaneously introduced and discharged from the particular treatment unit operation.

Semicontinuous Process - Treatment operations are semicontinuous when 1) after the initial charge, no wastes are added to the process but some part of the waste is continuously discharge, or 2) no material is discharged from the process but wastes or treatment chemicals are continuously added for a finite period of time. An example of the former system could be a thermal desorption process where a fixed amount of waste is heated and vapors are continuously withdrawn.

Soil - Any of the various types of natural surface materials present above bedrock.

Soil Classification - As used in this form, the term is meant to describe any of five groupings of soil based on particle size. The soil groupings and associate particle size are as follows: clay (.0002 to .002 millimeters), silt (.002 to .02 mm), fine sand (.02 to .2 mm), coarse sand (0.2 to 2.0 mm), and gravel (greater than 2 mm).*

Soil Survey Staff, 1975, Soil Taxonomy Handbook No. 436. U.S. Government Printing Office, p. 40 (Appendix 1).

Sludge - A semi-solid material with a moisture content typically between 2 and 20 percent. The term is used here to identify the applicability of various technologies to a material that contains significant amounts of moisture but is relatively viscous and may present some problems with regard to pumping and mixing. Examples of sludges include residuals from treatment of metal wastes and the mixture of waste/soil at the bottom of a waste lagoon.

Ground water in situ - As used here, the term "ground water" refers to subsurface water found in the zone of saturation (i.e., the fraction of the subsurface where all pore space is filled with water). Treatment of "ground water in situ" refers to treatment of ground water in place.

Technology Limitations - This term is meant to describe any contaminant, contaminant group, or waste parameter that can prohibit the applicability of a technology to a given waste, or adversely affect that technology in treating a particular waste. For example, biodegradation is inhibited by high concentration of toxic metals, and thermal desorption requires more energy in the presence of significant amounts of moisture. Other factors that may affect applicability and/or performance include soil particle size, oil and grease concentration, total organic carbon concentration (TOC), moisture content, cyanide concentration, and complex metals.

Treatability Studies - As used here, the term applies to treatment technology tests (usually at the bench or pilot scale) conducted to generate data on the untreated and treated concentrations (i.e., performance data) of various constituents, constituent groups, or pollutant parameters. These performance data are then used to assess whether a particular technology is a viable option for cleanup of actual hazardous waste sites or used to determine design parameters.

Operating Principle - These are the underlying scientific explanation for "why" a treatment technology works. For example, the operating principle of thermal desorption is that the addition of energy (in this case, in the form of heat) can cause chemicals to volatilize (i.e., go from liquid to vapor phase) and thereby be separated from the waste of concern. (Note: An explanation of "how" heat is supplied to a various chemical is a description of the various treatment operations.)

Transportable Technology - Any technology that can be moved either completely assembled or in various parts and then reassembled at a hazardous waste site is considered to be a transportable technology.

Fixed Technology - A technology that can only be used at the locations at which it is already assembled.

In situ - As used here, the term is meant to describe the treatment of hazardous wastes in the media and at the location that they are found. In situ treatment does not involve any excavation of the wastes.

Contaminant - For the purpose of this information request, any of the hazardous substances that are listed later in this appendix are considered contaminants. These are the same substances that are designated as hazardous under CERCLA at 40 CFR 302.4.

Contaminant Group - As used here, a term that applies to any of the generic names used to describe multiple contaminants that have similar chemical and/or physical properties. Two examples of contaminant groups are volatile organic compounds (VOCs) and radioactive metals.

Pollutant Parameter - Any of the terms used to describe waste characteristics as a whole as opposed to discrete groups of individual contaminants. Pollutant parameters include biochemical oxygen demand (BOD), total organic carbon (TOC), pH, and moisture content.

APPENDIX C KEY TO CONTAMINANT GROUPS

CONTAMINANT GROUP CODES FOR HAZARDOUS SUBSTANCES LIST

Organic	Inorganic	
A Halogenated volatiles	M Heavy metals	
B Halogenated semivolatiles	Nonmetallic toxic elements (As, F)	
C Nonhalogenated volatiles	Radioactive metals	
D Nonhalogenated semivolatiles	P Asbestos	
E Organic pesticides/herbicides	Inorganic cyanides	
F Dioxins/furans	R Inorganic corrosives	
G PCBs		
H Polynuclear aromatics (PNAs)	Miscellaneous	
I Solvents	S Explosives/propellants	
J Benzene-toluene-ethylbenzene-xylene (BTEX)	T Organometallic pesticides/herbicides	
K Organic cyanide		
L Organic corrosives		

HAZARDOUS SUBSTANCES

Organic Contaminant Group

CAS No.	
208968	AcenaphthyleneD,H
83329	Acenaphthene
75070	AcetaldehydeC
67641	Acetone
75058	Acetonitrile
98862	AcetophenoneD
591082	Acetyl-2-thiourea, 1D
107028	Acrolein
79061	AcrylamideD
79107	Acrylic acid
107131	AcrylonitrileC
124049	Adipic acidL
116063	Aldicarb E
309002	AldrinE
107186	Allyl alcoholE
62533	Aniline D,I,L
120127	Anthracene D,H
1912249	Atrazine E
2642719	Azinphos-ethylE
86500	Azinphos-methylE
151564	AziridineC
15150	
71432	BenzeneC,I,J
98884	Benzene carbonyl chlorideB
92875	BenzidineD
205992	Benzofluoranthene, 3,4H
65850	Benzoic acid
100470	BenzonitrileA,C,I
95169	Benzothiazole, 1,2 D,I
50328	Benzo (a) pyreneD,H
206440	Benzo (j,k) fluoreneH
207089	Benzo (k) fluorantheneD,H
100447	Benzyl chlorideA
56553	Benz (a) anthraceneD,H
117817	Bis (2-ethyl hexyl) phthalateD
111911	Bis (2-chloroethoxy) methaneB
111444	Bis (2-chloroethyl) etherB
542881	Bis (chloromethyl) etherB
75274	BromodichloromethaneA
74964	BromomethaneA
1689845	BromoxynilE
106990	Butadiene, 1,3C
71363	ButanolC
85687	Butlbenzyl phthalateD
94826	Butyric acid, 4-(2,4-dichloropC,L

133062	Captan	B
63252	Carbaryl	E
1563662	Carbofuran	E,F
75150	Carbon disulfide	C
56235	Carbon tetrachloride	A
78196	Carbophenothion	E
75876	Chloral	A
57749	Chlordane	E
106478	Chloroaniline, p	B
108907	Chlorobenzene	A
67663	Chloroform	A
74873	Chloromethane	A
107302	Chloromethyl methyl ether	A
106898	Chloromethyloxirane, 2	E
91587	Chloronaphthalene, 2	B
95578	Chlorophenol, 2-	B
59507	Chloro-3-methylphenol, 4	B
2921882	Chloropyrifos	E
218019	Chrysene	D,H
56724	Coumaphos	E
8021394	Creosote	Н
108394	Cresol, m-	D
106445	Cresol, p-	D
98828	Cumene	C,I
21725462	Cyanazine	E
110827	Cyclohexane	C, I
108941	Cyclohexanone	C
72548	DDD	E
72559	DDE	E
50293	DDT	
78488	DEF	-
333415	Diazinon	
132649	Dibenzofuran	
53703	Dibenz (a,h) anthracene	
124481	Dibromachloromethane	
106934	Dibromoethane, 1,2-	
96128	Dibromo-3-chloropropane, 1,2	
1918009	Dicamba	
95501	Dichlorobenzene, 1,2	
541731	Dichlorobenzene, 1,3	
106467	Dichlorobenzene, 1,4-	
91941	Dichlorobenzidine, 3,3	
75718	Dichlorodifluoromethane	•
75343	Dichloroethane, 1,1-	
107062	Dichloroethane, 1,2-	A

CAS No.

Organic Contaminant Group (continued)

CAS No.			CAS No.		
75354	Dichloroethene, 1,1-	A	122145	Fenitrothion	E
156592	Dichloroethylene, cis-1,2		86737	Fluorene	D,H
156605	Dichloroethylene, trans-1,2		50000	Formaldehyde	C
120832	Dichlorophenol, 2,4-		64186	Formic acid	
94757	Dichlorophenoxyacetic acid, 2		110009	Furan	
78875	Dichloropropane, 1,2		98011	Furfural	
542756	Dichloropropene, 1,3		, , ,		,-
62737	Dichloryos		765344	Glycidyaldehyde	С
115322	Dicofol		, , , , ,		
60571	Dieldrin		76448	Heptachlor	E
84662	Diethyl phthalate		1024573	Heptachlor epoxide	
111466	Diethylene glycol		118741	Hexachlorobenzene	
1660942	Diisopropylmethylphosphonate		87683	Hexachlorobutadieene	
60515	Dimethoate		60873	Hexachlorocyclohexane, alpha	
119904	Dimethoxybenzidine, 3,3		60873	Hexachlorocyclohexane, beta	
105679	Dimethyl phenol, 2,4-		60873	Hexachlorocyclohexane, delta	
13113	Dimethyl phthalate		77474	Hexachlorocyclopentadiene	
77781	Dimethyl sulfate		67721	Hexachloroethane	
99650	Dinitrobenzene, 1,3-		70304	Hexachlorophene	
51285			110543	Hexane	
121142	Dinitrophenol, 2,4		1689834	Ioxynil	•
606202			78831	Isobutanol	
88857	Dinitrotoluene, 2,6-		78591		
			78391	Isophorone	D
123911	Dioxane, 1,4		142500	V	т:
78342	Dioxathion		143500	Kepone	E
122667	Diphenylhydrazine, 1,2-		50000	T. T. Carllana	_
85007	Diquat		58899	Lindane	E
298044	Disulfoton	•	101755	No. 1 at 2	0.5
330541	Diuron		121755	Malathion	•
84742	Di-n-butyl phthalate		108316	Maleic anhydride	
117840	Di-n-octyl phthalate	D	123331	Maleric hydrazide	
115007	T. J 10	_	126987	Methacrylonitrile	
115297	Endosulfan		67561	Methanol	
959988	Endosulfan		16752775	Methomyl	
33212659	Endolsulfan II		72435	Methoxychlor	
1031078	Endolsulfan sulfate		79221	Methyl chlorocarbonate	
145733	Endothall		78933	Methyl ethyl ketone	
72208	Endrin		108101	Methyl isobutyl ketone	
7421934	Endrin aldehyde		80626	Methyl methacrylate	
563122	Ethion		101144	Methylene bis (2-chloroaniline)	
141786	Ethyl acetate		75092	Methylene chloride	
100414	Ethyl benzene		23855	Mirex	E
75003	Ethyl chloride				
60297	Ethyl ether		91203	Naphthalene	
107211	Ethylene glycol		100016	Nitroaniline, p-	
110805	Ethylene glycol monoethyl ether		98953	Nitrobenzene	D
759944	Ethylpropylthio carbomate, S	E	100027	Nitrophenol, 4-	D

Organic Contaminant Group (continued)

CAS No.		CAS No.	
1116547	Nitrosodiethanolamine, nD	1746016	TCDDF
55185	Nitrosodiethylamine, nD	95943	Tetrachlorobenzene, 1,2,4,5B
62759	Nitrosodimethylamine, nD	630206	Tetrachloroethane, 1,1,1,2A,E,I
86306	Nitrosodiphenylamine, nD	79345	Tetrachloroethane, 1,1,2,2A
930552	Nitorsopyrrolidine, nD	127184	Tetrachloroethene A
924163	Nitroso-di-n-butylamine, nD	58902	Tetrachlorophenol, 2,3,4,6B
615532	Nitroso-di-n-methylurethane, nD	3689245	TetraethyldithiopyrophosphateE
99990	Nitrotoluene, 4D	109999	TetrahydrofuranF,I
		137268	ThiramE
56382	Parathion, ethylE	108883	TolueneC,J
298000	Parathion, methylE	584849	Toluene diisocyanateD
1336363	PCBsG	8001352	ToxapheneE
608935	PentachlorobenzeneB	93721	TP, 2,4,5
76017	PentachloroethaneB	75252	TribromomethaneA
82688	PentachloronitrobenzeneB	120821	Trichlorobenzene, 1,2,4B
87865	PentachlorophenolB	71556	Trichloroethane, 1,1,1A
85018	PhenanthreneD,H	79005	Trichloroethane, 1,1,2A
108952	PhenolD	79016	TrichloroethyleneA
139662	Phenyl sulfideD	75694	Trichlorofluoromethane
62384	Phenylmercurie acetateE	933788	Trichlorophenol, 2,3,5B
298022	PhorateC,E	95954	Trichlorophenol, 2,4,5B
75445	PhosgeneE	88062	Trichlorophenol, 2,4,6B
13171216	PhosphamidonE	609198	Trichlorophenol, 3,4,5B
7803512	PhosphineE	93765	Trichlorophenoxyacetic acid, 2L
85449	Phthalic anhydrideD,E	933788	Trichloro-1,2,2-trifluoroethaneA,I
23950585	PronamideD	27323417	TriethanolamineE
129000	PyreneD,H	126727	Tris (2,3-dibromopropyl) phosphateB
110861	PyridineC,I		
		108054	Vinyl acetateC
91225	QuinolineD,H	75014	Vinyl chlorideA
108463	ResorcinolD	81812	WarfarinE
299843	RonnelE		
		108383	Xylene, mCJ
57249	StrychnineE,H	95476	Xylene, oC,J
100425	StyreneC	106423	Xylene, pC,J

Inorganic Contaminant Group

CAS No.		
7429905	AluminumM	
20859738	Aluminum phosphide M	
7440360	Antimony	
7440382	Arsenic M	
1327533	Arsenic trioxide	
1303339	Arsenic trisulfide	
1303339	Atsente distince	
7440393	BariumM	
542621	Barium cyanideM,Q)
7440417	Beryllium M	
7440439	CadmiumM	
13765190	Calcium chromateM	
7778543	Calcium hypochloriteM	
1333820	Chromic acidM,R	
7440473	Chromium M	
	Chromium (III)M	
	Chromium (VI) M	
7440484	CobaltM	
7440508	CopperM	
544923	Copper cyanideM,Q)
		•
7720787	Ferrous sulfate	
7439896	IronM	
7439921	LeadM	
7439965	Manganese M	
7439905	Mercury M	
1437710	Mercury	
7440020	NickelM	
7718549	Nickel chlorideM	
10102440	Nitrogen dioxideR	
7789006	Potassium chromateM	
151508	Potassium cyanideM,Q	
506616	Potassium silver cyanideM,Q	
7783008	Selenious acidM,R	
7782492	SeleniumM	
7440224	SilverM	
506649	Silver cyanideM,Q	
7440235	Sodium M	
26628228	Sodium azideM	
7681494	Sodium fluorideM	
7775113	Sodium chromate	

CAS No.	
143339	Sodium cyanideM,Q
1310732	Sodium hydroxideM,R
	•
7440280	ThalliumM
1314325	Thallic oxideM
563688	Thallium acetateM
6533739	Thallim carbonateM
7791120	Thallium chlorideM
10102451	Thallium nitrateM
12039520	Thallium selenideM
7446186	Thallium (I) sulfateM
7440291	ThoriumM
1314621	Vanadium pentoxideM
7440666	Zinc M
557211	Zinc cyanideM,Q
1314847	Zinc phosphideM
7733020	Zinc sulfate
Explosives	Propellants
Explosives CAS No.	Propellants
	Propellants Ammonia
CAS No.	
CAS No. 7664417	AmmoniaS
CAS No. 7664417 131748 7773060	Ammonia
CAS No. 7664417 131748 7773060 460195	Ammonia
CAS No. 7664417 131748 7773060	Ammonia
CAS No. 7664417 131748 7773060 460195 2691410	Ammonia
CAS No. 7664417 131748 7773060 460195	Ammonia
CAS No. 7664417 131748 7773060 460195 2691410 302012	Ammonia
CAS No. 7664417 131748 7773060 460195 2691410 302012 55630	Ammonia S Ammonium picrate S Ammonium sulfamate S Cyanogen S Cyclotetramethylenetetranitramine S Hydrazine S Nitroglycerine S
CAS No. 7664417 131748 7773060 460195 2691410 302012	Ammonia
CAS No. 7664417 131748 7773060 460195 2691410 302012 55630	Ammonia S Ammonium picrate S Ammonium sulfamate S Cyanogen S Cyclotetramethylenetetranitramine S Hydrazine S Nitroglycerine S
CAS No. 7664417 131748 7773060 460195 2691410 302012 55630 99990 26628228	Ammonia S Ammonium picrate S Ammonium sulfamate S Cyanogen S Cyclotetramethylenetetranitramine S Hydrazine S Nitroglycerine S Nitrotoluene, 4- S Sodium azide M, S
CAS No. 7664417 131748 7773060 460195 2691410 302012 55630 99990 26628228	Ammonia S Ammonium picrate S Ammonium sulfamate S Cyanogen S Cyclotetramethylenetetranitramine S Hydrazine S Nitroglycerine S Nitrotoluene, 4- S Sodium azide M, S Trinitrobenzene, 1,3,5 S
CAS No. 7664417 131748 7773060 460195 2691410 302012 55630 99990 26628228	Ammonia S Ammonium picrate S Ammonium sulfamate S Cyanogen S Cyclotetramethylenetetranitramine S Hydrazine S Nitroglycerine S Nitrotoluene, 4- S Sodium azide M, S

APPENDIX D VENDOR INFORMATION FORM

Blank Submittal Form

NOTE: You may submit data electronically instead of typing or writing responses on this Vendor Information Form. Each form is accompanied by one 3.5" IBM-compatible diskette. If you need additional diskettes, call the VISITT Hotline at 800/245-4505 or 703/883-8448.

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY VENDOR INFORMATION SYSTEM FOR INNOVATIVE TREATMENT TECHNOLOGIES (VISITT) VENDOR INFORMATION FORM

PART 1: GENERAL INFORMATION AND TECHNOLOGY OVERVIEW

1.	Date Submitted/	
2.	Developer/Vendor Name	
3.	Street Address	
4.	City Sta	ate/Province Zip Code
5.	Country	_
6.	a. Contact Name:	
	b. Title:	
7.	Contact Phone ()	8. Fax Number ()
9.	Technology Type.* Check one only. Fill	out a separate form for each additional technology.
	Acid Extraction	Materials Handling
	Adsorption - In Situ	Off-Gas Treatment
	Air Sparging - In Situ Ground Water	Pyrolysis
	Bioremediation - In Situ Ground Water	☐ Slagging - Off-Gas Treated
	Bioremediation - In Situ Lagoon	Soil Flushing - In Situ
	Bioremediation - In Situ Soil	Soil Vapor Extraction
	Bioremediation - Slurry Phase	Soil Vapor Extraction - Thermally Enhanced
	Bioremediation - Solid Phase	Soil Washing
	Bioventing	Solvent Extraction
	Chemical Treatment - Dechlorination	Thermal Desorption
	Chemical Treatment - In Situ Ground Water	Thermal Desorption - Off-Gas Treated
	Chemical Treatment - Other	☐ Vitrification
	Delivery/Extraction Systems	☐ Vitrification - Off-Gas Treated
	Magnetic Separation	Other:

^{*} See Appendix B for definitions of technology types.

Vendor Name:	 -	
Technology Type:		

0a.	Technology Name Assigne	ed By Vendor. (If	differ	ent than Question 9).
0b.	. Registered trademark?	☐ Yes		No
1.	Patents			
	a. Is technology patented?	Yes		No
	b. Is patent pending?	Yes		No
2.	Superfund Innovative Tech	nology Evaluatio	n (SI	E) Program.
	a. Is this technology being tested	or has this technolog	y been	tested in EPA SITE Emerging Technology Program?
		Yes		No
	b. Is this technology being tested	or has this technolog	y been	tested in EPA SITE Demonstration Program?
		Yes		No
	whether full-scale system is/	will be batch, conti Parts 2 and 3 allow	nuous v mor	
		Description	r dela est	일 하는 방향은 그 없는 이 얼굴에 다른 경우를 살아 되었습니다.
	the solvent. Super Chemical is			on technology (SUPER) utilizing Super Chemical as
	Chemical is soluble in water ((hydrophilic) and abov	re 65 i	ty of inverse miscibility; below 65 degrees F, Super degrees F, Super Chemical is insoluble in water ater and water-soluble compounds and warm Super
	■ 1 10 10 11 12 13 14 15 15 15 15 15 15 15	and the second of the second o		esticides, PAHs, semi-volatile organics, and VOCs.
	Chemical can extract organic co Within the unit, the soil is con- contaminants dissolve in the soil contaminated solvents are recla The clean washed soil is moved when the soil exits the system, it washing is concentrated 1,000 to	ontaminants, such as P ntinuously washed wit solution, and are rem limed in a closed-loop to a closed-loop dryer s t is relatively free of orga to 10,000 times, reduct	CBs, p th Sup loved circuit, system anics, a ing the	

Vendor Name:	
Technology Type:	

13.	Description of Technology (Continued).	

Vendor Name:	
Technology Type:	

14. **Technology Highlights**. In 200 words or less, describe in terms of contaminants treated, performance, implementation, or cost, the key marketable features of technology, such as treatment niche and advantages over other technologies.

Technology Highlights The SUPER solvent extraction process can treat soils, sludges, and sediments contaminated with PCBs, carcinogenic PAHs, pesticides, and VOCs at 20% to 40% of incineration costs. Treated products from the SUPER process include: water suitable for discharge, oil for recycle as fuel, and solids that can be returned to the site as backfill. The process can also reduce the initial volume of contaminated material by as much as 90%. The SUPER solvent extraction process operates at near ambient pressures and temperatures, uses off-the-shelf process equipment, and controls air emissions. The extraction efficiency (organic removal efficiency) achieved is as high as 99%. Solvent recovery is also greater than 99%. The process can treat up to 300 tons per day of contaminated soil. This technology is well accepted by communities because air emissions are minimized.

Vendor Name:	
Technology Type:	

15. **Technical Limitations.** In 200 words or less, describe technical limitations, such as specific contaminants, that could adversely affect applicability or performance.

Technology Limitations The SUPER process is not applicable for metal-only, (e.g., radioactive) or other inorganic wastes, but its performance is not affected by inorganics at low concentrations. This process may require screening or crushing to 0.25 inches, and other feed preparation operations depending on the waste. The extraction efficiency of an organic contaminant will depend on its solubility in the solvent. The solvent used is best suited for PCBs and pesticides.

Vendor Name:	
Technology Type:	

16. Other Comments. In 200 words or less, provide additional technology information, such as technology history, status, capabilities, experience, and applicable permits obtained (e.g., TSCA, RCRA).

EXAMPLE Other Comments The SUPER process has been successfully demonstrated at bench scale, pilot scale, and at full scale. A full-scale SUPER unit was used to treat PCB-contaminated sludges at the BAD Oil Refining Superfund site. Two pilot-scale units have been built. One was operated under the SITE program to treat soils and sludges contaminated with PCBs. Bench-scale treatability studies have been conducted on contaminated soils containing petrochemical compounds, pharmaceutical compounds, pesticides, PCBs, and wood preserving wastes containing PAHs.

			Technology Type:	
	PART 1: G	ENERAL INFORMATION AN	TECHNOLOGY OVERVIE	W (Continued)
17.	Technology Stat Check only one.	us. Using the following definit	ons, indicate the operational	status of the technology
		wailable equipment is sized and corust fill out Part 2).	mercially available for actual site	remediation. (If you select ful
	operating con	Available equipment is of sufficient ditions for a full-scale system. However must fill out <i>Part 3</i>).	size to verify technology feasibiliver, it is not of the size typically us	ty or establish the design and ed for a cleanup. (If you selec
	c. Bench scale laboratory. D	or emerging. Technology shown lata from these studies cannot be us	to be feasible through the use of the discount of the technology to full to scale up the technology to full the technology the techn	f bench-top equipment in the
18.		Check "actual" for all media tha hich technology may be appl		nology. Check "potential
	Actual Potenti	ial		
		Soil (in situ) Soil (ex situ) Sludge (Does not include mu Solid (e.g., slag) Natural sediment (in situ) Natural sediment (ex situ) Ground water in situ Off-gas generated from a prin	nicipal sewage sludge)	gy
19.	all that have be technology may in Part 5. If yo	and Contaminant Groups* To the treated by your technology be applied to in the future. Do the technology is materials has estion may not apply.	y (i.e., data exist). Check ta for actual contaminants to	"potential" for all that the reated should be included
	Actual Potential		Actual Potential	
		alogenated volatiles alogenated semivolatiles onhalogenated volatiles onhalogenated semivolatiles rganic pesticides/herbicides ioxins/furans CBs olynuclear aromatics (PNAs)	Heavy metals Nonmetallic s Radioactive n Asbestos Inorganic cya Inorganic con Miscellaneous	oxic elements netals unides
		olvents enzene-toluene-ethylbenzene- viene (BTEX)	Explosives/p	ropellants lic pesticides/herbicides
		cetonitrile (organic cyanide) rganic acids	Others (specify):	
	•			

Vendor Name: _

* See Appendix C for key to contaminant groups.

D-7

Vendor Name:	
Technology Type:	

20. **Industrial Waste Sources or Site Types Treated.** Check all that may apply. Treatment data should be available for those sites for which "actual" is checked. (See Table A for wastes typically associated with each industry.)

Actual Potential	Actual Potential
Agriculture Battery recycling/disposal Chloro-alkali manufacturing Coal gasification Dry cleaners Electroplating Herbicide manufacturing/use Industrial landfills Inorganic/organic pigments Machine shops Metal ore mining and smelting Municipal Landfill	Munitions Manufacturing Paint/ink formulation Pesticide manufacturing/use Petroleum refining and reuse Photographic products Plastics manufacturing Pulp and paper industry Other organic chemical manufacturing Other inorganic chemical manufacturing Semiconductor manufacturing Rubber manufacturing Wood preserving Uranium mining
Vendor Services. Check all that apply. Equipment manufacturer Subcontractor for cleanup services Prime contractor for full-service remediation Other (specify)	

21.

Vendor Name:	
Technology Type:	

TABLE A

Contaminants/Wastes Associated With Industrial Waste Sources or Site Types

Chloro-Alkali Manufacturing : Chlorine Compounds, Mercury

Coal Gasification : PAHs
 Agriculture : Pesticides

4. Battery Recycling/Disposal : Lead (acid)5. Dry Cleaners : Solvents

6. Electroplating : Chrome, Metals

7. Herbicide Manufacturing/Use : Pesticides

8. Industrial Landfills : Wastes from Multiple Sources

9. Inorganic/Organic Pigments : Solvents, Chrome, Zinc

10. Machine Shops : Metals, Oils

11. Metal Ore Mining and Smelting : Metals

12. Municipal Landfills : Wastes from Multiple Sources

13. Munitions Manufacturing : Explosives, Lead

14. Paint/Ink Formulation : Solvents, Some Metals (Chrome, Zinc)

15. Pesticide Manufacturing/Use : Pesticides

16. Petroleum Refining and Reuse : Petroleum, Hydrocarbons, BTEX

17. Photographic Products
18. Plastics Manufacturing
19. Silver, Bromide, Solvent
19. Polymers, Phthalates

19. Pulp and Paper Industry : Chlorinated Organics, Dioxins

20. Other Organic Chemical Manufacturing : Organics, Metals (used for Catalyst)

21. Other Inorganic Chemical Manufacturing: Inorganics, Metals

22. Semiconductor Manufacturing
 23. Rubber Manufacturing
 24. Wood Preserving
 25. Degreasing Agents (Solvents), Metals
 26. Rubber, Plastics, Polymers, Organics
 27. Creosote, PCP, Arsenic, Chrome, PAHs

25. Uranium Mining : Uranium, Radioactive Metals

Vendor Name:	·
Technology Type:	

PART 2: FULL-SCALE EQUIPMENT/CAPABILITIES

You must complete this part if Question 17a is checked (i.e., technology is at full scale). You may also complete this part if the technology is at pilot scale.

22. **Major Unit Processes.** In 300 words or less, describe the steps and operation of the full-scale system, including list of key components (e.g., pre- and post-processing). Provide more detail than you did in Question 13.

EXAMPLE

Major Unit Processes

Pre-Processing

- · Front-End Loader and Weight Scale
- Shredder
- Radial Stacker Belt Conveyor and Surge Hopper
 - 1. Stockpiled soil is transported to a weigh scale by a front-end loader.
 - Soil is deposited directly on a power shredding device. Classified soil with a top size of less than 2 inches passes through the shredder into the feed conveyor.
 - 3. The feed conveyor is an enclosed radial stacker belt conveyor that is 18 inches wide and 60 feet long. The conveyor discharges into the surge hopper located above the thermal processor. The soil will be fed into the LT system at regular intervals to maintain the surge hopper seal.

Process

- Thermal Processor
- · Induced Draft Fan for Vapors
- Horizontal Screw Conveyor and Ash Conditioner
 - 1. The thermal processor houses four intermeshed screw conveyors. The function of each screw conveyor is to move soil forward through the processor and to thoroughly mix the material, providing indirect contact between the heat transfer fluid and the soil. The shafts and flights of the screw conveyors and the processor jackets are hollow to allow circulation of a heat transfer fluid (i.e., hot oil).
 - 2. Vapors are driven off the soil and are drawn out of the thermal processor by an induced draft (ID) fan.
 - 3. Soil is discharged from the thermal processor onto a horizontal screw conveyor and then an ash conditioner.
 - The conditioner is a ribbon flight screw conveyor. Water spray nozzles are installed in the conditioner housing to cool the discharge material and to minimize fugitive dust emissions.

Post-Processing

- Stacker Belt Conveyor and Dump Truck
 - The conditioner discharges onto an inclined stacker belt. The stacker belt conveys the wetted processed soil from the conditioner to the dump truck.

Vendor Name:	
Technology Type:	

PART 2: FULL-SCALE EQUIPMENT/CAPABILITIES (Continued)

22.	Major Unit Processes.	(Continued)

Vendor Name:	
Technology Type:	

PART 2: FULL-SCALE EQUIPMENT/CAPABILITIES (Continued)

Transportable	Fixed		n situ	
b. City:	·	and State:		of fixed facility
Number of Full-Scal	le Systems			
Planned/in	design	Under Construction		Constructed
Capacity Range per	Hour.			
to	0		(units)	☐ Not applicab
	nge. Provide a "ballpa xclude excavation, perm			eated. Include wa
to	0	oer	(units)	
a significant effect on price.	nit Price. With "1" being a unit price. If technolog	the highest, rank a	ation and waste	
a significant effect on price. Initial conta Target con Waste qua Depth of conta	unit price. If technolog aminant concentration taminant concentration	the highest, rank a		handling cannot af
a significant effect on price. Initial conta Target con Waste qua Depth of conta	aminant concentration taminant concentration ntity ontamination round water raste characteristics	the highest, rank a	Site preparation Waste handling/p Amount of debris Utility/fuel rates	handling cannot at
a significant effect on price. Initial conta Target con Waste qua Depth of conta Depth to good Residual was contact to the price of the price	aminant concentration taminant concentration ntity ontamination round water raste characteristics	the highest, rank a	Site preparation Waste handling/p Amount of debris Utility/fuel rates	handling cannot af
a significant effect on price. Initial contant arget con Waste quant Depth of contant Depth to go Residual was Other Factors (specify) Full-Scale Cleanups a. If you are a subcontant depth contant are subcontant ar	aminant concentration taminant concentration ntity ontamination round water raste characteristics	the highest, rank a y is in situ, excava	Site preparation Waste handling/p Amount of debris Utility/fuel rates Labor rates	handling cannot af

Vendor Name:	
Technology Type:	

PART 3: PILOT-SCALE EQUIPMENT/CAPABILITIES

You must complete this part if Question 17b is checked. You may also complete this part if the technology is at full scale or bench scale.

29. **Major Unit Processes.** In 200 words or less, describe steps and operation of the pilot-scale treatment system, including list of key components (e.g., pre- and post-processing) of the pilot-scale system. Provide more detail than you did in Question 13.

EXAMPLE

Major Unit Processes

Pilot-scale testing involves processing the soils or bulk soils through various operations of reduced-size equipment which when set in series would be similar to a fulf-scale operation. The equipment consists of the following:

- 1. A hopper and screen for feed preparation. Removal of tramp material and sizing, if needed.
- Mixing or attrition tank where the prepared feed is introduced to the liquids. In the most basic scheme contaminant extraction takes place at this stage.
- Classification circuit consisting of a sump, pump, and cyclone for separation of coarse sand, gravel, and organics from fine clays and sitts.
- 4. If contaminant extraction requires, coarse material is subjected to a specific gravity (S.G.) separation utilizing a vessel, cyclone, or hydrosizer. Contaminant bearing organics (low S.G.) are separated from the clean, coarse (high S.G.) material.
- Clean, coarse material is dewatered with a screen, although in full-scale operation, additional dryers (centrifuges)
 may be employed.
- Contaminant bearing low S.G. organics are dewatered with a screen and collected for disposal or secondary treatment.
- 7. Clays and silts are flocculated in a reaction tank and gravity concentrated in a thickener or clarifier.
- 8. Thickened, contaminant bearing clays and silts are dewatered in a belt press and sent for disposal or secondary processing.
- Recycled liquid from the thickening and dewatering process are collected and in some cases treated before being returned to the mixing/attrition tank.

•	
	(Continued)

	Technology Type:
	PART 3: PILOT-SCALE EQUIPMENT/CAPABILITIES (Continued)
29.	Major Unit Processes. (Continued)
30.	Pilot-scale facility is (Check only one)
	Transportable Fixed In Situ
	b. City: and State: of fixed facility.
31.	Number of Pilot-Scale Systems
	Planned/in design Under construction Constructed
32.	Capacity Range Per Hour. Prorate capacity of batch processes.
	to (units)
33.	How many times have you used this technology at your facility or at other locations to conduct pilot scale studies on actual wastes? Count studies pertaining to the same site once, regardless of the number of different wastes or tests. Do not count tests on surrogate wastes.
34.	Can you conduct pilot-scale treatability studies on some types of waste at your location?
	☐ Yes ☐ No
	At a contaminated site?
	☐ Yes ☐ No
35.	Quantity of Waste Needed for Pilot-Scale Treatability Study. Give estimated range of quantity of waste needed to test, at the pilot scale, the feasibility of this technology on a specific waste.
	to (units)

Vendor Name: __

Vendor Name:	
Technology Type:	

PART 4: TREATABILITY STUDY CAPABILITIES (BENCH SCALE)

36.	Can you conduct bench-scale treatability studies on some types of waste at your location?
	Yes No
7.	Number of Bench-Scale Studies Conducted. Estimate total number of bench-scale studie conducted on actual waste from different sources or sites. Count studies pertaining to the same sit once, regardless of the number of different wastes or tests. Do not count tests on surrogate wastes
18.	Description of Bench-Scale Testing Procedures. In 200 words or less, describe the type of test the would be performed to determine feasibility of this technology for treating a specific waste.
	EXAMPLE
	Description of Bench-Scale Testing Procedures
	In our feasibility assessment tests, we usually start with a sample of the soil to be treated, and a knowledge of the nature and level of contaminants and the effluent goals to be met. The following steps are then taken:
	a. The optimal conditions for soil washing will be studied, such as pH, time, and chelating agent and concentration.
	b. Various likely adsorbents are studied on a batch basis to determine which are most effective at removing the metals of interest from the chelating agent in the washing water.
	c. One or more selected media are then studied on columns to determine their metal retention ability in a continuous- flow situation.
	d. For the surviving adsorbent(s), the ion elution performance is then determined; after this step, one resin will have been selected as optimal for the particular task under study.
	e. The selected adsorbent is then subjected to a number of charge/regeneration cycles to establish its ruggedness.
<u> </u>	

Vendor Name:	
Technology Type:	

PART 5: SUMMARY OF PERFORMANCE DATA

39. Summarize treatment results obtained for up to *five* specific contaminants, contaminant groups, or pollutant parameters that best represent technology performance. Data provided do not have to correspond to the projects listed in *Part 6*, but should be supported by documentation available on request.

Note:	(1)	List one contaminant per page. May list contaminant more than once if different treatability ranges apply.
	(2) and (3)	Circle appropriate units; for concentration that were non-detect write N.D.; treated concentration should be lower than untreated concentration unless the technology is dewatering or some other volume reduction method. If a concentration range cannot be given, provide an average and note it as such.
	(4)	Check scale of equipment used to produce data given in (3).
	(5)	Check the appropriate test sample matrix.
	(6)	Check soil classification if appropriate. More than one classification may be checked.
	(7)	Briefly describe waste or media treated (e.g., 3,000 cubic yards of oily sludge, 5,000 cubic yards of solven contaminated soil)
	(8)	Explain any conditions that may have impacted treated concentration achieved, such as cleanup standards site conditions, and mode of operation.

39a.

2) Untreated Concentration Range	(3) Treated Concentration Range	(4) Equipment Scale
Units: mg/kg mg/l (Circle one)	Units: mg/kg mg/l (Circle one)	(Check only one)
Lower Limit	Lower Limit	Bench
То	То	Pilot
Upper Limit	Upper Limit	Full
(5) Matrix (Check all that apply)	(6) Soli Classification (Cl	heck all that apply)
Unsaturated Soil	Clay (0.0002 to 0.002 mm)	
Saturated Soil	Silt (0.002 to 0.02 mm)	
Ground Water	Fine Sand (0.02 to 0.2 mm)	
Gas Phase	Coarse Sand (0	0.2 to 2.0 mm)
Sediment	Gravel (greater	than 2.0 mm)
Sludge	Not applicable	
Waste Description (10 words or less):		
Comments:		

Vendor Name:	
Technology Type: _	

PART 5: SUMMARY OF PERFORMANCE DATA (Continued)

39b.

Contaminant or Pollutant Parameter:		
2) Untreated Concentration Range	(3) Treated Concentration Range	(4) Equipment Scale
Units: mg/kg mg/l (Circle one)	Units: mg/kg mg/l (Circle one)	(Check only one)
Lower Limit	Lower Limit	Bench
То	То	Pilot
10		Full
Upper Limit	Upper Limit	
(5) Matrix (Check all that apply)	(6) Soll Classification (C	heck all that apply)
Unsaturated Soil	Clay (0.0002 to	0.002 mm)
Saturated Soil	Silt (0.002 to 0.02 mm)	
Ground Water	Fine Sand (0.02	2 to 0.2 mm)
Gas Phase	Coarse Sand (0	0.2 to 2.0 mm)
Sediment	Gravel (greater	than 2.0 mm)
Sludge	Not applicable	
Waste Description (10 words or less):		
Comments:		

39c.

(2) Untreated Concentration Range	(3) Treated Concentration Range	(4) Equipment Scale
Units: mg/kg mg/l (Circle one)	Units: mg/kg mg/l (Circle one)	(Check only one)
Lower Limit	Lower Limit	Bench
То	То	Pilot
Upper Limit	Upper Limit	Full
(5) Matrix (Check all that apply)	(6) Soil Classification (C	heck all that apply)
Unsaturated Soil	Clay (0.0002 to 0.002 mm)	
Saturated Soil	Silt (0.002 to 0.02 mm)	
Ground Water	Fine Sand (0.0	2 to 0.2 mm)
Gas Phase	Coarse Sand (0.2 to 2.0 mm)
Sediment	Gravel (greate	r than 2.0 mm)
Sludge	Not applicable	
Waste Description (10 words or less):		
Comments:		

Vendor Name:	
Technology Type:	

PART 5: SUMMARY OF PERFORMANCE DATA (Continued)

39d.

(2) Untreated Concentration Range	(3) Treated Concentration Range	(4) Equipment Scale
Units: mg/kg mg/l (Circle one)	Units: mg/kg mg/l (Circle one)	(Check only one)
Lower Limit	Lower Limit	Bench
То	То	Pilot
Upper Limit	Upper Limit	Full
(5) Matrix (Check all that apply)	(6) Soli Classification (CA	eck all that apply)
Unsaturated Soil	Clay (0.0002 to	0.002 mm)
Saturated Soil	Silt (0.002 to 0.02 mm)	
Ground Water	Fine Sand (0.02 to 0.2 mm)	
Gas Phase	Coarse Sand (0.2 to 2.0 mm)	
Sediment	Gravel (greater	than 2.0 mm)
Sludge	Not applicable	
Waste Description (10 words or less):		
	·	
Comments:		

39e.

2) Untreated Concentration Range	(3) Treated Concentration Range	(4) Equipment Scale
Units: mg/kg mg/l (Circle one)	Units: mg/kg mg/l (Circle one) (Check only o	
То	Lower Limit	Pilot
Upper Limit	Upper Limit	
(5) Matrix (Check all that apply)	(6) Soil Classification (C	heck all that apply)
Unsaturated Soil	Clay (0.0002 to 0.002 mm)	
Saturated Soil	Silt (0.002 to 0.02 mm)	
Ground Water	Fine Sand (0.02 to 0.2 mm)	
Gas Phase	Coarse Sand (0.2 to 2.0 mm)	
Sediment	Gravel (greater	than 2.0 mm)
Sludge	Not applicable	
Waste Description (10 words or less):		
Comments:		

Vendor Name:	
Technology Type:	

40. List up to five representative projects that can also serve as references. Full- and pilot-scale projects are of most importance. EPA reserves the right to add information on projects conducted for the federal government of which EPA is aware.

Location:	Project Took Place at Site Named	At another Site (i.e., a Test Facility)
City	Yes	Yes
		No
State/Province:	No	No
Country		
Regulatory Authority or Statute	Application Type	(Check only one)
(Check all that apply)	Full-Scale Cleanup	EPA SITE Emerging
RCRA Corrective Action	Field Demonstration	Technology Program
CERCLA	Pilot-Scale Treatability Study	Research
TSCA Safe Drinking Water Act	Bench-Scale Treatability Study TSCA National Demonstration	Other (specify):
UST Corrective Action	TSCA National Demonstration TSCA Research and Development	
State (specify):	EPA SITE Demonstration Program	
Other (Specify):		
Not Applicable		
Media Treated (Check all that apply)	Contaminant Group Trea	ted (Check all that apply)
Soil (in situ)	Organic	Inorganic
Soil (ex situ)	J. 3	3
Sludge	Halogenated Volatiles	Heavy Metals
Solid	Halogenated Semivolatiles	Nonmetallic Toxic Elemen
Natural Sediment (in situ)	Nonhalogenated Volatiles	Radioactive Metals
Natural Sediment (ex situ)	Nonhalogenated Semivolatiles	Asbestos
Ground Water In Situ	Organic	Inorganic Cyanides
Off-gas from a primary treatment technology	Pesticides/Herbicides Dioxins/Furans	Inorganic Corrosives
treatment technology	PCBs	Miscellaneous
Equipment Scale	Polynuclear Aromatics (PNAs)	Miscenalieous
A	Solvents	Explosives/Propellants
(Check one only)	Benzene-toluene-ethylbenzene-	Organometallic pesticides
Bench Pilot	xylene (BTEX)	herbicides
Full	Acetonitrile	
	Organic Acids	
Volume/Quantity:	Person outside of company familiar with pro	ject (optional):
(Units)	Name:	Company:
	Address:	
Project Status		
Contracted:	Is Literature Available on this Project? (Include	citations in Part 7)
Month Year	Yes	No
In Cleanup: Yes No	Additional Project Information:	
Completed:		
·		

Vendor Name:	
Technology Type:	

40b.

Location:	Project Took Place at Site Named	At another Site (i.e., a Test Facility)
City	Yes	Yes
State/Province:	No	No
Country		
Regulatory Authority or Statute	Application Type	(Check only one)
(Check all that apply) RCRA Corrective Action CERCLA TSCA Safe Drinking Water Act UST Corrective Action State (specify): Other (Specify):	Full-Scale Cleanup Field Demonstration Pilot-Scale Treatability Study Bench-Scale Treatability Study TSCA National Demonstration TSCA Research and Development EPA SITE Demonstration Program	EPA SITE Emerging Technology Program Research Other (specify):
Not Applicable Media Treated (Check all that apply)	Contaminant Group Trea	ted (Check all that apply)
Soil (in situ) Soil (ex situ) Sludge Solid Natural Sediment (in situ) Natural Sediment (ex situ) Ground Water In Situ Off-gas from a primary treatment technology Equipment Scale (Check one only) Bench Pilot Full	Organic Halogenated Volatiles Halogenated Semivolatiles Nonhalogenated Volatiles Nonhalogenated Semivolatiles Organic Pesticides/Herbicides Dioxins/Furans PCBs Polynuclear Aromatics (PNAs) Solvents Benzene-toluene-ethylbenzene- xylene (BTEX) Acetonitrile Organic Acids	Inorganic Heavy Metals Nonmetallic Toxic Element Radioactive Metals Asbestos Inorganic Cyanides Inorganic Corrosives Miscellaneous Explosives/Propellants Organometallic pesticides/ herbicides
Volume/Quantity:	Person outside of company familiar with pro	ject (optional):
Project Status	Address:	Company:
Contracted:	Is Literature Available on this Project? (Include	citations in Part 7)
Month Year	Yes	No
In Cleanup: Yes No	Additional Project Information:	
Completed:		
Month Year		

Vendor Name:	 	
Technology Type:	 	

4	K)	С

Site Name or Industry Type if Client Identity Confidential:			
Location:	Project Took Place at Site Named	At another Site (i.e., a Test Facility)	
City	Yes	Yes	
State/Province:	No	No	
Country			
Regulatory Authority or Statute	Application Type	(Check only one)	
(Check all that apply) RCRA Corrective Action CERCLA TSCA Safe Drinking Water Act UST Corrective Action State (specify): Other (Specify): Not Applicable	Full-Scale Cleanup Field Demonstration Pilot-Scale Treatability Study Bench-Scale Treatability Study TSCA National Demonstration TSCA Research and Development EPA SITE Demonstration Program	EPA SITE Emerging Technology Program Research Other (specify):	
Media Treated (Check all that apply)	Contaminant Group Trea	ted (Check all that apply)	
Soil (in situ) Soil (ex situ) Sludge Solid Natural Sediment (in situ) Natural Sediment (ex situ) Ground Water In Situ Off-gas from a primary treatment technology Equipment Scale (Check one only) Bench Pilot Full	Organic Halogenated Volatiles Halogenated Semivolatiles Nonhalogenated Volatiles Nonhalogenated Semivolatiles Organic Pesticides/Herbicides Dioxins/Furans PCBs Polynuclear Aromatics (PNAs) Solvents Benzene-toluene-ethylbenzene- xylene (BTEX) Acetonitrile Organic Acids	Inorganic Heavy Metals Nonmetallic Toxic Elements Radioactive Metals Asbestos Inorganic Cyanides Inorganic Corrosives Miscellaneous Explosives/Propellants Organometallic pesticides/ herbicides	
Volume/Quantity:(Units)	Person outside of company familiar with pro	ject (optional): Company:	
Project Status	Address:		
Contracted:	Is Literature Available on this Project? (Include	citations in Part 7)	
Month Year	Yes	No	
In Cleanup: Yes No	Additional Project Information:		
Completed:			
Month Year			

Vendor Name:	
Technology Type:	

40d.

I anaklam.	Design Took Bloom A Older Mark	As a superior Otto O
Location:	Project Took Place at Site Named	At another Site (i.e., a Test Facility)
City	Yes	Yes
State/Province:	No	No
Country	_	
Regulatory Authority or Statute	Application Type	(Check only one)
(Check all that apply) RCRA Corrective Action CERCLA TSCA Safe Drinking Water Act UST Corrective Action State (specify): Other (Specify):	Full-Scale Cleanup Field Demonstration Pilot-Scale Treatability Study Bench-Scale Treatability Study TSCA National Demonstration TSCA Research and Development EPA SITE Demonstration Program	EPA SITE Emerging Technology Program Research Other (specify):
Not Applicable Media Treated (Check all that apply)	Contaminant Group Treat	ted (Check all that apply)
Soil (in situ) Soil (ex situ) Sludge Solid Natural Sediment (in situ) Natural Sediment (ex situ) Ground Water In Situ Off-gas from a primary treatment technology Equipment Scale (Check one only) Bench Pilot Full	Halogenated Volatiles Halogenated Semivolatiles Nonhalogenated Volatiles Nonhalogenated Semivolatiles Organic Pesticides/Herbicides Dioxins/Furans PCBs Polynuclear Aromatics (PNAs) Solvents Benzene-toluene-ethylbenzene- xylene (BTEX) Acetonitrile Organic Acids	Inorganic Heavy Metals Nonmetallic Toxic Elements Radioactive Metals Asbestos Inorganic Cyanides Inorganic Corrosives Miscellaneous Explosives/Propellants Organometallic pesticides/ herbicides
Volume/Quantity:	Person outside of company familiar with pro	-
Project Status	Address:	Company:
Contracted:	Is Literature Available on this Project? (Include	citations in Part 7)
MonthYear	Yes	No
In Cleanup: Yes No	Additional Project Information:	
Completed:		
MonthYear		

Vendor Name:	
Technology Type:	

40e.

Location:	Project Took Place at Site Named	At another Site (i.e., a Test Facility)	
City	Yes	Yes	
State/Province:	No	No	
Country	_		
Regulatory Authority or Statute	Application Type	(Check only one)	
(Check all that apply) RCRA Corrective Action CERCLA TSCA Safe Drinking Water Act UST Corrective Action State (specify): Other (Specify):	Full-Scale Cleanup Field Demonstration Pilot-Scale Treatability Study Bench-Scale Treatability Study TSCA National Demonstration TSCA Research and Development EPA SITE Demonstration Program	EPA SITE Emerging Technology Program Research Other (specify):	
Not Applicable			
Media Treated (Check all that apply)	Contaminant Group Trea	ted (Check all that apply)	
Soil (in situ) Soil (ex situ) Sludge Solid Natural Sediment (in situ) Natural Sediment (ex situ) Ground Water In Situ Off-gas from a primary treatment technology Equipment Scale (Check one only) Bench Pilot Full	Halogenated Volatiles Halogenated Semivolatiles Nonhalogenated Volatiles Nonhalogenated Semivolatiles Organic Pesticides/Herbicides Dioxins/Furans PCBs Polynuclear Aromatics (PNAs) Solvents Benzene-toluene-ethylbenzene- xylene (BTEX) Acetonitrile Organic Acids	Inorganic Heavy Metals Nonmetallic Toxic Element Radioactive Metals Asbestos Inorganic Cyanides Inorganic Corrosives Miscellaneous Explosives/Propellants Organometallic pesticides/ herbicides	
Volume/Quantity:	Person outside of company familiar with project (optional):		
Project Status	Address:	Company:	
Contracted:	Is Literature Available on this Project? (Include citations in Part 7)		
MonthYear	Yes	No	
n Cleanup: Yes No	Additional Project Information:		
Completed:			

/endor Name:	· · ·		
rechnology Type:		····	

PART 7: LITERATURE AND TECHNICAL REFERENCES

41. List and attach available documentation (e.g., journal articles, conference papers, patents) that best describes technology and vendor capabilities. Avoid listing references that contain the same data. Do not include personal references. EPA reserves the right to add to the list other publicly available references. EPA will abstract references and include in the Alternative Treatment Technology Information Center (ATTIC) operated by the Office of Research and Development.

	Author(s):	
	Title:	
	Journal/Conference:	
	Date:	NTIS/EPA Document Number(s):
	Author(s):	
	Title:	
	Journal/Conference:	
	Date:	NTIS/EPA Document Number(s):
	Author(s):	
	Title:	
	Journal/Conference:	
	Date:	NTIS/EPA Document Number(s):
	Author(s):	
	Title:	
	Journal/Conference:	
	Date:	NTIS/EPA Document Number(s):
	Author(s):	
	Title:	
	Journal/Conference:	
Ì	Date:	NTIS/EPA Document Number(s):

APPENDIX E - INSTRUCTIONS FOR FILING BY COMPUTER DISKETTE

Mail Completed VIF Diskette and Hard Copy To: PRC Environmental Management, Inc., VISITT System Operator, 1505 PRC Drive, McLean, VA 22102

This appendix explains the use of the enclosed vendor information software package for applicants to the U.S. Environmental Protection Agency's (EPA) Vendor Information System for Innovative Treatment Technologies (VISITT). The enclosed software enables VISITT participants to complete the Vendor Information Form (VIF).

The software produces a form that looks similar to the blank form in Appendix D.

HARDWARE REQUIREMENTS

An IBM compatible microcomputer with the following characteristics is necessary to operate the enclosed software:


- DOS 3.3 or higher and Files = 45 in config.sys
- A floppy disk drive for 3-1/2-inch double density diskette
- At least 640K of random access memory (RAM)
- Any conventional printer (optional)

STARTING THE SOFTWARE

Insert the disk into the appropriate disk drive. If your 3-1/2-inch floppy disk drive is drive A:, type A:, press <Enter>, then at the A: prompt, type VENDOR. If your 3-1/2-inch disk drive is drive B:, type B:, press <Enter>, and then at the B: prompt, type VENDOR. The main menu will appear on your screen.

ENTERING INFORMATION

- From the main menu, you will be able to choose any
 of the options by using the left and right arrows on
 your keyboard and by pressing <Enter> while the
 cursor is positioned on an option you want.
- At the bottom of each screen, you will find the functions you can perform on that screen and their corresponding keys.
- The screen will prompt you when you can press the function one <F1> key for on-line help.
- The escape key <Esc> will take you back to the previous screen. The arrow keys will move the cursor to any available position on the screen.
- The function ten <F10> key selects chemicals and assigns them to the appropriate contaminant group.



Main Menu

When you are completing the information for the vendor form, you can choose one of four options: view <V>, add <A>, edit <E>, or delete <D>. These options will appear at the top of the screens and you may choose whichever is appropriate. The page up <PgUp> and page down <PgDn> keys will allow you to move within the form once <V>, <A>, or <E> is chosen. By pressing <Esc>, you will return to the viewing mode.

PRINTING FORMS

The VIF software has many print options. By moving the cursor to the print menu in the main menu, you can print the following:

- A VIF for a specific technology
- All completed VIFs
- A blank VIF

We recommend that you print out the VIF(s) for your own files, as well as for EPA submittal after completing the information.

EXITING THE SOFTWARE

If you press <Esc> to return to the VIF software's main menu, you can exit by either pressing <Q>, or <Esc> and then <Enter>.

OTHER INFORMATION

You can copy the VIF software onto your computer's hard drive by inserting the disk(s) into the floppy drive and by using the appropriate DOS copy command. This will allow you to save a copy of the software and your files.