MTR-7144

Air Pollution Assessment of Carbon Tetrachloride

RICHARD JOHNS

FEBRUARY 1976

MITRE

Air Pollution Assessment
of Carbon Tetrachloride

RICHARD JOHNS

FEBRUARY 1976

Department Approval. _____

MITRE Project Approval: _____

ABSTRACT

This report concerns the organochlorine solvent carbon

tetrochloride, which is used primarily in the manufacture of

fluorocarbons. The toxic effects of the solvent in both animals

and man are discussed and the probability of those effects

occurring at the ambient atmospheric concentrations to which

the general population is exposed is assessed. Methods for

atmospheric sampling of carbon tetrachloride and available

control technology for the prevention of release to the

environment are also discussed.

ACKNOWLEDGEMENTS

TABLE OF CONTENTS

LIST OF FIGURES

LIST OF TABLES

I. SUMMARY AND CONCLUSIONS

Carbon tetrachloride is a colorless, nonflammable liquid, possessing excellent solvent properties for fats, oils, plastics and many organic chemicals. It is not highly reactive and is neither oxidized readily in air nor hydrolyzed rapidly in water. The chemical is decomposed to toxic products such as hydrogen chloride and phosgene on contact with hot metal. It is estimated to have a half-life of 10 to 33 weeks toward atmospheric photodegradation. An octanol/water distribution coefficient of 2.64 indicates a mild tendency for carbon tetrachloride accumulation in body lipids.

Depending upon the organism and route of administration, certain concentrations of carbon tetrachloride result in toxic, carcinogenic, or mutagenic activity in mammals, the liver being the primary center of damage. Hepatotoxicity of the compound is enhanced by certain dietary factors, particularly alcohol ingestion. The chemical is absorbed through the lungs and from the gastrointestinal tract, but only marginally through the skin. Carcinogenic studies using laboratory animals have shown tumors of the liver to result from repeated oral and subcutaneous administration of the chemical. The appearance of hepatomas in man, several years after carbon tetrachloride poisoning, has been reported in several cases. Several biochemical indices have been developed recently which forewarn of clinical symptoms of chronic exposure to carbon tetrachloride. The American Conference of Govern-

mental Industrial Hygienists has recommended a threshold limit value of 65 mg/m^3 (10 ppm), which has been adopted by the Occupational Safety and Health Administration (OSHA) as a maximum 8-hour-average level for workplace atmospheres. The odor threshold of carbon tetrachloride is about 500 mg/m^3 and, hence, is entirely inadequate as a signal of danger.

Ambient data on localized carbon tetrachloride concentrations are sparse; hence, population exposure is not widely assessable from experimental data. A study in the Los Angeles Basin revealed an atmospheric concentration range of 1 to 2 µg/m^3 over 54 ground-level stations, with an excursion to 10 µg/m^3 at one site. Analytical measurements were made using a gas chromatograph equ_pped with an electron capture detector. This is the method of choice for halo-hydrocarbons, and is capable of detecting carbon tetrachloride at the parts-per-billion level.

Exposure over a 75-year lifetime to the 2 µg/m^3 level of carbon tetrachloride found in the Los Angeles Basin is approximately equivalent to one day's occupational exposure at the OSHA limit of 65 mg/m^3. The atmospheric concentration of the chemical near production facilities may be estimated with an atmospheric diffusion model. For a typical carbon tetrachloride plant, an atmospheric concentration of 1.4 mg/m^3 at a point 500 meters downwind of the plant is developed. Exposure to this concentration over a 75-year lifetime is equivalent in dose to

a 7-year occupational exposure at the OSHA limit for workroom atmospheres. The downwind distance of 500 meters is representative of a location near the property line of a production facility.

Population exposure may arise from dispersive uses of carbon tetrachloride, but levels of exposure are unknown. The use of the product as a fumigant for rodents carries the potential for exposure of building occupants, neighbors, and bystanders. Solvent use has declined and carbon tetrachloride is no longer generally available as a consumer product. The high vapor density of this compound warrants concern for localized ground-level vapor sinks which may accumulate hazardous levels of carbon tetrachloride. Such sinks can be envisioned, for example, in basements of buildings undergoing fumigation.

The chemical can enter the environment through various routes. Losses to the atmosphere are possible in the production, handling, and distribution of carbon tetrachloride. Dispersive uses of the chemical contribute further to the atmospheric burden, although they account for only a small fraction of consumption. Carbon tetrachloride is ubiquitous in the troposphere, and global studies indicate a natural occurrence of the compound. At an altitude of 5 to 10 km, the background is typically 0.5 to 1.0 $\mu g/m^3$ carbon tetrachloride. From global atmospheric measurements, it can be estimated that the worldwide atmospheric burden exceeds the total production of carbon tetrachloride during this century by at least twentyfold, thus indicating the likelihood of a non-industrial source. The compound has been found in a variety of

environmental samples at the parts-per-billion level, but no significant accumulation in the food chain has been shown.

Carbon tetrachloride is produced at 11 plant sites in the United States, largely concentrated in the Gulf Coast area. The compound ranks as a major industrial chemical, with annual production in excess of one billion pounds. The bulk of carbon tetrachloride production (95 percent in 1973) is used in the manufacture of fluorocarbons (trichlorofluoromethane and dichlorodifluoromethane); hence, the market is highly sensitive to the demand for aerosol products. Demand grew at a rate of 6.8 percent per year from 1960 to 1970, but has shown a leveling trend due to slowing growth of aerosol products. Should the use of fluorocarbon propellant be banned in the future, demand for carbon tetrachloride could be expected to diminish to about 45 percent of its current level.

Two critical considerations in the air pollution assessment of carbon tetrachloride are: (1) accumulation of man-made residues of the chemical in the upper atmosphere, and (2) exposure risk in the vicinity of sources of the chemical. The latter consideration relates directly to the health of population groups near sources, whereas the former concerns the steady-state composition of the troposphere and attendant health effects. Occupational and consumer exposure to carbon tetrachloride vapor are not air pollution problems in a strategic sense.

The evidence for natural sources of carbon tetrachloride implies

that the relative atmospheric contribution from anthropogenic sources is minor. Based on available evidence, there appears no need for additional control of carbon tetrachloride emissions so far as the total atmospheric sink is concerned.

Measured concentrations of carbon tetrachloride in urban atmospheres, as well as estimated levels near production facilities, are not significantly greater than the worldwide background of 0.5 to 1.0 $\mu g/m^3$. These levels are about five orders of magnitude below the threshold limit value and, hence, pose no probable risk to local populations near sources.

The risk from dispersive applications of carbon tetrachloride is difficult to control. The threshold limit value is exceeded by the evaporation of one milliliter of the solvent into a 3-meter cubical room.

Carbon tetrachloride and other chlorohydrocarbons are scheduled for study by the National Institute for Occupational Safety and Health during 1976. Occupational risk will be the primary focus of this work, but "fenceline" measurements may be included in the study. A study of the carcinogenic potential of carbon tetrachloride is in progress at the National Cancer Institute.

II. AIR POLLUTION ASSESSMENT REPORT

A. PHYSICAL AND CHEMICAL PROPERTIES

Carbon tetrachloride is a colorless, nonflammable liquid, possessing excellent solvent properties for fats, oil, plastics, rubber, and many organic chemicals. The principal physical properties of the compound are shown in Table I. The chemical shows no oxygen uptake in the standard BOD test*, nor is it readily decomposed by photodegradation. Carbon tetrachloride is estimated to have a half-life of 10 to 33 weeks toward atmospheric photodegradation (1). The vapor is decomposed above 200°C into hydrogen chloride, chlorine, phosgene and other products. The production of toxic degradation is enhanced by the presence of hot metal; hence, the former use of the chemical in small fire extinguishers has been abandoned. At 250°C, carbon tetrachloride becomes an active chlorinating agent for oxides of metals such as aluminum and zinc.

Carbon tetrachloride hydrolyzes very slowly in contact with water, showing a half-life of 70,000 years at a pH of 1.0 to 7.0. Hydrolysis is accelerated by the presence of iron, zinc, and other metals. The chemical is inert to strong acids, but is decomposed by strong alcholic alkali or strong bases to simple inorganic products. An octanol/water partition coefficient** of 2.64 (Table I) indicates a mild tendency

---

*Biochemical Oxygen Demand. A measurement of oxygen consumption during controlled biochemical degradation.
**A partition coefficient expresses the equilibrium concentration ratio of a solute between two phases which are in mutual contact.

TABLE I

CARBON TETRACHLORIDE

Physical Properties

Chemical Formula	CCl_4
Molecular Weight	153.84
Boiling Point	$76.9^{\circ}C$
Melting Point	$-22.9^{\circ}C$
Vapor Pressure, $25^{\circ}C$	115.2mm Hg
Specific gravity, liquid	1.589
Specific gravity, vapor vs. air	5.32
Refractive Index, $20^{\circ}C$	1.4607
Solubility, Water	0.8 g/l
Solubility, Octanol	∞
Partition Coefficient, Octanol/Water	2.64
Partition Coefficient, Water/Air, V/V, $20^{\circ}C$	1.1

Sources: Kirk, R. E. Encyclopedia of Chemical Technology, Second Edition. New York, Wiley, 1968.

National Science Foundation Panel on Manufactured Organic Chemicals, SRI Data, 1975.

for carbon tetrachloride accumulation in body lipids. Carbon tetrachloride shows a water/air partition coefficient of 1.1, expressed in terms of volume. This indicates that the chemical is slightly more soluble in air than in an equal volume of water. In terms of mass, this indicates that the chemical is about 1,000 times more soluble in air than in water. Reduced to practical considerations, a body of water swept with air will tend to transfer its carbon tetrachloride content to the air phase, which will be the primary medium of environmental transport.

B. EFFECTS

Carbon tetrachloride has been shown to be toxic to mammals by a variety of exposure routes. It is readily absorbed in the mammalian gastrointestinal tract or lung, while little dermal absorption occurs. The absorption rate of ingested carbon tetrachloride is greatly affected by the diet; ethanol consumption or high-fat diets will greatly enhance carbon tetrachloride uptake (2). Any absorbed carbon tetrachloride will be metabolized, though rather slowly, in the liver. This slow rate of degradation is thought to be a primary factor in the toxicity of carbon tetrachloride (3). The liver and kidney are usually the first organs to evidence dysfunction or destruction as a result of carbon tetrachloride exposure by ingestion or inhalation (2). Because of the rather slow degradation rate, repeated exposure to carbon tetrachloride, even at low doses, becomes significant. The relative acute toxicity of carbon tetrachloride to selected mammalian species is shown in Table II, emphasizing variability in terms of species, routes of administration, and exposure period.

The American Conference of Governmental Industrial Hygenists (ACGIH) has recommended a threshold limit value (TLV)* for carbon tetrachloride in the workplace of 65 mg/m^3 (10 ppm). The odor threshold of carbon tetrachloride is approximately 500 mg/m^3 and, hence,

---

*The minimum concentration known to produce a physiological response.

TABLE II

ACUTE TOXICITY OF CARBON TETRACHLORIDE

ANIMAL	ROUTE	DOSE	DOSAGE	LENGTH OF EXPOSURE	REFERENCE
Rat	Inhal.	LC_{50}	2515 mg/m^3	7 hr/day; 5 day/wk	Adams et al, Arch. Ind. Hyg. Occ. Med. 6; 50 (1952)
	Inhal.	MLC	150 g/m^3	30 min.	Spiegel et al, AEC Report #MODC-1715 (1947/48)
	Inhal.	LC_{50}	50 g/m^3	4 hr.	Tox. Appl. Pharm. 18; 168 (1971)
	Oral	LD_{50}	7460 mg/kg		Smyth, unpb. data, Mellon Institute
	Oral	LD_{50}	2920 mg/kg		McCollister, et al, Arch. Ind. Hyg. 13; 1 (1956)
Mouse	Inhal.	MLC	51 g/m^3	104 min.	Muller, Arch. Exp. Path. Pharm. 109; 276 (1925)
	Oral	MLD	6000 mg/kg		J. Nat. Can. Inst. 30; 837 (1963)
	Oral	LD_{50}	12800 mg/kg		Dybing, Acta pharm 2; 233 (1946)
	SC	LD_{100}	3554 mg/kg		Rothschild, Hospital 27; 1017 (1945)
Hamster	Oral	MLD	320 mg/kg		Fuhner, Arch. Exp. Path. Pharm. 97; 86 (1923)
Rabbit	Oral	LD	6380-9975 mg/kg		Lamson, J. Pharm. Exp. Ther. 22; 215 (1923)
	Oral	LD	900-10,700 mg/kg		Fuhner, op. cit.
Cat	Inhal.	MLC	90 g/m^3	70 min.	Reuss, Thesis, Worzburg (1932)
	SC	LD_{33}	4785 mg/kg		Cantarow, et al, J. Pharm. Exp. Ther. 63; 153 (1938)
Dog	Oral	MLD	4000 mg/kg		Barsocm et al, Qtly. J. Pharm. 7; 205 (1935)
	Oral	LD	25000 mg/kg		Lamson, op. cit.
	IV	MLD	125 mg/kg		Barsoom, op. cit.
Human	Inhal.	MLC	125 mg/m^3		Elkins, Chem. of Ind. Tox. 2nd Ed., Wiley N.Y.
	Inhal.	MLC	6288 mg/m^3		Amer. Pest Cent., Inc., Kansas, (1966)

Inhal. - Inhallation
SC - subcutaneous
IV - intravenous
LC - lethal concentration
LD - lethal dose
MLD - minimum lethal dose
MLC - minimum lethal concentration
LC_{50} - concentration lethal to 50 percent of a sample population under stated experimental conditions.

LD_{50} - dose fatal to 50 percent of a sample population under stated experimental conditions.

LD_{100} - dose fatal to 100 percent of a sample population under stated experimental conditions.

would certainly not be considered a satisfactory warning of excessive
exposure.

Exposure to carbon tetrachloride in laboratory animals, including
rats, mice, and hamsters, resulted in liver tumors following a variety
of routes of administration including inhalation, ingestion, sub-
cutaneous, and intrarectal. One oral dose study on dogs was negative
and a trout study gave borderline results. There is no evidence of
carcinogenicity to any other organ than the liver, although most
studies were shorter than the life-spans of the animals and tumors
in other organs cannot be ruled out. In humans, no long-term follow-up
study has been reported. Cases of liver tumors in man, following acute
poisoning, have been reported (4). While the results cannot be dis-
missed, their significance is to date unclear. Positive indications
of the mutagenicity of carbon tetrachloride have been reported (5).
The possible teratogenicity of carbon tetrachloride remains in ques-
tion.

There is evidence that potentiation may occur between effects of
carbon tetrachloride exposure and other stresses. Alcohol consumption,
food composition, drug use (especially barbituates), and non-specific
environmental stresses are known to potentiate carbon tetrachloride
damage in mammals (2,6,7). In contrast, diets rich in certain vitamins
or amino acids (notably sulfhydryl-containing compounds) may offer
some degree of protection from liver damage resulting from carbon
tetrachloride exposure (2).

11

Several biochemical indices (e.g., serum iron levels, glutamate dehydrogenase activity) have been developed recently that provide indications of past carbon tetrachloride exposure in industrial workers. Such tests forewarn the appearance of the more conventional clinical symptoms of hepatotoxicity (2).

The physical properties of carbon tetrachloride (high vapor pressure and low solubility) should permit some degree of environmental transport, with the majority of movement occurring in the vapor phase. Biochemical degradation occurs to a limited degree in mammalian systems, with major metabolites being chloroform ($CHCl_3$) and carbon dioxide (CO_2). However, no evidence of carbon tetrachloride degradation by microbial action has been found. Carbon tetrachloride shows no oxygen consumption in the standard BOD test (8).

Carbon tetrachloride has been found in a variety of environmental samples at the µg/kg range or lower (see Table III). Sediment samples have not shown any tendency to concentrate carbon tetrachloride to any appreciable degree above the level found in the surrounding water. Bioaccumulation in marine life does not appear to be a problem (bioconcentration factor of 20 in rainbow trout). Observed carbon tetrachloride concentrations vary from 1 µg/kg in fish flesh, to a maximum of 50 µg/kg in seabird eggs and seal blubber. Analyses of a variety of foodstuffs indicate the presence of carbon tetrachloride at levels comparable to those found elsewhere in the environment (see Table IV). It should be noted that cereal grains which have been recently fumi-

12

TABLE III

TYPICAL CONCENTRATIONS OF CARBON TETRACHLORIDE IN THE ENVIRONMENT

	RANGE (μg/kg wet)
Rainwater	0.01 – 1
Surface water	0.01 – 1
Potable water	0.01 – 1
Seawater	0.1 – 1
Marine sediments	0.1 – 1
Marine invertebrates	1 – 10
Fish	1 – 10
.Waterbirds	1 – 100
Marine mammals	1 – 10
Fatty foods	1 – 10
Non-fatty foods	1
Human organs	1
Human body fat	1 – 10

Source: McConnell, G., D. M. Ferguson, and C. R. Pearson. "Chlorinated Hydrocarbons and the Environment." Endeavour, January 1975, p. 13-18.

TABLE IV

OBSERVED CARBON TETRACHLORIDE CONCENTRATIONS IN FOODSTUFFS

	RANGE (ug/kg wet)
Dairy produce	0.2 - 14
Meat	7 - 9
Oils & Fats	0.7 - 18
Beverages	0.2 - 6
Fruit & vegetables	3 - 20

Source: McConnell, G., D. M. Ferguson, and C. R. Pearson. "Chlorinated Hydrocarbons and the Environment." Endeavour, January 1975, p. 13-18.

gated with carbon tetrachloride can contain residues as high as 60 mg/kg, while dairy cows under treatment with a carbon tetrachloride anthelmintic preparation can produce milk containing carbon tetrachloride in concentrations of up to 3 mg/kg (9). In both these instances, dietary intake of carbon tetrachloride can be greatly diminished if adequate time passes (in storage, handling, and processing) between treatment and ingestion. Observed levels of carbon tetrachloride in human tissues have not indicated any inordinate accumulation. As with other chlorinated hydrocarbons, carbon tetrachloride tends to be lipid-soluble, but available evidence indicates no bioaccumulation of carbon tetrachloride in fatty tissues beyond a factor of about 20 over levels found in kidney, liver, brain, and other tissues (1). A 96-hour LC_{50}* of approximately 50 mg/1 has been reported in fish (8).

*Lethal Concentration-50. Concentration lethal to 50 percent of sample population, after 96 hours of exposure.

15

C. AMBIENT CONCENTRATIONS, POPULATION AT RISK AND MEASUREMENT
    TECHNOLOGY

Carbon tetrachloride has been monitored extensively in plant

atmospheres, and an industrial standard of 65 mg/m^3 8-hour-average

daily exposure has been adopted by the Occupational Safety and Health

Administration. The chemical is not routinely monitored in ambient

air, and only sparse data are available on atmospheric concentrations

in population centers. One study in the Los Angeles Basin reveals a

concentration range of 1 to 2 μg/m^3 over 54 ground-level sampling stations

in the area, with an excursion to 10 μg/m^3 near Carson (10). This

latter station was possibly located near a source of the material.

Atmospheric concentrations of carbon tetrachloride downwind of

production facilities may be estimated from hypothetical plant para-

meters, when analytical measurements are lacking. The total atmo-

spheric release of the chemical from the 11 production facilities in

the United States is estimated to be 15 million pounds per year (5).

Hypothetical plant conditions could be used as inputs to a Gaussian

plume equation* from Turner's Workbook of Atmospheric Disperson Esti-

mates (11). The basic diffusion equation should be modified, however,

due to the effect of the plant itself on the flow of air. Mechanical

---

*Ground-level downwind concentrations resulting from a point source
 are predicted by the following equation:

$$\chi(x, 0, 0; H) = \frac{Q}{\pi \sigma_y \sigma_z u} \exp\left[-1/2 \left(\frac{H}{\sigma_z}\right)^2 \right]$$

turbulence in the wake of a building tends to produce aerodynamic downwash, resulting in the fairly rapid diffusion of a gaseous emission down to the ground. This region of disturbed flow extends downwind a distance equal to several times the height of the building. While this situation does not result in a Gaussian-distributed plume, it is proposed that a modification of the usual formula still can be employed. This is because the turbulent mixing in the wake of the building is assumed to be distributed uniformly in the vertical direction, analogous to the situation where a plume is trapped below an inversion layer. A limited vertical mixing height can be modeled using the equation:

$$\chi(x, 0, z; H) = \frac{Q}{\pi\sigma_y u \ (.8L)}$$

where: Q = uniform emission rate (grams/sec)
  u = mean wind speed affecting the plume (meters/sec)
  H = effective stack height; that is, sum of stack height plus plume rise (meters)
  σ_y = horizontal dispersion coefficient evaluated in terms of downwind distance to the point for which the concentration is being computed (meters)
  σ_z = vertical dispersion coefficient evaluated in terms of downwind distance to the point for which the concentration is being computed (meters)
  L = the vertical limit of the mixing depth

In the case of an isolated rectangular building, it is assumed that L equals 1.5 times the building height.

In addition, there is a horizontal wind turbulence which is assumed to result in an initial horizontal plume spread equal to the width of the building normal to the wind direction. This is analogous

to an area source emission where the area source is the building top. This can be modeled using a further modification of the basic Gaussian diffusion equation. A virtual point source is assumed upwind from the building at a distance where the plume spread (for the given stability conditions) would equal the crosswind width of the building. The modified diffusion equation is therefore:

$$\chi(x,\ 0,\ z;\ H)\ =\ \frac{Q}{\pi\sigma_y'\ u\ (1.2h)}$$

where H is the building height and σ_y' is based on the downwind distance to the receptor point plus the upwind distance to the virtual point source.

Based on the production losses of individual carbon tetrachloride plants and the assumption that these plants operate 360 days per year and 24 hours per day (assuming 5 days/year downtime), it has been computed that a typical plant would have a carbon tetrachloride emission rate of 20 grams per second. Using the modified diffusion equation, the ambient carbon tetrachloride concentration 500 meters downwind from the release point was calculated to be approximately 1.4 mg/m^3.* The downwind distance of 500 meters from the source was chosen to represent a point within the perimeter of a plant, and ambient concentrations in surrounding neighborhoods could be expected to be

---

*Additional assumptions: (1) carbon tetrachloride is nonreactive; (2) building height is 50 feet (15.24 meters), and its width equals 100 feet (30.48 meters); (3) stability class is neutral; (4) wind speed is 6 meters/sec.

significantly lower. The predicted value exceeds background levels measured in the Los Angeles basin by about one thousandfold.

The global atmospheric concentration of carbon tetrachloride is reported to be 0.5 to 1.0 $\mu g/m^3$ at 5 to 10 km altitude (12). The predicted ground-level concentration 500 meters downwind of a plant may exceed this background level by a factor of 1500. There exists no ambient standard for carbon tetrachloride at present, but it is an interesting observation that a resident 500 meters downwind of a plant would receive, in a 75-year lifetime, an exposure equivalent to that of an industrial worker in 7 years of work at the maximum legal occupational level.

The global atmospheric carbon tetrachloride concentration appears to be surprisingly constant (12). The hemispheric concentrations are quite similar, even through the majority of production and use of carbon tetrachloride occurs in the Northern Hemisphere. In addition, carbon tetrachloride does not follow the atmospheric patterns of the other halogenated hydrocarbons (of anthropogenic origin) which tend to occur in clearly defined global isopleths surrounding industrial regions of the world. Finally, the total atmospheric amount of carbon tetrachloride appears to be in excess of those industrial releases of the chemical, even if one assumes no loss through degradation. For these reasons, a natural source of carbon tetrachloride has been suggested, possibly a reaction in the troposphere of methane with chlorine in a complex sequence of reactions. Preliminary laboratory studies

have shown that the reaction in air of methane (CH_4) and chlorine (Cl_2) results in the production of small but significant quantities of carbon tetrachloride (13).

In addition, it is postulated that the chemical may be synthesized by certain forms of vegetation. The entire industrial production of carbon tetrachloride during the twentieth century can account for only two to five percent of the worldwide background concentration (12).

Chemical analysis of carbon tetrachloride at trace levels is well established. Early techniques depended on pyrolytic decomposition of the airborne sample, followed by conventional analysis for liberated chloride. Modern gas chromatographic techniques using an electron capture detector are capable of quantitative analysis for atmospheric carbon tetrachloride at the parts-per-trillion level. Colorimetric and polarographic procedures have also been reported which are suitable for the analysis of environmental and physiological samples of the chemical.

D. SOURCES

Domestic production of carbon tetrachloride was slightly in ex-
cess of one billion pounds in 1974, having shown an average growth
rate of 6.8 percent throughout the previous decade (14). Demand is
estimated to remain at the billion-pound-per-annum level for the 1974-
75 period and future growth is uncertain. The carbon tetrachloride
market is closely tied to sales of aerosol products, since 95 percent
of demand is for the synthesis of fluorocarbon gases and the bulk of
these materials is used for aerosol can propellants. The leveling of
carbon tetrachloride demand reflects a declining trend in aerosol
sales, following a decade of strong growth. Should the use of fluoro-
carbon propellant be banned in the future, carbon tetrachloride demand
could be expected to drop to about 45 percent of its current level.

Carbon tetrachloride production capacity is estimated to exceed
current demand by about 50 percent, although plant facilities are
generally adaptable to the synthesis of other chlorinated solvents.
Certain facilities, known as "swing" plants, are designed to produce
carbon tetrachloride and perchloroethylene in variable ratios. The
operator may elect to vary the product mix by as much as 50 percent.
There are 11 carbon tetrachloride production facilities in the
United States, with a total capacity of 1.5 billion pounds per year,
located as shown in Figure 1. Detailed supporting data are shown in
Table V. Estimates of plant capacity may be misleading, since the
proportion of "swing" plants is unknown. Foreign trade in carbon

FIGURE 1
**CARBON TETRACHLORIDE PRODUCTION CAPACITY**

⬤ = 100 Million Pounds/year

TABLE V

CARBON TETRACHLORIDE PRODUCTION DATA

PRODUCER	LOCATION	CAPACITY Million Lbs./yr.
Allied Chemical	Moundsville, WV	8
	Freeport, TX	130
	Pittsburg, CA	45
	Plaquemine, LA	100
DuPont	Corpus Christi, TX	500
FMC Corporation	S. Charleston, WV	300
Stauffer Chemical	LeMoyne, AL	200
	Louisville, KY	70
	Niagara Falls, NY	150
Vulcan Chemicals	Geismar, LA	35
	Wichita, KS	40

Total Capacity   1,578

Total Production (1973) 1,047

Source: Stanford Research Institute, Directory of Chemical Producers. Menlo Park, 1975.

tetrachloride appears to be a minor factor in the domestic supply
of the material.

Dispersive uses account for 5 percent of carbon tetrachloride
production, or about 50 million pounds per year. The chemical is used
as a grain fumigant, cleaning agent, rodenticide, anthelmintic, and
specialty solvent. Such applications provide direct entry of carbon
tetrachloride to the atmosphere. Production losses are estimated to
release an additional 15 million pounds per year of the chemical to
the environment. Commercial demand for carbon tetrachloride is outlined
in Figure 2 and summarized in Table VI.

FIGURE 2
CARBON TETRACHLORIDE—COMMERCIAL PATHWAYS
(1973 DATA)

SURPLUS - 4%
58 MILLION LBS/YEAR

IMPORTS ≅ EXPORTS

DISPERSIVE USES - 5%
49.5 MILLION LBS/YEAR

GRAIN FUMIGANT

RODENTICIDE

TOTAL U.S.
PRODUCTION
1047.3

MILLION LBS/YEAR

TOTAL U.S.
CONSUMPTION
989.3

MILLION LBS/YEAR

SOLVENT

CAPTIVE
USES
95%

PRODUCTION LOSSES 1.5%

DISTRIBUTION LOSSES
(NOT AVAILABLE)

16 MILLION LBS/YEAR

FLUOROCARBONS
939.8

MILLION LBS/YEAR

END
USES

AEROSOLS - 57%

563.9
MILLION LBS/YEAR

REFRIGERANT - 38%

375.9
MILLION LBS/YEAR

Source: National Science Foundation Panel on Manufactured Organic Chemicals, SRI Data, 1975.

25

TABLE VI

CARBON TETRACHLORIDE COMMERCIAL PATHWAYS

(U.S. Production 1.047 Billion Pounds, 1973)

INDUSTRIAL USES

	Percent	Amount (Million Lbs.)
Freon 11	56.1	587.8
Freon 12	37.4	391.8

DISPERSIVE USES

	Percent	Amount (Million Lbs.)
Grain Fumigant		
Rodenticide		
Anthelmintic	4.9	51.6
Cleaning Agent		
Solvent		

LOSSES

	Percent	Amount (Million Lbs.)
Production Losses	1.5	15.7
Distribution Losses		(not available)

Source: National Science Foundation Panel on Manufactured Organic
Chemicals, SRI Data, 1975.

E. CONTROL STRATEGY

Global studies of atmospheric carbon tetrachloride indicate background levels far in excess of those accountable to industrial sources. The industrial contribution to the atmosphere can account for only two to five percent of the worldwide background level, according to studies of Lovelock and Maggs (13).

The occupational hazard of carbon tetrachloride is well established, and industrial atmospheres are rigidly controlled with regard to solvent vapors. Local populations subjected to industrial losses or other significant emissions of carbon tetrachloride should be protected by control equipment at points of plant emissions. Sources can be controlled with gas scrubbers, adsorption filters, and condensors.

Dispersive applications of carbon tetrachloride probably account for the major occupational and population risks. The use of the material as an insect and rodent fumigant can be envisioned as an application which is inherently difficult to control. It is likely that carbon tetrachloride used in non-industrial applications is subject to no rigid standards for occupational safety or public exposure.

27

REFERENCES

1. McConnell, G., D. M. Ferguson and C. R. Pearson. "Chlorinated Hydrocarbons and the Environment". Endeavour, January 1975, p. 13-18.

2. Patty, F. A. Industrial Hygiene and Toxicology, second edition, pp. 1264-1268. Interscience, New York, 1963.

3. Lal, H., S. K. Puri and G. Fuller. "Enhanced Toxicity of Carbon Tetrachloride Inhalation after Phenoliarbital Pretreatment." Pharmacalogy Research 2 (2), 143-147 (1970).

4. Tracey, J. P., and Sherlock, P. "Hepatoma Following Carbon Tetra-chloride Poisoning." N.Y. State J. Med. 68, 2202 (1968).

5. National Science Foundation Panel on Manufactured Organic Chemicals in the Environment, SRI Data, 1975.

6. Yudina, T. V., and Y. V. Novikov. "Changes in the Permeability of Histohematic Barriers under the action of Chemical Environmental Factors. Gig. Sanit. 36 (11), 14-18 (1971).

7. Traiger, G. J., and G. L. Plaa. "Relation of Alcohol Metabalism to the Potentiation of Carbon Tetrachloride Hepatotoxicity Induced by Aliphatic Alcohols." J. Pharmacol Exp. Ther. 183 (3), 481-488 (1972).

8. Ouellette, R. P., The Mitre Corp., Personal Communication.

9. International Agency for Research on Cancer. IARC Monographs on the Evaluation of Carcinogenic Risk, 1, 53-60, 1972.

10. Simmonds, P. G., P. S. Kerrin, J. E. Lovelock, and F. H. Shair. "Distribution of Atmospheric Halocarbons in the Air Over the Los Angeles Basin." Atm. Envir. 8, 209-216 (1974).

11. Turner, D. B. Workbook of Atmospheric Dispersion Estimates. U.S. Department of Health, Education and Welfare, Revised 1969.

12. Lovelock, J. E. "Atmospheric Hydrocarbons and Stratospheric Ozone." Nature 252, 291-293 (1974).

13. Lovelock, J. E., R. J. Maggs, and R. J. Wade. "Halogenated Hydrocarbons In and Over the Atlantic." Nature 241, 194-196 (1973).

14. Stanford Research Institute, Chemical Economics Handbook. Menlo Park, 1973.

Additional Resources

American Conference of Governmental Industrial Hygenists. Documentation of the Threshold Limit Values for Substances in Workroom Air, Third Edition, Cincinnati, 1971.

American Society for Testing and Materials. Instrumentation for Monitoring Air Quality, Special Technical Publication 555, Philadelphia, 1974.

Bond, Richard G., and Conrad P. Straub, Handbook of Environmental Control. Chemical Rubber Company, Cleveland, 1972.

Chemical Marketing Reporter, 202 (7), 9 (1975).

Danielson, J. A. Air Pollution Engineering Manual. Environmental Protection Agency, Research Triangle Park, N.C., 1973.

Kirk, R. E., Encyclopedia of Chemical Technology, Second Edition. New York, Wiley, 1968.

Liss, P. S., and P. G. Slater. "Flux of Gases Across the Air-Sea Interface." Nature 247:181-184 (1974).

Stanford Research Institute, Directory of Chemical Producers, Menlo Park, 1975.

Sunshine, Irving. Handbook of Analytical Toxicology. Chemical Rubber Company, Cleveland, 1969.

Tariff Schedules of the United States Annotated. United States International Trade Commission, Washington, 1975.

United States Department of Health, Education and Welfare. Survey of Compounds Which Have Been Tested for Carcinogenic Activity. Public Health Service Publication #149, 1971.

United States Department of Health, Education and Welfare. The Toxic Substances List. Public Health Service, National Institute for Occupational Safety and Health. Rockville, Maryland, 1973.

United States House of Representatives, Committee on Interstate and Foreign Commerce, Fluorocarbons - Impact on Health and Environment, HR 17577 and HR 17547. Government Printing Office, Washington, 1975.

United States Production and Sales of Miscellaneous Chemicals, 1973 Preliminary. United States International Trade Commission, Washington, 1975.

Additional Resources (Concluded)

Wilkness, P. E., R. A. Lamontagne, R. E. Larson, J. W. Swinnerton, C. R. Dickson and T. Thompson. "Atmospheric Trace Gases in the Southern Hemisphere." Nat. Phys. Sci. 245:45-47.

Von Oettingen, W.F. The Halogenated Hydrocarbons of Industrial and Toxicological Importance, pp. 107-174. Elsevier, Amsterdam, 1964.

TECHNICAL REPORT DATA
(Please read Instructions on the reverse before completing)

1 REPORT NO MTR-7144	2.	3 RECIPIENT'S ACCESSION·NO.
4. TITLE AND SUBTITLE Air Pollution Assessment of Carbon Tetrachloride		**5 REPORT DATE** February 1976
		6. PERFORMING ORGANIZATION CODE
7 AUTHOR(S) Richard Johns		**8. PERFORMING ORGANIZATION REPORT NO.**
9 PERFORMING ORGANIZATION NAME AND ADDRESS The Mitre Corporation McLean, Virginia 22101		**10 PROGRAM ELEMENT NO.**
		11. CONTRACT/GRANT NO. 68-02-1495
12 SPONSORING AGENCY NAME AND ADDRESS U. S. Environmental Protection Agency Office of Air and Waste Management Office of Air Quality Planning and Standards Research Triangle Park, North Carolina 27711		**13. TYPE OF REPORT AND PERIOD COVERED** Final
		14. SPONSORING AGENCY CODE EPA-AWM

15 SUPPLEMENTARY NOTES

16. ABSTRACT

This report concerns the organochlorine solvent carbon tetrochloride, which is used primarily in the manufacture of fluorocarbons. The toxic effects of the solvent in both animals and man are discussed and the probability of those effects occurring at the ambient atmospheric concentrations to which the general population is exposed is assessed. Methods for atmospheric sampling of carbon tetrachloride and available control technology for the prevention of release to the environment are also discussed.

17. KEY WORDS AND DOCUMENT ANALYSIS

a DESCRIPTORS	b. IDENTIFIERS/OPEN ENDED TERMS	c. COSATI Field/Group
Organic Compounds Hydrocarbons Organic Solvents Carcinogens Physiological Effects Fluorohydrocarbons Air Pollution Control Stationary Sources	Air Pollution	

18 DISTRIBUTION STATEMENT Unlimited	19 SECURITY CLASS *(This Report)* Unclassified	21 NO. OF PAGES 36
	20 SECURITY CLASS *(This page)* Unclassified	22 PRICE

EPA Form 2220-1 (9-73)

INSTRUCTIONS

1. **REPORT NUMBER**
   Insert the EPA report number as it appears on the cover of the publication.

2. **LEAVE BLANK**

3. **RECIPIENTS ACCESSION NUMBER**
   Reserved for use by each report recipient.

4. **TITLE AND SUBTITLE**
   Title should indicate clearly and briefly the subject coverage of the report, and be displayed prominently. Set subtitle, if used, in smaller type or otherwise subordinate it to main title. When a report is prepared in more than one volume, repeat the primary title, add volume number and include subtitle for the specific title.

5. **REPORT DATE**
   Each report shall carry a date indicating at least month and year. Indicate the basis on which it was selected *(e g , date of issue, date of approval, date of preparation, etc.)*.

6. **PERFORMING ORGANIZATION CODE**
   Leave blank.

7. **AUTHOR(S)**
   Give name(s) in conventional order *(John R. Doe, J. Robert Doe, etc)* List author's affiliation if it differs from the performing organization.

8. **PERFORMING ORGANIZATION REPORT NUMBER**
   Insert if performing organization wishes to assign this number.

9. **PERFORMING ORGANIZATION NAME AND ADDRESS**
   Give name, street, city, state, and ZIP code. List no more than two levels of an organizational hirearchy

10. **PROGRAM ELEMENT NUMBER**
    Use the program element number under which the report was prepared. Subordinate numbers may be included in parentheses.

11. **CONTRACT/GRANT NUMBER**
    Insert contract or grant number under which report was prepared.

12. **SPONSORING AGENCY NAME AND ADDRESS**
    Include ZIP code.

13. **TYPE OF REPORT AND PERIOD COVERED**
    Indicate interim final, etc., and if applicable, dates covered.

14. **SPONSORING AGENCY CODE**
    Leave blank.

15. **SUPPLEMENTARY NOTES**
    Enter information not included elsewhere but useful, such as Prepared in cooperation with, Translation of, Presented at conference of, To be published in, Supersedes, Supplements, etc

16. **ABSTRACT**
    Include a brief *(200 words or less)* factual summary of the most significant information contained in the report If the report contains a significant bibliography or literature survey, mention it here.

17. **KEY WORDS AND DOCUMENT ANALYSIS**
    (a) DESCRIPTORS - Select from the Thesaurus of Engineering and Scientific Terms the proper authorized terms that identify the major concept of the research and are sufficiently specific and precise to be used as index entries for cataloging.

    (b) IDENTIFIERS AND OPEN-ENDED TERMS - Use identifiers for project names, code names, equipment designators, etc Use open-ended terms written in descriptor form for those subjects for which no descriptor exists.

    (c) COSATI FIELD GROUP - Field and group assignments are to be taken from the 1965 COSATI Subject Category List Since the majority of documents are multidisciplinary in nature, the Primary Field/Group assignment(s) will be specific discipline, area of human endeavor, or type of physical object. The application(s) will be cross-referenced with secondary Field/Group assignments that will follow the primary posting(s).

18. **DISTRIBUTION STATEMENT**
    Denote releasability to the public or limitation for reasons other than security for example "Release Unlimited." Cite any availability to the public, with address and price.

19. & 20. **SECURITY CLASSIFICATION**
    DO NOT submit classified reports to the National Technical Information service.

21. **NUMBER OF PAGES**
    Insert the total number of pages, including this one and unnumbered pages, but exclude distribution list, if any.

22. **PRICE**
    Insert the price set by the National Technical Information Service or the Government Printing Office, if known