

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT SECTION 313

EPCRA/TRI TRAINING MATERIALS

Reporting Year 2001 Spring 2002

Module 1: TRI Overview

TRAINING DISCLAIMER

This document was developed for the sole purpose of helping potential reporters understand and comply with the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA). Nothing in this document is intended to independently alter, supplement, or revoke the statutory and/or regulatory requirements imposed by EPCRA section 313 and the applicable regulations at 40 CFR 372 et seq. Although these training materials provide an overview of the section 313 reporting requirements, facilities should consult the statute and regulations when developing threshold determinations and calculating releases and other waste management amounts. Facilities should be aware that EPA also provides guidance documents containing both sector specific guidance and guidance on specific elements of the EPCRA section 313 program. Covered facilities are encouraged to consult these guidance documents for additional assistance. Facilities may also receive specifically for Reporting Year 2001, for reports due on July 1, 2002. Facilities should be aware that EPA may promulgate regulatory changes to the EPCRA section 313 program that may alter reporting requirements for future reporting years.

TOXICS RELEASE INVENTORY REPORTING REQUIREMENTS (EPCRA SECTION 313)

CONTACT INFORMATION ABT ASSOCIATES CONTACTS

Adam Burke (617) 349-2774 adam_burke@abtassoc.com Lia Crompton (617) 349-2719 lia_crompton@abtassoc.com

Hilary Eustace (617) 349-2767 hilary_eustace@abtassoc.com

Cheryl Keenan (617) 349-2778 cheryl_keenan@abtassoc.com

Trey Kellett (617) 520-3571 trey_kellett@abtassoc.com Bill Norton (617) 349-2788 bill_norton@abtassoc.com

Alice Tome (301) 913-0552 alice_tome@abtassoc.com

CONTACT INFORMATION EASTERN RESEARCH GROUP CONTACTS

Leslie Crawford (770) 420-9580 leslie.crawford@erg.com

Kurt Rindfusz (703) 633-1676 kurt.rindfusz@erg.com

Doug Spengel (703) 633-1605 doug.spengel@erg.com Molly Merrifield (703) 633-1639 molly_merrifield@erg.com

Torsten Rothman (863) 699-9125 torllyn@strato.net

John Wilhelmi (781) 674-7312 john.wilhelmi@erg.com


A-3

WHO MUST REPORT?

- **Facilities (Private- and Public-sector)**
 - In covered primary SIC code(s) or Federal facilities; and
 - With 10 or more full-time employees (equivalent of 20,000 hours per year); and
 - That exceed manufacture, <u>or</u> process, <u>or</u> otherwise use thresholds for each Section 313 chemical

WHAT TO REPORT?

- File a TRI report for each Section 313 chemical exceeding an activity threshold
- Submit to U.S. EPA, and either designated state officials or designated tribal office by July 1st for preceding calendar year's activities
 - July 1, 2002 (January 1 December 31, 2001 activities)



COVERED SIC CODES

Industrial Sector	Primary SIC Code
Manufacturing	20-39
Metal mining	10 (except 1011, 1081, and 1094)
Coal mining	12 (except 1241)
Electrical utilities	4911, 4931, and 4939, limited to facilities that combust coal and/or oil for the purpose of generating electricity for distribution in commerce
Treatment, Storage, and Disposal facilities	4953, limited to RCRA Subtitle C permitted or interim status facilities
Solvent recovery services	7389, limited to facilities primarily engaged in solvent recovery services on a contract or fee basis
Chemical distributors	5169
Petroleum bulk terminals	5171

A-7

FEDERAL FACILITIES

- **■** Federal facilities (covered by Executive Order 13148)
 - Owned or operated by Executive Branch agencies
 - » No restrictions based on SIC code
 - » Includes federal prisons, national parks, federal hospitals
 - With 10 or more full-time employees (equivalent of 20,000 hours per year)
 - That exceed manufacture, <u>or</u> process, <u>or</u> otherwise use thresholds
 - Agency responsible for reporting on activities at Federal facilities that are conducted by, for, or in support of the agency

SIC CODES

- Section 313 subjects facilities to reporting based on classification of primary activities in the Standard Industrial Classification (SIC) system (§372.22)
- On April 9, 1997 (62 FR 17288), the North American Industry Classification (NAIC) System was implemented
- SIC codes are to be used until EPA transitions to new NAIC system in future reporting years
- An OMB crosswalk exists between the SIC and new NAIC codes (see 62 FR 172188)


A-9

DEFINITION OF "FACILITY"

- "Facility all buildings, equipment, structures, and other stationary items which are located on a single site or contiguous or adjacent sites and which are owned or operated by the same person (or by any person which controls, is controlled by, or under common control with, such person)." (EPCRA §329(4))
- Establishment unique and separate economic unit of a "facility" (§372.3)
- Auxiliary facility primarily supports a covered establishment's activities at another facility

MULTI-ESTABLISHMENT FACILITY


Three separate establishments located on contiguous/adjacent property owned by same person(s), is one facility under EPCRA (§372.22(b))




A-11

MULTI-ESTABLISHMENT FACILITY

- **■** Determining how facilities report
 - Federal facilities and federal contractors (GOCOs)




Ex. 1: Two separate reporting facilities (HUD and DOT including Coast Guard)



Ex. 2: One reporting facility (DOE)

AUXILIARY FACILITY

- Non-contiguous and non-adjacent to a covered establishment
- Primary function is to support a covered establishment's activities at another facility (e.g., warehouses, laboratories)
- Assumes SIC code of covered establishment for reporting purposes
- Employee and chemical activity threshold determinations are separate!



EMPLOYEE THRESHOLD

- 10 full-time employees (20,000 hours) (§§372.3 and 372.22(a))
 - · Worked at or directly for facility
 - Includes operational staff, administrative staff, contractors, dedicated sales staff, company drivers, off-site direct corporate support
 - Does NOT include contract drivers or janitorial contractors
- Determinations based on available time management systems/data

A-15

THRESHOLDS TRIGGERING EPCRA SECTION 313 REPORTING

- Section 313 chemicals that are listed as persistent, bioaccumulative, and toxic (PBT) are subject to separate and lower thresholds (§372.28)
- A facility meeting the SIC code (or Federal facility) and employee criteria must file a TRI report for a non-PBT Section 313 chemical if the facility (§372.25):
 - Manufactured (including imported) more than 25,000 pounds per year, or
 - Processed more than 25,000 pounds per year, or
 - Otherwise used more than 10,000 pounds per year
- Activity thresholds are calculated independently
- Threshold calculations are based on cumulative quantities per Section 313 chemical over the reporting year

THRESHOLDS TRIGGERING EPCRA SECTION 313 REPORTING

■ If a facility manufactures, processes, or otherwise uses any chemicals that are listed as persistent, bioaccumulative, and toxic (PBT), the threshold quantity is one of the following per Section 313 chemical or category per year (§372.28):

0.1 grams	Dioxin and dioxin-like compounds				
10 pounds	Highly persistent and highly bloaccumulative				
100 pounds	Persistent and bioaccumulative				
Threshold Level	Type of PBT Chemical				

A-17

CATEGORIES OF MANUFACTURING ACTIVITIES

- Manufacturing (§372.3) generating a Section 313 chemical
 - · Intentionally producing chemicals for:
 - » Sale
 - » Distribution
 - » On-site use or processing (e.g., intermediates)
 - Coincidentally producing chemicals as impurities or byproducts:
 - At <u>any point</u> at the facility, including waste treatment and fuel combustion
 - Importing
 - » "Cause" to be imported

CATEGORIES OF PROCESSING ACTIVITIES

- Processing (§372.3) preparation of a Section 313 chemical for distribution in commerce
 - Using as a reactant to manufacture another substance or product
 - · Adding as a formulation component
 - Incorporating as an article component
 - · Repackaging for distribution
 - » Including quantities sent off-site for recycling
 - · As an impurity

A-19

REPACKAGING AS A PROCESSING ACTIVITY

- Repackaging a Section 313 chemical for distribution in commerce is considered processing
 - · Repackaging includes transfer:
 - » From container to tanker truck and vice-versa
 - » Between similar size containers
 - » Via pipeline to/from a tank
 - · Repackaging does not include:
 - » Sampling without repackaging
 - » Re-labeling
- Repackaging without distribution into commerce is not considered processing

OTHERWISE USE

- Otherwise using (§372.3) includes most activities that are <u>not</u> manufacturing or processing
 - Examples
 - » Chemical processing aid (e.g., solvents)
 - » Manufacturing aid (e.g., lubricants, refrigerants)
 - Ancillary activities (e.g., chemicals used to remediate wastes)

A-21

OTHERWISE USE (CONTINUED)

- Otherwise use of a Section 313 chemical also includes on-site disposal, stabilization (without subsequent distribution in commerce), or treatment for destruction if:
 - Section 313 chemical was received from off-site for the purposes of further waste management, or
 - Section 313 chemical was manufactured as a result of waste management activities on materials received from off-site for the purpose of further waste management
- Waste management activities include recycling, combustion for energy recovery, treatment for destruction, waste stabilization and release (including disposal)

CALCULATING ACTIVITY THRESHOLDS

- Calculate total amount of Section 313 chemical to a threshold activity
 - Example:
 - » A plant uses MEK to manufacture liquid industrial adhesive for distribution in commerce. The plant adds 27,000 pounds of MEK to the liquid adhesive-making operation during the reporting year, but 3,000 pounds are volatilized during the operation
 - » 27,000 pounds of MEK is processed, reporting required


A-23

CALCULATING ACTIVITY THRESHOLDS

- Activities that, alone, do <u>NOT</u> constitute an activity threshold
 - Storage
 - Remediation of on-site contamination (does not include chemicals manufactured during remediation)
 - · Re-labeling without repackaging
 - · Direct reuse onsite
 - · On-site recycling
 - Transfers sent off-site for further waste management (not including recycling)

Note: These activities may not be exempt from reporting if threshold is exceeded through other activities.





EPCRA SECTION 313 REPORTING EXEMPTIONS



SECTION 313 EXEMPTIONS

- Designed to reduce the burden of reporting associated with small or ancillary chemical uses
- If an exemption applies, then the amount of a Section 313 chemical subject to the exemption does not have to be included in:
 - · Threshold determinations
 - · Release and other waste management reporting
 - · Supplier notification
- Recognize that exemptions only apply in <u>certain</u> <u>limited</u> circumstances

SECTION 313 EXEMPTIONS

- **■** Types of exemptions (§372.38)
 - · De minimis
 - Articles
 - Laboratory activities
 - · Otherwise use exemptions
 - » Motor vehicle maintenance
 - » Routine janitorial or facility grounds maintenance
 - » Structural components
 - » Personai use
 - » Intake water and air
 - Mining (extraction activities and overburden)

B-3

DE MINIMIS EXEMPTION

- The quantity of a non-PBT Section 313 chemical in a mixture or other trade name product is eligible for the exemption if the chemical is:
 - Any non-PBT Section 313 chemicals present at a concentration of <u>less than 1%</u> by weight (§372.38(a))

or

• An OSHA-defined non-PBT carcinogen present at a concentration of <u>less than 0.1%</u> by weight

DE MINIMIS EXEMPTION How It Works

- *De minimis* exemption <u>can</u> apply to non-PBT chemicals:
 - In mixtures or other trade name products processed or otherwise used
 - Only two manufacturing activities:
 - » Coincidentally manufactured as impurities that remain in products
 - » Imported in mixtures or other trade name products

B-5

DE MINIMIS EXEMPTION How It Works

- De minimis exemption does <u>not</u> apply to:
 - Manufacturing chemicals (in most cases)
 - » Manufacturing chemicals as by-products
 - » Coincidentally manufacturing chemicals
 - As by-products of waste treatment or fuel combustion
 - Section 313 chemicals listed as persistent, bioaccumulative, and toxic (PBT) (except for supplier notification)


DE MINIMIS EXEMPTION How It Works

- De minimis exemption does not apply to:
 - Wastes and waste streams, from non-exempt sources, that are processed or otherwise used
 - » Wastes received from off-site for purposes of on-site incineration
 - Releases and other waste management activities from mixtures or other trade name products that are not associated with a processing or otherwise use activity
 - » Material storage not associated with processing or otherwise use activities

B-7

DE MINIMIS EXEMPTION How It Works


■ De minimis concentration for toluene is 1.0% (not an OSHA carcinogen)



■ Toluene in cleaning mixture is below *de minimis* concentration and is eligible for the exemption

DE MINIMIS EXEMPTION How It Works

Processing a non-PBT Section 313 chemical in a mixture to below the de minimis concentration does not exempt the chemical from threshold determinations and release and other waste management calculations



Toluene ≥ 1%

- De minimis exemption does not apply
- Threshold determination required
- Release and other waste management calculations required


Toluene <1%

- De minimis exemption does not apply
- Threshold determination required
- Release and other waste management calculations still required

B-9

DE MINIMIS EXEMPTION How It Works

Processing a non-PBT Section 313 chemical in a mixture to above the de minimis concentration triggers threshold determinations and release and other waste management calculation requirements



ARTICLES EXEMPTION

- "Article" is defined (§372.38(b)) as an item that is already manufactured and:
 - Is formed into a specific shape or design during manufacture; and
 - Has end-use functions dependent in whole or in part on its shape or design during end-use; and
 - Does not release a Section 313 chemical under normal processing or otherwise use conditions at a facility
- The articles exemption does not apply to the manufacture of articles

B-11

ARTICLES EXEMPTION How It Works

- Releases of a Section 313 chemical from an article may negate the exemption. To maintain the article status, total releases from all like items must be:
 - In a recognizable form; or
 - · Recycled, directly reused; or
 - 0.5 pounds or less (may be rounded down to zero)
- If more than 0.5 pounds of a Section 313 chemical are released from all like items in a non-recognizable form and are not recycled or directly reused, none of the items meet the articles exemption

ARTICLES EXEMPTION Examples

- Wire is cut to specified lengths. Wastes include off-spec cuts and dust
 - Generation of off-spec cuts that are recognizable as articles will not, by itself, negate the article status
 - Dust and off-spec cuts not recognizable as articles, with greater than 0.5 pounds of a Section 313 chemical released, and not recycled or directly reused, negate the article status
- Fluorescent light bulbs are installed containing mercury.
 The used bulbs are crushed in an enclosed container prior to recycling
 - Crushing bulbs prior to disposal is not considered release during use; exemption is not negated

B-13

ARTICLES EXEMPTION Examples

- Pipe is cut to specified lengths. Wastes include offspec cuts and dust
 - Facility estimates that from all uses of the same type of pipe over the reporting year, a total of 2 pounds of chromium releases and 0.3 pounds of nickel releases occur
 - Because total chromium releases are greater than 0.5
 pounds over the reporting year, the articles exemption is
 negated for all uses of the pipe including both the chromium
 and nickel in the pipe (even though total nickel releases
 were less than 0.5 pounds)

LABORATORY ACTIVITIES EXEMPTION

- Section 313 chemicals manufactured, processed, or otherwise used in certain laboratory activities, performed under the supervision of a technically qualified individual, may be eligible for the exemption (§372.38(d))
- Activity must occur in a laboratory to be exempt
- Laboratories, themselves, are <u>not</u> exempt

B-15

LABORATORY ACTIVITIES EXEMPTION

- Definition of technically qualified individual (§720.3(ee))
 - Capable of understanding the health and environmental risks associated with the chemical substance which is used under his or her supervision because of education, training, or experience, or a combination of these factors;
 - Responsible for enforcing appropriate methods of conducting scientific experimentation, analysis, or chemical research to minimize such risks; and
 - Responsible for the safety assessments and clearances related to the procurement, storage, use, and disposal of the chemical substance as may be appropriate or required within the scope of conducting a research and development activity.

LABORATORY ACTIVITIES EXEMPTION How It Works

- Section 313 chemicals manufactured, processed, or otherwise used in these laboratory activities are eligible for the exemption
 - · Sampling and analysis
 - Quality assurance
 - Quality control

B-17

LABORATORY ACTIVITIES EXEMPTION How It Works

- Section 313 chemicals manufactured, processed, or otherwise used in these laboratory activities are <u>NOT</u> exempt
 - Any activities conducted outside laboratories
 - Specialty chemical production
 - Pilot-scale plant operations
 - Support services
 - Photo processing
 - · Equipment maintenance/cleaning

MOTOR VEHICLES EXEMPTION

- Section 313 chemicals otherwise used to maintain motor vehicles operated by the facility are eligible for the exemption (§372.38(c)(4))
- Examples of motor vehicles eligible for the exemption include cars, trucks, airplanes, and forklifts
- **Examples of exempt motor vehicle maintenance:**
 - Body repairs
 - · Parts washing and plating
 - Fueling and adding other fluids (e.g., ethylene glycol)

B-19

ROUTINE JANITORIAL OR FACILITY GROUNDS MAINTENANCE EXEMPTION

- Section 313 chemicals contained in products otherwise used for non-process related routine janitorial or facility grounds maintenance are eligible for the exemption (§372.38(c)(2))
 - Phenol in bathroom disinfectants
 - · Pesticides in lawn care products
- Section 313 chemicals otherwise used in process-related activities are <u>not</u> exempt
 - Facility equipment maintenance
 - Cleaning or maintenance activities that are integral to the production process of the facility

STRUCTURAL COMPONENT EXEMPTION

- The otherwise use of Section 313 chemicals, that are part of structural components of a facility, are eligible for the exemption provided the structure is not process related (§372.38(c)(1))
 - Copper in pipe used in construction of employees' bathroom facilities
 - Metals, pigments, and solvents in paint applied to facility structure


B-21


OTHER EPCRA SECTION 313 EXEMPTIONS

- Section 313 chemicals contained in non-process related items for employee personal use (§372.38(c)(3))
 - HCFC-22 in air conditioners used solely for employee comfort
 - Chlorine used to treat on-site potable water
 - Phenol in a facility medical dispensary
- Section 313 chemicals found in intake water (e.g., process water and non-contact cooling water) and air (e.g., used as compressed air) (§372.38(c)(5))

SIC CODE-SPECIFIC EXEMPTIONS

- SIC Code 12: Coal mining extraction activities are exempt from threshold determinations and release reporting (§372.38(g))
 - Coal extraction: the physical removal or exposure of ore, coal, minerals, waste rock, or overburden prior to beneficiation, and encompasses all extraction-related activities prior to beneficiation (§372.3)
- SIC Code 10: Chemicals in metal mining overburden that are processed or otherwise used are specifically exempt from TRI reporting (§372. 38(h))
 - Overburden: unconsolidated material that overlies a deposit of useful materials or ores (§372.3)





DETERMINING THRESHOLDS

- Identify what Section 313 chemicals are handled onsite
- Identify concentrations of Section 313 chemicals
- Collect data and calculate quantities towards each threshold

C-3

DETERMINING THRESHOLDS

Identify Chemicals and Concentrations:

MSDS

Specifications

Waste Profiles

Process Knowledge

Other References (AP-42, Merck Index)

Supplier Notification

<u>Collect Data to Calculate</u> Thresholds:

Inventory Records

Throughput/Production Data

Purchase Records

EPCRA or Other Env. Reports

Ask the User

Call the Vendor

C-4

SECTION 313 CHEMICALS AND CHEMICAL CATEGORIES

- Original list developed from Maryland "High Production Volume" and New Jersey "Right to Know" chemical lists
- Current list contains over 600 individual chemicals and chemical categories (See Table II of the EPA's *TRI Reporting Forms and Instructions* document)
- Petition process to add or delete chemicals or forms of chemicals (EPCRA Section 313(e))

C-5

SECTION 313 CHEMICAL QUALIFIERS

Qualifiers - Listed chemicals with parenthetic qualifiers subject to TRI reporting only if manufactured, processed, or otherwise used in specified form (§372.25(g)). Below are some examples (see Table II of EPA's TRI Reporting Forms and Instructions document):

CHEMICAL	CAS#	QUALIFIER
Aluminum	7429-90-5	Fume or dust
Aluminum oxide	1344-28-1	Fibrous forms
Asbestos	1332-21-4	Friable forms
Isopropyi alcohol	67-63-0	Only manufacturers using strong acid process
Phosphorus	7723-14-0	Yellow or white
Saccharin	81-07-2	Manufacture only
Hydrochloric acid	7647-01-0	Acid aerosols
Sulfuric acid	7664-93-9	Acid aerosols
Vanadium	7440-62-2	Except when contained in alloy C-6

SECTION 313 CHEMICALS

- Calculate threshold determinations and releases and other waste management estimates by multiplying the percentage of a Section 313 chemical by the total amount of the mixture, other trade name product, or waste
 - Example: 80,000 pounds of a solvent containing benzene was used on-site at the facility to clean machinery. The solvent contains 10% benzene.
 - » 80,000 lbs. X 10% = 8,000 lbs. of benzene otherwise used

C-7

COMPOUND CATEGORIES

- Count together all compounds that fall within a category, even if different compounds within a category are used in separate operations
 - Example: If a facility processes 20,000 pounds of 2-Butoxyethanol in one operation and 10,000 pounds of 2-(2-Butoxyethoxy)ethanol in another operation during the reporting year
 - 30,000 pounds of glycol ethers have been processed.
 Reporting for glycol ethers category is required
- Consider the entire weight of the compounds in the category when determining thresholds
 - Calculations for release and other waste management estimate are different for metal and nitrate compounds

C-8

SUPPLIER NOTIFICATION FOR MIXTURES AND OTHER TRADE NAME PRODUCTS

- Supplier notification (§372.45) requires suppliers to facilities described in §372.22 (i.e., covered facilities) to:
 - Identify Section 313 chemical(s) by name and CAS number
 - Identify Section 313 chemical(s) as being subject to Section 313 requirements
 - Provide concentration (or range) of Section 313 chemicals in mixtures and other trade name products (not wastes)
 - Provide notification at least annually in writing or attached to the MSDS
 - · Update notification when changes occur
 - Only facilities in primary SIC codes 20-39 must initiate the notification

C-4

DETERMINING CONCENTRATIONS IN MIXTURES OR OTHER TRADE NAME PRODUCTS

- Include a Section 313 chemical in the threshold determinations if you know (§372.30(b)(3)):
 - Exact concentration use concentration provided
 - Upper bound use upper limit
 - Range use the midpoint of the range
 - Lower bound subtract out other known constituents, create a range, and use the midpoint of range
- Note: Thresholds are based on weight in pounds, except for dioxins and dioxin-like compounds

DETERMINING CONCENTRATIONS IN WASTES

- De minimis exemption does not apply to wastes that are processed or otherwise used
- If concentration is exact, upper bound, range, or lower bound, use the guidance for mixtures and other trade name products
- If concentration is below detection limit, use engineering judgment:
 - If the Section 313 chemical is expected to be present, you could assume 1/2 of full detection limit
 - If the Section 313 chemical is not expected to be present, vou could assume 0

C-11

MEETING MULTIPLE THRESHOLDS

- There are many situations where one Section 313 chemical must be counted towards multiple activity thresholds
 - Section 313 chemicals manufactured or imported on-site, then used or incorporated into a product (processed)
 - Section 313 chemicals formed during destruction of wastes received from off-site and subsequently destroyed on-site (manufactured and otherwise used)
 - Section 313 chemicals that are otherwise used on-site, recycled, then processed
- Section 313 chemicals should not be counted twice towards the same activity threshold

C-12

WATCH FOR DOUBLE COUNTING WITHIN THE SAME ACTIVITY THRESHOLD!!!

- For threshold determinations, Section 313 chemicals reused or recycled at a facility: count original amount used only once (§372.25(e))
 - Note: Section 313 chemicals sent off-site for recycling and returned to the facility are considered new materials and counted for threshold determinations
 - For materials in use from previous years: count only the quantity added during current reporting year

C-13

MULTI-ESTABLISHMENT FACILITY

- **Determining how facilities report**
 - Multi-establishment facility (§372.30(c))
 - » Apply threshold determination on aggregate amount of chemicals used at <u>facility</u>
 - » Able to file separate Form R reports for each establishment if they are distinct economic entities (must be designated as part of a facility on Form R)
 - » Report <u>all</u> releases and other waste management activities of reportable Section 313 chemicals
 - » Avoid double-counting of chemicals involved in intrafacility transfers

CALCULATING THRESHOLDS

- Consider all activities
- **Consider all sources**
- Identify the avenues through which mixtures and trade name products enter your facility
 - Purchasing/inventory control
 - Contractors
 - Bulk deliveries
 - Capital purchases
 - "Credit card" or "emergency" purchases
 - Chemicals used in neutralization, refrigerants, cleaners, paints, lubricants (for non-vehicles), fuel (for non-vehicles), refractory bricks

C-15

ORCHESTRATING DATA COLLECTION

- Methods for orchestrating data collection
 - Coordinate with purchasing/vendors
 - Develop inventory controls
 - Require requisition or "sign out" procedure for Section 313 chemicals
 - Take year-end inventories
- Identify ALL chemical purchasing and usage
- Threshold determination worksheets for both PBT and non-PBT Section 313 chemicals

eporting Year:tep 1. Identify amounts of			······					
ixture Name or Other Identifier		Percent by Welcht	Total Weight					
			<u> </u>	Manufac	tured	Press		Otherwise Used
Joe's Degreeser	Purchasing		10,000					5,000
Yellow Bethroom Paint	Vendor	- 6	30,000					1,500
Parts Washer Fluid	Purchasing	40	10,000	<u> </u>				4,000
	+							
					_			
	} 	_						
	 							
btotal:			·	(A)		(B)	No.	(C) 10,500 <u>m</u>
ixture Name as Listed Above	Applicable			Enough Amount of the Toxic Chemical from Above (in Bu):				
				Magnifec	tured	Prece		Otherwise Used
Yellow Bathroom Paint	Struct, Com	-	100					1,500
								
	 							
								
								<u> </u>
	 							
	 							
·				ريم		(B)	Pec.	(C ₁) 1,500 1bm
htetal:	<u> </u>	1		<u> </u>				<u> </u>

MANAGEMENT PRACTICES

■ Begin early

- Implement a program to gather "real-time" data on usage
- · Searches for historical information can be difficult

■ Use a team approach

- Include all relevant personnel (e.g., engineering, environmental, operations)
- · Spread the work

RECORDKEEPING

- **■** Detailed records
 - Improve reporting accuracy and data quality
 - · Reduce replication of effort from year to year
- Well-labeled calculations and assumptions
 - Serve as standard operating procedures (SOPs) for future vears
 - Ensure consistency from year to year, especially if personnel responsible for reporting change
- EPA will review records during a data quality audit

C-19

TRI REPORTING SOFTWARE

- For the Reporting year (RY) 2001, EPA is distributing two types of reporting software to assist facilities in reporting to the Toxics Release Inventory (TRI).
- The TRI-Made Easy (TRI-ME) Reporting Software was distributed to a limited number of facilities for a pilot in RY 2000. It is now available to all facilities for RY 2001.
- The Automated TRI Reporting Software (ATRS) is the traditional reporting software that has been distributed by EPA for a number of years.
- For RY 2001, facilities may report using either *ATRS* or *TRI-ME*; however, EPA plans to transition from *ATRS* to *TRI-ME* in the near future.

C-20

TRI REPORTING SOFTWARE

- Both ATRS and TRI-ME will be distributed via CD ROM to all facilities that have reported to TRI in the last two reporting years. The software will also be available to download from EPA's website at www.epa.gov/tri.
- The TRI-ME software is an interactive, intelligent, user-friendly software program that assist facilities in determining and completing their TRI reporting obligations. In contrast, while ATRS allows facilities to complete the Form Rs and As on their personal computers, it provides much less guidance and assistance.
- Both TRI-ME and ATRS allow users to access and search the TRI Assistance Library (TRIAL). TRI-ME is intelligently linked to TRIAL so that the user can view pre-selected TRI definitions and guidance from TRIAL that are relevant to specific TRI-ME screens.

C-21

OVERVIEW OF FORM R, PART I

- Two principal types of information
 - Facility-specific
 - Chemical-specific
- One form must be submitted to EPA and to the SERC/TERC for each Section 313 chemical or chemical category exceeding applicable thresholds (§372.30(a))

PART I: FACILITY INFORMATION

- Identifies the facility
- Provides key data for linking information to other databases
- **■** Identifies key personnel

C-23

PART I. SECTIONS 1 AND 2

- Reporting year is the calendar year to which the reported information applies; not the year in which the form is submitted
- Trade secret submissions require substantiation (40 CFR 350)
- Two forms are required for trade secret submissions:
 - One complete
 - · One "sanitized" version

	PART I. FACILITY IDENTIFICATION INFORMATION		
	SECTION 1. REPORTING YEAR		
	SECTION 2. TRADE SECRET INFORMATION		
2.1	Are you claiming the toxic chemical identified on page 2 trade secret?	2.2	le this copy 🔲 Senitized 🔲 Uncenitized
	Yes (Answer question 2.2; Attach substantiation forms) No Do not answer 2.2; go to Section 3		(Answer only If "YES" in 2.1)

PART I. SECTION 3

- An original signature is required
- Name must be legible (printed or typed)
- Title of the official who signs is also required

SECTION S. CERTIFICATION (Important: Reed and sign after completing all form sections.)

I hereby certify that I have reviewed the attached documents and that, to the best of my knowledge and belief, the submitted information is true and complete and that the amounts and values in this report are accurate based on reasonable estimates using data available to the preparers of this report.

Name and official title of conscriperator or center management official:

Signature:

Date eigned:

C-25

PART I. SECTION 4.1

- All parts of the facility name and address are essential
- Mailing address required if different from street address
- TRI facility identification number (if a form was filed in a previous reporting year) or "New Facility" (if reporting for the first time)
- All establishments at one facility should use the same TRI facility identification number (if reporting separately)

SECTION 4. FACILITY IDENTIFICATION					
4.1	TRI Facility ID Number				
Facility or Entablishment Home	Earling or Establishment Home or Mellino Address (I different from about address)				
	Mellog Address				
ClarCounts/State/Sta Code	Olle/Countr/Relate/Zie Code Country Rico-Lith:				

PART I. SECTION 4.1

■ Federal facilities

• Enter name of Federal department or agency standard acronym followed by the site name

SECTION 4. FACILITY IDENTIFICATION						
4.1	TRI Facility ID Humber					
U.S. DOE Kansas City Plant	Entity on Classic Connect Marine of Medical Address (II different from alrest address)					
	To a server					
City/County/Wester/Zip Code	Chyfinia/Zio Code Country (Non-US)					

C-27

PART I. SECTION 4.2 THROUGH 4.4

- Specify whether the form covers all or part of the facility
 - Federal facilities and GOCOs also check either "c" or "d," but not both
- List name and phone number
 - Technical contact should be able to explain data to EPA
 - Public contact should be able to represent the facility's data to the public

SECTION 4. FACILITY IDENTIFICATION (Continued)						
4.2	This report contains information for: This report contains information for: This report contains information for: This report contains information for: An entire D. Part of a A Faderal D. Good					
4.3	Technical Contact Name		Telephone Number (include area code)			
4.4	Public Contact Name		Telephone Number (include area code)			

PART I. SECTION 4.5 THROUGH 4.6

- Enter covered <u>4-digit</u> SIC code(s)
 - Enter primary SIC code in first box (a.)
 - Enter other covered SIC codes in decreasing order of significance
- Supply latitude and longitude coordinates

4.5	SIC Code(s) (4-digits)		Primary				-		
					D.	C.	•	•	•
		Deg	1900	Minutes	Seconde		Degrees	Minutes	Seconde
4.6	Latitude					Longitude			
	İ								

C-29

PART I. SECTION 4.7 THROUGH 4.10

- Enter the specified identification numbers or "NA" if not applicable
 - Enter Dun and Bradstreet number(s)
 - EPA ID numbers (assigned to RCRA-covered facilities)
 - NPDES permit number(s)
 - Underground Injection Well Code (UIC) I.D. number(s)

4.7	Dun & Bradstreet Number(s) (9 digits)	4.8	EPA Identification Number(s) (RCRA LD. No.) (12 cheracters)	4.9	Facility NPDES Permit Number(s) (9 characters)	4.10	Underground Injection Well Code (UIC) LD. Number(s) (12 digits)
a		d		a		8.	
b.		b.		b .		b.	

PART I. SECTION 5

■ Private-sector and GOCO facilities

• Enter complete name and Dun & Bradstreet number of parent company

■ Federal facilities

- Enter the complete name of department or agency for parent company (e.g., U.S. Department of Interior)
- Check "NA" for Dun & Bradstreet number of parent company

SECT	SECTION S. PARENT COMPANY INFORMATION					
5.1	Name of Perent Company NA					
5.2	Parent Company's Dun & Bradstreet Number	□ NA	(9 digite)			

C-31

PART II: CHEMICAL-SPECIFIC INFORMATION

■ Identifies

- · Section 313 chemical and its uses at the facility
- · Quantities released or otherwise managed as wastes
- Waste management and source reduction activities
- Maximum quantity of the Section 313 chemical on site at one time

PART II. SECTIONS 1 AND 2: TOXIC CHEMICAL OR MIXTURE IDENTITY

- Complete either Sections 1.1 & 1.2 or Section 1.3 or Section 2
- Enter CAS number or category code and name of Section 313 chemical or chemical category (except on "sanitized" form)
- Enter generic name <u>only</u> if claiming Section 313 chemical name as a trade secret (Section 1.3)

8EC	TION 1. TOXIC CHEMICAL IDENTITY	(Important: DO NOT complete this section If you completed Section 2 below.)		
1.1	CAS Number (MIPORTANT: Enter only one number exectly as it a	pposes on the Section 313 list. Enter cutaginy each il reporting a chamical cutagory.)		
1.2	Total: Chamical or Chamical Category Hame (Important: Enter only one name exactly as it appears on the Section 313 list.)			
1.3	Genedic Chemical Name (Important: Complete ently if Part I, Sec	clim 2.1 is checked "yes." Generic name must be obusturally descriptive.)		

C-33

PART II. SECTIONS 1 AND 2: TOXIC CHEMICAL OR MIXTURE IDENTITY

■ If supplier claims trade secret, report generic name by supplier

SECT	TION 2. MIXTURE COMPONENT IDENTITY	(important: DO NOT complete this section if you complete Section 1 above.)
2.1	Generic Chemical Name Provided by Supplier (Important: Maximum	of 70 characters, including numbers, latters, spaces, and punctuation.)

PART II. SECTION 3 OF THE FORM R: ACTIVITIES AND USES OF THE CHEMICAL AT THE FACILITY

- Specify use(s) of the Section 313 chemical: manufacture, process, or otherwise use
- Report only activities taking place at reporting facility
- Check all applicable boxes

SECTION 3. ACTIVITIES AND USES OF THE TOXIC CHEMICAL AT THE FACILITY (Important: Check all that apply)				
3.1 Manufacture the toxic chemical:	3.2 Process the toxic chemical:	3.3 Otherwise use the toxic chemical:		
e. Produce b. Import				
if produce or import: C. For on-site use/processing d. For sale/distribution e. As a byproduct f. As an impurity	a. As a reactant b. As a formulation component c. As an article component d. Repackaging e. As an impurity	a.		

EXERCISE #1

IDENTIFYING EPCRA SECTION 313 CHEMICALS

Purpose:

Familiarize participants with the chemical lists in Table 2 of EPA's TRI

Forms and Instructions document.

Ability to identify correctly Section 313 chemicals from MSDSs.

Take-Aways:

Understanding of nuances of chemical compositions.

Materials:

TRI Reporting Forms and Instructions document

Material Safety Data Sheets (MSDSs)

Instructions:

Attached is a package of chemicals, chemical compounds, and chemical mixtures present at your facility. Determine if any of these chemicals or parts of these chemicals is on the EPCRA Section 313 list. If you determine that a chemical or component of a product or mixture is on the list present at or above the appropriate *de minimis* level, prepare a list of

the appropriate Section 313 chemicals and CAS numbers.

IDENTIFYING EPCRA SECTION 313 CHEMICALS

MSDS Name	Section 313 Chemical(s) Name	Concentration	Notes
	,		
		`	

MEADOWEROOK COMPANY SPELTER. WEST VIRGINIA 26438

RAW MATERIAL SUPPLIER DATA SHEET

I. TRADE NAME CRUDE ZINC OXIDE

CHEHICAL NAME ZINC CXIDE EPA/GAS 1314-13-2

MANUFACTURER

MEADOWEROOK COMPANY

DIV OF I. L. DIAMOND & CO., INC.

SPECIFICATIONS	GRADE A	GRADE B
Zn	50-59%	60 Z -68 Z
Fe	1-32	1-3%
Za Fe Al Pb Cl Cd Cu	.8-3.5%	.8-3.5Z
Pb	0.1-0.5 Avg. 0.2	0.1-0.5 Avg.0.2%
C1	0.0-0.32	0.0-0.32
Cd.		There .01
Cu	0.04-0.40	0.04-0.40

- II. NON TOXIC SOLID MATERIAL WITH A PARTICLE SIZE RANGE UP TO 1/4 INCH.
- III. SPECIFIC GRAVITY 5.6.
 AFPARENT DENSITY 130-160 LBS/CU FOOT
 NON SOLUABLE IN WATER NON VOLATILE
 LIGHT GRAY, ODORLESS COARSE POHDER
 - IV. NO FIRE OR EXPLOSION HAZARD. CAN REACT WITH MAGNESIUM OR CARBON WHEN HEATED.
 - V. NO PARTICULAR HEALTH HAZARD. TLV (S) FOR PRINCIPLE INGRED IENT PEL 5 Mg/M' FOR ZINC OXIDE FUME
 - VI. NON REACTIVE AT AMBIENT EXCEPT WITH MINERAL ACIDS
- VII. SPILL OR LEAK PROCEDURES Clean up & return to labeled containers
- VII. PERSONAL PROTECTION Nicsh respirator suggested for comfort when material is dry & dusty

HANDLERS SHOULD WEAR GLOVES AND SAFETY COCCLES.

3M Center St. Paul. Minnesota 55144-1000 . 612/733-1110

MATERIAL SAFETY DATA SHEET



DIVISION: INDUSTRIAL MINERAL DIVISION TRADE NAME: IM BRAND ROOFING GRANULES (WAUSAU, WI) 98-0111-1217-8 98-0111-1221-0 98-0111-1253-3 98-0111-1218-6 98-0111-1219-4 3N I.D. NUMBER: 98-0111-1216-0 98-0111-1222-5 98-0111-1223-6 98-0111-1220-2 98-0111-1252-5 98-0111-1290-5 98-0111-1278-0 98-0111-1288-9 98-0111-1293-9 98-0111-1320-0 98-0111-1324-2 98-0111-1445-5 98-0111-1292-1 98-0111-1294-7 98-0111-1319-2 98-0111-1323-4 98-0111-1321-6 98-0111-1318-4 98-0111-1325-9 98-0111-1322-6 98-0111-1444-8 98-0111-1446-3 98-0111-1348-1 98-0111-1449-7 98-0111-1453-9 98-0111-1450-5 98-0111-1447-1 98-0111-1448-9 98-0111-1454-7 98-0111-1451-3 98-0111-1452-1 98-0111-1488-5 98-0111-1457-0 98-0111-1484-4 ISSUED: SEPTEMBER 13, 1994 SUPERSEDES: NOVEMBER 23, 1993 DOCUMENT: 10-0170-0 PERCENT 1. INGREDIENT C.A.S. NO. 35.0 30.0 PLAGIOCLASE FELDSPAR None 14808-60-7 35 25 QUARTZPOTASSIUM FELDSPAR 25 20 Nene < 5.0 1332-58-7 5.0 < KAOLIN .. 0.9 < 0.9 HYDROTREATED HEAVY NAPHTHENIC 0.9 PETROLEUM DISTILLATES 64742-52-5 e 0.9 0.9 < ZINC FERRITE 12063-19-3 NOTE: THE AMOUNT OF DUST GENERATED WHILE HANDLING THESE ROOFING GRANULES IS EXPECTED TO VARY DEPENDING ON THE USER'S OPERATION. THE LEVEL OF RESPIRABLE CRYSTALLINE SILICA IS EXPECTED TO BE LESS THAN 15% OF THE RESPIRABLE DUST. THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL OR CHEMICALS SUBJECT TO THE REPORTI REQUIREMENTS OF SECTION 313 OF TITLE III OF THE EMERGENCY PLANNING ANDCOMMUNITY RIGHT-ACT OF 1986 AND 40 CFR PART 372: CHROMIUM OXIDE (TRIVALENT CHROMIUM) ZINC FERRITE 2. PHYSICAL DATA ECILING POINT:..... N/A

N/A N/A N/A

N/A

N/A

2.6-2.7 H/A

EVAPORATION RATE:.....

SOLUBILITY IN WATER:

:T 2192 .T 3M Center

PAGE St. Paul. Minnesota 55!44-1000

512/733-1110

MATERIAL SAFETY DATA SHEET

MSDS: 3M BRAND ROOFING GRANULES (WAUSAU. WI) SEPTEMBER 13, 1994

PAGE: 2 of 5

Z. PHYSICAL DATA

(CONTINUES)

VOC LESS H20 & EXEMPT SOLVENT

pH: SL BASIC

VISCOSITY: MELIING POINT. H/A N/A

APPEARANCE AND COOK: Granules, Various colors, slightly oily oder

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: FLAMMABLE LIMITS - LEL: FLAMMABLE LIMITS - UEL: AUTOIGNITION TEMPERATURE: N/A N/A N/A N/A

EXTINGUISHING MEDIA:

Non-combustible. Choose material suitable for surrounding fire. SPECIAL FIRE FIGHTING PROCEDURES:

Not applicable

UNUSUAL FIRE AND EXPLOSION HAZARDS:
No unusual fire or explosion hazards are anticipated.

4. REACTIVITY DATA

STABILITY: Stable INCOMPATIBILITY - MATERIALS TO AVOID:

Not applicable.

HAZARDOUS POLYMERIZATION: Will Not Occur HAZARDOUS DECOMPOSITION PRODUCTS:

None known.

S. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Observe precautions from other sections. Collect spilled material. Use wet sweeping compound or water to avoid dusting.

RECOMMENDED DISPOSAL:

Dispose of weste product in a semitary landfill.

Had Radamedand

Since regulations vary, consult applicable regulations or authorities before disposal.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:
U.S. EPA Hazardous Wasta Number = None (Not U.S. EPA Hazardous). the event of an uncontrolled release of this material, the user should determine if the release qualifies as a resertable quantity.

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

3M Center St. Paul. Minnesota 55144-1000 612/733-1110

07-08 12745

CT 2192 -7 PAGE

MATERIAL SAFETY DATA SHEET

MSDS: 3M BRAND ROOFING GRANULES (WAUSAU, WI) SEPTEMBER 13, 1994

PAGE: 3 of 5

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

No need for first aid is anticipated in the event of skin contact.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact. The following should be worn alone or in combination, as appropriate, to prevent eye contact: Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact...

VENTILATION PROTECTION:

If exhaust ventilation is not available, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of dust. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask dust respirator.

PREVENTION. OF ACCIDENTAL INGESTION: Wash hands after handling and before esting.

RECOMMENDED STORAGE: Net applicable.

FIRE AND EXPLOSION AVOIDANCE: Not applicable.

INGREDIENTS	EXPOSURE LIMITS VALUE	INTT	TYPE AUTH SKINE	
PLAGIOCLASE FELDSPAR	NONE	NONE mg/m3 sertz resp.	HONE HONE	_

:: 2192 -

3M Center

PAGE

St. Paul. Minnesota 55144-1000

612/733-1110

MATERIAL SAFETY DATA SHEET

MSDS: 3M BRAND ROOFING GRANULES (WAUSAU, WI) SEPTEMBER 13, 1994

PAGE: 4 of 5

7. PRECAUTIONARY INFORMATION (continued)

INGREDIENTS VALUE UNIT TYPE AUTH S	KINZ
QUARTZ 0.1 mg/m3 TWA QSMA	
as quartz ress. dust	
POTASSIUM FELDSPAR	
SUDIUM SILICATE NOME NOME NOME NOME NOME	
KAOLIN Z mg/m3 TWA ACGIH	
respirable dust.	
KAOLIN 10 mg/m3 TWA OSHA	
CARBON BLACK 3.5 mg/m3 TWA ACGIH	
CARBON BLACK TWA CSHA CHROMIUM O.S ME/MS TWA CSHA CHROMIUM OXIDE (TRIVALENT CHROMIUM) 0.5 ME/MS TWA ACGIN	
CHROMIUM UXIDE (TRIVALENT CHROMIUM) 0.5 mg/m3. TWA ACGIH	
CHROMIUM OXIDE (TRIVALENT CHROMIUM) 0.5 mg/m3 TWA OSHA	
as Cr	
HYDROTREATED HEAVY NAPHTHENIC	
PETROLEUM DISTILLATES 5 mg/m3 TWA CMRG	
HYDROTREATED HEAVY NAPHTHENIC	
PETROLEUM DISTILLATES 18 mg/m3 STEL CHRG	
RUTILE TITANIUM DIOXIDE 10 mg/m3 TWA ACGIH	
RUTILE TITANIUM DIOXIDE	
IRON OXIDE (FE203) 5 mg/m3 TWA ACGIH	
IRON OXIDE (FEZOS) 10 mg/m3 TWA OSHA	
IRON OXIDE (FE203) 10 mg/m3 TWA OSHA	
IRON OXIDE (FEZOS) 5 mg/ms TWA ACGIH	
as fe	
ZINC FERRITE NONE NONE NONE NONE	

I SKIN NOTATION: Listed substances indicated with "Y" under SKIN refer to the potential contribution to the overall expesure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly by direct contact with the substance. Vehicles can alter skin absorption.

SCURCE OF EXPOSURE LIMIT DATA:

- ACBIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration CMRO: Chemical Manufacture Recommended Guidelines NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

May cause eye irritation if dust gets into eyes.

SKIN CONTACT:

He adverse health effects are expected from skin contact.

INHALATION:

Single overexposure, above recommended guidelines, may cause:

07-08 12747

3M Center St. Paul. Minnesota 55144-1000 612/733-1110

> CT 2192 PAGE

MATERIAL SAFETY DATA SHEET

HSDS: 3H BRAND ROOFING GRANULES (WAUSAU, WI) SEPTEMBER 13, 1994

PAGE: 5 of 5

8. HEALTH HAZARD DATA

(continued)

Irritation (upper respiratory): signs/symptoms can include sereness of the nose and threat, coughing and sneezing.

Prolonged or repeated overexposure, above recommended guidelines, MBY CAUSE:

Silicosis: signs/symptoms can include shortness of breath and persistent cougning.

Pneumoconiosis (general): signs/symptoms can include persistent cougning and shortness of breath.

IF SWALLDWED.

Ingestion is not a likely route of exposure to this product.

QUARTZ SILICA (14808-60-7) is a potential cancer hazard causing lung tumors by the inhalation and intratracheel routes of exposure in laboratory animal studies (NTP anticipated human carcingen, IARC probable human carcinogen ZA, Calif. Proposition 65).


SECTION CHANGE DATES

HEADING	SECTION	CHANGED	SINCE	HOVEMBER	23,	1993	ISSUE
INGREDIENTS	SECTION	CHANGED	SINCE	NOVEMBER	23,	1993	ISSUE
ENVIRON. DATA	SECTION	CHANGED	SINCE	NOVEMBER	23,	1993	ISSUE
PRECAUT. INFO.	SECTION	CHANGED	SINCE	HOVEHBER	23,	1993	ISSUE
HEALTH HAZD. DATA	SECTION	CHANGED	SINCE	NOVEMBER	23,	1993	ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable

the information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using the material in commination with any

MATERIAL SAFETY DATA SHEET



1-A

Page i of 6 Issued 4/97

3 Old Sharman From Daneury CT 06810 (203) 791-3500

EMERGENCY TELEPHONE NO:

(203) 791-3500 M-F 8:30-5:00 ET

CHEMTREC 1-800-424-9300 (for Chemical Emergency

spill, leak, fire exposure or accident, 24 hours)

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

INSTAPAK . COMPONENT "A"

Chemical Name:

Polymethylene Polyphenylisocyanate

Trade Name:

Polymeric MDI

Chemical Family:

Aromatic Isocyanates

Chemical Formula:

N.A.

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients:	CAS No.	Wt.%	OSHA-PEL	ACGIH-TLV
Polymeric Diphenylmethane	9016-87-9	100	N.E.	N.E.
Diisocyanate ("polymeric" MDI)				
Contains:				
4,4'-Diphenylmethane diisocyanate			0. 02 ppm	0.005 ppm
(4,4'-MDI; CAS 101-68-8; ≈ 45%)			(Ceiling)	(TWA)
Other MDI isomers and oligomers			N.E.	N.E.

SECTION 3 - HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW

Health Hazards: Irritating to eyes, respiratory system and skin. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitized persons. Sensitized persons should not be exposed to any mixture containing unreacted MDI.

Physical Hazards: Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

Appearance: Dark brown liquid.

Odor: Slightly aromatic (musty).

Note: Read the entire MSDS for a more thorough evaluation of the hazards.

Page 1 of 6 Issued 4/97

SECTION 4 - FIRST AID MEASURES

men from Darbury CT 18816 2031 791 3500

Inhalation: Remove from further exposure and obtain medical attention. Treatment is symptomatic for primary irritation or difficulty in breathing. If breathing is labored, oxygen should be administered bqualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing. Asthmatic-like symptoms, if manifested, may develop immediately, or be delayed for up to several hours.

Skin Contact: Wash affected area thoroughly with soap and water. Launder contaminated clothing thoroughly before reuse. If irritation, redness, or a burning sensation develops and persists, obtain medical advice.

Eve Contact: Flush with copious amounts of water for at least 15 minutes, holding lids open with fingers. If irritation persists, repeat flushing. Refer individual to a physician for immediate follow-up.

Ingestion: Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water then give i or 2 glasses of water to drink. Refer person to medical personnel for immediate attention.

Note to Physicians: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for 48 hours. Pulmonary disorders may be aggravated by overexposure.

SECTION 5 - FIRE-FIGHTING MEASURES

Flash Point: 390° F (199° C) [Pensky-Martens Closed Cup]

Flammable Limits (lower): Not available Flammable Limits (upper): Not available

Extinguishing Media: Carbon dioxide (CO2), dry chemical, or chemical foam. If water is used, large quantities are required. Contain run-off water with temporary barriers.

Fire and Explosion Hazards: Containers may burst under intense heat. Avoid water contamination in closed containers; carbon dioxide is evolved which can cause pressure build-up. Caution: Reaction between water and hot isocyanate can be vigorous.

Special Fire Fighting Procedures: Firefighters must wear self-contained breathing apparatus to protect against toxic and irritating vapors; full protective clothing should also be worn.

NFPA Hazard Code:

Health:

2

Flammability: Reactivity:

Special Hazard: None

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Evacuate area surrounding the spill and prevent further leakage, spillage or entry into drains. Eye and skin protection should be worn during spill cleanup and ventilation maintained. If the potential for airborne concentrations of MDI above the PEL exists, then respiratory protection should be worn.

on, excess institutes accurate to the best knowledge of Sealed Air Corporation, The data on this acc

I-A

Page 3 of 6 Issued 4/97

Enquestro Produce Conques -3 Old Snorman Franc, Caregry, CT 26816. (223) 791-3502

SECTION 6 - ACCIDENTAL RELEASE MEASURES (continued)

Contain and cover spill with loose absorbent (earth, sand, sawdust or other absorbent material), or absorbent pillows, pads or socks. Collect absorbed material in open containers or plastic bass, and treat with deactivating solution (90% water, 8% concentrated ammonia, 2% detergent). Allow to stand uncovered for 48-72 hours to permit carbon dioxide to escape and solidification to occur. Wash spill area with deactivating solution and let stand for 15 minutes or longer. Dispose of spilled material properly.

SECTION 7 - HANDLING AND STORAGE

Storage Temperature: Min. 50° F (10° C) Max. 100° F (38° C)

Average Shelf Life: 6 months

Special Sensitivity: Reacts with moisture to produce carbon dioxide gas.

Precautions to be Taken in Handling and Storage: Do not store drums uncovered outdoors. Do not reseal containers unless it is certain that no moisture contamination has occurred. Do not breathe vapors or allow skin contact.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

OSHA-PEL:

4.4'-Diphenvimethane diisocyanate:

Ceiling = 0.02 ppm

ACGIH-TLV: 4.4'-Diphenvimethane diisocyanate;

TWA = 0.005 ppm

HMIS Hazard Code:

Health

3 1

B

Flammability

Rescrivity 1

PPE

(Personal Protective Equipment)

Respiratory Protection: Due to the low vapor pressure of this material, the PEL is not likely to be exceeded under normal conditions. If the material is heated or spilled in a confined area, respiratory protection should be worn. Because of their short life and lack of breakthrough indicators, cartridge type respirators equipped for organic vapors are generally not recommended for use with isocyanates. They can be used for short term emergency situations at concentrations below the PEL where the presence of adequate breathing oxygen can be assured. Where concentrations exceed the PEL, air supplied respirators must be used.

Eve Protection: Goggies or safety glasses with side shields.

Protective Clothing: Chemical resistant butyl rubber, nitrile rubber, neoprene, or other suitable protective gioves.

Ventilation: Use local exhaust ventilation if necessary to maintain levels below the PEL. For guidance on engineering controls refer to the ACGIH publication "Industrial Ventilation".

Other: Eyewash station, safety shower and deactivating solution should be available. Refer to the "Recommendations for the Safe Use and Handling of Instabak" Foam-in-Place Chemicals" bulletin before handling instabaka chemicals.

I-A

Page 4 of 6 Issued 4/97

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Color: Dark brown Odor: Slightly aromatic (musry)

Vapor Density (Air = 1): 8.5 Molecular Weight: Approx. 350

Melting Point: N. E.

Boiling Point: 406° F (208° C)

Vapor Pressure: < 10° mm Hg @ 25° C (for Polymeric MDI)

Specific Gravity: 1.24 @ 25° C Buik Density: 10.3 lbs/gai % Volatile by Volume: Nil

Solubility in Water: Not soluble. Reacts slowly with water

to liberate CO, ges.

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Avoid temperatures above 110° F (43° C) or below 40° F (4° C). Polymerization: May occur at elevated temperatures in the presence of moisture, alkalies, tertiary amines and metal compounds.

Conditions to Avoid: Contact with moisture and other materials which contain active hydrogen. Incompatible Materials: Water, amines, strong bases and alcohols. The reaction with water is slow at temperatures less than 120°F (49°C) but is accelerated at higher temperatures.

Hazardous Decomposition Products: Highly unlikely under normal industrial use. Exposure to fire or extreme hear may generate oxides of carbon, oxides of nitrogen, and traces of hydrogen cyanide.

SECTION 11 - TOXICOLOGICAL INFORMATION

Polymeric MDI:

LD_{se}, Orai:

>15,800 mg/kg (rat)

LD Dermai:

>5000 mg/kg (rabbit)

LC, Inhaiation:

370 - 490 mg/m³/4 hours (rat) for an aerosol of polymeric MDI

Primary Route(s) of Exposure: Skin contact from liquid. Inhalation. However, due to the low vapor pressure. overexposure is not expected under normal conditions unless material is heated or used in a poorly ventilated area.

Inhalation: This product is a respiratory irritant and potential respiratory sensitizer. Inhalation of vapor or aerosol at levels above the occupational exposure limit can cause respiratory sensitization. Symptoms may include irritation to the eyes, nose, throat, and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitized person: Sensitized persons should be removed from any further exposure. Persons with assisma-type conditions or othe: chronic respiratory diseases should be excluded from working with MDI. In a single evaluation of 5 men occupationally exposed to MDI and hydrocarbon solvent vapors under conditions where adequate ventilation or other safety precautions were not used, neuropsychologic findings were attributed to MDI.

Skin Contact: May cause irritation or rash. Can cause skin discoloration. Repeated and/or prolonged contact may result in skin sensitization. There is limited evidence from laboratory tests that skin contact may play a r in respiratory sensitization. This data reinforces the need to prevent direct skin contact and the importance of protective gloves.

2 Old Sharman Fres. Daneury CT 26810 2031 791-2500

1-4

Page 5 of 6 Issued 4/97

SECTION 11 - TOXICOLOGICAL INFORMATION (continued)

Eye Contact: Liquid can cause eye irritation, tearing, reddening and swelling. Permanent corneal injury is unlikely. Exposure to MDI vapors in excess of 0.02 ppm may cause irritation.

Ingestion: Ingestion is unlikely. Based on the acute oral LD₁₀, this product is considered practically non-toxic by ingestion. Ingestion can cause irritation and corrosive action in the mouth, stomach and digestive tract.

Chronic Effects: A study was conducted where groups of rats were exposed for 6 hours/day, 5 days/week for a lifetime to atmospheres of respirable polymeric MDI aerosol either at concentrations of 0, 0.2, 1, or 6 mg/m² (which corresponds to MDI levels equal to the OSHA-PEL, 5 times the OSHA-FEL and 30 times the OSHA-PEL). No adverse effects were observed at 0.2 mg/m² concentrations. At the 1 mg/m² concentration, minimal nasal and lung irritant effects were seen. Only at the top concentration (6 mg/m²) was there an increased incidence of benigh tumor of the lung (adenoma) and one malignant tumor (adenocarcinoma). Overall, the tumor incidence, both benigh and malignant, and the number of animals with tumors were not different. The increased incidence of lung tumors is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumor formation will occur.

Carcinogenicity: The ingredients of this product (>0.1%) are not classified as carcinogenic by ACGIH or IARC. not regulated as carcinogens by OSHA and not listed as carcinogens by NTP.

Mutagenicity: There is no substantial evidence of mutagenic potential.

Reproductive Effects: No adverse reproductive effects are anticipated.

Teratogenicity and Fetotoxicity: No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. The dose that produced this effect (1.2 ppm) is 60 times higher than the OSHA-PEL. Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations well in excess of the defined occupational exposure limits.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate and Distribution: It is unlikely that significant environmental exposure in the air or water will arise, based on consideration of the production and use of the substance.

Persistence and Degradation: Immiscible with water, but will react with water to produce carbon dioxide, and inert and non-biodegradable solids.

Aquatic Toxicity:

LC₁₀:

>1000 mg/l (Zebra tish) At the highest level of 1000 mg/l, there were no deaths.

EC₂₀ (24 hour):

>1000 mg/l (Daphnea magna)

EC,

>100 mg/l (E. Coli)

SECTION 13 - DISPOSAL CONSIDERATIONS

Incinerate or dispose of in accordance with existing federal, state and local environmental control regulations. This material is not a hazardous waste under RCRA 40 CFR 261 when disposed of in its purchased form. Small quantities should be treated with deactivation solution outlined in Section 6. Refer to the "Recommendations for the Safe Use and Handling of Instapak³ Foam-in-Place Chemicals" bulletin for additional information concerning disposal of wastes and empty containers. Chemical waste, regardless of quantity, should never be poured into drains, sewers or waterways.

I-A

Page 6 of 6 Issued 4/97

Engineeres Products Division 13 DIG Shermen Fran - Caroury - CT 28818 - (253) 791-3500

SECTION 14 - TRANSPORT INFORMATION

<u>DOT</u>: Containers less than 5,000 pounds are not regulated.

IMO: Not regulated.

IATA/ICAO Class: Not regulated.

Reportable Quantity (RO): 5.000 lbs. for Methylene diphenyl diisocyanate (MDI), CAS #101-68-8 (= 45% of product).

SECTION 15 - REGULATORY INFORMATION

OSHA Status: This product is considered hazardous under the Federal OSHA Hazard Communication Standard 19 CFR 1910.1200.

ISCA Status: All ingredients are listed or are not required to be listed.

SARA 302 Extremely Hazardous Substances: None

SARA 311/312 Hazard Categories:

Immediate (acute) Health Hazard

Delayed (chronic) Health Hazard

Reactive Hazard

SARA 313 Listed Ingredients: This product contains the following chemicals subject to the reporting requirements: 100% Disocyanate compounds (Category Code N120).

RCRA Status: Discarded product is not a hazardous waste under RCRA, 40 CFR 261, when disposed of in its purchased form.

SECTION 16 - OTHER INFORMATION

The following states have regulations that apply to the use of this product.

MA Massachusetts Hazardous Substance List

NJ New Jersey Hazardous Substance List

PA Pennsylvania Hazardous Substance List

The appropriate state agency should be contacted for further details on regulatory requirements for the substances shown below.

. .

Ingredient

CAS No.

V1. 1/4

Methylene bisphenyi isocyanate (MDI)

101-68-8

AS

(Benzene, 1,1'-methylenebis[4-] isocyanato-)

Section(s) Revised:

Format change

Printed on recycled paper (50% secondary material, minimum 10% post consumer) using vegetable based inks M-3 Rev. 4/97

4 C . NOT ESTABLISHED H.A. . MOTAPPLICABLE AT . ACTIVE INGRES

. The sale on the sale on the

MAR 9 1992

Smargancy France

Material Safety Data Sheet

708-438-1800

Section 1 Productionnifications

TRADE NAME Endcorseen 4933

DOT SHIPPING NAME

PRODUCTTYPE Return line treatment

CDDE IDENT. 15-933

Section 2: Hazardous Ingredients

	CAS NUMBER	%	EXPOSURE CRITERIA		
Morpholine	110-71-8	< 15	TUA: 20 pps	(skin)	
Cycloherylasise	108-71-6	< 30	TUA: 10 pps	(skin)	
Diethylaminosthamol	100-37-8	< 40	TUA: 10 pps	(skin)	

× NA 1719

MMIS 3-2-0			
Section 3 Physical Data			
SOILING POINT, 760 mm Hg) 150 F	MEDING POINT	WA.
FREEZING POINT	- 85 F	WAPOR PERSONAL	
SPECIFIC GRAVITY INTO 11	0 95	SOLUBERTY IN HIS	appreciable
MAPOR DENSITY (AIR = 1)	140	PARORATION RATE (Se Ace 1)	
% VOLATILES BY VOLUME	ND.		12 2
APPEARANCE & ODOR			

Clear, pale gellow liquid

Section 4 Fire & Explosion Hazard Data

FLASH POINT (& METHOD USED)

PLANMANT LIMITS IN AIR % SYVOLUME LOWER

AUTO KINITION TEMPERATURE

EXTINGUISHING MEDIA:

135 F TCC

MATER FIR

FRAM

SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters should wear full protective gear including self contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Home trous

Section 5 Reactivity Data

STABILITY PHORMAL CONDITIONS

CONDITIONS TO MOD

INCOMPATIBILITY MATERIALS TO ANCIDE

Fritzeen heet. men flage

Strong acids. cridizing agents

HAZARDOUS DECOMPOSITION PRODUCTS

Unides of carbon 1 mitrogen

HAZARDOUS POLYMERIZATION ULTI ant neers

CONDITIONS TO AVOID

GRACE Dearborn

Decirbert Division W. R. Grece & Co. - Conn., 300 Genesee Street, Lake Zurich, IL 60047 (708) 438-1800



Section 6 Health Hozangan formation

TOXICITY INFORMATION:

Exposure level not established for product. See Section 2 for component information. Exposure may occur through skin absorption.

INHALATION: Inhalation of mist may irritate respiratory passages.

INGESTION: Harmful if suallowed.

SKIN CONTACT: Prolonged or Prequent skin contact will cause irritation and may cause chemical burns. Possible skin sensitizer.

EYE CONTACT names itritation

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove affected person to fresh air and treat symptoms.

If conscious, give water to dilute and contact physician INGESTION:

immediately.

SKIN CONTACT: Wash with soap & water. Remove contaminated clothing and

wash before reuse.

EYE CONTACT: Flush with water for 15 minutes and smak medical attention.

Section 7 Special Protection Information

VENTILATION REQUIREMENTS

adequate sechanical ventilation in receip below evenume criteria

RESPIRATORY PROTECTION (SPECIFY TYPE)

Head NTON/MSNA seammed receivator is the errors medianis is errorded

EYE PROTECTION CLOVES Tenervieus,

Thesical gongles and fane shield other PROTECTIVE CLOTHING AND SQUIPMENT

Long sleeve work shirt and pents. chemical-protective aprox

Section 8 Spill or Leak Procedures

STEPS TO TAKE IF MATERIAL IS DELEASED OR SPELED

Extinguish all flames in the vicinity. Wear protective clothing including chemical resistant overshoes. Dike spill and soak up on an inert absorbent material. Flush area of spill with water.

WASTE DISPOSAL METHOD

Dispose of in accordance with federal, state and local regulations.

This product is not formulated with chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

Product is considered as EPA ignitable hazardous waste, DO01 (40 CFR 241)

Product does not contain impredients with CERCLA reportable quantities.

Section 9 Special Precautions

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store containers closed and away from extreme temperatures.

OTHER PRECAUTIONS

FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

PREPARED BY: Ruthe R.

1/24/92 DATE

N. C II CO COMPANDATO O COMPAND OF THE SE.

Æ Dearborn

Decrborn Division W ?. Grace & Co. - Conn., 300 Genesee Street, Lake Zurich, IL 60047 (708) 438-1800

Phone: 800-255-3423

602-258-2402

Date: May 1, 1990

MATERIAL SAFETY DATA SHEET

******************************	SECTION I .	- PRODUCT	IDENTIFICATION TEXTERES	*****

Product Name: AL-5(R) DE-ICING FLUID

General/Generic ID: Glycol-Alcohol Solution

INGREDIENT	CAS NO	cas name	4 701	PEL	TLV (UNITS)
		******			*********
Ethylene Glycol*	107-21-1	1,2-Ethanediol	9 5	50 ppm	50 ppe ceiling vapor
Isopropyl Alcohol	67-63-0	2-Propanol	<10	400 ppa	400 ppm

^{*}Subject to reporting requirements of Section 313 of SARA Title III

	PROPERTY	REFINEMENT	reasure tent
	Initial Boiling Point	Product	256 deg F (124 deg C) 8760 mm Hg
	Specific Gravity (H2O=1)		1.095 @ 68 deg F (20 deg C)
•	Vapor Density	Heavier Than Air	2.5 (Air=1)
	Percent Volatiles By Volume	Ingredients with initial Boiling points below 425 deg F	100%
	Appearance and Odor		Coloriess liquid, faint alcohol odor
	Vapor Pressure	Product	9.4 mm Hg & 68 deg F (20 deg C)
	Solubility in Water % by Wt.		100\$
	Evaporation Rate	Sutyl Acetate = 1	>1.00

⁽R) Registered Trademark of Canyon Industries, Inc.

Flash Point: 138 deg F (Pensky-Martens, ASTM 93)

Flammable Limits

in Air, % by Volume: Component (lowest) Lover: 2.0 Upper: 12.7

Extinguishing Media: Water, Fog or Carbon Dioxide or Dry Chemical

Special Fire Fighting

Procedures: Do not spray fires directly. A solid stream of water directed into not, burning liquid can

cause frothing. Use self-contained breathing apparatus and protective clothing.

Unusual Fire and

Explosion Hazards: None

NFPA Hazard Rating: Health: 1 Fire: 2 Reactivity: 0

Permissible Exposure Level (PEL): 50 ppa

Threshold Limit Value (TLV): 50 ppm

EFFECTS OF OVEREXPOSURE FOR PRODUCT:

Can cause irritation, redness, tearing. Eyes:

Can cause irritation. Prolonged or repeated contact can cause irritation, defatting, Skin:

deraatitis.

Excessive inhalation of vapors can cause masal and respiratory irritation. Breathing:

May cause abdominal disconfort and pain, dizziness, salaise, lumbar pain, oliguria, uremia, Swallowing:

and central nervous system depression. Severe kidney damage accompanies gross overexposure.

Chronic effects

of Overexposure: Inhalation of mists may produce signs of central nervous system effects, particularly

dizziness and mystageus.

Other Health

Hazards: None currently known.

EMERGENCY AND FIRST AID PROCEDURES:

If conscious, give two glasses of water, induce vomiting by sticking finger down throat. Call a If swallowed:

physician issediately. Never give anything by mouth to an unconscious person.

Remove contaminated clothing and thoroughly wash exposed area with soap and water. Launder If on skin:

contaminated clothing before reuse.

Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. If in eyes:

If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If If inhaled:

breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical

attention.

Conditions to Avoid: None HAZARDOUS POLYMERIZATION: Will not occur

Heat, sparks, and open flames Conditions to Avoid: Stable STABILITY:

Strong oxidizing agents (e.g. nitric and sulfuric acids, permanganates, etc.) INCOMPATIBILITY:

HAZARDOUS COMPUSTION OR

Burning may produce toxic materials: Carbon dioxide and/or carbon monoxide, etc. DECOMPOSITION PRODUCTS:

EXTERES OF THE PROCESS OF THE PROCES

STEPS TO BE TAKEN IF MATERIAL

IS RELEASED OR SPILLED:

-Vear suitable protective equipment.

-Small spills should be flushed with large quantities of water.

-Larger spills should be collected for disposal.

WASTE DISPOSAL METHOD:

Incinerate in a furnace where permitted under appropriate Federal, State, and local

regulations. See Section IX.

RESPIRATORY PROTECTION: Self-contained breathing apparatus in high concentrations.

VENTILATION:

Provide sufficient mechanical (general) and/or local exhaust ventilation to maintain exposure

below TLY (s).

PROTECTIVE GLOVES:

Vear resistant gloves such as: Rubber, Plastic, Neoprene, Buna-N.

EYE PROTECTION:

Chemical splash googles in compliance with OSMA regulations are advised.

OTHER PROTECTIVE

EQUIPMENT:

Eye bath and safety shower.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks and open flames.

May be fatal if swallowed.

Do not breathe mist. Avoid prolonged or repeated breathing of vapor.

Avoid contact with eves.

Wash thoroughly after handling.

Keep container closed. Do not store in open or unlabeled containers.

FOR INDUSTRIAL USE ONLY

OTHER PRECAUTIONS: Where heavy concentrations of a fine mist are present, a respirator should be used to

prevent inhaling mist particles. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid),

all hazard precautions given in this data sheet sust be observed.

The information contained herein is believed to be accurate but is not varranted to be whether originating with Canyon Industries, Inc. or not. The information is presented solely for consideration, investigation, and verification. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circustances.

EXERCISE #2: DETERMINING THRESHOLDS MANUFACTURING CASE STUDY

Using the information in the exercise, complete the following tasks to determine which chemicals will require you to prepare a TRI report.

- 1. Identify each listed Section 313 chemical or chemical category manufactured, processed, and/or otherwise used at the facility that you should evaluate for threshold determinations.
- 2. Use the attached threshold determination worksheets to determine which toxic chemicals meet or exceed an applicable threshold for manufacture, process, or otherwise use.
- 3. Prepare Part II, Sections 1, 2 and 3 of Form R for each Section 313 chemical that exceeds an applicable threshold.

Make any necessary assumptions and be prepared to identify the assumptions you have made and the approach you used in completing this exercise.

Facility Description and Chemical Usage

Darcy Corp. operates adjacent plants at a site in central Ohio: Plant 1 manufactures industrial refrigeration units and Plant 2 manufactures molded plastic components for a variety of consumer product applications. Plant 1 employs a staff of 1,600 employees. Plant 2 employs a staff of 800 full-time employees. The two plants operate independently.

Plant 1 uses Hi-Copper Brass Tubing (90.0 percent copper, 9.2 percent zinc) in the manufacture of the air conditioners' components. The tubing is cut, bent into the appropriate shapes, and welded into the air conditioning units. Plant 1 estimates that these activities generate over 0.5 pounds of copper releases to air and water. The purchasing department indicates that Plant 1 received 100,000 pounds of Hi-Copper Brass Tubing in the reporting year.

One of the refrigerants used by Plant 1 in its products is HCFC-22 (>98.0 percent pure). The A100 series of refrigeration units use HCFC-22. In the reporting year, the facility produced 240 of these units, each of which contains 100 pounds of HCFC-22. Information provided by the HCFC-22 supplier indicates that they delivered 20,000 pounds to the site's HCFC-22 storage tank in the reporting year. Inventory records for the HCFC-22 storage tank indicated that the tank contained 15,000 pounds at the beginning of the reporting year and 9,000 pounds at the end of the reporting year.

Plant 1 paints certain refrigeration unit components using a paint that contains 10-weight percent methyl ethyl ketone (MEK), a solvent. Paint booth logs indicate Plant 1 used 110,000 pounds of this paint in these painting operations.

Plant 2 uses a resin in an injection molding process to make various plastic components. Inventory records indicate that the facility used 300,000 pounds of the resin in the reporting year.

The resin contains 4-weight percent of barium hydroxide and 1.5 percent elemental zinc. Information obtained from the vendor indicates that during the curing of the resin, 1 pound of anhydrous ammonia is generated for each 100 pounds of resin used.

Inventory records indicate that 10,000 pounds of an adhesive that contains 12-weight percent MEK was used as a solvent in the adhesive application operations in the reporting year.

In the reporting year, a contractor painted the exterior and interior of all buildings on site. The contractor reported that their paint usage in the reporting year was 20,000 pounds, containing 5-weight percent MEK.

In the reporting year, remediation of soil contaminated with 1,1,1-trichloroethane and 2-butanone (MEK) was conducted with a soil vapor extraction (SVE) system. After being processed through an activated carbon adsorption unit that is 99 percent efficient in capturing the organic emissions, the exhaust from the SVE system is emitted to the air through a stack. The SVE system is estimated to extract from the ground and send to the activated carbon adsorption unit 20 pounds of 1,1,1-trichloroethane and 10 pounds of MEK every month. The carbon is replaced every 10 months and the spent carbon is sent to ACME for incineration.

Chemical:

#	Mixture Name or Other Identifier	Information Source	Percent by Weight	Total Weight (lbs.)	Amount of Chemical by Activity (lbs.)		ctivity (lbs.)
					Manufactured	Processed	Otherwise Used
	REPORTABLE SUBTOTAL						

#	Mixture Name or Other Identifier	Exemption	Note Fraction or Percent Exempt (if applicable)	Amount of Chemical by Activity (lbs.)		Activity (lbs.)	
·				Manufactured	Processed	Otherwise Used	
	EX	EMPT SUBTOTAL					
	TOTAL (REPORTABLE – EXEMPT)						
	REPORTING THRESHOLD						

Reporting Year:			Chemical:
-----------------	--	--	-----------

#	Mixture Name or Other Identifier	Information Source	Percent by Weight	Total Weight (lbs.)	Amount of Chemical by Activity (lbs.)		ctivity (lbs.)
	·				Manufactured	Processed	Otherwise Used
.,							
	REPORTABLE SUBTOTAL						

#	Mixture Name or Other Identifier			Amount of (Chemical by A	Activity (lbs.)
				Manufactured	Processed	Otherwise Used
	EXEM	PT SUBTOTAL				
	TOTAL (REP					
	REPORT					

Reporting Year:	Chemical:
-----------------	-----------

Mixture Name or Other Identifier	Information Source	Percent by Weight	Total Weight (lbs.)	Amount of Ch	Amount of Chemical by Activity (lb	
			Manufactured	Processed	Otherwise Used	
DEDODTAD	I E CUDTOTAL					
	Other Identifier		Other Identifier Source by Weight	Other Identifier Source by Weight (lbs.)	Other Identifier Source by Weight (lbs.) Manufactured	Other Identifier Source by Weight (lbs.) Manufactured Processed

#	Mixture Name or Other Identifier	Exemption	Note Fraction or Percent Exempt (if applicable)	Amount of Chemical by Activity (lbs.)		Activity (lbs.)
	1.			Manufactured	Processed	Otherwise Used
	EXEM					
	TOTAL (REPO					
	REPORTI					

Reporting Year: Chemic	al:
------------------------	-----

Mixture Name or Other Identifier	Information Source	Percent by Weight	Total Weight (lbs.)	Amount of Chemical by Activity (lbs		tivity (ios.)
				Manufactured	Processed	Otherwise Used
REPORTA	RI E SUBTOTAL					
		Other Identifier Source REPORTABLE SUBTOTAL		(lbs.)	(lbs.) Manufactured	(lbs.) Manufactured Processed

#	Mixture Name or Other Identifier	Exemption	Note Fraction or Percent Exempt (if applicable)	Amount of Chemical by Activity (lbs.)		Activity (lbs.)
	·			Manufactured	Processed	Otherwise Used
	EXEM	PT SUBTOTAL				
	TOTAL (REP					
	REPORT					

Reporting Year:	Chemical:
-----------------	-----------

#	Mixture Name or Other Identifier	Information Source	Percent by Weight	Total Weight (lbs.)	Amount of Chemical by Activity (lbs.)		ctivity (lbs.)
					Manufactured	Processed	Otherwise Used
	REPORTABLE SUBTOTAL						

#	Mixture Name or Other Identifier	Exemption	Note Fraction or Percent Exempt (if applicable)	Amount of Chemical by Activity (lbs.)		
				Manufactured	Processed	Otherwise Used
	EXEMI	PT SUBTOTAL				
	TOTAL (REPO	ORTABLE – EXEMPT)				
	REPORTI	NG THRESHOLD				

Chemical:

#	Mixture Name or Other Identifier	Information Source	Percent by Weight	Total Weight (lbs.)	Amount of Chemical by Activity (lbs.)		
			14		Manufactured	Processed	Otherwise Used
				_			
	REPORTABLE SUBTOTAL						

#	Mixture Name or Other Identifier	Exemption	Note Fraction or Percent Exempt (if applicable)	Amount of Chemical by Activity (lbs.)		
				Manufactured	Processed	Otherwise Used
	EXEMI					
	TOTAL (REPO					
	REPORTI	NG THRESHOLD				

EPA FORM R PART II. CHEMICAL-SPECIFIC INFORMATION

TRI Facility ID Number	
Toxic Chemical, Category or Generic Name	

						TOAR CHAIR	at, Catagory or Generic Name
SECTION 1. TOXIC CHEMICAL IDENTITY (Important: DO NOT complete this section if you completed Section 2 below.)							
1.1 CA	AS Number (Important: Enter only one n	umber exactly as it a	ppears on the Section	on 313 list. Enter calego	ory code if report	ing a chemical ca	tegory.)
1.2 Ta	xic Chemical or Chemical Category Na	me (Important: Enter	only one name exac	tly as it appears on the	Section 313 list)	
1.3 Ge	eneric Chemical Name (Important: Com	plete only if Part 1, S	ection 2.1 is checked	d "yes". Generic Name	must be structu	rally descriptive.)	
(If	istribution of Each Membe there are any numbers in boxes to reported in percentages and the 1 2 3 4	I-17, then every fi	old must be filled i	in with either 0 or so	me number b lata available,		d 100. Distribution should
	ON 2. MIXTURE COMPO	NENT IDENT	TITY (Imported	et. DO NOT second		lam Maran sam	mining Position & shows
	eneric Chemical Name Provided by Su						
SECTIO	ON 3. ACTIVITIES AND (Important: Check all t		E TOXIC CHI	EMICAL AT TH	E FACILIT	ry	
3.1 N	Manufacture the toxic che	mical: 3.2	Process the	toxic chemical	i: 3.3	Otherwise	use the toxic chemical:
a. c. d. e. f.	if produce or import: a. As a reactant b. As a formulation component c. For on-site use/processing d. For sale/distribution c. As an article component e. As a byproduct a. As a chemical processing aid b. As a manufacturing aid c. As an article component c. Ancillary or other use						
SECTIO	ON 4. MAXIMUM AMOU	NT OF THE T	OXIC CHEM	CAL ONSITE	AT ANY TI	ME DURIN	G THE CALENDAR YEAR
4.1	(Enter two-d	igit code from	instruction pa	ackage.)		a som oggå af er som ming Til s	
SECTIO	ON 5. QUANTITY OF TH	E TOXIC CH	EMICAL ENT	ERING EACH	ENVIRON	MENTAL M	EDIUM ONSITE
			A. Total Release (Enter range of	(pounds/yeer*) code or estimate**)	B. Basis o	f Estimate ode)	C. % From Stormwater
	ugitive or non-paint ir emissions	NA					
	stack or point ir emissions	NA		_			
	Xscharges to receiving streams or vater bodies (enter one name per t						
S	Stream or Water Body Nar	me					
5.3.1							
5.3.2							
5.3.3							
If additional pages of Part II, Section 5.3 are attached, indicate the total number of pages in this box and indicate the Part II, Section 5.3 page number in this box. (example: 1,2,3, etc.)							

^{*} For Dioxin or Dioxin-like compounds, report in grams/year

EPA FORM R

Toxic Chemical, Category or Generic I	Vame

PART II. CHEMICAL-SPE	ECIFIC INFORMATION	Toxic Chemical, Category or Generic Name						
ATOMA TOVIO CUENCAL INCUITATA								
SECTION 1. TOXIC CHEMICAL IDENTITY (Important: DO NOT complete this section if you completed Section 2 below.)								
1.1 CAS Number (Important: Enter only one number exact)	y as it appears on the Section 313 list. Enter category o	code if reporting a chemical category.)						
Toxic Chemical or Chemical Category Name (Important	t: Enter only one name exactly as it appears on the Sec	ction 313 Est.)						
1.2								
1.3 Generic Chemical Name (Important: Complete only If P	Part 1, Section 2.1 is checked "yee". Generic Name mu	st be structurally descriptive.)						
	lioxin and Dioxin-like Compounds Ca							
•	wary field must be filled in with either 0 or some i equal 100%. If you do not have speciation data	number between 0.01 and 100. Distribution should a waitable, Indicate NA.)						
1 2 3 4 5	6 7 8 9 10	11 12 13 14 15 16 17						
SECTION 2. MIXTURE COMPONENT II								
2.1 Generic Chamical Name Provided by Supplier (Imports	ant: Maximum of 79 characters, including numbers, letter	ers, spaces, and punctuellon.)						
SECTION 3. ACTIVITIES AND USES OF	SECTION 3. ACTIVITIES AND USES OF THE TOXIC CHEMICAL AT THE FACILITY (Important: Check all that apply.)							
3.1 Manufacture the toxic chemical:	3.2 Process the toxic chemical:	3.3 Otherwise use the toxic chemical:						
a. Produce b. Import		_						
If produce or import:	a. As a reactant	a. As a chemical processing aid						
c. For on-site use/processing d. For sale/distribution	b. As a formulation component c. As an article component	b. As a manufacturing aid						
d. For sale/distribution e. As a byproduct	d. As an article component	c. Ancillary or other use						
f. As an impurity	e. As an impurity							
SECTION 4. MAXIMUM AMOUNT OF T	HE TOXIC CHEMICAL ONSITE AT	ANY TIME DURING THE CALENDAR YEAR						
4.1 (Enter two-digit code	from instruction package.)							
SECTION 5. QUANTITY OF THE TOXIC	CHEMICAL ENTERING EACH EN	IVIRONMENTAL MEDIUM ONSITE						
	A. Total Release (pounds/year*) (Enter range code or estimate**)	B. Basis of Estimate C. % From Stormwater (enter code)						
5.1 Fugitive or non-point air emissions NA								
5.2 Stack or point air emissions NA								
5.3 Discharges to receiving streams or water bodies (enter one name per box)								
Stream or Water Body Name								
5.3.1								
5.3.2								
5.3.3								
radditional pages of Part II, Section 5.3 are attached, indicate the total number of pages in this box indicate the Part II, Section 5.3 page number in this box. (example: 1,2,3, etc.)								


								Pt	ge 2 of 5	
						TRI Facil	ity ID Number			
		EPA FORM								
	PART II. CHEMI	CAL-SPECII	FIC INFORM	ATION		Toxic Ch	emical, Category	or Generic Na	me	
SEC.	SECTION 1. TOXIC CHEMICAL IDENTITY (Important: DO NOT complete this section if you completed Section 2 below.)									
1.1	CAS Number (important: Enter only one number exactly as it appears on the Section 313 list. Enter category code if reporting a chemical category.)									
				45	4			· · · · · · · · · · · · · · · · · · ·		
1.2	Toxic Chemical or Chemical Category	Name (important Enti	or only one name exact	ny as it appears on	the Section 313	1 18L)				
4.2	Generic Chemical Name (Important: C	omplete only if Part 1,	Section 2.1 is checked	l "yea". Generic Ne	me must be str	ucturally descrip	five.)			
1.3										
1.4	Distribution of Each Memi (If there are any numbers in boxe			_	_	_	If and 100 Dielvii	willian ehavild		
	be reported in percentages and the							JUNGII SI KOSKI		
TAXA T	1 2 3	4 5 6	7 8	9 1	0 11	12 1	3 14	15 16	17	
NA										
SEC	TION 2. MIXTURE COM	PONENT IDEN	ITITY (Importan	nt: DO NOT con	npiete this s	ection if you	completed Seci	ion 1 above.)		
2.1	Generic Chemical Name Provided by	Supplier (Important: M	inximum of 70 characte	rs, including numbe	ers, letters, spec	oes, and punctus	dion.)			
2.1										
SEC	TION 3. ACTIVITIES AN		HE TOXIC CHE	MICAL AT	THE FACI	LITY			-	
3.1	Manufacture the toxic c		2 Process the	toxic chemic	cal: 3.	3 Otherw	ise use the to	wic chemic	al·	
			2 1100633 116	TOXIC CITOSIS	<u> </u>	3	190 090 110 11	AIG GIGIIIC	<u>aı.</u>	
.	If produce or import:	mport	. As a reac	tant	a	. Asa	chemical proces	sing aid		
c.	For on-site use/processir	ıg b	As a form	ulation compone	ent b	. Asa	manufacturing ai	ld		
d.	For sale/distribution	C	. As an artk	cle component	0	. Ancil	liary or other use			
ę.	As a byproduct	d	i. Repackag	ing		اسبيب				
f.	As an impurity		. As an imp	urity						
SEC	TION 4. MAXIMUM AMO	UNT OF THE	TOXIC CHEMI	CAL ONSITI	E AT ANY	TIME DU	RING THE CA	ALENDAR	YEAR	
4.1	(Enter two	-digit code fror	m instruction pa	ackage.)				34 33 :		
SEC	SECTION 5. QUANTITY OF THE TOXIC CHEMICAL ENTERING EACH ENVIRONMENTAL MEDIUM ONSITE									
			A. Total Release (Enter range o	(pounds/year	· 1	ils of Estimate er code)	C. % From	Stormwater		
5.1	Fugitive or non-point air emissions	NA		-						
5.2	Stack or point air emissions	NA 🔙								
5.3	Discharges to receiving streams water bodies (enter one name po									
	Stream or Water Body N					·		on the second of the second	ang s display title anania	
5.3.1	1									
5.3.2			†							
		······································		· · · · · · · · · · · · · · · · · · ·						
5.3.3			<u>i</u>							

(example: 1,2,3, etc.)

and indicate the Part II, Section 5.3 page number in this box.

if additional pages of Part II, Section 5.3 are attached, Indicate the total number of pages in this box

TRI RELEASE AND OTHER WASTE MANAGEMENT REPORTING



SECTION 313 REPORTING

- Importance of a structured process for release and other waste management reporting
 - Ensures accurate data
 - Reduces burden in completing Form R report
 - Systematic approach reduces redundancy over time
 - » Team approach distributes responsibility
 - Ensures compliance with TRI reporting requirements

E-3

REPORTING METHOD

- Identify potential release and other waste management sources
- Identify available data and tools
- **■** Collect data
- Estimate quantity of chemical being released and otherwise managed as waste
- **■** Document your work

TOOLS AND DATA SOURCES FOR CALCULATING REPORTING ESTIMATES

- Process flow diagrams
- Waste management manifests, invoices, and waste profiles
- **■** Environmental monitoring data
- Permit applications
- RCRA (BRS), NPDES, CAA, CERCLA and other env. reports
- Engineering calculations and other notes
- **EPA guidance**

E-5

CALCULATING REPORTING ESTIMATES

- **■** Consider all sources (routine and non-routine)
- Reasonable estimates required by law
- **■** Facility determines best approach
- Data and approach must be documented

TECHNIQUES FOR ESTIMATING CHEMICAL QUANTITIES

- Use of monitoring data (M)
- Mass balance calculation (C)
- **■** Use of emission factors (E)
- **■** Engineering calculations (O)
- Use the code on the Form R for the method used to estimate the largest portion of the release

E-7

ANALYSIS OF MONITORING DATA

- Product of measured concentrations, volumetric flow rates, and density equals pounds of chemical released per year
- Most commonly used for wastewater (Discharge monitoring reports (DMRs))
- Use Basis of Estimate code "M" if calculations based primarily on monitoring data

MASS BALANCE CALCULATION

- Mass Balance is based on the law of conservation of mass
- Input + Generation = Output + Amount Reacted + Accumulation
- Most useful in simple situations
- Use Basis of Estimate code "C"
 - Example: Estimating wastewater releases from process

E-9

USE OF PUBLISHED EMISSION FACTORS

- Emission factors are used to describe the quantity of chemical released as a function of:
 - Specific chemical used
 - Specific process used
 - · Specific equipment used
- Available in Compilation of Air Pollutant Emission Factors (AP-42)
- Use Basis of Estimate code "E" only when chemicalspecific emission factor is used

ENGINEERING CALCULATIONS

- Calculations based on best engineering judgment/assumptions
- Calculations based on process knowledge
- Use of non-chemical-specific emission factors
- Use of non-published emission factors
- Use Basis of Estimate code "O"

E-11

NON-PBT CHEMICAL ESTIMATES

- Values for non-PBT Section 313 chemicals must be entered in whole numbers
 - EPA allows using two significant figures when reporting releases and other waste management estimates
 - If estimate is more precise, additional significant figures should be used based on precision of data used to calculate the estimate
 - For estimates of non-PBT Section 313 chemicals under 1,000 pounds, a range code can be used:
 - » A= 1-10 pounds; B = 11-499 pounds; C = 500-999 pounds

"NA" VS. "0"

- Use "NA" (not applicable) when no possibility of the Section 313 chemical being released to or otherwise managed as waste in that media (e.g., facility has no on-site landfill) or when no release to or other waste management in the specific media occurs
- Use "0" when no release occurs or < 0.5 pounds of a non-PBT Section 313 chemical from a waste stream is directed towards that medium
 - Example: Discharge to water is zero; however, release possible if control equipment fails
 - Must indicate a Basis of Estimate code (i.e., M, C, E, O) for all numerical estimates, including "0"

E-13

PART II. SECTION 4: MAXIMUM AMOUNT OF THE TOXIC CHEMICAL ON-SITE AT ANY TIME DURING YEAR

- Insert appropriate code from instructions indicating the maximum quantity on-site
- Use maximum total (non-exempt) amount present at one time during reporting year, even if the Section 313 chemical is present at more than one location at the facility
- Include amounts in storage, processes, and wastes (but not those amounts which have been previously land disposed)

	SECTION 4. MAXIMUM AMOUNT OF THE TOXIC CHEMICA TANY TIME DURING THE CALENDAR YEAR	L ON-SITE
4.1	(Enter two-digit code from instruction package.)	

PART II. SECTION 4: MAXIMUM AMOUNT OF THE TOXIC CHEMICAL ON-SITE AT ANY TIME DURING YEAR

- Part II, Section 4.1: Maximum amount on-site at any time during the calendar year
 - · Based on amount in storage, process, and wastes
 - · Not the same as Tier II maximum amount on site
 - » Tier II is usually by mixtures, Form R is chemical-specific
 - » Tier II excludes hazardous wastes, Form R does not
- **■** Data sources
 - Tier II records/calculations
 - Waste inventory data

E-15

PART II. SECTION 5: QUANTITY OF THE TOXIC CHEMICAL ENTERING EACH ENVIRONMENTAL MEDIUM

- Report <u>total</u> releases of the Section 313 chemical to each environmental medium on-site
- In column A, Total Release, report total quantity
 - A range code can be used for non-PBT Section 313 chemical quantities less than 1,000 pounds
 - A = 1 10 pounds
 - B = 11 499 pounds
 - > C = 500 999 pounds

PART II. SECTION 5: ON-SITE AIR EMISSIONS

- Section 5.1 Fugitive or non-point air emissions
 - Enter total fugitive releases of the Section 313 chemical in column
 A, including leaks, evaporative losses, building ventilation, or other non-point air emissions
- Section 5.2 Stack or point air emissions
 - Enter total releases to air from point sources, including stacks, vents, pipes, ducts, storage tanks, or other confined air streams

			A. Total Release grounds year) (unior range from incirculates or collects)	S. Basis of Estimate (mter code)	C. % From Stormwater
5.1	Fugitive or non-point air emissions	□ NA			
5.2	Stack or point air emissions	□NA			

FUGITIVE EMISSIONS

- Part II, Section 5.1: Fugitive or non-point air emissions
 - Approach: ID potential sources -> ID data/tools --> estimate
- **■** Data sources/tools
 - · Engineering calculations
 - Emission factors
 - Monitoring data
 - Mass balance

STACK EMISSIONS

- Part II, Section 5.2: Stack or point-source air emissions
 - Approach: ID potential sources -> ID data/tools -> estimate
 - · Data sources/tools
 - Air permit applications
 - CAA Title V air inventories
 - » Process and production data
 - Engineering calculations
 - » Mass balance
 - » Emission factors

E-19

PART II. SECTION 5: ON-SITE WASTEWATER DISCHARGES

- Section 5.3 Releases to streams or water bodies
 - Enter names of streams or water bodies to which your facility directly discharges the Section 313 chemical. If there is no name, enter the closest stream or water body with a name
 - Enter total amount of releases to each receiving stream or water body in column A; include amounts from stormwater runoff, if available
 - Indicate in column C the percentage of the total quantity (by weight) of the Section 313 chemical contributed by stormwater

SEC	SECTION 5. QUANTITY OF THE TOXIC CHEMICAL ENTERING EACH ENVIRONMENTAL MEDIUM				
5.3	Discharges to receiving streams or water bodies (enter one name per box)				
	Stream or Water Body Name	A. Yotal Release (poundar/year) (enter range from habractions or estimate)	B. Basic of Estimate (enter code)	C. % From Stormunter	
5.3.1					
5.3.2		:			
5.2.3					

WASTEWATER DISCHARGES

- Part II, Section 5.3: Release to stream or water body and Part II, Section 6.1: Discharges to POTW
 - Approach: ID potential sources --> ID data/tools --> estimate
- Potential release sources
 - · Wastewater treatment facility discharge
 - Storm drains
- Data/tools
 - · Monitoring, if available
 - · DMRs or other required monitoring data
 - NPDES permits/permit applications
 - · Process knowledge and/or mass balance

E-21

CALCULATING WASTEWATER DISCHARGES

■ Recommended approach: Calculate the yearly pounds of methanol discharged using the following data concerning wastewater discharges of methanol:

<u>Date</u>	Conc. (mg/L)	Flow (MGD)	Amt.(lbs/day)
3/1	1.0	1.0	8.33
9/8	0.2	0.2	33
		A	verage = 4.33

(4.33 lbs/day) x (365 days/yr.) = 1581 lbs/yr.

MGD = million gallons per day

1 mg/L = 8.33 lbs/million gal

PART II. SECTION 5: ON-SITE INJECTION WELLS

- Section 5.4.1 Underground injection to Class I wells
 - Enter total amount of Section 313 chemical injected into Class I wells at facility in column A and basis of estimate code in column B
- Section 5.4.2 Underground injection to Class II V wells
 - Enter total amount of Section 313 chemical injected into Class II V wells at facility in column A and basis of estimate code in column B

SECTION 5. QUANTITY OF THE TOXIC CHEMICAL ENTERING EACH ENVIRONMENTAL MEDIUM					
			A. Total Release gounts/ year) (enter range from instructions or estimate)	B. Basis of Estimate (enter code)	C. % From Stormwater
5.4. 1	Underground injections on- alte to Class I Wells	□ NA			
5.4.1	Underground injections on- site to Class II-V Wells	□ NA			

PART II. SECTION 5: RELEASES TO LAND ON-SITE

- Section 5.5 Releases to land on-site
 - Other disposal (5.5.4) includes spills or leaks of the Section 313 chemical to land
 - Quantities of Section 313 chemicals released to air or water during the reporting year of the initial release to land (e.g., volatilization from surface impoundments) are not included here

		NA	A. Total Release (pounts) year) (enter range code from instructions or estimate)	B. Seeis of Estimate (enter code)
5.5	Disposal to land on-site			
5.5.1A	RCRA Subtitle C landfills			
5.5.1B	Other landfills			
5.5.2	Land treatment/application farming			
5.5.3	Surface impoundment			
5.5.4	Other disposal			

RELEASED TO LAND ON-SITE

- Approach: ID potential sources -> ID data/tools --> estimate
- Potential sources of release to land
 - · Intentional storage or disposal in on-site units
 - Spills
 - Leaks
- Data/tools:
 - · Operating records/analytical data
 - · Spill reports
 - · Process knowledge

E-25

CHEMICAL MIGRATION GUIDANCE

- Migration of reportable chemical within one environmental medium (e.g., from land to land: landfill leaching into soil)
 - Only required to report initial release of chemical to the environment
- Migration of chemical from one environmental medium to another (e.g., from land to air: volatilization from a lagoon) within the reporting year
 - Release estimates should be calculated and reported for all media in Part II, Sections 5, 6, and 8 of Form R

WASTE RELEASED TO LAND ON-SITE--**STORAGE**

- Storage of wastes on the land
 - · Regular shipment schedule
 - Must transfer the waste off-site before that reporting year's Form R report is submitted or July 1, whichever comes first
 - » Report material transferred off-site during the year in Part II, Section 6 of Form R
 - No regular shipment schedule
 - » Report material added to pile that remains on-site during the year as the quantity released to land, Part II, Section 5.5.4 of Form R

E-27

PART II. SECTION 6: TRANSFERS TO OFF-SITE LOCATIONS

- Includes both off-site location information and quantities of Section 313 chemicals transferred to off-site locations
- Report quantities of a Section 313 chemical sent off-site to any POTW or other location for recycling, energy recovery, waste treatment, or disposal
- Report only total quantity of a Section 313 chemical transferred off-site, not entire waste
- In Sections 6.1 and 6.2, Total Transfers, report total quantity
 - A range code can be used for non-PBT Section 313 chemical quantities less than 1,000 pounds

 - A = 1 10 pounds
 B = 11 499 pounds
 C = 500 999 pounds

PART II. SECTION 6: TRANSFERS TO POTWs

- Section 6.1 Discharges to publicly owned treatment works
 - Enter total quantity of the Section 313 chemical transferred to all POTWs and basis of estimate

6.1 DISCHARGES TO PUBLICLY OWNED TREATMENT WORKS (POTWs)				
6.1.A Total Quantity Transferred to POTWs and Basis of Estimate				
6.1.A.1 Total Transfers (pounds/year) 6.1.A.2 Basis of Estimate (enter range code or estimate) (enter code)				

E-29

PART II. SECTION 6: TRANSFERS TO POTWs

- Section 6.1.B POTW name and location
 - · Include name and address of each POTW
 - Photocopy page 3 if reporting discharges to more than 2 POTWs (TRI-ME/ATRS accommodates this without photocopying)

SECTI	ON 6. TRANSFERS	OF THE TOXIC CHEMICA	UL IN WASTES TO OFF-SITE LO	CATIONS
	6.1 DISCHARGE	S TO PUBLICLY OWNER	TREATMENT WORKS (POTWs	
6.1.B.	POTW Name			
PO	TW Address			
City	- '	State	County	Zip
6.1.B.	POTW Name			
PO	TW Address			
City		State	County	ΖΦ

PART II. SECTION 6: TRANSFERS TO OTHER OFF-SITE LOCATIONS

- Section 6.2 Transfers to other off-site locations
 - · Include name, address, and EPA identification (RCRA ID) number
 - Enter quantities, basis of estimate, and codes for multiple activities (waste treatment, disposal, recycling, and energy recovery) in Rows 1 through 4
 - Photocopy page 4 if reporting more than 2 off-site transfer locations (TRI-ME/ATRS accommodates this without photocopying)

SECTION 6.2 TRANSFERS TO OTHER OFF-SITE LOCATIONS						
6.2. OFF-SITE EPA IDENTIFICATIO	N NUMBER (RCRA ID NO.)					
Off-eite Location Name						
Off-eite Address						
City State	County	Zip Country (Non-US)				
la location under control of reporting	facility or parent company?	es 🗆 No				
A. Total Transfers (pounde/year) (enter range code or estimate)						
1.	1.	1.M				
2.	2.	2.M				
3.	3.	3.M				
4.	4.	4.M				

E-31

OFF-SITE WASTE MANAGEMENT

- Approach: ID potential sources --> ID data/tools --> estimate
- Potential sources of off-site waste management
 - Identify final disposition of the Section 313 chemical
 - » Disposal
 - Waste treatment
 - Energy recovery
 - » Recycling
- Data/tools
 - · Waste manifests and vendor receipts
 - RCRA reports
 - · Waste characterization analyses, profiles

PART II. SECTION 7: ON-SITE WASTE MANAGEMENT

Examples of on-site waste management (Section 7)

- Air pollution control devices (Section 7A)
- Wastewater treatment processes (Section 7A)
- Energy recovery devices (Section 7B)
- Recycling devices (Section 7C)

E-33

PART II. SECTION 7A: ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY

- Report each waste treatment method that the Section 313 chemical undergoes
 - Include even if method has no effect on the Section 313 chemical
- Only data element in Form R focusing on the entire waste stream rather than the Section 313 chemical in the waste stream

SECTION 7A. ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY								
Not Applicable (NA) - Check here if no on-alte waste treatment is applied to any waste stream containing the toxic chemical or chemical category.								
a. General Wasto Stream (enter code)	b. Weste Treatment Mathod(a) Sequence [eater 3-character code(a)]	c. Range of Influent Concentration	d. Weste Treatment Efficiency Estimate	a. Based on Operating Date?				
7A.1a	7A.1b 1 2	7A.1c	7A.1d	7A.1e				
	3		*	Y•• No				

PART II. SECTION 7A: ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY

- Section 7A.a General waste stream
 - Enter a waste stream code for each waste treatment method sequence
 - There are four waste stream types: Gaseous, Wastewater, Liquid Waste. Solid Waste
- Section 7A.b Waste treatment method(s) sequence
 - Enter code(s) from EPA's TRI Reporting Forms and Instructions document for on-site waste treatment method(s) used
 - Enter code(s) regardless of whether waste treatment actually affected the Section 313 chemical
 - Report waste treatment method(s) used on aggregate waste stream as single stream
 - · If applicable, enter codes in sequence in which they occur

E-35

PART II. SECTION 7A: ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY

- Section 7A.c Range of influent concentration
 - Use range of concentration of the Section 313 chemical in waste stream as it typically enters treatment equipment
 - Enter code(s) for concentration ranges (parts per million) from EPA's TRI Reporting Forms and Instructions document
- Section 7A.d Waste treatment efficiency estimate
 - Waste treatment efficiency expressed as percent removal of the <u>Section 313 chemical</u> from waste stream through biological degradation, chemical conversion, or physical removal
 - Use overall efficiency of waste treatment sequence, not a specific waste treatment method
 - Use percent removal or destruction of Section 313 chemical only, not other constituents of the waste stream

PART II. SECTION 7A: ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY

- Section 7A.e Based on Operating Data?
 - Check "yes" if efficiency estimate is based on monitoring from typical operating conditions
 - Check "no" if efficiency estimate is based on published data for similar processes or equipment supplier's literature, or if the influent or effluent waste comparison or the flow rate was otherwise estimated

E-37

PART II. SECTION 7A: ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY

■ Procedures for using two lines of data to enter 9 or more sequential waste treatment methods

SECTION 7A. ON-SITE WASTE TREATMENT METHODS AND EFFICIENCY								
Not Applicable (NA) - Check here if no on-site waste treatment is applied to any waste stream containing the toxic chemical or chemical category.								
a. General Wasto Stream (enter code)	h. Waste Treatment Mathor(h) Sequence [enter 3-chemicler code(s)]				c. Range of Influent Concentration	d. Waste Treatment Efficiency Enforces	s. Based on Operating Date?	
7A1a	7A.1b	1 P12]	P18	7A.1c	7A.1d	7A.1e	
w	3 P17 6 P21	4 P61] • [] • [P42	NA.	*	¥ 8	
	7A2b	7 P21 Ar C44] <u>•</u> [] ₂[P11	7A.2c	7A.2d	7A.2e	
7A.2a	,	~	ינ ינ	NA .		/ A.M.	/Aut	
	•	4] • [] • [1	99 %	*	
7A.3a	7A1b	1 A01] 2[NA .	7A.3c	7A.3d	7A.3a	
^		4] • [] • [1	91 %	Ž Ö	

PART II. SECTION 7B: ON-SITE ENERGY RECOVERY PROCESSES

- Enter on-site energy recovery methods for Section 313 chemical
 - Section 313 chemical must be combustible and have a significant heating value (e.g., 5,000 BTU/lb.)
 - Combustion unit is integrated into an energy recovery system (e.g., industrial furnace, industrial kiin, or boller)
- **■** Enter codes in descending order by quantities combusted

SECTION 7B. ON-SITE ENERGY RECOVERY PROCESSES							
Not Applicable (NA) - Check here if no on-site energy recovery is applied to any waste stream containing the toxic chemical or chemical category.							
Energy Recovery Methods (enter 3-character code(s))							
1	2	3	4				

E-39

PART II. SECTION 7C: ON-SITE RECYCLING PROCESSES

- Enter methods used for on-site recycling of the Section 313 chemical
 - Codes for recycling methods used are found in EPA's TRI Reporting Forms and Instructions document
 - · Do not include energy recovery processes
- Enter codes in descending order by quantities recycled

SECTION 7C. ON-SITE RECYCLING PROCESSES						
Not Applicable (NA) - Check here if no on-alte recycling is applied to any waste stream containing the toxic chemical or chemical category.						
Recycling Methods (enter 8-character code(s))						

PHOTOCOPYING PAGES OF FORM R

- Form R pages may be photocopied if additional space is necessary to complete these sections (photocopying is not necessary with TRI-ME/ATRS)
 - Section 6.1: Transfers to POTWs
 - Section 6.2: Transfers to Other Off-Site Locations
 - Section 7A: Waste Treatment Methods and Efficiency
- When photocopying pages, you must complete the box on each page to indicate the number of copies you are attaching
- For the page being photocopied, enter in the left box the total number of pages submitted including the original

original + number photocopied = total pages submitted

· In the second box, indicate the position of the individual page

Example

If additional pages of Part II, Sections 6.2/7A are attached, indicate the total number of pages in this box [3] and indicate which Part II, Sections 6.2/7A page this is, here. [3] (example: 1.2.3. etc.)


E-41


BEST PRACTICE: RECORDKEEPING

- Importance of good recordkeeping
 - Detailed records improve reporting accuracy and data quality
 - Well-labeled calculations and engineering assumptions serve as standard operating procedures for future years
 - Reduce replication
 - Ensure consistency
- Requirements
 - All records used to complete Form R reports must be kept for three years (40 CFR 372.10)
 - EPA will review records during a data quality audit

REFERENCE SOURCES

- Estimating Releases and Waste Treatment Efficiencies
- EPA Industry Guidance located at http://www.epa.gov/tri
- AP-42: Compilation of Air Pollutant Emission Factors located at http://www.epa.gov/ttn/chief
- Technology Transfer Network located at http://www.epa.gov/ttn
 - AP-42
 - WATER9 program
 - » Updates WATER8, CHEMDAT8, and CHEM9
 - TANKS program
- Perry's Chemical Engineer's Handbook; CRC Handbook of Chemistry and Physics; Lange's Handbook of Chemistry





THINGS TO REMEMBER WHEN COMPLETING SECTION 8

- Key concepts
 - Waste streams
 - · Process streams
 - · Reportable recycling
 - Source reduction activities
- Facilities should apply these concepts consistently
 - Across facility
 - · Across agency/company

F-3

RELEASES AND OTHER WASTE MANAGEMENT

- Part II, Sections 8.1 through 8.7 of Form R
 - Column A Prior Reporting Year Estimate
 - Column B Current Reporting Year Estimate
 - Column C Next Reporting Year Projection
 - Column D Following Reporting Year Projection

RELEASES AND OTHER WASTE MANAGEMENT

- Part II, Sections 8.1 through 8.7 of Form R
 - Quantity of a Section 313 chemical reported in Sections 8.1 through 8.7 does not include releases (including on-site and off-site disposal) and other off-site waste management activities resulting from remedial actions, catastrophic events, or one-time events not associated with production process. These quantities should be reported in Section 8.8 only

F-5

RELEASES

- Section 8.1: Quantity released
 - Quantity of a Section 313 chemical "released"
 - » Definition of release: "...any spilling, leaking, pumping, pouring, emitting, emptying, discharging, injecting, escaping, leaching, dumping, or disposing...into the environment..." (EPCRA Section 329(8))
 - » Includes fugitive and stack air emissions, releases to land, releases to water, underground injections, and onsite and off-site disposal
 - » Includes metals in wastes sent to a POTW (metals cannot be destroyed)

RELEASES

- Section 8.1: Quantity released (continued)
 - Section 8.1 = Sections 5 + 6.2 (disposal only) + 6.1(for metals and metal compounds only) - 8.8 (release or off-site disposal only)
 - · Possible data sources
 - » Data and calculations from Sections 5 and 6 of Form R

F-7

ENERGY RECOVERY

- Sections 8.2 and 8.3: On-site and off-site energy recovery
 - Things to remember about energy recovery
 - » Combustion unit (e.g., industrial furnace, industrial kiln, or boiler) must be integrated into an energy recovery system
 - » Section 313 chemical must have significant heating value (e.g., 5,000 BTU/lb.)
 - » Section 313 chemicals that are, or are contained in, traditional fuels should not be reported as combusted for energy recovery

ENERGY RECOVERY

- Section 8.2: On-site energy recovery
 - Quantity of Section 313 chemical used for energy recovery on-site
 - » Quantity actually combusted in the energy recovery unit
 - not the quantity entering the unit
 - A code reported in Section 7B indicates that an estimate should be calculated for Section 8.2
 - Possible data sources
 - » Engineering process specifications
 - » Mass balance calculations
 - » Best engineering judgement

F-9

ENERGY RECOVERY

- Section 8.3: Off-site energy recovery
 - Quantity of Section 313 chemical that is *transferred* off-site for energy recovery
 - Includes total quantity of Section 313 chemical transferred off-site for energy recovery purposes - not quantity actually combusted off-site
 - · Possible data sources
 - » Section 6.2 (codes M56 and M92) of Form R
 - » Receipts from off-site facilities
 - » RCRA hazardous waste manifests

RECYCLING

- Section 8.4: On-site recycling
 - Quantity of Section 313 chemical recycled on-site
 - » Includes total quantity of Section 313 chemical recovered from the recycling process and made available for further use
 - Possible data sources
 - » Engineering process specifications
 - » Mass balance calculations
 - A code reported in Section 7C indicates that an estimate should be calculated for Section 8.4

F-11

CALCULATING QUANTITY RECYCLED IN SECTION 8.4 Facility Fugitive Air Emissions Quantity Recycling Operation Unusable Residues sent offsite for disposal

RECYCLING

- Section 8.5: Off-site recycling
 - Quantity of Section 313 chemical transferred off-site for recycling
 - Includes total quantity of Section 313 chemical transferred to off-site locations for recycling
 - Possible data sources
 - » Section 6.2 of Form R (only for recycling destinations)
 - » Receipts from off-site recycling facilities
 - » RCRA hazardous waste manifests
 - » RCRA hazardous waste report (BRS)

F-13

WASTE TREATMENT

- Section 8.6: Quantity treated on-site
 - Quantity of Section 313 chemical treated on-site
 - » Includes all quantities of Section 313 chemical destroyed
 - Possible data sources
 - » Calculations used to complete Section 7A of Form R
 - Remember to include quantities that are actually destroyed (or converted to a non-listed form), not just removed from the waste stream

WASTE TREATMENT


- Section 8.7: Off-site waste treatment
 - The amount of Section 313 chemical that is transferred offsite for waste treatment
 - » Includes all quantities of Section 313 chemical transferred to off-site facilities for waste treatment
 - · Possible data sources
 - » Sections 6.1 and 6.2 (i.e., off-site transfers for waste treatment)
 - Important: Assume all Section 6.1 quantities are treated, except metals and metal compounds

F-15

REMEDIAL, CATASTROPHIC, OR ONE-TIME RELEASES

- Section 8.8: Remedial, catastrophic, or one-time releases
 - Quantity of Section 313 chemical released into the environment or transferred off-site as a result of:
 - » Remediation
 - » Catastrophic events (e.g., earthquake, hurricane, fire, floods)
 - » One-time events not associated with production processes (e.g., pipe rupture due to unexpected weather)
 - Does not include Section 313 chemicals treated, recovered for energy, or recycled ON-SITE
 - Excludes quantities in Sections 8.1 through 8.7

CALCULATING QUANTITY REPORTED IN SECTION 8.8




REMEDIAL, CATASTROPHIC, OR ONE-TIME RELEASES

- Section 8.8 (continued)
 - Possible data sources
 - » Quantities reported in Part II, Sections 5 and 6
 - » Accident investigation reports
 - » Inventory reconciliation
 - » Mass balance calculations
 - » Monitoring reports (e.g., pH, discharge monitoring reports, continuous emissions monitoring)
 - » CERCLA reports filed with the National Response Center
 - » Release notification reports required under EPCRA Section 304

SOURCE REDUCTION AND OTHER WASTE MANAGEMENT ACTIVITIES

■ Important points regarding Sections 8.1 through 8.8

- Sum of the quantities in Sections 8.1 through 8.7 equals the total quantity of the Section 313 chemical "entering any waste stream (or otherwise released into the environment) prior to recycling, treatment, or disposal." (PPA Section 6607(b)(1))
- Quantities reported in Sections 8.1 through 8.7 are exclusive of each other
- Sum of Sections 8.1 through 8.7 is mutually exclusive of the quantity in Section 8.8



PRODUCTION RATIO OR ACTIVITY INDEX

- Section 8.9: Production ratio or activity index
 - A ratio of production or activity involving the Section 313 chemical in the reporting year to production or activity in the previous year
 - Allows quantities of the Section 313 chemical reported in Sections 8.1 through 8.7 in the current year to be compared to quantities reported in the prior year
 - Production ratio or activity index is determined by dividing the level of production (or activity) in the current year by the level of production (or activity) in the prior year
 - Select methodology least likely to be affected by potential source reduction activities

F-21

PRODUCTION RATIO

- Use production ratio if Section 313 chemical usage is related to a production level
 - Equation

Quantity of Product: Current Reporting Year

Quantity of Product: Prior Reporting Year

Example:

Oven manufacturing

40,000 ovens assembled (Current RY)

= 1.14

35,000 ovens assembled (Prior RY)

ACTIVITY INDEX

- Use activity index if Section 313 chemical usage is related to an activity and not to a production level
 - Equation

Level of Activity: Current Reporting Year

Level of Activity: Prior Reporting Year

Example:

Tank washouts

60 Washouts (Current RY)

50 Washouts (Prior RY)

= 1.2

F-23

PRODUCTION RATIO OR ACTIVITY INDEX

- Possible data sources
 - Production reports
 - Maintenance records for otherwise used chemicals
 - Waste minimization section of the RCRA hazardous waste report
 - State/corporate pollution prevention reports

SOURCE REDUCTION ACTIVITIES

■ Section 8.10

- Source reduction practices used with respect to the Section 313 chemical at the facility and the methods used to identify those activities
- This section includes only those source reduction activities implemented during the reporting year
 - » Only include activities that reduce or eliminate quantities reported in Sections 8.1 through 8.7

F-25

SOURCE REDUCTION ACTIVITIES

■ Section 8.10 (continued)

- · Possible data sources
 - » Standard operating procedures
 - » Process changes or equipment changes (e.g., replacements, adjustments)
 - » Raw material changes
 - » Work orders for process changes
 - » Product redesign specifications
 - » Audit reports and follow-up actions
 - Waste minimization section of the RCRA hazardous waste report
 - » State/corporate pollution prevention reports

OPTIONAL INFORMATION

■ Section 8.11

- Facility should indicate whether additional optional information on source reduction, recycling, or pollution control activities is included with the report
- · A one-page summary is encouraged
- Facility can provide information on previous years' activities
- EPA and others use this information for granting awards and recognition to companies and employees

FORM A SUBMISSION

ALTERNATE THRESHOLD RULE

- If alternate threshold criteria met:
 - Form R report is not required
 - No release, other waste management, or source reduction reporting
 - Submit certification statement (Form A)
- Final rule published in 1994 (§372.27; November 30, 1994; 59 FR 61501)
- Does not apply to PBT chemicals

_	United State	ne .		TOXIC	CHEM	ICAL RELEAS	SE INVENTO	RY		
4	Environmental Protection Agency				CHEMICAL RELEASE INVENTORY FORM A					
WHERE TO SEND COMPLETED FORMS: 1. EPCRA Reporting Center P.O Box 3348						PROPRIATE STATE OFFICE ee instructions in Appendix F) Enter "X" here if this is a revision				
			•	VA 22116-3348 XIC CHEMICAL	RELEAS	SE INVENTORY		For EPA	A use only	
Imp	ortant: See i	nstructions	to determin	e when "No	t App	licable (NA)	" boxes she	ould be	checked.	
		Р	ART I. FAC	ILITY IDEN	NTIFI	CATION INF	ORMATIC	N		
SEC	TION 1. REPO	ORTING YEA	\R	-						
SEC	TION 2. TRAI	DE SECRET	INFORMATIO	N						
2.1	Yes (Answe	ne toxic chemical er question 2.2; substantiation fo		2 trade secret? (Do not answer 2 Go to Section 3)		2.2 Is this cop	nly if "YES" in 2.	Sanitized	Uns	anitized
SEC	TION 3. CERT	TIFICATION	(Important:	Read and si	gn afte	er completing	ali form sec	ctions.)		
amou	by certify that to the nt as defined in 40 (factured, processed	CFR 372.27 (a), (did not exceed 500	pounds for this n	eporting	year and that the c	chemical was	ortable		
Name	and official title of o	owner/operator or	r senior manageme	nt official:			Signature:			Date Signed:
SEC	TION 4. FACI	LITY IDENTI	FICATION							
4.1	-				TRI Facility ID Number					
Facility	y or Establishment Na	nme			Facility	or Establishment Na	me or Mailing Add	ress(if differe	nt from street add	iress)
Street					Mailing	Address				
City/Co	ounty/State/Zip Code				City/State/Zip Code Country (Non-US)					
			 				,	.		
4.2	This report contai	ns information fo	r: (important : ch	eck c or d if app	licable)		1 - 1 1	A Federal facility	d	GOCO
4.3	Technical Contact Name Telephone Number (include area code)					area code				
4.4 Intentionally left blank										
	Intentionally left b	lank								
4.5	Intentionally left b		Primary a.	b .		C.	d.	•.		f.
4.5			· · · · · · · · · · · · · · · · · · ·	b. Secon	nds		d. Degrees		Minutes	f. Seconds
	SIC Code (s) (4 d	ligits) Degrees	a. Minutes	Secon	· · ·	Longitude	Degrees	Lindows	Minutes	Seconds
4.5	SIC Code (s) (4 d	Degrees	8.	Secon	A 9		Degrees ermit racters)	Undergr		Seconds /ell Code
4.5 4.6 4.7	SIC Code (s) (4 d	Degrees 4.8	Minutes EPA Identification	Secon	4.9 a.	Longitude	Degrees ermit 4.10 a.	Undergr	Minutes ound Injection V	Seconds /ell Code
4.5 4.6 4.7 a. b.	SIC Code (s) (4 d Latitude Dun & Bradstreet Number(s) (9 digi	Degrees its) 4.8 a. b.	EPA Identification (RCRA I.D. No.) (Secon Number 12 characters)	4.9	Longitude	Degrees ermit racters)	Undergr	Minutes ound Injection V	Seconds /ell Code
4.5 4.6 4.7 a. b.	SIC Code (s) (4 d	Degrees its) 4.8 a. b.	EPA Identification (RCRA I.D. No.) (Secon Number 12 characters)	4.9 a.	Longitude	Degrees ermit 4.10 a.	Undergr	Minutes ound Injection V	Seconds /ell Code

Page	of
rage	ot

	EPA FORM A		
	PART II. CHEMICAL IDENTIFICATION TRIFID:		
	Do not use this form for reporting PBT chemicals including Dioxin and Dioxin-like Compounds*		
SECTIO	ON 1. TOXIC CHEMICAL IDENTITY	Report _	_of
4.4	CAS Number (Important: Enter only one number exactly as it appears on the Section 313 list. Enter category code if reporting a chemical category.)		
1.1			
4.0	Toxic Chemical or Chemical Category Name (Important: Enter only one name exactly as it appears on the Section 313 list.)		
1.2			
	Generic Chemical Name (Important: Complete only if Part 1, Section 2.1 is checked "yes". Generic Name must be structurally descriptive.)		
1.3			
SECTIO	ON 2. MIXTURE COMPONENT IDENTITY (Important: DO NOT complete this section if you completed Section 1	above.)	
	Generic Chemical Name Provided by Supplier (Important: Maximum of 70 characters, including numbers, letters, spaces, and punctuation.)		
2.1			
SECTIO	ON 1. TOXIC CHEMICAL IDENTITY	Report _	of
	CAS Number (Important: Enter only one number exactly as it appears on the Section 313 list. Enter category code if reporting a chemical category.)		
1.1			
4.0	Toxic Chemical or Chemical Category Name (Important: Enter only one name exactly as it appears on the Section 313 list.)		
1.2			
4.5	Generic Chemical Name (Important: Complete only if Part 1, Section 2.1 is checked "yes". Generic Name must be structurally descriptive.)		
1.3			
SECTI	ON 2. MIXTURE COMPONENT IDENTITY (Important: DO NOT complete this section if you completed Section	1 above.)	
2.4	Generic Chemical Name Provided by Supplier (Important: Maximum of 70 characters, including numbers, letters, spaces, and punctuation.)		
2.1			
SECTI	ON 1. TOXIC CHEMICAL IDENTITY	Report _	of
4.4	CAS Number (Important: Enter only one number exactly as it appears on the Section 313 list. Enter category code if reporting a chemical category.)		
1.1			
4.5	Toxic Chemical or Chemical Category Name (Important: Enter only one name exactly as it appears on the Section 313 list.)		
1.2			
<u> </u>	Generic Chemical Name (Important: Complete only if Part 1, Section 2.1 is checked "yes". Generic Name must be structurally descriptive.)		
1.3			
SECTI	ON 2. MIXTURE COMPONENT IDENTITY (Important: DO NOT complete this section if you completed Section	1 above.)	
	Generic Chemical Name Provided by Supplier (Important: Maximum of 70 characters, including numbers, letters, spaces, and punctuation.)		
2.1			
SECTI	ON 1. TOXIC CHEMICAL IDENTITY	Report _	of
	CAS Number (Important: Enter only one number exactly as it appears on the Section 313 list. Enter category code if reporting a chemical category.)		
1.1			
4.5	Toxic Chemical or Chemical Category Name (Important: Enter only one name exactly as it appears on the Section 313 list.)		
1.2			
	Generic Chemical Name (Important: Complete only if Part 1, Section 2.1 is checked "yes". Generic Name must be structurally descriptive.)		
1.3			
SECTI	I ON 2. MIXTURE COMPONENT IDENTITY (Important: DO NOT complete this section if you completed Section	1 above.)	-
	Generic Chemical Name Provided by Supplier (Important: Maximum of 70 characters, including numbers, letters, spaces, and punctuation.)	-	
2.1			

ALTERNATE THRESHOLD RULE

- Criteria for submitting a Form A
 - Do not exceed 1,000,000 pounds manufactured, processed, or otherwise used; and
 - Do not exceed 500 pounds for the total annual reportable amount for a Section 313 chemical. Equivalent to the sum of the quantities calculated for Sections 8.1 - 8.7 of the Form R

G-7

POP QUIZ

- You manufacture 100,000 pounds of a non-PBT Section 313 chemical. You sell 99,950 pounds as a product. You emit 25 pounds out a stack, and send 25 pounds off-site for disposal. Do you meet the criteria for submitting a Form A?
- You use 50,000 pounds of nitric acid as a cleaner.

 The entire amount is neutralized in your on-site wastewater treatment operation and there are no air or water releases. Do you meet the criteria for submitting a Form A?

ALTERNATE THRESHOLD RULE

■ Recordkeeping

- All documentation to support the determination, including:
 - » Detailed records
 - » Well-labeled calculations and assumptions
- All records used to determine eligibility to file the Form A must be kept for a period of 3 years from the date of the submission of the certification statement (§372.10(d))

G-9

OVERVIEW: FORM R VS. FORM A

■ Form R

- Standard reporting method
- For all Section 313 chemicals
- Report releases, other waste management, and source reduction activities
- Recordkeeping requirements

■ Form A

- Alternate certification statement
- Not allowed for PBT chemicals
- Use for total reportable amounts not exceeding 500 pounds
- Recordkeeping requirements

G-10