

EPA-600/2-77-029b  
June 1977

REVIEW AND ASSESSMENT OF  
DEEP-WELL INJECTION OF HAZARDOUS WASTE

Volume II - Appendices A, B, & C

by

Louis R. Reeder  
James H. Cobbs  
John W. Field, Jr.  
William D. Finley  
Steven C. Vokurka  
Bernard N. Rolfe

Louis R. Reeder and Associates  
Tulsa, Oklahoma 74135

Contract No. 68-03-2013

Project Officer

Carlton C. Wiles  
Solid and Hazardous Waste Research Division  
Municipal Environmental Research Laboratory  
Cincinnati, Ohio 45268

MUNICIPAL ENVIRONMENTAL RESEARCH LABORATORY  
OFFICE OF RESEARCH AND DEVELOPMENT  
U. S. ENVIRONMENTAL PROTECTION AGENCY  
CINCINNATI, OHIO 45268

READY  
JUN 14 1977  
U. S. ENVIRONMENTAL PROTECTION AGENCY

## DISCLAIMER

This report has been reviewed by the Municipal Environmental Research Laboratory, U. S. Environmental Protection Agency, and approved for publication. Approval does not signify that the contents necessarily reflect the views and policies of the U. S. Environmental Protection Agency, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

## FOREWORD

The Environmental Protection Agency was created because of increasing public and government concern about the dangers of pollution to the health and welfare of the American people. Noxious air, foul water, and spoiled land are tragic testimony to the deterioration of our natural environment. The complexity of that environment and the interplay between its components require a concentrated and integrated attack on the problem.

Research and development is that necessary first step in problem solution and it involves defining the problem, measuring its impact, and searching for solutions. The Municipal Environmental Research Laboratory develops new and improved technology and systems for the prevention, treatment, and management of wastewater and solid and hazardous waste pollutant discharges from municipal and community sources, for the preservation and treatment of public drinking water supplies, and to minimize the adverse economic, social, health, and aesthetic effects of pollution. This publication is one of the products of that research; a most vital communications link between the researcher and the user community.

This contract was supported by the EPA to provide a comprehensive review and data compilation of deep-well injection as a control and disposal technology for hazardous waste. Because of the large amount of information resulting from this contract, the report is divided into four volumes. Readers interested only in the general information about deep-wells are referred to Volume I. Those interested in the detailed data compiled during this work are referred to the remaining volumes in addition to Volume I. The information is providing input into the EPA's program for assessing control technologies available for managing the Nation's large quantities of hazardous materials.

Francis T. Mayo, Director  
Municipal Environmental Research  
Laboratory

## ABSTRACT

A review and analysis of the available information related to deep-well injection, and an assessment as to the adequacy of this method for managing hazardous wastes and ensuring protecting the environment was made.

One hundred-five deep-well related research projects were identified and hazardous waste research projects numbered 186. More than 1,000 papers related to deep-well injection of industrial waste were reviewed.

Geologic and engineering data are available in many areas to locate, design and operate a deep-well system receiving hazardous wastes. The most serious problems encountered are because of failure to use available geologic information and accepted and proven engineering practices in design and completion. A small group of waste chemicals with high human and ecological hazard ratings, little known degradability characteristics or long persistence times are identified as undesirable for injection unless containment within the host reservoir is certain.

There is a paucity of information on salaquifer chemistry, and the chemical and microbiological reactions of waste within a receiving salaquifer. Monitoring of deep-well systems needs to be developed into a predictive tool to be fully effective.

State statutes and regulations vary greatly on deep-well injection. To alleviate any problems arising from the use of interstate aquifers for injection, and for more effective management and control of deep-well systems, a standardization of regulations is considered necessary.

This report was submitted in fulfillment of EPA Contract 68-03-2103. The report is comprised of 4 volumes; the main text, Appendices A through C, Appendix D, and Appendices E through J. This volume is comprised of Appendices A, B, and C. Appendix A is the Bibliography of literature used during the study. Appendix B is a compilation of patents related to deep-well systems.



Appendix C provides available chracterization profiles of chemical wastes being injected into deep-wells. Other volumes provide the main text and additional appendices of detailed data.

As a result of EPA review of this document, there were a number of questions and issues raised as to the conclusions made versus those warranted based upon available information. The user is referred to Appendix J for additional information resulting from this review and the contractors' response to that review.

## CONTENTS

	<u>Page</u>
Foreword	iii
Abstract	iv
Appendix A - Bibliography	187
Appendix B - Patents Related to Deep-Well Systems	294
Appendix C - Waste Characterization Profiles	296

## SECTION XI

### APPENDIX A - BIBLIOGRAPHY

Abbott, W. G., "Organization and Operation of Cooperative Salt Water Disposal Systems," West Texas Oil Lifting Short Course, 7th Annu. Proc.: Lubbock, Texas, Texas Technol. Univ., Dep. Petrol. Eng., pp 103-104, 1960.

Abbott, W. G., "Salt Water Disposal System Design Considerations," West Texas Oil Lifting Short Course, 9th Annu. Proc.: Lubbock, Texas, Tex. Technol. Univ., Dep. Petrol. Eng., pp 183-184, 1962.

Abbott, W. G., "Salt Water Disposal System--Design, Construction, and Operation," West Texas Oil Lifting Short Course, 10th Annu. Proc.: Lubbock, Texas, Tex. Technol. Univ. Dep. Petrol. Eng., pp 17-18, 1963.

Abbott, W. G., "The Operation of Salt Water Disposal Systems," Southwestern Petroleum Short Course, 13th Annu. Proc.: Lubbock, Texas, Tex. Technol. Univ., Dep. Petrol. Eng., pp 141-143, 1966.

Abegglen, D. E., et al, The Effects of Drain Wells on the Ground Water Quality of the Snake River Plain, Idaho Bur. Mines Geol. Pamphlet 148, 51 pp, 1970.

Adams, J. R., "Dispersion in Anisotropic Porous Media," Michigan State Univ. Ph.D. thesis, 100 pp, 1967, Diss. Abs., Vol. 28, No. 1, pp 190B-191B, 1967.

Adinoff, A. M., "Disposal of Organic Chemical Wastes to Underground Formations," Industrial Waste Conference, 9th Lafayette, Ind., 1954, Proc.: Purdue Univ. Eng. Bull, Vol. 39, No. 2, pp 32-38, 1955.

Alciatore, A. F., et al, "Diatomaceous Earth Filtration of Water for Subsurface Injection," Petrol. Eng., Vol. 27, No. 5, pp B57-B58, B60, B62, 1955.

Alcorn, I. W., "Salt Water Disposal Injection Systems," Oil Weekly, Vol. 110, No. 13, p 20, 1943.

Allen, D. R., Environmental Aspects of Oil Producing Operations, Long Beach, California, 46th Annu. SPE of AIME Fall Mtg., (New Orleans, Oct. 3-6, 1971) Preprint, No. SPE-3450, 11 pp, 1971.

Allen, M. J., and S. M. Morrison, "Bacterial Movement Through Fractured Bedrock," Ground Water, Vol. 11, No. 2, pp 6-10, March-April, 1971.

Alverson, R. M., Deep Well Disposal Study for Baldwin, Escambia, and Mobile Counties, Alabama, Ala. Geol. Surv. Circ., No. 58, 53 pp, 10 Pl., 1970.

Alverson, R. M. (See Henry, H. R.)

American Association of Petroleum Geologists, Radioactive Waste Disposal Potentials in Selected Geologic Basins - a Reconnaissance Study, U. S. Atomic Energy Comm., San Francisco Oper. Office, Rep. SAN-413-2, 31 pp, 1964.

American Petroleum Institute, Subsurface Salt-Water Disposal, Div. Prod. Publication, 92 pp (Book 3 of the Vocational Training Ser.), 1960.

American Petroleum Institute, Recommended Practice for Biological Analysis of Subsurface Injection Water, Div. Prod. R. P. 38, 2nd ed., 7 pp, 1965.

Ames, L. L., Jr., and B. F. Hajek, Statistical Analysis of Cesium and Strontium Sorption on Soils, Battelle Memorial Inst. Pacific Northwest Lab. Rep., BNWL-CC-539, 11 pp, 1966.

Ames, L. L., Jr. (See Nelson, J. L.)

Amramy, A., "Waste Treatment for Groundwater Recharge," J. Water Pollut. Contr. Fed., Vol. 36 No. 3, Pt. 1, pp 296-298, 1964.

Anderson, J. R., and J. N. Dornbush, Investigation of the Influence of Waste Disposal Practices on Ground Water Qualities, S. Dak. State Univ. Water Resources Inst. Tech. Completion Rep., 41 pp, 1968.

Andresen, K. H., and F. T. Gardner, "The Use and Requirements of Subsurface Injection Water in Oil Production," Oil Gas J., Vol. 49, No. 18, pp 72-76, 1950.

Angerman, T. W., Deep-Well Disposal A New Field for Oil and Gas Techniques, API Drilling Prod. Pract., 1969, pp 169-174, 1970.

Anonymous, An Act to Prohibit the Surface Discharging Salt-water on the Surface of Lands to Prohibit Tax Deductions to those who Discharge Saltwater: and for other Purposes, Act 254, Acts of Arkansas, pp 795-796, 1969.

Anonymous, "Annu. Can. Inst. Mining Met. Western Mtg. (Saskatoon, Sask., 10/22-26/72) Program and Abstr. of P.," Can. Mining Met. Bull., Vol. 65, No. 726, pp 15-28, Oct. 1972.

Anonymous, "Automatic System at Rio Bravo Features Salt-Water Injection," Oil Gas J., Vol. 50, No. 25, pp 133-135, 1952.

Anonymous, "Basic Techniques (Water Pollution Control)," Chem. Eng., Vol. 77, No. 9, pp 63-70, April 27, 1970.

Anonymous, "California Acts to Cut Water Pollution," Oil Gas J., Vol. 55, No. 28, pp 66-67, 1957.

Anonymous, "Coaters go to the Well," Chem. Week, Vol. 100, No. 6, pp 79-80, 1967.

Anonymous, "Control of Underground Waste Disposal," J. Amer. Water Works Ass., Vol. 44, No. 8, pp 685-689, 1952.

Anonymous, "Cooperative Salt Water Disposal System Serves Earth Operators," Oil Weekly, Vol. 123, No. 6, pp 28-29, 1946.

Anonymous, "Crack Down on Oil Field Pollution," Petrol. Eng., Vol. 39, No. 7, pp 33-36, 1967.

Anonymous, "Deep Injection Wells," Water Well J., Vol. 22, No. 8, pp 12-13, 1968.

Anonymous, "Deep-Well Disposal Gaining Favor," J. Water Pollut. Contr. Fed., Vol. 45, No. 3, Pt. 1, pp 404-406, March 1973.

Anonymous, "Deep Well Injection is Effective for Waste Disposal," Environ. Sci. Technol., Vol. 2, No. 6, pp 406-410, 1968.

Anonymous, Disposal of Brines and Mineralized Waters, Kans. Statutes Ann. Secs. 55-1003 thru 55-1007, 1964.

Anonymous, "Disposal of Oil Field Brines in the Arkansas River Drainage Area in Western Kansas," Amer. J. Public Health, Vol. 27, No. 1, p 49, 1937.

Anonymous, Disposal of Oil Wastes, Oklahoma Statutes Ann., Title 52, Secs. 296, 309 thru 319, 1969 as amended (Supp. 1970).

Anonymous, "The Disposal Well Act," Texas Water Quality Bd. Publication No. 72-01, 16 pp, Feb. 1972; Abstr. No. 73-6GD-00439, Pollut. Abstr., Vol. 41, No. 6, p 36, Nov. 1973.

Anonymous, "Dowell Demonstrates Techniques for Sealing Boreholes in Salt Formations," Dowell Xtra, Vol. 26, No. 3, pp 4-5, March 1974.

Anonymous, "East Texas Water Disposal," Oil Gas J., Vol. 37, No. 30, pp 50, 52, 1938.

Anonymous, Environmental Research, API Publication No. 4206, 75 pp, Jan. 1974.

Anonymous, "Fiberglass Reinforced Epoxy Tubing Rising in Downhole Use," Petrol. Equip. Serv., Vol. 30, No. 1, pp 20-21, 1967.

Anonymous, "56th Annual Report of the State Oil and Gas Supervisor," Sum. Oper. Calif. Oil Fields, Vol. 56, No. 1, 66 pp, 6 Pl., 1970.

Anonymous, "Findings and Recommendations on Underground Waste Disposal," J. Amer. Water Works Ass., Vol. 45, No. 12, pp 1295-1297, 1953.

Anonymous, General Rules and Regulations Relating to Wells, Utah Dept. of Natural Resources, Div. of Oil and Gas Conservation, Rules C-1 thru E-6, p 28-48, 21 p, 1969.

Anonymous, Industrial Waste Conference, 22nd, 1967 Proc., Purdue Univ. Eng. Bull., Vol. 52, No. 3, Pt. 1, pp 1-552, Pt. 2, pp 553-1122, 1968.

Anonymous, Industrial Waste Conference, 23rd, 1968 Proc., Purdue Univ. Eng. Bull., Vol. 53, No. 2, Pt. 1, pp 1-618, Pt. 2, pp 619-1255, 1969.

Anonymous, "Information Sources on Water Pollution Control," J. Water Pollut. Contr. Fed., Vol. 45, No. 3, Pt. 2, pp 125-153, March 1973.

Anonymous, Injection Well Act, Texas Civil Statutes Ann. Title 128, Art. 7621B (Supp 1970).

Anonymous, Injection Well-Earthquake Relationship-Rocky Mountain Arsenal, Denver, Colorado, U. S. Army Corps Eng., Omaha Dist. Rep. Invest., 54 pp, 1966.

Anonymous, "How to Bury a Major Pollution Problem," Water Well J., Vol. 22, No. 8, p 20, 1968.

Anonymous, "Injection Well Incorporates Many Safeguards," Ground Water Age, Vol. 2, No. 10, pp 34-37, 1968.

Anonymous, "Injection Wells Pose a Potential Threat," Environ. Sci. Technol., Vol. 6, No. 2, pp 120-122, Feb. 1972.

Anonymous, "Joint Disposal Plant for Salt Oil Well Water," Nat. Petrol. News, Vol. 29, No. 47, p 23, 1937.

Anonymous, "Learning to Whip Well Woes," Chem. Week, Vol. 96, No. 15, pp 113, 115, 1965.

Anonymous, "Looking for Water? There's Plenty in the Ground" Chem. Week, Vol. 104, No. 8, pp 77-78, Feb. 22, 1969.

Anonymous, "Metropolitan Drillsite Offers Optimum Economics" Petrol. Eng., Vol. 41, No. 13, pp 51-54, Dec. 1969.

Anonymous, "Movements of Contaminants Through Geologic Formations," Water Well J., Vol. 16, No. 3, pp 12-13, 1962.

Anonymous, Plugging Oil and Gas Wells, Indiana Statutes Ann. Secs. 46-1733 thru 46-1740 (1970 Supp).

Anonymous, "Production Waste Goes Underground at Holland-Suco," Civil Eng., Vol. 36, No. 5, p 92, 1966.

Anonymous, "The Protection of Groundwater Resources," Water Well J., Vol. 24, No. 7, p 31-33, July 1970.

Anonymous, Regulation of Oil and Gas Wells, Kans. Statutes Ann. Secs. 55-115 thru 55-142, 1964.

Anonymous, "Replenishing the Aquifer with Treated Sewage Effluent," Ground Water Age, Vol. 2, No. 8, pp 30-35, 1968.

Anonymous, Rules and Regulations for Subsurface Disposal Systems, Colo. Dept. Health, Water Pollut. Contr. Comm., 1970.

Anonymous, "Salt Water Disposal," Nat. Petrol. News, Vol. 21, No. 37, p 67, 1929.

Anonymous, "Salt Water Disposal at Midale-Shell Lays 92,000 Feet of Field Gathering Lines," Oil Can., Vol. 9, No. 51, pp 13-14, 1957.

Anonymous, "Salt Water Disposal and Oilfield Water Conservation," Petrol. Equip. Serv., Vol. 30, No. 4, pp 22, 24-26, 28, 1967.

Anonymous, "Salt Water Disposal System," Oil Weekly, Vol. 99, No. 11, pp 23-26, 1940.

Anonymous, "Spent Pulping Liquors to be Discharged Underground," Chem. Eng. News, Vol. 41, No. 35, pp 128-129, 1963.

Anonymous, Subsurface Water Pollution - A Selective Annotated Bibliography, Pt. 1. Subsurface Waste Injection--Unnumbered Publ., U. S. Environ. Protect. Agency, Washington, D. C., 164 pp, March 1972.

Anonymous, "Tested Scale Control Unit Shows Promise in SWD (salt-water disposal) Wells," Kans.-Okla. Oil Reporter, Vol. 6, No. 5, pp 58-59, 1963.

Anonymous, "There's a New 'Brine Line' for East Texas Field Disposal," Petrol. Equip. Serv., Vol. 29, No. 5, pp 8-10, 1966.

Anonymous, "Underground Waste Disposal and Control," J. Amer. Water Works Ass., Vol. 49, No. 10, pp 1334-1342, 1957.

Anonymous, "Underground Waste Disposal and Groundwater Contamination," J. Amer. Water Works Ass., Vol. 52, No. 5, pp 619-622, 1960.

Anonymous, "University Scientists Study East Texas Oil Field Salt Water Disposal System," Nat. Petrol. News, Vol. 37, No. 36A, pp R726-R728, 1945.



Anonymous, Waste Disposal in Deep Wells, Nat. Ind. Pollut. Contr. Council, Washington, D. C., Feb. 1971.

Anonymous, "Waste Disposal in Deep Wells," (Unnumbered Publ.), Natl. Ind. Pollut. Contr. Council, Washington, D. C., pp 23, Feb. 1971, Com-71-50242; Abstr., Gov. Rep. Announce., Vol. 71, No. 15, p 153, Aug. 10, 1971.

Anonymous, "Unique Triple Completion Made," Petrol. Weekly, Vol. 12, No. 18, p 30, 1961.

Anonymous, "Waste Well Goes Down Over Two Miles," Eng. News-Rec., Vol. 165, No. 24, p 32, 1960.

Anonymous, "Well Technology Serves the Mining Industry," Johnson Drillers J., Vol. 41, No. 2, pp 1-4, 1969.

Archambault, J. and J. Lemoine, "Conditions du Stockage Souterrain des Residus Radioactifs (Underground Storage Conditions for Radioactive Wastes)," La Retention et la Migration des ions radioactifs dans les sols-Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 21-23, 1963, (In French with Engl. abstr.).

Ardzhevanidze, G. Sh. (See Smolyaninov, V. G.)

Argonne National Laboratory, "Waste Disposal," Reactor Fuel Process., Vol. 4, No. 1, pp 46-54, 1961.

Arlin, Z. E., "Deep Well Disposal of Uranium Tailing Water," Ground Disposal of Radioactive Wastes Conference, 2d, At. Energy of Can. Limited and U. S. At. Energy Comm. Div. Reactor Devel. Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform., TID-7628, pp 356-362, 1961.

Arlin, Z. E. (See Lynn, R. D.)

Armstrong, F. E. (See Watkins, J.)

Arnold, E. D. (ed.), Compilation and Analysis of Waste Disposal Information, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., CF-57-2-20, 295 pp, March 13, 1957.

Arnold, W. D., and J. D. Crouse, "Radium Removal from Uranium Mill Effluents with Inorganic Ion Exchangers," Ind. Eng. Chem., Process Design Devel., Vol. 4, No. 3, pp 333-337, 1965.

Bachmat, Y., "On the Similitude of Dispersion Phenomena in Homogeneous and Isotropic Porous Mediums," Water Resources Res., Vol. 3, No. 4, pp 1079-1083, 1967.

Bachmat, Y. (See Bear, J.)

Back, W., and B. B. Hanshaw, "Hydrogeology of the Northern Yucatan Peninsula, Mexico," Yucatan Field Trip Guide Book (2d edition) -- Geol. Soc. Amer., 1967 Annu. Mtg., Field Trip 7, New Orleans, La., New Orleans Geol. Soc., pp 64-78, 1967.

Baetsle, L. H., et al, "Transport van Radioisotopen in de Bodem (Transportation of Radioisotopes in the Soil)," Mededel. van de Landbouwhogeschool en de Opzoekingsstations van de staat te Gent, Vol. 30, No. 2, pp 933-940, 1965 (In Flemish with French, Engl. and Ger. abstr.).

Baetsle, L. H., and J. Souffriau, "Fundamentals of the Dispersion of Radionuclides in Sandy Aquifers (SM-83/41)," Isotopes in Hydrology--Int. At. Energy Agency and Int. Union Geodesy and Geophys., Vienna, 1966, Symp. Program, Int. At. Energy Agency (STI/PUB/141), pp 617-627, 1967.

Baetsle, L. H., and P. de Jonghe, "Investigations on the Movement of Radioactive Substances in the Ground--Part III, Practical Aspects of the Program and Physicochemical Considerations," Ground Disposal of Radioactive Wastes Conference, 2d, At. Energy of Can., Limited, and U. S. At. Energy Comm., Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-6728, pp 198-210, 1962.

Baetsle, L. H., and W. F. Maes, "Disperse van de Radioisotopen in de bodem (Dispersion of Radioisotopes in the Soil)," Pedologie, Vol. 14, No. 2, pp 205-227, 1964 (In Flemish).

Baetsle, L. H., and J. Souffriau, "Installation of Chemical Barriers in Aquifers and Their Significance in Accidental Contamination," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nuclear Energy Agency, Vienna, 1967, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 229-240, 1967.

Baetsle, L. H. (See de Jonghe, P.)

Baetsle, L. H. (See Souffriau, J.)

Baffa, J. J., and J. Bartilucci, "Wastewater Reclamation by Groundwater Recharge on Long Island," J. Water Pollut. Contr. Fed., Vol. 39, No. 3, Pt 1, pp 431-445, 1967.

Baffa, J. J., "Injection Well Experience at Riverhead, N. Y.," J. Amer. Water Works Ass., Vol. 62, No. 1, pp 41-46, Jan. 1970.

Bain, G. L., Salty Groundwater in the Pocatalico River Basin, W. Va. Geol. Econ. Surv. Circ. No. 11, Oct. 1970.

Bagretsov, V. F. (See Spitsyn, V. I.)

Bagretsov, V. F. (See Zakharov, S. I.)

Baier, D. C. (See Wesner, G. M.)

Bailey, G. W., "Reactions of Nitrogenous and Phosphatic Compounds with Soils and Geologic Strata," Soils and Sediment in Water Pollution Control, Fed. Water Pollut. Contr. Admin., Southeast Water Lab. Rep., 90 pp, 1968.

Baker, B. L., Soil Percolation Studies, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-19188, 14 pp, 1960.

Baker, B. L., Soil Percolation Studies, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-19186, 5 pp, 1960.

Baker, W. M., "Waste Disposal Well Completion and Maintenance," Ind. Water Wastes, Vol. 8, No. 6, pp 43-47 (Also in Purdue Univ. Eng. Bull., Vol. 48, No. 3, pp 66-73, 1964.

Baltz, E. H. (See Clebsch, A., Jr.)

Balukova, V. D. (See Spitsyn, V. I.)

Banks, H. O., "Utilization of Underground Storage Reservoirs," Amer. Soc. Civil Eng. Proc., Vol. 78, pp 1-15, 1952.

Baranov, Yu. I. (See Zabelin, N. V.)

Barbreau, A., "Depositif pour l'etude de la retention des radioisotopes par les rockes meubles, en fonction de la permeabilite (Device Designed to Study Radioisotope Retention by Soft Earth Material, According to the Permeability)," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 117-121, 1963 (In French with Engl. Abstr.).

Barbreau, A., and P. Escalier des Orres, "Stockage de dechets radioactifs dans des cavities formees dans le sel par dissolution--Etudes prelabes (Radioactive Waste Storage in Cavities formed by Dissolution in Salt--Preliminary Studies)," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nuclear Energy Agency, Vienna, 1967, Symp. Proc. Int. At. Energy Agency, (STI/PUB/156), pp 495-508, 1967 (In French with Engl. Abstr.).

Barbreau, A., "Possibilities of Injection of Radioactive Waste into Deep, Permeable Geological Formations," Disposal of Radioactive Wastes Into the Ground--Int. At. Energy Agency and Europe. Nuclear Energy Agency, Vienna, 1967, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 607-620, 1967.

Barbut, G., "Avoiding the Contamination of Flowing Waters and Purifying Residual Waters Within the Extraction Oil Field From Ticleni," Petrol. Gaze, Vol. 22, No. 3, pp 175-179, March 1971 (In Romanian).

Bardwell, G. E., "Some Statistical Features of the Relationship between Rocky Mountain Arsenal Waste Disposal and Frequency of Earthquakes," Mountain Geol., Vol. 3, No. 1, pp 37-42, 1966.

Barkman, J. H., and D. H. Davidson, Measuring Water Quality and Predicting Well Impairment, 46th Annu. SPE of AIME Fall Mtg., (New Orleans, Oct. 3-6, 1971) Preprint No. SPE-3543, 12 pp, 1971.

Barlow, A. C., "Basic Disposal-Well Design," AAPG & USGS Underground Waste Manag. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), pp 2080-2081, Nov. 1971.

Barr, E. J., Jr., Feasibility Study of a Seismic Reflection Monitoring System for Underground Waste-Material Injection Sites, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 207-218, 1973.

Barracclough, J. T., "Waste Injection into a Deep Limestone in Northwestern Florida," Ground Water, Vol. 4, No. 1, pp 22-24, 1966.

Barracclough, J. T., et al, Hydrology of the National Reactor Testing Station, Idaho, 1966, U. S. Geol. Surv. open-file Rep. (IDO-22049), 95 pp, 1967 (Also AEC Rep. TID-4500).

Barracclough, J. T. (See Morris, D. A.)

Barracclough, J. T. (See Robertson, J. B.)

Bartilucci, N. J. (See Baffa, J. J.)

Battle, J. L. (See Jessen, F. W.)

Batz, M. E., "Deep Well Disposal of Nylon Waste Water," Chem. Eng. Progr., Vol. 60, No. 10, pp 85-88, 1964.

Baumann, E. R. (See Huang, J. Y. C.)

Baumgartner, A. W. (See Holben, J. H.)

Bayazeed, A. F., and E. C. Donaldson, Deep Well Disposal of Steel Pickling Acid, 46th Annu. SPE of AIME Fall Mtg. (New Orleans, Oct. 3-6, 1971), Preprint No. SPE-3615, 8 pp, 1971.

Bayazeed, A. F., and E. C. Donaldson, Subsurface Disposal of Pickle Liguor, U. S. Bur. Mines Rep. Invest. No. 7804, 35 pp, 1973.

Bazhenov, Yu. M. (See Sobolev, I. A.)

Bear, J., and M. Jacobs, "On the Movement of Water Bodies Injected into Aquifers," J. Hydrol., Vol. 3, No. 1, pp 35-57, 1965.

Bear, J., and Y. Bachmat, A Generalized Theory on Hydrodynamic Dispersion in Porous Media, Int. Ass. Sci. Hydrol. Publication 72, pp 7-16, 1967.

Bear, J., "On the Tensor Form of Dispersion in Porous Media," J. Geophys. Res., Vol. 66, No. 4, pp 1185-1197, 1961.

Bear, J., "Some Experiments in Dispersion," J. Geophys. Res., Vol. 66, No. 8, pp 2455-2467, 1961.

Bear, J. (See Harpaz, Y.)

Beardon, P. (See Talbot, J. S.)

Beasley, R. B. (See Curr, R. B.)

Beckett, J. K., "Low-Cost Water Treatment Solves Disposal Problems," World Oil, Vol. 173, No. 6, pp 64-67, Nov. 1971.

Beeson, C. M. (See Johnson, N.)

Beikman, H. M., Geology of the Powder River Basin, Wyoming and Montana, with reference to Subsurface Disposal of Radioactive Wastes, U. S. Geol. Surv. Trace Elements Invest. Rep., TEI-823, 85 pp, 1962.

Belitskii, A. A., and E. I. Orlove, Okhrana podzemnykh vod ot radioaktivnykh zagryaznenii (Protection of Ground Waters from Radioactive Contamination), Moscow, Izdatel'stvo Meditsina, 208 pp, 1968.

Belot, Y., and C. Gailledreau, "Effect of Column Length on the Sr-90 Removal by a Calcite-Phosphate Column," Ground Disposal of Radioactive Wastes Conference, 2d, At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 211-213, 1962.

Belot, Y. (See Caron, C.)

Belter, W. G., "Ground Disposal - Its Role in the U. S. Radioactive Waste Management Operations," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 3-10, 1963.

Belter, W. G., "Waste Management Activities in the Atomic Energy Commission," Ground Water, Vol. 1, No. 1, pp 17-24, 1963.

Belter, W. G., "New Developments in the USAEC Ground Disposal Program 1959-1961," Ground-Disposal of Radioactive Wastes Conference, 2d, At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 12-16, 1962.

Belter, W. G., Deep Disposal Systems for Radioactive Wastes, Amer. Ass. Petrol. Geol. Mem. No. 18, pp 341-354, Dec. 1972.

Bennett, E. R., Diffusional and Convective Transport of Miscible Fluids in Granular Media, Berkeley, Calif., Calif. Univ., 185 pp (Thesis), 1967.

Bennett, R. R. (See da Costa, J. A.)

Bensen, D. W. (See Nelson, J. L.)

Beranek, J., and I. C. Roberts, "An International Programme of Ground Disposal Research and Development," La retention et migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 17-20, 1963.

Baranek, J. (See Honstead, J. F.)

Bergstrom, R. E., Feasibility of Subsurface Disposal of Industrial Wastes in Illinois, Ill. Geol. Survey Circ. 426, 18 p, 1968.

Bergstrom, R. E., "Feasibility Criteria for Subsurface Waste Disposal in Illinois," Ground Water, Vol. 6, No. 5, pp 5-9, 1968.

Berk, R. G., Disposal Well Problems in Chicago and Bakersfield Areas, ASCE Nat. Water Resources Eng. Mtg., Phoenix, Ariz., 1971.

Berk, R. G., "Disposal Well Problems in Chicago and Bakersfield Areas," J. Sanit. Eng. Div. Amer. Soc. Civil Eng. Proc., Vol. 97, No. SA5, pp 675-688, Oct. 1971.

Bernard, G. C., "Effect of Reactions between Interstitial and Injected Waters on Permeability of Rocks," Prod. Mon., Vol. 20, No. 2, pp 26-32, 1955.

Bhaskaran, T. R. (See Subrahmanyam, K.)

Bierschenk, W. H. (See Raymond, J. R.)

Bierschenk, W. H., "Hydrological Aspects of Radioactive Waste Disposal," J. Sanit. Eng. Div. Amer. Soc. Civil Eng. Proc., Vol. 84, No. SA6, 11 pp, 1958.

Bierschenk, W. H., Aquifer Characteristics and Ground Water Movement at Hanford (Wash.), U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-4500, 77 pp, 1959.

Biggar, J. W., "Considerations in the Use of Chloride and Tritium in Ground Water Recharge Operations," Bienn. Conf. on Ground Water Recharge, 3rd, 1961 Proc., Fresno, Calif., U. S. Dep. Agr., Soil and Water Conserv. Res. Div., Southwest Br., Ground-Water Recharge Lab., 3 pp, 1962.

Bignell, L.G.E., "Salt Water Disposal Wells," Oil Gas J., Vol. 30, No. 16, pp 45-46, 1935.

Billings, N., "Ground-Water Pollution in Michigan," Sewage Ind. Wastes, Vol. 22, pp 1596-1600, Dec. 1950.

Birch, F., Thermal Consideration in Deep Disposal of Radioactive Waste, Nat. Acad. Sci. - Nat. Res. Counc. Publication 588, 22 pp, 1958.

Black, H. H. (See Klassen, C. W.)

Black, W. B., "Underground Waste Disposal," Sewage Ind. Waste, Vol. 30, No. 5, pp 669-672, 1958.

Blair, J. V., "Treatment of Produced Salt Water Prior to Underground Disposal in Sand Formations," Oil Gas J., Vol. 49, No. 42, pp 176-179, 181, 183, 185, 1951.

Blanco, R. E., and F. L. Parker, Waste Treatment and Disposal Quarterly Progress Report, U. S. At. Energy, Comm. Oak Ridge Nat. Lab. Rep., ORNL-TM-482, 90 pp, 1963.

Blance, R. E., and K. E. Cowser, Waste Treatment and Disposal Semiannual Progress Report, July-December 1967, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-TM-2294, 134 pp, 1969.

Blanco, R. E. (See Parker, F. L.)

Bleakley, W. B., "Shell's SWD Meets Pollution Standards," Oil Gas J., Vol. 68, No. 38, pp 144-146, Sept. 21, 1970.



Bleakley, W. B., "Wilmington Attacks Water Problems," Oil Gas J., Vol. 70, No. 36, pp 71-73, Sept. 4, 1972.

Blomeke, J. O., et al, "Disposal in Natural Salt Formation," Sec. 3 of Radioactive Waste Disposal, Health Phys. Div. Annu. Prog. Report for Period ending Jan 30, 1963, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-3492, pp 19-37, 1963.

Blomeke, J. O. (See Bradshaw, R. L.)

Blomeke, J. O. (See de Laguna, W.)

Blomeke, J. O. (See Perona, J. J.)

Blyth, C. R. (See Bredehoeft, J. D.)

Bochever, F. M., and A. E. Oradovskaya, "Convective Salt Diffusion in a Radial Subsurface Stream in Relation to the Protection of Subsurface Waters from Contaminated Discharges," Transl. from Dokl. Vodgeo, No. 13, pp 159-180, 1966 (Soviet Hydrol: Selec. Pap., Issue No. 4, pp 416-431, 1967).

Bochever, F. M. (See Oradovskaya, A. E.)

Bodine, J. A., "Chevron CPC Experience to Aid Future Planning," Oil Gas J., Vol. 70, No. 10, pp 113-114, 119, 122, 124-125, 128, 130, March 6, 1972.

Boegly, W. J., et al, "Disposal in Natural Salt Formations," Health, Phys. Div. Annu. Prog. Rep. for Period Ending July 31, 1964, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-3697, pp 19-31, 1964.

Boegly, W. J., Jr., et al, "Project Salt Vault-Radioactive Waste Disposal in a Salt Mine," Industrial Waste Conference, 20th, Lafayette, Ind., 1965, Proc., Purdue Univ. Eng. Bull., Vol. 19, No. 41, pp 398-409, 1965.

Boegly, W. J., Jr., et al, The Feasibility of Deep-Well Injection of Waste Brine from Inland Desalting Plants, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-25081, 76 pp, 1969.

Boegly, W. J., Jr., et al, "Project Salt Vault-A Demonstration Disposal of High Level Radioactive Solids in Lyons, Kansas Salt Mine," Health Phys., Vol 12, No. 3, pp 417-424, 1966.

Boegly, W. J., Jr., et al, Disposal of Radioactive Wastes in Geologic Formations, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-P2537, 24 pp, 1966.

Boegly, W. J., Jr., et al, "Disposal of High Activity Power Reactor Wastes in Salt Mines--Mine Renovations Required for Project Salt Vault," Nucl. Eng. Design, Vol. 8, No. 3, pp 360-366, 1968.

Boegly, W. J., Jr. (See Blomeke, J. O.)

Boegly, W. J., Jr. (See Bradshaw, R. L.)

Boegly, W. J., Jr. (See Empson, F. M.)

Boegly, W. J., Jr. (See Schaffer, W. F., Jr.)

Boehme, G. (See Krause, H.)

Bonet, E. J., "Aquifer Behavior with Injection," J. Petrol. Technol., Vol. 21, pp 1210-1216, Sep. 1969.

Bookman, M., "Waste Water Role in Meeting Water Requirements," J. Sanit. Eng. Div. Amer. Soc. Civil Eng. Proc. Vol. 85, No. SA6, pp 111-125, 1959.

Boresi, A. P. (See Deere, D. U.)

Borowezyk, M., et al, "Single-Well Pulse Techniques," Isotopes in Hydrology--Int. At. Energy Agency and Int. Union Geodesy and Geophysics, Vienna, 1966, Symp. Proc., Int. At. Energy Agency (STI/PUB/141), pp 507-519, 1967.

Botset, H. G. (See Wycoff, R. D.)

Bovard, P., and A. Grauby, "Etude de la migration des radioelements dans les sols en place (Study of Radioelement Migration in the "in-place" Soils)," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 123-129, 1963 (In French with Engl. Abstr.).

Bowen, B. M., Jr., et al, "Geology and Hydrology in the Dispersal of Radioactive Wastes," Georgia Acad. Sci. Bull., Vol. 17, No. 4, pp 145-152, 1959.

Boyce, E., "The Disposal of Brines from Oil Drilling and Petroleum Operations," Amer. Water Works Ass., Vol. 29, No. 3, pp 362, 369, 1937.

Brace, W. F., "An Extension of the Griffith Theory of Fracture to Rocks," J. Geophys. Res., Vol. 65, No. 10, pp 3477-3480, 1960.

Bradford, A. (See Evans, D. M.)

Bradshaw, R. L., et al, "Ultimate Storage of High Level Waste Solids and Liquids in Salt Formations," La retentions et la migration des ions radioactifs dans les sols-Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 257-268, 1963.

Bradshaw, R. L., et al, "Model and Underground Studies of the Influence of Stress, Temperature, and Radiation on Flow and Stability in Rock Salt Mines," Int. Soc. Rock Mechanics Cong., 1st, 1966 Proc., Vol. 2, Lisbon, Port., Laboratorio Nacional Engenharia Civil, pp 429-433, 1966.

Bradshaw, R. L., et al, "Disposal of High Activity Power Reactor Wastes in Salt Mines--A Concept and Field Scale Demonstration," Nucl. Struct. Eng., Vol. 2, No. 4, pp 438-446, 1965.

Bradshaw, R. L., et al, Properties of Salt Important in Radioactive Waste Disposal, Geol. Soc. Amer. Spec. Paper 88, pp 643-659, 1968.

Bradshaw, R. L., et al, "Disposal of Solid Wastes in Salt Formation," Pt. 6 of Evaluation of Ultimate Disposal Methods for Liquid and Solid Radioactive Wastes, U. S. At. Energy Comm., Oak Ridge Nat. Lab Rep., ORNL-3358, 90 pp, 1969.

Bradshaw, R. L. (See Blomeke, J. O.)

Bradshaw, R. L. (See Boegly, W. J., Jr.)

Bradshaw, R. L. (See Empson, F. M.)

Bradshaw, R. L. (See McClain, W. C.)

Bradshaw, R. L. (See Perona, J. J.)

Bredehoeft, J. D., et al, "Possible Mechanism for Concentration of Brines in Subsurface Formations," Amer. Ass. Petrol. Geol. Bull., Vol. 47, No. 2, pp 257-269, 1963.

Bredehoeft, J. D. (See Cooper, H. H.)

Bremser, S. M. (See White, W. A.)

Brezner, G. P. (See Tofflemire, T. J.)

Briggs, L. L., Jr., Geology of Subsurface Waste Disposal in Michigan Basin, Amer. Ass. Petrol. Geol. Mem. 10, pp 128-153, 1968.

Brinkley, F. S. (See McClain, W. C.)

Brogdon, B. R. (See Knox, J. A.)

Brooks, N. H. (See List, E. J.)

Brown, D. J., et al, "Appraisal of Hanford's (Wash.) Waste Disposal in Integration of Field Techniques," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 181-188, 1963.

Brown, D. J., and J. R. Raymond, "Radiologic Monitoring of Ground Water at the Hanford Project," J. Amer. Water Works Ass., Vol. 54, No. 10, pp 1201-1212, 1962.

Brown, D. J., and J. R. Raymond, Hanford (Wash.) Experience in the Radiological Monitoring of Ground Water, Richland, Wash., General Electric Co., Hanford At. Prod. Oper. Rep., HW-SA-2566, 23 pp.

Brown, D. J., "Migration Characteristics of Radionuclides Through Sediments Underlying the Hanford Reservation," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nuclear Energy Agency, Vienna, 1967, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 215-225, 1967.

Brown, K. E., and F. W. Jessen, "Effects of Pressure and Temperature on Cavities in Salt," Trans. Soc. Petrol. Eng. AIME, Vol. 216, pp 341-345, 1959 (Tech. Rep. 8097).

Brown, P., "Pollution and Attendant Problems," Okla. Bar Ass. J., Vol. 40, No. 7, pp 417-422, 1969.

Brown, P. G., "Potential Uses of Reclaimed Municipal Waste Water," Bienn. Microbiol. Symp. 2nd, 1964 Proc., Amer. Petrol. Inst., Pap. 18, pp 144-155, 1965.

Brown, R. E., et al, "Geological and Hydrological Aspects of the Disposal of Liquid Radioactive Wastes," Seminar on Sanitary Engineering Aspects of the Atomic Energy Industry-- U. S. At. Energy Comm. and U. S. Public Health Serv., 1955 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7517, Pt. 1b, pp 413-425, 1956.

Brown, R. E., and J. R. Raymond, Geophysical Seismic Evaluation Study at Hanford (Wash.), Battelle Mem. Inst. Pacific Northwest Lab. Rep., BNWL-47, 40 pp, 1965.

Brown, R. E., Proposed Disposal to Ground of NPR Decontamination Wastes at an Inland Site, Gen. Elec. Co., Hanford At. Prod. Oper. Rep. HW-69426, 9 pp, 1961.

Brown, R. E., and J. R. Raymond, "The Measurement of Hanford's Geohydrologic Features Affecting Waste Disposal," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 77-79, 1961.

Brown, R. E. (See Brown, D. J.)

Brown, R. F. (See Keys, W. S.)

Brown, R. W., and C. W. Spalding, "Deep-Well Disposal of Spent Hardwood Pulping Liquors," J. Water Pollut. Contr. Fed., Vol. 38, No. 12, pp 1916-1925, 1966.

Brownlow, A. D. (See Champlin, J. B. F.)

Bruch, J. C., and R. L. Street, "Two-Dimensional Dispersion," J. Sanitary Eng. Div., Amer. Soc. Civil Eng. Proc., Vol. 93, No. SA6, pp 17-39, 1967.

Bruckner, W. H. (See DeChant, J.)

Bruns, H. (See Lang, A.)

Buckham, J. A. (See Slansky, C. M.)

Burgy, R. H. (See Lewis, D. C.)

Burke, R. G., "Texas Toughens Antipollution Line," Oil Gas J., Vol. 64, No. 1, pp 47-48, 1966.

Burns, R. H., "British Thoughts on Ground Disposal of Radioactive Wastes," Ground Disposal of Radioactive Wastes Conference, 2nd At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961, Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 583-589, 1962.

Burns & Roe Inc. Staff, "Disposal of Brines Produced in Renovation of Municipal Waste Water," Water Pollut. Contr. Res. Ser. No. ORD-17070 DLY 05/70, 113 pp, May 1970: Abstr. No. W71-04614, Selec. Water Resources Abstr., Vol. 4, No. 9, pp 50-51, May 1, 1971.

Butler, R. G., et al, "Underground Movement of Bacterial and Chemical Pollutants," J. Amer. Water Works, Ass., Vol. 46, No. 2, pp 97-111, 1954.

Calberg, B. L. (See Felsenthal, M.)

Calhoun, G. H. (See Carroll, F. M.)

California Department of Water Resources, Dispersion and Persistence of Synthetic Detergents in Ground Water, San Bernardino and Riverside Counties, California, Calif. Water Quality Contr. Board Publication 30, 66 pp, 1965.

California Department of Water Resources, Fresno-Clovis Metropolitan Area Water Quality Investigation, Bulletin 143-3, 54 pp, 1965.

California Department of Water Resources, Reclamation of Water from Sewage and Industrial Wastes--Progress Report, July 1, 1953-June 30, 1955, Bulletin 68, 24 pp, 1958

California University Sanitary Engineering Research Laboratory, Investigation of Travel of Pollution, Calif. Water Pollut. Contr. Board Publication 11, 218 pp, 1954.

California University Sanitary Engineering Research Laboratory, Studies in Water Reclamation, Tech. Bull. 13, 65 pp, 1955.

Callahan, J. T., "The Role of the U. S. Geological Survey in Waste Disposal Monitoring," Ground Water, Vol. 10, No. 3, pp 6-9, May-June 1972.

Callahan, J. T. (See Stewart, J. W.)

Capitant, B., et al, "Etude experimentale de l'injection a haute pression d'effluents radioactifs dans des couches geologiques disclassees (Experimental Study of the High Pressure Injection of Radioactive Effluents into Fracture Geological Layers)," Disposal of Radioactive Wastes into the Ground-- Int. At. Energy Agency and Europe. Nuclear Energy Agency, 1967, Symp. Proc., Int. At. Energy Agency, (STI/PUB/156), pp 621-650, 1967 (In French with Engl. abstr.).

Carlberg, B. L., and R. R. Matthews, Continuous Membranes to Supplement and Improve Cement Linings for Pipe, NACE Corrosion/72 Conf. (St. Louis, Mar. 20-24, 1972) Preprint No. 52, 5 pp, 1972.

Carlile, W. C. (See Knox, J. A.)

Carnahan, C. L., and J. V. A. Sharp, "Non-Equilibrium Phenomena in Chemical Transport by Ground-Water Flow Systems," Annu. AGU Fall Mtg. (San Francisco, Dec. 5, 1972) Preprint No. 72, 13 pp, 1972; Abstr. No. W73-10329, Selec. Water Resources Abstr., Vol. 6, No. 16, p 61, August 15, 1973.

Caron, C., et al, "Principe du rejet direct dans le sol des boues radioactives (Principle of 'Ground Disposal Injection' of Radioactive Sludge)," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 165-180, 1963 (In French with Engl. Abstr.).

Carpenter, H. S., Jr. (See Spalding, C. W.)

Carroll, F. M., and G. H. Calhoun, "Effect of Tubing Size on Disposal Well May be More than you Think," World Oil, Vol. 143, No. 6, pp 182, 185-186, 189, 1956.

Carter, R. F. (See Stewart, J. W.)

Case, L. C., "Chemical Problems in Salt Water Injection," World Oil, Vol. 128, No. 12, pp 142-144, 152, 1949.

Caswell, C. A., "Underground Waste Disposal--Concepts and Misconceptions," Environ. Sci. Technol., Vol. 4, No. 8, pp 642-647, 1970.

Cecil, L. K., "Underground Disposal of Process Waste Water," Ind. Eng. Chem., Vol. 42, No. 4, pp 594-599, 1950 (Also published in J. Amer. Water Works Ass., Vol. 42, No. 11, p 56, 1950).

Champlin, J. B. F., and G. G. Eicholz, "The Movement of Radioactive Sodium and Ruthenium Through a Simulated Aquifer," Water Resources Res., Vol. 4, No. 1, pp 147-158, 1968.

Champlin, J. B. F., et al, Laboratory Testing and Evaluation of Porous Permeable Rock for Nuclear Waste Disposal, U. S. Bur. Mines Rep. Invest. 6926, 33 pp, 1967.

Champlin, J. B. F., "Research on Field Problems on Injecting Solutions into Permeable Rocks," Ground Disposal of Radioactive Wastes Conference, 2nd At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961, Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 324-326, 1962.

Champlin, J. B. F., "The Transport of Radioisotopes by Fine Particulate Matter in Aquifers," Georgia Inst. Technol. Ph.D. Thesis, 199 pp, 1970; Abstr. No. 70-19, 265, Diss. Abstr. Int., Sect. B, Vol. 31, No. 4, p 2017-B, Oct. 1970.

Chappelear, J. E., and C. W. Vole, "The Injection of a Hot Liquid into a Porous Medium," Soc. Petrol. Eng. J., Vol. 9, No. 1, pp 100-114, 1969.

Chase, E. B. (See Rima, D. R.)

Chase, G. H. (See Morris, D. A.)

Chemical Engineering Progress Symposium Series 97, Amer. Inst. Chem. Eng., New York, Vol. 65, 315 pp, 1969.

Cherry, J. A., et al, Hydrogeologic Studies at a Subsurface Radioactive-Waste-Management Site in West Central Canada, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, 1973.

Christenson, C. W., and R. Thomas, "Movement of Plutonium Through Los Alamos Tuff," Ground Disposal of Radioactive Wastes Conference, 2nd At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 248-281, 1962.



Christi, R. J., Storage of Radioactive Wastes in Basement Rock Beneath the Savannah River Plant, E. I. du Pont de Nemours Savannah River Lab. Rep., DP-844, 39 pp and App. A-G (67 pp), 1964.

Clark, A. G., "Produced Water Injection System Design," Oilweek, Vol. 22, No. 31, pp 38-40, 67, Sept. 20, 1971.

Clark, F. R. (See Holland, H. R.)

Clark, J. R., and H. A. Pohl, "Earth Disposal of Radioactive Wastes at SRP (Savannah River Plant) (S. C.)," Seminar on Sanitary Engineering Aspects of the Atomic Energy Industry - U. S. At. Energy Comm. and U. S. Public Health Serv., 1955 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7517, Pt. 1a, pp 162-169, 1956.

Cleary, E. J., and D. L. Warner, Perspective on the Regulation of Underground Injection of Wastewaters, Cincinnati, Ohio River Valley Water Sanit. Comm. Rep., 88 pp, Dec. 1969.

Cleary, E. J., and D. L. Warner, "Some Considerations in Underground Wastewater Disposal," J. Amer. Water Works Ass., Vol. 62, No. 8, pp 489-498, Aug. 1970.

Cleary, J. M., Hydraulic Fracture Theory - Part 1, Mechanics and Materials, Part 2, Fracture Orientation and Possibility of Fracture Control, Ill. Geol. Surv. Circ. 251 (24 pp) and 252 (19 pp), 1958.

Clebsch, A., Jr., and E. H. Baltz, "Progress in the United States of America Toward Deep-Well Disposal of Liquid and Gaseous Radioactive Wastes," Disposal of Radioactive Wastes into the Ground, Int. At. Energy Agency and Europe; Nuclear Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 591-606, 1967.

Clebsch, A., Jr., and A. E. Peckham, "Research by the United States Geological Survey Related to the Movement of Radio-nuclides in the Earth Environment," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 189-197, 1963.

Clistter, W. E. (See Cherry, J. A.)

Cloud, W. F., "Oil Field Water Problems," Petroleum Production, Oklahoma University Press, Oklahoma City, pp 483-511, 1937.

Cocanower, R. D., et al, "Computerized Temperature Decay - An Asset to Temperature Logging," J. Petrol. Technol., Vol. 11, No. 8, pp 933-941, 1969.

Cohen, P., and C. N. Durfor, "Design and Construction of a Unique Injection Well on Long Island, New York," Geological Survey Research 1966, U. S. Geol. Surv. Prof. Pap. 550-D, pp D253, D257, 1966.

Cohen, P., and C. N. Durfor, Artificial-Recharge Experiments Utilizing Renovated Sewage-Plant Effluent-A Feasibility Study at Bay Park, New York, U.S.A., Int. Ass. Sci. Hydrol. Publication 72, pp 193-199, 1967.

Collins, A. G., How Oil & Gas Well Drilling and Production can Contribute to Pollution, Abstr., 160th Nat. Amer. Chem. Soc. Mtg. (Chicago, Sept. 14-18, 1970) Pap. No. WATR 1, 1970.

Collins, A. G., "Oil and Gas Wells-Potential Polluters of the Environment," J. Water Pollut. Contr. Fed., Vol. 43, No. 12, pp 2383-2393, Dec. 1971.

Colorado Department of Health Staff, "Rules and Regulations for Subsurface Disposal Systems," Mountain Geol., Vol. 8, No. 1, pp 31-37, Jan. 1971.

Colton, G. W., Geologic Summary of the Appalachian Basin, with Reference to the Subsurface Disposal of Radioactive Waste Solutions, U. S. Geol. Surv. Trace Elements Invest. Rep., TEI-791, 121 pp, 1961.

Columbus, N., "The Design and Construction of Hele-Shaw Models," Ground Water, Vol. 4, No. 2, pp 16-22, 1966.

Conger, H. C., Evaluation of Oxygen Corrosion in Waterflood and Disposal Water Systems, Amer. Inst. Mining Met. Petrol. Eng. Reprint, No. SPE-1775, 6 pp, 1967.

Conway, E. R., Soil Percolation Studies, U. S. At. Energy Comm Rep., TID-19189, pp 17-58, 1962.

Cooper, H. H., et al, "Response of a Finite-Diameter Well to an Instantaneous Charge of Water," Water Resources Res. Vol. 3, No. 1, pp 263-269, 1967.

- Costell, D. C. (See Morgan, J. M., Jr.)
- Cowser, K. E. (See Blanco, R. E.)
- Cowser, K. E. (See Tadmor, J.)
- Cos, L. G., and K. E. Taylor, "Designing Reliability into Saltwater Systems," Oil Gas J., Vol. 69, No. 40, pp 87-91, Oct. 4, 1971.
- Cox, W. E. (See Walker, W. R.)
- Cozzeus, F. R., "Tracing Underground Water by Means of Dyes," Amer. Dyestuff Reporter, Vol. 29, pp 169-170, Apr. 1940.
- Crain, L. J., Ground Water Pollution from Natural Gas and Oil Production in New York, New York Water Resources Comm. Rep. Invest. RI-5, 15 pp, 1969.
- Crawford, P. B., "How to Locate Casing Leaks and Thief Zones in Water Injection Wells," Prod. Mon., Vol. 26, No. 9, pp 6-8, 1962.
- Crawford, P. B., "Importance of Chemical Composition of the Infected Water on Effective Permeability," Prod. Mon., Vol. 30, pp 11-12, 1966.
- Crooker, J. T., and F. H. Schnoor, "Waste Water Injection in the Stevens Zone, Greeley Field," Oil Weekly, Vol. 121, No. 7, p 56, 1946 (Abstr. only).
- Crouse, J. D. (See Arnold, W. D.)
- Curry, R. B., and R. P. Beasley, "Flow of Colloidal Suspensions Through Porous Media as Related to Reservoir Sealing," Amer. Soc. Eng. Trans., Vol. 5, No. 2, pp 160-164, 1962.
- da Costa, J. A., and R. R. Bennett, The Pattern of Flow in the Vicinity of a Recharging and Discharging Pair of Wells in an Aquifer having Areal Parallel Flow, Int. Ass. Sci. Hydrol. Publication 52, pp 524-536, 1960.
- Dagan, G., "Hydrodynamic Dispersion in a Nonhomogeneous Porous Column," J. Geophys. Res., Vol. 72, No. 16, pp 4074, 1967.

Davids, H. W., and M. Lieber, "Underground Water Contamination by Chromium Wastes," Water Sewage Works, Vol. 98, No. 12, pp 528-534, 1951.

Davidson, D. H. (See Barkman, J. H.)

Daview, D. W. (See Wright, C. C.)

Davis, K. E. (See Funk, R. J.)

Davis, L. E. (See Stiff, H. A., Jr.)

Davis, T. F. (See Voress, H. E.)

Davis, W. B. (See Elliston, H. W.)

Davis, W. J., "West Edmond Salt Water Disposal Plant Initiates Service to Member Operators," Petrol. Eng., Vol 17, No. 3, pp 106, 108, 110, 112, 114, 1945.

Dean, B. T., "The Design and Operation of a Deep-Well Disposal System," J. Water Pollut. Contr. Fed., Vol. 37, No. 2, pp 245-254, 1965.

De Buchananne, G. D., and P. E. LaMoreaux, "Geologic Control Related to Ground-Water Contamination," Water Well J., Vol. 16, No. 3, pp 8, 40-44, 1962.

De Chant, J., and W. H. Bruckner, Control of Steel Corrosion in Chloride Waters with Anodic Inhibitor, 24th NACE Conf. (Cleveland, Ohio Mar. 18-22, 1968) Proc., pp 294-306, 1969.

Deere, D. U., et al, An Evaluation of the Factors Influencing the Stability of a Large Underground Cavity, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., AECU-4654, 85 pp, 1959.

de Jonghe, P., et al, "Etat D'avancement du Programme D'etudes sur le Mouvement de Radioelements dans le sol au C.E.N. a Mol (Status Report of the Belgian Studies Programme on the Movement of Radioelements in Soil)," La retention et la migration des ions radioactifs dans les sols-Colloque International, Saclay, France, 1962, Paris Presses Universitaires de France, pp 25-40, 1963 (In French with Engl. Abstr.).

de Jonghe, P. (See Baetsle, L. H.)

deJosselin de Jong, G., "Longitudinal and Transverse Diffusion in Granular Deposit," Trans. Amer. Geophys. Union, Vol. 39, No. 1, pp 67-74, 1958.

deJosselin de Jong, G., "Dispersion in Flow Through Porous Media," Ground Disposal of Radioactive Wastes Conference, Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7621, pp 123-130, 1961.

de Laguna, W., "Engineering Geology of Radioactive Waste Disposal," Reviews in Engineering Geology, Vol. 1, Geol. Soc. Amer., New York, pp 129-160, 1962.

de Laguna, W., Importance of Deep Permeable Disposal Formation in Location of a Large Nuclear-Fuel Reprocessing Plant, Amer. Ass. Petrol. Geol. Mem. 10, pp 21-31, 1968.

de Laguna, W., "Radioactive Waste Disposal by Hydraulic Fracturing," Ground Water, Vol. 6, No. 6, pp 47, 1968 (Abstr. only).

de Laguna, W., Radioactive Waste Disposal by Hydraulic Fracturing, Purdue Univ. Eng. Bull. Eng. Ext. Ser. No. 137 (Pt. 2), pp 795-804, 1970.

de Laguna, W., "Radioactive Waste Disposal by Hydraulic Fracturing," Ind. Water Eng., Vol. 7, No. 10, pp 32-37, Oct. 1970.

de Laguna, W., "Radioactive Waste Disposal by Hydraulic Fracturing," Nucl. Safety, Vol. 11, pp 391-400, Sept. Oct. 1970: Abstr. No. 48250, Nucl. Sci. Abstr., Vol. 24, No. 23, p 4711, Dec. 15, 1970.

de Laguna, W., and J. O. Blomeke, The Disposal of Power Reactor Waste into Deep Wells, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., CF-57-6-23, 48 pp, 1957.

de Laguna, W., et al, "Disposal by Hydraulic Fracturing," Pt. 1 of Radioactive Waste Disposal, Health Phys. Div. Annu. Progress Rep. for Period Ending July 31, 1962, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-3347, pp 5-10, 1962.

de Laguna, W., et al, "Disposal by Hydraulic Fracturing,"  
Sec. 2 of Radioactive Waste Disposal, Health Phys. Div.  
Annu. Progress Rep. for Period Ending Jan. 30, 1963, U. S.  
At. Energy Comm. Oak Ridge Nat. Lab. Rep. ORNL-3492, pp 13-  
18, 1963.

de Laguna, W., et al, Engineering Development of Hydraulic  
Fracturing as a Method for Permanent Disposal of Radioactive  
Wastes, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep.  
ORNL-4259, 261 pp, 1968.

Dennison, E. G., and F. Simpson, Hydrogeologic and Economic  
Factors in Decision Making under Uncertainty for Normative  
Subsurface Disposal of Fluid Wastes, Northern Williston  
Basin, Saskatchewan, Canada, 2nd Int. AAPG-USGS-IAHS Under-  
ground Waste Manage. & Artificial Recharge Symp. (New Orleans:  
Sept. 26-30, 1973) Preprints, Vol. 2, pp 879-927, 1973.

de Witt, W., Jr., Geology of the Michigan Basin with Refer-  
ence Subsurface Disposal of Radioactive Wastes, U. S. Geol.  
Surv. Trace Elements Invest. Rep., TEI-771, 100 pp, 1960.

Deutsch, M., Ground-Water Contamination and Legal Controls  
in Michigan, U. S. Geol. Surv. Water-Supply Pap. 1691,  
79 pp, 1963.

Deutsch, M., "Natural Controls Involved in Shallow Aquifer  
Contamination," Ground Water, Vol. 3, No. 3, pp 37-40, 1965.

Devine, J. M. (See Schmidt, L.)

Dial, L. H., "Salt Water Disposal in the East Texas Field,"  
Petrol. Eng., Vol. 15, No. 2, pp 59-62, 1943.

Dial, L. H., "Design, Construction and Operation of a Salt  
Water Disposal System," Petrol. Eng., Vol. 15, No. 12,  
pp 51-56, 1944.

Dial, L. H. (See Morris, W. S.)

Dietrich, J. A. (See Hoover, D. B.)

Dillingham, M. (See Cacanower, R. D.)

Dmitrieva, M. N. (See Malysheva, L. N.)

Dobroskok, B. E. (See Maksutov, R. A.)

Dolan, J. P., et al, "Special Applications of Drill-stem Test Pressure Data," Trans. Amer. Inst. Mining Metall. Petrol. Eng., Vol. 210, pp 318-324, 1953, (Tech. Pap. 4667).

Dolgikh, P. F. (See Mal'tsev, E. D.)

Don, N. S. (See Titkov, N. I.)

Donaldson, A. L. (See Ostroot, G. W.)

Donaldson, E. C., Subsurface Disposal of Industrial Wastes in the United States, U. S. Bur. Mines Inform. Circ. 8212, 34 pp, 1964.

Donaldson, E. C., "Injection Wells and Operations Today," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), pp 2082-2083, Nov. 1971.

Donaldson, E. C., and R. T. Johansen, The Application of Petroleum Engineering Science and Technology to Subsurface Disposal of Liquid Industrial Wastes, 45th Annu. SPE of AIME Fall Mtg. (Houston, Oct. 4-7, 1970) Preprint No. SPE-3025, 8 pp, 1970.

Donaldson, E. C., and R. T. Johansen, History of a Two-Well Industrial Waste Disposal System, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans Sept. 26-30, 1973), Preprints - Vol. 1, pp 603-621, 1973.

Donaldson, E. C. (See Bayazeed, A. F.)

Donaldson, E. C. (See Johansen, R. T.)

Dornbush, J. N. (See Anderson, J. R.)

Doty, L. F. (See Warner, D. L.)

Dracka, O. (See Mackrle, V.)

Drescher, W. J., Hydrology of Deep-Well Disposal of Radioactive Liquid Wastes, Amer. Ass. Petrol. Geol. Mem. 4, pp 399-406, 1965.

Drescher, W. J., "Hydrologic Considerations in Deep-Well Disposal of Radioactive Liquid Wastes,": Amer. Ass. Petrol. Geol. Bull., Vol. 47, No. 12, pp 2073, 1963 (Abstr. only).

Dunlop, A. K., et al, "ODSA-Oxygen Scavenger and Inhibitor," Mat. Protect., Vol. 8, No. 3, pp 27-30, 1969.

Durfor, C. N. (See Cohen, P.)

Eakin, J. L. (See Eckard, W. E.)

Earlougher, R. C., Jr., Variable-Flowrate Reservoir Limit Testing, 47th Annu. SPE of AIME Fall Mtg. (San Antonio, Oct. 8-11, 1972), Preprint No. SPE-3892, 11 pp, 1972.

Eastwood, E. R. (See Tamura, T.)

Eckard, W. E., et al, "Improving Permeability in Underground Formations--A Progress Report," Prod. Mon., Vol. 32, No. 3, p 54, 1968.

Eddy, G. E., "The Effectiveness of Michigan's Oil and Gas Law is Preventing Pollution of the State's Ground Waters," Ground Water, Vol. 3, No. 2, pp 35-36, 1965.

Eddy, G. E., "Subsurface Disposal of Industrial Wastes," Interstate Oil Compact Comm. Comm. Bull., Vol. 9, No. 2, pp 71-79, 1967.

Eddy, G. E. (See Ives, R. E.)

Edgerton, J. H. (See Bowen, B. M., Jr.)

Edigarov, G. N., "Sostoyaniye ochistnykh sooruzheniy kanalizatsii na promyslakh npu Bavlyneft' (Status of Waste Purification and Disposal in the Oil Fields of Bavlyneft)," Konferentsia po bor'ba zagryazneniem vodoemov, Moscow, 1956 (Conference on Struggle with Pollution of Reservoirs by Waste Waters) Moscow, Gosudarstvennoe Nauchno-Tekhnicheskoe Izdatel'stvo Neftyanoi i Gorno-Toplivnoi Literatury (State Scientific Technical Publishing House of Petroleum and Mining Industry), pp 40-43, 1958 (In Russian).

Edmund, R. W., and E. D. Goebel, Subsurface Waste-Disposal Potential in Salina Basin of Kansas, Amer. Ass. Petrol. Geol. Mem. 10, pp 154-164, 1968.



Ehrlich, G. G., "Role of Biota in Underground Waste Injection and Storage," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.: Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2083, Nov. 1971.

Eichenberg, W., "Dalum Oil Field," Erdoel Erdgas Z., Vol. 85, No. 4, pp 126-136, April 1969 (In German).

Eicholz, G. G. (See Champlin, J. B. F.)

Einarsen, C. A. (See Dolan, J. P.)

Elliott, A. M., "Subsurface Waste Disposal Problems," Industrial Water and Waste Conference, 7th, Tex. Water Pollut. Contr. Ass. Proc., Tex. Univ., Austin, Tex., pp 111-37 - 111-47, 1967.

Ellis, W. R., et al, "The Investigation of Water Flow Through Porous Mediums by Means of Radiotracers," Water Resources Res., Vol. 4, No. 2, pp 413-416, 1968.

Elliston, H. H., "Design and Operation of Subsurface Salt-Water Disposal System," Oil Weekly, Vol. 122, No. 2, pp 34-38, 1946.

Elliston, H. H., Salt Water Disposal Systems, Amer. Petrol. Inst. Drilling and Prod. Pract., 1942, pp 98-117, 1943.

Elliston, H. W., and W. B. Davis, "A Method of Handling Salt-Water Disposal Including Treatment of Water," Oil Gas J., Vol. 43, No. 4, pp 59-61, 1944.

Emara, S. (See Mitry, E.)

Embshoff, A. C., "Treating Oil-Field Waters," Oil Gas J., Vol. 34, No. 52, pp 199, 202, 1936.

Empson, F. M., et al, Radioactive Waste Disposal in Salt, Geol. Soc. Amer. Spec. Pap. 73, pp 273-274, 1963 (Abstr. only).

Empson, F. M., et al, "Demonstration of Disposal of High-Level Radioactive Solids in Salt," Symp. on Salt, 2nd, Vol. 1, Northern Ohio Geol. Soc., Cleveland, Ohio, pp 432-443, 1966.

Empson, F. M., et al, Demonstration of Disposal of High-Level Radioactive Solids in Salt, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-P-1568, 33 pp, 1964.

Empson, F. M., et al, Project Salt Vault--Design and Operation, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-P-2058, 20 pp, 1966.

Empson, F. M. (See Boegly, W. J., Jr.)

Empson, F. M. (See Bradshaw, R. L.)

Empson, F. M. (See McClain, W. C.)

Engquist, M. A., and V. H. Ryan, "An Economical Method of Preparing Oil Well Brines for Disposal," Amer. Chem. Soc., Petrol. Chem. Div. Water, Sewage Sanit. Chem. Div. Joint Symp. Proc., Am. Chem. Soc., Washington, D. C., pp 169-176, 1953.

Erickson, M. D., and R. A. Walker, Ground Water Analog Test Model, General Elec. Co., Hanford At. Prod. Oper. Rep., HW-80086, 14 pp, 1964.

Escalier des Orres, P. (See Barbreau, A.)

Esmail, O. J., and O. K. Kimbler, "Investigation of the Technical Feasibility of Storing Fresh Water in Saline Aquifers," Water Resources Res., Vol. 3, No. 3, pp 683-695, 1967.

Esmaili, H., and V. H. Scott, "Unconfined Aquifer Characteristics and Well Flow," J. Irrig. Drainage Div., Amer. Soc. Civil Eng. Proc., Vol. 94, No. IR 1, pp 115-136, 1968.

Esmaili, H., "A Solution for Determination of Aquifer Characteristics and Unsteady Flow Through Injection Wells by Numerical Methods," California Univ., Davis, D. Eng. Thesis, 112 pp, 1966; Diss. Abstr., Vol. 27, No. 11, p 3923-B, 1967.

Essig, T. H., Radiological Status of the Ground Water Beneath the Hanford Project, January-June 1968, Battelle Mem. Inst. Pacific Northwest Lab. Rep., BNWL-984, 20 pp, 1969.

Evans, D. M., "The Denver Area Earthquakes and the Rocky Mountain Arsenal Disposal Well," Mountain Geol., Vol. 3, No. 1, pp 23-36, 1966.

Evans, D. M., and A. Bradford, "Under the Rug," Environment, Vol. 11, No. 8, pp 3-31, 1969.

Ewing, B. B. (See Kaufman, W. J.)

Fagin, K. M., "Salt Water Injection Projects in Oklahoma," Petrol. Eng., Vol. 23, No. 4, p B72, 1951.

Fair, G. M., et al, "Ground-Water Flow," Water Supply and Wastewater Removal, Vol. 1 of Water and Wastewater Engineering, John Wiley and Sons, New York, pp 9-1 - 9-35, 1966.

Farah, M. Y. (See Mitry, E.)

Farvolden, R. N. (See Maxey, G. B.)

Farvolden, R. N. (See Williams, R. E.)

Fast, C. R. (See Howard, G. C.)

Faulkner, G. L. (See Puri, H. S.)

Fellows, F. G., "Removing Oils, Tars, Alkalis from Refinery Wastes," Wastes Eng., Vol. 22, No. 9, pp 468-470, 1951.

Felsenthal, M., and B. L. Calberg, "Measuring Quality of Injection Waters," Petrol. Eng., Vol. 28, No. 12, pp B53-B55, 1956.

Feltis, R. C. (See Goode, H. D.)

Fenimore, J. W. (See Reichert, S. O.)

Ferris, J. G., "Ground-Water Aquifers as Waste-Disposal Reservoirs--An Outline of the Basic Hydrologic Problems Involved," Pollution Abatement Conf. Proc., Manufacturing Chem. Ass., Washington, D. C., pp 68-74, 1951.

Ferry, H. C., "Disposal of Wastes from California Oil Fields" Petrol. World, Vol. 52, No. 17, p 12, 1955 (Abstr. only).

Fetter, G. W., Jr., and R. G. Holzmacher, "Groundwater Recharge with Treated Wastewater," J. Water Pollut. Contr. Fed., Vol. 46, No. 2, pp 260-270, Feb. 1974.

Fineman, P., "Progress in Waste-Disposal Research and Development," Power Reactor Technol., Vol. 10, No. 2, pp 176-179 (Spring), 1967.

Fink, B. E., "State Regulation of Subsurface Disposal in Texas," Industrial Water and Waste Conference, 7th, Tex. Water Pollut. Contr. Ass. Proc., Tex. Univ., Austin, pp 111-58 - 111-66, 1967. (Also in Water and Sewage Works, Vol. 116, No. 5, pp 1/W-20 - 1/W-22, 1967).

Fink, B. E., Investigation of Ground-and Surface-Water Contamination near Harrold, Wilbarger County, Texas, Tex. Water Comm. Rep., LD-0365, 22 pp, 1965.

Finklea, E. E. (See Moran, J. H.)

Finogenov, I. S., and G. N. Girilovich, "Cementing of Deep Wells with a Construction Type of Slag-Portland Cement," Neft Khoz, No. 2, pp 16-19, Feb. 1971 (In Russian).

Fox, C., "Radioactive Isotopes Trace Underground Waters," Public Works, Vol. 83, pp 57-58, Jan. 1952 (Also published in Munic. Util., Vol. 90, No. 4, pp 30-32, 1952).

Fox, J. K., "Policies for Effective and Economic Control of the Environment," Executive Management Seminar, Washington, D.C., Feb. 7-9, 1969, Wisc. Univ. Water Resources Res. Center, 22 pp, 1969.

Frank, W. J., "Engine Exhaust Economically Sweetens Injection Water," World Oil, Vol. 168, No. 4, pp 79-80, 83, 86, March 1969.

Freeze, R. A., and P. A. Witherspoon, "Analytical and Numerical Solutions to the Mathematical Model, Pt. 1, Theoretical Analysis of Regional Groundwater Flow," Water Resources Res., Vol. 2, No. 4, pp 641-656, 1966.

Friedman, M. (See Swolfs, H. S.)

Fryberger, J. S., "Rehabilitation of a Brine-Polluted Aquifer," Rept. No. EPA-R2-72-014, 61 pp, Dec. 1972, Abstr. No. W73-07431, Selec. Water Resources Abstr., Vol. 6, No. 12, p 63, June 15, 1973.

Fuelhart, D. E., "Subsurface Disposal of Oil Field Brines," Oil Gas J., Vol. 36, No. 34, pp 46, 48-50, 1938.

Funk, R. J., and K. E. Davis, "Control of Unconsolidated Sands in Waste-Disposal Wells," AAPG & USGS Under-ground Water Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2084, Nov. 1971.

Gaillardet, C., "French Studies of Absorption by Soils," Nucl. Safety, Vol. 4, No. 1, pp 86-88, 1962.

Gaillardet, C., "Reactions Physico-Chimiques Lors du Mouvement Souterrain Des Radioisotopes (Physico-Chemical Reactions in the Underground Movement of Radioisotopes)," La rétention et la migration des ions radioactifs dans les sols-Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 269-275, 1963 (In French with Eng. abstr.).

Gaillardet, C. (See Belot, Y.)

Gaillardet, C. (See Caron, C.)

Galley, J. E., "Fluids in Subsurface Environments, Introduction," Fluids in Subsurface Environments--A Symposium, Amer. Ass. Petrol. Geol. Mem. 4, pp 1-10, 1965.

Galley, J. E., "Economic and Industrial Potential of Geologic Basins and Reservoir Strata," Subsurface Disposal in Geologic Basins--A Study of Reservoir Strata, Amer. Ass. Petrol. Geol. Mem. 10, pp 1-10, 1968.

Galley, J. E. (Ed.), Subsurface Disposal in Geologic Basins--A Study of Reservoir Strata, Amer. Ass. Petrol. Geol. Mem. 10, 253 pp, 1968.

Galley, J. E., "Geologic Basin Studies as Related to Deep-Well Disposal," Ground Disposal of Radioactive Wastes Conf., 2nd, At. Energy Comm. Div. Reactor Devel. Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 347-355, 1962.

Galley, J. E. (See Young, A.)

Garbarini, G. S., and H. K. Veal, Potential of Denver Basin for Disposal of Liquid Wastes, Amer. Ass. Petrol. Geol. Mem. 10, pp 165-185, 1968.

Garcia-Bengochea, J. I., "Recharge of Carbonaceous Saline Aquifer of South Florida with Treated Sanitary Wastewater," Artificial Groundwater Recharge Conference, University of Reading, England, Sept. 21-24, 1970.

Garcia-Bengochea, J. I., and R. O. Vernon, Deep Well Disposal of Wastewaters in Saline Aquifers of South Florida, Paper Presented at 50th Annu. Mtg. Amer. Geophys. Union, Wash. D. C., Apr. 21-25, 1969.

Garcia-Bengochea, J. I., and R. O. Vernon, "Deep Well Disposal of Waste Waters in Saline Aquifers of South Florida," Water Resources Res., Vol. 6, No. 5, pp 1464-1470, Oct. 1970.

Garcia-Bengochea, J. I., et al, Artificial Recharge of Treated Waste Waters and Rainfall Runoff Into Deep Saline Aquifers of Peninsula of Florida, 2nd Int. AAPG-USGS-IAHC Underground Water Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 505-525, 1973.

Gardner, F. T. (See Andresen, K. H.)

Gardner, T. D., "Fibercast Plastic Pipe Finds Use as Oil Well Tubing," World Petrol. Vol. 23, No. 9, pp 42-44, 1952.

Gardner, T. R. (See Lasater, R. M.)

Garrett, A. A. (See Piper, A. M.)

Garrett, J. H. (See Mecham, O. E.)

Gawad, A. (See Mitry, E. O.)

Gelhar, L. W., et al, "Density Induced Mixing in Confined Aquifers," Environ. Protect. Agency Water Pollut. Contr. Res. Ser. 130 pp, 1972 (PB-211, 298); Abstr. No. W72-12041, Selec. Water Resources Abstr., Vol. 5, No. 20, pp 49-50, Oct. 15, 1972.

Gammel, L., and S. G. Pearsall, "Transport of Fission Products Through the Soil Following Injection from a Well and Methods Used for Removal," La retention et la migration des ions radioactifs dans les sols-Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 199-206, 1963.

Genet, E., "Note Sur Des Determinations De Cheminements Liquides Souterrains par la Methode Chimique (Determination of Groundwater Flow Routes by a Chemical Method)," Terres et Eaux Supplement Scientifique No. 3, pp 73-81, 1954 (Supplement to Terres et Eaux, Vol. 6, No. 23, 1954).

Geological Survey of Alabama, Deep Well Disposal Study for Baldwin, Escambia and Mobile Counties, Alabama, Circular No. 58, 79 pp, June, 1970.

George, W. J., "Treating and Disposing of Radioactive Wastes," Chem. Eng., Vol. 66, No. 25, pp 151-160, 1959.

Georgescu, A., "The Squire's Theorem for a Movement in a Porous Medium," Petrol. Gaze., Vol. 24, No. 11, pp 676-678, Nov. 1973 (In Romanian).

Geyer, J. C. (See Morgan, J. M., Jr.)

Geyer, J. C. (See Fair, G. M.)

Giaimo, A. A. (See Vecchioli, J.)

Gibbon, A., "Salt Water Disposal Rules," Oil Weekly, Vol. 117, No. 12, pp 52-56, 1945.

Gibbon A., "Glass Fiber Installed in Salt Water Disposal Wells," World Oil, Vol. 135, No. 4, pp 203, 205, 1952.

Girilovich, G. N. (See Finogenov, I. S.)

Glassock, F. M. (See Lasater, R. M.)

Floyna, E. F. (See Reynolds, T. D.)

Glumov, I. F. (See Maksutov, R. A.)

Geobel, E. D. (See Edmund, R. W.)

Goode, H. D. and R. C. Feltis, Water Production from Oil Wells of the Uinta Basin, Uintah and Duchesne Counties, Utah, Utah Geol. Mineral. Surv. Water-Resources Bull. 1, 29 pp, 1962.

Goodheart, L. B., Plan for Salt Water Disposal, 16th Annu. SW. Petrol. Short Course Ass. Mtg. (Lubbock, Tex., Apr. 17-18, 1969), Proc., pp 185-187, Apr. 1969.

Goolsby, D. A., "Hydrogeochemical Effects of Injecting Wastes into a Limestone Aquifer Near Pensacola, Florida," Ground Water, Vol. 9, No. 1, pp 13-19, Jan, Feb. 1971.

Goolsby, D. A., "Geochemical Effects and Movement of Injected Industrial Waste in a Limestone Aquifer," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11, (Pt. 1), p 2084, Nov. 1971.

Gotaa, H. B. (See Krone, R. B.)

Grandone, P., and L. Schmidt, Survey of Subsurface Brine Disposal Systems in Western Kansas Oil Fields, U. S. Bur. Mines Rep. Invest. 3719, 20 pp, 1943.

Grauby, A. (See Bovard, P.)

Graves, B. S. "Underground Disposal of Sour Water," Short Course for Superintendents and Operators of Water, Sewerage, and Industrial Waste Disposal Systems, 24th Annu. Proc., Louisiana State Univ. Eng. Exp. Sta. Bull. 67, pp 74-80, 1961.

Graves, B. S., Underground Disposal of Industrial Waste in Louisiana, Soc. Mining Eng., Amer. Inst. Mining Met. Petrol. Eng., Preprint No. 64-H-315, 7 pp, 1964.

Greenberg, A. E. (See Maehler, C. Z.)

Greenkorn, R. A., and D. P. Kessler, "Dispersion in Heterogeneous Nonuniform Anisotropic Porous Media," Ind. Eng. Chem., Vol. 61, No. 9, pp 14-32, Sept. 1969.

Greenkorn, R. A. (See Gupta, S. P.)

Griggs, D. T. (See Healy, J. H.)

Grisak, G. E. (See Cherry, J. A.)

Grison, G. (See Capitant, B.)

Grubbs, D. M., and T. H. Hughes, Conservation of Fresh-Water Resources by Deep-Well Disposal of Liquid Wastes, Appendix B: Part I Chemical Reactions between Acid Industrial Wastes, Formation Waters, and Minerals in Salaquifers of Alabama; Part II, Laboratory Study of Selected Reservoir Rocks, Alabama Univ. Nat. Resources Cent., 1970.



Grubbs, D. M., et al, Conservation of Fresh-Water Resources by Deep-Well Disposal of Liquid Wastes, Alabama Univ. Nat. Resources Cent., May 1970.

Grubbs, D. M., et al, "Compatability of Subsurface Reservoirs with Injected Liquid Wastes," (Alabama Univ.), Rep. No. W72-12656, OWRR-B-030-ALA (1), 141 pp, June 1972, PB-211, 326; Abstr., Gov. Rep. Announce., Vol. 72, No. 19, p 64, Oct. 10, 1972.

Grubbs, D. M. (See Haynes, C. D.)

Gupta, S. P., and R. A. Greenkorn, "Dispersion During Flow in Porous Media, with Bilinear Absorption," Water Resources Res., Vol. 9, No. 5, pp 1357-1368, Oct. 1973.

Gurewitz, P. H. (See Kulin, G.)

Gustafson, C. E. (See Legros, P. G.)

Hackett, J. E., "Ground-Water Contamination in an Urban Environment," Ground Water, Vol. 3, No. 3, pp 27-30, 1965.

Hadsell, F. A., "History of Earthquakes in Colorado," Colo. Sch. Mines Quart., Vol. 63, No. 1, pp 57-72, 1968 (Also published in Mines Mag., Vol. 58, No. 6, pp 20-27, 1968).

Hajek, B. F., Absorption, Migration, and Dispersion of Strontium and Cesium in an N-Area Soil, Battelle Mem. Inst. Pacific Northwest Lab. Rep., BNWL-CC-208, 20 pp, 1965.

Hajek, B. F. (See Ames, L. L., Jr.)

Halevy, E., et al, Borehole Dilution Techniques, A Critical Review, Int. At. Energy Agency Symp., (Vienna, Austria, Nov. 14-18, 1966) Proc., pp 531-564, May 1967.

Halevy, E. (See Mercado, A.)

Halko, D. L. (See Spalding, C. W.)

Hall, M. W., "Petroleum-Processing Wastes," J. Water Pollut. Contr. Fed., Vol. 44, No. 6, pp 1098-1101, June 1972.

Halligan, E. G., "Deep Well Fluid Waste Disposal," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy of Canada, Limited and U. S. At. Energy Comm. Div. Reactor Devel., Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep. TID-7628, pp 363-373, 1962.

Halloway, H. D., and T. W. McSpadden, "How We are Fighting Corrosion," Oil Gas J., Vol. 59, No. 22, pp 146-148, 150, 1961.

Hamilton, D. H., and R. L. Meehan, "Ground Rupture in the Baldwin Hills," Science, Vol. 172, No. 3981, pp 333-344, Apr. 23, 1971.

Hamilton, R. M. (See Healy, J. H.)

Hamrick, J. M. (See Gelhar, L. W.)

Hanby, K. P., et al, Subsurface Disposal of Liquid Industrial Wastes in Alabama - A Current Status Report, 2nd Int. AAPG-USGS-(AHC Underground Waste Manage. & Artificial Recharge Symp., New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 72-90, 1973.

Haney, W. A. (See Brown, D. J.)

Haney, W. A. (See Nelson, J. L.)

Haney, W. A. (See Nelson, R. W.)

Hannah, S. A. (See Warner, D. L.)

Hanshaw, B. B. (See Back, W.)

Hardaway, J. E., Possibilities for Subsurface Waste Disposal in a Structural Syncline in Pennsylvania, Amer. Ass. Petrol. Geol. Mem. 10, pp 93-127, Aug. 1968.

Harleman, D. R. F., and R. R. Rummer, "Longitudinal and Lateral Dispersion in an Istropic Porous Medium," J. Fluid Mech., Vol. 16, Pt. 3, pp 385-394, July 1963.

Harleman, D. R. F., et al, "Dispersion-Permeability Correlation in Porous Media," J. Hydraul. Div., Amer. Soc. Civil Eng. Proc., Vol.89, No. HY 2, pp 67-85, 1963.

Harleman, D. R. F. (See Hoopes, J. A.)

Harleman, D. R. F. (See Shamir, U. Y.)

Harmon, B., "Contamination of Ground-Water Resources," Civil Eng., Vol. 11, No. 6, pp 345-347, 1941.

Harpaz, Y., and J. Bear, Investigations on Mixing of Waters in Underground Storage Operations, Int. Ass. Sci. Hydrol. Publication 64, pp 132-153, 1964.

Harpaz, Y., Field Experiments in Recharge and Mixing Through Wells, Tahal-Water Planning for Israel, Ltd., Tech. Rept. 17, 54 pp, 1965.

Harpaz, Y. (See Sternau, R.)

Harris, M. B. (See Alciatore, A. F.)

Harrison, T. P., II, "Federal Regulations as They Relate to Underground Waste Management," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2085, Nov. 1971.

Hartman, C. D., "Deep-Well Disposal of Steel-Mill Wastes," J. Water Pollut. Contr. Fed., Vol. 40, No. 1, pp 95-100, 1968.

Hartman, C. D., "Deep Well Waste Disposal at Midwest Steel," Iron Steel Eng., Vol. 43, No. 12, pp 118-121, 1966.

Hatfield, J. R. (See Hicks, L. B.)

Hawkins, D. B., A System for the Evaluation of Liquid Waste Disposal, U. S. At. Energy Comm. Idaho Oper. Office Rep. IDO-12052, 46 pp, 1966.

Hawkins, D. B., "Mineral Reaction Studies at National Reactor Testing Station, Idaho," The Use of Inorganic Exchange Material for Radioactive Waste Treatment-A Working Meeting Held in Washington, D. C., Aug. 13-14, 1962, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7644, pp 151-175, 1963.

Hawkins, R. H., "Improved Burial of Solid Radioactive Wastes," Ground Disposal of Radioactive Wastes Conference, 2nd At. Energy of Canada, Limited and U. S. At. Energy Comm. Div. Reactor Devel. Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep. TID-7628, pp 462-468, 1962.

Haynes, C. D., Pressure-Fracture Gradient Problems in Deep-Well Waste Disposal, (Alabama Univ.) Completion Rep. OWRR-A-037-ALA, 38 pp, Sept. 1974.

Haynes, C. D. and D. M Grubbs, Design and Cost of Liquid-Waste Disposal Systems, Univ. of Alabama Natural Resources Center, Rep. 692, 120 pp, 169, PB-194, 113, 120 pp, May, 1970.

Haynes, C. D., Pressure Buildup-Chemical Incompatibility in Liquid Injection Wells, SPE of AIME Rocky Mt. Reg. Mtg. (Billings, Mont., May 15-16, 1974), Preprint No. SPE 4932, 10 pp, 1974.

Haynes, C. D. (See Grubbs, D. M.)

Haywood, R. W., "Basic Data for Chemical Waste Disposal," Sewage Ind. Wastes, Vol. 30, No. 9, pp 1156-1159, 1958.

Healy, J. H., et al, "Earthquakes Induced by Fluid Injection and Explosion," Tectonophysics, Vol. 9, Nos. 2-3, pp 205-214, Mar. 1970.

Healy, J. H., et al, "The Denver Earthquakes," Science, Vol. 161, No. 2848, pp 1301-1310, 1968.

Heath, L. J. (See Eckard, W. E.)

Heckard, J. M., "Deep Well Injection of Liquid Wastes," Eng. Bull. No. 35, pp 22-27, 1969; Abstr. No. W73-09247, Selec. Water Resources Abstr., Vol. 6, no. 15, p 86, Aug. 1, 1973.

Heemstra, R. J. (See Watkins, J. W.)

Hem, J. D., Chemical Equilibrium Diagrams for Ground-Water Systems, Int. Ass. Sci. Hydrol. Bull. 19, pp 45-53, 1960.

Henkel, H. O., "Surface and Underground Disposal of Chemical Wastes at Victoria, Texas," Sewage Ind. Wastes, Vol. 25, No. 9, pp 1044-1049, 1953.

Henkel, H. O. "Deep-Well Disposal of Chemical Wastes," Chem. Eng. Progr., Vol. 51, No. 12, pp 551-554, 1955.

Henkel, H. O., "Deep Well Disposal of Chemical Waste Water," Power, Vol. 112, No. 3, pp 82-85, 1968.

Henry, H. R., and F. A. Kohout, "Waste Disposal in Saline Aquifers Affected by Geothermal Heating," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2085, Nov. 1971.

Henry, H. R., et al, "Aquifer Performance Tests Under Two-Phase Flow Conditions," (Alabama Univ.), Rep. No. OWRR B-020-ALA(1), 117 pp, Mar. 1971 (PB-209, 535): Abstr. No. W72-08591, Selec. Water Resources Abstr., Vol. 5, No. 15, pp 13-14, 1972.

Herzig, J. P., and P. LeGoff, "On the Flow of Suspensions Through Porous Media," 6th Amer. Chem. Soc. I & EC Div. State-of-the-Art Summer Symp. (Washington, D. C., June 9-11, 1969) Pap.; Abstr., Ind. Eng. Chem., Vol 61, No. 5, p 7, May 1969.

Hewett, P. S. (See Lansing, A. C.)

Hewitt, D. E., Radio Alarm Monitoring and Related Automation Equipment, Heart of Amer. Kansas Oil Lifting Short Course (Great Bend, Kans., Mar. 8-9, 1972) Selec. Pap., 13 pp, 1972.

Heyman, L. (See Kelly, D. R.)

Hicks, L. B., and J. R. Hatfield, "Salt Water Disposal Practices in Kansas," Oil Gas J., Vol. 47, No. 50, pp 113-114, 116, 1949.

Hidalgo, R. V., and L. D. Woodfork, EDP as an Aid for Decision Making in Subsurface Injection of Liquid Wastes, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 133-146, 1973.

Hieple, L. R., "Effectiveness of Coarse-grained Media for Filtration," J. Amer. Water Works Ass., Vol. 51, No. 6, pp 749-760, 1959.

Hill, G. A. (See Dolan, J. P.)

Hill, R. B., "Regulation of Subsurface Disposal in Texas," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), P 2086, Nov. 1971.

Hilton, W. O. (See Metzler, D. F.)

Hinnen, A., "Liability of Oil Lessee for Saline Pollution of Water Supply on Adjacent Lands," 443 p 2D 354-360 (Kansas 1968).

Hochhausen, E., "Operators Cooperate in Water Disposal System," Petrol. Eng., Vol. 27, No. 2, pp B75-B77, B80, 1955.

Hochhausen, E., "Redwater Water Disposal System," Can. Oil Gas Ind., Vol. 8, No. 9, pp 52-56, 1955.

Hochhausen, E., "Salt Water Disposal," Can. Oil Gas. Ind., Vol. 12, No. 1, pp 79-80, 1959.

Hoeger, R. L., "Hydrodynamic Study of the Western Denver Basin, Colorado," Colo Sch. Mines Quart., Vol. 63, No. 1, pp 245-251, 1968.

Holben, J. H., and A. W. Baumgartner, "Water Management," Oil Gas Petrochem. Equip., Vol. 16, No. 12, pp 4-5, Oct. 1970.

Holland, H. R., and F. R. Clark, "A Disposal Well for Spent Sulfuric Acid from Alkylating-iso-butane and Butylenes", Industrial Waste Conference, 19th, Proc., Purdue Univ. Eng. Bull., No. 1, pp 195-199, 1964.

Holland, D. W., Salt Water Disposal Wells, Zones of Interest, and Production Company Viewpoints in the Tri-State Area of Texas, Oklahoma, and Kansas, Heart of Amer. Drilling & Prod. Inst. Mtg. (Liberal, Kans., Feb. 8-9, 1972) Selec. Pap., 14 pp, 1972.

Holliman, W. C. (See Taylor, S. S.)

Hollister, J. C., and R. J. Weimer, "General Summary and Conclusions, Geophysical and Geological Studies of the Relationships between the Denver Earthquake and the Rocky Mountain Arsenal Well," Colo. Sch. Mines Quart., Vol. 63, No. 1, Pt. A, pp 1-8, 1968.

Hollister, J. C., and R. J. Weimer, (Eds.), "Geophysical and Geological Studies of the Relationships Between the Denver Earthquake and the Rocky Mountain Arsenal Well," Colo. Sch. Mines Quart., Vol. 63, No. 1, Pt. A (Papers) 251 pp, Pt. B (Maps), 1968.

Holmstrom, L., "How Kansas-Nebraska Natural Completes Its Disposal Wells," Drilling, Vol. 30, No. 6, pp 45, 48, 1969.

Holzmacher, R. G. (See Fetter, G. W., Jr.)

Honstead, J. F., "The Role of 'Ground Disposal' in Radioactive Waste Management Process," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 11-15, 1963.

Honstead, J. F., and J. Beranek, "Waste Management Implications in Nuclear Site Selection," Siting of Reactors and Nuclear Research Centres, Int. At. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/72), pp 201-207, 1963.

Hoopes, J. A., and D. R. F. Harleman, Waste Water Recharge and Dispersion in Porous Media, Mass. Inst. Technol. Hydrodynamics Lab. Rep. 75, 166 pp, 1965.

Hoopes, J. A., and D. R. F. Harleman, "Dispersion in Radial Flow from a Recharge Well," J. Geophys. Res., Vol. 72, No. 14, pp 3595-3607, 1967.

Hoopes, J. A., and D. R. F. Harleman, "Wastewater Recharge and Dispersion in Porous Media," J. Hydraul. Div. Amer. Soc. Civil Eng. Proc., Vol. 93, No. HY 5, pp 51-71, 1967.

Hoove, D. B., and J. A. Dietrich, Seismic Activity During the 1968 Test Pumping at the Rocky Mountain Arsenal Disposal Well, U. S. Geol. Surv. Circ. 613, 35 pp, 1969.

Hoover, D. B. (See Van Poolen, H. K.)

Horton, R. E., The Drainage of Ponds into Drilled Wells, U. S. Geol. Surv. Water-Supply Pap. 145, pp 30-39, 1905.

Hough, L. W., "Injection Wells-Hazards and State Regulations," Short Course for Superintendents and Operators of Water, Sewerage and Industrial Waste Disposal Systems, 26th Annu. Proc., Louisiana State Univ., Eng. Exp. Sta. Bull. 75, pp 108-114, 1964 (Also published as Hough, L. W., Salt Water and Waste Disposal Wells - State Regulations and Geological Problems, Louisiana Geol. Surv., 10 pp, 1968.

Howard, R. L. (See Dunlop, A. K.)

Howard, G. C., and C. R. Fast, Hydraulic Fracturing, Society of Petroleum Engineers of AIME, New York, N. Y., 1970.

Hower, W. F., et al, "Compatibility of Injection Fluids with Reservoir Components," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2086, Nov. 1971.

Huang, J. Y. C., and E. R. Baumann, Least Cost Sand Filter Design for Iron Removal, 63rd Annu. AIChE Filtration Symp. (Chicago, Nov. 29, 1970-Dec. 3, 1970), Preprint, No. 21c, 18 pp, 1970.

Hubbart, M. K., and D. G. Willis, "Mechanics of Hydraulic Fracturing," Trans. Amer. Inst. Mining Met. Petrol. Eng., Vol. 210, pp 153-168, 1957 (Tech. Pap. 4597).

Hughes, R. F., "Denver's Man-Made Earthquakes--Fact or Fancy," Mines Mag., Vol. 58, No. 7, pp 22-24, 1968.

Hughes, T. H. (See Grubbs, D. M.)

Hulse, B. T. (See Selm. R. P.)

Hundley, C. L., and J. T. Matulis, "Deep Well Disposal," Ground Water, Vol. 1, No. 2, pp 15-17, 33, 1963.

Hundley, C. L., and J. T. Matulis, "Deep-Well Disposal," Industrial Waste Conference, 17, Proc., Purdue Univ. Eng. Bull., Vol. 47, No. 2, pp 175-180, 1962.

Hunn, J. D. (See Wilson, W. E.)

Hauser, V. L. (See Rebhun, M.)

Ihrig, H. K., "Stream Pollution Hazards Minimized by Improved Salt Water Disposal," Oil Gas J., Vol. 34, No. 49, p 51, 1936.

Ihrig, H. K., "Oil Producers Making Rapid Progress in Salt Water Disposal Programs," Oil Gas J., Vol. 34, No. 50, pp 36, 38, 1936.

Inoue, Y., and W. J. Kaufman, "Dispersion Relations in Injection Disposal of Radioactive Wastes," Ground Disposal of Radioactive Wastes Conference, Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-6721, pp 131-139, 1961.



Inoue, Y., and W. J. Kaufman, "Studies of Injection Disposal," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel. Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 303-321, 1962.

Inoue, Y., and W. J. Kaufman, "Prediction of Movement of Radionuclides in Solution Through Porous Media," Health Phys., Vol. 9, No. 7, pp 705-715, 1963.

Inoue, Y., "Prediction of Radionuclide Migration in Ground Water at the Japan Atomic Energy Research Institute," Disposal of Radioactive Wastes into the Ground, Int. At. Energy Agency and Europe. Nucl. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 199-213, 1967.

Inoue, Y. (See Iwai, S.)

Inoue, Y. (See Kaufman, W. J.)

International Atomic Energy Agency, Radioactive Waste Disposal into the Ground, Safety Ser. No. 15, 111 pp, 1965.

Irish, E. R., "A Comparison of Ground Waste Disposal Status at Hanford (Wash.)," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Comm. Div. Reactor Devel., Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep. TID-7628, pp 491-505, 1962.

Irwin, J. H., and R. B. Morton, Hydrogeologic Information on the Glorieta Sandstone and the Ogallala Formation in the Oklahoma Panhandle and Adjoining Areas as Related to the Underground Waste Disposal, U. S. Geol. Surv. Circ. 630, 29 pp, 1969.

Isaacson, R. E., The Hanford Exploratory Deep Well, Atlantic Richfield, Hanford Co. Rep., ARH-SA-47, 18 pp, 1969.

Ives, K. J., "Rapid Filtration," Water Res., Vol. 4, No. 3, pp 201-223, March 1970.

Ives, R. E., and G. E. Eddy, Subsurface Disposal of Industrial Wastes, Interstate Oil Compact Comm. Study, 109 pp, 1968.

Ives, R. E., and G. E. Eddy, Subsurface Disposal of Industrial Wastes, (Unnumbered Publ.), Interstate Oil Compact Comm., Oklahoma City, 61 pp, First Suppl., Jan 1970.

Iwai, S., et al, "Movement Through Soil of Radioactive Nuclides Contained in Chemical Processing Waste," Nippon Genshiryoku Gakkaishi, Vol. 10, No. 8, pp 435-440, 1968 (In Japanese).

Jacobs, D. G., "Mineral Exchange Work at Oak Ridge National Laboratory," The Use Of Inorganic Exchange Material for Radioactive Waste Treatment-A working meeting held in Washington, D. C., Aug. 13-14, 1962, U. S. At. Energy Comm. Div. Tech. Inform. Rep. TID-7644, pp 187-189, 1963.

Jacobs, D. G., "Ion Exchange in the Deep-Well Disposal of Radioactive Wastes," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 43-54, 1963.

Jacobs, D. G., et al, "Liquid Injection into Deep Permeable Formations, Sec. 1 of Radioactive Waste Disposal," Health Physics Division Annual Progress Report for Period Ending Jan. 30, 1963, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-3492, pp 3-12, 1963.

Jacobs, D. G., "Movement of Radionuclides Through the Ground," Nucl. Safety, Vol. 5, No. 1, pp 109-114, 1963.

Jacobs, D. G., and M. U. Shaikh, "Liquid Injection into Deep Permeable Formations," Health Physics Division Annual Progress Report for Period Ending July 31, 1964, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-3697, pp 3-10, 1964.

Jacobs, D. G., et al, "Application of Mineral Exchange to Reactor Technology," Health Physics Division Annual Progress Report for Period Ending July 31, 1966, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-4007, pp 27-33, 1966.

Jacobs, D. G., "Behavior of Radioactive Gases Discharged into the Ground," Nucl. Safety, Vol. 8, No. 2, pp 175-178, 1967.

Jacobs, D. G. (See Boegly, W. J., Jr.)

Jacobs, M. (See Bear, J.)

Jamison, D. K. (See Morgan, J. M., Jr.)

Jansen, G., Jr., Thermal Consequences of Leaks in Radioactive Waste Storage Tanks, General Electric Company, Hanford At. Prod. Oper. Rep., HW-80848, 12 pp, 1964.

Jargon, J. R. (See Van Poolen, H. K.)

Jennings, A. R. (See Schroeder, M. C.)

Jensen, R. G. (See Barraclough, J. T.)

Jessen, F. W., and J. L. Battle, "Brine Stabilization with Sodium Hexametaphosphate," Ind. Eng. Chem., Vol. 35, No. 6, pp 650-654, 1943.

Jessen, F. W., Technical Problems of Salt Water Injection, Amer. Petrol. Inst. Drilling Prod. Pract., 1944, pp 112-121, 1945.

Jessen, F. W., "Subsurface Disposal of Oil Field Brines," Chem. Eng. Prog., Vol. 45, No. 1, pp 11-16, 1949.

Jessen, F. W. (See Brown, K. E.)

Joers, J. C., and R. V. Smith, "Determination of Effective Formation Permeabilities and Operation Efficiencies of Water Input Wells," Prod. Mon., Vol. 18, No. 12, pp 21-28, 1954. (Also in Petrol. Eng., Vol. 26, No. 11, 7 p, 1954.)

Johansen, R. T., and E. C. Donaldson, Well-Injection System for Industrial Waste, A. I. Ch. E. Symp. Ser., No. 129, pp 336-344, 1973.

Johansen, R. T. (See Donaldson, E. C.)

John, E. C. (See Purtymun, W. D.)

Johnson, D. W., Relation of the Law to Underground Waters, U. S. Geol. Surv. Water-Supply Pap. 122, 55 pp, 1905.

Johnson, G. L., (See Purtymun, W. D.)

Johnson, N., and C. M. Beeson, "Water Permeability of Reservoir Sand," Trans. Amer. Inst. Mining Met. Eng., Vol. 16, pp 43-55, 1945 (Tech. Pap. 1871).

- Johnston, O. C. (See Perkins, T. K.)
- Jones, O. R. (See Schneider, A. D.)
- Jones, O. S., Disposition of Oil Field Brines, Kans. Univ. Publications, Lawrence, Kans., 192 pp, 1945.
- Jones, O. S., "Salt Water Disposal Problems," Oil Weekly, Vol. 120, No. 9, pp 34-36, 38, 1946.
- Jones, O. S., "Subsurface Brine Disposal," Oil Weekly, Vol. 120, No. 9, pp 27-29, 1946.
- Jones, O. S., "Subsurface Disposal of Inland Oil Field Brines Conserves Fresh Water Supply," Civil Eng., Vol. 17, No. 2, pp 60-63, 1947.
- Jones, O. S., Fresh Water Protection from Pollution Arising in the Oil Fields, Kans. Univ. Press, Lawrence, Kans., 132 pp, 1950.
- Jones, P. H., Hydrology of Radioactive-Waste Disposal at the Idaho Chemical Processing Plant, National Reactor Testing Station, Idaho, U. S. Geol. Survey Prof. Pap. 424-D, pp D374-D376, 1961.
- Jones, P. H., Application of Bore-Hole Geophysics in Hydrologic Investigations in Volcanic Terrane, Geol. Soc. Amer. Spec. Pap. 68, pp 33-34, 1961 (Abstr. only).
- Jones, P. H., and E. Shuter, Hydrology of Radioactive Waste Disposal in the Mtr-ETR area, National Reactor Testing Station, Idaho, U. S. Geol. Surv. Prof. Pap. 450-C, pp C113-C116, 1962.
- Jones, P. H., and B. L. Schmalz, "Distribution of Radionuclides in Groundwater at the National Reactor Testing Station, with Particular Reference to Tritium," J. Geophys. Res., Vol. 67, No. 9, pp 3570-3571, 1962 (Abstr. only).
- Jones, P. H., "Geophysical Research at the National Reactor Testing Station," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy of Can. Limited and U. S. At. Energy Comm. Div. Reactor Devel. Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 99-114, 1962.

Jubboori, S. A., "Injection of Sediment Containing Water into Permeable Unconfined Formations," Massachusetts Univ. Ph.D Thesis, 129 pp, 1972; Abstr. No. 72-19, 473, Diss. Abstr. Int., Sec. B., Vol. 33, No. 1, p 17-B, July 1972.

Kaplan, M. (See Lewelling, H.)

Karadi, G. M. (See Krizek, M. I.)

Karimov, N. Kh. (See Titkov, N. I.)

Kasline, F. E., "Production Statistics," Sum. Oper. Calif. Oil Fields, Vol. 56, No. 2, 133 pp, 1970.

Kastrop, J. E., "Brine Disposed at Small Cost," World Oil, Vol. 134, No. 6, pp 162-164, 1952.

Katz, D. L., and K. H. Coats, Underground Storage of Fluids, Ulrich's Books, Inc., Ann Arbor, Mich., 575 pp, 1968.

Katz, D. L., "Liquid-Waste Storage in Abnormal-Pressure Reservoirs," Nucleonics, Vol. 20, No. 4, p 71, 1962.

Kaufman, M. I., "Subsurface Wastewater Injection, Florida," J. Irrig. Drainage Div. Amer. Soc. Civil Eng. Proc., Vol. 99, No. IRI, pp 53-70, Mar. 1973.

Kaufman, W. J., "The Containment of Radioactive Wastes in Deep Geologic Formations," Disposal of Radioactive Wastes, Vol. 2 - Int. At. Energy Agency and United Nations Educ., Sci. Cult. Organ. Sci. Conf. Proc., Int. At. Energy Agency (STI/PUB/18), pp 533-546, 1960.

Kaufman, W. J., et al, Underground Movement of Radioactive Wastes, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep. AECU-3115, 92 pp, 1955.

Kaufman, W. J., et al, "Disposal of Radioactive Wastes into Deep Geologic Formations," J. Water Pollut. Contr. Fed., Vol. 33, No. 1, pp 73-84, 1961.

Kaufman, W. J. (Ed.), Ground Disposal of Radioactive Wastes Conf., 1959 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7621, 1968 pp, 1961.

Kaufman, W. J. (See Inoue, Y.)

Kaufman, W. J. (See Orcutt, R. G.)

Kaufman, W. J. (See Rifai, M. N. E.)

Keeley, J. W., "Problems of Groundwater Pollution by Brine," Public Works, Vol. 97, No. 3, pp 149, 158, 160, 162, Mar. 1966; Abstr. No. W73-12770, Selec. Water Resources Abstr., Vol. 6, No. 20, pp 55-56, 1973.

Kehle, R. O., "The Determination of Tectonic Stresses Through Analysis of Hydraulic Well Fracturing," J. Geophys. Res., Vol. 69, No. 2, pp 259-273, 1964.

Kelly, D. R., et al, Oil and Gas Developments in Pennsylvania in 1968, Penn. Geol. Surv. Progr. Rep. No. 177, 51 pp, 1969.

Kemler, E. M., "Reservoir Data and Production Problems," Oil Weekly, Vol. 113, No. 8, p 72, and Vol. 113, No. 9, pp 34-36, 1944.

Kerrigan, J. V. (See Kaufman, W. J.)

Kessler, D. P. (See Greenkorn, R. A.)

Kevi, L. (See Ellis, W. R.)

Keys, W. S., and R. F. Brown, Role of Borehole Geophysics in Underground Waste Storage and Artificial Recharge, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973), Preprints, Vol. 1, pp 147-191, 1973.

Khomchik, L. M. (See Sobolev, I. A.)

Kidd, R. E. (See Hanby, K. P.)

Kim, Y. E. (See Jacobs, D. G.)

Kimbler, O. K. (See Esmail, O. J.)

King, H. H., "Water Disposal Plan-East Texas Operators Start Experiment as Volume Increases," Oil Weekly, Vol. 80, No. 10, p 14, 1936.

King, H. H., "Feasibility of Returning Salt Water," Oil Weekly, Vol. 91, No. 12, pp 23-24, 26, 28, 1938.

King, L. G., Mathematical Model for Underground Discharge of Radioactive Gases, Battelle Mem. Inst. Pacific Northwest Lab. Rep., BNWL-SA-1152, 21 pp, 1967.

King, L. G., Mathematical Models for Underground Injection of Gaseous Wastes into the Vadose Zone, Battelle Mem. Inst. Pacific Northwest Lab. Per., BNWL-945, 149 pp, 1968.

Kiselev, N. G. (See Redkin, I. I.)

Klassen, C. W., et al, Suggestions for Prevention of Pollution of Waters by Oil Field Wastes, Ill. Dep. Pub. Health, Springfield, Ill., 22 pp, 1938 (revised 1940).

Klein, G. (See Kaufman, W. J.)

Klein, G. (See Orcutt, R. G.)

Klotz, D., "Investigations Relating to Dispersion in Porous Media," Z. Deut. Geol. Ges., Vol. 124, No. 2, pp 523-533, 1973 (In German).

Klotzman, M., and B. Ven, "Celanese Chemical (Co.) Pumps Wastes into Disposal Wells," Oil Gas J., Vol. 64, No. 15, pp 84-87, 1966.

Knodell, J. D., Jr., "Liability for Pollution of Surface and Underground Waters," Rocky Mt. Mineral Law Inst., Vol. 12, pp 33-99, 1967; Abstr. No. W71-10904, Selec. Water Resources Abstr., Vol. 4, No. 20, p 59, Oct. 15, 1971.

Knoll, K. C. (See Nelson, J. L.)

Knowles, D. B., "Hydrologic Aspects of the Disposal of Oil-Field Brines in Alabama," Ground Water, Vol. 3, No. 2, pp 22-27, 1965.

Knox, J. A., et al, "Preparation and Stimulation of Water Injection and Disposal Wells," Southwestern Petroleum Short Course, 15th Annu., Proc., Tex. Technol. Univ., Lubbock, Tex., pp 1-7, 1968.

Knudsen, C. N. (See Reisenauer, A. E.)

Koger, W., "Planning a Water Injection System," Corrosion Control Short Course, 1968 Proc., Okla. Univ., Norman, Okla., pp R1-10, 1968.

Koger, W. C., Cathodic Protection of Production Equipment, Okla. Univ. Corrosion Contr. Short Course (Norman, Sept. 15-17, 1969), Proc. pp R-1 - R-8, 1969.

Kohout, F. A. (See Henry, H. R.)

Komar, C. A., Hardness, Tensile Strength and Impact Toughness of Reservoir Sandstone at Extreme Temperatures, U. S. Bur. Mines Rep. Invest. No. 7571, 10 pp, 1971.

Kominek, E. G., "Accelerated Waste Treatment Methods," Chem. Eng. Prog., Vol. 45, No. 7, pp 417-420, 1949.

Kornfeld, J. A., "Salt Water Disposal System," Petrol. Interamer., Vol. 9, No. 8, p 22, 1951.

Korver, J. A., "Fluid Flow from Nuclear Chimneys," Water Resources Res., Vol. 2, No. 2, pp 297-310, 1966.

Kostin, P. P., "Sanitary Protective Zone During Creation of Underground Storage for Liquid Wastes," Razvedka Okhrana Nedr, No. 2, pp 42-45, Feb. 1971 (In Russian).

Kramer, J. R., "Subsurface Brines and Mineral Equilibria," Chem. Geol., Vol. 4, No. 1-2, pp 37-50, 1969.

Krause, H., "Disposal of Radioactive Wastes into Deep Geological Formations," At. Energy Rev., Vol. 7, No. 1, pp 47-70, 1969.

Krause, H., et al, "Project for Storing Radioactive Wastes in a Salt Cavity," Disposal of Radioactive Wastes into the Ground, Int. At. Energy Agency and Europe. Nucl. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 479-494, 1967.

Kreidler, W. L., "Preliminary Study of Underground Disposal of Industrial Liquid Waste in New York State," Subsurface Disposal of Industrial Wastes, Interstate Oil Compact Comm. Stud., Oklahoma City, Okla., pp 100-109, 1968.



Kreiger, J. H., "The Law of the Underground," Civil Eng., Vol. 34, No. 3, pp 52-53, 1964.

Kriz, G. J. (See Lewis, D. C.)

Krizek, R. J., et al, Dispersion of a Contaminant in Fissured Rock, Int. Soc. Rock Mech. & Int. Ass. Eng. Geol. Percolation Through Fissured Rock Symp. (Stuttgart, Sept. 18-19, 1972), Proc., 15 pp, 1972 (Pap. No. T3-C).

Krone, R. B., et al, "Direct Recharge of Ground Water with Sewage Effluents," J. Sant. Eng. Div., Amer. Soc. Civil Eng. Proc., Vol. 83, No. SA 4, 25 pp, 1957 (Paper 1335).

Kryukov, I. I. (See Virgin, N. N.)

Ku, H. F. H. (See Vecchioli, J.)

Kubota, H., "Problems in Disposal of Radioactive Liquid Wastes in Salt," Chem. Eng. Prog., Symp. Ser., Vol. 60, No. 53, pp 68-73, 1964.

Kuehn, K., "Geo-Scientific Investigations in the Asse II Salt Mine (Lower Saxony, Germany)," Disposal of Radioactive Wastes into the Ground-- Int. At. Energy Agency and Europe. Nucl. At. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 509-518, 1967.

Kulin, G., and P. H. Gurewitz, Hydraulic Research in the United States and Canada, 1972, Nat. Bur. Stand. Spec. Publication No. 382, 38 pp, 1974.

Kuo, C. H., "Pressure Behavior in Subsurface Disposal of Liquid Industrial Wastes," J. Water Pollut. Contr. Fed., Vol. 44, No. 12, pp 2325-2333, Dec. 1972.

Lambert, D. E., "Plastic Pipe Gains Wide Acceptance," Pipe Line Ind., Vol. 33, No. 3, pp 45-47, Sept. 1970.

LaMoreaux, P. E. (See DeBuchananne, G. D.)

LaMoreaux, P. E. (See Hanby, K. P.)

Lang, A., "Pollution of Water Supplies, Especially of Underground Streams, by Chemical Wastes and by Garbage," J. Amer. Water Works Ass., Vol. 25, No. 8, p 1181, 1933 (Abstr. only).

Lang, A., and H. Bruns, "On Pollution of Ground Water by Chemicals," Gas, Wasser, Warne, Vol. 83, p 6, Jan. 6, 1941; (Abstr. published in J. Amer. Water Works Ass., Vol. 33, No. 11, pp 2075, 2076, 1941).

Langdon, J. C., "The Railroad Commission Looks at Pollution," S. Tex. Law J., Vol. 8, pp 179-187, 1966; Abstr. No. W71-10916, Selec. Water Resources Abstr., Vol 4, No. 20, p 60, Oct. 15, 1971.

Langhaar, H. L. (See Deere, D. U.)

Lansing, A. C., and P. S. Hewett, "Disposal of Phenolic Waste to Underground Formations," Industrial Waste Conference, 9th, 1954 Proc., Purdue Univ. Eng. Bull., Vol. 39, No. 2, pp 184-194, 1955.

Lasater, R. M., et al, "Scale Deposits are Controlled Now with Liquid Inhibitors," Oil Gas J., Vol. 66, No. 3, pp 88-89, 92-93, 1968.

Lasater, R. M. (See Hower, W. F.)

Latta, B. F., Subsurface Disposal of Waste in Kansas, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 622-633, 1973.

Lazarescu, M., and C. Papadopol, "Operatia de Epurare Si Injectie In Strat, Metoda De Evacuare a Apelor Sarate Diu Exploatarile Petroliere (Bed Treatment and Injection as a Method of Salt Brine Evacuation from Petroleum-Mining Operations)," Hidrotehnica, Gospodaria Apelor, Meteorologia, Vol. 11, No. 8, pp 422-426, 450, 1966 (In Romanian).

Leahy, M. J., "Disposal of Oil Field Brines," Oil Weekly, Vol. 96, No. 5, pp 19-20, 22, 24, 1940.

Leal, P. L. (See Romero, E.)

Lebedev, G. I., "Printsipial'nye resheniya po kanalizovaniyu neftepromyslov Tatarii i Zapadnoi chasti Bashkirii i primenie v etix raionax fiziko-khimicheskogo metody doochistki promyslovyx stochnyx vod (Principle Decisions Relating to Drainage in the Oil Fields of Tatar and Western Bashkir, and Application in the Regions of Physicochemical Method of Secondary Purification of Industrial Waste Waters)," Konferentsia po bor'ba zagryazneniem vodoemov, Moscow, 1956, (Conference on Struggle with Pollution of Reservoirs by Waste Water), Moscow, Gosudarstvennoe Nauchno-Tekhnicheskoe Izdatel'stvo Neftyanoi i Gorno-Toplivnoi Literatury (State Scientific Technical Publishing House of Petroleum and Mining Industry), pp 26-33, 1958.

Lee, J. A., "Throw Your Wastes Down a Well," Chem. Eng., Vol. 57, No. 9, pp 137-139, 1950.

Lee, M. "Underground Disposal of Salt Water," Oil Gas J., Vol. 34, No. 44, pp 41-44, 1936.

Leenheer, J. A. (See Malcolm, R. L.)

Legge, M. S. (See Mecham, O. E.)

LeGoff, P. (See Herzig, J. P.)

LeGrand, H. E., Geology and Ground-Water Hydrology of the Atlantic and Gulf Coastal Plain as Related to Disposal of Radioactive Wastes, U. S. Geol. Surv. Trace Elements Invest. Rep., TEI-805, 169 pp, 1962.

LeGrand, H. E., "Graphic Evaluation of Hydrologic Factors in Management of Radioactive Wastes," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy of Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel. Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 67-76, 1962.

LeGrand, H. E., "Patterns of Contaminated Zones of Water in the Ground," Water Resources Res., Vol. 1, No. 1, pp 83-95, 1965.

LeGrand, H. E., "Environmental Framework of Ground-Water Contamination," Ground Water, Vol. 3, No. 2, pp 11-15, 1965.

LeGrand, H. E., "Role of Ground Water Contamination in Water Management," J. Amer. Water Works Ass., Vol. 59, No. 5, pp 557-565, 1967.

Legros, P. G., et al, A Study of Deep Well Disposal of Desalination Brine Waste, Office of Saline Water Res. Develop. Progr. Rep. No. 456, June 1969.

Legros, P. G. (See McIlhenny, W. F.)

Liebert, B. M., et al, "The Problem of Displacing Connate Water by Waste Waters from Porous Media with Simultaneous Chemical Reaction Between Them," Izv. Vyssh. Ucheb. Zavedenii, Neft Gaz, No. 7, pp 77-79, 1972 (In Russian).

Leidner, R. N., "Waste Water Treatment for the Burns Harbor Plant of Bethlehem Steel Corporation," J. Water Pollut. Contr. Fed., Vol. 41, No. 5, Pt. 1, pp 695-807, May 1969.

Leisure, E. R., History of Pollution Abatement, Heart of Amer. Kansas Oil Lifting Short Course (Great Bend, Kans., Mar. 14-15, 1973) Proc., 8 pp, 1973.

Lemoine, J. (See Archambault, J.)

Lenau, C. W., "Dispersion from Recharge Well," J. Eng. Mech. Div. Amer. Soc. Civil Eng. Proc., Vol. 98, No. EM2, pp 331-344, April. 1972.

Lenau, C. W., "Contamination of Discharge Well From Recharge Well," J. Hydraul. Div. Amer. Soc. Civil Eng. Proc., Vol. 99, No. HY8, pp 1247-1263, Aug. 1973.

Lerman, B. I. (See Usoltsev, L. N.)

Leveque, P. (See Capitant, B.)

Levi, H. W., and N. Miekeley, "Studies on Ion Diffusion in Vermiculite," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 161-168, 1967.

Lewelling, H., and M. Kaplan, "What to do about Salt Water," Petrol. Eng., Vol. 31, No. 7, pp B19-B24, 1959.

Lewis, D. C., et al, "Tracer Dilution Sampling Technique to Determine Hydraulic Conductivity of Fractured Rock," Water Resources Res., Vol. 2, No. 3, pp 533-542, 1966.

Li, W-H, and G-T Yeh, "Dispersion at the Interface of Miscible Liquids in a Soil," Water Resources Res., Vol. 4, No. 2, pp 369-377, 1968.

Lieber, M., and W. F. Welsch, "Contamination of Ground Water by Cadmium," J. Amer. Water Works Ass., Vol. 46, No. 6, pp 541-547, 1954.

Lieber, M. (See Davids, H. W.)

Lieberman, J. A., Disposal of High-Level Radioactive Waste Products, Nat. Res. Council Div. Earth Sci. Annu. Rep., 1954-55, pp 65-77, 1955.

Linville, B., Petroleum and Oil Shale Research of the Bureau of Mines, Fiscal Year 1969, U. S. Bur. Mines Inform. Circ. No. 8525, 122 pp, 1971.

Lippok, W. (See Schwille, F.)

List, E. J., and N. H. Brooks, "Lateral Dispersion in Saturated Porous Media," J. Geophys. Res., Vol. 72, No. 10, pp 2531, 1967.

Lockett, D. E., "Subsurface Disposal of Industrial Waste Water," Industrial Water and Waste Conference, 7th, Texas Water Pollution Control Ass., 1967, Proc., Texas Univ., Austin, Texas, pp 111-48 - 111-57, 1967.

Loewenstein, H., "An Injection Probe for Rapid Placement of Radioisotopes in Soil," Soil Sci. Soc. Amer. Proc., Vol. 29, No. 3, pp 328-329, 1965.

Lofgren, B. E., Hazards of Waste Disposal in Groundwater Basins, 2nd Int. AAPG USGS IAHS Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 2, pp 715-728, 1973.

Loleit, A. J. (See Peterson, J. A.)

Lombard, W. K., The Design and Operation of a Private Waste Disposal Plant Near Sarnia, Ontario, Proc., Ind. Waste Conf. 24th, Purdue Univ., May 6-8, 1969.

Lomenick, T. F. (See Boegly, W. J., Jr.)

Lomenick, T. F. (See Bradshaw, R. L.)

Lorenz, W. C. (See Stephan, R. W.)

Louisiana State Department of Conservation, Activities of the Division of Research and Statistics, Fourteenth Bien-nial Report (1938-1939), pp 282, 313, 1940.

Ludwig, G. K., "Gas Engine Power for Salt Water Disposal Maintains Oil Production," Diesel Gas Turbine Progr., Vol. 35, No. 7, pp 46-47, 1969.

Luff, G. S., "Underground Waste Disposal for American Airlines, Inc.," Oklahoma Industrial Wastes Conference, 11th, Pt. 1, Okla. Water, Sewage and Industrial Wastes Ass., 1960 Proc., Oklahoma State Univ., Stillwater, Okla., pp 71-80, 1960.

Lum, D., Preliminary Report on Geohydrologic Exploration for Deep Well Disposal of Effluent, Waimanalo Sewage Treatment Plant, Oahu, Hawaii, State Dept. of Land and Natural Resources, Div. of Water and Land Development, Department of the Land and Natural Resources, Circ. C 54, 14 pp.

Lynch, E. J., Transport of Radionuclides by Groundwater--Some Theoretical Aspects, Hazleton-Nuclear Science Corp., Pala Alto, Calif., and Carroll E. Bradberry and Associates, Los Altos, Calif., Rep., HNS-1229-61, 56 pp, Nov. 1964.

Lynn, R. D., and Z. E. Arlin, "Anaconda Successfully Disposes of Uranium Mill Waste Water by Deep Well Injection," Mining Eng., Vol. 14, No. 7, pp 49-52, 1962.

Lynn, R. D., and Z. E. Arlin, "Deep Well Construction for the Disposal of Uranium Mill Tailing Water by the Anaconda Co. at Grants, N. M.," Trans. Soc. Mining Eng., AIME, Vol. 223, No. 3, pp 230-237, 1962.

Lytle, W. S. (See Kelly, D. R.)

Mackrie, V., et al, Hydrodynamics of the Disposal of Low-Level Liquid Radioactive Wastes in Soil, Int. At. Energy Agency (NP-15859), Contract No. 98, 142 pp, 1965.

MacLay, R. W. (See Pickering, R. T.)

MacLeod, I. C., "Disposal of Spent Caustic and Phenolic Water in Deep Wells," Ontario Industrial Waste Conference, 8th, 1961 Proc., Ontario Water Resources Comm., Water and Pollut. Advisory Comm., pp 49-58, 1961.

Maehler, C. Z., and A. E. Greenberg, "Identification of Petroleum Industry Wastes in Groundwaters," J. Water Pollut. Contr. Fed., Vol. 34, No. 12, pp 1262-1267, 1962.

Maes, W. F. (See Baetsle, L. H.)

Maes, W. F. (See de Jonghe, P.)

Maini, Y. N. T. (See Noorishad, J.)

Mairhofer, J. (See Borowczyk, M.)

Majeske, E. C. (See Legros, P. G.)

Major, M. W., and R. B. Simon, "A Seismic Study of the Denver (Derby) Earthquakes," Colo. Sch. Mines Quart., Vol. 63, No. 1, pp 9-55, 1968.

Maksutov, R. A., et al, "Field and Laboratory Experiments on Water Injection with Variable Injection Pressures at the Wellhead," Neftepromyslovoe Delo, No. 11, pp 20-21, 1973 (In Russian).

Malcolm, R. L., and J. A. Leenheer, Case History of Subsurface Waste Injection of an Industrial Organic Waste, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 565-584, 1973.

Malina, J. F., Jr., and J. C. Moseley, II, "Disposal-Well Dimensions, Injection Rates, and Cost Responses," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1961) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2088, Nov. 1971.

Malina, J. F., Jr. (See Moseley, J. C., II)

Mal'tsev, E. D., et al, "The Thermal Factor in the Problem of Inserting Radioactive Wastes into Mineral Deposits," Soviet J. At. Energy, Vol. 12, No. 1, pp 32-36, 1962 (Translated from Atomnaya Energiya, Vol. 12, No. 1, pp 36-39, 1962).

Malysheva, L. N., and N. N. Dmitrieva, "Effect of Added Surface-Active Agents on Flow of Water and Industrial Discharges," Nauch. Tekh. Sb. Ser. Neftepromyslovoe Delo, No. 8, pp 21-26, 1969 (In Russian).

Manneschmidt, J. F. (See Witkowski, E. J.)

Manning, J. C., "Deep Well Injection of Industrial Wastes," Industrial Waste Conference, 23rd, 1968 Proc., Purdue Univ. Eng. Bull., Vol. 21, No. 3, pp 11-13, 1969.

Marceaux, N. J., "A New Way of Life for Oil Contaminated Disposal Systems," Baroid News Bull., Vol. 21, No. 3, pp 11-13, 1969.

Mardock, E. S. (See Watkins, J. W.)

Marine, I. W., "The Use of a Tracer Test to Verify an Estimate of the Groundwater Velocity in Fractured Crystalline Rock at the Savannah River Plant Near Aiken, S. C.," Isotope Techniques in the Hydrologic Cycle--Symp., Amer. Geophys. Union Geophys. Ser., No. 11, pp 171-179, 1967.

Marine, I. W., Geohydrology of Buried Triassic Basin at Savannah River Plant, South Carolina, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 481-504, 1973.

Marine, I. W. (See Proctor, J. F.)

Marine, I. W. (See Webster, D. S.)

Markhasin, I. L. (See Leibert, B. M.)

Marsh, J. H., "Design of Waste Disposal Wells," Ground Water, Vol. 6, No. 2, pp 4-8, 1968.



Marshall, G. E., and J. R. Stephens, "Observations of Earth-Tilt and Earthquake Correlation, Denver Area, Colorado," Earthquake Notes, Vol. 39, Nos. 1-2, pp 23-36, 1968.

Martensen, V. N., "Primeneniye Skorykh Keramzitoverykh Fil'Trov Dlya Ochistki Promyshlennykh Stoknykh Vod ot Vzveshennykh Veshchestv i Nefti (Use of Rapid Clay Filters for Purifying Produced Waters by Removing Suspended Particles and Crude Oil)," Izv. Vyssh. Ucheb. Zavedenii, Neft Gaz, No. 11, pp 111-114, 1968 (In Russian).

Marter, W. L., "Ground Waste Disposal Practices at the Savannah River Plant (SM-93/7)," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 95-106, 1967.

Martinez, J. D., "Environmental Significance of Salt," Amer. Assn. Petrol. Geol. Bull., Vol. 55, No. 6, pp 810-825, June 1971.

Mathews, R. D. (See Legros, P. G.)

Matiisen, A., Defining Injection Profiles Using the Neutron Lifetime Log and High Sigma Fluids, 14th Annu. SPWLA Logging Symp. (Lafayette, La., May 6-9, 1973) Trans., Pap. No. V, 13 pp, 1973.

Matthews, R. R. (See Carlberg, B. L.)

Matson, G. C., Pollution in Limestone, U. S. Geol. Surv. Water-Supply Pap. 258, pp 48-56, 1911.

Matulis, J. T. (See Hundley, C. L.)

Mawson, C. A., Management of Radioactive Wastes, D. Van Nostrand Co., Princeton, N. J., 196 pp, 1965.

Mawson, C. A. (See Merritt, W. F.)

Maxey, G. B., and R. N. Farvolden, "Hydrogeological Factors in Problems of Contamination in Arid Lands," Ground Water, Vol. 3, No. 4, pp 29-32, 1965.

Maxey, G. B., (See Bredehoeft, J. D.)

Maxwell, B. W. (See McMillion, L. G.)

McCann, T. P., et al, Possibilities for Disposal of Industrial Wastes in Subsurface Rocks of North Flank of Appalachian Basin in New York, Amer. Ass. Petrol. Geol. Mem. 10, pp 43-92, 1968.

McClain, W. C., et al, "Disposal by Hydraulic Fracturing," Health Physics Division Annual Progress Report for Period Ending July 31, 1966, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-4007, pp 10-14, 1966.

McClain, W. C., Hydraulic Fracturing as a Waste Disposal Method, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-P-3054, 20 pp, 1967.

McClain, W. C., et al, Disposal of High Level Solidified Wastes in Salt Mines, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-P-3053, 22 pp, 1967.

McClain, W. C., "Rock Mechanics in the Disposal of Radioactive Wastes by Hydraulic Fracturing," Felsmechanik Ingenieurgeologie (Int. Soc. Rock Mech. J.), Vol. 6, No. 3, pp 139-161, 1968.

McClain, W. C. "Site Evaluations," Nucl. Eng. Design, Vol. 9, No. 3, pp 315-326, 1969.

McClain, W. C., The Mechanics of Hydraulic Fractures in Shales, 3rd Northern Ohio Geol. Soc. Salt Symp. (Cleveland, Apr. 22-24, 1969) Proc., Vol. 2, pp 410-420, 1970

McClain, W. C., "Earthquakes Induced by Underground Fluid Injection," Rept. No. ORNL-TM-3154, 17 pp, Oct. 1970; Abstr. No. 38197, Nuc. Sci. Abstr., Vol. 24, No. 23, p 4705, Dec. 15, 1970.

McClain, W. C., "Seismic Mapping of Hydraulic Fractures," Oak Ridge Nat. Lab. Tech. Mem. No. 3502, 32 pp, Aug. 1971; Abstr. No. 48604, Nucl. Sci. Abstr., Vol. 25, p 4771, Nov. 15, 1971.

McClain, W. C. (See Boegly, W. J., Jr.)

McClain, W. C. (See Bradshaw, R. L.)

McColgan, R., Water Treatment Plant Wastes Disposal, Report to AWWA Research Foundation, Nov. 11, 1970.

McConiga, M. W. (See Brown, R. E.)

McDonald, J. R. (See Henry, H. R.)

McGauhey, P. H. (See Butler, R. G.)

McGauhey, P. H. (See Krone, R. B.)

McGhan, V. L. (See Raymond, J. R.)

McIlhenny, W. F., et al, The Disposal of Waste Brine from Desalting Operations, Purdue Univ. Eng. Bull. Eng. Ext. Ser. No. 137 (Pt. 2), pp 559-574, 1970.

McLean, D. P., Subsurface Disposal of Liquid Wastes in Ontario, 7th Annu. Ontario Petrol. Inst. Inc. Conf. (Windsor, Ont., Oct. 30-Nov. 1, 1968) Pap., No. 7, 15 pp, 1968.

McLean, D. D., "Subsurface Disposal--Precautionary Measures," Ind. Water Eng., Vol. 6, No. 8, pp 20-22, 1969.

McLean, D. D., Subsurface Disposal of Liquid Wastes in Ontario (Canada), Ontario Dept. Energy and Resources Manage., Petrol. Resources Sect., Pap. 68-2, 91 pp, 1968.

McMaster, W. M., and H. D. Waller, Geology and Soils of Whiteoak Creek Basin, Tennessee, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-TM-1108, 36 pp, 1965.

McMillion, L. G., "Hydrologic Aspects of Disposal of Oil-Field Brines in Texas," Ground Water, Vol. 3, No. 4, pp 36-42, 1965.

McMillion, L. G., Sr., and B. W. Maxwell, Determination of Pollutational Potential of the Ogallala Aquifer by Salt Water Injection, Robert S. Kerr Water Research Center, Ada, Oklahoma, June 1970.

McMillion, L. G., Environmental Protection Agency Activities on Subsurface Waste Injection, Heart of Amer. Drilling & Prod. Inst. Mtg. (Liberal, Kans., Feb. 8-9, 1972) Selec. Pap., 17 pp, 1972.

McSpadden, T. W. (See Halloway, H. D.)

McWilliams, J., "Large Saltwater Disposal Systems at East Texas and Hastings Oil Fields, Texas," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2088, Nov. 1971.

Mecham, O. E., and J. H. Garrett, "Deep Injection Disposal Well for Liquid Toxic Wastes," Am. Soc. Civil Engineers Proc. Paper 3650; J. Constr. Div. Amer. Soc. Civil Eng. Trans., Vol. 89, No. CO 2, pp 111-121, 1963.

Mecham, O. E., and M. S. Legge, "How to Forecast Accurate Drilling Costs," World Oil, Vol. 151, No. 5, pp 112-116, 1960.

Meehan, R. L. (See Hamilton, D. H.)

Meenaghan, G. F., Ultimate Disposal of Waste Waters by Deep-Well Injection, 19th Annu. SW. Petro. Short Course Ass. Mtg. (Lubbock, Texas, Apr. 20-21, 1972) Proc., pp 167-172, 1972.

Meers, R. J., Design, Drilling and Completion, Operation, and Cost of Underground Waste Disposal Wells in Gulf Coast Region of Texas and Louisiana, 2nd Int. AAPG USGS IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 337-345, 1973.

Mehlhor, P. F. (See Harleman, D. R. F.)

Mercado, A., and E. Halevy, "Determining the Average Porosity and Permeability of a Stratified Aquifer with the Aid of Radioactive Tracers," Water Resources Res., Vol. 2, No. 3, pp 525-531, 1966.

Mercado, A., Underground Water Storage Study, Recharge and Mixing Experiments in the Haifa Bay Field, Tahal-Water Planning for Israel, Ltd., Tel Aviv, Israel, Tech. Rep. 18, Pub. 495, 37 pp, 1966.

Mercado, A., The Spreading Pattern of Injected Water in a Permeability Stratified Aquifer, Int. Ass. Sci. Hydrol. Pub. 72, pp 23-36, 1967.

Mercado, A. (See Sternau, R.)

Merkt, E. E., Jr. (See Plummer, F. B.)

Merritt, W. F., and C. A. Mawson, "Experience with Ground Disposal at Chalk River (Canada)," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 79-92, 1967.

Metzler, D. F., and W. O. Hilton, "Oil Industry Wastes -- Their Threat to Fresh Water," N. Dak. Water Works Conf. Bull., Vol. 20, No. 4, pp 14-15, 1952.

Miekeley, N. (See Levi, H. W.)

Mihram, R. G. (See Hower, W. F.)

Miklyutin, V. N., Sbros Stochnykh Vod Neftepromyslov v pobloshvchayushchie Skvazhiny (Disposal of Waste Waters in Oilfields into Absorbing Wells), Kuybyshev, Gosudarstvennyi Institut po Proktirovaniu i Issledovatel'skim Rabatam v. Neftedobyvaiushchei Promyshlennosti Trudy, No. 1, pp 455-467, 1958 (In Russian).

Miller, E. B., Jr. (See Rhea, A. S.)

Miller, J. S. (See Gelhar, L. W.)

Million, C. L., "Conoco Technology Curbs Production Pollution," Petrol. Eng., Vol. 45, No. 9, pp 42, 44, 46, Aug. 1973.

Mills, B., "Injection Method for Salt Water Disposal," Oil Weekly, Vol. 97, No. 8, pp 15-18, 20, 22-25, 1940 (Additional installments in Vol. 97, No. 9, pp 19-26, and Vol. 97, No. 10, pp 19-27).

Mitchell, R. (See Nevo, Z.)

Mitchell, R. C., "Water Pollution in Kansas," Oil Gas J., Vol. 34, No. 43, pp 49-50, 52, 1936.

Mitry, E., et al, "Further Studies on the Uptake of Long-Lived Fission Products on some Clays from the United Arab Republic with a View to Eventual Ground Disposal," Practices in the Treatment of Low-and Intermediate-Level Radioactive Wastes--Int. At. Energy Agency, 1965 Symp. Proc., Int. At. Energy Agency, STI/Pub/116), pp 921-930, 1966.

Moffett, J. G., Jr., "Underground Disposal of Industrial Wastes," Short Course for Superintendents and Operators of Water and Sewerage Systems, 23rd Annu. Proc., Louisiana State Univ. Eng. Exp. Sta. Bull. 64, pp 155-162, 1960.

Moore, B. H. (See Samuelson, G. J.)

Moore, W. D., "The Pressure Performance of 5 Fields Completed in a Common Aquifer," Trans. Amer. Inst. Mining Met. Petrol. Eng., Vol. 195, pp 297-302, 1952 (Tech. Pap. 3460).

Moran, J. H., and E. E. Finklea, "Theoretical Analysis of Pressure Phenomena Associated with the Wireline Formation Tester," J. Petrol. Technol., Vol. 14, No. 8, pp 899-908, 1962.

Morgan, J. M., Jr., et al, (Eds.), Ground Disposal of Radioactive Wastes Conference, 2nd At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel. 1961 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, Book 1, pp 1-300, Book 2, pp 301-644, 1962.

Morgan, J. M., Jr., et al, "Land Burial of Solid Packaged Low Hazard Potential Radioactive Wastes in the United States," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel. 1961 Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 396-427, 1962.

Morris, B. P. (See Cancanower, R. D.)

Morris, D. A., et al, Hydrology of Subsurface Waste Disposal, National Reactor Testing Station, Idaho--Annual Progress Report, 1964, U. S. Geol. Surv. Open-File Rep., (IDO-22047), 304 pp, 1965.

Morris, D. A., Use of Chemical and Radioactive Tracers at the National Reactor Testing Station, Idaho, Amer. Geophys. Union Geophys. Mon. Ser., No. 11, pp 130-142, 1967.

Morris, D. A., et al, Hydrology of Subsurface Waste Disposal, National Reactor Testing Station, Idaho--Annual Progress Report, 1963, U. S. Geol. Surv. Open-File Rep., (IDO-22046), 228 pp, 1964.

Morris, W. S., "Subsurface Disposal of Salt Water in the East Texas Field," Petrol. Eng., Vol. 14, No. 11, pp 41-49, 53, 1943.

Morris, W. S., and L. H. Dial, "Salt Water Disposal Program in the East Texas Field," Oil Gas J., Vol. 42, No. 29, p 56, 1943 (Abstr. only).

Morris, W. S., "Methods of Salt-Water Disposal in Oil Fields, East Texas Oil Field," J. Amer. Water Works Ass., Vol. 37, No. 6, pp 569-572, 1945.

Morris, W. S., "How the World's Largest Brine Injection Project is Handled," Oil Gas J., Vol. 45, No. 14, pp 72-82, 86, 91, 1946.

Morris, W. S., "Engineering Factors for Pressure Filters, Pits, Injection Wells, and Other Items Used in the East Texas Field," Oil Gas J., Vol. 45, No. 16, pp 86-90, 124, 1946.

Morris, W. S., "East Texas Field has Record of Outstanding Results from its Four-Year Program of Salt Water Disposal," Oil Gas J., Vol. 45, No. 17, pp 92, 95, 97, 1946.

Morris, W. S., "Salt Water Injection and Maintenance in the East Texas Field," Oil Weekly, Vol. 124, No. 4, p 66, 1946 (Abstr. only).

Morris, W. S., "Results of Water Injection in Woodbine Reservoir of the East Texas Field," Amer. Petrol. Inst. Proc., Vol. 27, No. 4, pp 36-45, 1947.

Morris, W. S., "Subsurface Disposal of Salt Water from Oil Wells," J. Water Pollut. Contr. Fed., Vol. 32, No. 1, pp 41-51, 1960.

Morris, W. S., "Fighting Scale in Salt Water Lines," Petrol. Eng., Vol. 39, No. 2, pp 55-56, 58, 1967.

Morton, R. B. (See Irwin, J. H.)

Morton, R. J. (See Struxness, E. G.)

Moseley, J. C., II, and J. F. Malina, Jr., Relation Between Selected Physical Parameters and Cost Responses for the Deep Well Disposal of Aqueous Industrial Wastes, Univ. Tex. Cent. Res. Water Resources Rep., CR WR 28, 276 pp, Aug. 1968 (Technical rep. to U. S. Public Health Service EHE 07-6801).

Moseley, J. C., II (See Malina, J. F.)

Moser, H. (See Halevy, E.)

Mudra, P. J., and B. L. Schmalz, An Appraisal of Gaseous Waste Disposal into the Lithosphere at the National Reactor Testing Station, Idaho, U. S. At. Energy Comm. Idaho Oper. Office Rep., IDO-12024, 141 pp, 1965.

Murata, K. J., "Internal Structure of Silicate Minerals that Gelatinize with Acid," Amer. Mineral., Vol. 28, No. 11/12, pp 545-562, 1943.

Murata, K. J., The Significance of Internal Structure in Gelatinizing Silicate Minerals, U. S. Geol. Surv. Bull. 950, pp 25-33, 1946.

Muravev, I. M., "Determining the Permissible Amount of Impurities in Injection Water," Neft. Khoz., Vol. 45, No. 3, pp 47-49, 1967 (In Russian).

Mutszer, P. (See Zilliox, L.)

Myers, B. M. (See Rima, D. R.)

Myers, O. H. (See Jacobs, D. G.)

Nace, R. L., "Contributions of Geology to the Problem of Radioactive Waste Disposal," Disposal of Radioactive Wastes, Vol. 2--Int. At. Energy Agency and United Nations Educ., Sci. and Cult. Organ., 1959 Sci. Conf. Proc., Int. At. Energy Agency (STI/PUB/18), pp 456-480, 1960.

Nace, R. L., "Underground Storage of Radioactive Wastes," Interstate Oil Compact Comm. Comm. Bull., Vol. 3, No. 1, 15 pp, 1961.

Nace, R. L., Management of Radioactive Waste in a Basalt Terrane, Idaho, Geol. Soc. Amer. Spec. Pap. 68, p 315, 1962 (Abstr. only).

Nace, R. L., Problems of Underground Storage of Wastes, 71st Nat. AICHE Ground Water as a Water Resource Mtg. (Dallas, Feb. 20-23, 1972) Preprint No. 33d, 11 pp, 1972.



Naeser, C. R., "Geochemical Studies Pertaining to Ground Studies of Radioactive Wastes," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 237-247, 1962.

Naor, I. (See Orcutt, R. G.)

Nazarov, A. I. (See Yudin, F. P.)

Nelson, J. L., et al, "Laboratory, Pilot and Field Scale Studies of Fission Product Migration Rates in Soils," La retention et la migration des ions radioactifs dan les sols-Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 107-115, 1963.

Nelson, J. L., et al, Chemical Effluents Technology, Gen. Elec. Co., Hanford At. Prod. Oper. Rep., HW-73337, pp 158-237, 1962.

Nelson, J. L., et al, "Hanford (Wash.), Studies in Geochemistry," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Tech. Inform. Rep., TID-7628, pp 214-236, 1963.

Nelson, R. W., and W. A. Haney, "Analog Simulation of Hanford Ground Water Flow," La retention et la migration des ions radioactifs dans les sols--Colloque International, Saclay, France, 1962, Paris Presses Universitaires de France, pp 131-138, 1963.

Nelson, R. W., "A Sequence for Predicting Waste Transport by Ground Water," Amer. Water Resources Ass. Mtg., 1st Annu. Amer. Water Resources Assn. Proc. Ser., No. 1, pp 80-87C, 1965.

Nelson, R. W., "Mathematical and Numerical Formulation," Steady Darcian Transport of Fluids in Heterogeneous Partially Saturated Porous Media, Gen. Elec. Co., Hanford At. Prod. Oper. Rep., HW-72335, 36 pp, 1962.

Nelson, R. W., and A. E. Reisenauer, "Hanford (Wash.) Studies on Flow in Porous Media," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Comm. Div. Reactor Devel. 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 130-144, 1962.

Nelson, R. W. (See Reisenauer, A. E.)

Neuman, S. P. (See Witherspoon, P. A.)

Nevill, G. L. (See Legros, P. G.)

Nevo, Z., and R. Mitchell, "Factors Affecting Biological Clogging of Sand Associated with Ground-Water Recharge," Water Res., Vol. 1, No. 3, pp 231-236, 1967.

Nicholson, G. B., "Backwash by Gas Lift Increases Efficiency of Salt Water Injection," Oil Weekly, Vol. 121, No. 13, pp 36-37, 1946.

Niskimaki, K. (See Laai, S.)

Noble, E. A., Multiple Use and Problems of Saline Aquifers in North Dakota, 46th Annu. SPE of AIME Fall Mtg. (New Orleans, Oct. 3-6, 1971) Preprint, No. SPE-3454, 4 pp, 1971.

Noorishad, J., et al, The Influence of Fluid Injection on the State and Stress in the Earth's Crust, Int. Soc. Rock Mech. & Int. Ass. Eng. Geol. Percolation Through Fissured Rock Symp. (Stuttgart, Sept. 18-19, 1972) Proc., 11 pp, 1972 (Pap. No. T2-H).

Norris, F. A., "Evaluation of Salt Water Disposal into Potential Groundwater Resources," Rep. No. W72-01895, EPA-16060-HIJ-02/72, 24 pp, Feb. 1972; Abstr., Gov. Rep. Announce., Vol. 72, No. 17, p 73, Sept. 10, 1972.

Novak, L. T., "Transport Phenomena in Porous Media with Emphasis on Water Movement in Soils," Michigan State Univ. Ph.D. Thesis, 219 pp, 1972; Abstr. No. 73-12, 790, Diss. Abstr. Int., Sect. B, Vol. 34, No. 1, p 201-B, July 1973.

Novotny, D. (See Strnad, M.)

Nowak, T. J., "The Estimation of Water-Injection Profiles from Temperature Surveys," Trans. Amer. Inst. Mining Met. Petrol. Eng., Vol. 198, pp 303-312, 1952 (Tech. Pap. 3637).

Nutting, P. G., The Action of Some Aqueous Solutions on Clays of the Montmorillonite Group, U. S. Geol. Surv. Prof. Pap. 197-F, pp 219-235, 1943.

Ogata, A., Effect of the Injection Scheme on the Spread of Tracers in a Ground-Water Reservoir, U. S. Geol. Surv. Prof. Pap. 475-B, pp B199-B202, 1963.

Okun, D. A. (See Fair, G. M.)

Oleney, V. I. (See Maksutov, R. A.)

Olson, E. A. (See Smith, E. R.)

Oradovskaya, A. E., and F. M. Bochever, "Some Problems in Flow of Polluted Plant Effluents in Natural Water-Bearing Formations," Izv. Akad. Nauk SSSR, Mekh. Zhidkosti Gaza, No. 6, pp 196-202, Nov.-Dec. 1969 (In Russian).

Oradovskaya, A. E. (See Bochever, F. M.)

Orcutt, R. G., et al, "Underground Movement of Radioactive Wastes," Sewage Ind. Wastes, Vol. 29, No. 7, pp 791-804, 1957.

Orcutt, R. G., et al, "Hydraulic and Ion-Exchange Phenomena in the Underground Movement of Radiostrontium," Seminar on Sanitary Engineering Aspects of the Atomic Energy Industry, U. S. At. Energy Comm. U. S. Public Health Serv., 1955 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7517, Pt. 1a, pp 191-211, 1956.

Orcutt, R. G. (See Kaufman, W. J.)

Orcutt, D. H. (See Warner, D. L.)

Orlob, G. T., and G. N. Radhakrishna, "The Effects of Entrapped Gasses on the Hydraulic Characteristics of Porous Media," Amer. Geophys. Union Trans., Vol. 39, No. 4, pp 648-659, 1958.

Orlob, G. T., "Effect of Water Reclamation Practices on Quality of Ground Water," Conference on California Ground-Water Situation Proc., Calif. Univ. Water Resources Cent. Contrib. 2, pp 146-156, 1956.

Orlob, G. T., Assimilative Capacity of Receiving Waters in Relation to the Pulp and Paper Industry, Calif. State Water Pollut. Contr. Board Publication 17, pp 73-100, 1957.

Orlob, G. T. (See Butler, R. G.)

Orlova, E. I. (See Belitskii, A. S.)

O'Rourke, E. V., "The Uses of Water Injection to the Sub-surface Through Boreholes," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Ltd. and U. S. At. Energy Comm. Div. Reactor Devel. 1961 Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 374-379, 1962.

Ostroff, A. G., Introduction to Oil Field Water Technology, Prentice-Hall, Inc., Englewood Cliffs, N. J., 1965.

Ostroot, G. W., and A. L. Donaldson, Sub-Surface Disposal of Acidic Effluents, SPE of AIME Evangeline Sect. Reg. Mtg. (Lafayette, La., Nov. 9-10, 1970) Preprint, No. SPE-3201, 12 pp, 1970.

Ostroot, G. W., and J. Ramos, "Deep-Well Acid Disposal-Planning and Completion," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), pp 2088-2089, Nov. 1971.

Otton, E. G., Geologic and Hydrologic Factors Bearing on Subsurface Storage of Liquid Wastes in Maryland, Maryland Geol. Surv., 1970.

Owens, E. O. (See Taylor, S. S.)

Page, R. D., "Pollution Control for Oil Field Brines," Drill Bit, Vol. 15, No. 9, pp 32-36, 1967.

Papadopol, C. (See Lazarescu, M.)

Papadopoulos, I. S. (See Cooper, H. H.)

Paradiso, S. J., "Disposal of Fine Chemical Wastes," Industrial Waste Conference, 10th, Proc. Purdue Univ. Eng. Bull., Vol. 40, No. 1, pp 49-60, 1956.

Parker, F. L., "Status of Radioactive Waste Disposal in U. S. A.," Am. Soc. Civil Engineers Proc., J. Sanit. Eng. Div. Amer. Soc. Civil Eng. Proc., Vol. 95, No. SA 3, pp 439-464, 1969 (Paper 6597).

Parker, F. L., and R. E. Blanco, Waste Treatment and Disposal Progress Report for November-December 1962, and January 1963, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep. ORNL-TM-516, 134 pp, 1963.

Parker, F. L., "Radioactive Waste Disposal," Health Physics Division Annual Progress Report for Period Ending July 31, 1965, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep. ORNL-3849, pp 1-42, 1965.

Parker, F. L., "Radioactive Waste Disposal," Health Physics Division Annual Progress Report for Period Ending July 31, 1966, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep. ORNL-4077, pp 1-41, 1966.

Parker, F. L. (See Blanco, R. E.)

Parker, F. L. (See Boegly, W. J., Jr.)

Parker, F. L. (See Schaffer, W. F., Jr.)

Parker, F. L. (See Struxness, E. G.)

Parker, R. G., Environmental Factors Related to Deep Well Fluid Injection (Reprint of paper presented to Petroleum Industry Technical Conference, Urbana, Ill., 1968), Ill. Geol. Surv., 23 pp, 1968.

Parsons, P. J., Migration from a Single Source of Liquid Waste Deposited in Porous Media, At. Energy Canada, Ltd. Rep. CRER-1077, 25 pp, 1962 (Also available as Rep. AECL-1485).

Parsons, P. J., The Liquid Disposal Area, At. Energy Can., Ltd. Rep. CRER-1089, 19 pp, 1962 (Also available as Rep. AECL-1561).

Payne, B. W., "Production and Disposal of Salt Water in the East Texas Oil Field," Oil Weekly, Vol. 105, No. 11, pp 21-38, 1942.

Payne, R. D., "Emphasis on Change in Pollution Control Regulation," Interstate Oil Compact Comm. Comm. Bull., Vol. 13, No. 1, pp 1-4, June 1971.

Payne, R. W., A Simplified Method of Analyzing Pressure/Rate/Time Performance of Industrial Waste Disposal Wells, AIME Environ. Quality Conf. (Washington, D. C., Jun. 7-9, 1971) Preprint, No. EQC-65, pp 359-366, 1971.

Payne, R. W., "Waste Disposal Well Performance," Water Wastes Eng., Vol. 7, No. 7, pp D-14 - D-18, July 1970; Abstr. No. W73-12779, Selec. Water Resources Abstr., Vol. 6, No. 20, p 85, Oct. 15, 1973.

Pearce, W. A., "Water Flow Chart for Designing Salt-Water-Disposal System," Oil Weekly, Vol. 113, No. 1, pp 16-17, 1944.

Pearsall, S. G. (See Gemmel, L.)

Peckham, A. E., "Underground Waste Disposal Studies--Chemical Processing Plant Area (Idaho)," Ground Disposal of Radioactive Wastes Conference, Berkeley, Calif., 1959 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7621, pp 157-166, 1961.

Peckham, A. E. (See Clebsch, A., Jr.)

Pecsock, D. A., Disposal of Nuclear Power Reactor Wastes by Injection into Deep Wells, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., CF-54-10-64, 24 pp, 1954.

Perkins, T. K., and O. C. Johnston, "A Study of Immiscible Fingering in Linear Models," Soc. Petrol. Eng. J., Vol. 9, No. 1, pp 39-46, 1969.

Perona, J. J., et al, Comparative Costs for Final Disposal of Radioactive Solids in Concrete Vaults, Granite, and Salt Formations, U. S. At. Energy Comm., Oak Ridge Nat. Lab. Rep., ORNL-TM-664, 22 pp, 1963.

Perona, J. J. (See Bradshaw, R. L.)

Peterson, J. A., et al, Sedimentary History and Economic Geology of San Juan Basin, New Mexico and Colorado, Amer. Ass. Petrol. Geol. Mem. 10, pp 186-231, 1968.

Peterson, S. F., "Methods of Salt-Water Disposal in Oil Fields, Illinois Oil Fields," J. Amer. Water Works Ass., Vol. 37, No. 6, pp 573-576, 1945.

Peterson, S. F., "Utilization of Salt Water in Illinois Oil Fields," Oil Gas J., Vol. 43, No. 36, pp 69, 71-72, 1945.

Pettyjohn, W. A., "Water Pollution by Oil-Field Brines and Related Industrial Wastes in Ohio," Ohio J. Sci., Vol. 71, No. 5, pp 257-269, Sept. 1971.

Phillips, R. V., "Liability of Oil Companies for Polluting Underlying Strata," 180 p 2D 270-278 (Kansas 1947).

Pickering, R. J., and R. W. Maclay, Steps Toward Design of Systems for Monitoring Ground-Water Quality, 160th Nat. Amer. Chem. Soc. Mtg. (Chicago, Sept. 14-18, 1970) Pap., No. Watr. 65, 1970 (Abstr. only).

Pickett, A., Industrial Wastes and Their Relation to the Re-use of Water, Calif. Univ. Water Resources Cent. Contrib. 3, pp 31-36, 1957.

Pickett, G. R., "Properties of the Rocky Mountain Arsenal Disposal Reservoir and Their Relation to Derby Earthquakes," Colo. Sch. Mines Quart., Vol. 63, No. 1, pp 73-100, 1968.

Pierce, R. L., "Reducing Land Subsidence in the Wilmington Oil Field by the Use of Saline Waters," Amer. Geophys. Union Trans., Vol. 50, No. 4, p 152, 1969 (Abstr. only).

Pierce, W. G., and E. I. Rich, Summary of Rock Salt Deposits in the United States as Possible Storage Sites for Radio-active Waste Materials, U. S. Geol. Surv. Bull. 1148, 91 pp, 1962.

Pilgram, D. H., and K. K. Watson, "The Application of Radio-isotope Techniques to Water Engineering Investigations," Australian Inst. Eng. J., Vol. 37, No. 7/8, pp 175-184, 1965.

Pilov, A. A. (See Redrin, I. I.)

Pimenov, M. K. (See Spitsyn, V. I.)

Pimenov, M. K. (See Yudin, F. P.)

Pimenov, M. K. (See Zakharov, S. I.)

Piper, A. M., Disposal of Liquid Wastes by Injection Underground--Neither Myth nor Millenium, U. S. Geol. Surv. Circ. 631, 15 pp, 1969.

Piper, A. M., "Disposal of Liquid Wastes by Injection Underground: Neither Myth nor Millenium," Chem. Eng. Progr. Symp. Ser., Vol. 65, No. 97, pp 5-18, 1969.

Piper, A. M., et al, Native and Contaminated Ground Water in the Long Beach--Santa Ana Area, California, U. S. Geol. Surv. Water-Supply Pap. 1136, 320 pp, 1953.

Plummer, F. B., et al, "Effect of Certain Microorganisms on the Injection of Water into Sand," Petrol. Technol., Vol. 7, No. 1, 13 p, 1944.

Plummer, F. B., "Methods of Testing Salt Water for Injection into Oil Sands," Oil Gas J., Vol. 44, No. 16, pp 145-146, 1945.

Plummer, F. B., "Calcium Carbonate Precipitates in Water-Disposal Systems," Oil Gas J., Vol. 44, No. 17, pp 83-84, 1945.

Pohl, H. A. (See Clark, J. R.)

Polak, A. F. (See Leibert, B. M.)

Poland, J. F., "Subsidence and Its Control," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt.1), p 2089, Nov. 1971.

Pollard, P., "Evaluation of Acid Treatments from Pressure Build-up Analysis," Trans. Amer. Inst. Mining Metall. Petrol. Eng., Vol. 216, pp 38-43, 1959 (Tech. Pap. 8043).

Porter, A. L., Jr. "Developments Leading Up to the Area-Wide Brine Disposal Order of the New Mexico Oil Conservation Commission," Interstate Oil Compact Comm. Comm. Bull., Vol. 12, No. 2, pp 24-27, Dec. 1970.

Power, H. H. (See Plummer, F. B.)



Powers, T. J., and C. W. Querio, "Check on Deep-Well Disposal for Specially Troublesome Wastes," Power, Vol. 105, No. 8, pp 94-95, 1961.

Powers, T. J. (See Querio, C. W.)

Pozov, F. I. (See Smolyaninov, V. G.)

Preul, H. C., "Underground Pollution Analysis and Control," Water Res., Vol. 6, No. 10, pp 1141-1154, Oct. 1972.

Price, D., "Rate and Extent of Migration of a 'one-shot' Contaminant in an Alluvial Aquifer in Keizer, Oregon," Geological Survey Research 1967, U. S. Geol. Surv. Prof. Pap. 575-B, pp B217-B220.

Privrasky, N. C. (See McCann, T. P.)

Proctor, J. F., and I. W. Marine, "Geologic, Hydrologic and Safety Considerations in the Storage of Radioactive Wastes in a Vault Excavated in Crystalline Rock," Nucl. Sci. Eng., Vol. 22, No. 3, pp 350-365, 1965.

Proctor, J. F. (See Webster, D. S.)

Prout, W. E., "Studies of the Containment of Radioactive Wastes in Underground Mined Caverns at the Savannah River Plant," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 380-395, 1962.

Prusick, H., "Chemical Treatment of Injection Well," Forty-Second Texas Water Works Short School Proc., Tex. Water and Sewage Works Ass., pp 165-174, 1960.

Pryor, M. F. (See Wilhelm, C. J.)

Puri, H. S., et al, Hydrogeology of Subsurface Liquid Waste Storage in Florida, 2nd Int. AAPG-USGS-IAHS Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 2, pp 825-849, 1973.

Purtymun, W. D., et al, "Distribution of Radioactivity in the Alluvium of a Disposal Area at Los Alamos, New Mexico," Geological Survey Research 1966, U. S. Geol. Surv. Prof. Pap. 550-D, pp D25-D252, 1966.

Querio, C. W., and T. J. Powers, "Deep Well Disposal of Industrial Waste-Water," J. Water Pollut. Contr. Fed., Vol. 34, No. 2, pp 136-144, 1962.

Querio, C. W. (See Powers, T. J.)

Radhakrishna, G. N. (See Orlob, G. T.)

Rady, J. J., "Treatment and Disposal of Oil Field Brines," Oil Gas J., Vol. 38, No. 44, pp 48-49, 51, 1940.

Raifsnider, P. J. (See Dunlop, A. K.)

Raleigh, C. B., "Earthquakes and Fluid Injection," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2090, Nov. 1971.

Raleigh, C. B. (See Healy, J. H.)

Ramdohr, H., Untersuchungen zur Standortwahl einer Versuchskaverne zur Einlagerung Radioaktiver Rueckstaende (Siting Investigations for a Prototype Cavity for Radioactive Waste Storage), U. S. At. Energy Comm. Rep., BMWF-FBK-65-06, 40 pp, 1965 (In German).

Ramdohr, H. (See Krause, H.)

Ramey, B. J., "Deep-Down Waste Disposal," Mech. Eng., Vol. 90, No. 8 pp 28-31, 1968.

Ramos, J. (See Ostroot, G. W.)

Rancon, D., "Mecanisme de la Contamination Radioactive des Roches Consolidees Impermeables ou tres peu Permeables, (Mechanism of Radioactive Contamination in Consolidated Impermeable Rocks or Rocks of Very Low Permeability)," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency, Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 179-197, 1967 (In French).

Rawson, D. E., Industrial Applications of Contained Nuclear Explosions, Calif. Univ., Lawrence Radiation Lab. Rep., UCRL-14756, 59 pp, 1966.

Raymond, J. R., and W. H. Bierschenk, "Hydrologic Investigations at Hanford (Washington)," Amer. Geophys. Union Trans. Vol. 38, No. 5, pp 724-729, 1957.

Raymond, J. R., and V. L. McGhan, Scintillation Probe Results on 200 Area Waste Disposal Site Monitoring Wells, Gen. Elec. Co., Hanford At. Prod. Oper. Rep., HW-84577, 62 pp, 1964.

Raymond, J. R. (See Brown, D. J.)

Rebhun, M., and V. L. Hauser, Clearification of Turbid Water with Polyelectrolytes for Recharge Through Wells, Technion-Israel Inst. of Tech., Haifa Sanitary Engineering Lab., and Agricultural Research Service, Bushland, Tex. Southern Plains Branch, 1967.

Reck, C. W., and E. J. Simmons, Water Resources of the Buffalo-Niagara Falls Region, U. S. Geol. Surv., Circ. 173, 26 pp, 1952.

Reed, P., "Water-Flooding and Brine Disposal Methods Used in the Mid-Continent," Oil Gas J., Vol. 36, No. 44, pp 84-85, 88, 1938.

Reed, P., "Brine Disposal Plant," Oil Gas J., Vol. 37, No. 5, pp 44-46, 1938.

Reed, P., "Magnolia Petroleum Company's Water Disposal Project," Oil Gas J., Vol. 37, No. 32, pp 30-32, 34, 37, 1938.

Reed, P., "Disposal of Oil Field Brine," Oil Gas J., Vol. 37, No. 46, pp 174-175, 1939.

Reed, P., "Water Injection in Southeast Kansas," Oil Gas J., Vol. 39, No. 36, pp 54-56, 1941.

Reeder, L. R., Feasibility of Underground Waste Disposal in Northeastern Oklahoma, Geol. Soc. Amer. Abstracts with Programs, Vol. 4, No. 4, p 289, Feb. 1972.

Reeder, L. R., Underground Waste Disposal Systems, Geol. Soc. Amer. Abstracts with Programs, Vol. 4, No. 4, p 290, Feb. 1972.

Reeder, L. R., Reservoir Aspects of Deep Well Disposal, Amer. Ass. Petrol. Geol. Mid Continent Regional Mtg. (Tulsa, Oct. 3-5, 1973) Program, pp 26-27, 1973 (Abstr. only).

Redkin, I. I., et al, "Experimental Prolonged Injection of Waste Water, Obtained from Crude Oil Processing Units, Into Productive Zones of Kuleshovskii Field," Nauch.-Tekh. SB. Ser. Neftepromyslovoe Delo., No. 1, pp 31-36, 1970 (In Russian).

Reichert, S. O., "Disposal of Radioactive Waste to the Ground at the Savannah River Plant (South Carolina)," Ground Disposal of Radioactive Wastes Conference, 2nd At. Energy Can., Ltd. and U. S. At. Energy Comm. Div. Reactor Devel. 1961 Proc., Book 1 U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 115-129, 1962.

Reichert, S. O., "Radionuclides in Groundwater at the Savannah River (South Carolina) Plant Waste Disposal Facilities," J. Geophys. Res., Vol. 67, No. 11, pp 4363-4374, 1962.

Reichert, S. O., and J. W. Finimore, Lithology and Hydrology of Radioactive Waste-Disposal Sites, Savannah River Plant, South Carolina, Geol. Soc. Amer. Eng. Geol. Case Hist., No. 5, pp 53-69, 1964.

Reisenauer, A. E., et al, "The Computer Program," Steady Darcian Transport of Fluids in Heterogeneous Partially Saturated Porous Media, Gen. Elec. Co. Hanford At. Prod. Oper. Rep., HW-72335, 84 pp, 1963.

Reisenauer, A. E. (See Nelson, R. W.)

Reist, P. C., "Disposal of Waste Radioactive Gases in Porous Underground Media," Nucl. Appl., Vol. 3, No. 8, pp 474-480, 1967.

Repenning, C. A., Geologic Summary of the San Juan Basin, New Mexico, with reference to Disposal of Liquid Radioactive Waste, U. S. Geol. Surv. Trace Elements Invest. Rep., TEI-603, 57 pp, 1959.

Repenning, C. A., Geologic Summary of the Central Valley of California, with Reference to Disposal of Liquid Radioactive Waste, U. S. Geol. Surv. Trace Elements Invest. Rep., TEI-769, 69 pp, 1960.

Reynolds, T. D., and E. F. Gloyna, Reactor Fuel Waste Disposal Project--Permeability of Rock Salt and Creep of Underground Salt Cavities-Final Report, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-12383, 121 pp, 1960.

Rhea, A. S., and E. B. Miller, Jr., "Disposal of Salt Water in the East Texas Field," Petrol. Technol., Vol. 3, No. 1, pp 1-10, 1940 (Tech. Pap. 1151).

Rhoades, D. W. (See Wilding, M. W.)

Rice, I. M., "Salt Water Disposal in the Permian Basin," Prod. Mon., Vol. 32, No. 3, pp 28-30, 1968.

Rice, I. M., "New Plastic Tubing Tried in Oil Field Service," Oil Gas J., Vol. 51, No. 14, pp 106-107, 1952.

Rice, I. M., "Guidelines for Disposal Systems," Petrol. Eng., Vol. 39, No. 7, pp 36-38, 1967.

Rich, E. I. (See Pierce, W. G.)

Richardson, R. M., "Significance of Climate in Relation to the Disposal of Radioactive Waste at Shallow Depth Below Ground," La retention et la migration des ions radioactifs dans les sols-Colloque International, Saclay, France, 1962, Paris, Presses Universitaires de France, pp 207-211, 1963.

Richardson, R. M. (See Warde, J. M.)

Rifai, M. N., et al, Dispersion Phenomena in Laminar Flow Through Porous Media--Progress Report No. 2, Canal Seepage Research, July 1, 1955 to June 30, 1956, Calif. Univ. Sanit. Eng. Res. Lab. Div. Civil Eng. I.E.R. Ser. No. 93, Issue No. 2, 157 pp, 1956.

Rifai, M. N. E. (See Orcutt, R. G.)

Rima, D. R., "Some Factors to be Considered in the Design of Waste Disposal Wells," Sanitary and Water Resources Eng. Conf., 8th Annu. Proc., Vanderbilt Univ., Dept. Civil Eng., pp 119-127, 1969.

Rintoul, B., "The Other Alaska," Calif. Oil World, Vol. 62, No. 20, pp 29, 22, 24-25, 28-30, Oct. 31, 1969.

Robeck, G. G. (See Warner, D. L.)

Roberts, I. C. (See Beranek, J.)

Robertson, J. B., Behavior of Xenon-133 Gas After Injection Underground-Molecular Diffusion, Materials Balance, and Barometric Pressure Effects, U. S. Geol. Surv. Open-File Rep., (IDO-22051), 37 p, (Also available as U. S. At. Energy Comm. Rep., TID-4500) 1969.

Robertson, J. B., Vertical Molecular Diffusion of Xenon-133 Gas After Injection Underground, U. S. Geol. Surv. Prof. Pap. 700-D, pp D287-D300, 1970.

Robertson, J. B., and J. T. Barraclough, Radioactive- and Chemical-Waste Transport in Groundwater at National Reactor Testing Station, Idaho: 20-year Case History and Digital Model, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 291-322, 1973.

Robertson, J. B. (See Barraclough, J. T.)

Robinson, B. P., Ion-Exchange Minerals and Disposal of Radioactive Wastes--A Survey of Literature, U. S. Geol. Surv. Water-Supply Pap. 1616, 132 pp, 1962.

Roedder, E., Problems in the Disposal of Acid Aluminum Nitrate High-Level Radioactive Waste Solutions by Injection into Deep-Lying Permeable Formations, U. S. Geol. Surv. Bull. 1088, 65 pp, 1959.

Rogowski, A. S. (See Tamura, T.)

Rold, J. W., Pollution Problems in the "Oil Patch", 45th Annu. SPE of AIME Fall Mtg. (Houston, Oct. 4-7, 1970), Preprint No. SPE-3024, 4 pp, 1970. (Also in Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 6, pp 807-809, June 1971.)

Romero, E., and P. L. Leal, Plugging of Porous Media by Light Particles in Suspension, 3rd Soc. Venez. Ing. Petrol. Tec. Petrol. Conf. (Maracaibo, Oct. 14-16, 1971) Proc., Vol. 1, pp 51-65, 1972 (In Spanish).

Rorabaugh, M. I., "Problems of Waste Disposal and Ground Water Quality," J. Amer. Water Works Ass., Vol. 52, No. 8, pp 979-982, 1960.

Rose, J. L., "Advanced Waste Treatment in Nassau County, New York, Water Provided for Injection into Groundwater Aquifers," Water Waste Eng., Vol. 7, No. 2, pp 38-39, Feb. 1970.

- Rosenashvili, G. G. (See Smolvaninov, V. G.)
- Rosenshein, J. S. (See Wilson, W. E.)
- Rothe, J. P., "Man-Made Earthquakes," Tectonophysics, Vol. 9, Nos. 2-3, pp 215-238, March 1970.
- Rowe, P. P. (See Brown, R. E.)
- Ruby, W. W. (See Healy, J. H.)
- Rudd, N., Some Geological Factors in Deep Well Disposal Site Evaluation, SME of AIME Fall Mtg. (Seattle, Sept. 22-24, 1971) Preprint, No. 71-AG-325, 17 pp, 1971.
- Rudd, N., Subsurface Liquid Waste Disposal and Its Feasibility in Pennsylvania, Penn. Geol. Surv. Environ. Geol. Rep., No. 3, 111 pp, 1972.
- Rummer, R. R. (See Harleman, D. R. F.)
- Runyan, E. E., "Cement Lining, Modern Technology put an Old Tool to Work in Battle Against Corrosion," Drill Bit, Vol. 12, No. 10, pp 4-7, 1965.
- Ryan, V. H. (See Engquist, M. A.)
- Sadow, R. D., "How Monsanto Handles its Petrochemical Wastes," Wastes Eng., Vol. 34, No. 12, pp 640-644, 664, 1963.
- Sadow, R. D., "Waste Treatment at a Large Petrochemical Plant," J. Water Pollu. Contr. Fed., Vol. 38, No. 3, pp 428-441, 1966.
- Sadow, R. D., "Pretreatment of Industrial Wastewaters for Subsurface Injection," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2090, Nov. 1971.
- Samuelson, G. J., and B. H. Moore, "Chemical Compatibility Problems in Water Injection Systems," Oil Gas J., Vol. 56, No. 9, pp 113, 115, 118, 120, 1958.

Sand, F., "Waste Disposal," Water Resources Applications, Underground Storage of Natural Gas, and Waste Disposal Using Underground Nuclear Explosions, U. S. At. Energy Comm. Peaceful Nucl. Explosions Rep., PNE-3008, pp 64-71, 1967.

Sandberg, C. A., Geology of the Williston Basin, North Dakota, Montana, and South Dakota with Reference to Subsurface Disposal of Radioactive Wastes, U. S. Geol. Surv. Trace Elements Invest. Rep., TEI-809, 156 pp, 1962.

Sanders, T. P., "Salt Water Disposal in Michigan," Oil Gas J., Vol. 35, No. 34, pp 47, 49, 1937.

Sanford, R. M., "Closed Siphon System for Water Disposal," Oil Gas J., Vol. 40, No. 42, pp 57-58, 1942.

Sauty, J. P., "A Mathematical Model of the Propagation of a Pollution Front in an Aquifer," Houille Blanche, Vol. 26, No. 8, pp 731-735, 1971, (In French); Abstr. No. 4653, Appl. Mech. Rev., Vol. 26, No. 6, p 735, June 1973.

Sceva, J. E., Liquid Waste Disposal in the Lava Terrane of Central Oregon, Fed. Water Pollut. Contr. Admin. Pacific Northwest Water Lab. Tech. Proj. Br. Rep., FR-4, 1968.

Schaffer, W. F., Jr., et al, Project Salt Water Vault (Kansas)--Design and Demonstration of Equipment, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-P-1987, 36 pp, 1964.

Scheidegger, A. E., "General Statistical Hydrodynamics in Porous Media," Geofis. Pura Appl., Vol. 30, pp 17-26, Jan. Apr. 1955.

Scheidegger, A. E., Underground Dispersion of Miscible Liquids, Int. Ass. Aci. Hydrol. Pub. 52, pp 462-469, 1960.

Schicht, R. J., "Feasibility of Recharging Treated Sewage Effluent into a Deep Sandstone Aquifer," Ground Water, Vol. 9, No. 6, pp 29-35, Nov.-Dec. 1971.

Schicht, R. J., Deep-Well Injection of Desalting-Land Waste Brine, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 652-663, 1973.



Schmalz, B. L., "National Reactor Testing Station Waste Disposal Practice and Programs," Ground Disposal of Radioactive Wastes Conference, Energy Can. Limited and U. S. At. Energy Comm. Div. Reactor Devel. 1961 Proc., Book 2, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 536-568, 1962.

Schmalz, B. L., (Compiler), Injection of Gas into the Lithosphere at the National Reactor Testing Station, Idaho Falls, Idaho, U. S. At. Energy Comm. Idaho Oper. Office Rep., IDO-12069, 166 pp, 1969 (Also available as U. S. At. Energy Comm. Rep., TID-4500).

Schmalz, B. L. (See Jones, P. H.)

Schmalz, B. L. (See Mudra, P. J.)

Schmidt, L., and J. M. Devine, The Disposal of Oil Field Brines, U. S. Bur. Mines Rep. Invest. 2945, 17 pp, 1929.

Schmidt, L., and J. M. Devine, "Oil Field Brines Present a Problem," Oil Gas J., Vol. 28, No. 17, p 39, 1929.

Schmidt, L., et al, "Disposing of Oil Field Brines," Petrol. World, Vol. 32, No. 415, pp 103-106, 1935.

Schmidt, L. (See Grandone, P.)

Schmidt, L. (See Wilhelm, C. J.)

Schneider, A. D., et al, Movement and Recovery of Herbicides in the Ogallala Aquifer, The Ogallala Aquifer--A Symposium, Tex. Tech. Univ., Int. Cent. for Arid and Semi-Arid Land Stud. Spec. Rep. No. 39, pp 219-226, 1970.

Schnoor, F. H. (See Crooker, J. T.)

Schroeder, M. C., and R. A. Jennings, Laboratory Studies of the Radioactive Contamination of Aquifers, Calif. Univ., Lawrence Radiat. Lab. Rep., UCRL-13074, 120 pp, 1963.

Schuchardt, M. C. (See Krause, H.)

Schwarz, J. (See Rebhun, M.)

Schwarz, J. (See Sternau, R.)

Schwibach, J., "Research on the Permanent Disposal of Radioactive Wastes in Salt Formations in the Federal Republic of Germany," Disposal of Radioactive Wastes into the Ground-- Int. At. Energy Agency and Europe. Nucl. Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 465-477, 1967.

Schwille, F., et al, "Model Experiments on Fluid Flow in the Ground," Int. At. Energy Agency and Europe. Nucl. Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 151-160, 1967.

Sclater, K. C., "Salt Water Disposal," Petrol. Eng., Vol. 1, No. 4, p 38, 1930.

Scopel, L. J., "Pressure Injection Disposal Well, Rocky Mountain Arsenal, Denver, Colorado," Mountain Geol., Vol. 1, No. 1, pp 35-42, 1964.

Scott, J., "Pollution '70: Challenge, Crisis, Change," Petrol. Eng., Vol. 42, No. 11, pp 39-43, Oct. 1970.

Scott, V. H. (See Esmaili, H.)

Sealand, O. M. (See Boegly, W. J., Jr.)

Sealand, O. M. (See Jacobs, D. G.)

Selivanov, B. K. (See Redkin, I. I.)

Selm, R. P., and B. T. Hulse, "Deep Well Disposal of Industrial Wastes," Industrial Waste Conference, 14th, 1959 Proc., Purdue Univ. Eng. Bull., Vol. 44, No. 5, pp 566-586, 1960 (Also published in Chem. Eng. Prog., Vol. 56, No. 5, pp 138, 140, 142, 144, 1960).

Sexton, R. C. (See de Laguna, W.)

Shaikh, M. U. (See Jacobs, D. G.)

Shakely, S. F., Pollution and Pollution Control, 44th Annu. SPE of AIME Fall Mtg. (Denver, Sept. 28-Oct. 1, 1969) Preprint, No. SPE 2532, 4 pp, 1969.

Shakely, S. F., Salt Water Disposal, 5th Annu. Heart. Amer. Well Drilling, Prod., Maintenance Inst. Mtg. (Liberal, Kans., Feb. 3-4, 1970) Preprint, 4 pp, 1970.

Shamin, V. S. (See Mal'tsev, E. D.)

Shamir, U. Y., and D. R. F. Harleman, "Numerical Solutions for Dispersion in Porous Mediums," Water Resources Res., Vol. 3, No. 2, pp 557-581, 1967.

Shamir, U. Y., and D. R. F. Harleman, "Dispersion in Layered Porous Media," J. Hydraul. Div. Amer. Soc. Civil Eng. Proc. Vol. 93, No. HY 5, pp 237-260, 1967 (Pap. 5445).

Shannon, E. S., "Underground Disposal of Activated Sludge," J. Water Pollut. Contr. Fed., Vol. 40, No. 12, pp 2059-2061, 1968.

Shannon, R. L., Radioactive Waste Disposal--A Bibliography of Unclassified Literature, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-375, 8 pp, 1950.

Sharp, J. V. A. (See Carnahan, C. L.)

Shelby, J. M. (See Bowen, B. M., Jr.)

Sheldrick, M. G., Deep Well Disposal--Answer to Pollution or New Pollution Problem?, 26th Nace Conf. (Philadelphia, Mar. 2-6, 1970) Proc., pp 445-448, 1970.

Sheldrick, M. G., "Deep-Well Disposal--Are Safeguards Being Ignored?" Chem. Eng., Vol. 76, No. 7, pp 74-76, 78, 1969.

Sherzhukov, B. S. (See Verigin, N. N.)

Shindala, A., "Treatment and Disposal of Radioactive Wastes," Water Sewage Works, Vol. 115, 1968 Reference Number, pp R210-R212, Nov. 29, 1968.

Shoeneck, W. E., Injection of Water into Underground Reservoirs in Michigan, Amer. Petrol. Inst. Drilling Prod. Pract., 1945, pp 95-116, 1945.

Short, E. H., Jr., "Latest Improvements Incorporated into Conroe Salt Water Disposal Plant," Oil Gas J., Vol. 44, No. 36, pp 95, 97-98, 1946.

Shuter, E. (See Jones, P. H.)

Signor, D. C., Laboratory Facility for Studies Related to Artificial Recharge, 2nd Int. AAPG-USGS-IAHS Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 2, pp 799-822, 1973.

Simmons, E. J. (See Reck, C. W.)

Simon, R. B., "The Denver Earthquakes, 1962-1967," Earthquake Notes, Vol. 39, Nos. 1-2, pp 37-40, 1968.

Simon, R. B. (See Major, M. W.)

Simons, H. F., "Salt Water Disposal Plant in Illinois Field," Oil Gas J., Vol. 39, No. 34, pp 32-33, 1941.

Simons, H. F., "East Texas Salt-Water Disposal Project May Set Pattern for Future," Oil Gas J., Vol. 41, No. 39, pp 38-41, 1943.

Simpson, E. (See Souffriau, J.)

Siple, G. E., "Geohydrology of Storage of Radioactive Waste in Crystalline Rocks at the AEC Savannah River Plant, South Carolina," Geological Survey Research 1964, U. S. Geol. Surv. Prof. Pap. 501-C, pp C180-C184, 1964.

Skibitzke, H. E., Temperature Rise Within Radioactive Wastes Injected into Deep Formations, U. S. Geol. Surv. Prof. Pap. 368-A, 8 pp, 1961.

Slagle, K. A., and J. M. Stogner, "Oil Fields Yield New Deep-Well Disposal Technique," Water Sewage Works, Vol. 116, No. 6, pp 238-244, 1969.

Slansky, C. M., and J. A. Buckham, "Ultimate Management of Radioactive Liquid Wastes," Chem. Eng. Prog., Symp. Ser., Vol. 685, No. 97, pp 26-31, 1969.

Smirnov, A. S., "Nadezhnyi Sposob Ochistki Stokhnykh Promyslovykh Vod (A Reliable Method for Purifying the Waste Waters in Oil Fields)," Neft. Khoz., Vol. 35, No. 7, pp 66-67, 1957 (In Russian).

Smith, H. F., "Subsurface Storage and Disposal in Illinois," Ground Water, Vol. 9, No. 6, pp 20-28, Nov.-Dec. 1971.

Smith, H. L., and L. N. Stickland, "Membrane Filter Tests Evaluate Quality of Injection Waters," Baroid News Bull., Vol. 23, No. 1, pp 21-27, 1972.

Smith, J. E., "Cooperation is Key to Pollution Control in East Texas," Petrol. Eng., Vol. 43, No. 12, pp 44-46, 48, 51, Nov. 1971.

Smith, L. E., "Disposal of Salt Water in Oil Fields," Nat. Petrol. News, Vol. 28, No. 53, pp 50-51, 1936.

Smith, R. D., "Burying your Pickle Liquor Disposal Problem," Civil Eng., Vol. 39, No. 11, pp 37-38, 1969.

Smith, R. E., "Petrographic Properties Influencing the Reservoir Potential of the Gatesburg Formation Based on Studies Near State College and Tyrone, Pennsylvania," Prod. Mon., Vol. 31, No. 6, pp 18-23, 1967.

Smith, R. V. (See Joers, J. C.)

Smith, R. W., and W. W. Wen, "Absorption of Cationic and Anionic Surfactants on Kaolinite," Mining Symposium, 27th Annu. Minnesota Univ., and AIME, Minnesota Sec., 39th Annu. Mtg., pp 193-196, 1966.

Smolyanivov, V. G., et al, "Use of Wine Industrial Wastes as a Retarder in Hardening of Cement Slurries," Burenie, No. 2, pp 22-25, 1971 (In Russian).

Sniegocki, R. T., "Plugging by Air Entrapment in Artificial Recharge Tests," Water Well J., Vol. 13, No. 6, pp 17-18, 43-44, 1959.

Sniegocki, R. T., "Ground-Water Recharge and Conservation--Effects on Viscosity and Temperature," J. Amer. Water Works Ass., Vol. 52, No. 12, pp 1487-1490, 1960.

Sniegocki, R. T., Geochemical Aspects of Artificial Recharge in the Grand Prairie Region, Arkansas, U. S. Geol. Surv. Water-Supply Pap. 1615-E, 41 pp, 1963.

Snow, D. T., "Hydraulic Characteristics of Fractured Metamorphic Rocks of Front Range and Implications to the Rocky Mountain Arsenal Well," Colo. Sch. Mines Quart., Vol. 63, No. 1, pp 167-199, 1968.

Snyder, R. E., "Recent Technology Previews New Production Trends," World Oil, Vol. 170, No. 3, pp 82-85, Feb. 15, 1970.

Sobolev, I. A., et al, "Opytnoye Zakhoroneniye Radioaktivnykh Otkhdov Nizkogo Urovnya Aktivnosti V Glinistykh Gruntakh Na Moskovskoy Stanstii (The Experimental Disposal of Low-Level Radioactive Wastes in Clay Soil at the Moscow Disposal Center)," The Experimental Disposal of Low-Level Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 37-47, 1967 (In Russian).

Socias, E. (See Krizek, R. J.)

Souffriau, J., et al, "The Copper-Rod Method for Measuring Ground-Water Flow," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 155-165, 1962.

Souffriau, J. (See Baetsle, L. H.)

Spalding, C. W., et al, "Deep-Well Disposal of Spent Pulping Liquors," TAPPI (Tech. Ass. Pulp Paper Ind.), Vol. 48, No. 5, pp 68A-71A, 1965.

Spalding, C. W. (See Brown, R. W.)

Spencer, C. W. (See Peterson, J. A.)

Spicyn, W. J., "Problem odpadow Promieniotworczych W Technice Wspolczesnej (Problems of Radioactive Wastes in Modern Technology)," Nukleonika, Vol. 2, No. 3, pp 451-464, 1957 (In Polish).

Spitsyn, E. Ya., "Treatment and Disposal of Radioactive Wastes," Transl. from Atomizdat, Moskva, 1965.

Spitsyn, V. I., and V. D. Balukova, "Investigation of Sorption and Migration of Radioactive Isotopes in Soils and Rocks of Various Compositions," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 169-177, 1967.

Spitsyn, V. I., et al, "Scientific Prerequisites for Utilizing Deep-Lying Formations for Burying Liquid Radioactive Wastes," Disposal of Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency, (STI/PUB/156), pp 563-576, 1967.

Spitsyn, V. I., et al, "Physiochemical Conditions of Underground Disposal of Radioactive Wastes," Soviet At. Energy, Vol. 24, No. 2, pp 160-163, 1968 (Translated from Atomnaya Energiya, Vol. 24, No. 2, pp 133-136, 1968).

Sproul, C. R. (See Garcia-Bengochea, J. I.)

Stahl, C. D., "Compatibility of Interstitial and Injection Waters," Prod. Mon., Vol. 26, No. 11, pp 14-15, 1962.

Stallman, R. W., "Data Needs for Predicting Problems Caused by the Use of Subsurface Reservoirs," Water Resources Res., Vol. 8, No. 1, pp 238-241, Feb. 1972.

Stallman, R. W., Subsurface Waste Storage--The Scientist's Dilemma, Amer. Ass. Petrol. Geol. Mem., No. 18, pp 6-10, Dec. 1972.

Staner, P. (See de Jonghe, P.)

Stanonis, F. L., Oil Field Technology Applied to Subsurface Disposal of Industrial Fluid Wastes, Kentucky Geol. Surv. Spec. Publication 16, Ser. 10, pp 90-96, 1969.

Stead, F. W., "Distribution in Groundwater of Radionuclides from Underground Nuclear Explosions," Engineering with Nuclear Explosives, Proc. Third Plowshare Symp., Apr. 1964, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7695, pp 127-138, 1964.

Stead, F. L. (See McCann, T. P.)

Stearns, G. M., "Disposal Line Cost Comparison," Oil Gas J., Vol. 42, No. 11, p 47, 1943.

Stefanko, R., "Subsurface Disposal of Mine Water," Soc. Mining Eng. Trans., Vol. 247, No. 1, pp 54-60, 1970.

Stephan, R. W., and W. C. Lorenz, Survey of Costs on Methods for Control of Acid Mine Drainage Pollution, Attachment E. to Appendix C - The Incidence and Formation of Mine Drainage Pollution, Bureau of Mines Report, Vol. 18 of 25 Vols. on Development of Resources in Appalachia, 1967.

Stephens, J. R. (See Marshall, G. E.)

Stericker, W., "Prevention of Corrosion of Steel Pipe Lines by Oil Well Brines," Oil Gas J., Vol. 39, No. 42, pp 72, 74, 1941.

Sternau, R., et al, Radio-Isotope Tracers in Large-Scale Recharge Studies of Groundwater, Int. At. Energy Agency Symp. (Vienna, Austria, Nov. 14-18, 1966) Proc., pp 489-505, May 1967.

Stevens, D. B., "Wastewater Reuse," J. Water Pollut. Contr. Fed., Vol. 40, No. 4, pp 677-683, Apr. 1968.

Stevenson, J. D. (See Morgan, J. M., Jr.)

Stewart, J. W., et al, Geologic and Hydrologic Investigation at the Site of the Georgia Nuclear Laboratory, Dawson County, Georgia, U. S. Geol. Surv. Bull. 1133-F, pp F1-F90, 1964.

Stewart, J. W., Infiltration and Permeability of Weathered Crystalline Rocks, Georgia Nuclear Laboratory, Dawson County, Georgia, U. S. Geol. Surv. Bull. 1133-D, pp D1-D59, 1964.

Stewart, R. S., "Techniques of Deep Well Disposal - A Safe and Efficient Method of Pollution Control," 15th Ontario Ind. Waste Conf. (Ontario, Jun. 9-12, 1968) Proc., pp 37-43, 1968; Abstr. No. W71-08015, Selec. Water Resources Abstr., Vol. 4, No. 15, p 64, Aug. 1, 1971.

St. John, A. N. T., and T. R. Thierry, "Use of Fluorocarbons for Fluid Handling Equipment," Mater. Protect. Performance, Vol. 9, No. 9, pp 15-18, Sept. 1970.

Stiff, H. A., Jr., and L. E. Davis, "A Method for Predicting the Tendency of Oil Field Waters to Deposit Calcium Carbonate," J. Petrol. Technol., Vol. 4, No. 9, pp 213-216, 1952 (Also published in Trans. Amer. Inst. Mining Met. Petrol. Eng., Vol. 195, pp 213-216, 1952, Tech. Pap. 3395).



Stogner, J. M. (See Slagle, K. A.)

Stormer, H. A., Fluid Cylinders for High Pressure Waterflood Pumps, Int. NACE Corrosion Forum (Chicago, Mar. 22-26, 1971) Preprint, No. 15, 11 pp, 1971.

Stormont, D. H., "East Texas Salt-Water Injection Plants," Oil Gas J., Vol. 40, No. 22, pp 34-35, 1941.

Stormont, D. H., "Cost Estimates for Reinjecting Salt Water to the East Texas Woodbine Sand," Oil Weekly, Vol. 104, No. 2, pp 24-26, 1941.

Stormont, D. H., "Automatic Brine Disposal Plant Small but Efficient," Oil Gas J., Vol. 51, No. 36, p 114, 1953.

Stow, S. H. (See Grubbs, D. M.)

Straub, C. P., "Discharge to the Soil Environment," Low Level Radioactive Wastes--Their Handling, Treatment and Disposal, U. S. At. Energy Comm. Div. Tech. Inform., pp 103-128, 1964.

Street, R. L. (See Bruch, J. C.)

Strnad, M., and D. Novotny, "Determination of the Mechanical Compatibility of Porous Rocks with Waste Water in its Sub-surface Disposal," Water Res., Vol. 7, No. 11, pp 1599-1607, Nov. 1973.

Struxness, E. G., et al, Radioactive Waste Disposal, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-3347, pp 1-46, 1962.

Struxness, E. G. (See Boegly, W. J., Jr.)

Struxness, E. G. (See de Laguna, W.)

Subrahmanyam, K., and T. R. Bhaskaran, "The Risk of Pollution of Ground Water from Borehole Latrines," Indian (Calcutta), Med. Gaz., Vol. 85, pp 418-420, Sept. 1950.

Sun, R. J., "Theoretical Size of Hydraulically Induced Horizontal Fractures and Corresponding Surface Uplift in an Idealized Medium," J. Geophys. Res., Vol. 74, No. 25, pp 5995-6011, 1969.

Sun, R. J., Hydraulic Fracturing as a Tool for Disposal of Wastes in Shale, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 219-270, 1973.

Svec, J. (See Mackrle, V.)

Swolfs, H. S., and M. Friedman, "Mechanical and Chemical Effects of Pore Fluids on Rock Properties," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11, (Pt. 1), p 2090, Nov. 1971.

Swolfs, H. S., Chemical Effects of Pore Fluids on Rock Properties, Amer. Ass. Petrol. Geol. Mem., No. 18, pp 224-234, Dec. 1972.

Tadmor, J., and K. E. Cowser, "Underground Disposal of Krypton-85 from Nuclear Fuel Reprocessing Plants," Nucl. Eng. Design, Vol. 6, No. 3, pp 243-250, 1967.

Talbot, J. S., and P. Beardon, "The Deep Well Method of Industrial Waste Disposal," Chem. Eng. Progr., Vol. 60, No. 1, pp 49-52, 1964.

Talbot, J. S., "Some Basic Factors in the Consideration and Installation of Deep-Well Disposal Systems," Industrial Water and Waste Conference, 7th, Tex. Water Pollut. Contr. Ass., 1967 Proc., Tex. Univ., pp 111-1 - 111-24, 1967.

Talbot, J. S., "Some Basic Factors in the Consideration and Installation of Deep Well Disposal Systems," Water Sewage Works, Vol. 115, 1968 Reference Number, pp R210-R212, Nov. 29, 1968.

Talbot, J. S., "Requirements for Monitoring of Industrial Deep-Well Waste Disposal Systems," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), pp 2090-2091, Nov. 1971.

Tamura, T., "Chemical Development of Waste-Cement Mixes," Nucl. Eng. Design, Vol. 5, No. 4, pp 477-485, 1967.

Tamura, T., "Strontium Reactions with Minerals," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 186-197, 1962.

Tamura, T., et al, "Fate of Nuclides in Terrestrial Environment," Radioactive Waste Disposal, U. S. At. Energy Comm. Oak Ridge Nat. Lab. Rep., ORNL-4007, pp 3-9, 1966.

Tamura, T. (See de Laguna, W.)

Tamura, T. (See McClain, W. C.)

Taylor, K. E. (See Cox, L. G.)

Taylor, S. S., et al, Study of Brine-Disposal Systems in Illinois Oil Fields, U. S. Bur. Mines Rep. Invest. 3534, 20 pp, 1940.

Taylor, S. S., and E. O. Owens, Subsurface Disposal of Oil-Field Brines in Oklahoma, U. S. Bur. Mines Rep. Invest. 3603, 54 pp, 1942.

Taylor, S. S., et al, Typical Oil Field Brine-Conditioning Systems, Preparing Brine for Subsurface Injection, U. S. Bur. Mines Rep. Invest. 3434, 71 pp, 1939.

Teasdale, W. E. (See Barraclough, J. T.)

Teis, K. R., "Subsurface Disposal of Oil Field Brines," Oil Weekly, Vol. 100, No. 5, pp 16-22, 24, 1941.

Telfair, J. S., Jr., The Pollution of Artesian Ground Waters in Suwannee and Orange Counties, Florida, by Artificial Recharge Through Drainage Wells, Florida State Board Health, Bur. Sanit. Eng. Interim Rep. Invest., 40 pp, 1948.

Theis, C. V., "Geologic and Hydrologic Factors in Ground Disposal of Waste," Sanitary Engineering Conference, Baltimore, Md., April 15, 16, 1954, U. S. At. Energy Comm. Rep., WASH-275, pp 261-283, 1955.

Theis, C. V., "A Review of the Ground-Water Geology of the Major Waste Producing Sites," Seminar on Sanitary Engineering Aspects of the Atomic Energy Industry--U. S. At. Energy Comm. and U. S. Public Health Serv., 1955 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7517, Pt. 1a, pp 116-131, 1956.

Thierry, T. R. (See St. John, A. N. T.)

Thomas, H. C., "Problems in Sorption on Clay Minerals Illustrated with Data on the System Cs-Ba-Montmorillonite," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can., Limited and U. S. At. Energy Comm. Div. Reactor Devel., 1961 Proc., Book 1, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7628, pp 179-186, 1962.

Thomas, R. D. (See Champlin, J. B. F.)

Thomas, R. G. (See Christenson, C. W.)

Thorne, H. M. (See Schmidt, L.)

Thorne, H. M. (See Wilhelm, C. J.)

Thurston, W. R., "Summary of Princeton Conference on Disposal of High-Level Radioactive Waste Products in Geologic Structures," Seminar on Sanitary Engineering Aspects of the Atomic Energy Industry--U. S. At. Energy Comm. and U. S. Pub. Health Serv., 1955 Proc., U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7517, Pt. 1a, pp 47-52.

Tillson, D. D. (See Raymond, J. R.)

Titkov, N. I., et al, "Light Thermal and Salt Stable Materials for Cementing Deep Wells," Neft. Khoz., No. 2, pp 19-22, Feb. 1971 (In Russian).

Todd, D. K. (See Rifai, M. N. E.)

Tofflemire, T. J., "A Review of the 1969 Literature on Waste Water and Water Pollution Control-Deep-Well Injection," J. Water Pollut. Contr. Fed., Vol. 42, No. 6, pp 1231-1235, June 1970.

Tofflemire, T. J., and G. P. Brezner, "Deep-Well Injection of Waste Water," J. Water Pollut. Contr. Fed., Vol. 43, No. 7, pp 1468-1479, July 1971.

Tofflemire, T. J., and F. E. VanAlstyne, "Wastewater Treatment: Deep-Well Injection," J. Water Pollut. Contr. Fed., Vol. 45, No. 6, pp 1103-1108, June 1973.

Towers, L. H., "Salt Water Disposal Plant in Oil Field," Petrol. Eng., Vol. 9, No. 6, pp 52, 54, 1938.

Trelease, F. J., "Liability for Harm From Underground Waste Disposal," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11 (Pt. 1), p 2091, Nov. 1971.

Troemper, A. P., "Salt Water Disposal," Independ. Mon., Vol. 12, No. 9, pp 17-20, and Vol. 12, No. 10, pp 19-24, 1942.

Tucker, W. E., "Subsurface Disposal of Liquid Industrial Wastes in Alabama--A Current Status Report," Ground Water, Vol. 9, No. 6, pp 10-19, Nov.-Dec. 1971.

Tucker, W. E., and R. E. Kidd, Deep-Well Disposal in Alabama, Ala. Geol. Surv. Bull. 104, 203 pp, 1973.

Tucker, W. E. (See Grubbs, D. M.)

Turner, W. J., "Deep-Well Disposal," Water Wastes Eng., Vol. 7, No. 9, pp E28-E31, 1970; Abstr. No. 05466, Abstr. No. Amer. Geol., p 843, May 1971.

Ulrich, R. A. (See Peterson, J. A.)

U. S. Office Water Resources Res. Staff, "Subsurface Water Pollution. A Selective Annotated Bibliography. Pt. 1. Subsurface Waste Injection," Rept. No. WRSIC-72-220E W72-12685, 164 pp, March 1972, PB-211, 340; Abstr., Gov. Rept. Announce., Vol. 72, No. 19, p 117, Oct. 10, 1972.

Usoltsev, L. N., and B. I. Lerman, "Results from Study of Wells to be used for Disposal of Produced Waters," Razvedka Okhrana Nedr, No. 9, pp 55-57, Sept. 1970 (In Russian).

Valiullin, A. V. (See Maksutov, R. A.)

VanAlstyne, F. E. (See Tofflemire, T. J.)

Van Den Berg, J., et al, "Developments in East-Central States in 1969," Amer. Ass. Petrol. Geol. Bull., Vol. 54, No. 6, pp 965-973, June 1970.

van Everdingen, A. F., Fluid Mechanics of Deep-Well Disposals, Amer. Ass. Petrol. Geol. Mem. 10, pp 32-42, 1968.

van Poollen, H. K., and J. R. Jargon, "Steady-State and Unsteady-State Flow of Non-Newtonian Fluids Through Porous Media," Soc. Petrol. Eng. J., Vol. 9, No. 1, pp 80-88, 1969.

van Poollen, H. K., and D. B. Hoover, Waste Disposal and Earthquakes at the Rocky Mountain Arsenal, Derby, Colorado, 44th Annu. SPE of AIME Fall Mtg. (Denver, Sept. 28-Oct. 1, 1969) Preprint, No. SPE 2558, 15 pp, 1969.

van Poollen, H. K., and D. B. Hoover, "Waste Disposal and Earthquakes at the Rocky Mountain Arsenal, Derby, Colorado," J. Petrol. Technol., Vol. 22, No. 8, pp 983-993, Aug. 1970.

Veal, H. K. (See Garbarini, G. S.)

Vecchioli, J., "A Note on Bacterial Growth Around a Recharge Well at Bay Park, Long Island, New York," Water Resources Res., Vol. 6, No. 5, pp 1415-1419, Oct. 1970.

Vecchioli, J., and A. A. Giaimo, Corrosion of Well-Casing and Screen Metals in Water From the Magothy Aquifer and in Injected Reclaimed Water, Bay Park, Long Island, New York, U. S. Geol. Surv. Prof. Pap., No. 800-B, pp B247-B251, 1972.

Vecchioli, J., and H. F. H. Ku, Preliminary Results of Injecting Highly Treated Sewage-Plant Effluent into a Deep Sand Aquifer at Bay Park, New York, U. S. Geol. Surv. Prof. Pap., No. 751-A, 16 pp, 1972.

Veir, B. B., "Celanese Deep-Well Disposal Practices," Industrial Water and Waste Conference, 7th, Texas Water Pollution Control Ass., 1967 Proc., Tex. Univ., pp 111-25 - 111-36, 1967 (Also published in Water Sewage Works, Vol. 116, No. 5, pp 1/W21-1/W24, 1969).

Velov, Yu. V. (See Maksutov, R. A.)

Ven, B. (See Klotzman, M.)

Verigin, N. N., and B. S. Sherzhukov, Some Questions Concerning Geochemical Hydrodynamics, Int. Assn. Sci. Hydrol. Publication 78, pp 45-53, 1968.

Verigin, N. N., et al, "Problems Samorazogreva Pri Zenslyanom Zakhoroneni Tverdykh Radioaktivnykh Otkhodov (Problem of Heat Generation in Underground Storage of Solid Radioactive Wastes)," Disposal of Radioactive Wastes into the Ground-- Int. At. Energy Agency and Europe. Nucl. Energy Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 441-454, 1967 (In Russian).

Vernon, R. O., The Beneficial Uses of Zones of High Transmissivities in the Florida Subsurface for Water Storage and Waste Disposal, Florida Dept. Natur. Resources Bur. Geol. Inform. Circ., No. 70, 42 pp, 1970.

Vernon, R. O. (See Garcia-Bengochea, J. I.)

Volek, C. W. (See Chapplear, J. E.)

Voress, H. E., et al, (Compilers), Radioactive Waste Processing and Disposal - A Bibliography of Selected Report Literature, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-3311, 131 pp, 1958.

Wagner, W. R. (See Kelly, D. R.)

Wainerdi, R. E., "The Disposal of Radioactive Waste," Prod. Mon., Vol. 25, No. 1, pp 6-7, 1961.

Walker, E. H., Ground-Water Resources of the Hopkinsville Quadrangle, Kentucky, U. S. Geol. Surv. Water-Supply Pap. 1325, 98 pp, 1956.

Walker, R. A. (See Erickson, M. D.)

Walker, T. R., "Ground-Water Contamination in the Rocky Mountain Arsenal Area, Denver, Colorado," Geol. Soc. Amer. Bull., Vol. 72, No. 3, pp 489-494, 1961.

Walker, W. R., and R. C. Stewart, "Deep Well Disposal of Wastes," J. Sanit. Eng. Div. Amer. Soc. Civil Eng. Proc., Vol. 94, No. SA 5, pp 945-968, 1968 (Paper 6171).

Walker, H. D. (See McMaster, W. M.)

Wallace, A. T. (See Abegglen, D. E.)

Wallin, W. E. (See Alciatore, A. F.)

WAPORA, Inc., Compilation of Industrial and Municipal Injection Wells in the United States, U. S. Environmental Protection Agency, 1350 pp, 1974.

Warde, J. M., and R. M. Richardson, "Waste Disposal - Vital to Atomic Power Development," Mining Eng., Vol. 7, No. 5, pp 458-461, 1955.

Warner, D. L., "Deep-Well Disposal of Industrial Wastes," Chem. Eng., Vol. 72, No. 1, pp 73-78, 1965.

Warner, D. L., Deep-Well Injection of Liquid Waste--A Review of Existing Knowledge and an Evaluation of Research Needs, U. S. Public Health Serv. Publication 999-WP-21, 55 pp, 1965.

Warner, D. L., "Deep Well Waste Injection - Reaction with Aquifer Water," J. Sanit. Eng. Div., Vol. 92, No. SA 4, pp 45-69, 1966 (Paper 4881).

Warner, D. L., "Subsurface Injection of Liquid Wastes," Natural Gas, Coal, Ground Water - Exploring New Methods and Techniques in Resources Research - Western Resources Conf., 8th Colo. Sch. Mines, Colorado Univ. Press, Boulder, Colo., pp 107-125, 1967.

Warner, D. L., and L. F. Doty, Chemical Reaction Between Recharge Water and Aquifer Water, Int. Ass. Sci. Hydro. Publication 72, pp 278-288, 1967.

Warner, D. L., et al, "Injection Wells for Pollution Control and Conservation," Bienn. Microbiology Symposium, 3rd, 1966 Reprints, Amer. Petrol. Inst., Prod. Div., pp 192-200, 1967.

Warner, D. L., Deep-Wells for Industrial Waste Injection in the United States, Summary of Data, Fed. Water Pollut. Contr. Admin., Water Pollut. Contr. Res. Ser. Publication WP-20-10, 45 pp, 1967.

Warner, D. L., Subsurface Disposal of Liquid Industrial Wastes by Deep-Well Injection, Amer. Ass. Petrol. Geol. Mem. 10, pp 11-20, 1968.

Warner, D. L., Survey of Industrial Waste Injection Wells, Spons. by U. S. Geol. Surv., 2036 pp, 1973.



Warner, D. L., and D. H. Orcutt, Industrial Wastewater-Injection Wells in United States - Status of Use and Regulation, 1973, 2nd Int. AAPG-USGS-IAHS Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 2, pp 687-697, 1973.

Warner, D. L. (See Cleary, E. J.)

Watkins, J. W., "Corrosion and Chemical Testing of Waters for Subsurface Injection," Prod. Mon., Vol. 14, No. 4, pp 15-19, 1950 (Additional installments in Vol. 14, No. 5, pp 30-31, and Vol. 14, No. 6, pp 25-31).

Watkins, J. W., Analytical Methods of Testing Waters to be Injected into Subsurface Oil Productive Strata, U. S. Bur. Mines Rep. Invest. 5031, 29 pp, 1954.

Watkins, J. W., "Design and Operation of Plants for the Preparation of Water for Injection into Oil Reservoirs," J. Petrol. Technol., Vol. 7, No. 4, pp 17-23, 1955.

Watkins, J. W., "New Trends in Treating Water for Injection," World Oil, Vol. 146, No. 1, pp 143, 145, 146-150, 1958.

Watkins, J. W., and E. S. Mardock, "Use of Radioactive Iodine as a Tracer in Water-Flooding Operations," Trans. Amer. Inst. Mining Met. Petrol. Eng., Vol. 201, pp 209-216, 1954 (Tech. Pap. 3894).

Watkins, J. W., and J. Wright, "Corrosive Action on Steel by Gases Dissolved in Water," Petrol. Eng., Vol. 25, No. 12, pp B50-B51, B53, B55, B57, 1953.

Watkins, J. W., et al, "Feasibility of Radioactive Waste Disposal in Shallow Sedimentary Formations," Nucl. Sci. Eng., Vol. 7, No. 2, pp 133-143, 1960.

Watson, K. K. (See Pilgrim, D. H.)

Watson, L. C., "Mineral Exchange in Canada's Waste Treatment Program," The Use of Inorganic Exchange Material for Radioactive Waste Treatment--A Working Meeting Held in Washington, D. C., Aug. 13-14, 1962, U. S. At. Energy Comm. Div. Tech. Inform. Rep., TID-7644, pp 75-82, 1963.

Wayman, C. H., "Absorption on Clay Mineral Surfaces," Principles and Applications of Water Chemistry--Rudolfs Res. Conf., 4th, Rutgers Univ., Proc., John Wiley and Sons, New York and London, pp 127-167, 1967.

Webster, D. S., et al, Two-Well Tracer Test in Fractured Crystalline Rock, U. S. Geol. Surv. Water-Supply Pap. 1544-1, 22 pp, 1970.

Weeren, H. O., "Pipe Radioactive Wastes to Shale Beds," Heating, Piping, Air Conditioning, Vol. 36, No. 11, pp 122-123, 1964.

Weeren, H. O., "Design of ORNL's Shale-Fracturing Plant," Nucl. Eng. Design, Vol. 4, No. 5, pp 108-117, 1966.

Weeren, H. O. (See de Laguna, W.)

Weimer, R. J. (See Hollister, J. C.)

Weisflog, D. (See Schwille, F.)

Welsch, W. F. (See Lieber, M.)

Wen, W. W. (See Smith, R. W.)

Wesner, G. M., and D. C. Baier, "Injection of Reclaimed Wastewater into Confined Aquifers," J. Amer. Water Works Ass., Vol. 62, No. 3, pp 203-210, March 1970.

Wesner, G. M., and D. C. Baier, "Injection of Wastewater into Confined Aquifers," Johnson Drillers J., Vol. 42, No. 3, pp 1-5, May-June 1970.

West, S. W., Disposal of Uranium-Mill Effluent Near Grants, New Mexico, U. S. Geol. Surv. Prof. Pap. 424-D, pp D376, D379, 1961.

West, S. W., Disposal of Uranium-Mill Effluent by Well Injection in the Grants Area, Valencia County, New Mexico, U.S. Geol. Surv. Prof. Pap., No. 386-D, 32 pp, 4 Pl., 1973.

Wheeler, C. T., Jr., "Tip Top Gas Field, Sublette County, Wyoming," Earth Sci. Bull., Vol. 4, No. 1, 12 pp (Mid-Bull. Suppl.), March 1971.

White, W. A. (See Bredehoeft, J. D.)

White, W. A., and S. M. Bremser, Effects of a Soap, a Detergent, and a Water Softener on the Plasticity of Earth Materials, Ill. Geol. Surv. Environ. Geol. Notes, No. 12, 15 pp, 1966.

Wiebenga, W. A. (See Ellis, W. R.)

Wiese, A. F. (See Schneider, A. D.)

Wilding, M. W., and D. W. Rhodes, Removal of Radioisotopes from Solution by Earth Materials from Eastern Idaho, Phillips Petrol. Co., At. Energy Div. Rep., Conf-179-5, 12 pp, 1964.

Wilhelm, C. J., and L. Schmidt, Preliminary Report on the Disposal of Oil-Field Brines in Ritz-Canton Oil Field, McPherson County, Kansas, U. S. Bur. Mines Rep. Invest. 3297, 20 pp, 1935.

Wilhelm, C. J., et al, Disposal of Oil-Field Brines in the Arkansas River Drainage Area in Western Kansas, U. S. Bur. Mines Rep. Invest. 3318, 28 pp, 1936.

Wilhelm, C. J. (See Schmidt, L.)

Wilhelm, C. J. (See Taylor, S. S.)

Williams, B. F., "Salt of the Earth--A Pollution Problem," Water Works Eng., Vol. 93, No. 19, pp 1165-1167, 1194, 1940.

Williams, G. F., "Formation Cleaner Increases Stimulation Results," Petrol. Eng., Vol. 39, No. 11, pp 81, 84, 1967.

Williams, N., "Preventing Water Pollution," Oil Gas J., Vol. 35, No. 48, pp 153-154, 156, 1937.

Williams, R. E., and R. N. Farvolden, "The Influence of Joints on the Movements of Ground Water Through Glacial Till," J. Hydrol., Vol. 5, No. 2, pp 163-170, 1967.

Williams, R. E. (See Abegglen, D. E.)

Willis, D. G. (See Hubbert, M. K.)

Wilmoth, B. M., "Changes in Ground Water Quality from Pressure Injection of Waste Brine in West Virginia," Annu. Geol. Soc. Amer. & Ass. Soc. Mtg. (Washington, D. C., Nov. 1-3, 1971) Program, v. 3, No. 7, p 752, Oct. 1971 (Abstr. only).

Wilson, J. E. (See McCann, T. P.)

Wilson, J. L. (See Gelhar, L. W.)

Wilson, W. E., et al, Hydrologic Evaluation of Industrial-Waste Injection at Mulberry, Florida, 2nd Int. AAPG-USGS-IAHC Underground Waste Manage. & Artificial Recharge Symp. (New Orleans, Sept. 26-30, 1973) Preprints, Vol. 1, pp 552-564, 1973.

Winar, R. M., The Deepest Underground Sewer in Michigan, Amer. Petrol. Inst. Div. Prod. Pap. 826-37-C (Postprint), 8 pp, 1966.

Winar, R. M., "Underground Disposal of Waste Water," Ind. Water Eng., Vol. 4, No. 3, pp 21-24, 1967.

Winston, G. O. (See Puri, H. S.)

Witherspoon, P. A., and S. P. Neuman, "Hydrodynamics of Fluid Injection," AAPG & USGS Underground Waste Manage. & Environ. Implications Symp. (Houston, Dec. 5-9, 1971) Pap.; Abstr., Amer. Ass. Petrol. Geol. Bull., Vol. 55, No. 11, (Pt. 1), p 2092, Nov. 1971.

Witherspoon, P. A. (See Freeze, R. A.)

Witkowski, E. J., and J. F. Manneschildt, "Ground Disposal of Liquid Wastes at Oak Ridge National Laboratory," Ground Disposal of Radioactive Wastes Conference, 2nd, At. Energy Can. Ltd. and U. S. At. Energy Comm., Div. Tech. Inform. Rep., TID-7628, pp 506-512, 1962.

Witherspoon, P. A. (See Noorishad, J.)

Woodard, H. J. (See Garcia-Bengochea, J. I.)

Woodfork, L. D. (See Hidalgo, R. V.)

World Health Organization, "Pollution of Ground Water," J. Amer. Water Works Ass., Vol. 49, No. 4, pp 392-396, 1957.

Wright, C. C., "Water Quality Control for Subsurface Injection," Prod. Mon., Vol. 24, No. 12, pp 30-34, 1960.

Wright, C. C., and D. W. Davies, The Disposal of Oil Field Waste Water, Amer. Petrol. Inst. Drilling and Prod. Prac., 1966, pp 191-197, 1967.

Wright, J. (See Watkins, J. W.)

Wright, J. L., "Underground Waste Disposal," Ind. Water Eng., Vol. 6, No. 5, pp 24-27, 1969.

Wycoff, R. D., and H. G. Botset, "The Flow of Gas-Liquid Mixtures through Unconsolidated Sands," J. Appl. Phys., Vol. 7, No. 9, pp 325, 345, 1936.

Yeh, G-T. (See Li, W-H)

Young, A., and J. E. Galley, (Eds.), Fluids in Subsurface Environments--A Symposium, Amer. Ass. Petrol. Geol. Mem. 4, 414 pp, 1965.

Yudin, F. P., et al, Experience in Burial of Liquid Radioactive Wastes in Deep Geological Formations, U. S. Joint Publication Res. Serv. Publication 46535, 10 pp (Transl. from Atomnaya Energiya, Vol. 25, No. 2, pp 128-133), 1968.

Yudin, F. P. (See Mal'tsev, E. D.)

Yudin, F. P. (See Spitsyn, V. I.)

Zabelin, N. V., and Yu. I. Baranov, "Well Head Equipment Designed for Water Injection," Chem. Petrol. Eng., Nos. 3-4, pp 189-192, March-April, 1970 (Transl. of Khim. Neft. Mashinostr., No. 3, pp 1-3, March 1970, In Russian).

Zajic, J., "Geologogische Untersuchungen Ueber Moeglichkeiten Der Einlagerung Radioaktiver Abfaelle in Der CSSR (Geological Studies on the Possibility of Storing Radioactive Waste in Czechoslovakia)," Kernenergie (Berlin), Vol. 10, pp 312-318, 1967 (In German).

Zakharov, S. I., et al, "Nekotorye Rezul'taty Ekspluatatsii Opytno-Promysklennoy Ustanovki Po Udaleniyu Zhidkikh Radioaktivnykh Otkhodov V Glubinnye Formatsii Zemnoy Kory (SM-93/42) (Some Results of Operation of Pilot Scale Installation for Disposal of Liquid Radioactive Wastes in Deep Formations of Earth's Crust)," Disposal of Liquid Radioactive Wastes into the Ground--Int. At. Energy Agency and Europe. Nucl. Energy, Agency, 1967 Symp. Proc., Int. At. Energy Agency (STI/PUB/156), pp 577-590, 1967 (In Russian).

## SECTION XI

### APPENDIX B - PATENTS RELATED TO DEEP-WELL SYSTEMS

Colburn, W. A., (Atomic Storage Corp.), "Method of Storing Toxic Fluids and the Lime," U. S. 3,526, 279, c. Sept. 1, 1970, f. Dec. 8, 1966 (Appl. 600, 152), 1970.

Culpepper, G. O., Jr., asr., J. W. Kendall and J. W. Pitts, "Method and Apparatus for Cleaning Solids for Pollution Free Disposal," U. S. 3,736, 774, c. May 22, 1973, f. Jan. 29, 1971 (Appl. 110,826), 1973.

Dreher, K. D., R. D. Sydansk, asrs., (Marathon Oil Co.), "Inhibiting Salt Water Intrusion into Fresh Water Aquifers," U. S. 3,642,067, c. Feb. 15, 1972, f. July 23, 1970 (Appl. 57,827), 1972.

Eck, J. C., asr., "Method for the Removal of Suspended Matter in Waste Water Treatment," Can. 857,344, c. Dec. 1, 1970, f. Jan. 30, 1968 (Pr. U. S. June 15, 1967, Appl. 646,188), Abstr., Can. Pat. Office Rec., v. 98, No. 48, p 5058, Dec. 1, 1970.

Levens, F. T., "Well System," U. S. 3,768, 555, c. Oct. 30, 1973, f. Feb. 3, 1972 (Appl. 223,191), 1973.

Lienau, R., and W. Franz, asrs., "Apparatus with Tubing for Introducing Liquids into Suitable Geologic Formations," Ger. 1,300,088, c. July 31, 1969, f. Jan. 22, 1968, (Appl. 114,277), (Sued Chemie AG), Abstr., Auszuege Pat. (Ger.), v. 15, No. 31, 1 2364, July 31, 1969, (In German).

Means, J. O., "Method of Killing Organisms by Use of Radioactive Materials," U. S. 3,489,218, c. Jan. 13, 1970, f. Aug. 22, 1966, Dow Chemical Company.

Nebolsine, R., "Apparatus for Effecting the Filtration of Fluids for Example Water and Charging Underground Formations," Gr. Brit. 1,286,877, c. Aug. 23, 1972, f. Dec. 9, 1969 (Appl. 60, 150).

Oleen, D. C., asr., "Waterflood Process using Organic Phosphate Esters," U. S. 3,480,083, c. Nov. 25, 1969, f. Mar. 27, 1968 (Appl. 716-312), (Nalco Chemical Co.).

Parks, C. F., and E. Goddard, asrs., (Dow Chemical Co.), "Plugging of Permeable Materials," U. S. 3,583,167, c. June 8, 1971, f. May 8, 1969, (Appl. 823, 159).

Perkins, L. E., asr. (Halliburton Co.), "Filter Apparatus for Well Tool String," U. S. 3,515,210, c. June 2, 1970, f. June 20, 1968 (Appl. 738,459).

Poettmann, F. H., "Limiting Contamination of Waste Disposal Wells," U. S. 3,606,925, c. Sept. 21, 1971, f. Nov. 3, 1969 (Appl. 873,669), (Marathon Oil Co.).

Tosch, W. C., "Prevention of Salt Water Encroachment into Fresh Water Aquifers," U. S. 3,587,737, c. June 28, 1971, f. Nov. 5, 1969, Marathon Oil Company.

## SECTION XI

### APPENDIX C

#### WASTE CHARACTERIZATION PROFILES

The information contained in these profiles was obtained from various sources<sup>1,2,3,4</sup>. They contain detailed information, where available, about the chemicals which are contained in waste streams being injected into deep-well disposal systems. The chemicals are listed alphabetically in the Table of Contents for this Appendix.

The hazard ratings which have been used in these profiles were developed by Booz-Allen Research, Inc.<sup>1</sup> The key to the rating system is:

- 3 - Severely hazardous
- 2 - Slight to moderate hazard
- 1 - Minimal hazard
- U - Effects unknown



## CONTENTS

### APPENDIX C

#### WASTE CHARACTERIZATION PROFILES

<u>CHEMICAL</u>	<u>PAGE</u>
Acetaldehyde	304
Acetic acid	307
Acetone	304
Acetylene	311
Acrolein	319
Adipic Acid	322
Adiponitrile	324
Allyl Alcohol	325
Aluminum Oxide	331
Amides	336
Ammonia	337
Ammonium Chloride	339
Ammonium Chromate	343
Ammonium Dichromate	343
Ammonium Hydroxide	337
Ammonium Nitrate	339

<u>CHEMICAL</u>	<u>PAGE</u>
Ammonium Thiocyanate	350
Amyl Alcohol	325
Aniline	351
Arsenic Trioxide	353
Benzene	313
Benzoic Acid	356
Boron	358
Boron Chloride	359
Butane	311
Butanol	326
Butyl Disulfide	361
Butyl Mercaptan	362
Butyl Phenol	367
Butyric Acid	372
Cadmium	373
Cadmium Chloride	373
Calcium Chloride	377
Calcium Hydroxide	377
Calcium Oxide	378
Caprolactum	381

<u>CHEMICAL</u>	<u>PAGE</u>
Carbon Disulfide	382
Chlorine	385
Chloroform	388
Chlorinated Hydrocarbons	388
Chromic Acid	391
Copper Chloride	393
Cresol	367
Cumene	313
Cumene Hydroperoxide	395
Cyclohexane	312
Diazinon	396
Diethylstilbestrol	369
Dinitrobenzene	397
Dinitrotoluene	400
Dioxane	402
Diphenyl Amine	406
Epichlorohydrin	388
Ethane	312
Ethers	403
Ethyl Acetate	409

<u>CHEMICAL</u>	<u>PAGE</u>
Ethyl Disulfide	414
Ethylene	312
Ethylene Glycol	327
Ethyl Mercaptan	363
Ethyl Phenol	367
Ferric Chloride	415
Ferrous Chloride	416
Ferrous Sulfate	417
Formaldehyde	307
Formic Acid	419
Glycerin	328
Gold Chloride	421
Hexamethylenediamine	422
Hexanol	425
Hydrochloric Acid	426
Hydrogen Cyanide	428
Hydrogen Peroxide	431
Magnesium Oxide	331
Mercury	433
Mercuric Chloride	433

<u>CHEMICAL</u>	<u>PAGE</u>
Mercuric Diammonium Chloride	434
Mercuric Nitrate	433
Mercuric Sulfate	434
Methane	445
Methyl Acetate	409
Methyl Cellulose	446
Methyl Ethyl Ketone	304
Methyl Mercaptan	363
Methyl Methacrylate	410
Nitric Acid	447
Nitrobenzene	449
p-Nitrophenol	451
Phenol	368
Phosphorous Oxychloride	453
Phosphorous Pentachloride	453
Phosphorous Trichloride	454
Polyvinyl Alcohol	457
Potassium Chromate	343
Potassium Dichromate	344
Potassium Sulfate	378

<u>CHEMICAL</u>	<u>PAGE</u>
Propanol	458
Propargyl Alcohol	460
Propylene Oxide	403
Radium - 226	461
Silica	464
Silicon Tetrachloride	466
Silver Chloride	468
Sodium Carbonate	340
Sodium Chromate	344
Sodium Dichromate	345
Sodium Ferrocyanide	469
Sodium Fluoride	470
Sodium Formate	308
Sodium Hypochlorite	473
Sodium Monoxide	475
Sodium Nitrate	340
Sodium Nitrite	477
Sodium Sulfate	479
Sodium Sulfite	480
Stannic Oxide	482

<u>CHEMICAL</u>	<u>PAGE</u>
Sulfuric Acid	483
Terephthalic Acid	485
Thorium - 230	486
Toluene Diamine	487
p-Toluic Acid	489
Uranium	490
Urea	422
Valeric Acid	492
Vanadium Pentoxide	332
Vinyl Acetate	410
Xylene	313
Xylenol	369
Zinc Oxide	332

ACETALDEHYDE, ACETONE, METHYL ETHYL KETONE

ACETALDEHYDE

CHEMICAL FORMULA:  $\text{CH}_3\text{-}\overset{\text{O}}{\underset{\text{||}}{\text{C}}}\text{-H}$

GENERAL DESCRIPTION: Colorless, fuming, flammable liquid. IUC Name: Ethanal. Also called acetic aldehyde and aldehyde.

Molecular Wt.: 44.05 Melting Pt.: -123.5°C Boiling Pt.: 20.8°C

Density: (Liquid) 0.7827 g/cc @ 20°C (Gas) 1.52 g/l

Vapor Pressure:

Flash Pt.: -36° F (CC) Autoignition Temperature: 365° F

Explosive Limits in Air (Wt%): Lower 4.0% Upper 57%

Solubility:

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other:

DOT Classification: Flammable liquid, red label

Coast Guard Classification: Red label

ACETONE

CHEMICAL FORMULA:  $\text{CH}_3\text{-}\overset{\text{O}}{\underset{\text{||}}{\text{C}}}\text{-CH}_3$

GENERAL DESCRIPTION: Colorless, flammable liquid. IUC Name: 2-Propanone. Also called dimethyl ketone.

Molecular Wt.: 58.08 Melting Pt.: -94.6°C Boiling Pt.: 56.48°C

Density: (Liquid) 0.7972 g/cc @ 15° C (Gas) 2.00 g/l

Vapor Pressure: 400 mm @ 39.5°C

Flash Pt.: 0° F (CC) Autoignition Temperature: 1000° F

Explosive Limits in Air (Wt%): Lower 2.6% Upper 12.8%

Solubility:

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other: Miscible DMF, chloroform, ether

DOT Classification: Flammable liquid, red label

Coast Guard Classification: Red label MCA warning label

METHYL ETHYL KETONE

CHEMICAL FORMULA:  $\text{C}_2\text{H}_5\text{-}\overset{\text{O}}{\underset{\text{||}}{\text{C}}}\text{-CH}_3$

GENERAL DESCRIPTION: Colorless liquid, IUC Name: 2 Butanone. Also called MEK and ethyl methyl ketone.



Molecular Wt.: 72.10      Melting Pt.: -85.9°C      Boiling Pt.: 79.57°C  
 Density: (Liquid) 0.806 g/cc @ 20° C      (Gas) 2.41 g/l  
 Vapor Pressure: 71.2 mm @ 20° C  
 Flash Pt.: 22° F (TOC)      Autoignition Temperature: 960° F  
 Explosive Limits in Air (Wt%): Lower 1.8% Upper 10%  
 Solubility:  
     Hot Water: 19 g/100 ml @ 90°C      Cold Water: 35.3 g/100 ml @ 10°C  
     Ethanol: Infinitely soluble      Other: Ether  
 DOT Classification: Flammable, red label  
 Coast Guard Classification: Red label

MANUFACTURE: Catalytic oxidation or dehydration of the corresponding alcohol.

USE: Solvents and intermediates in the manufacture of chemicals and synthetic resins.

TOXICOLOGY. Narcotic and anesthetic. Highly irritating to the eyes and the mucous membranes of the respiratory tract. May affect the lungs. Ingestion causes nausea, vomiting, headaches and dizziness and has irritating effect.

The Threshold Limit Values (TLV) and Maximum Allowable Concentrations (MAC are:

<u>MATERIAL</u>	<u>TLV</u>		<u>MAC</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	<u>ppm</u>
Acetaldehyde	100	180	200
Acetone	1000	2400	1000
Methyl Ethyl Ketone	200	590	250

The Booz-Allen Ratings for these materials are:

<u>COMPOUND</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Acetaldehyde	2	2	2	3	3	2	2	1	2
Acetone	2	2	1	2	1	2	2	1	U
Methyl Ethyl Ketone	2	1	1	1	1	1	2	1	2

OTHER HAZARDS: Potential fire hazards.

HANDLING, STORAGE TRANSPORTATION: These materials should be handled in a well ventilated area and protective clothing and respirators are recommended. In case of accidental contact, all contaminated clothing should be removed and the skin washed thoroughly with soap and water.

DISPOSAL/REUSE: In some processes recycling is possible in others the materials are not recoverable. Many processes result in dilute waste streams which have a high chemical and biological oxygen demand. They can be treated on-site or discharged into municipal sewers.

Recommended Provisional Limits for these carbonyl compounds are as follows:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Acetaldehyde	1.0	1.8	0.01 TLV
Acetone	10	24	0.01 TLV
Methyl Ethyl Ketone	2	5.9	0.01 TLV

<u>Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
<u>Water and Soil</u>	<u>ppm (mg/l)</u>	
Acetaldehyde	9.0	Stokinger & Woodward Method
Acetone	60.0	Stokinger & Woodward Method
Methyl Ethyl Ketone	29.5	Stokinger & Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

Recycling is the best practice when possible.

<u>DISPOSAL METHODS</u>	<u>EVALUATION</u>
Treatment to reduce chemical and biological oxygen demand. Discharge into sewers.	Satisfactory
Incineration	Satisfactory

#### APPLICABILITY TO NATIONAL DISPOSAL SITES:

These aliphatic carbonyl compounds are not considered to be candidate waste stream constituents for National Disposal Site treatment.

ACETIC ACID, FORMALDEHYDE, SODIUM FORMATE

ACETIC ACID

CHEMICAL FORMULA:  $\text{CH}_3\text{-}\overset{\text{O}}{\underset{\text{||}}{\text{C}}}\text{-OH}$

GENERAL DESCRIPTION: Colorless corrosive liquid. IUC Name: Ethanoic Acid. Also called vinegar acid, methane carboxylic acid.

Molecular Wt.: 60.05 Melting Pt.: 16.7°C Boiling Pt.: 118°C

Density: (Liquid) 1.049 g/cc @ 25° C (Gas) 2.07 g/l

Vapor Pressure: 11.4 mm @ 20° C

Flash Pt.: 109° F (CC) Autoignition Temperature: 800° F

Explosive Limits in Air (Wt%): Lower 5.4% Upper 16.0% @ 212°F

Solubility:

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other: Miscible glycerol, carbon tetrachloride, very slightly soluble in carbon disulfide.

IATA Classification: Corrosive liquid, white label

Coast Guard Classification: Combustible liquid

MANUFACTURE: From acetaldehyde by catalytic oxidation in either batch, continuous batch or gas phase processes, by catalytic gas phase oxidation of butane or by the destructive distillation of wood.

USES: To make cellulose acetate (47%), vinyl acetate (25%), and other acetates (16%), miscellaneous uses (12%),

FORMALDEHYDE

CHEMICAL FORMULA:  $\text{HC}\overset{\text{O}}{\underset{\text{||}}{\text{H}}}$

GENERAL DESCRIPTION: Colorless gas. IUC Name: Methanal. Also called oxomethane.

Molecular Wt.: 30.03 Melting Pt.: -92°C Boiling Pt.: -19.5°C

Density: (Liquid) 0.815 g/cc @ 20° C (Gas) 1.067 g/l

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: 572° F

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: 55% Ethanol: Soluble

Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: By the catalytic oxidation of methanol at 300 to 600° C using a silver-copper or iron-molybdenum-vanadium catalyst. Gaseous formaldehyde

polymerizes readily and is sold only in aqueous solutions.

USES: To make resins (60%), pentaerythritol (9%), ethylene glycol (12%), hexamethylenetetraamine (5) and miscellaneous items (14%)

#### SODIUM FORMATE

CHEMICAL FORMULA:  $\text{H}-\overset{\text{O}}{\parallel}{\text{C}}-\text{ONa}$

GENERAL DESCRIPTION: Colorless crystalline solid. Neutral, pH 7, in aqueous solution.

Molecular Wt.: 68.02 Melting Pt.: 253°C Boiling Pt.: \_\_\_\_\_

Density: (Solid) 1.92 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Very soluble Cold Water: Very Sol. Ethanol: Slightly

Other: Soluble in glycerol

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: By the reaction of carbon monoxide with sodium hydroxide at 100 to 150 psi.

USES: Major use is to make formic acid which is used for textile dyeing and finishing, chemical synthesis and in the leather industry.

TOXICOLOGY: Acetic acid and its derivatives are irritants and corrosive on contact with tissue, particularly the eyes and upper respiratory tract. Ingestion causes a burning sensation pain in the stomach followed by nausea and vomiting. Contact with the skin causes reddening followed by wrinkling and peeling. Repeated contact can cause dermatitis.

Formaldehyde solution causes irritation. If swallowed, it causes violent vomiting and diarrhea which can lead to collapse and death. Repeated skin contact can cause dermatitis.

Sodium formate dust causes irritation of the eyes and the upper respiratory tract. Continued contact may cause ulcerations of the respiratory tract and skin lesions characterized by cracking and fissuring of the skin.

The Threshold Limit Values (TLV) and Maximum Allowable Concentrations (MAC) are:

<u>COMPOUND</u>	<u>ppm</u>	<u>TLV</u>	<u>MAC</u>
		<u>mg/M<sup>3</sup></u>	
Acetic Acid	10	25	-
Formaldehyde	5	6	5
Sodium Formate	5	9	-
		(as free acid)	

The Booz-Allen Ratings on these compounds are as follows:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Acetic Acid	2	2	2	1	3	2	2	1	U
Formaldehyde	3	3	3	2	3	U	2	1	2
Sodium Formate	3	3	3	U	2	U	1	1	1

OTHER HAZARDS: No others known.

HANDLING, STORAGE, TRANSPORTATION: Handle in a well ventilated area. Protective clothing and respirators are recommended. In case of contact, all contaminated clothing should be removed instantly and the skin washed thoroughly with soap and water. Showers and eye fountains must be available for serious accidents. In case of eye contact wash with large amounts of water.

Store in a cool, dry, well ventilated area, away from fire hazards.

DISPOSAL/REUSE: The uses of these materials are such that there is a high degree of utilization due to recycling of unreacted materials. The main source of waste being scrubbing to remove trace amounts.

Recommended Provisional Limits for these compounds are:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Acetic Acid	0.10	0.25	0.01 TLV
Formaldehyde	0.05	0.06	0.01 TLV
Sodium Formate	-	0.09	0.01 TLV
		(as free acid)	

<u>Contaminant in</u> <u>Water and Soil</u>	<u>Provisional Limit</u> <u>ppm or mg/l</u>	<u>Basis for Recommendation</u>
Acetic Acid	1.25	Stokinger and Woodward Method
Formaldehyde	0.15	Stokinger and Woodward Method
Sodium Formate	0.45	Stokinger and Woodward Method
	(as free acid)	

EVALUATION OF WASTE MANAGEMENT:

<u>DISPOSAL METHODS</u>	<u>EVALUATION</u>
Recycling	Best choice when possible
Treatment of waste water to reduce biological and chemical oxygen demand. On site or at municipal waste treatment systems.	Satisfactory
Incineration	Satisfactory
Process modifications in production have substantially reduced the amounts of wastes produced.	

APPLICABILITY TO NATIONAL DISPOSAL SITES: Acetic acid, formaldehyde and sodium formate can be adequately treated by common industrial and municipal techniques. They are not considered to be candidate waste stream constituents for National Disposal Sites.

ALIPHATIC AND AROMATIC HYDROCARBONS

ALIPHATIC

ACETYLENE, BUTANE, CYCLOHEXANE, ETHANE, ETHYLENE

AROMATIC

BENZENE, CUMENE, XYLENE

ACETYLENE

CHEMICAL FORMULA:  $\text{CH} \equiv \text{CH}$

GENERAL DESCRIPTION: Colorless, flammable Gas, garlic like odor, IUC Name: Ethyne. Sublimes at  $-84.0^{\circ}\text{C}$  Forms explosive compounds with copper and silver.

Molecular Wt.: 26.04 Melting Pt.:  $-81.6^{\circ}\text{C}$  Boiling Pt.:  $-84.0^{\circ}\text{C}$  sublimes

Density: (Liquid) \_\_\_\_\_ (Gas) 1.173 g/l @  $0^{\circ}\text{C}$

Vapor Pressure: 40 atm @  $16.8^{\circ}\text{C}$

Flash Pt.:  $0^{\circ}\text{F}$  (CC) Autoignition Temperature:  $571^{\circ}\text{F}$

Explosive Limits in Air (Wt%): Lower 2.5% Upper 80%

Solubility:

Hot Water: - Cold Water: Slightly Ethanol: -

Other: Ether, benzene, acetone

DOT Classification: Flammable gas, red gas label

Coast Guard Classification: Red gas label

BUTANE

CHEMICAL FORMULA:  $\text{CH}_3(\text{CH}_2)_2\text{CH}_3$

GENERAL DESCRIPTION: Colorless, flammable gas. IUC Name: n-Butane.

Molecular Wt.: 58.1 Melting Pt.:  $-138.6^{\circ}\text{C}$  Boiling Pt.:  $-0.5^{\circ}\text{C}$

Density: (Liquid) 0.599 g/cc @  $0^{\circ}\text{C}$  (Gas) 2.046 g/l

Vapor Pressure: 2 atm @  $18.8^{\circ}\text{C}$

Flash Pt.:  $-76^{\circ}\text{F}$  (CC) Autoignition Temperature:  $761^{\circ}\text{F}$

Explosive Limits in Air (Wt%): Lower 1.9% Upper 8.5%

Solubility:


Hot Water: Insoluble Cold Water: Insoluble Ethanol: Soluble

Other: Ether, chloroform.

DOT Classification: Flammable, red gas label

Coast Guard Classification: Red gas label

CYCLOHEXANE

CHEMICAL FORMULA:  $C_6H_{12}$ , 

GENERAL DESCRIPTION: Colorless, flammable gas. Also called hexamethylene.  
Molecular Wt.: 84.16 Melting Pt.: 6.5°C Boiling Pt.: 80.7°C  
Density: (Liquid) -0.7791 g/cc @ 20° C (Gas) 2.90 g/l  
Vapor Pressure: 100 mm @ 60.8°C  
Flash Pt.: -4° F Autoignition Temperature: 500° F  
Explosive Limits in Air (Wt%): Lower 1.3% Upper 8.4%  
Solubility:  
Hot Water: Insoluble Cold Water: Insoluble Ethanol: Soluble  
Other: Ether  
DOT Classification: Flammable red label  
Coast Guard Classification: Red label

ETHANE

CHEMICAL FORMULA:  $CH_3CH_3$

GENERAL DESCRIPTION: Colorless, flammable gas. Also called dimethyl  
Molecular Wt.: 30.07 Melting Pt.: -172°C Boiling Pt.: -88.6°C  
Density: (Liquid) 0.561 g/cc @ -100°C (Gas) 1.04 g/l  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.: \_\_\_\_\_ Autoignition Temperature: 959°F  
Explosive Limits in Air (Wt%): Lower 3.0% Upper 12.5%  
Solubility:  
Hot Water: Insoluble Cold Water: Insoluble Ethanol: Slightly  
Other: \_\_\_\_\_  
DOT Classification: Flammable, red label  
Coast Guard Classification: Red gas label

ETHYLENE

CHEMICAL FORMULA:  $CH_2 = CH_2$

GENERAL DESCRIPTION: Colorless, flammable gas. IUC Name: Ethene. Also called etherin.  
Molecular Wt.: 28.05 Melting Pt.: -169.4°C Boiling Pt.: -103.9°C  
Density: (Liquid) 0.566 g/cc @ -102°C (Gas) 1.26 g/l  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.: \_\_\_\_\_ Autoignition Temperature: 842°F  
Explosive Limits in Air (Wt%): Lower 3.1% Upper 32%



Solubility:

Hot Water: Insoluble Cold Water: Insoluble Ethanol: Slightly  
Other: Ether  
DOT Classification: Flammable, red label  
Coast Guard Classification: Red label


BENZENE

CHEMICAL FORMULA:  $C_6H_6$ , 

GENERAL DESCRIPTION: Flammable liquid. Also called benzol and coal naphtha.  
Molecular Wt.: 78.11 Melting Pt.: 5.51°C Boiling Pt.: 80.093°C  
Density: (Liquid) 0.8794 g/cc @ 20° C (Gas) 2.77 g/l  
Vapor Pressure: 100 mm @ 26.1°C  
Flash Pt.: 12°F (CC) Autoignition Temperature: 1044° F  
Explosive Limits in Air (Wt%): Lower 1.3% Upper 7.1%  
Solubility:

Hot Water: Insoluble Cold Water: Insoluble Ethanol: Miscible  
Other: Chloroform, ether, acetone.  
DOT Classification: Flammable, red label  
Coast Guard Classification: Red label

CUMENE

CHEMICAL FORMULA:  $C_6H_5CH(CH_3)_2$ , 

GENERAL DESCRIPTION: Liquid. IUC Name: Isopropylbenzene. Also called cumol, 2-phenylpropane.  
Molecular Wt.: 120.19 Melting Pt.: -96.0°C Boiling Pt.: 152° C  
Density: (Liquid) 0.864 g/cc @ 20° C (Gas) 4.1 g/l  
Vapor Pressure: 10 mm @ 38.3° C  
Flash Pt.: 111° F Autoignition Temperature: 795° F  
Explosive Limits in Air (Wt%): Lower 0.9% Upper 6.5%  
Solubility:


Hot Water: Insoluble Cold Water: Insoluble Ethanol: Soluble  
Other: \_\_\_\_\_  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_

XYLENE

Three isomers exist. meta-xylene, ortho-xylene and para-xylene

m - XYLENE

CHEMICAL FORMULA:  $C_6H_4(CH_3)_2$ ,



GENERAL DESCRIPTION: Colorless flammable liquid. IUC Name: 1,3 - dimethyl benzene. Also called m-xyltol.

Molecular Wt.: 106.2 Melting Pt.: -47.9°C Boiling Pt.: 139°C

Density: (Liquid) 0.864 g/cc @ 20° C (Gas) 3.66 g/l

Vapor Pressure: 10 mm @ 28.3°C

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: 982° F

Explosive Limits in Air (Wt%): Lower 1.1% Upper 7.0%

Solubility:

Hot Water: Insoluble Cold Water: Insoluble Ethanol: Miscible


Other: Ether

DOT Classification: Flammable, red label

Coast Guard Classification: Red label

o-XYLENE

CHEMICAL FORMULA:  $C_6H_4(CH_3)_2$ ,



GENERAL DESCRIPTION: Colorless flammable liquid. IUC Name: 1,2 -dimethyl benzene. Also called o-Xyltol.

Molecular Wt.: 106.2 Melting Pt.: -29.5°C Boiling Pt.: 144.4°C

Density: (Liquid) 0.880 g/cc @ 32.1°C (Gas) 3.66 g/l

Vapor Pressure: 10 mm @ 32.1°C

Flash Pt.: 90°F Autoignition Temperature: 867° F

Explosive Limits in Air (Wt%): Lower 1.0% Upper 6.0%

Solubility:

Hot Water: Insoluble Cold Water: Insoluble Ethanol: Miscible


Other: Ether

DOT Classification: Flammable, red label

Coast Guard Classification: Red label

p-XYLENE

CHEMICAL FORMULA:  $C_6H_4(CH_3)_2$ ,



GENERAL DESCRIPTION: Colorless flammable liquid. IUC Name: 1,4 dimethyl bezene. Also called p-xyltol.

Molecular Wt.: 106.2      Melting Pt.: 13.2°C      Boiling Pt.: 138.3°C  
 Density: (Liquid) 0.86 gm/cc @ 20° C      (Gas) 3.66 g/l  
 Vapor Pressure: 10 mm @ 27.3°C  
 Flash Pt.: 103° F ( 0C)      Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower 1.1%      Upper 7.0%  
 Solubility:  
     Hot Water: Insoluble      Cold Water: Insoluble      Ethanol: Soluble  
     Other: Ether  
 DOT Classification: Flammable, red label  
 Coast Guard Classification: Red label

MANUFACTURE: Saturated hydrocarbons and small amounts of benzene and unsaturated aliphatics are isolated directly from petroleum by distillation. The alkenes are usually made from the corresponding saturated material by dehydration at high temperatures over chromia-alumina catalysts.

USES: Saturated aliphatic and aromatic hydrocarbons are used as fuels, solvents reaction media and in formulations of many industrial and consumer items. Alkenes and alkene dimers and trimers are used either to produce polymers or to make other monomers.

TOXICOLOGY: Aliphatics are simple asphyxiant gases having no toxic effect, but acting to exclude oxygen from the lungs. Lower boiling hydrocarbons can cause frostbite when spilled on the skin. Repeated contact with the skin can cause irritation.

Aromatics are poisonous through inhalation, ingestion or skin absorption. Strongly irritating to skin, producing erythema, burning, and in severe cases edema. High vapor concentration is similar to other anesthetic gases. Chronic exposure produces toxic action on blood forming tissue.

The Threshold Limit Values (TLV) and Maximum Allowable Concentrations (MAC) that have been established are:

<u>Aliphatic Hydrocarbons</u>	<u>TLV</u>		<u>MAC</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	<u>ppm</u>
Acetylene	-	-	-
Butane	500	1200	-
Cyclohexane	300	1050	400
Ethane	-	-	-
Ethylene	-	-	-
<u>Aromatic Hydrocarbons</u>			
Benzene	25	80	25
Cumene	50	245	100
Xylene	100	435	200

The Booz-Allen Ratings for these hydrocarbons are:

<u>Aliphatic Hydrocarbons</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Acetylene	1	1	1	1	2	1	2	1	2
Butane	2	1	1	1	1	U	2	1	2
Cyclohexane	1	1	1	1	3	U	2	1	2
Ethane	2	1	1	1	U	U	2	1	1
Ethylene	2	1	1	2	3	U	2	1	2

<u>Aromatic Hydrocarbons</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Benzene	2	2	2	1	3	U	2	1	2
Cumene	3	3	2	1	3	U	2	1	2
Xylene	1	1	1	1	3	1	2	1	1

OTHER HAZARDS: All are Flammable and explosive. The acetylene is especially so, and dry salts of acetylene are very prone to spontaneous detonation.

HANDLING, STORAGE, TRANSPORTATION: Care must be exercised in handling, storing, and transporting to prevent container leakage. The pure materials have very little odor, adding to the danger. Keep away from fire hazards and in a cool well-ventilated area. Areas where these materials are used should be equipped with spark proof electrical equipment. Protect from heat and sudden temperature rise.

DISPOSAL/REUSE: Most unused or unreacted material is recycled. Main sources of waste are dilute aqueous solutions resulting from washing procedures. These wastes are discharged into the sewer after skimming and primary treatment to reduce the hydrocarbon content.

Some waste is discharged directly into rivers and streams. Sludges are landfilled. Some liquid waste is incinerated.

Some waste from small users is picked up by scavengers who dispose of it by reclaiming, landfill, ocean burial, open burning or any other method that seems appropriate.

For disposal of the compounds into the environment the following Provisional Limits are recommended:

<u>Constituent in Air</u>	<u>Provisional Limit</u>		<u>Basis for</u>
<u>Aliphatic Hydrocarbons</u>	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	<u>Recommendation</u>
Acetylene	-	22	Based on Similar Compounds
Butane	5	12	0.01 TLV
Cyclohexane	3	10.5	0.01 TLV
Ethane	-	9	Based on Similar Compounds
Ethylene	-	22	Based on Similar Compounds
<u>Aromatic Hydrocarbons</u>			
Benzene	0.25	0.80	0.01 TLV
Cumene	0.5	2.45	0.01 TLV
Xylene	1.0	4.35	0.01 TLV
<u>Constituent in Water and Soil</u>	<u>Provisional Limits</u>		<u>Basis for</u>
	<u>ppm (mg/l)</u>		<u>Recommendation</u>
<u>Aliphatic Hydrocarbons</u>			
Acetylene	110		Based on Similar Compounds
Butane	60		Stokinger & Woodward Method
Cyclohexane	52.5		Stokinger & Woodward Method
Ethane	45		Based on Similar Compounds
Ethylene	110		Based on Similar Compounds
<u>Aromatic Hydrocarbons</u>			
Benzene	3.5		Stokinger & Woodward Method
Cumene	12.25		Stokinger & Woodward Method
Xylene	4.35		Stokinger & Woodward Method

EVALUATION OF WASTE MANAGEMENT:

<u>DISPOSAL METHODS</u>	<u>EVALUATION</u>
Recycling	Best Choice when possible
Discharge of dilute aqueous streams into the municipal or industrial sewer after preliminary treatment	Satisfactory
Incineration	Satisfactory
Landfill of residue, sludges and hydrocarbon mixtures obtained during manufacture and use	Not satisfactory due to long term threat to underground water supplies
Uncontrolled disposal by local scavengers	Potentially good due to concentrating of wastes at few sites

APPLICABLE TO NATIONAL DISPOSAL SITES: All of these materials can be handled easily and safely locally by common industrial techniques, therefore, they are not considered candidates for National Disposal Sites.

# ACROLEIN

CHEMICAL FORMULA:  $\text{CH}_2=\overset{\text{O}}{\underset{\text{||}}{\text{C}}}\text{HCH}$

GENERAL DESCRIPTION: Colorless, volatile unstable, flammable liquid. IUC Name: 2-propenal. Also called acrylaldehyde, acrylic aldehyde, allyl aldehyde.

Molecular Wt.: 56.06      Melting Pt.: -87.7°C      Boiling Pt.: 52.5°C  
Density: (Liquid) 0.841 g/cc @ 20°C      (Gas) 1.44 g/l  
Vapor Pressure: 760 mm @ 52.5°C; 215 mm @ 20°C; 678.5 mm @ 50°C  
Flash Pt.:      Autoignition Temperature: 532°F  
Explosive Limits in Air (Wt%): Lower 2.8%      Upper 31%  
Solubility:  
    Hot Water: 24.0% (wt)      Cold Water: 20.8% (wt) @ 20°C  
    Other: Soluble in ether      Ethanol: Soluble  
Coast Guard Classification: Flammable  
DOT Classification: 28, 29

MANUFACTURE: By the direct oxidation of propylene or by the cross-condensation of acetaldehyde. Large scale commercial facilities for the manufacture of acrolein are operated by Union Carbide and Shell Chemical.

USES: In the manufacture of pharmaceuticals, amino acids, odorants, dye-stuffs, textile finishing, resins, paper chemicals, polyesters, and polyurethanes.

TOXICOLOGY: Acrolein is highly toxic and is poisonous by ingestion, inhalation, and absorption through the skin. It is intensely irritating to the eyes, respiratory tract and lungs. The liquid can cause severe burns to the eyes and skin. The Threshold Limit Value quoted in the current Occupational Safety and Health Standards is 0.1 ppm. The TRW assessment of the toxicological information recommends a limit in air of 0.001 ppm (0.0025 mg/M<sup>3</sup>) for 24 hour exposure.

The Booz-Allen Ratings for Acrolein are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	2	2	3	2	2	U	2

OTHER HAZARDS: Acrolein monomer is a dangerous substance due to its flammability and high reactivity. In addition to it being explosive between 2.8 and 31 percent by volume in air it may be subject to explosive polymerization if inadequately inhibited.

HANDLING, STORAGE, TRANSPORTATION: Acrolein requires special methods of handling. All processing equipment and storage facilities should be located

outdoors to provide adequate ventilation. All electrical equipment, including flashlights, used around acrolein should be vapor tight or explosion proof. All equipment should be properly grounded. Static electricity should be guarded against. Copper metal or its alloys is recommended in distillation systems because of the inhibiting effect afforded by these metals, although iron and steel are satisfactory construction materials for handling inhibited acrolein. Acrolein should be stored under an oxygen-free atmosphere as an acid to prevent explosive polymerization. Large quantities should be stored in non-draining, diked areas. Acrolein is shipped under an oxygen-free atmosphere and inhibited with hydroquinone.

DISPOSAL/REUSE: The products formed in the neutralization of dilute streams must be considered when disposing of acrolein in aqueous waste streams. The reaction with the carbon-carbon double bond is catalyzed by base.

Current techniques use neutralization of acrolein with base and lagooning. Waste acrolein streams are too dilute for incineration, therefore, secondary treatment or deep well disposal is presently used.

In releasing acrolein to the environment the following Recommended Provisional Limits should be considered:

<u>Acrolein as a Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.001 ppm (0.0025 mg/M <sup>3</sup> )	0.01 TLV
Water and Soil	0.01 ppm	Stokinger and Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES: Acrolein appears in waste streams in low concentrations and only rarely as concentrated waste.

#### METHODS OF DISPOSAL

#### EVALUATION

Return to a manufacturer for reprocessing when possible

Best Choice

Incineration in two stages to convert acrolein to CO<sub>2</sub> and water.

Satisfactory

#### DILUTE AQUEOUS WASTE

Secondary treatment

Insufficient information to evaluate

Deep well disposal

Inadequate due to lack of assurance that a deep-well will operate satisfactorily over a long period; little research into long-term effectiveness and deep-well injection in real-



METHODS OF DISPOSAL

EVALUATION

ly long term storage of hazardous materials, as opposed to conversion to a non-hazardous material.

Combustion after evaporative concentration.

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Due to its high chemical reactivity, toxicity, flammability and difficulties in processing it is anticipated that acrolein waste will require treatment at National Disposal Sites.

## ADIPIC ACID

CHEMICAL FORMULA:  $\text{HO}_2\text{C}(\text{CH}_2)_4\text{CO}_2\text{H}$

GENERAL DESCRIPTION: Colorless crystalline solid. IUC Name: 1,6 - hexanedioic acid. Also called 1,4 - butane dicarboxylic acid.

Molecular Wt.: 146.14 Melting Pt.: 152°C Boiling Pt.: 337.5°C

Density: (Solid) 1.360 g/cc @ 25°C (Gas) 5.04 g/l

Vapor Pressure: 1 mm @ 159.5°C

Flash Pt.: 385°F (CC) Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Soluble Cold Water: Soluble Ethanol: Soluble

Other: Methanol, acetone

MANUFACTURE: Catalytic oxidation of cyclohexanol

USES: In the production of nylon 6/6 (88%), esters for plasticizers and synthetic lubricants and in urethans.

TOXICITY: Very low.

The Booz-Allen Ratings for adipic acid are as follows:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
U	U	U	1	2	U	1	1	1

OTHER HAZARDS: No hazards.

HANDLING STORAGE AND TRANSPORTATION: No particular hazards

DISPOSAL/REUSE: Any unused material is recycled. Dilute waste streams can be treated on site or discharged into the municipal sewer after pH adjustment.

Recommended Provisional Limits for adipic acid are:

<u>Adipic Acid as</u> <u>Contaminant in</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Air	-	0.25	Based on Similar Compounds
Soil and water	1.25	-	Based on Similar Compounds

EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>Disposal Methods</u>	<u>Evaluation</u>
Recycling	Best choice when possible
Treatment of waste to reduce chemical and biological oxygen demand, and discharge into municipal sewers	Satisfactory
Incineration	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Adipic acid can best be handled by municipal or industrial disposal methods and is not considered a candidate waste stream constituent for National Disposal Sites.

## ADIPONITRILE

CHEMICAL FORMULA:  $\text{CN}(\text{CH}_2)_4\text{CN}$

GENERAL DESCRIPTION: Water-white liquid, practically odorless. Also called 1,4 dicyanobutane and tetramethylene cyanide.

Molecular Wt.: 108.14 Melting Pt.: 23°C Boiling Pt.: 295°C

Density: (Liquid) 0.965 g/cc @ 20°C (Gas)

Vapor Pressure:

Flash Pt.: 199.4°F Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Cold Water: Ethanol:

Other:

DOT Classification:

Coast Guard Classification:

TOXICOLOGY: Toxic since the nitrile group will behave like a cyanide when ingested or absorbed into the body by contact. It produces disturbances of the respiration and circulation, irritation of the stomach and intestines and loss of weight.

OTHER HAZARDS: Combustion products may contain hydrocyanic acid. It is a moderate fire hazard when exposed to heat or flames. When heated to decomposition, it emits highly toxic fumes. It can react with oxidizing materials.

HANDLING, STORAGE, TRANSPORTATION: Handle with care in a well ventilated area. Store away from heat, open flames and oxidizing materials. Wear protective equipment to prevent inhalation, ingestion or skin contact.

## ALCOHOLS

(Allyl Alcohol, Amyl Alcohol, Ethylene Glycol, Butanols, Glycerin)

### ALLYL ALCOHOL

CHEMICAL FORMULA:  $\text{CH}_2=\text{CH}-\text{CH}_2\text{OH}$

GENERAL DESCRIPTION: Colorless liquid. Pungent odor. Polymerizes slowly on storage to a thick syrup. IUC Name: 2-Propen-1-ol

Molecular Wt.: 58.08 Melting Pt.:  $-129^\circ\text{C}$  Boiling Pt.:  $96-97^\circ\text{C}$

Density: (Liquid) 0.8540 gm/ml @  $20^\circ\text{C}$  (Gas) 2.00 g/l

Vapor Pressure: 10 mm @  $10.5^\circ\text{C}$

Flash Pt.:  $70^\circ\text{F}$  (O.C.) Autoignition Temperature:  $713^\circ\text{F}$

Explosive Limits in Air (Wt%): Lower 2.5% Upper 18%

Solubility:

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other: Miscible chloroform, ether, petroleum ether

DOT Classification:

Coast Guard Classification:

### AMYL ALCOHOL

Two Isomers are Listed Here

#### n-Amyl Alcohol

CHEMICAL FORMULA:  $\text{CH}_3-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{OH}$

GENERAL DESCRIPTION: Colorless liquid. IUC Name: 1-Pentanol. Also called pentyl alcohol, n-butyl carbinol

Molecular Wt.: 88.15 Melting Pt.:  $-79^\circ\text{C}$  Boiling Pt.:  $138.1^\circ\text{C}$

Density: (Liquid) 0.824 g/cc @  $20^\circ\text{C}$  (Gas) 3.04 g/l

Vapor Pressure: 1 mm @  $13.6^\circ\text{C}$  10 mm @  $44.9^\circ\text{C}$

Flash Pt.:  $100^\circ\text{F}$  (C.C.) Autoignition Temperature:  $572^\circ\text{F}$

Explosive Limits in Air (Wt%): Lower 1.2% Upper 10% @  $100^\circ\text{C}$

Solubility:

Hot Water: Cold Water: 2.7 g/100 ml @  $22^\circ\text{C}$  Ethanol: Miscible

Other:

DOT Classification:

Coast Guard Classification: Combustible liquid

#### sec - Amyl Alcohol

CHEMICAL FORMULA:  $\text{CH}_3-\overset{\text{OH}}{\text{CH}}-\text{CH}_2-\text{CH}_2-\text{CH}_3$

GENERAL DESCRIPTION: Colorless liquid. IUC Name: 2: Pentanol. Also called methyl propyl carbinol  
Molecular Wt.: 88.15 Melting Pt.: -50°C Boiling Pt.: 119.3°C  
Density: (Liquid) 0.811 g/cc @ 20° C (Gas) 3.04 g/l  
Vapor Pressure:  
Flash Pt.: 105° F (O.C.) Autoignition Temperature: 650 to 725°F  
Explosive Limits in Air (Wt%): Lower -- Upper 9.0%  
Solubility:  
Cold Water: 16.6 g/100 ml @ 20° C Hot Water: Ethanol: Miscible  
Other: Miscible in ether.  
DOT Classification:  
Coast Guard Classification:

BUTANOL  
(There are three isomers)

1- BUTANOL

CHEMICAL FORMULA:  $\text{CH}_3\text{-CH}_2\text{-CH}_2\text{-CH}_2\text{OH}$

GENERAL DESCRIPTION: Colorless flammable liquid. Also called n- butyl alcohol, propyl carbinol.  
Molecular Wt.: 74.12 Melting Pt.: -90°C Boiling Pt.: 117-118°C  
Density: (Liquid) 0.810 g/cc @ 20°C (Gas) 2.55 g/l  
Vapor Pressure: 5.5 mm @ 20°C  
Flash Pt.: 36-38°C Autoignition Temperature: 689°F  
Explosive Limits in Air (Wt%): Lower 1.4% Upper 11.2%  
Solubility:  
Cold Water: 9.1 ml/100 ml @ 25°C Hot Water: Ethanol: Miscible  
Other: Miscible in ether and many other organic solvents  
DOT Classification:  
Coast Guard Classification:  
MCA warning label

2- BUTANOL

CHEMICAL FORMULA:  $\text{CH}_3\overset{\text{OH}}{\text{CH}}\text{CH}_2\text{CH}_3$

GENERAL DESCRIPTION: Colorless flammable liquid. Also called sec-butyl alcohol, methyl alkyl carbinol.  
Molecular Wt.: 74.12 Melting Pt.: -89°C Boiling Pt.: 99.5°C  
Density: (Liquid) 0.808 g/cc @ 20°C (Gas) 2.55 g/l  
Vapor Pressure: 10 mm @ 20°C  
Flash Pt.: 75° F (C.C.) Autoignition Temperature: 763°F  
Explosive Limits in Air (Wt%): Lower 1.7% @100°C Upper 9.8% @100° C

Solubility:


Hot Water: \_\_\_\_\_ Cold Water: 10 wt% Ethanol: miscible  
Other: Miscible in ether and other organic solvents

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MCA warning label

tert-BUTANOL



GENERAL DESCRIPTION: Colorless liquid or crystalline solid. IUC Name: 2-Methyl-2-propanol

Molecular Wt.: 74.12 Melting Pt.: 25.3°C Boiling Pt.: 82.41°C

Density: (Liquid) 0.7887 g/cc @ 20°C (Gas) 2.55 g/l

Vapor Pressure: 40 mm @ 24.5°C

Flash Pt.: 52°F (C.C.) Autoignition Temperature: 892°F

Explosive Limits in Air (Wt%): Lower 2.4% Upper 8.0%

Solubility:

Hot Water: Soluble Cold Water: Soluble Ethanol: Miscible


Other: Miscible in ether

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MCA warning label

ETHYLENE GLYCOL



GENERAL DESCRIPTION: Colorless very hygroscopic liquid. IUC Name: 1,2-ethanediol. Also called glycol and glycol alcohol

Molecular Wt.: 102.1 Freezing Pt.: -13°C Boiling Pt.: 197.5°C

Density: (Liquid) 1.113 g/cc @ 25°C (Gas) 214 g/l

Vapor Pressure: 0.05 mm @ 20°C

Flash Pt.: 232° F (CC) Autoignition Temperature: 775° F

Explosive Limits in Air (Wt%): Lower 3.2% Upper \_\_\_\_\_

Solubility:

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other: Soluble in lower alcohols, acetic acid, acetone, pyridine.

Insoluble in benzene and its homologues, chlorinated hydrocarbons.

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

## GLYCERIN

CHEMICAL FORMULA:  $\begin{array}{c} \text{OH} \quad \text{OH} \quad \text{OH} \\ | \quad | \quad | \\ \text{CH}_2 - \text{CH} - \text{CH}_2 \end{array}$

GENERAL DESCRIPTION: Colorless liquid or crystalline solid. IUC Name: 1,2,3-Propanetriol. Also called glycerol. Absorbs water,  $\text{H}_2\text{S}$ , HCN and  $\text{SO}_2$  readily.

Molecular Wt.: 92.09      Melting Pt.: 17.9°C      Boiling Pt.: 290°C  
Density: (Liquid) 1.260 g/cc @ 20°C      (Gas) 3.17 g/l  
Vapor Pressure: 0.0025 mm @ 50°C  
Flash Pt.: 320° F      Autoignition Temperature: 739°F  
Explosive Limits in Air (Wt%): Lower      Upper

Solubility:

Hot Water: Miscible      Cold Water: Miscible      Ethanol: Miscible  
Other: Soluble in ethyl acetate, ether; insoluble in benzene, chloroform, petroleum solvents.

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Hydration of alkenes, synthesized from propylene and triglycerides, oxo process or hydroformulation of the alkenes.

USES: As solvents and chemical intermediates. Glycerin and glycols are used as anti-freeze and in cosmetics.

TOXICOLOGY: All are relatively non toxic except allyl alcohol. All are irritants to mucous membranes, particularly the eyes, nose and respiratory passages. Ingestion causes headache, nausea, vomiting and delirium. Repeated exposure can cause damage to the kidneys, liver and blood vessels. Allyl alcohol is a strong irritant and damage to the kidneys and liver occurs at much lower concentration.

The Threshold Limit Value (TLV) and Maximum Allowable Concentrations (MAC) are as follows:

<u>Compound</u>	<u>TLV</u>		<u>MAC</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	<u>ppm</u>
Allyl Alcohol	2	5	2
Amyl Alcohol	-	-	-
Butanols	100	300	100
Ethylene Glycol	-	-	-
Glycerin	400	980	400



The Booz-Allen Ratings are as follows:

<u>COMPOUND</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Allyl Alcohol	2	2	2	3	3	U	2	1	2
Amyl Alcohol	2	3	2	3	2	U	2	1	2
Butanols	1	2	1	1	3	U	2	1	2
Ethylene Glycol	1	2	1	1	1	U	2	1	1
Glycerin	1	1	1	1	1	U	1	1	1

OTHER HAZARDS: All are flammable to some degree.

HANDLING, STORAGE, TRANSPORTATION: Handle in a well ventilated area. Protective clothing and respirators are recommended. In case of contact all contaminated clothing should be removed and the skin washed thoroughly.

DISPOSAL/REUSE: In some processes, materials are recycled as much as possible. Many processes result in dilute waste streams. They can be treated on site or discharged into the municipal sewer.

For release into the environment, the following Provisional Limits are listed below:

<u>Contaminant in Air</u>	<u>Provisional Limits</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Allyl Alcohol	0.02	0.05	0.01 TLV
Amyl Alcohol	-	3.0	Based on similar compounds
Butanols	1.0	3.0	0.01 TLV
Ethylene Glycol	-	2.0	Based on similar compounds
Glycerin	-	2.0	Based on similar compounds

<u>Contaminant in Water and Soil</u>	<u>Provisional Limits</u> <u>ppm</u>	<u>Basis for Recommendation</u>
Allyl Alcohol	0.23	Stokinger & Woodward Method
Amyl Alcohol	15	Based on Similar Compounds
Butanols	15	Stokinger & Woodward Method
Ethylene Glycol	1.0	Based on Similar Compounds
Glycerin	1.0	Based on Similar Compounds

EVALUATION OF WASTE MANAGEMENT:

#### DISPOSAL METHODS

Recycling

#### EVALUATION

Best choice when possible

Treatment of waste water to reduce chemical and biological oxygen demand. Discharge to sewer

Satisfactory

Incineration

Satisfactory

#### APPLICABILITY TO NATIONAL DISPOSAL SITES:

These compounds can be handled by municipal and industrial disposal methods. They are not considered waste stream candidates for National Disposal Sites.

ALUMINUM OXIDE, MAGNESIUM OXIDE, VANADIUM PENTOXIDE, ZINC OXIDE

ALUMINUM OXIDE

CHEMICAL FORMULA:  $\text{Al}_2\text{O}_3$

GENERAL DESCRIPTION: White crystalline powder. Also called alumina.

Molecular Wt.: 101.96 Melting Pt.: 2045°C Boiling Pt.: 2980°C

Density: (Solid) 3.965 g/cc @ 25°C (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Insoluble Cold Water: Insoluble

Ethanol: Insoluble Other:

DOT Classification:

Coast Guard Classification:

MANUFACTURE: From aluminum hydroxide such as bauxite. The Bayer process is one method used.

USES: As an absorbent and desiccant for drying gases and liquids, as a catalyst for various chemical reactions, as abrasives, in the manufacture of refractories, in absorption chromatography, as filler for paints and varnishes, in the manufacture of alloys, ceramic materials, electrical insulators and resistors, dental cements, glass, artificial gems and in coating for metals.

MAGNESIUM OXIDE

CHEMICAL FORMULA:  $\text{MgO}$

GENERAL DESCRIPTION: Colorless crystalline powder. It takes up  $\text{CO}_2$  and water from the air.

Molecular Wt.: 40.32 Melting Pt.: 2800°C Boiling Pt.: 3600°C

Density: (Solid) 3.58 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 0.0086 g/100 ml @ 30°C Cold Water: 0.00062 g/100 ml

Ethanol: Insoluble Other: Soluble in acids and ammonium salts.

DOT Classification:

Coast Guard Classification:

MANUFACTURE: It occurs in nature as the mineral perclase. It is manufactured by calcination of magnesium carbonate, magnesium hydroxide or by decomposition of magnesium chloride.

USES: In the manufacture of refractories, magnesium metal and oxychloride cements, as an ingredient in mixed fertilizer, in the manufacture of magnesium salts, as a neutralizing agent and vulcanization accelerator in the compounding of neoprene and other rubbers, as a decolorizing agent for solvents in the dry cleaning industry, as an absorbent and a catalyst, as an ingredient of various pharmaceutical and cosmetic formulations such as dentifrices and powders, as an antacid and laxative for man and as a laxative for young foals, calves, pigs and dogs.

#### VANADIUM PENTOXIDE

CHEMICAL FORMULA:  $V_2 O_5$

GENERAL DESCRIPTION: Yellow to red crystalline solid.

Molecular Wt.: 181.88 Melting Pt.: 690°C Boiling Pt.: 1750°C d

Density: (Solid) 3.357 g/cc @ 18°C (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Cold Water: 0.8 g/cc @ 20°C

Ethanol: Insoluble Other:

DOT Classification:

Coast Guard Classification:

MANUFACTURE: By carefully igniting ammonium vanadate and by slightly acidifying an alkaline, aqueous solution of ammonium vanadate.

USES: As a catalyst for various chemical reactions, particularly those involving oxidation such as the oxidation of  $SO_2$  and  $SO_3$  in making sulfuric acid, in the manufacture of yellow glass, and for inhibiting ultraviolet light transmission in glass, as a developer in photography, and in the manufacture of aniline black.

#### ZINC OXIDE

CHEMICAL FORMULA:  $Zn O$

GENERAL DESCRIPTION: White or yellowish powder. Also called chinese white and flowers of zinc.

Molecular Wt.: 81.37 Melting Pt.: 1975°C Boiling Pt.:

Density: (Solid) 5.47 g/cc (Gas)

Vapor Pressure: \_\_\_\_\_  
 Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
 Solubility:  
     Hot Water: \_\_\_\_\_ Cold Water: 0.00016 g/100 ml @ 29° C  
     Ethanol: Insoluble \_\_\_\_\_ Other: Soluble in acids, alkalis,  
             NH<sub>4</sub>Cl  
 DOT Classification: \_\_\_\_\_  
 Coast Guard Classification: \_\_\_\_\_

**MANUFACTURE:** By the vaporization of metallic zinc by indirect heating in the presence of CO gas and oxidation of the zinc vapor with preheated air. It can also be produced from the zinc ore, franklinite or from zinc blende. It occurs naturally as the mineral zincite.

**USES:** As a pigment in white paints, in cosmetics, driers, quick-setting cements, in dental cements, in the manufacture of opaque glass and certain types of transparent glass, in the manufacture of enamels, automobile tires, white glue, matches, white printing inks, porcelains, zinc green, as an analytical chemical reagent, as an astringent, antiseptic, protective in skin diseases; in veterinary applications as a dressing in moist eczema and on wounds and otorrhea in dogs.

**TOXICOLOGY:** The materials included in this report are non-toxic. However inhalation of the solid particles could cause some physical damage.

Aluminum oxide is non-toxic, but it has been reported that inhalation of finely divided particles can cause physical damage to the lung.

Inhalation of freshly formed magnesium may cause metal fume fever. There is no evidence that it can produce any true systemic poisoning.

Vanadium compounds act chiefly as irritants to the conjunctivae and respiratory tracts. Prolonged exposures may lead to pulmonary involvement. Responses are acute, but never chronic.

Inhalation of fresh fumes of zinc oxide can cause a disease known as "brass founders' ague" or "brass chills". However, there is no cumulative effect to the inhalation of zinc fume. The zinc oxide dust which is not freshly formed is virtually innocuous, but it can block the ducts of the sebaceous glands and give rise to a papular, pustular eczema in men engaged in packing this compound into barrels.

The Threshold Limit Values (TLV) and Lethal Doses or Concentrations are as follows:

<u>Contaminant in Air</u>	<u>TLV</u>	<u>Lethal Dose or Concentration</u>
Aluminum Oxide	*	-
Magnesium Oxide	15 mg/M <sup>3</sup> (fume)	-

<u>Contaminant in Air</u>	<u>TLV</u>	<u>Lethal Dose or Concentration</u>
Vanadium Pentoxide	0.5 mg/M <sup>3</sup> (dust) 0.1 mg/M <sup>3</sup> (fume)	-
Zinc Oxide	5 mg/M <sup>3</sup> (fume)	ih IC <sub>CA</sub> : 2500 mg/M <sup>3</sup> rat

\* The proposed TLV is 10 mg/M<sup>3</sup> or 30 million particles /ft<sup>3</sup> whichever is smaller.

The Booz-Allen Ratings are:

<u>CONTAMINANT</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Aluminum Oxide	2	1	1	1	U	3	2	1	1
Magnesium Oxide	-	-	-	-	-	-	-	-	-
Vanadium Pentoxide	3	1	1	3	U	3	2	1	1
Zinc Oxide	2	1	1	3	3	U	1	1	1

OTHER HAZARDS: No other hazards known.

HANDLING, STORAGE, TRANSPORTATION: The chief concern in handling and storage is to maintain adequate ventilation of the dust and fume by workers. Dusty materials must be shipped in plastic-coated bags to prevent pollution during transportation.

DISPOSAL/REUSE: Contaminated materials are usually disposed of rather than reprocessed for reuse. The following Provisional Limits should be considered before disposal into the environment:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Aluminum Oxide	0.1 mg/M <sup>3</sup> or 0.3 million particles/ft <sup>3</sup> *	0.01 TLV
Magnesium Oxide	0.10 mg/M <sup>3</sup>	0.01 TLV
Vanadium Pentoxide	0.005 mg/M <sup>3</sup> (fume)	0.01 TLV
	0.001 mg/M <sup>3</sup> (dust)	0.01 TLV
Zinc Oxide	0.5 mg/M <sup>3</sup>	0.01 TLV

\*Whichever is the smaller

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Aluminum Oxide	0.5 ppm (mg/l)	Stokinger and Woodward Method
Magnesium Oxide	125 ppm (mg/l) as Mg	Drinking Water Standard
Vanadium Pentoxide	0.05 ppm (mg/l) as V	Chronic toxicity
Zinc Oxide	5 ppm (mg/l) as Zn	Drinking Water Standard

EVALUATION OF WASTE DISPOSAL PRACTICES:

DISPOSAL METHODS

EVALUATION

Landfill

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Since landfill provides a convenient and adequate method of disposal for these materials they are not considered to be candidates for disposal at National Disposal Sites.

## AMIDES

CHEMICAL FORMULA: The general formula for amides is  $R - \overset{\overset{O}{\parallel}}{C} - NH_2$  where R is an alkyl or aryl group.

GENERAL DESCRIPTION: Neutral compounds which are closely related to the organic acids.

TOXICOLOGY: Most of the saturated amides have low toxicity. The unsaturated and N-substituted amides are frequently irritants and may be absorbed through the skin. In animal experiments, the unsaturated and N-substituted amides have caused injury to the liver kidney and brain.



## AMMONIA, AMMONIUM HYDROXIDE

Ammonium hydroxide is essentially ammonia dissolved in water. This report will cover ammonium hydroxide.

CHEMICAL FORMULA:  $\text{NH}_4\text{OH}$

GENERAL DESCRIPTION: Colorless liquid. Also called aqua ammonia, water of ammonia, aqua ammonium, ammonium hydrate.

Molecular Wt.: 35.05 Melting Pt.:  $-77^\circ\text{C}$  Boiling Pt.: \_\_\_\_\_

Density: (Liquid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: Soluble Ethanol: \_\_\_\_\_

Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MCA Warning Label

MANUFACTURE: Ammonia is produced in large tonnage by the Haber process in which hydrogen and nitrogen gases react catalytically under elevated temperatures and pressure.

USES: The weaker solution (10%) is used as a reflex stimulant

The stronger solution (28-29%) may be used for the following purposes:

- (1) as a detergent and in removing stains, bleaching, calico printing and extracting plant colors and alkaloids.
- (2) in the manufacture of ammonium salts and aniline dyes.
- (3) as a chemical reagent and in a variety of other uses.

TOXICOLOGY: Irritating to the eyes and mucous membranes.

Corneal ulcers may be caused by the splashing of ammonia water in the eye. Emits toxic fumes upon heating. Edema of the respiratory tract, spasm of the glottis, and asphyxia result from inhalation of concentrated fumes.

The Threshold Limit Value (TLV) is  $35 \text{ mg/M}^3(\text{NH}_3)$

The Lethal Dose (LD) is  $250 \text{ mg}(\text{NH}_3)/\text{Kg rat}$ .

The Booz-Allen Ratings for ammonia are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
2	3	2	0	3	0	2	1	2

OTHER HAZARDS : No other hazards known.

HANDLING, STORAGE, TRANSPORTATION: Contact with the skin and inhalation of the fume should be avoided. Ammonia should be kept tightly closed.

DISPOSAL/REUSE: For the safe disposal of ammonia into the environment, the following Provisional Limits are recommended:

<u>Contaminant in Air</u>	<u>Maximum Exposure Limit</u>	<u>Basis for Recommendation</u>
Ammonium Hydroxide	0.2 mg/M3 as NH <sub>3</sub>	0.01 TLV for NaOH
<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis For Recommendation</u>
Ammonium Hydroxide	0.01 ppm (mg/l)	Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES

##### METHOD OF DISPOSAL

Neutralize to ammonium nitrate with nitric acid and use as a fertilizer

##### EVALUATION

Satisfactory

#### APPLICABILITY TO NATIONAL DISPOSAL SITES:

Ammonium hydroxide as a waste stream constituent is not considered to be a candidate for disposal at a National Disposal Site.

AMMONIUM CHLORIDE, AMMONIUM NITRATE, SODIUM CARBONATE, SODIUM NITRATE

AMMONIUM CHLORIDE

CHEMICAL FORMULA:  $\text{NH}_4\text{Cl}$

GENERAL DESCRIPTION: White crystalline solid. Also called sal ammoniac.

Molecular Wt.: 53.50 Melting Pt.: Boiling Pt.: 350°C

Density: (Solid) 1.54 g/cc (Gas) (sublimes)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 29.7 g/100 ml @ 0°C Cold Water: 75.8 g/100 ml @ 100°C

Ethanol: Slightly soluble Other: Soluble in  $\text{NH}_4\text{OH}$

DOT Classification:

Coast Guard Classification:

MANUFACTURE: The commercial grade is usually produced by the Solvay Ammonia-Soda process. It is also made by reacting ammonium sulfate with sodium chloride.

USES: In soldering flux, washing powders, pickling agents for zinc coating and tinning, electroplating and medicine and in the manufacture of dyes, various ammonia compounds, fertilizer and cement for pipe joints.

AMMONIUM NITRATE

CHEMICAL FORMULA:  $\text{NH}_4\text{NO}_3$

GENERAL DESCRIPTION: Colorless crystalline material. Also called Norway Saltpeter.

Molecular Wt.: 80.05 Melting Pt.: 169.6°C Boiling Pt.: 210°C

Density: (Solid) 1.725 g/cc @ 23°C (Gas) (decomposes)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 87 g/100 g @ 100°C Cold Water: 118 g/100 g @ 0°C Ethanol: 2.8 g/100 g @ 20°C

Other: Soluble in alkaline

DOT Classification: Oxidizing material, yellow label

Coast Guard Classification: Oxidizing material, yellow label

MANUFACTURE: There are four basic processes for the manufacture of ammonium nitrate: Prilling or spraying, the Stengel process, crystallization and graining. All ammonium nitrate is made by neutralizing nitric acid with ammonia.

USES: Important as a nitrogen fertilizer. In the manufacture of many explosives, and nitrous oxide, an anesthetic.

#### SODIUM CARBONATE

CHEMICAL FORMULA:  $\text{Na}_2\text{CO}_3$

GENERAL DESCRIPTION: White, hygroscopic crystalline powder. Also called soda ash.

Molecular Wt.: 106.00 Melting Pt.: 851°C Boiling Pt.: ~~decomposes~~

Density: (Solid) 2.509 g/cc @ 0°C (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 45.5 g/100 ml @ 100°C Cold Water: 7.1 g/100 ml @ 0°C

Other: Ethanol: Insoluble

DOT Classification:

Coast Guard Classification:

MANUFACTURE: Over 90% of the world's soda-ash is made by the Solvay Ammonia-Soda process. The rest is recovered from natural deposits or brines. The raw materials for the Solvay process are coke, salt, lime and ammonia.

USES: By the glass, soap, water treatment, chemical, pulp and paper, petroleum, nonferrous metals and textile industries.

#### SODIUM NITRATE

CHEMICAL FORMULA:  $\text{NaNO}_3$

GENERAL DESCRIPTION: Colorless, transparent, odorless, crystalline solid. Also called Chile Saltpeter, soda niter, nitratine.

Molecular Wt.: 85.01 Melting Pt.: 308°C Boiling Pt.: ~~decomposes~~

Density: (Solid) 2.267 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 180 g/100 ml @ 100°C Cold Water: 73 g/100 ml @ 100°C

Ethanol: Slightly soluble Other: Glycerol soluble

DOT Classification: Oxidizing material

Coast Guard Classification: Oxidizing material

MANUFACTURE: By reacting sodium carbonate with nitric acid or by recrystallization of Chile Saltpeter, which is impure sodium nitrate.

USES: In fertilizers and in explosives.

TOXICOLOGY: These materials are not particularly toxic. Soda ash, because of its alkalinity is irritating to the skin and respiratory tract. Threshold Limit Values have not been established for these materials. The Lethal Doses are:

<u>Contaminant</u>	<u>Lethal Dose</u>
Ammonium Chloride	im LD <sub>50</sub> : 30 mg/kg, rat
Ammonium Nitrate	-----
Sodium Carbonate	or LD <sub>50</sub> : 4200 mg/kg, rat
Sodium Nitrate	ip LD <sub>50</sub> : 326 mg/kg, rat

The Booz-Allen Ratings are:

<u>Contaminant</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Ammonium Chloride	1	1	1	2	2	U	2	1	1
Ammonium Nitrate	1	1	1	U	2	U	2	1	3
Sodium Carbonate	2	2	2	1	3	1	1	1	1
Sodium Nitrate	2	2	1	3	1	U	2	1	2

OTHER HAZARDS: Ammonium and sodium nitrate are fire hazards when in contact with organic materials or other readily oxidizable substances. Ammonium nitrate may explode under confinement at high temperature. A mixture of diesel oil and ammonium nitrate is used industrially as an explosive. Upon heating, ammonium nitrate and sodium nitrate give off toxic fumes of nitrogen oxides.

HANDLING, STORAGE, TRANSPORTATION: Store in a dry place protect from moisture, keep ammonium and sodium nitrate away from reducing agents. Sodium carbonate is alkaline and in water will attack aluminum.

DISPOSAL/REUSE: Industrially contaminated materials may on occasion be reprocessed for reuse. If disposal is to be carried out, the following recommended provisional limits should be considered:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Ammonium Chloride	0.10 mg/M <sup>3</sup>	0.01 TLV
Ammonium Nitrate	0.05 mg/M <sup>3</sup>	Data for similar compounds
Sodium Carbonate	0.02 mg/M <sup>3</sup>	Data for similar compounds
Sodium Nitrate	0.05 mg/M <sup>3</sup>	Data for similar compounds

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Ammonium Chloride	250 mg/l as Cl	Drinking Water Standard
Ammonium Nitrate	45 mg/l as NO <sub>3</sub>	Drinking Water Standard
Sodium Carbonate	0.1 mg/l	Stokinger and Woodward Method
Sodium Nitrate	45 mg/l as NO <sub>3</sub>	Drinking Water Standard

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### DISPOSAL METHODS

##### EVALUATION

Dilute to provisional limits and discharge into sewers or natural streams

Satisfactory

Treat ammonium nitrate and ammonium chloride with NaOH to liberate ammonia and soluble salts. Recover the ammonia and dilute the salts to the Provisional Limits then discharge the salts into streams or sewers

Satisfactory

Incineration after water dilution. Use gas cleaning devices for the effluent gases.

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: The materials discussed in this report have been classified as probable waste stream constituents for municipal disposal and are not considered candidates for disposal at National Disposal Sites.

HEXAVALENT CHROMIUM COMPOUNDS  
(AMMONIUM CHROMATE, AMMONIUM DICHROMATE, POTASSIUM CHROMATE,  
POTASSIUM DICHROMATE, SODIUM DICHROMATE, SODIUM CHROMATE)

AMMONIUM CHROMATE

CHEMICAL FORMULA:  $(\text{NH}_4)_2 \text{CrO}_4$

GENERAL DESCRIPTION: Yellow crystalline solid. Aqueous solution is alkaline.

Molecular Wt.: 152.09 Melting Pt.: d Boiling Pt.: \_\_\_\_\_

Density: (Solid) 1.91 g/cc @ 12°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: d Cold Water: 40.5 g/100 cc @ 30°C

Ethanol: Insoluble Other: Slightly soluble in  $\text{NH}_3$

DOT Classification: Flammable Solid, yellow label

Coast Guard Classification: Flammable solid, yellow label.

MANUFACTURE: Sodium chromate is combined with ammonium sulfate.

AMMONIUM DICHROMATE

CHEMICAL FORMULA:  $(\text{NH}_4)_2 \text{Cr}_2 \text{O}_7$

GENERAL DESCRIPTION: Orange crystalline solid. Aqueous solution is acid.

Molecular Wt.: 252.10 Melting Pt.: d Boiling Pt.: \_\_\_\_\_

Density: (Solid) 2.15 g/cc @ 25°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: 89 g/100 cc @ 30°C Cold Water: 30.8 g/100 cc @ 15°C

Ethanol: Soluble Other: \_\_\_\_\_

DOT Classification: Flammable solid, yellow label

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Sodium dichromate is combined with ammonium sulfate.

POTASSIUM CHROMATE

CHEMICAL FORMULA:  $\text{K}_2 \text{Cr}_2 \text{O}_7$

GENERAL DESCRIPTION: Yellow crystalline solid. Aqueous solution is alkaline.

Molecular Wt.: 194.20 Melting Pt.: 968.3° C Boiling Pt.: \_\_\_\_\_

Density: (Solid) 2.732 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Hot Water: 79.2 g/100 cc 100°C Cold Water: 62.9 g/100 cc @ 20°C

Ethanol: Insoluble Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Reacting potassium chloride and sodium chromate, or roasting the ore with potassium carbonate.

#### POTASSIUM DICHROMATE

CHEMICAL FORMULA:  $K_2Cr_2O_7$

GENERAL DESCRIPTION: Red crystalline solid. Aqueous solution is acid.

Molecular Wt.: 294.19 Melting Pt.: 398°C Boiling Pt.: d 500°C

Density: (Solid) 2.68 g/cc @ 25°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Hot Water: 102 g/100 cc @ 100°C Cold Water: 4.9 g/100 cc @ 0°C

Ethanol: Insoluble Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Potassium dichromate can be produced by chrome ore roasting with potassium carbonate. Reacting potassium chloride and sodium chromate is a preferred method.

#### SODIUM CHROMATE

CHEMICAL FORMULA:  $Na_2CrO_4$

GENERAL DESCRIPTION: Yellow crystalline solid.

Molecular Wt.: 162 Melting Pt.: \_\_\_\_\_ Boiling Pt.: \_\_\_\_\_

Density: (Solid) 2.710 - 2.736 g/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Hot Water: \_\_\_\_\_ Cold Water: 87.3 g/100 cc @ 30°C



Ethanol: Slightly soluble Other: Soluble in ethyl alcohol  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Roasting chrome ore with soda ash and/or lime.

SODIUM DICHROMATE

CHEMICAL FORMULA:  $\text{Na}_2\text{Cr}_2\text{O}_7$

GENERAL DESCRIPTION: Red crystalline solid                      anh. 356.7°C M.P.  
Molecular Wt.: 298.1                      Melting Pt.:  $-2\text{H}_2\text{O}$  100°C Boiling Pt.: 400°C  
Density: (Solid) 2.52 g/cc @ 13°C                      (Gas) \_\_\_\_\_ (decomposes)  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility:  
    Hot Water: 508 g/100 cc @ 80°C                      Cold Water: 238 g/100 cc @ 0°C  
    Ethanol: Insoluble                      Other: \_\_\_\_\_  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_  
IATA Classification: Class A, No label, no limit  
MCA Requires warning label

MANUFACTURE: Roasting chrome ore with soda ash and/or lime. The resulting sodium chromate is processed further to yield the dichromate.

USES: The distribution of  $\text{Na}_2\text{Cr}_2\text{O}_7$  used in 1968 was: Pigments 40%, leather tanning 18%, chromic acid (plating) 17%, metal treatment 10%, textiles and dyes 6%, export and other 9%. The estimate for use made in 1968 for 1972 was 145,000 tons.

SOURCES AND TYPES OF CHROMATE WASTE: All of the industries mentioned above with the possible exception of the pigment industry. Almost all cooling towers. About 32,000 tons of chromium waste, calculated as chromic acid, from the metal finishing industry, most of this is reduced to  $\text{Cr}^{+3}$ . See Table 17.

TOXICOLOGY: Very corrosive when in contact with skin or mucous membranes. Produce ulcerous lesions which heal slowly. Have been associated with lung cancer. The TLV for hexavalent chromates is 0.1 mg/M<sup>3</sup> in air while that for chromate ions is 0.5 mg/M<sup>3</sup> in air. Very toxic to marine and plant life.

The Booz-Allen Ratings for these compounds are:

Table 17. TYPICAL METAL FINISHING WASTE STREAMS CONTAINING CHROMIUM

Waste Description	Form	Source:	
		Industry	Process
3000 ppm of a mixture of chromium, 20% aluminum sulfate and 35% sulfuric acid (trace of copper, nickel, lead)	Liquid	Aluminum anodizing bath with drag out	
12.5% chromic acid - dichromate in 10% to 30% sulfuric acid with 5000 to 120,000 ppm chromium (85% as Cr <sup>+3</sup> ) with 100-1000 ppm lead, copper and iron.	Liquid	Metal finishing	
Dilute chromic acid solution containing chromium +3 at 100-200 ppm and chromium +6 at 2000 to 4000 ppm with traces of organics (combined wash waters).	Liquid	Metal plating	
Partially neutralized aqueous plating waste containing 5-10% zinc chromate, and 5-10% zinc phosphate contaminated with various organic oils.	Liquid	Zinc plating	
Solutions of chromates and dichromates in sulfuric acid (6-12%) containing 5000-170,000 ppm chromium with copper lead and traces of organics.	Liquid	Formation of protective and decorative coatings (metal)	
0.1-0.5% chromium, 100-400 ppm copper, 100-600 ppm nickel in 5-10% aqueous hydrofluoric-hydrochloric acid.	Liquid	Plating preparation (metal)	
1 to 20% chromium in solids concentrations of 10-80% from settling and/or dewatering processes. Includes copper in varying amounts with varying amounts of inert filter aids.	Sludge	Chemical process (plating operation, manufacturing metallurgical)	
100-1000 ppm chromium as alkaline cyanide solution (6-20%) with copper in varying amounts with possible traces of organics, nickel, lead and zinc.	Liquid	Metal plating (formation of protective and decorative coatings)	

Table 17. TYPICAL METAL FINISHING WASTE STREAMS CONTAINING CHROMIUM (cont'd.)

Waste Description	Source:	
	Form	Industry/Process
5-6% Chromic acid in water solution with 1% iron	Liquid	(1) Metal plating (2) Ship building
9% chromic acid in water solution with 1% iron	Liquid	Metal finishing and plating
0.1-1% sodium or potassium dichromate in water, usually sulfuric acid present in a 1-15% concentration	Liquid	(1) Metal Finishing (2) Shipbuilding (3) Plating

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Ammonium Chromate	3	3	3	U	2	U	2	1	2
Ammonium Dichromate	3	2	3	2	2	U	2	1	2
Potassium Chromate	3	3	3	3	3	3	1	1	1
Potassium Dichromate	3	3	3	U	3	3	1	1	1
Sodium Chromate	3	3	3	3	2	U	1	1	1
Sodium Dichromate	3	3	3	U	3	U	1	1	1

OTHER HAZARDS: Powerful oxidizing agents and should not be mixed with reducing agents or organic materials. Concentrated aqueous solutions will attack metals at high temperatures.

HANDLING, STORAGE, TRANSPORTATION: Avoid storing at high temperature. Avoid contact with reducing agents. Avoid creation of dust during handling, transfer and storage. Workers must be protected against contact of these materials with eyes, skin and internal organs. DOT classifies ammonium chromate and dichromate as flammable solids which require yellow labels.

DISPOSAL/REUSE: Discharge into open water ways is severely restricted. U.S. Public Health Service recommends 0.05 ppm as upper limit for potable water. Discharge of  $\text{Cr}^{6+}$  into municipal sewage is normally set at near 5 ppm. For safe disposal of chromates, the following Provisional Limits for release into the environment are recommended:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Ammonium Chromate	0.001 mg/M <sup>3</sup> as CrO <sub>3</sub>	0.01 TLV
Ammonium Dichromate	0.001 mg/M <sup>3</sup> as CrO <sub>3</sub>	0.01 TLV
Potassium Chromate	0.001 mg/M <sup>3</sup> as CrO <sub>3</sub>	0.01 TLV
Potassium Dichromate	0.001 mg/M <sup>3</sup> as CrO <sub>3</sub>	0.01 TLV
Sodium Chromate	0.001 mg/M <sup>3</sup> as CrO <sub>3</sub>	0.01 TLV
Sodium Dichromate	0.001 mg/M <sup>3</sup> as CrO <sub>3</sub>	0.01 TLV

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Ammonium Chromate	0.05 ppm (mg/l) as Cr	Drinking Water Standard
Ammonium Dichromate	0.05 ppm (mg/l) as Cr	Drinking Water Standard
Potassium Chromate	0.05 ppm (mg/l) as Cr	Drinking Water Standard
Potassium Dichromate	0.05 ppm (mg/l) as Cr	Drinking Water Standard
Sodium Chromate	0.05 ppm (mg/l) as Cr	Drinking Water Standard
Sodium Dichromate	0.05 ppm (mg/l) as Cr	Drinking Water Standard

Reclamation of chromium from waste sludges is seldom practiced.

EVALUATION OF WASTE MANAGEMENT PRACTICES:

EVALUATION

Reduction and precipitation as hydroxides, with disposal of sludges in either approved landfills or by incineration. Ion exchange electro chemical reduction.

Satisfactory

Direct precipitation  
by use of barium or lead salts

Not satisfactory due to potential handling problems due to poisonous heavy metals.

Ion flotation, electrodialysis, activated-carbon absorption, liquid-liquid extraction, activated carbon reduction, and reverse osmosis

Promising method in various stages of development

APPLICABILITY TO NATIONAL DISPOSAL SITES: The chromates discussed here are considered as candidate waste stream constituents for National Disposal Sites.

# AMMONIUM THIOCYANATE

CHEMICAL FORMULA:  $\text{NH}_4\text{SCN}$

GENERAL DESCRIPTION: Colorless solid. Also called ammonium sulfocyanate  
 Molecular Wt.: 76.1 Melting Pt.: 149.6°C Boiling Pt.: 170°C  
 Density: (Solid) 1.305 g/cc (Gas) decomposes  
 Vapor Pressure: \_\_\_\_\_  
 Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
 Solubility:  
     Hot Water: \_\_\_\_\_ Cold Water: \_\_\_\_\_  
     Ethanol: \_\_\_\_\_ Other: \_\_\_\_\_  
 DOT Classification: \_\_\_\_\_  
 Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: Prolonged absorption may produce various skin eruptions, running nose, and occasionally dizziness, cramps, nausea, vomiting and mild or severe disturbances of the nervous system. Thiocyanates have a low acute toxicity.


The Booz-Allen Ratings for thiocyanates are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
1	1	2	U	U	U	2	1	1

OTHER HAZARDS: Dangerous. Thiocyanites emit highly toxic fumes of cyanides when heated to decomposition or on contact with acid or acid fumes.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool, dry, well ventilated area, away from heat or open flames.

# ANILINE

CHEMICAL FORMULA:  $C_6H_5NH_2$  „ 

GENERAL DESCRIPTION: Colorless oily liquid. Also called phenylamine, aminobenzene.

Molecular Wt.: 93.12 Melting Pt.: 6.2°C Boiling Pt.: 184.4°C  
 Density: (Liquid) 1.02 @ 20°C (Gas) 3.22 g/l  
 Vapor Pressure: 1 mm @ 35°C 10 mm @ 70°C  
 Flash Pt.: 168°F Autoignition Temperature: 617°C  
 Explosive Limits in Air (Wt%): Lower - Upper -  
 Solubility:

Hot Water: 6.4 g/100 ml Cold Water: 3.9g/100 ml Ethanol: soluble

Other: Benzene, miscible in chloroform

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: By the reduction of nitrobenzene or by the amination of chlorobenzene. Total U.S. production of aniline for 1970 was 398,362,000#.

## MANUFACTURERS OF ANILINE ARE:

Allied Chemical Corporation  
 American Cyanamid Company  
 E.I. duPont de Nemours & Company, Incorporated  
 First Chemical Corporation  
 Mobay Chemical Company  
 Rubican Chemicals, Incorporated  
 Uniroyal, Incorporated

USES: In the manufacture of dyes, rubber chemicals, sulfa drugs and synthetic sweetening agents.

TOXICOLOGY: Highly toxic. May enter the body through the lungs, the gastro intestinal tract or skin. Long and continued exposure to even small amounts may produce tumors and cancer of the bladder. May produce anoxemia and depression of the central nervous system. Acute exposures produce methemoglobinaemia and anoxemia. Less acute exposure over weeks or months produce hemolysis of the red blood cells followed by stimulation of the bone marrow and attempts at regeneration. The liver may be affected with the production of jaundice.

The Threshold Limit value for aniline is: 5 ppm (19 mg/M<sup>3</sup>).

The Booz-Allen Ratings for aniline are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
3	3	3	1	2	U	2	1	2

OTHER HAZARDS: Some fire hazard.

HANDLING, STORAGE, TRANSPORTATION: Should be handled in a way to prevent contact. Keep containers closed and prevent leakage. Store in a cool, well-ventilated area away from fire hazards.

DISPOSAL/REUSE: Contaminated or degraded materials which cannot be recycled must be disposed of in a safe manner. The following are Recommended Provisional Limits for release into the environment:

	<u>Provisional Limits</u>	<u>Basis for Recommendation</u>
Contaminant in Air	0.05 ppm (.019 mg/M <sup>3</sup> )	0.01 TLV
Contaminant in Soil and Water	0.95 ppm (mg/l)	Stokinger and Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES:

All possible waste aniline should be recycled.

DISPOSAL METHODS

EVALUATION

Incineration with oxides of nitrogen removed from effluent gases by scrubber, catalytic and/or thermal devices

Recommended

Activated sludge treatment

Satisfactory

Activated carbon treatment

Satisfactory

APPLICABILITY TO NATIONAL SITES: Aniline is satisfactorily treated at industrial sites and is not considered a candidate for National Disposal Site Treatment.



## ARSENIC TRIOXIDE

CHEMICAL FORMULA:  $\text{As}_2\text{O}_3$

GENERAL DESCRIPTION: Highly toxic colorless crystal. Also called white arsenic

Molecular Wt.: 197.82°C Melting Pt.: Sublimes 193°C Boiling Pt.: 4572°C

Density: (Solid) 3.738 g/cc (Gas)

Vapor Pressure: 1 mm @ 212°C, 10 mm @ 259.7°C, 100 mm @ 332.5°C

Flash Pt.: None Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower None Upper

Solubility:

Hot Water: 11.46 g/100 cc @ 100°C Cold Water: 2.04 g/100 cc @ 25°C

Ethanol: Soluble Other: Alkal. and HCl

DOT Classification: Poisonous solid, Class B

Coast Guard Classification:

MANUFACTURE: Occurs in nature as ores containing various arsenic compounds. The ores are not mined and processed for the arsenic, but arsenic is a major by-product of the copper, lead, zinc and gold smelting industries. American Smelting and Refining Company produced 14,000 tons (12,700,000kg) of arsenic trioxide in 1970.

USES: The major use of arsenic trioxide is in the production of agricultural pesticides. These are used in cattle and sheep dip solutions, applied to foliage or to the ground and for wood preservatives. Arsenic trioxide is also used in the glass industry.

TOXICOLOGY: Arsenic trioxide is a powerful poison. The systemic effects are usually caused by ingestion. As little as 0.1 gram ingested can be fatal. It can also be absorbed by inhalation of the dust. Skin contact can cause dermatitis, but normally will not cause systemic symptoms. The acute poisoning symptoms include difficulty in swallowing, severe abdominal pain, vomiting, diarrhea, pain in the limbs, muscle cramps, cold damp skin, rapid weak pulse, shock, unconsciousness, convulsions, and death. The symptoms of chronic low level arsenic exposure are difficult to diagnose due to the wide variety of unpredictable symptoms which may arise.

Arsenic trioxide is highly toxic to most forms of animal life. Adverse effects on vegetation have been observed in areas downwind from where arsenic trioxide trash has been burned, but detailed information on plant effects is not available.

The Booz-Allen Ratings for arsenic trioxide are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	2	3	3	3	3	1	2

OTHER HAZARDS: Arsenic trioxide is noncombustible, nonexplosive and as a dry solid is noncorrosive to steel. It should be considered a hazard if heated, since it sublimes at 193°C

HANDLING, STORAGE, TRANSPORTATION: Because of its highly toxic nature, special care must be taken to prevent contact with personnel in the storage, handling, transportation and disposal of arsenic trioxide. Arsenic trioxide should be stored away from food products and combustible materials. It should be stored in containers which are siftproof. Spills should be cleaned up immediately in such a way so as not to generate dust. It should be shipped in steel drums or tight wooden drums. Steel hopper or bottom outlet, siftproof, self clearing railcars equipped with weatherproof covers are also used.

DISPOSAL/REUSE: American Smelting and Refining is accepting crude  $As_2O_3$  from the smelting industry on a broad scale. Flue dust from other smelters is sent to ASARCO for residual metals recovery and  $As_2O_3$  purification. For release of arsenic trioxide to the environment the following Provisional Limits are recommended:

<u>Arsenic Trioxide as a Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.005 mg/M <sup>3</sup> as As	0.01 TLV for As
Water and Soil	0.05 ppm (mg/l) as As	Drinking Water Standard

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Recycling/reprocessing. Acceptance of flue dust from other smelters by American Smelting and Refining Co.	Most satisfactory
Land burial	Satisfactory, but expensive and $As_2O_3$ is lost.
Long term storage	Satisfactory

#### Abatement in Flue Streams

Multistage electrostatic Precipitators	Less than adequate
Filter/bag house	Adequate but expensive
TRW charged droplet scrubber	Adequate
Wet vacuum filtering	Very little information, but reported to be 100% effective

APPLICABILITY TO NATIONAL DISPOSAL SITES: Arsenic trioxide is considered as a candidate for National Disposal Sites for the following reasons: (1) It is highly toxic and nondegradable; (2)  $\text{As}_2\text{O}_3$  waste is present in large quantities; (3)  $\text{As}_2\text{O}_3$  waste is widely distributed and comes from a large number of industries; and (4) the feasibility of a centrally located facility has already been shown by the treatment of flue dust from other smelters at ASARCO in Tacoma, Washington.

c1ccccc1C(=O)Oc1ccccc1C(=O)O

Coast Guard Classification:

356

EVALUATION OF WASTE MANAGEMENT:

PRACTICES:

As much material as possible is recycled. This is the best method of handling contaminated material.

METHODS OF DISPOSAL

EVALUATION

Discharge into sewer after pH adjustment to 6.0 to 9.0 for treatment in the municipal sewage plant

Satisfactory

Incineration

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Benzoic acid waste can be treated by industrial or municipal disposal methods and is not considered to be a candidate for National Disposal Sites.

## BORON

CHEMICAL FORMULA: B

GENERAL DESCRIPTION: Crystals or yellow or brown amorphous powder.

Atomic Wt.: 10.82 Melting Pt.: 2300°C Boiling Pt.: 2550°C  
Density (Solid): 3.33 g/cc @ 20°C

TOXICOLOGY: Boron compounds are not highly toxic and are not considered industrial poisons. Boron affects the central nervous system. Boron poisoning causes depression of the circulation, persistent vomiting and diarrhea followed by profound shock and coma. The temperature is subnormal and the body may be covered by a scarletina-form rash. Poisoning can be caused by absorption from ointments applied to burned areas or wounds. It is not absorbed through intact skin.

OTHER HAZARDS: Boron is a moderate fire hazard in the form of dust when exposed to air or by reaction with oxidizing materials. It is also an explosion hazard in the form of dust.

## BORON CHLORIDE

CHEMICAL FORMULA:  $\text{BCl}_3$

GENERAL DESCRIPTION: Colorless fuming liquid. Also called boron trichloride.

Molecular Wt.: 117.17 Melting Pt.: -107.3°C Boiling Pt.: 12.5°C

Density: (Liquid) 1.349 g/cc @ 11°C (Gas) 4.03 g/l

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_


Hot Water: decomposes Cold Water: \_\_\_\_\_ Ethanol: decomposes

Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: By chlorination of a mixture of boron trioxide and carbon at a temperature range of from 1600 to 1800°F Also by the following reactions:



USES: In the manufacture of boron compounds, as an acidic catalyst for organic reactions, in the purification of aluminum, magnesium, zinc and copper alloys and to remove nitrides, carbides and oxides.

TOXICOLOGY: The toxic effect of boron chloride is not too well known. However, when heated to decomposition, it will emit toxic fumes of chlorides. The reported Lethal Concentration is "ih  $\text{LC}_{50}$ : 20 ppm rat".

The Booz-Allen Ratings are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
2	2	2	2	U	U	2	2	2

OTHER HAZARDS: Boron chloride hydrolyzes readily in moist air or water to yield corrosive hydrochloric acid.

HANDLING, STORAGE, TRANSPORTATION: Contact with skin and inhalation of fumes should be avoided. It should be kept away from food. The container should be kept tightly closed.

DISPOSAL/REUSE: Boron chloride probably could not be economically reprocess-

sed for reuse when it is contaminated or present in a waste stream. For its safe disposal the following Provisional Limits should be considered before releasing it into the environment:

<u>BCl<sub>3</sub> as a Contaminant in air</u>	<u>Maximum Exposure Limit</u>	<u>Basis for Recommendation</u>
	0.03 mg/M <sup>3</sup>	0.01 TLV for BF <sub>3</sub>
<u>BCl<sub>3</sub> as a Contaminant in Soil and Water</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
	0.15 ppm (mg/l)	Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Neutralization with soda ash-slaked lime solution. The neutral solution of sodium or calcium chloride and borate are formed and can be discharged to streams.	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Boron chloride as a waste stream constituent can be adequately disposed of in the industrial sites by conventional means and is not considered to be a candidate for disposal at National Disposal Sites.



BUTYL DISULFIDE

CHEMICAL FORMULA:  $\text{CH}_3(\text{CH}_2)_3\text{S}(\text{CH}_2)_3\text{CH}_3$

GENERAL DESCRIPTION: Colorless liquid. IUC Name: 1-butyldithiobutane.

Molecular Wt.: 178.4 Melting Pt.: Boiling Pt.: 103°C @ 15

Density: (Liquid) (Gas) /mm Hg

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Insoluble Cold Water: Ethanol: Infinitely

Other: Infinitely soluble in ether /soluble

DOT Classification:

Coast Guard Classification:

TOXICOLOGY: Animal experiments suggest that alkyl disulfides are dangerous and may cause hemolytic anemia. They may also produce allergic dermatitis.

OTHER HAZARDS: Dangerous when heated to decomposition, it emits highly toxic fumes of sulfides. It probably reacts strongly with powerful oxidizers. It is probably a moderate fire hazard.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool, dry well ventilated area away from heat and open flame. Avoid breathing fumes.

MERCAPTANS  
(BUTYL MERCAPTAN, ETHYL MERCAPTAN, METHYL MERCAPTAN)

BUTYL MERCAPTAN

There are three isomers

n - BUTYL MERCAPTAN

CHEMICAL FORMULA:  $\text{CH}_3(\text{CH}_2)_2\text{CH}_2\text{SH}$

GENERAL DESCRIPTION: Colorless liquid, skunk-like odor. IUC Name: 1-Butanethiol. Also called normal butyl thioalcohol and thiobutyl alcohol.  
Molecular Wt.: 90.19 Melting Pt.:  $-115.9^\circ\text{C}$  Boiling Pt.:  $98.2^\circ\text{C}$   
Density: (Liquid) 0.8365 g/cc @  $25^\circ\text{C}$  (Gas) 3.1 g/l  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.:  $35^\circ\text{F}$  Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility: \_\_\_\_\_  
Hot Water: \_\_\_\_\_ Cold Water: Slightly Ethanol: Very soluble  
Other: Very soluble in ether, liquid hydrogen sulfide  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: Flammable liquid.

sec - BUTYL MERCAPTAN

CHEMICAL FORMULA:  $\text{CH}_3\text{CH}_2\text{CH}(\text{SH})\text{CH}_3$

GENERAL DESCRIPTION: Mobile liquid, skunk-like odor. IUC Name: 2-Butanethiol. Also called sec-butyl thioalcohol  
Molecular Wt.: 90.19 Melting Pt.:  $-165^\circ\text{C}$  Boiling Pt.:  $84-85^\circ\text{C}$   
Density: (Liquid) 0.83 @  $17^\circ\text{C}$  (Gas) \_\_\_\_\_  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility: \_\_\_\_\_  
Hot Water: \_\_\_\_\_ Cold Water: slightly Ethanol: Very  
Other: Very soluble in ether, liquid hydrogen sulfide  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_

tert - BUTYL MERCAPTAN

CHEMICAL FORMULA:  $(CH_3)_3CSH$

GENERAL DESCRIPTION: Liquid, skunk like odor. IUC Name: 2-Methyl-2-propane-thiol.

Molecular Wt.: 90.19 Melting Pt.:  $-0.5^{\circ}C$  Boiling Pt.:  $63.7-64.2^{\circ}C$

Density: (Liquid) 0.79-82 g/cc @  $15^{\circ}C$  (Gas) 3.1 g/l

Vapor Pressure:

Flash Pt.:  $-15^{\circ}F$  Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Cold Water: Slightly Ethanol: Very

Other: Very soluble in ether, liquid hydrogen sulfide.

DOT Classification:

Coast Guard Classification:

ETHYL MERCAPTAN

CHEMICAL FORMULA:  $CH_3CH_2SH$

GENERAL DESCRIPTION: Colorless liquid, penetrating garlic-like odor. IUC Name: Ethanethiol. Also called ethyl thioalcohol, ethyl hydrosulfide, ethyl sulfhydrate.

Molecular Wt.: 62.13 Melting Pt.:  $-121 -140^{\circ}C$  Boiling Pt.:  $34 - 37^{\circ}C$

Density: (Liquid) 0.83907 g/cc @  $20^{\circ}C$  (Gas) 2.14 g/l

Vapor Pressure:

Flash Pt.:  $<80^{\circ}F$  (CC) Autoignition Temperature:  $570^{\circ}F$

Explosive Limits in Air (Wt%): Lower 2.8% Upper 18.2%

Solubility:

Hot Water: Cold Water: 67 parts Ethanol: Soluble

Other: Soluble in ether

DOT Classification:

Coast Guard Classification:

METHYL MERCAPTAN

CHEMICAL FORMULA:  $CH_3SH$

GENERAL DESCRIPTION: Liquid or gas. IUC Name: Methanethiol.

Molecular Wt.: 48.10 Melting Pt.:  $-121^{\circ}C$  Boiling Pt.:  $7.6^{\circ}C$

Density: (Liquid) 0.868 g/cc @  $20^{\circ}C$  (Gas) 1.66 g/l

Vapor Pressure: 43.7 psi @  $100^{\circ}F$ ; 2 atm @  $26.1^{\circ}C$ ; 5 atm @  $55.9^{\circ}C$

Flash Pt.: 0°F Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower                      Upper                       
 Solubility:  
     Hot Water: Slightly Cold Water: Freely Ethanol: Very  
     Other: Very soluble in methanol, very soluble in ether  
 DOT Classification: \_\_\_\_\_  
 Coast Guard Classification: Flammable gas.

MANUFACTURE: Reaction of hydrogen sulfide with olefins or alcohols. Methyl mercaptan is manufactured by Air Products and Chemical Inc., and Pennwalt Corp. n-Butyl and ethyl mercaptan are manufactured by Pennwalt Corp. and Phillips Petroleum Company.

USES: Ethyl and butyl mercaptan are used as intermediates in the manufacture of various agricultural chemicals. Methyl mercaptan is used in the first step of a commercial synthesis of methionine, an amino acid feed supplement.

TOXICOLOGY: Butyl, ethyl and methyl mercaptan are moderately toxic when ingested, inhaled or come in contact with the skin. n-Butyl mercaptan may cause nausea from its odor and may be narcotic in high concentrations. Ethyl mercaptan may cause neusea, headache and irritability. Methyl mercaptan poisoning is somewhat similar to that of hydrogen sulfide, although less severe.

The Threshold Limit Values (TLV) and Maximum Allowable Concentrations for these compounds are:

<u>MERCAPTAN</u>	<u>TLV</u>	<u>MAC</u>
Butyl	0.5 ppm	10 ppm for 8-hour exposure
Ethyl	0.5 ppm	250 ppm for 8-hour exposure
Methyl	0.5 ppm	50 ppm for 8-hour exposure

The Booz-Allen Ratings for thse mercaptans are:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Butyl	2	2	2	1	U	U	2	1	2
Ethyl	2	2	2	U	U	U	2	2	2
Methyl	2	2	2	2	3	U	2	2	2

OTHER HAZARDS: All of the mercaptans listed in this report are flammable. Ethyl mercaptan has known explosive limits. They emit highly toxic fumes when heated to decomposition.

HANDLING, STORAGE, TRANSPORTATION: Steel, stainless steel and copper-free

steel alloys are the preferred materials of construction for mercaptan service. Stainless steel should be used for any vessel or line which is to be open and exposed to air frequently.

Aluminum is also suitable for mercaptan use provided the pressure rating of aluminum equipment or piping is sufficient to meet pressure requirements of the application.

Venting of storage tanks in order to reduce pressure should be to a scrubber to remove the mercaptan. Only hermetically sealed pumps should be used.

Plastic gloves and chemical goggles should be worn to protect the skin and eyes when handling mercaptans. A self-contained breather type mask is recommended for protection when working in areas of high vapor concentration or for prolonged exposure to lower concentrations of vapor.

DISPOSAL/REUSE: When mercaptans are disposed of by release to the environment, the acceptable criteria for releasing  $H_2S$  and  $SO_2$  must be considered. The Provisional Limits for releasing the mercaptans,  $H_2S$  and  $SO_2$  are:

<u>Contaminant in Air</u>	<u>Provisional Limits</u>	<u>Basis for Recommendation</u>
Butyl Mercaptan	0.005 ppm (0.01 mg/M <sup>3</sup> )	0.01 TLV
Ethyl Mercaptan	0.005 ppm (0.01 mg/M <sup>3</sup> )	0.01 TLV
Methyl Mercaptan	0.005 ppm (0.01 mg/M <sup>3</sup> )	0.01 TLV
$H_2S$ released to air outside plant.	0.1 ppm	Below odor detection level
$H_2S$ released to air inside plant	10 ppm	TLV for repeated 8-hour exposure
$SO_2$	200lb/hr of $SO_2$ effluent at a maximum stack concentration of 500 ppm.	Los Angeles Air-Pollution Control District Rule 53.2

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Butyl Mercaptan	0.05 ppm (mg/l)/24 hrs	Stokinger and Woodward Method
Ethyl Mercaptan	0.05 ppm (mg/l)/24 hrs	Stokinger and Woodward Method
Methyl Mercaptan	0.075 ppm (mg/l)/24 hrs	Stokinger and Woodward Method
$H_2S$ released to water sources	0.1 mg/l	To avoid fish kill and water taste.

EVALUATION OF WASTE MANAGEMENT PRACTICES: Recycling of contaminated mercaptans is possible sometimes and this is the best means of liquid waste disposal.

METHODS OF DISPOSAL

EVALUATION

Incineration of both liquid and gaseous waste with a scrubber for the effluent gas.

Satisfactory

For small volume gas scrubbing can be used.

Satisfactory


APPLICABILITY TO NATIONAL DISPOSAL SITES: Adequate methods for handling mercaptan waste are available and are now being used, therefore, these materials are not considered candidate waste stream constituents for National Disposal Sites.

## PHENOLS

(Butyl Phenol, Ethyl Phenol, Carboic Acid (Phenol),  
Cresylic Acid (Cresol), Xylenol, Diethylstilbestrol)

### BUTYL PHENOL


The description of one isomer, para-tertiary-butyl phenol, will be given here.



GENERAL DESCRIPTION: Practically white flakes or crystals. IUC Name 4-t-butylphenol. Also called butylphen and 4-(d,d-dimethylethyl)-phenol.  
Molecular Wt.: 150.21 Melting Pt.: 98°C Boiling Pt.: 237°C  
Density: (Solid) 0.9081 g/cc @ 114°C (Gas) 5.1 g/l  
Vapor Pressure: 1 mm @ 70°C  
Flash Pt.: Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility:  
Hot Water: Cold Water: Insoluble  
Ethanol: Soluble Other: Soluble in ether  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_


### ETHYL PHENOL

The description of one isomer ortho-ethyl-phenol will be given here.



GENERAL DESCRIPTION: Colorless liquid, phenol odor. Also called phlorol.  
Molecular Wt.: 122.17 Melting Pt.: <18°C Boiling Pt.: 207°C  
Density: (Liquid) 1.0371 g/cc @ 0°C (Gas) \_\_\_\_\_  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.: Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility:  
Hot Water: Slightly Cold Water: Slightly Ethanol: Very Sol.  
Other: Soluble in ether, acetone and benzene  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_

### PHENOL

CHEMICAL FORMULA:  $C_6H_5OH$ , 

GENERAL DESCRIPTION: White crystalline solid which turns pink or red if not perfectly pure. Burning taste. Distinctive odor. Also called carbolic acid and phenylic acid.

Molecular Wt.: 94.11 Melting Pt.: 40.6°C Boiling Pt.: 181.9°C

Density: (Solid) 1.072 g/cc (Gas)

Vapor Pressure: 1 mm @ 40.1°C

Flash Pt.: 175°F (C.C.) Autoignition Temperature: 1319°F

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Cold Water: 1 g/15 ml @ 16°C

Ethanol: Soluble Other: Soluble in chloroform, ether glycerol and carbon disulfide

DOT Classification: Poison B, poison label, 55 gallons


Coast Guard Classification: Poison B

MCA Warning Label


IATA Classification: Poison B, poison label  
1 litre (passenger), 220 litres (cargo)

### CRESOL

CHEMICAL FORMULA:  $CH_3C_6H_4OH$ ,



ortho-cresol



meta-cresol



para-cresol

GENERAL DESCRIPTION: Colorless or yellowish to brown-yellow or pink liquid. Phenol like odor. Mixture of the cresol isomers. Also called cresylic acid, cresylol and tricresol.

Molecular Wt.: 108.1 Melting Pt.: 10.9-35.5°C Boiling Pt.: 191-203°C

Density: (Liquid) 1.030-1.038 g/cc @ 25°C (Gas) 3.72 g/l

Vapor Pressure: 1 mm @ 38-53°C

Flash Pt.: 110°F Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper 1.35% @ 300°F

Solubility:

Hot Water: Cold Water: 50 parts Ethanol: miscible

Other: Soluble in benzene, ether, glycerol, petroleum ether & alkali

DOT Classification:

Coast Guard Classification: Flammable liquid


MCA Warning Label

IATA Classification: Poison B, poison label  
1 litre (passenger), 220 litres (cargo)



### XYLENOL

The description of 3,5-xyleneol will be given here. The physical constants are similar and the solubilities are the same for all isomers.



GENERAL DESCRIPTION: White crystalline solid. IUC Name: 3,5-dimethylphenol. Also called 1-hydroxy-3,5-dimethyl-benzene, and 5-hydroxy-1,3-dimethyl benzene.

Molecular Wt.: 122.16 Melting Pt.: 64°C Boiling Pt.: 219.5°C

Density: (Solid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_


Hot Water: \_\_\_\_\_ Cold Water: Slightly

Ethanol: Soluble Other: Soluble in chloroform, ether &

DOT Classification: \_\_\_\_\_ /benzene.

Coast Guard Classification: \_\_\_\_\_

### DIETHYLSTILBESTROL



GENERAL DESCRIPTION: Crystalline solid. Also called stilbestrol.

Molecular Wt.: 268.34 Melting Pt.: 169-172°C Boiling Pt.: \_\_\_\_\_

Density: (Solid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Hot Water: \_\_\_\_\_ Cold Water: Almost insoluble

Ethanol: Soluble Other: Soluble in ether, chloroform, fatty oils, dilute hydroxides.

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Butyl and ethyl phenols are manufactured by alkylation of phenol with the appropriate olefin in the presence of an acid catalyst.

Phenol is manufacture principally by cumene peroxidation and by alkaline hydrolysis of chlorobenzene.

Cresol, which exists as a mixture of three isomers, and xlenol, which exists as six isomers, are derived from coal tar.

Diethylstilbestrol is derived from a variety of methods and starting materials.

USES: Cresol is used in the manufacture of synthetic resins and as a local antiseptic and disinfectant. Xlenol is used the preparation of disinfectants and synthetic resins.

Butyl and ethyl phenols are used as antiozidants and in the manufacture of antioxidants and synthetic resins.

Phenol: About 50% is used in the preparation of phenolic resins. The rest is used in the synthesis of monomers for other resins.

Diethylstilbestrol is used in estrogenic hormone therapy in humans, as an aid to increase weight in cattle, sheep and pigs and as a caponization agent for poultry.

TOXICOLOGY: Phenol, cresol, xlenol and butyl and ethyl phenol principally effect the nervous system causing headache, dizziness and muscular weakness followed, in acute cases, by loss of conciousness, collapse and death. They are corrosive to body tissues. Fatal doses may be absorbed thru the skin.

Diethylstilbestrol is corrosive to body tissue to a lesser degree than the other phenols treated here. When used in hormone therapy is has shown such side effects as gastrointestinal upset, dizziness, menstrual disturbances and headache. Its use has been associated with cell damage. This indicates the inadvisability of its use during pregnancy and lactation. There has been a great deal of concern recently with birth defects possibly caused by ingestion of meat containing trace amounts of diethylstilbestrol used to fatten cattle.

The Booz-Allen Ratings are:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Butyl Phenol	1	1	2	U	U	U	2	1	2
Ethyl Phenol	1	1	U	U	U	U	1	1	2
Cresol	2	2	2	2	3	U	2	1	2
Phenol	3	3	3	2	3	U	2	1	2
Diethylstilbestrol	2	2	2	1	U	U	1	1	1
Xlenol	3	3	3	2	3	U	1	1	1

OTHER HAZARDS: All of these phenols are considered slight fire hazards. Toxic fumes are emitted when heated to decomposition.

HANDLING, STORAGE, TRANSPORTATION: The most important considerations in the handling, storage and transportation of these materials are provisions for adequate ventilation in work areas and fire prevention procedures. Wear protective equipment to prevent skin and eye contact.

DISPOSAL/REUSE: For disposal of contaminated material the following Provisional Limits are recommended:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Phenol (Carbolic Acid)	0.05	0.19	0.01 TLV
Cresol (Cresylic Acid)	0.05	0.19	0.01 TLV
Ethyl Phenol	-	0.19	Based on similar compounds
Butyl Phenol	-	0.19	Based on similar compounds
Diethylstilbestrol	-	0.19	Based on similar compounds
Xylenol	-	0.19	Based on similar compounds

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm or mg/l</u>		
Phenol (Carbolic Acid)	0.001		Drinking Water Standard
Cresol (Cresylic Acid)	0.001		Drinking Water Standard
Ethyl Phenol	0.001		Based on similar compounds
Butyl Phenol	0.001		Based on similar compounds
Diethylstilbestrol	0.001		Based on similar compounds
Xylenol	0.001		Based on similar compounds

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Biological treatment of aqueous wastes	Satisfactory
Controlled incineration of organic and aqueous waste	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Wastes containing these materials may be properly disposed of at industrial or municipal facilities. These materials are not considered to be waste stream constituents for National Disposal Sites.

## BUTYRIC ACID

CHEMICAL FORMULA:  $\text{CH}_3(\text{CH}_2)_2\overset{\text{O}}{\underset{\text{OH}}{\text{C}}}$

GENERAL DESCRIPTION: Colorless liquid. IUC Name: Butanoic acid. Also called ethyl acetic acid, propyl formic acid and n-butyric acid

Molecular Wt.: 88.10 Melting Pt.:  $-7.9^\circ\text{C}$  Boiling Pt.:  $163.5^\circ\text{C}$

Density: (Liquid) 0.959 g/cc @  $20^\circ\text{C}$  (Gas)

Vapor Pressure: 0.43 mm @  $20^\circ\text{C}$

Flash Pt.:  $161^\circ\text{F}$  Autoignition Temperature:  $846^\circ\text{F}$

Explosive Limits in Air (Wt%): Lower 2.0% Upper 10.0%

Solubility:

Hot Water: Cold Water: 5.62 g/100 ml @  $-1.1^\circ\text{C}$

Ethanol: Infinitely soluble Other: Infinitely soluble in ether

DOT Classification:

Coast Guard Classification:

TOXICOLOGY: Butyric acid is not particularly toxic.

OTHER HAZARDS: Moderate fire hazard when exposed to heat or flame. It can react with oxidizing materials.

## CADMIUM, CADMIUM CHLORIDE

### CADMIUM

CHEMICAL FORMULA: Cd

GENERAL DESCRIPTION: Silver-white malleable metal.

Atomic Wt.: 112.41 Melting Pt.: 320.9° C Boiling Pt.: 767°C

Density: (Solid) 8.642 g/cc (Gas)

Vapor Pressure: 1 mm @ 394°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Insoluble Cold Water: Insoluble

Ethanol: Other: Hot sulfuric acid, ammonium nitrate

DOT Classification:

Coast Guard Classification:

MANUFACTURE: Cadmium is not found as a free mineral in nature. It is prepared commercially as a by-product of primary metal industries, especially the zinc industry. It is found in zinc, lead and copper ores and in other ores which contain zinc minerals. It separates out with zinc when ores containing several minerals are separated. Cadmium compounds contain cadmium mainly in the divalent state.

Cadmium ore is mixed with sodium chloride and coal or coke and heated in a sintering furnace. The dust and chloride fume is digested with sulfuric acid and then purified by distillation or electrolysis.

Cadmium is also produced from the purification of zinc sulfate solutions, from zinc sulfide manufacture, from the purification of zinc solutions after electrolytic zinc manufacture and from lead smelting.

Large-scale commercial manufacturing facilities for cadmium metal are: Amax, Blackwell, Oklahoma; Asarco, Denver, Colorado; Asarco, Corpus Christi, Texas; American Zinc Company, East St. Louis, Illinois; Anaconda, Great Falls, Montana; and New Jersey Zinc, Depue, Illinois.

USES: The chief use is in electroplating iron and steel. Cadmium plating operations include aircraft components, automobiles, electrical and electronic apparatus, household appliances, radio and television sets, hardware and fasteners. Cadmium metal is also used in pigments, plastic alloys, nickel-cadmium batteries, fungicides, nuclear energy applications, phosphors for television tubes, photography, lithography, process engraving, glass, x-ray screens, and in compounds for curing rubber.

### CADMIUM CHLORIDE

CHEMICAL FORMULA: Cd Cl<sub>2</sub>

GENERAL DESCRIPTION: Colorless crystals.

Molecular Wt.: 183.32      Melting Pt.: 568° C      Boiling Pt.: 960° C

Density: (Solid) 4.047 g/cc @ 25°C      (Gas)

Vapor Pressure: 10 mm @ 656° C, 10 mm @ 797° C

Flash Pt.:      Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower      Upper

Solubility:

Hot Water: 147 g/100 g @ 100°C      Cold Water: 90 g/100 g @ 0°C

Ethanol: Slightly soluble      Other: 1.52 g/100 ml @ 15°C, insoluble

DOT Classification:      /in acetone & ether.

Coast Guard Classification:

MANUFACTURE: By dissolving the metal in aqueous hydrochloric acid and evaporating in a stream of hydrogen chloride gas and by dissolving the oxide or carbonate in hydrochloric acid.

Manufacturers of cadmium chloride are: Allied Chemical Corporation, Marcus Hook, Pennsylvania; J.T. Baker Chemical Company, Phillipsburg, New Jersey; Chemetron Corporation, New Brunswick, New Jersey; The Harshaw Chemical Co., Cleveland, Ohio; Mallinckrodt Chemical Works, St. Louis, Missouri.

USES: In photography, in dyeing and calico printing, in the vacuum tube industry, in the manufacture of cadmium yellow, special mirrors, as an ice nucleating agent, in lubricants, and in the analysis of sulfides to absorb the hydrogen sulfide.

TOXICOLOGY: The inhalation of cadmium dusts or fumes affects the respiratory tract primarily, and may also affect the kidneys. Even brief exposure to high concentrations may result in pulmonary edema and death. In fatal cases fatty degeneration of the kidneys have been noted. Ingestion of cadmium results in a gastrointestinal type of poisoning.

Inhalation of the dust or fumes may cause dryness of the throat, coughing, headache, a sense of constriction in the chest, shortness of breath (dyspnea) and vomiting. More severe exposure results in marked lung changes, with persistent cough, pain in the chest, severe dyspnea and prostration which may terminate fatally. X-ray changes are usually similar to those seen in broncho-pneumonia. The urine is frequently dark. These symptoms are usually delayed for some hours after exposure, and fatal concentrations may be breathed without sufficient discomfort to warn the workman to leave the exposed area.

Ingestion of cadmium results in sudden nausea, salivation, vomiting, diarrhea and abdominal pain. Symptoms begin almost immediately after ingestion.

A yellow discoloration of the teeth has been reported in workers exposed to cadmium.

In fish oxygen inhibition occurs at levels as low as 0.0033 micromoles/ml and can be of such severity as to cause the death of fish particularly the bluegill. Expressed as cadmium, data indicates that the acute lethal level for fish varies from about 0.01 to about 10 mg/liter depending on the test animal the types of water, temperature and time of exposure. Cadmium acts synergistically with other substances to increase toxicity.

The relative oral LD<sub>50</sub> value to the rat is 88 mg/kg for cadmium chloride. The Threshold Limit Value (TLV) in air is 0.2 mg/cubic meter for cadmium and cadmium chloride. The permissible criteria for soluble cadmium in public water supplies is 0.01 mg/liter.

The Booz-Allen Ratings are:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Cadmium	3	3	1	3	U	U	2	1	2
Cadmium Chloride	3	3	3	3	3	3	2	1	2

OTHER HAZARDS: The fire and explosive hazard of cadmium metal in the form of dust is moderate when exposed to heat or flame or by reaction with oxidizing materials.

HANDLING, STORAGE, TRANSPORTATION: Care should be exercised in handling cadmium and its compounds because of their high toxicity. In case of skin contact wash with plenty of soap and water. Store away from food and feeds or any other material intended for human or animal consumption.

DISPOSAL/REUSE: The major sources of cadmium waste are the electroplating industry, nickel-cadmium battery manufacturers, paint manufacturers and paint residue left in old containers. The total amount of cadmium waste from the electroplating industry is estimated to be 1.44 million pounds per year. The greater portion of cadmium in air and water waste streams can be recovered for reuse. For the safe disposal of cadmium and cadmium chloride into the environment, the following Provisional Limits are recommended:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Cadmium Metal (powder)	0.002 mg/M <sup>3</sup>	0.01 TLV
Cadmium Chloride	0.002 mg/M <sup>3</sup>	0.01 TLV
<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Cadmium Metal (powder)	0.01 ppm	Drinking Water Standard
Cadmium Chloride	0.01 ppm	Drinking Water Standard

## EVALUATION OF WASTE MANAGEMENT:

### Removal from Air

For removal of cadmium from air electrostatic precipitators, bag houses and cyclones are used for abatement, but there is little information known about the specific application of these procedures for controlling cadmium pollution.

### Removal for Water

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Adsorption with activated-carbon bed	Satisfactory
Coagulation and filtration	Adequate
Ion exchange	Adequate
Reverse Osmosis	Not satisfactory, doesn't reduce the cadmium sufficiently

For concentrated cadmium waste disposal, coagulation with lime followed by sedimentation and sand filtration is the only proven and adequate treatment method.

APPLICABILITY TO NATIONAL DISPOSAL SITES: Cadmium and cadmium compounds are considered as candidate waste stream constituents for National Disposal Sites due to the extremely high degree of toxicity of all cadmium compounds, the nondegradable nature of the toxic cadmium component of all cadmium compounds, cadmium wastes are present in sizable quantities, a significant amount of cadmium waste is contributed by small plating shops where treatment is either technically or economically infeasible and the cadmium hydroxide waste should be disposed of in California Class 1 type landfills only and are not being adequately handled at present.



CALCIUM CHLORIDE, CALCIUM HYDROXIDE, POTASSIUM SULFATE, CALCIUM OXIDE

CALCIUM CHLORIDE

CHEMICAL FORMULA:  $\text{CaCl}_2$

GENERAL DESCRIPTION: Colorless, very hygroscopic, crystalline solid.

Molecular Wt.: 110.99 Melting Pt.:  $772^\circ\text{C}$  Boiling Pt.:  $>1160^\circ\text{C}$

Density: (Solid) 2.15 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 159 g/100 ml @  $100^\circ\text{C}$  Cold Water: 74.5 g/100 ml @  $20^\circ\text{C}$

Ethanol: Soluble Other: Soluble in acetic acid-acetone

DOT Classification:

Coast Guard Classification:

MANUFACTURE: About 50-60% of the calcium chloride sold in the U.S. is manufactured from natural brines.

USES: As a dehydrating and drying agent for organic liquids and in desiccators, for drying gases, in refrigeration plants to make brine, in control of snow and ice on highways and streets, in dust control on secondary roads, unpaved streets and highway shoulders, in freezeproofing of coal and ores, in both shipping and stockpiling, and in concrete mixes to give quicker initial set, high early strength and greater ultimate strength.

CALCIUM HYDROXIDE

CHEMICAL FORMULA:  $\text{Ca}(\text{OH})_2$

GENERAL DESCRIPTION: Colorless crystalline solid. Also called hydrate lime and slaked lime. Absorbs  $\text{CO}_2$  from the air.

Molecular Wt.: 74.09 Melting Pt.:  $-H_2O@580^\circ\text{C}$  Boiling Pt.: Decomposes

Density: (Solid) 2.24 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 0.077 g/100 ml @  $100^\circ\text{C}$  Cold Water: 1.85 g/100 ml @  $0^\circ\text{C}$

Ethanol: Insoluble Other: Soluble in acids and ammonium salts.

DOT Classification:

Coast Guard Classification:

MANUFACTURE: Commercially prepared from brine.

USES: Manufacture of mortars, plastics, cements, soda ash by the Solvay method, in dehairing hides, in water paints, as antiemetic and in infant feeding formulas to decrease sizes of curds formed from cow's milk.

#### CALCIUM OXIDE

CHEMICAL FORMULA:  $\text{CaO}$

GENERAL DESCRIPTION: Colorless crystalline solid. Also called unslaked lime, quick lime and burnt lime. Absorbs  $\text{CO}_2$  and water.

Molecular Wt.: 56.08      Melting Pt.:  $2580^\circ\text{C}$       Boiling Pt.:  $2850^\circ\text{C}$   
Density: (Solid) 3.37 g/cc      (Gas)

Vapor Pressure:

Flash Pt.:      Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower      Upper

Solubility: decomposes      decomposes

Hot Water: 0.07 g/100 ml @  $80^\circ\text{C}$       Cold Water: .13 g/100 ml @  $10^\circ\text{C}$

Ethanol:      Other: Soluble in acids

DOT Classification:

Coast Guard Classification:

MANUFACTURE: From calcination of limestone in a kiln.

USES: In the manufacture of mortar and plastics, in various metallurgical processes, in the manufacture of slaked lime, as a desiccant, in the manufacture of bleaching agents, pesticides, inorganic and organic salts of calcium, and chlorinated lime, in water purification and treatment, in paper pulp processing, in the manufacture of glass and ceramics, in deodorizing vegetable oils and in dehairing hides.

#### POTASSIUM SULFATE

CHEMICAL FORMULA:  $\text{K}_2\text{SO}_4$

GENERAL DESCRIPTION: Colorless or white crystalline solid. Readily absorbs  $\text{CO}_2$  from air.

Molecular Wt.: 174.27      Melting Pt.:  $1069^\circ\text{C}$       Boiling Pt.:  $1689^\circ\text{C}$   
Density: (Solid) 2.662 g/cc      (Gas)

Vapor Pressure:

Flash Pt.:      Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower      Upper

Solubility:

Hot Water: 24.1 g/100 ml      Cold Water: 12 g/100 ml @  $25^\circ\text{C}$

Ethanol: Insoluble      Other:

DOT Classification: \_\_\_\_\_  
 Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: From langbeinite ore,  $K_2SO_4 \cdot 2MgSO_4$ , from Searles Lake brine, by the reaction:  $2KCl + H_2SO_4 \rightarrow K_2SO_4 + 2HCl$  and by burning sulfur with excess air mixed with steam and then passing the gaseous mixture through a bed of porous KCl briquets.

USES: As fertilizers, in the manufacture of potassium alum, potassium carbonate, glass, and SBR latex rubber, in smokeless powder and as an analytical reagent.

TOXICOLOGY: Generally speaking, calcium compounds are non-toxic. Calcium chloride is completely innocuous. Calcium hydroxide is irritating to the skin and respiratory system. In the form of dust calcium hydroxide can cause dermatitis and irritation of the eyes and mucous membranes. Potassium sulfate is non-toxic.

The Threshold Limit Value (TLV) and Lethal Doses are as follows:

Contaminant	TLV, mg/M <sup>3</sup>	Lethal Dose
Calcium Chloride	-	or LD <sub>50</sub> 4000 mg/kg rat
Calcium Hydroxide	-	or LD <sub>50</sub> 7340 mg/kg rat
Potassium Sulfate	-	sc LD <sub>Ca</sub> 3000 mg/kg guinea pig
Calcium Oxide	5	

The Booz-Allen Ratings are:

Contaminant	HUMAN			ECOLOGICAL			EXPLOSION		
	Air	Water	Land	Air	Water	Land	Air	Water	Land
Calcium Chloride	1	1	1	1	2	U	2	1	2
Calcium Hydroxide	-	-	-	-	-	-	-	-	-
Potassium Sulfate	1	3	2	2	2	U	2	1	1
Calcium Oxide	3	2	2	U	2	U	1	2	1

OTHER HAZARDS: Calcium chloride and calcium oxide generate much heat when dissolved in water, due to the heat of solution and the reaction of calcium oxide to calcium hydroxide.

HANDLING, STORAGE, TRANSPORTATION: In storage, these materials must be kept tightly closed and dry because most of them absorb moisture and/or carbon dioxide from the air. Adequate ventilation and dust control should be maintained particularly for storing and handling calcium hydroxide.

DISPOSAL/REUSE: Industrially, contaminated materials will not be considered for reuse, based on economic considerations. If these materials are to be released into the environment, the following Provisional Limits should be considered:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Calcium Chloride	0.07 mg/M <sup>3</sup> as HCl	0.01 TLV for HCl
Calcium Hydroxide	0.05 mg/M <sup>3</sup>	0.01 TLV for CaO
Potassium Sulfate	0.01 mg/M <sup>3</sup> as H <sub>2</sub> SO <sub>4</sub>	0.01 TLV for H <sub>2</sub> SO <sub>4</sub>
Calcium oxide	0.05 mg/M <sup>3</sup>	0.01 TLV

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Calcium Chloride	250 ppm (mg/l) as Cl	Drinking Water Standard
Calcium Hydroxide	0.25 ppm (mg/l)	Stokinger and Woodward Method
Potassium Sulfate	250 ppm (mg/l) as SO <sub>4</sub>	Drinking Water Standard
Calcium Oxide	0.25 ppm (mg/l)	Stokinger and Woodward Method

#### EVALUATION OF WASTE DISPOSAL METHODS:

##### DISPOSAL METHODS

Carbonate precipitation of the chlorides with soda ash and recovery of the CaCO<sub>3</sub> and discharge of the brine to sewers or any other waterways.

Satisfactory

Neutralization with HCl and carbonate precipitation for contaminated CaO and Ca(OH)<sub>2</sub> and treatment of the chlorides as above or diluted and discharged to sewers or streams.


Satisfactory

Potassium sulfate and calcium chloride dilute streams may be discharged to streams.

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: The chemicals discussed in this report are probable candidates for municipal disposal and are not considered waste stream candidates for National Disposal Sites.

CAPROLACTUM

CHEMICAL FORMULA:  $C_6H_{11}NO$ , 

GENERAL DESCRIPTION: White crystalline solid. Also called 2-oxohexamethylenimine.

Molecular Wt.: 113.16 Melting Pt.: 69°C Boiling Pt.: \_\_\_\_\_

Density: (Solid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: 6 mm @ 120°C

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: \_\_\_\_\_

Ethanol: \_\_\_\_\_ Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: May be an irritant.

OTHER HAZARDS: It emits toxic fumes when heated to decomposition.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool well ventilated place.

## CARBON DISULFIDE

CHEMICAL FORMULA:  $\text{CS}_2$

**GENERAL DESCRIPTION:** Highly flammable colorless liquid. Also called carbon bisulfide, dicarbonic anhydride.

Molecular Wt.: 76.14 Melting Pt.: -112°C Boiling Pt.: 45°C

Density: (Liquid) 1.2628 gm/cc @ 20°C (Gas) 2.67 gm/l @ 20°C

Vapor Pressure: 400 mm @ 28°C 760 mm @ 26.5°C

Flash Pt.: -30°F; -22°F Autoignition Temperature: 100°F

Explosive Limits in Air (Wt%): Lower                      Upper 50%

Solubility:

Hot Water:                      Cold Water: Very slightly Ethanol: Miscible

Other: Soluble in chloroform, ether, benzene, carbon tetrachloride and oils.

DOT Classification: Flammable liquid, red label

Coast Guard Classification: Flammable liquid, red label

**MANUFACTURE:** By the reduction of sulfur with methane in the presence of a silica-gel catalyst at 570 to 620°C and 20 to 30 psig.

**USES:** Essential ingredient of xanthates used in the manufacture of viscose rayon, cellophane, cellulose sponge, non-woven fabrics and others. It is the raw material for carbon tetrachloride. Carbon disulfide is an excellent solubilizer for oils, waxes, sulfur and sulfur compounds. Used for removing paraffin from pipelines and oil well casings. Used for extraction of vegetable oils. Absorbent clays and petroleum catalysts are regenerated with  $\text{CS}_2$ . Used in emulsion polymerization, as nitrocellulose and polyvinyl solvents, in recovery of sulfur ores, and as a solvent in vaporphase curing of rubber sheets. Used in agriculture as grain fumigants, soil conditioners, herbicides, rodenticides and nematocides. Used as insecticidal fumigant for nursery stocks and soil treatment against beetles. Used in treatment of wood to improve flexural strength, as a corrosion inhibitor and in deworming of livestock.

**TOXICOLOGY:** Carbon disulfide poisoning is usually caused by breathing the fumes. Poisoning can be through the skin. Skin contact can cause local inflammation.

The chief toxic effect is on the central nervous system, acting as a narcotic an anesthetic in acute poisoning with death following from respiratory failure. In chronic poisoning, the effect on the nervous system is one of central and peripheral damage, which may be permanent if the damage has been severe. A secondary effect may be anemia. Neuritis and disturbance of vision are the commonest early changes. Often there is pain in the affected parts, particularly in the limbs. Increasing loss of strength follows. Wasting of muscles may occur. Mental symptoms vary from simple excitation or depression irritability in mild cases to mental deterioration, Parkinsonian paralysis and even insanity. These changes are accompanied by

insomnia, loss of memory and personality changes. Chronic fatigue is a very common complaint.

The Threshold Limit Value (TLV) and Maximum Allowable Concentration are 20 ppm and 60 mg/M<sup>3</sup> respectively.

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	2	3	2	2	1	2

OTHER HAZARDS: Carbon disulfide is a highly flammable, volatile liquid with a low flash point (-22°F), wide explosive range and an autoignition temperature of 100°C (212°F). Contact with exposed steam lines or the surface of an ordinary electric light bulb may cause ignition. Carbon disulfide vapor when mixed with air or oxygen in certain concentrations, is flammable and explosive. Carbon disulfide reacts violently or explosively with azides, chlorine in the presence of iron, chlorine monoxide and fluorine.

HANDLING, STORAGE, TRANSPORTATION: Due to the high degree of flammability and extreme volatility of carbon disulfide, strict ICC precautions regulate the loading, handling, transporting and labelling of containers. Non-sparking tools and hose connections must be used and the container should be grounded to prevent accumulation of static electricity. Transfer is accomplished by water padding, nitrogen displacement or pumping. Vapors should be purged from empty drums with steam while empty tank cars must have four "Dangerous Empty" placards in place.

Drums and other containers of carbon disulfide should be stored in a cool, dry, and well-ventilated place away from acute fire hazards. Storage should be limited to minimize the hazard and the storage area should be of fire-resistant construction and equipped with sprinklers and/or portable fire extinguishers.

DISPOSAL/REUSE: The major use (65%) of carbon disulfide is in the production of cellophane and rayon by extraction of the desired compounds as xanthites. After extraction, the carbon disulfide is regenerated and reused.

When carbon disulfide is used as a chemical intermediate in production, any unreacted material is carefully recovered for reuse.

Carbon disulfide used as an extraction solvent in emulsion polymerization and in extractive regeneration is recycled indefinitely.

In the agricultural field, mixtures of carbon disulfide escape directly into the environment and cannot be recovered.

Recommended Provisional Limits for carbon disulfide in the environment are as follows:

<u>Carbon Disulfide in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.2 ppm	.01 TLV
Water and Soil	1.0 ppm (mg/l)	Stokinger and Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES: The industries that use carbon disulfide as a chemical intermediate or as a solvent recycle as much material as possible. This is the method of choice, whenever possible.

DISPOSAL METHOD

EVALUATION

Controlled incineration with SO<sub>2</sub> scrubber

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: The wastes generated in the manufacture and use of carbon disulfide can best be handled and treated at or near the site or generation by recycling or incineration. Since these methods represent common industrial technology, carbon disulfide is not judged to be a candidate waste stream constituent for National Disposal Sites.



## CHLORINE

CHEMICAL FORMULA:  $\text{Cl}_2$

GENERAL DESCRIPTION: Greenish yellow gas, liquid or crystalline solid.  
Molecular Wt.: 70.906      Melting Pt.:  $-101^\circ\text{C}$       Boiling Pt.:  $-34.05^\circ\text{C}$   
Density: (Solid) 1.468 g/cc @  $0^\circ\text{C}$       (Gas) 3.214 g/l @  $0^\circ\text{C}$   
Vapor Pressure: 85.46 psia @  $70^\circ\text{F}$ , 151.12 psia @  $105^\circ\text{F}$ , 174.69 psia @  $115^\circ\text{F}$   
Flash Pt.:      Autoignition Temperature:        
Explosive Limits in Air (Wt%): Lower      Upper        
Solubility:  
    Hot Water: 0.54% @  $30^\circ\text{C}$       Cold Water: 0.8% @  $10^\circ\text{C}$   
    Ethanol: Reacts      Other: Soluble in alkaline water  
DOT Classification: nonflammable gas, green label, 150 lbs  
Coast Guard Classification: non flammable gas, green gas label  
MCA Warning Label  
IATA Classification: Nonflammable gas, green label  
    Not acceptable (passenger) 70 kilograms (cargo)

MANUFACTURE: Diaphragm and mercury electrolytic cells and molten salt cells.

USES: Hydrochloric acid manufacture, organic chlorinations, pulp bleaching, metallurgical processing and bleach manufacture:

TOXICOLOGY: (Human Toxicology)-Chlorine is an extremely powerful ves-  
sant and respiratory irritant. Its action is that of a severe irritant  
rather than as a toxic agent; high concentrations cause pulmonary edema which  
may be fatal. Lower concentrations cause coughing, smarting of the eyes,  
chest discomfort, nausea, and vomiting. The effects of different concen-  
trations are shown below:

<u>EFFECT</u>	<u>CHLORINE, ppm</u>
Min. Conc. detectable by odor	3.5
Min. Conc. causing throat irritation	15
Min. Conc. causing coughing	30
Min. Conc. causing slight symptoms after several hours	1
Max. Conc. that can be breathed for one hour without damage	4
Conc. dangerous in 30 minutes	40-60
Conc. likely to be fatal after a few deep breaths	1,000
TLV for 8-hour exposure	1

Liquid chlorine causes severe irritation and blistering of the skin.

(Aquatic Toxicology)-The toxicity of chlorine solutions in water is usually  
not a problem. Dissolved chlorine reacts rapidly with organic and other

oxidizable substances in natural streams and chlorine escapes from water at a pH of less than 7 at a rapid rate.

(Plant Toxicology)-At concentrations of 0.1 to 1.5 ppm of chlorine gas, the most common symptoms of chlorine poisoning of plants have been found to be necrosis and bleaching of the foliage. Bleaching of the leaves occurs from exposure to low concentrations of chlorine.

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	2	1	2	3	U	2	2	2

OTHER HAZARDS: Most chlorine is very corrosive to all of the common materials of construction except high silica iron, monel, hasteloy C, silver and noble platinum metals. At low pressures wet chlorine can be handled in chemical stoneware, glass, porcelain, and certain plastics.

Chlorine is capable of supporting combustion of many materials. It also reacts very rapidly with many compounds, both organic and inorganic.

HANDLING, STORAGE, TRANSPORTATION: Adequate procedures for safe handling; transportation and storage of chlorine are provided by Matheson in the Matheson Gas Data Book. It is shipped in 100-lb and 150-lb. steel cylinders, single unit tank cars of 30,000 lbs and multi-unit tank cars of 15 one-ton units.

DISPOSAL REUSE: Current practice in chlorine disposal usually involves recycling, recovery, alkaline scrubbing, or venting. The safe disposal of chlorine must take into account the safe release of chlorine to the environment. The Recommended Provisional Limits for chlorine in the atmosphere, in potable water sources, and in marine habitats are:

<u>Chlorine as</u> <u>Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.03 mg/M <sup>3</sup>	0.01 TLV
Water and Soil	0.15 mg/l	Stokinger & Woodward Method
Marine Habitats	0.003	0.01 Fish Toxicity

EVALUATION OF WASTE MANAGEMENT PRACTICES: In 1969, 9.5 million tons of chlorine were produced with an estimated 78,200 tons being emitted to the atmosphere. A summary of the chlorine emissions and their sources is presented below:

<u>SOURCE</u>	<u>CHLORINE EMISSIONS, TONS</u>
Chlorine Manufacture	47,000
Hydrochloric Acid Manufacture	800
Chemical and Industrial Processes:	
Organic Chlorination	8,500
Pulp Bleaching	18,000
Metallurgical Processing	2,000
Bleach Manufacture	900
Miscellaneous	1,000
<u>DISPOSAL METHODS</u>	<u>EVALUATION</u>
Recycling and recovery	Satisfactory
Water scrubbing followed by alkaline scrubbing of dilute streams	Satisfactory
Silica gel absorption	Satisfactory
Reaction with sulfur	Not recommended due to the disposal problem of sulfur chlorides produced.
Carbon tetrachloride scrubbers	Not recommended due to spills and losses of carbon tetrachloride.

APPLICABILITY TO NATIONAL DISPOSAL SITES: Chlorine waste can be handled adequately at industrial site. Some capacity will be needed at National Disposal Sites to process occasional tank-car or smaller lots which are required to be disposed of in a safe, pollution free manner and for secondary gas streams generated within the National Disposal Site as a result of processing other waste.

## HALOGENATED HYDROCARBONS

(Chloroform, Epichlorohydrin, and Chlorinated Hydrocarbons in general)

### CHLOROFORM

CHEMICAL FORMULA:  $\text{CHCl}_3$

GENERAL DESCRIPTION: Colorless liquid with a heavy, ethereal odor. IUC Name: Trichloromethane.

Molecular Wt.: 119.38 Melting Pt.:  $-63.5^\circ\text{C}$  Boiling Pt.:  $61.2^\circ\text{C}$

Density: (Liquid) 1.4916 g/cc @  $18^\circ\text{C}$  (Gas)

Vapor Pressure: 15 psig @  $84^\circ\text{C}$ ; 60 psig @  $120^\circ\text{C}$

Flash Pt.: Nonflammable Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Slightly Cold Water: Slightly Ethanol: Miscible

Other: Miscible in all proportions in ether, acetone, benzene, and ligroin.

DOT Classification:

Coast Guard Classification:

### EPICHLOROHYDRIN

CHEMICAL FORMULA:  $\text{OCH}_2\text{CHCH}_2\text{Cl}$

GENERAL DESCRIPTION: Colorless, mobile liquid, irritating chloroform-like odor. IUC Name: 1-chloro-2,3-epoxypropane. Also called  $\alpha$ -epichlorohydrin,  $\gamma$ -chloropropylene oxide, chloromethyloxirane.

Molecular Wt.: 92.53 Melting Pt.:  $-25.6^\circ\text{C}$  Boiling Pt.:  $116.5^\circ\text{C}$

Density: (Liquid) 1.1801 g/cc @  $20^\circ\text{C}$  (Gas) 3.29 g/l

Vapor Pressure: 10 mm @  $16.6^\circ\text{C}$  100 mm @  $62^\circ\text{C}$  400 mm @  $98^\circ\text{C}$

Flash Pt.:  $105^\circ\text{F}$  (O.C.) Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Decomposes Cold Water: Slightly Ethanol:  $\infty$

Other: Soluble in benzene, ether ( $\infty$ ), chloroform, trichloroethylene, carbon tetrachloride, immiscible in petroleum hydrocarbons.

DOT Classification:

Coast Guard Classification:

MCA warning label

MANUFACTURE: Most chlorinated hydrocarbons are produced by addition and/or substitution reactions..

USES: Chlorinated hydrocarbons are used as refrigerant propellants, as sol-

vents, soil fumigants, insecticides, medical and veterinary uses and in organic synthesis of other compounds.

Chloroform is one of the chlorinated hydrocarbons used in the medical and veterinary field and to make refrigerants.

Epichlorohydrin is used in epoxy resins.

**TOXICOLOGY:** In aliphatic hydrocarbons the substitution of a chlorine atom greatly increases the anesthetic action of the compound and the chlorine derivative is usually less specific in its action and may affect other tissues of the body in addition to the central nervous system. In many cases the chlorine derivative is quite toxic. The chlorinated hydrocarbons are also irritants to the eyes and mucous membranes. Repeated exposure to the skin may cause dermatitis and may be absorbed through the skin. Chloroform, in addition to its narcotic effect, may cause damage to the liver heart & kidneys. It is hard to predict the toxicity of the aromatic hydrocarbons. In most cases the aromatic chlorine compounds are no more toxic and are frequently less toxic than the corresponding aromatic hydrocarbons.

The Threshold Limit Values (TLV) and Maximum Allowable Concentrations are:

	<u>ppm</u>	<u>TLV</u> <u>mg/M<sup>3</sup></u>	<u>MAC</u> <u>ppm</u>
Chloroform	25	120	50
Epichlorohydrin	5	19	--

The Booz-Allen Ratings on these materials are:

	<u>Air</u>	<u>HUMAN</u> <u>Water</u>	<u>Land</u>	<u>Air</u>	<u>ECOLOGY</u> <u>Water</u>	<u>Land</u>	<u>Air</u>	<u>EXPLOSIVE</u> <u>Water</u>	<u>Land</u>
Chloroform	3	1	1	2	3	U	2	2	2
Epichlorohydrin	3	3	3	2	3	U	2	1	2

**OTHER HAZARDS:** When heated to decomposition all chlorohydrocarbons give off noxious and highly toxic fumes, including chloroacids, free chlorine and phosgene. They will also react explosively when they come into contact with alkaline and alkaline earth metals. They may be very corrosive to aluminum.

**HANDLING, STORAGE, TRANSPORTATION:** Handle in a well-ventilated area. Wear protective clothing and respirators when necessary, avoid skin contact and inhalation. In cases of accidental contact, all contaminated clothing should be removed instantly and the skin washed thoroughly with soap and water.

Store in a dry, cool, well-ventilated area away from acute fire hazards.

DISPOSAL/REUSE: In manufacture there is a residue left which needs disposal although some material is recycled or reclaimed. In most cases of use however, the materials are lost to the atmosphere. Users of large volume chemical intermediates, including chloroform and epichlorohydrin recycle any unused materials. Usually these materials do not come into contact with aqueous media, so discharge of dilute aqueous streams is not a problem.

For disposal of these materials the following Provisional Limits are recommended:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Chloroform	0.25	1.2	0.01 TLV
Epichlorohydrin	0.05	0.19	Based on similar compounds

<u>Contaminant in</u> <u>Water and Soil</u>	<u>Provisional Limit</u> <u>ppm or mg/l</u>	<u>Basis for Recommendation</u>
Chloroform	6	Stokinger & Woodward Method
Epichlorohydrin	0.95	Stokinger & Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES: Recycling or reclaiming is the preferred method of handling waste from the chlorinated hydrocarbons when possible.

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Incineration with the use of an acid scrubber.	Satisfactory
Landfill of residue and sludges	Not satisfactory unless totally isolated from ground and surface water due to long term hazard.

APPLICABILITY TO NATIONAL DISPOSAL SITES: These materials can be handled best at the site of generation by incineration. Except in extreme cases these compounds are not considered candidates for National Disposal Site disposal.

## CHROMIC ACID

CHEMICAL FORMULA :  $\text{Cr O}_3$

GENERAL DESCRIPTION: Red crystalline solid. Poisonous, powerful oxidizer.

IUC Name: Chromium trioxide. Also called chromic anhydride

Molecular Wt.: 100.01 Melting Pt.: 197°C d Boiling Pt.: \_\_\_\_\_

Density: (Solid) 2.70 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: 206.7 g/100 g @ 100°C Cold Water: 164.9 g/100 g @ 0°C

Ethanol: \_\_\_\_\_ Other: H<sub>2</sub>SO<sub>4</sub>

DOT Classification: Oxidizing material\*

Coast Guard Classification: Oxidizing material

\* In solution DOT classification is corrosive liquid, white label, 1 gallon maximum.

MANUFACTURE: Produced by the reaction of sodium dichromate and sulfuric acid and by sulfuric acid charged with sulfur dioxide.

USES: Almost exclusively in the metal finishing industry. About half of this is used in direct decorative chromic plating. Annual consumption is approximately 30,000 tons with 90% in the metal treating industry and the remaining 10 percent used for catalyst manufacture, refractory or exported.

SOURCES AND TYPES OF WASTE: Large amounts from the metal finishing and chrome plating industry.

TOXICOLOGY: Very corrosive and strong oxidizer. In contact with skin or mucous membranes, it can cause ulcerous lesions which heal slowly. The salts of chromic acid have also been associated with lung cancer. The Threshold Limit Value for hexavalent chromates is 0.1 mg/M<sup>3</sup> in air. Drinking water should contain no more than 0.05 ppm. Should be kept away from terrestrial plant life. No exact information on aquatic plant and animal life, but is probably very harmful.

The Booz-Allen Ratings for chromic acid are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	2	3	U	2	1	2

OTHER HAZARDS: Should not be mixed with organic or reducing agents. Even

dilute organic solutions can produce violent reactions if heated. Concentrated aqueous solutions will attack some metals.

HANDLING, STORAGE, TRANSPORTATION: Should be stored away from high temperatures or reducing agents. The creation of  $\text{CrO}_3$  dust must be avoided during handling, storage and transportation. Workers should be adequately protected from contact of chromium trioxide with skin, eyes or internal organs. Adequate supervising control and employee education of the hazards is recommended.

DISPOSAL/REUSE: Discharge into open waterways is severely restricted. U.S. Public Health Service recommends 0.05 ppm as upper limit in drinking water. The upper limits of hexavalent chromium discharge into municipal sewage systems is normally set at about 0.05 ppm.

For the safe disposal of chromic acid into the environment, the following Provisional Limits are recommended:

<u>Chromic Acid in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.001 mg/M <sup>3</sup> as $\text{CrO}_3$	0.01 TLV
Water and Soil	0.05 ppm (mg/l) as Cr	Drinking Water Standard

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHODS</u>	<u>EVALUATION</u>
Reduction and precipitation as hydroxides, with disposal of sludges in either approved landfills or by incineration.	Satisfactory
Ion exchange	Satisfactory
Electro chemical reduction	Satisfactory
Direct precipitation by use of barium or lead salts	Not satisfactory, potential handling problems due to poisonous heavy metals.
Ion flotation, electrodialysis, activated carbon absorptions, liquid-liquid extraction, activated carbon reduction, and reverse osmosis.	Promising methods in various styles of development

APPLICABILITY TO NATIONAL DISPOSAL SITES: Chromic acid is considered as a candidate waste stream constituent for National Disposal Sites.



COPPER CHLORIDE

CUPRIC CHLORIDE

CHEMICAL FORMULA:  $\text{Cu Cl}_2$

GENERAL DESCRIPTION: Yellowish-brown, hygroscopic powder.

Molecular Wt.: 134.45 Melting Pt.: 498°C Boiling Pt.: 993° C  
decomposes to  $\text{CuCl}$

Density: (Solid) 3.054 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 107.9 g/100 ml @ 100°C Cold Water: 70.6 g/100 ml @ 0°C

Ethanol: 53 g/100 ml @ 15°C Other: 68 g/100 ml in methanol @ 15°C

DOT Classification:

Coast Guard Classification:

IATA Classification: Other restricted articles class B, no label required  
12 kilograms (passenger), 45 kilograms (cargo)

USES: Many copper containing compounds are used as fungicides.

CUPROUS CHLORIDE

CHEMICAL FORMULA:  $\text{Cu Cl}$

GENERAL DESCRIPTION: White crystalline solid. Also called nantokite.

Molecular Wt.: 99.00 Melting Pt.: 422°C Boiling Pt.: 1366°C

Density: (Solid) 3.53 g/cc (Gas)

Vapor Pressure: 1 mm at 546°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Cold Water: Insoluble

Ethanol: Other: Soluble in  $\text{HCl}$  and  $\text{NH}_4\text{OH}$ .

DOT Classification:

Coast Guard Classification:

USES: Many copper containing compounds are used as fungicides.

TOXICOLOGY: May cause irritation of the skin and conjunctivae which may be on an allergic basis. Inhalation of copper dust has caused, in animals, hemolysis of the red blood cells, deposition of hemofuscin in the liver and pancreas, and injury to the lung cells. Injection of the dust has caused

cirrhosis of the liver and pancreas, and a condition closely resembling hemochromatosis, or bronzed diabetes. However, considerable trial exposure to copper compounds has not resulted in such disease.

OTHER HAZARDS: Chlorides when heated to decomposition or on contact with acids or acid fumes evolve highly toxic chloride fumes.

CUMENE HYDROPEROXIDE

CHEMICAL FORMULA:

GENERAL DESCRIPTION: Colorless to pale-yellow liquid. Also called  $\alpha$ -dimethyl benzyl hydroperoxide.

Molecular Wt.: \_\_\_\_\_ Melting Pt.: \_\_\_\_\_ Boiling Pt.: 153°C

Density: (Liquid) 1.05 g/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: 175°F Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: \_\_\_\_\_ Ethanol: \_\_\_\_\_

Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

## DIAZINON

CHEMICAL FORMULA:  $C_{12}H_{22}N_2O_3PS$

GENERAL DESCRIPTION: Liquid with faint ester-like odor. Also called G-24, 480, O, O-diethyl-O, 2-isopropyl, 4-methyl-pyrimidyl thiophosphate.

Molecular Wt.: 304.4 Melting Pt.: Boiling Pt.: 84°C @0.002

Density: (Liquid) 1.116 g/cc @ 20°C (Gas) /mm

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Cold Water: Ethanol:

Other:

DOT Classification:

Coast Guard Classification:


IATA Classification: Other restricted articles, class A, no label required  
no limit (passenger and cargo)

TOXICOLOGY: Very toxic by absorption through the skin inhalation or by ingestion. It is similar to parathion which can cause death from a small amount being splashed on the skin if not washed off immediately and all contaminated clothing is not removed. All of the organophosphorus insecticides function by cholinesterase inhibition. This enzyme is an essential constituent of the nervous system. Symptoms of parathion poisoning are headache, giddiness, blurred vision, weakness, nausea, cramps, diarrhea, discomfort of the chest, sweating, miosis, tearing, salivation, pulmonary edema, cyanosis, papilledema, convulsions, coma and loss of reflexes and sphincter control.

DINITROBENZENE

Three isomers exist

o - DINITROBENZENE

CHEMICAL FORMULA:  $C_6H_4(NO_2)_2$  

GENERAL DESCRIPTION: Colorless to yellowish crystalline solid. IUC Name: 1,2 - dinitrobenzene

Molecular Wt.: 168.11 Melting Pt.: 118°C Boiling Pt.: 302.8°C  
Density: (Solid) 1.571 g/cc at °C (Gas) 5.79 g/l @ 770 ppm

Vapor Pressure: -

Flash Pt.: 302°F Autoignition Temperature: \_\_\_\_\_


Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:  
Hot Water: \_\_\_\_\_ Cold Water: Slightly Ethanol: Soluble  
Other: Very soluble in chloroform and hot alcohol

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

m - DINITROBENZENE

CHEMICAL FORMULA:  $C_6H_4(NO_2)_2$  

GENERAL DESCRIPTION: Colorless to yellowish crystalline solid. IUC Name: 1,3 - dinitrobenzene

Molecular Wt.: 168.11 Melting Pt.: 90°C Boiling Pt.: 291°C  
Density: (Solid) 1.571 g/cc @ 0°C (Gas) @ 756 mm

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_


Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:  
Hot Water: \_\_\_\_\_ Cold Water: Insoluble Ethanol: Very soluble  
Other: Soluble in ether, chloroform. Very soluble in benzene.

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

p - DINITROBENZENE

CHEMICAL FORMULA:  $C_6H_4(NO_2)_2$  

GENERAL DESCRIPTION: Colorless to yellowish crystalline solid. IUC Name: 1, 4 - dinitrobenzene.  
Molecular Wt.: 168.11 Melting Pt.: 172°C 90°C Boiling Pt.: 299°C @  
Density: (Solid) 1.625 g/cc @ 20°C (Gas) /777 mm  
Vapor Pressure: \_\_\_\_\_  
Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility: \_\_\_\_\_  
Hot Water: \_\_\_\_\_ Cold Water: Insoluble  
Ethanol: Slightly soluble Other: Soluble in chloroform and acetic acid  
DOT Classification: \_\_\_\_\_  
Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Meta-dinitrobenzene is made by direct nitration of benzene using nitric acid and sulfuric acid. Ortho-and para-dinitrobenzene are prepared by oxidation of primary aromatic amines.

USES: As explosives.

TOXICOLOGY: Dinitrobenzene is very toxic. It has an irritating effect on the respiratory system and causes the skin to become bluish in color. It produces anemia, jaundice, enlarged liver or yellow atrophy, degeneration of kidneys and injury to the central nervous system. 1,2-Dinitrobenzene has a Threshold Limit Value of 1 mg/M<sup>3</sup> and it may be absorbed through the skin. 1, 4 dinitrobenzene has an oral LD in cats of 29.4 mg/kg.

The Booz-Allen Ratings for ortho-dinitrobenzene are as follows:

<u>MATERIAL</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
o - dinitrobenzene	3	3	3	U	3	U	3	2	2

OTHER HAZARDS: Severe explosion hazards. When heated to decomposition they emit highly toxic fumes of nitrogen and explode.

HANDLING, STORAGE, TRANSPORTATION: When handling avoid contact with the skin. Use protective clothing. Protect from shock and heat. In the Code of Federal Regulations, Title 49, Transportation, these material are classed as Poison B.

DISPOSAL/REUSE: Disposal or reuse of waste streams containing these compounds must take into account their explosive and toxic nature.

Recommended Provisional Limits for dinitrobenzene are as follows:

<u>Dinitrobenzene in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.01 mg/M <sup>3</sup>	.01 TLV
Water and Soil	0.05 ppm (mg/l)	Stokinger & Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES:

METHODS OF DISPOSAL

EVALUATION

CONCENTRATED NITROBENZENE

Dilution with other combustible materials which are not explosive and incineration under controlled condition, using scrubbers for the effluent gases.

Satisfactory

DILUTE DINITROBENZENE


Concentrate waste streams and dispose of by treating as discussed for concentrated dinitrobenzene.

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Dinitrobenzene can be treated at the point of generation and is not considered to be a waste stream constituent for National Disposal Sites.

## DINITROTOLUENE

There are five isomers of dinitrotoluene. The description will be given for only 2, 4 - dinitrotoluene.



GENERAL DESCRIPTION: Yellow crystalline solid. Also called 1-methyl-2-4 di-nitrotoluene.

Molecular Wt.: 182.13 Melting Pt.: 69.5°C Boiling Pt.: 300°C  
 Density: (Solid) 1.521 g/cc (Gas) \_\_\_\_\_ (slightly decomposes)

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Cold Water 0.02 g/100 ml @ 22°C Hot Water \_\_\_\_\_ Ethanol 30.4 g/100 ml  
 @ 15°C Others Soluble in ether

DOT Classification: Explosive class 2, group D

Coast Guard Classification: \_\_\_\_\_

IATA Classification: Poison B, poison label.  
1 litre (passenger), 220 litres (cargo)

MANUFACTURE: By the stepwise nitration of toluene with mixed acid (sulfuric and nitric acids).

USES: In explosives, propellents polyurethanes and as a dye intermediate. Much is reduced to the diamine and then reacted with phosgene to make toluene diisocyanate

TOXICOLOGY: Dinitrotoluene can enter the body by inhalation, ingestion and absorption through the skin. Skin contact may result in staining of the skin and dermatitis. It may cause irritation of mucous membranes and of the eyes. Symptoms of dinitrotoluene poisoning are dermatitis, gastritis and methemoglobinemia which in turn give rise to cyanosis aplastic anemia and toxic hepatitis. The Threshold Limit Value (TLV) is 1.5 mg/M<sup>3</sup> and the Booz-Allen Ratings for 2-4 dinitrotoluene are:

<u>HUMAN</u>			<u>ECOLOGY</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	2	U	3	U	3	1	2

OTHER HAZARDS: Dinitrotoluene can be detonated by a very strong initiator.



It may explode when involved in a fire. Fire fighting should be done by remote control. Water, carbon dioxide, dry sodium carbonate or carbon tetrachloride may be used to extinguish burning dinitrotoluene. Its hazard properties are:

Explosion temperature @ 5 seconds:	310°C
Vacuum Stability @ 120°C :	0.04 cc/hr
Friction @ 8 ft/sec :	950 lb.

HANDLING, STORAGE, TRANSPORTATION: When handling, protective clothing, rubber gloves and eye protection should be worn. Avoid skin and eye contact inhalation and ingestion. Dinitrotoluene is shipped in bottles, cans, metal barrels, drums and wooden barrels or kegs with liners.

DISPOSAL/REUSE: For the disposal of dinitrotoluene waste, the following Recommended Provisional Limits for dinitrotoluene in the environment are:

<u>Dinitrotoluene as a</u> <u>Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.05 ppm (0.015 mg/M <sup>3</sup> )	.01 TLV
Water and Soil	0.075 mg/l	Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### METHODS OF DISPOSAL

##### EVALUATION

Open burning	Unacceptable. This method results in liberation of NO <sub>x</sub> .
Controlled incineration using NaHCO <sub>3</sub> or sand-soda ash mixture mixed with the waste and using an afterburner and an alkaline scrubber	Satisfactory
Controlled incineration using a solvent for the waste and using an afterburner and an alkaline scrubber	Satisfactory


APPLICABILITY TO NATIONAL DISPOSAL SITES: It is not anticipated that a National Disposal Site will be necessary for dinitrotoluene. However, National Disposal Sites will probably be necessary for small quantities of explosive and propellant wastes containing dinitrotoluene.

DIOXANE, PROPYLENE OXIDE, ETHERS

DIOXANE

There are two possible isomers m-Dioxane and p-Dioxane.

m - DIOXANE



GENERAL DESCRIPTION: Colorless liquid. Also called 1,3-dioxane, trimethylene glycol methylene ether; trimethylene methylene dioxide

Molecular Wt.: 88.10 Melting Pt.: ---- Boiling Pt.: 105°C

Density: (Liquid) 1.03422 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_


Hot Water: \_\_\_\_\_ Cold Water:  $\infty$  Ethanol:  $\infty$

Other:  $\infty$  in ether \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

p - DIOXANE



GENERAL DESCRIPTION: Colorless liquid. Also called 1,4-dioxane; diethylene oxide, diethylene dioxide, glycol ethylene ether.

Molecular Wt.: 88.10 Melting Pt.: 10°C Boiling Pt.: 101.1°C

Density: (Liquid) 1.0353 g/cc @ 20°C (Gas) 3.03 g/l

Vapor Pressure: 40 mm @ 25.2°C 100 mm @ 45.1°C

Flash Pt.: 54°F (C.C.) Autoignition Temperature: 45.1°C

Explosive Limits in Air (Wt%): Lower 1.97% Upper 22.2%

Solubility: \_\_\_\_\_

Hot Water:  $\infty$  Cold Water:  $\infty$  Ethanol:  $\infty$

Other: Ether, Acetone, Organic solvents acetic acid.

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MCA warning label \_\_\_\_\_

IATA: Flammable liquid, red label

1 lit max. (passenger), 40 lit max. (cargo)

MANUFACTURE: Amsco Division; Ashland Chemical Co.; J.T. Baker Chemical Co.;

Corco Chemical Co.; Grant Chemical Co.; M C & B Manufacturing Chemists; Southland Solvents and Chemical Co.; Stoney-Mueller, Inc.; Union Carbide Corporation.

#### PROPYLENE OXIDE

CHEMICAL FORMULA:  $\text{OCH}_2\text{CHCH}_3$

GENERAL DESCRIPTION: Colorless liquid; ethereal odor. Also called 1,2-Epoxypropane, propane oxide.

Molecular Wt.: 58.08 Melting Pt.:  $-104.4^\circ \text{C}$  Boiling Pt.:  $33.9^\circ \text{C}$

Density: (Liquid) 0.8304 (Gas) 2.0 g/l

Vapor Pressure: 400 mm @  $17.8^\circ \text{C}$  760 mm @  $33.9^\circ \text{C}$

Flash Pt.:  $-35^\circ \text{F}$  (T.O.C.) Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower 2.1% Upper 21.5%

Solubility:

Hot Water: Soluble Cold Water: Soluble Ethanol:  $\infty$

Other:  $\infty$  in ether.

DOT Classification: Flammable liquid, red label

Coast Guard Classification: Flammable liquid, red label

IATA Classification: Flammable liquid, red label

1 litre max. (passenger), 40 litres (cargo).

#### ETHERS

There are many ethers. They will be treated generally in this report.

CHEMICAL FORMULA:  $\text{R-O-R'}$  where R and R' are the same or different alkyl or aryl groups.

MANUFACTURE: Catalytic dehydration of alcohols is used principally for the production of simple ethers. The Williamson ether synthesis may be used to prepare either simple or mixed ethers (where R is not the same as R').

USES: Ethers are used as solvents for organic reactions and extractions, as plasticizers, as vehicles for other products, as solvents of many organic compounds, as varnish and paint removers, as high boiling point solvents for gums resins waxes in lubricating oils, as insecticides, as cleaning solutions, in leather finishing, as motor fuel additives, in the synthesis of other organic compounds, and in the manufacture of pharmaceuticals, smokeless powder, and rubber cements. Diethyl ether is used as a general anesthetic in surgery.

Dioxane is used as a solvent for cellulose acetate, ethyl cellulose, benzyl cellulose, resins, oils, waxes, oil and spirit-soluble dyes and many other

organic and some inorganic compounds.

Propylene oxide is used in the manufacture of alkanoamines, polypropylene glycols, propylene glycol and in paint removers.

**TOXICOLOGY:** The principal hazard in industrial use and handling of the ethers is from inhalation of their vapors. As a class, they do not penetrate the skin in harmful amounts nor are they irritating to the skin. The simpler ethers such as ethyl ether, isopropyl ether, etc., are powerful narcotics which in large doses can cause death.

The Threshold Limit Values (TLV) for dioxane and propylene oxide are:

	<u>TLV</u>
Dioxane	100 ppm
Propylene Oxide	100 ppm

The Booz-Allen Ratings are as follows:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSIVE</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Dioxane	3	3	2	1	U	U	2	1	2
Propylene Oxide	2	2	2	2	1	U	2	1	2
Ethers	1	1	1	1	U	U	2	1	2

**OTHER HAZARDS:** The more volatile ethers, such as ethyl and methyl ether are particularly dangerous fire hazards because of their low ignition and flash points. Peroxides, which form in ethers upon standing pose the additional threat of detonation when an ether is heated after prolonged storage.

**HANDLING, STORAGE, TRANSPORTATION:** Store in a cool well-ventilated area out of the direct rays of the sun and away from heat and open flame and with "NO SMOKING" signs posted. Remove all leaking containers to an isolated well ventilated area or out doors and transfer to other suitable containers. All spills should be flushed away promptly with water.

Before starting a process involving distillation or evaporation a standard test must be passed and the peroxides removed from ethers failing to pass the test.

**DISPOSAL/REUSE:** The following Recommended Provisional Limits are given for the safe disposal of dioxane and propylene oxide:

<u>Contaminant in Air</u>	<u>Provisional Limits</u>	<u>Basis for Recommendation</u>
Dioxane	1.0 ppm (3.6 mg/M <sup>3</sup> )	0.01 TLV
Propylene Oxide	1.0 ppm (2.4 mg/M <sup>3</sup> )	0.01 TLV

<u>Contaminant in Water and Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Dioxane	18 ppm (mg/l)	Stokinger and Woodward Method
Propylene oxide	12 ppm (mg/l)	Stokinger and Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES: In all cases it would be better to recycle these materials when possible.

#### DISPOSAL METHOD

#### EVALUATION

Controlled burning, at a safe distance, of concentrated waste containing no peroxides.

Satisfactory

Destroying filled containers of concentrated peroxide containing waste using rifle fire at 100 feet or more away to perforate the containers. This should be done a safe distance away from habitation and where no harm can come to the surroundings. A blasting cap can be used instead of rifle fire.

Satisfactory

Dilute organic waste can be incinerated if the burning temperature is high enough to reduce the waste to CO<sub>2</sub> and water.


Satisfactory

Incineration of dilute aqueous waste at 1500° F

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Most of the wastes from these materials can be handled and treated at the site of generation. They are not considered to be candidates for National Disposal Sites.

# DIPHENYLAMINE

CHEMICAL FORMULA:  $(C_6H_5)_2NH$ , 

GENERAL DESCRIPTION: Colorless crystals with a floral odor. Also called N - phenylaniline, anilinobenzene.

Molecular Wt.: 169.24 Melting Pt.: 52.9°C Boiling Pt.: 302°C

Density: (Solid) 1.16 g/cc @ 20°C (Gas) 5.82 g/l

Vapor Pressure: 1 mm @ 108.3°C

Flash Pt.: 307°F (C.C.) Autoignition Temperature: 846°F

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Insoluble Cold Water: Insoluble Ethanol: Soluble

Other: Freely soluble in propyl alcohol, benzene, ether, glacial acetic acid, carbon disulfide.

DOT Classification:

Coast Guard Classification:

MANUFACTURE: Produced by heating aniline with aniline hydrochloride at 210 to 240°C. American Cyanamide and E.I. DuPont de Nemours operate commercial diphenylamine manufacturing facilities.

USES: As a rubber antioxidant, as an intermediate for pharmaceuticals, as an insecticide when fused with sulfur, as a stabilizer for explosives and in the preparation of azo dyes.

TOXICOLOGY: Diphenyl amine is highly toxic when ingested, inhaled or absorbed through the skin. It may be inhaled as the dust or vapor and is irritating to the mucous membranes. Symptoms of diphenylamine poisoning are bladder trouble, tachycardia, hypertension and skin trouble. The Threshold Limit Value (TLV) for diphenyl amine is 10 mg/M<sup>3</sup>.

The Booz-Allen Ratings are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
3	3	1	2	U	U	2	1	1

OTHER HAZARDS: Diphenyl amine emits highly toxic fumes when heated to decomposition.

HANDLING, STORAGE, TRANSPORTATION: Protective clothing, safety glasses, and respirators should be worn when handling diphenylamine if dust exposure is possible. Direct skin contact should be avoided.

Bulk diphenylamine may be stored in steel equipment for extended periods provided the temperature is kept below 65°C. Prolonged storage at temperatures

above 65°C may cause discoloration.

Diphenylamine is shipped in polypropylene lined paper bags, and 8,000 to 10,000 gallon tank cars. No labels are required.

**DISPOSAL/REUSE:** Aqueous waste streams are not associated with the manufacture of diphenylamine. The toxicity of the material and byproducts of disposal must be considered when disposing of organic diphenylamine waste streams. The Recommended Provisional Limits for releasing diphenylamine into the environment are as follows:

<u>Diphenylamine as a Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.1 mg/M <sup>3</sup>	0.01 TLV
Water and Soil	0.5 ppm (mg/l)	Stokinger and Woodward Method.

**EVALUATION OF WASTE MANAGEMENT:** Diphenylamine waste will usually be found in low concentrations in organic waste streams and rarely as concentrated waste.

#### METHODS OF DISPOSAL

#### EVALUATION

##### CONCENTRATED WASTE

Recycling and purification	Best choice when possible
Controlled incineration with scrubbers and/or thermal catalytic devices for the effluent gases	Satisfactory
Land burial	Satisfactory if the site is acceptable from a geologic and groundwater hydrology point of view and meets California Class 1 Landfill requirements.

##### DILUTE ORGANIC WASTE STREAMS

Incineration	Satisfactory
Plant Landfills	Satisfactory if the site is acceptable from a geologic and groundwater hydrology point of view and meets California Class 1 landfill requirements.

APPLICABILITY TO NATIONAL DISPOSAL SITES: Diphenylamine can be adequately treated at the point of generation and as a waste stream constituent is not considered to be a candidate for National Disposal Sites.



## ESTERS

(ETHYL ACETATE, METHYL ACETATE, METHYL METHACRYLATE, VINYL ACETATE)

### ETHYL ACETATE

CHEMICAL FORMULA:  $\text{CH}_3\text{C}(=\text{O})\text{OCH}_2\text{CH}_3$

GENERAL DESCRIPTION: Colorless flammable liquid. IUC Name: Ethyl ethanoate. Also called acetic ester.

Molecular Wt.: 88.10 Melting Pt.: -83.6°C Boiling Pt.: 77.15°C

Density: (Liquid) 0.8946 @ 25°C (Gas) 3.04 g/l

Vapor Pressure: 100 mm @ 27.0°C

Flash Pt.: 24° F Autoignition Temperature: 800°F

Explosive Limits in Air (Wt%): Lower 2.5% Upper 9%

Solubility:

Hot Water: Slightly Cold Water: Slightly Ethanol: Miscible

Other: Acetone, chloroform, ether

DOT Classification: Flammable, red label

Coast Guard Classification: Red label

MANUFACTURE: The most common method is the direct reaction of acetic acid with ethanol.

### METHYL ACETATE

CHEMICAL FORMULA:  $\text{CH}_3\text{C}(=\text{O})\text{OCH}_3$

GENERAL DESCRIPTION: Colorless, flammable liquid.

Molecular Wt.: 74.08 Melting Pt.: -98.7°C Boiling Pt.: 57.8°C

Density: (Liquid) 0.9274 g/cc @ 25° C (Gas) 2.55 g/l

Vapor Pressure: 100 mm @ 9.4°C

Flash Pt.: 14° F Autoignition Temperature: 935°F

Explosive Limits in Air (Wt%): Lower 3.1% Upper 16%

Solubility:

Hot Water: Soluble Cold Water: Soluble Ethanol: Miscible

Other: Ether

DOT Classification: Flammable, red label

Coast Guard Classification: Red label

MANUFACTURE: The direct reaction of acetic acid with methanol.

METHYL METHACRYLATE

CHEMICAL FORMULA:  $\text{CH}_2=\text{C}(\text{CH}_3)\text{COCH}_3$

GENERAL DESCRIPTION: Colorless flammable liquid. IUC Name: Methyl 2-methylpropenoate.

Molecular Wt.: 100.11 Melting Pt.: -50°C Boiling Pt.: 101.0°C  
Density: (Liquid) 0.936 g/cc @ 20°C (Gas) 3.45 g/l  
Vapor Pressure: 40 mm @ 25.5°C  
Flash Pt.: 50° F (O.C.) Autoignition Temperature: \_\_\_\_\_  
Explosive Limits in Air (Wt%): Lower 2.1% Upper 12.5%  
Solubility:  
Hot Water: \_\_\_\_\_ Cold Water: \_\_\_\_\_ Ethanol: \_\_\_\_\_  
Other: \_\_\_\_\_

DOT Classification: Flammable, red label

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Reaction of carbon monoxide, acetylene and methanol.

VINYL ACETATE

CHEMICAL FORMULA:  $\text{CH}_3\text{COOCH}=\text{CH}_2$

GENERAL DESCRIPTION: Colorless flammable liquid. IUC Name: Ethenyl ethanoate.

Molecular Wt.: 86.05 Melting Pt.: -100.2°C Boiling Pt.: 73°C  
Density: (Liquid) 0.9335 @ 20°C (Gas) 3.0 g/l  
Vapor Pressure: 100 mm @ 21.5° C  
Flash Pt.: 18° F Autoignition Temperature: 800°F  
Explosive Limits in Air (Wt%): Lower 2.6% Upper 13.4%  
Solubility:  
Hot Water: Slightly Cold Water: Slightly Ethanol: Miscible  
Other: Ether

DOT Classification: Flammable, red label

Coast Guard Classification: Red label

MANUFACTURE: By the reaction of acetic acid with acetylene..

USES: Esters are used as solvents, plasticizers, resins plastics and coatings, lubricants, and in laquers, paints, perfumes, flavors, cosmetics, soap and medicine.

TOXICOLOGY: Relatively non-toxic. Irritating to the mucous membranes, particularly the eyes, gums and respiratory passages. Prolonged contact can cause conjunctival irritation and corneal clouding. Mildly narcotic. Ethyl acetate can produce secondary anemia, leucocytosis and cloudy swelling and fatty degeneration of the viscera.

The Threshold Limit Values (TLV) and Maximum Allowable Concentrations (MAC) are:

<u>Material</u>	<u>ppm</u>	<u>TLV</u> <u>mg/M<sup>3</sup></u>	<u>MAC</u> <u>ppm</u>
Ethyl Acetate	400	1400	400
Methyl Acetate	200	610	200
Methyl Methacrylate	100	410	-
Vinyl Acetate	10	30	-

The Booz-Allen Ratings for these compounds are:

<u>COMPOUND</u>	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Ethyl Acetate	1	2	1	1	1	U	2	1	2
Methyl Acetate	2	2	1	1	1	U	2	1	1
Methyl Methacrylate	2	1	2	U	2	U	2	1	1
Vinyl Acetate	1	1	1	3	3	U	2	1	1

OTHER HAZARDS: These esters are flammable and in the presence of oxygen or other polymerization initiator, acrylate esters can polymerize violently.

HANDLING, STORAGE, TRANSPORTATION: Handle in a well-ventilated area. Wear protective clothing and respirators when contact is likely. In case of contact, remove clothing and wash the skin thoroughly with soap and water.

DISPOSAL/REUSE: Most of these materials are not recoverable, therefore many processes result in dilute ester waste streams with high chemical and biological oxygen demand. They can be treated on site or discharged into the municipal sewers.

Recommended Provisional Limits for release of these materials into the environment are:

<u>Contaminant in Air</u>	<u>Provisional Limits</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Ethyl Acetate	4.0	14	0.01 TLV
Methyl Acetate	2.0	6.1	0.01 TLV
Methyl Methacrylate	1.0	4.1	0.01 TLV
Vinyl Acetate	0.1	0.3	0.01 TLV

<u>Contaminant in</u> <u>Water and Soil</u>	<u>Provisional Limits</u> <u>ppm (mg/l)</u>	<u>Basis for Recommendation</u>
Ethyl Acetate	70.0	Stokinger and Woodward Method
Methyl Acetate	30.5	Stokinger and Woodward Method

<u>Contaminant in Water and Soil</u>	<u>Provisional Limits</u> <u>ppm or (mg/l)</u>	<u>Basis for Recommendation</u>
Methyl Methacrylate	20.5	Stokinger and Woodward Method
Vinyl Acetate	1.5	Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

Recycling is the best practice when possible.

#### DISPOSAL METHODS

#### EVALUATION

Discharge to municipal sewers

Best method if the discharge is uniform.

Incineration

Satisfactory

Treatment to reduce chemical and biological oxygen demand

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITE:

Municipal and industrial methods of disposal are adequate. These materials are not judged to be candidates for National Disposal Sites.

## ETHYL DISULFIDE

CHEMICAL FORMULA:  $C_2H_5SSC_2H_5$

GENERAL DESCRIPTION: Colorless oily liquid. IUC Name: Ethyldithioethane. Also called diethyl disulfide.

Molecular Wt.: 122.2 Melting Pt.: \_\_\_\_\_ Boiling Pt.: 154°C

Density: (Liquid) 0.99267 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Water: Very slightly soluble Ethanol Infinitely soluble

Other: Infinitely soluble in ether

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: Animal experiments suggest that the alkyl disulfides are dangerous and may cause hemolytic anemia. They may also produce dermatitis.

OTHER HAZARDS: Dangerous when heated to decomposition it emits highly toxic fumes of sulfides. It probably reacts violently with powerful oxidizers and is probably a moderate fire hazard.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool, dry well ventilated area, away from heat and open flames. Avoid breathing fumes.

FERRIC CHLORIDE

CHEMICAL FORMULA:  $\text{FeCl}_3$

GENERAL DESCRIPTION: Black-brown solid.

Molecular Wt.: 162.2 Melting Pt.: 282°C Boiling Pt.: 319°C

Density: (Solid) 2.804 g/cc @ 11°F (Gas)

Vapor Pressure: 1 mm @ 194°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 535.7 g/100 ml @ 100°C Cold Water: 74.4 g/100 ml @ 0°C

Ethanol: Very soluble Other: Very soluble in ether.

63 g/100 ml in acetone @ 18°C

CHEMICAL FORMULA:  $\text{FeCl}_3 \cdot 6\text{H}_2\text{O}$

GENERAL DESCRIPTION: Brown-yellow, very deliquescent, crystalline solid.

Molecular Wt.: 270.32 Melting Pt.: 37°C Boiling Pt.: 280-285°C

Density: (Solid) (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Infinitely soluble Cold Water: 91.9 g/100 ml @ 20°C

Ethanol: Soluble Other: Soluble in ether

DOT Classification:

Coast Guard Classification:

IATA Classification: Other restricted articles, class B, no label required  
12 kilograms (passenger), 45 kilograms (cargo)

OTHER HAZARDS: Dangerous. When heated to decomposition, it emits highly toxic fumes of hydrochloric acid. It will react with water to produce toxic fumes of hydrochloric acid. It will react with water to produce toxic and corrosive fumes.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool, dry place away from heat and flames.

## FERROUS CHLORIDE

CHEMICAL FORMULA:  $\text{Fe Cl}_2$

GENERAL DESCRIPTION: Green to yellow deliquescent crystalline solid. Also called Lawrencite.

Molecular Wt.: 126.8 Melting Pt.: 670-674°C Boiling Pt.: 1026°C

Density: (Solid) 2.98 g/cc (Gas)

Vapor Pressure: 10 mm @ 700°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 105.7 g/100 ml @ 100°C Cold Water: 64.4 g/100 ml @ 10°C

Ethanol: 100 g/100 ml Other: Soluble in acetone, insoluble in ether.

CHEMICAL FORMULA:  $\text{FeCl}_2 \cdot 4\text{H}_2\text{O}$

GENERAL DESCRIPTION: Blue green deliquescent crystalline solid.

Molecular Wt.: 198.83 Melting Pt.: Boiling Pt.:

Density: (Solid) 1.93 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 415.15 g/100 ml @ 100°C Cold Water: 160.1 g/100 ml @ 10°C

Ethanol: Soluble Other:

DOT Classification:

Coast Guard Classification:

OTHER HAZARDS: When heated to decomposition, it emits highly toxic fumes of hydrochloric acid.



## FERROUS SULFATE

CHEMICAL FORMULA:  $\text{FeSO}_4 \cdot 7\text{H}_2\text{O}$

GENERAL DESCRIPTION: Blue to green crystalline solid. Also called iron sulfate, copperas and green vitriol

Molecular Wt.: 278.01 Melting Pt.:  $64^\circ\text{C}-6\text{H}_2\text{O}$  Boiling Pt.:  $300^\circ\text{C}-7\text{H}_2\text{O}$

Density: (Solid) 1.898 g/cc @  $20^\circ\text{C}$  (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: 48.6 g/100 ml @  $50^\circ\text{C}$  Cold Water: 15.65 g/100 ml

Ethanol: Insoluble Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: As a by-product from production, direct reaction between dilute sulfuric acid and iron, and oxidation of pyrites in air followed by leaching and treatment with scrap iron.

USES: Water purification, source for other iron salts and oxides, fertilizer, feed additive, writing inks, pigments, medicine, deodorizer, metallurgy, aluminum etching and in wood preservative compositions.

TOXICOLOGY: Ferrous sulfate has caused death when excessive quantities have been ingested. The lowest lethal dose was 0.5 gm. The Threshold Limit Value for  $\text{FeSO}_4$  is 1 mg/M as Fe.

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
1	1	1	2	3	U	1	1	1

OTHER HAZARDS: Ferrous sulfate will corrode iron and most steels. It will hydrolyze to produce an acid solution.

HANDLING, STORAGE, TRANSPORTATION: Ferrous sulfate etches iron and aluminum. Other than protection from moisture, no special care is needed.

DISPOSAL/REUSE: If the quality and quantity of the waste makes it economically feasible, it can be reprocessed for reuse. For disposal into the environment, the following Provisional Limits are recommended:

<u>Ferrous Sulfate as a Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.01 mg/M <sup>3</sup> as Fe	0.01 TLV for Fe
Water and Soil	0.03 ppm as Fe	Drinking Water Standard

EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHODS

EVALUATION

Dissolve in a large excess of water and treat with a slight excess of soda ash and slaked lime. Let stand for 24 hours. The liquid is decanted into another container and neutralized with HCl. The liquid is diluted and discharged into a sewer or stream. The sludge is added to a landfill.

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Ferrous sulfate waste can be adequately treated at the point of generation and discharged into municipal sewers or streams and are not considered to be candidate waste stream constituents for National Disposal Sites.

## FORMIC ACID

CHEMICAL FORMULA:  $\text{H}-\overset{\text{O}}{\underset{\text{||}}{\text{C}}}-\text{OH}$

GENERAL DESCRIPTION: Colorless corrosive liquid. IUC Name: Methanoic Acid.

Molecular Wt.: 46.03 Melting Pt.: 8.2°C Boiling Pt.: 100.8°C

Density: (Liquid) 1.2267 g/cc @ 15° C (Gas) 1.59 g/l

Vapor Pressure: 40 mm @ 24° C

Flash Pt.: 156° F (O.C.) Autoignition Temperature: 1114°F

Explosive Limits in Air (Wt%): Lower 18% Upper 57%

Solubility: (90% Solution) (90% Solution)

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other: Ether

DOT Classification: Corrosive, white label

Coast Guard Classification: White label

MANUFACTURE: Reaction of sodium hydroxide and carbon monoxide to produce sodium formate which is then acidized to the acid.

USES: Textile dyeing and finishing. (50%) Chemical synthesis and in the leather industry.

TOXICOLOGY: Vapor causes irritation of the eyes and upper respiratory tract and skin lesions characterized by cracking and fissuring of the skin. Ingestion causes a burning pain in the stomach followed by nausea and vomiting.

The Threshold Limit Value (TLV) for formic acid is: 5 ppm or 9 mg/M<sup>3</sup>.

The Booz-Allen Ratings for formic acid are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	2	2	1	1	2	1	1

HANDLING, STORAGE, TRANSPORTATION: Formic acid should be handled in a well ventilated area. Protective clothing and respirators are recommended. In case of skin contact, all contaminated clothing should be removed and the skin washed with soap and water.

DISPOSAL/REUSE: Any unused material is recycled. Dilute waste streams can be treated on site or discharged to municipal sewers after pH adjustment.

Recommended Provisional Limits for formic acid are:

<u>Formic Acid as a Contaminant in</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Air	0.05	0.09	0.01 TLV
Water and Soil	0.45		Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT:

##### DISPOSAL METHODS

##### EVALUATION

Recycling

Best choice when possible

Treatment of waste to reduce chemical and biological oxygen demand and discharge into municipal sewers

Satisfactory

Incineration

Satisfactory

#### APPLICABILITY TO NATIONAL DISPOSAL SITES:

Formic acid waste can be satisfactorily treated by municipal and industrial methods and therefore is not considered a candidate waste stream constituent for National Disposal Sites.

## GOLD CHLORIDE

### AURIC CHLORIDE

CHEMICAL FORMULA:  $\text{Au Cl}_3$

GENERAL DESCRIPTION: Claret red crystalline solid. Also called gold chloride.

Molecular Wt.: 303.57 Melting Pt.: 254°C d Boiling Pt.: 265°C sub-  
Density: (Solid) 3.9 g/cc (Gas) /limes

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: Very soluble Cold Water: 68 gm/100 ml

Ethanol: Soluble Other: Soluble in ether, slightly  
soluble in  $\text{NH}_3$ , insoluble in carbon disulfide.

DOT Classification:

Coast Guard Classification:

### AUROUS CHLORIDE

CHEMICAL FORMULA:  $\text{Au Cl}$

GENERAL DESCRIPTION: Yellow crystalline solid.

Molecular Wt.: 232.66 Melting Pt.: 170°C decomposes to  $\text{AuCl}_3$

Density: (Solid) 7.4 g/cc Boiling Pt.: 289.5°C decomposes

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: decomposes Cold Water: decomposes, very slightly

Ethanol: Other: Soluble in  $\text{HCl}$  and  $\text{HBr}$

DOT Classification:

Coast Guard Classification:

TOXICOLOGY: Salts of gold may cause urticaria (hives), itching, purpura and other skin rashes, some of which may be severe. They may also cause damage to the blood forming organs resulting in aplastic anemia. The liver, kidneys and nervous system may also be affected.

OTHER HAZARDS: Chlorides, when heated to decomposition or on contact with acid or acid fumes, evolve highly toxic chloride fumes.

## HEXAMETHYLENEDIAMINE AND UREA

### HEXAMETHYLENEDIAMINE

CHEMICAL FORMULA:  $\text{H}_2\text{N}-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{NH}_2$

GENERAL DESCRIPTION: Colorless crystalline solid. IUC Name: 1,6-Hexanediamine.

Molecular Wt.: 116.21 Melting Pt.: 39-40°C Boiling Pt.: 196°C  
Density: (Liquid) \_\_\_\_\_ (Gas) \_\_\_\_\_ Sublimes at 204-205°C

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Hot Water: \_\_\_\_\_ Cold Water: Very Ethanol: Slightly

Other: Slightly soluble in benzene

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: Displacement of a reactive functional group from the aliphatic compound. By the following reaction:  $\text{CH}_2=\text{CH}-\text{CH}=\text{CH}_2 \xrightarrow{\text{Cl}_2} \text{ClCH}_2-\text{CH}=\text{CH}-\text{CH}_2\text{O}$   
 $\xrightarrow{\text{NaCN}} \text{NC}-\text{CH}_2-\text{CH}=\text{CH}-\text{CH}_2-\text{CN} \xrightarrow{\text{H}_2} \text{NH}_2\text{CH}_2\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{CH}_2-\text{NH}_2$  and several other processes.

USES: In the production of nylon 6, 6 and 6,10.

### UREA

CHEMICAL FORMULA:  $\text{H}_2\text{N}-\overset{\text{O}}{\underset{\text{||}}{\text{C}}}-\text{NH}_2$

GENERAL DESCRIPTION: Colorless crystalline solid. Also called carbamide, carbonyl disamide.

Molecular Wt.: 60.06 Melting Pt.: 132.7°C Boiling Pt.: Decomposes

Density: (Liquid) 1.335 gm/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air: Slightly dangerous when heated to decomposition.

Solubility: \_\_\_\_\_

Hot Water: Very soluble Cold Water: Soluble Ethanol: Soluble

Other: Slightly soluble in ether, soluble in methanol and glycerol

DOT Classification: None

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: By the reaction of carbon dioxide with ammonia at 150-200°C.

and 150-300 atm. pressure.

USES: Used as a fertilizer, cattle feed and resins.

TOXICOLOGY: Not particularly systematically toxic. Amines can cause corrosive and damaging effect on tissue. Repeated exposure to diamines can cause hypersensitivity, dermatitis and in some people allergenic and asthmatic reactions. Chronic ingestion of diamines can cause liver and kidney damage.

The Threshold Limit Values for these compounds are not available.

The Booze-Allen Ratings for these compounds are:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Hexamethylene Diamine	2	2	2	U	U	U	1	1	1
Urea	1	1	1	U	1	U	1	1	1

OTHER HAZARDS: When heated to decomposition, aliphatic amines may emit noxious, irritating and toxic fumes. Will react with some compounds to form potentially explosive mixture. Urea has no hazards.

HANDLING, STORAGE AND TRANSPORTATION: Handle in a well ventilated area. Use protective clothing and respirators where necessary. Store in a cool, dry, well ventilated place.

DISPOSAL/REUSE: In the manufacture of urea close to 100 percent of all raw materials and reaction products are used as feed and fertilizer. Heavy bottoms from purification of amines are disposed of by incineration, landfill, deep well injection or is processed to reduce the biological and chemical oxygen demand. Some nitrogen containing materials are produced in dilute waste streams in the manufacture of amines. These are usually discharged into sewers or rivers with out pretreatment or by deep well disposal.

The Recommended Provisional Limits for release into the environment are:

<u>Contaminant in Air</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm</u>	<u>mg/M<sup>3</sup></u>	
Hexamethylenediamine	-	0.04	Based on similar compounds.
Urea	-	0.06	Based on Similar compounds
<u>Contaminant in Soil and Water</u>	<u>Provisional Limit</u>		<u>Basis for Recommendation</u>
	<u>ppm or mg/l</u>		
Hexamethylenediamine	0.20		Based on similar compounds
Urea	0.30		Based on similar compounds

EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHODS

EVALUATION

Reformulation of products to reduce environmental impact, when necessary

Satisfactory

Treatment of waste water and water soluble by-products to reduce biological and chemical oxygen demand at manufacturing site or by municipal waste treatment system.

Satisfactory

Incineration of badly contaminated amines with scrubber

Satisfactory

Landfill of residue and sludges obtained during manufacture or use.

Less satisfactory than incineration due to long term threat to underground water.

APPLICABILITY TO NATIONAL DISPOSAL SITES: These materials are not recommended for disposal at National Disposal Sites, since they can be adequately handled by industrial methods.



1-HEXANOL

CHEMICAL FORMULA:  $\text{CH}_3(\text{CH}_2)_4\text{CH}_2\text{OH}$

GENERAL DESCRIPTION: Colorless liquid. Also called n-hexyl alcohol and amyl carbinol

Molecular Wt.: 102.17 Melting Pt.: -51.6°C Boiling Pt.: 157.2°C

Density: (Liquid) 0.8186 g/cc @ 20°C (Gas) 3.52 g/l

Vapor Pressure: 1 mm @ 24.4°C

Flash Pt.: 145°F Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Insoluble Cold Water: Insoluble Ethanol: Infinitely

Other: Infinitely soluble in ether /Soluble

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: Highly toxic.

OTHER HAZARDS: Moderate fire hazard. When exposed to heat or flame it can react with oxidizing materials.

HANDLING, STORAGE, TRANSPORTATION: When handling hexanol wear protective equipment to avoid contact. If there is accidental contact, wash the contacted area with soap and water. Remove contaminated clothing and wash before reuse. Store in a cool well ventilated place away from heat and open flame.

## HYDROCHLORIC ACID

CHEMICAL FORMULA: HCl

GENERAL DESCRIPTION: Colorless gas or colorless, poisonous fuming liquid. Also called muriatic acid, chlorohydric acid and hydrogen chloride.

Molecular Wt.: 36.46      Melting Pt.: -114.8°C      Boiling Pt.: -84.9°C  
Density: (Liquid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_  
Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
Solubility: \_\_\_\_\_ @ 0°C

Hot Water: 56.1g/100ml@60°C      Cold Water: 82.3g/100ml      Ethanol: Soluble  
Other: \_\_\_\_\_

DOT Classification: Corrosive liquid, white label (liquid)

Coast Guard Classification: Corrosive liquid, white label (liquid)

MCA Warning Label

IATA Classification: Corrosive liquid, white label.

1 liter (passenger) 5 liters (cargo)

Coast Guard (anhydrous) Classification: Nonflammable gas, green gas label

MANUFACTURE: Hydrochloric acid is produced from four major sources:

(1) as a by product in the chlorination of both the aromatic and aliphatic hydrocarbons;

(2) from the reaction between sulfuric acid and salts of hydrochloric acid;

(3) from the combustion of hydrogen and chlorine;

(4) from the Hargreaves type reactions such as:  $4 \text{NaCl} + 2\text{SO}_2 + \text{O}_2 + \text{H}_2\text{O} \longrightarrow 2\text{Na}_2\text{SO}_4 + 4\text{HCl}$ .

In 1969, 1.8 million tons were produced in the U.S.

USES:

(1) In the manufacture of pharmaceutical hydrochlorides, various inorganic and organic chlorides and chlorine;

(2) In chlorination, isomerization, polymerization and alkylation processes;

(3) as a chemical reagent.

TOXICOLOGY: Hydrochloric acid is strongly corrosive. It is an irritant to the mucous membranes of the eyes and the respiratory tract. On contact concentrated solution causes severe burns; permanent visual damage may occur. Inhalation of the fume causes coughing, choking and inflammation and ulceration of the respiratory tract.

The Threshold Limit Values (TLV) and Lethal Concentrations for HCl(g) are:

TLV7 mg/M<sup>3</sup>Lethal Concentrationih LC<sub>Ca</sub> : 1000 mg/M<sup>3</sup>, rabbit

The Booz Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	1	3	U	2	1	2

OTHER HAZARDS: No other hazards known.

HANDLING, STORAGE, TRANSPORTATION: Corrosive materials such as hydrochloric acid must be handled carefully. Contact with skin and inhalation of the fumes must be avoided. It should be kept away from food. Containers should be kept tightly closed.

DISPOSAL/REUSE: Provisional Limit for the safe disposal of hydrochloric acid into the environment are as follows:

<u>As a Contaminant in</u>	<u>Maximum Exposure Limit</u>	<u>Basis for Recommendation</u>
Air	0.07 mg (Vapor)/M <sup>3</sup>	0.01 TLV
	<u>Provisional Limit</u>	
Water and Soil	0.35 ppm (mg/l)	Stokinger and Fox Method

## EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHODEVALUATION

Neutralization with soda ash-slaked lime. Discharge after dilution

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Hydrochloric acid as a waste stream constituent is not considered to be a candidate for disposal at National Disposal Sites.

## HYDROGEN CYANIDE

CHEMICAL FORMULA: HCN

GENERAL DESCRIPTION: Colorless poisonous liquid. Faint odor of bitter almonds. Also called hydroorganic acid and prussic acid.

Molecular Wt.: 27.03 Melting Pt.: -13.2°C Boiling Pt.: 25.7°C

Density: (Liquid) 0.688 g/cc @ 20°C (Gas) 0.969 g/l @ 31°C

Vapor Pressure: 400 mm @ 9.8°C

Flash Pt.: 0°F (CC) Autoignition Temperature: 100°F

Explosive Limits in Air (Wt%): Lower 6% Upper 40%

Solubility:

Hot Water: Miscible Cold Water: Miscible Ethanol: Miscible

Other: Miscible in ether

DOT Classification: Class "A" poison

Coast Guard Classification: Class "A" poison

MANUFACTURE: HCN is manufactured commercially by six different processes:

(1) by treating a cyanide with dilute sulfuric acid; (2) by catalytically reacting ammonia and air with methane or natural gas; (3) by recovery from coke oven gases; (4) decomposition of formamide; (5) from ammonia and hydrocarbons by electrofluid reaction in the presence of a platinum-rhodium catalyst; and (6) by pyrolytic decomposition of residues from beet-sugar molasses.

USES: Used in the manufacture of acrylonitrile, acrylates, adiponitrile, cyanide salts, dyes, fumigants, chelates, rubbers and plastics.

TOXICOLOGY: (Human Toxicity) Hydrogen cyanide and the cyanides are true protoplasmic poisons. They combine in the tissues with enzymes associated with cellular oxidation. They thereby render oxygen unavailable to the tissues, and cause death through asphyxia. This effect lasts only while the cyanide is present; upon its removal, normal function is restored provided death has not already occurred. Hydrocyanic acid can be absorbed through the skin. The Threshold Limit Value (TLV) is 10 ppm in air (11 mg/M<sup>3</sup>).

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	3	3	U	3	2	3

(OTHER TOXICITY) Cyanides either as hydrogen cyanide or its salts are often found in industrial aqueous waste streams. Cyanide ion, for the most part, is unaffected by the basic water treatment plant. Many lower animals

and fish are able to convert cyanide to the thiocyanate ion which does not inhibit respiratory enzyme activity. A permissible criterion has been recommended of 0.20 mg/l for waste discharged into streams, and a desirable criterion of complete absence from public waters was recommended by the Federal Water Pollution Control Administration Water Quality Committee.

**OTHER HAZARDS:** When HCN is exposed to heat, flame or oxidizing materials, a fire or explosion may occur. Under certain conditions, particularly contact with alkaline materials, HCN can polymerize or decompose explosively. The compressed gas is commonly stabilized by the addition of acids.

**HANDLING, STORAGE, TRANSPORTATION:** Liquid hydrogen cyanide is subject to DOT regulations for the transportation of explosives and other dangerous articles. It is packed in metal cylinders for interstate transportation. The cylinders must have not more than 125 lb water capacity. It is not accepted for shipment by railway express.

Hydrogen cyanide should be stored in bulk, steel storage tanks and these should be kept cool and protected from mechanical injury.

**DISPOSAL/REUSE:** Hydrogen cyanide appears in both aqueous and gaseous waste streams from several operations. Complete removal is difficult. Provisional Limits for public exposure resulting from the disposal of HCN are as follows:

<u>HCN in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.11 mg/M <sup>3</sup>	0.01 TLV
Water and Soil	0.01 mg/l (as CN)	Drinking Water Standard

#### **EVALUATION OF WASTE MANAGEMENT PRACTICES:**

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Conversion to cyanate, then to carbon dioxide and ammonia.	Satisfactory
Removal from aqueous solution by passing air through the solution, then passing through an alkaline scrubber.	Satisfactory
Incineration and passing the effluent through an alkaline scrubber.	Satisfactory
By passing air containing HCN through a sodium or potassium hydroxide scrubber. The salts produced are recovered by evaporating the water containing the salts.	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: The waste streams containing hydrogen cyanide can be adequately treated at the source of waste generation and therefore are not considered candidates for National Disposal Sites.

## HYDROGEN PEROXIDE

CHEMICAL FORMULA:  $H_2O_2$

GENERAL DESCRIPTION: Colorless heavy liquid or at low temperatures a crystalline solid. Also called hydrogen dioxide and T-Stuff.

Molecular Wt.: 34.02      Melting Pt.:  $-89^{\circ}C$       Boiling Pt.:  $152.1^{\circ}C$

Density: (Liquid) 1.4649 g/cc @  $0^{\circ}C$       (Gas) \_\_\_\_\_

Vapor Pressure: 1 mm @  $15.3^{\circ}C$  \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: Infinitely Ethanol: \_\_\_\_\_

Other: \_\_\_\_\_

DOT Classification: Corrosive liquid, white label

Coast Guard Classification: Corrosive liquid, white label

MCA Warning label

### MANUFACTURE:

- (1) autoxidation of anthraquinone;
- (2) oxidation of lower secondary alcohol to yield  $H_2O_2$  and ketone;
- (3) electrolysis through ammonium persulfate.

70,000 tons of  $H_2O_2$  were produced in the United States in 1969.

### USES:

- (1) as a bleaching agent of cotton textiles;
- (2) as an oxidizing agent for organic compounds;
- (3) as an oxidizing agent for inorganic compounds;
- (4) in the manufacture of organic and inorganic peroxides;
- (5) in the plastic industry;
- (6) in pharmaceutical preparations, mouth washes, dentifrices, sanitary lotions.
- (7) as a topical antiseptic;
- (8) in rocket propulsions (using 90% solution).

TOXICOLOGY: Hydrogen peroxide is not a toxic material. However, strong solutions can cause burns of the skin and mucous membranes.

The Threshold Limit Value (TLV) for hydrogen peroxide is  $1.4 \text{ mg}/M^3$

The Booz-Allen Ratings for  $H_2O_2$  over 52% are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
3	3	3	2	3	U	3	1	3

OTHER HAZARDS: Hydrogen peroxide is a powerful oxidizer, particularly the concentrated solution. Heat is generated during hydrogen peroxide decomposition and therefore it is a fire hazard when heated or contacted with flammable materials.

HANDLING, STORAGE, TRANSPORTATION: Powerful oxidizers such as hydrogen peroxide should be kept away from reducing agents or combustible materials. Containers should be kept tightly closed.

DISPOSAL/REUSE: Provisional Limits for the safe disposal of hydrogen peroxide into the environment are as follows.

<u>H<sub>2</sub>O<sub>2</sub> as a Contaminant</u>	<u>Maximum Exposure</u>	<u>Basis for Recommendation</u>
in Air	0.014 mg/M <sup>3</sup>	0.01 TLV
	<u>Provisional Limit</u>	
in Water and Soil	0.07 ppm (mg/l)	Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Dilution with water to release the oxygen. Then discharge.	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Hydrogen peroxide as a waste stream constituent is not considered a candidate for disposal at National Disposal Sites.



MERCURY AND INORGANIC MERCURY COMPOUNDS  
MERCURY, MERCURIC CHLORIDE, MERCURIC NITRATE,  
MERCURIC SULFATE, MERCURIC DIAMMONIUM CHLORIDE

MERCURY

CHEMICAL FORMULA: Hg

GENERAL DESCRIPTION: Heavy metallic liquid. Commonly called quick-silver.  
Highly reactive with halogens, hydrogen, sulfide and sulfur

Molecular Wt.: 200.59 Melting Pt.: -389°C Boiling Pt.: 356.6°C

Density: (Liquid) 13.594 g/cc @ 20°C (Gas)

Vapor Pressure:  $1.2 \times 10^{-3}$  @ 20°C; 1 mm @ 126.2°C; 10 mm @ 184°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility: 20-30 ppm in

Hot Water: Cold Water: deaerated H<sub>2</sub>O Ethanol:

Other:

DOT Classification: Poison B

Coast Guard Classification:

MERCURIC CHLORIDE

CHEMICAL FORMULA: Hg Cl<sub>2</sub>

GENERAL DESCRIPTION: White crystals or powder. Also called corrosive sublimate. Highly toxic.

Molecular Wt.: 271.50 Melting Pt.: 276°C Boiling Pt.: 302°C

Density: (Solid) 5.440 g/cc @ 25°C (Gas)

Vapor Pressure: 1 mm @ 136.2°C; 10 mm @ 180.2°C; 100 mm @ 237°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 48 g/100 cc @ 100°C Cold Water: 6.9 g/100 cc @ 20°C

Ethanol: Soluble Other:

DOT Classification: Poison B

Coast Guard Classification:

MERCURIC NITRATE

CHEMICAL FORMULA: Hg(NO<sub>3</sub>)<sub>2</sub> · 1/2 H<sub>2</sub>O

GENERAL DESCRIPTION: White yellowish deliquescent powder. Highly toxic.

Molecular Wt.: 333.61 Melting Pt.: 79°C Boiling Pt.: Decomposes  
 Density: (Solid) 4.39 g/cc (Gas) \_\_\_\_\_  
 Vapor Pressure: \_\_\_\_\_  
 Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
 Solubility:  
     Hot Water: Decomposes Cold Water: Very soluble  
     Ethanol: Insoluble Other: Visible in HNO<sub>3</sub>, NH<sub>3</sub>, acetone.  
 Also has Formula Hg (NO<sub>3</sub>)<sub>2</sub> · H<sub>2</sub>O  
 Molecular Wt: 342.61 Colorless crystal or white powder, deliquescent.  
 Solubility:  
     Hot Water: \_\_\_\_\_ Cold Water: Soluble  
     Ethanol: Insoluble Other: soluble in HNO<sub>3</sub>  
 Coast Guard Classification: \_\_\_\_\_  
 DOT Classification: \_\_\_\_\_

#### MERCURIC SULFATE

CHEMICAL FORMULA: HgSO<sub>4</sub>

GENERAL DESCRIPTION: White crystalline powder.  
 Molecular Wt.: 296.65 Melting Pt.: Decomposes Boiling Pt.: \_\_\_\_\_  
 Density: (Solid) 6.47 g/cc (Gas) \_\_\_\_\_  
 Vapor Pressure: \_\_\_\_\_  
 Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
 Solubility:  
     Hot Water: --- Cold Water: Decomposes  
     Ethanol: Insoluble Other: Soluble in acids.  
 DOT Classification: Poison B  
 Coast Guard Classification: Poison B

#### MERCURIC DIAMMONIUM CHLORIDE

CHEMICAL FORMULA: Hg (NH<sub>3</sub>)<sub>2</sub>Cl<sub>2</sub>

GENERAL DESCRIPTION: Rhombohedral crystal.  
 Molecular Wt.: 305.56 Melting Pt.: 300°C Boiling Pt.: \_\_\_\_\_  
 Density: (Solid) \_\_\_\_\_ (Gas) \_\_\_\_\_  
 Vapor Pressure: \_\_\_\_\_  
 Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_  
 Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_  
 Solubility:  
     Hot Water: Decomposes Cold Water: Insoluble  
     Ethanol: \_\_\_\_\_ Other: \_\_\_\_\_

DOT Classification: Poison B  
Coast Guard Classification:

MANUFACTURE: Mercury: Most commonly by roasting cinnabar (mercuric sulfide) in either mechanical furnaces or retorts to volatilize the mercury, followed by condensation of the vapor. Leaching with either sodium hypochlorite or sodium sulfide. The major U.S. producers of mercury include the following:

Decoursey Mountain Mining Company; Anchorage, Alaska  
Harold Braggini; Atascadero, California  
COG Minerals Corp.; Denver, Colorado  
New Idria Mining and Chemical Co.; Guerneville, California  
Holly Minerals Corp.; Albuquerque, New Mexico  
Rare Metals Corp. of America; Salt Lake City, Utah  
Cordero Mining Co.; Palo Alto, California  
Arentz-Comstock Mining Venture; Salt Lake City, Utah  
Bonanza Oil and Mining Corp.; Sutherlin, Oregon

Mercuric Chloride: Produced commercially by the direct chlorination of mercury. Older processes, based on the reaction between mercurous sulfate and sodium chloride, are no longer extensively practiced in the United States.

Mercuric Nitrate: Made by dissolving mercury in an excess of hot concentrated nitric acid, followed by cooling to crystallize the hydrate.

Mercuric Sulfate: Prepared by reacting a paste of freshly precipitated and washed yellow mercuric oxide with the calculated amount of sulfuric acid, followed by filtration of the white crystalline sulfate on a nutsch and subsequent drying. It may also be prepared by heating mercury with an excess of sulfuric acid; the formation is favored at high temperatures.

Mercuric Diammonium Chloride: Made by dissolving mercuric chloride in a strong aqueous solution of ammonium chloride, and adding ammonia solution. It may also be prepared by treating finely powdered dry mercuric chloride with anhydrous ammonia vapor. The major U.S. producers of inorganic mercury chemicals include the following:

Allied Chemical Corp.; Specialty Chemicals Division; Morristown, New Jersey  
City Chemical Corp.; Jersey City, New Jersey  
Mallinckrodt Chemical Works, Industrial Chemical Division; Jersey City, New Jersey  
Merck & Co., Inc., Merck Chemical Division, Rahway, New Jersey  
Troy Chemical Corp.; Newark, New Jersey  
Ventron Corp., Alfa Products; Beverly, Massachusetts  
Ventron Corp., Chemicals Division; Beverly, Massachusetts

USES: The major use of mercury is as a cathode in the electrolytic preparation of chlorine and caustic soda. Large quantities of mercury are also used

in electrical apparatus, in industrial and control instruments, and in general laboratory applications. These potentially recyclable uses of mercury are for fluorescent and high pressure mercury lamps, arc rectifiers, mercury battery cells, switches, thermometers, barometers, diffusion pump, vacuum gage, and as a vibration damper.

The largest dissipative use of mercury is for mildewproofing paints. (Mercury is no longer used in antifouling paints). Mercury compounds are also widely used in agriculture as a result of their broad antifungal capabilities, for catalytic purposes, and formulated into many of the over-the-counter cosmetics (such as creams and lotions, hair preparations, and facial make-up) and patent medicines (antacids, astringents, eye drops, laxatives, nasal sprays, skin antiseptics, contraceptives). Mercury is used in dental amalgams, and to a decreasing extent, for the control of slime in the paper and pulp mills.

Individual figures of mercury consumption by use from 1967 to 1971 have been compiled by the Bureau of Mines (Table 18), and indicate that declining levels of consumption were noted for mercury uses in agriculture, catalysts, electrolytic preparation of chlorine and caustic soda, installation and expansion of chlor-alkali plants, and paper and pulp manufacture (Table 19).

An estimate of the current and future use pattern of mercury over the next few years has also been presented (Table 20). Of the eleven major categories represented, decreasing demands are forecasted in five, including agriculture, electrolytic preparation of chlorine and soda, installation and expansion of chlor-alkali plants, paints, and paper and pulp manufacture. The other six major uses of mercury are expected to continue at about the same level. These predicted trends in mercury consumption also point toward the same direction where future efforts of mercury recovery and pollution control should be aimed.

Of the four inorganic mercury compounds included in this report, mercuric diammonium chloride is of no commercial significance; whereas mercuric chloride is one of the most industrially important mercury compounds, as a catalyst in vinyl chloride manufacture and other organic reactions, and as a preservative for wood. In agriculture, it is used either as a dust or spray for the control of certain fungus diseases on seeds. Solutions of mercuric chloride are used medicinally as an antiseptic, and in photography to intensify negatives.

Mercuric nitrate is used in the preparation of other mercury compounds, and in particular, mercury fulminate. It is also used in the manufacture of felt, and for the destruction of phylloxera.

Mercuric sulfate is mainly used as an electrolyte for primary batteries. Aside from its occasional use as a catalyst, mercuric sulfate has been employed in conjunction with sodium chloride to extract gold and silver from roasted pyrites.

Table 18. MERCURY CONSUMED IN UNITED STATES BY USES

Use	Consumption, flasks			
	1967	1968	1968	1971
Agriculture (includes fungicides and bactericides for industrial purposes)	3,732	3,430	2,689	1,812
Analgamation	219	267	195	216
Catalysts	2,689	1,914	2,958	2,041
Dental preparations	1,359	2,089	3,083	1,799
Electrical apparatus	14,610	17,484	18,650	15,789
Electrolytic preparation of chlorine & caustic soda	14,306	17,458	20,720	14,977
General laboratory uses	1,133	1,246	2,041	1,513
Industrial & control instruments	3,865	3,935	6,981	4,035
Paint:				
Antifouling	152	392	244	193
Mildew proofing	7,026	10,174	9,486	8,771
Paper & pulp manufacture	446	417	588	316
Pharmaceuticals	283	424	724	571
Redistilled!	7,129	8,247	---	---
Other†	12,568	7,945	9,689	6,521
Total known uses	69,517	75,422	78,048	58,554
Total uses unknown	--	--	1,056	2,936
Grand total	69,517	75,422	79,104	61,490
				52,475

\* Withheld to avoid disclosing individual company confidential data; included with "Other".

! "Redistilled" used in industrial instruments, dental preparations, and electrical apparatus. Figures for the Redistilled category are not available after 1969, but have probably been broken down and added to the figures of the individual use categories.

† "Other" includes mercury used for installation and expansion of chlor-alkali plants.

Table 19. TRENDS IN USES OF MERCURY OVER THE PERIOD 1967 to 1971

Use	1971 Consumption	
	Flasks	Percent of Total
<u>Decreasing Level of Consumption</u>		
Agriculture	1,477	2.8
Catalysts	1,141	2.2
Electrolytic Preparation of Chlorine and Soda	12,262	23.4
Other Uses*	2,300	4.4
Subtotal	17,180	32.8
<u>No Significant Changes in Consumption</u>		
Dental Preparations	2,387	4.5
Electrical Apparatus	16,938	32.3
General Laboratory Uses	1,809	3.4
Industrial and Control Instruments	4,871	9.3
Paints	8,605	16.4
Pharmaceuticals	682	1.3
Subtotal	35,292	67.2
Grand total	52,472	100.0

\*Other uses include mercury used for installation and expansion of chlor-alkali plants, amalgamation, and in paper and pulp manufacture.

Table 20. ESTIMATED TRENDS IN CONSUMPTION OF MERCURY

Use	Estimated Mercury Consumption, flasks	
	1971	1974-1975
Agriculture	1,477	0
Catalysts	1,141	1,141
Dental Applications	2,387	2,387
Electrical Apparatus	16,938	16,938
Electrolytic Preparation of Chlorine and Soda	12,262	672*
General Laboratory Use	1,809	1,809
Industrial and Control Instruments	4,871	4,871
Paints	8,605	0
Paper and Pulp	10+	0
Pharmaceuticals	682	682
Others †	2,290	300
Totals	52,472	28,800

\*Based on Total mercury loss of 0.02 lb/ton chlorine produced and a chlorine production capacity of 7,000 tons per day.

+Estimated

†"Others" include mercury used for installation and expansion of chlor-alkali plants and amalgamation.

**SOURCES AND TYPES OF WASTE:** By far the single largest source of commercial discharges of mercury during 1968 was derived from inventory losses suffered by the chlor-alkali plants.

Of the mercury used in 1968 for other potentially recyclable uses, such as electrical equipment, measurement and control apparatus, and general laboratory uses, 520 tons were recycled and 660 tons had an unknown disposition, (in batteries, fluorescent tubes, switches, etc.) and probably ended up mostly in landfills, dumps, and incinerators.

The dissipative uses of mercury include paints, agriculture, dental fillings, catalysts, paper and pulp manufacture, and pharmaceuticals; a total of 26 percent (745 tons) of the mercury demand in 1968. Mercury from these various uses enter the environment in a variety of ways and at different rates.

Other man-made sources of environmental mercury include mine tailings and vapor released by the mining and smelting of mercury, and a stack loss of three percent during the refining process would mean that 31 tons were emitted into the atmosphere from smelting during 1968. In addition, ore deposits of heavy metals are generally surrounded by aureoles in which a notable enrichment in mercury has occurred, and considerable mercury generally escapes from stacks during the smelting of tin, zinc, copper, and gold. A single smelter handling 500 tons per day might emit as much as 10 lbs mercury vapor daily.

Another major source of airborne mercury is the combustion of paper products and fossil fuel. A conservative estimate of 550 tons of mercury is released annually in the United States by coal. It is believed that petroleum processing and oil burning contribute a substantial amount of mercury pollution in the U. S.

Mercury also enters into the environment through natural sources: Mercury ore deposits and precious metal or copper ore deposits, underground waters, oil field brines, hot springs, geothermal stream fields, and hot vapors which stream up through fine-grained muds produce mud volcanoes and deposit considerable quantities of mercury during condensation.

**TOXICOLOGY:** Inorganic mercury may enter into the body by adsorption through inhalation of elemental mercury vapor or aerosols of mercuric salts and by oral ingestion. Penetration through the skin, on the other hand, is rather slow.

Inhalation of mercury in concentrations of 1,200 to 8,500 micrograms per cubic meter in air results in acute intoxication, affecting primarily the digestive system and kidneys, and is characterized by a metallic taste, nausea, abdominal pain, vomiting, diarrhea, headache, and sometimes albuminuria. After a few days, the salivary glands swell, stomatitis and gingivitis develop, and a dark line of mercuric sulfide forms on the inflamed gums. Furthermore, teeth may loosen and ulcers may appear on the lips and



cheeks. Severe exposure to mercury vapor produces tightness and pain in the chest, difficulty in breathing, and coughing. Severe cases of acute poisoning are characterized in later stages by hemolysis, sleeplessness, headache, facial tide, digital tremors, delirium and hallucinations. Death as a result of extreme exhaustion frequently occurs with poisoning of this degree of severity. In milder cases of acute mercury poisoning, some patients recover within 10 to 14 days, but others may develop the chronic symptoms, such as muscular tremors or erethism.

Chronic poisoning of mercury is more common than the acute form. In the case of chronic poisoning of inorganic mercury, symptoms and signs involving the central nervous system are most commonly seen, the principal features being tremors and psychological disturbances. Symptoms related to the mouth, such as gingivitis, stomatitis, and excessive salivation, may occur along with a number of nonspecific symptoms such as loss of appetite, weight loss, anemia, and muscular weakness. Intoxication from mercury vapor or from absorption of mercuric salts may be due, in both cases, to the action of the mercuric ion. Metallic mercury is able to diffuse much more extensively into the blood cells and various tissues than inorganic mercury, but once distributed, most of it is oxidized to the mercuric form. In most cases symptoms of mercury poisoning were observed only among workers who had been exposed to mercury levels about 100 micrograms per cubic meter in air.

It has been reported that a 1 gm oral dose of mercuric chloride could cause death in adults whereas a 0.1 gm dose would lead to chronic illness. The acute oral  $LD_{50}$  of mercuric chloride to rat is 37 mg/kg body weight, and that mercuric nitrate to mouse is 4 mg/kg body weight.

The American Conference of Governmental Industrial Hygienists (ACGIH) has recommended as Threshold Limit Values (TLV) for 1971 a time-weighted average concentration of 50 micrograms per cubic meter in air for metallic mercury vapor and inorganic mercury compounds.

Mercuric chloride is toxic to aquatic life. No aquatic toxicity data are available for mercury, mercuric sulfate, or mercuric diammonium chloride, as mercuric sulfate decomposes in cold water into a yellow insoluble basic sulfate and free sulfuric acid, and both mercury and mercuric diammonium chloride are insoluble in cold water. It must be remembered, however, that mercury and all inorganic mercury compounds discharged into the aquatic environment could eventually be biologically converted into the more toxic methyl mercury by anaerobic microorganisms, which can then be concentrated through food chains to fish living in both fresh water and marine environments, thus leading to the present dimensions of the mercury pollution problem.

The Booz-Allen Ratings for these compounds are:

	<u>Air</u>	<u>HUMAN</u>		<u>Air</u>	<u>ECOLOGICAL</u>		<u>Air</u>	<u>EXPLOSION</u>	
		<u>Water</u>	<u>Land</u>		<u>Water</u>	<u>Land</u>		<u>Water</u>	<u>Land</u>
Mercury	3	3	3	U	3	U	2	1	1

	HUMAN			ECOLOGICAL			EXPLOSION		
	Air	Water	Land	Air	Water	Land	Air	Water	Land
Mercuric Chloride	3	3	3	3	3	U	2	1	
Mercuric Nitrate	3	3	3	U	3	U		1	3
Mercuric Sulfate	3	3	3	U	U	U	2	1	1
Mercuric Diammonium Chloride	3	3	3	U	U	U	2	1	2

OTHER HAZARDS: All inorganic mercury compounds, with the notable exception of the halides, decompose to give toxic fumes of mercury on heating.

In addition to its toxic properties, mercuric nitrate also possesses some of the properties of nitrates. Acetylene forms a sensitive acetylide when passed into an aqueous solution of mercuric nitrate. Alcohols should not be mixed with mercuric nitrate, as explosive mercury fulminate may be formed. Reactions of mercuric nitrate and phosphine give a yellow precipitate, which explodes when heated or subjected to shock. Mercuric nitrate also reacts with unsaturates and aromatics with violence if given time to generate enough heat, and could lead to explosions in its use for determining sulfur in Ball's reaction.

HANDLING, STORAGE, TRANSPORTATION: Exercise care in handling to minimize contact with the skin or the inhalation of airborne dust, as well as ingestion. Safety precautions should include adequate ventilation of all work and storage areas, enforcing strict standards of housekeeping and personal cleanliness, and the use of protective equipment. Workers should be examined periodically by competent physicians, and referred to medical treatment after any mishap that might give rise to an abnormally high intake of mercury.

Store in tight containers. Mercury, mercuric chloride, and mercuric sulfate are classified as Poison B by the Department of Transportation (DOT). Although mercuric nitrate and mercuric diammonium chloride are not on the DOT list of hazardous materials, the same regulations for Class B poisons should also be applied in the transportation of these compounds.

Spilled mercury and inorganic mercury compounds on floors can normally be handled by several of the removal methods available. Sweeping with special vacuum cleaners, followed by flooding with water, collection of the water with suction pumps, and subsequent removal of the mercury from the contaminated water by chemical precipitation, chemical reduction, ion exchange, or solvent extraction methods. For the chemical removal of mercury, a substance is generally applied to react readily with mercury at ambient temperatures forming nearly nonvolatile mercury compounds, which can then be swept up.

Methods suggested for treating water spills of mercury and inorganic mercury compounds include adsorption with activated carbon and ion-exchanger masses.

DISPOSAL/REUSE: The greater portion of mercury and inorganic mercury compounds present in air and water waste streams can be removed and the mercury recovered for its value. The safe disposal of mercury and inorganic mercury compounds must be defined in terms of Recommended Provisional Limits in the atmosphere and potable water source and/or marine habitat. The Provisional Limits are as follows:

<u>Contaminant in Air</u>	<u>Provisional Limits</u>	<u>Basis for Recommendation</u>
Mercury	0.0005 mg/M <sup>3</sup>	0.01 TLV
Mercuric Chloride	0.0005 mg/M <sup>3</sup> as Hg	0.01 TLV
Mercuric Nitrate	0.0005 mg/M <sup>3</sup> as Hg	0.01 TLV
Mercuric Sulfate	0.0005 mg/M <sup>3</sup> as Hg	0.01 TLV
Mercuric Diammonium Chloride	0.0005 mg/M <sup>3</sup> as Hg	0.01 TLV

<u>Contaminant in Water and Soil</u>	<u>Provisional Limits</u>	<u>Basis for Recommendation</u>
Mercury	0.005 ppm (mg/l)	U.S. Drinking Water Standard
Mercuric Chloride	0.005 ppm (mg/l) as Hg	U.S. Drinking Water Standard
Mercuric Nitrate	0.005 ppm (mg/l) as Hg	U.S. Drinking Water Standard
Mercuric Sulfate	0.005 ppm (mg/l) as Hg	U.S. Drinking Water Standard
Mercuric Diammonium Chloride	0.005 ppm (mg/l) as Hg	U.S. Drinking Water Standard

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### REMOVAL FROM GASES:

##### DISPOSAL METHODS

##### EVALUATION

Mist eliminators with second stage unit to remove the last remaining traces.	Satisfactory
Union Carbide purasiv Hg system	Satisfactory
Absorption with activated carbon	Unsatisfactory, too expensive and inefficient.
Scrubbing with sodium hypochlorite solution.	Satisfactory

REMOVAL FROM LIQUIDS:

DISPOSAL METHODS

EVALUATION

Chemical precipitation

Unsatisfactory due to difficulty in removing precipitate

Chemical reduction with zinc

Satisfactory

Chemical reduction by the Ventron sodium borohydride process.

Satisfactory

Ion exchange by the OSAKA soda process

Satisfactory

Ion exchange by the Artiebolaget Billingsfors Langed process

Satisfactory

Some other iron exchange processes are satisfactory in some cases.

Solvent extraction

Shows promise for the near future.

Chemical absorption

Laboratory and pilot plant data indicate satisfactory results.

Adsorption with activated carbon

Unsatisfactory does not reduce the mercury concentration below the recommended level.

SOLID: No methods have been designed and placed into operation.

APPLICABILITY TO NATIONAL DISPOSAL SITES: Some types of mercury could best be treated at the site of generation. There are some however, where no simple method exists for adequate disposal or recovery, and these are prime candidate waste streams for National Disposal Sites.

## METHANE

CHEMICAL FORMULA:  $\text{CH}_4$

GENERAL DESCRIPTION: Colorless, odorless, tasteless gas. Also called marsh gas and methyl hydride.

Molecular Wt.: 16.04 Melting Pt.: -184°C Boiling Pt.: -161.5°C

Density: (Liquid) 0.415 g/cc @ -164°C (Gas) 0.7168 g/l @ 0°C

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: 1000°F

Explosive Limits in Air (Wt%): Lower 5.3% Upper 14.0%

Solubility: \_\_\_\_\_

Hot Water: 9 cc @ 20°C/100ml Cold Water: \_\_\_\_\_ Ethanol: 60 cc/100ml

Other: 91 cc @ 20°C in ether /100 ml

DOT Classification: Flammable gas, red label, 300 pounds

Coast Guard Classification: Flammable gas, red label

IATA Classification: Flammable gas, red label  
not acceptable (passenger), 140 kilograms (cargo)

TOXICOLOGY: Methane is a simple asphyxiant.

OTHER HAZARDS: Methane is a dangerous fire and explosion hazard when exposed to heat or flame.

HANDLING, STORAGE, TRANSPORTATION: Avoid breathing the fumes. Store in a well ventilated area away from heat and flames.

## METHYL CELLULOSE

### CHEMICAL FORMULA

GENERAL DESCRIPTION: Grayish white fibrous powder. Also called cellulose methyl ether

Molecular Wt.: Varies from 40,000 to 180,000. Melting Pt.:           

Boiling Pt.:           

Density: (Solid)            (Gas)           

Vapor Pressure:           

Flash Pt.:            Autoignition Temperature:           

Explosive Limits in Air (Wt%): Lower            Upper           

Solubility:

Hot Water:            Cold Water:           

Ethanol: Insoluble Other: Soluble in acetic acid, in-  
soluble in ether and chloroform

DOT Classification:           

Coast Guard Classification:

## NITRIC ACID

CHEMICAL FORMULA:  $\text{HNO}_3$

GENERAL DESCRIPTION: Colorless to yellowish to red, fuming corrosive and poisonour liquid. Also called aqua fortis, hydrogen nitrate and azotic acid.

Molecular Wt.: 63.01      Melting Pt.:  $-42^\circ\text{C}$       Boiling Pt.:  $83^\circ\text{C}$

Density: (Liquid) 1.502 g/cc      (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Infinitely      Cold Water: Infinitely      Ethanol: \_\_\_\_\_

Other: \_\_\_\_\_

DOT Classification: Corrosive liquid, white label

Coast Guard Classification: Corrosive liquid, white label

MANUFACTURE: By the ammonia oxidation process.

USES: About 70 to 85% of  $\text{HNO}_3$  is used to produce ammonium nitrate which is used as a fertilizer, approximately 5-10% is used to produce cyclohexanone which is raw material for making the monomers for nylon, the rest is used for making various nitrates and nitro compounds.

TOXICOLOGY: Nitric acid is very corrosive. Its vapor is highly irritating to the skin and the mucous membranes of the eyes and respiratory tract. Continued exposure to the vapor may cause chronic bronchitis and chemical pneumonia. Ingestion of nitric acid causes burning and corrosion of mouth, esophagus and stomach, abdominal tenderness, shock and death.

The Threshold Limit Value (TLV) for nitric acid is 5 mg/M<sup>3</sup>.

The Booz-Allen Ratings for nitric acid are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	3	3	2	1	2	1

OTHER HAZARDS: Nitric acid is a powerful oxidizing agent, and a moderate fire hazard by chemical reaction with reducing agents. It can also explode on contact with powerful reducing agents.

HANDLING, STORAGE, TRANSPORTATION: Corrosive materials such as nitric acid must be handled carefully. Contact with skin and inhalation of the fumes should be avoided. It should be kept away from food. Since nitric acid is a powerful oxidizer it should not be stored near reducing agents or combustible materials. Containers should be kept tightly closed when not in use.

DISPOSAL/REUSE: For the safe disposal of nitric acid into the environment, the following Provisional Limits should be considered:

<u>Nitric Acid as a Contaminant in</u>	<u>Maximum Exposure Limit</u>	<u>Basis for Recommendation</u>
Air	0.05 mg/M <sup>3</sup>	0.01 TLV
	<u>Provisional Limit</u>	
Water and Soil	0.25 ppm (mg/l)	Stokinger and Woodward Method.

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### DISPOSAL METHOD

##### EVALUATION

Neutralization with soda ash-slaked lime solution. The neutral solution of sodium and calcium nitrate formed can be discharged after water dilution.

Satisfactory


Regeneration by steam distillation

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Nitric acid as a waste stream constituent can be adequately handled at industrial sites and is not considered a candidate for National Disposal Sites.



## NITROBENZENE

CHEMICAL FORMULA:  $C_6H_5NO_2$ , 

GENERAL DESCRIPTION: Bright yellow crystals or pale yellow liquid with an almond like odor. Also called nitrobenzol, oil of mirbane.

Molecular Wt.: 123.11 Melting Pt.: 5.7°C Boiling Pt.: 210.9°C

Density: (Liquid) 1.19867 g/cc @ 25°C (Gas) 4.75 g/l

Vapor Pressure: 1 mm @ 44.4°C; 22 mm @ 100°C; 50 mm @ 120°C

Flash Pt.: 87.8°C (C.C.) Autoignition Temperature: 900°F

Explosive Limits in Air (Wt%): Lower 1.8% @ 200°F Upper

Solubility:

Hot Water: 0.8 cc/100cc @ 80°C Cold Water: Very slightly Ethanol: Very

Other: Very soluble in ether, benzene and oils

DOT Classification: Poison B, poison label, 55 gal max container

Coast Guard Classification: Poison B, poison label

MANUFACTURE: Direct nitration of benzene using mixed sulfuric and nitric acid. Large scale commercial manufacturers are Allied, Cyanamid, First Chemical, Mobay, Monsanto and Rubicon.

USES: Manufacture of aniline for the synthesis of dyestuffs, rubber chemicals, photographic chemicals and drugs.

TOXICOLOGY: Highly toxic. Readily absorbed through the skin, by inhalation or by ingestion. Nitrobenzene may be almost immediately fatal if large areas of the body are in contact with the liquid or if massive concentrations are inhaled.

The Threshold Limit Value and Maximum Allowable Concentrations are 0.03 mg/l and 1 ppm (5 mg/M<sup>3</sup>) respectively and acute aquatic toxicity occurs at about 30 mg/l. The lethal dose orally in rabbits is 700 mg/kg.

The Booz-Allen Ratings for Nitrobenzene are:

HUMAN			ECOLOGICAL			EXPLOSIVE		
Air	Water	Land	Air	Water	Land	Air	Water	Land
3	3	3	2	3	1	3	1	3

OTHER HAZARDS: Moderate fire and explosive hazard when exposed to heat or flames.

HANDLING, STORAGE, TRANSPORTATION: Wear protective clothing and respirators when handling. Handle and store in a cool, well ventilated place away from heat or open flames. Ship according to DOT regulations.

DISPOSAL/REUSE: Aqueous waste streams of nitrobenzene are given primary and secondary treatment with lime and activated sludge digestion before being

discharged into waterways.

For disposal of nitrobenzene into the environment the following Provisional Limits are recommended:

<u>Nitrobenzene in</u>	<u>Provisional Limits</u>	<u>Basis for Recommendation</u>
Air	0.01 ppm (0.05 mg/M <sup>3</sup> )	0.01 TLV
Water and Soil	0.25 ppm (0.05 mg/l)	Stokinger & Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHOD

EVALUATION

CONCENTRATED NITROBENZENE

Return to manufacturer when contaminated	Best method
Incineration under controlled methods.	Satisfactory
Open Burning	Not acceptable, oxides of nitrogen and incomplete combustion products may be generated.
Landfill	Only if landfills meet California class 1 requirement.
Dilution of small amounts followed by secondary treatment.	Satisfactory


DILUTE AQUEOUS WASTE

Primary treatment followed by lime to adjust the pH to 7. Mix with municipal sewage. Let equilibrate one day then lagoon for 20 hours with municipal aeration	Satisfactory
Secondary treatment with activated sludge	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Nitrobenzene waste can be handled adequately at the source of generation provided it can be recycled or incinerated in a safe manner. It is not considered to be a candidate for National Disposal Sites.

para-NITROPHENOL

CHEMICAL FORMULA:  $\text{NO}_2\text{C}_6\text{H}_4\text{OH}$ ,



GENERAL DESCRIPTION: Colorless to slightly yellow crystalline solid. Also called 4-nitrophenol.

Molecular Wt.: 139.1 Melting Pt.: 113-114° Boiling Pt.: 279°C d

Density: (Solid) 1.270 g/cc @ 120°C (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 29 gm/100ml@90°C Cold Water: 1.6 gm/100 ml @ 25°C

Ethanol Very soluble Other: Very soluble in chloroform & ether.

DOT Classification:

Coast Guard Classification:

MANUFACTURE: By the hydrolysis of the corresponding nitrochlorobenzene with 15 percent sodium hydroxide at 160°C.

USE: The nitrophenols are used as intermediates in the preparation of dye-stuffs, plant sprays (parathion), aminophenols and photochemicals.

TOXICOLOGY: Nitrophenols are very toxic when ingested, inhaled or absorbed through the skin. The characteristic effects of poisoning are an increased metabolism with a rise in body temperature, headache, heavy sweating, thirst fatigue and just before death a sudden rise in body temperature. Chronic exposure is often characterized by hyperthermia, methemoglobinemia, depression, liver and kidney damage, cataracts, eczema, inflammation of the lymphatic glands and degeneration of the nails. Paranitrophenol is the most toxic of the three mononitrophenols.

The Maximum Allowable Concentration (MAC) for nitrophenol is 4 mg/M<sup>3</sup>. The Booz-Allen Ratings are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
3	3	1	3	3	U	3	1	2

OTHER HAZARDS: No other hazards than those mentioned under toxicology.

HANDLING, STORAGE AND TRANSPORTATION: Handle in a well-ventilated area. Avoid all skin contact. Wear protective clothing and respirators when necessary. In case of accidental contact, remove all contaminated clothing and

wash the skin with soap and water. Bicarbonate solutions will help in the removal of the nitrophenols.

Store in a cool, dry, well-ventilated area, away from acute fire hazards.

DISPOSAL/REUSE: A dilute aqueous waste stream and a small amount of distillation bottoms are produced in the manufacture of nitrophenols. The Manufacturing Chemists Association suggests that small quantities be disposed of by open burning or as a slurry by washing down the sewer. Disposal of large quantities by landfill in areas reserved for toxic wastes is suggested.

Recommended Provisional Limits for release of nitrophenol waste into the environment are as follows:

<u>Nitrophenol in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.002 mg/M <sup>3</sup>	Based on similar compounds
Water and Soil	0.010 ppm (mg/l)	Based on similar compounds

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Treatment of waste water to reduce biological and chemical oxygen demand.	Satisfactory
Controlled incineration with the use of scrubbers and/or thermal or catalytic devices to control the effluent oxides of nitrogen.	Satisfactory
Flushing small quantities down the sewer as a slurry.	Not satisfactory due to hazard caused by accumulation of vapors and damage to activated sludges in treatment plants due to insufficient dilution.
Landfill of large quantities at special toxic wastes landfill sites of the California Class 1 type.	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Waste nitrophenols can best be treated by industrial and municipal treatment, by incineration or by landfill at special sites. Nitrophenol as a waste stream constituent is not considered a candidate for National Disposal Sites.

PHOSPHORUS CHLORIDES  
(PHOSPHORUS OXYCHLORIDE, PHOSPHORUS PENTACHLORIDE, PHOSPHORUS TRICHLORIDE)

PHOSPHORUS OXYCHLORIDE

CHEMICAL FORMULA:  $\text{POCl}_3$

GENERAL DESCRIPTION: Clear colorless fuming liquid. Also called phosphoryl chloride.

Molecular Wt.: 153.35      Melting Pt.: 122°C      Boiling Pt.: 107.2°C

Density: (Liquid) 1.675 g/cc @ 20°C      (Gas) 5.30 g/l

Vapor Pressure: 40 mm @ 2.73°C; 100 mm @ 27.3°C; 400 mm @ 84.3°C

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Decomposes      Cold Water: Decomposes      Ethanol: Decomposes

Other: Carbon tetrachloride

DOT Classification: Corrosive liquid, white label, 1 quart

Coast Guard Classification: Corrosive liquid

MCA Warning Label

IATA Classification: Corrosive liquid, white label,  
not acceptable (passenger), 1 litre (cargo)

MANUFACTURE: Phosphorus trichloride oxidized with pure oxygen and air.

PHOSPHORUS PENTACHLORIDE

CHEMICAL FORMULA:  $\text{P Cl}_5$

GENERAL DESCRIPTION: A yellow white crystalline solid.

Sublimes at

Molecular Wt.: 208.3      Under Pressure      Melting Pt.: 148°C      Boiling Pt.: 160 ° C

Density: (Solid) 1.6 g/cc @ 20°C      (Gas) 4.65 g/l @ 296°C

Vapor Pressure: 1 mm Hg @ 55.5°C; 10 mm Hg @ 83.2°C; 100 mm Hg @ 117°C

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: Decomposes

Ethanol: \_\_\_\_\_ Other: Carbon tetrachloride, carbon  
disulfide; benzoyl chloride

DOT Classification: Flammable solid

Coast Guard Classification: Flammable Solid

MANUFACTURE: Phosphorus trichloride reacted with gaseous chlorine.

## PHOSPHORUS TRICHLORIDE

CHEMICAL FORMULA:  $\text{PCl}_3$

GENERAL DESCRIPTION: A colorless fuming liquid with pungent, irritating odor resembling that of hydrochloric acid. Also called phosphorus chloride.

Molecular Wt.: 137.35      Melting Pt.:  $-118.5^\circ\text{C}$       Boiling Pt.:  $75.5^\circ\text{C}$

Density: (Liquid) 1.575 g/cc @  $20^\circ\text{C}$       (Gas) 4.75 g/l @  $20^\circ\text{C}$

Vapor Pressure: 400 mm Hg @  $56.9^\circ\text{C}$ ; 100 mm Hg @  $21^\circ\text{C}$

Flash Pt.: Nonflammable      Autoignition Temperature: None

Explosive Limits in Air (Wt%): Lower      Upper

Solubility:

Hot Water: Decomposes      Cold Water: Decomposes      Ethanol: Soluble

Other: Chloroform, ether, benzene, carbon disulfide, carbon tetrachloride

DOT Classification: Corrosive Liquid

Coast Guard Classification: Corrosive Liquid

MANUFACTURE: Direct union of red or white phosphorus and gaseous chlorine. Most phosphorus chlorides are manufactured by: Monsanto, Sauget, Illinois; FMC, Nitro, West Virginia; Hooker, Niagara Falls, New York and Stauffer, Morrisville, Pennsylvania.

USES: All three,  $\text{POCl}_3$ ,  $\text{PCl}_5$ , and  $\text{PCl}_3$ , are used in manufacture of organic-phosphorus compounds.

$\text{POCl}_3$ : Organic synthesis of phosphate esters (tricresyl phosphate, a common plasticizer), in production of gasoline additives, insecticides, fire resistant hydraulic fluids and flame retarders.

$\text{PCl}_5$ : A chlorinating agent and catalyst in organic synthesis, catalyst in lubricant additive production and insecticide manufacture.

$\text{PCl}_3$ : Manufacture of organic acid chlorides, dye stuffs, organic antioxidants, vinyl stabilizers and plasticizers.

SOURCE AND TYPES OF WASTE: Main source is the material remaining in containers after emptying. Essentially no production waste. No dilute waste, all decomposes upon contact with water. Decomposition products are hydrochloric and phosphoric acid.

TOXICOLOGY: Phosphorus trichloride and phosphorus pentachloride: Prompt irritation of the eyes, nose, throat and lungs (all mucous membranes) from small amount in air, suffocation, bronchitis, edema and lung inflammation from extended exposures. Severe exposure (600 ppm) is lethal in a few minutes. Vapors irritating to skin. Liquid and solid can cause immediate severe skin burns. TLV for  $\text{PCl}_3$  in air is 0.5 ppm or 3 mg/ $\text{M}^3$ ; and for  $\text{PCl}_5$  in air is 1 mg/ $\text{M}^3$ .

Phosphorus oxychloride: Vapors irritating to all mucous membranes and to lungs. Liquid causes severe skin burns. Inhalation symptoms range from coughing to delayed wheezing due to bronchial irritation or pulmonary edema.

Aquatic toxicity: None, all decompose to HCl and  $H_3PO_4$  in water. 0.1-10 ppm  $H_3PO_4$  affect fish. 1.0 ppm HCl will affect fish.

The Booz-Allen Ratings for these phosphorous chloride compounds are:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
Phosphorus Oxychloride	3	3	3	U	U	U	2	2	2
Phosphorus Pentachloride	3	3	3	3	U	U	2	2	2
Phosphorus Trichloride	3	3	3	U	3	U	2	2	2

OTHER HAZARDS:  $PCl_3$  and  $PCl_5$  neither flammable nor explosive. Each reacts violently with small amounts of water liberating heat, spontaneously flammable phosphine gas, HCl,  $H_3PO_4$  and spontaneously flammable phosphorous  $POCl_3$  neither flammable nor explosive. Corrosive in pure state. Reacts violently with water, giving off HCl,  $H_3PO_4$  and steam. Reacts violently with alkalies and fibrous organic matter.

HANDLING, STORAGE, TRANSPORTATION: Protective clothing should be worn including gas-tight safety goggles, face shields, rubber shoes, rubber gloves, rubber apron and acid-gas canister type respirator. Use fume scrubbers when loading drums, tank cars or tank trucks. Store in a well ventilated, cool, dry area. Use ceramic-lined, lead-lined or nickel-lined drums and keep sealed when storing the two liquids. Solid  $PCl_5$  can be stored in ordinary steel carboys or steel drums. Keep containers tightly closed.

DISPOSAL/REUSE: Recycle to plant production, decomposition with large amounts of water. For large amounts, add phosphoric acid or add the phosphorous chloride to large amounts of water, neutralize and sewer.

Provisional Limits for Disposal:

<u>In Air</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Phosphorus Oxychloride	0.07 mg/M <sup>3</sup> as HCl	0.01 TLV for HCl
Phosphorus Trichloride	0.03 mg/M <sup>3</sup>	0.01 TLV
Phosphorus Pentachloride	0.01 mg/M <sup>3</sup>	0.01 TLV

<u>In Water &amp; Soil</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Phosphorus Oxychloride	0.35 ppm (mg/l)	Stokinger and Woodward Method
Phosphorus Trichloride	0.15 ppm (mg/l)	Stokinger and Woodward Method
Phosphorus Pentachloride	0.05 ppm (mg/l)	Stokinger and Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHOD

EVALUATION

Removal from air by refrigerated condensation and by water decomposition

Satisfactory

In water, they are not removed, only neutralized and sent to sewer. Concentrated waste is recycled, decomposed with water or chemically degraded with  $H_3PO_4$ . The decomposed and degraded products are neutralized and sewerred.

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: These materials are not considered candidates for National Disposal Site disposal.



POLYVINYL ALCOHOL

CHEMICAL FORMULA:  $\text{--CH}_2\underset{\text{OH}}{\underset{|}{\text{CH}}}(\text{CH}_2\underset{\text{OH}}{\underset{|}{\text{CH}}})_2\text{CH}_2\underset{\text{OH}}{\underset{|}{\text{CH}}}\text{--}$

GENERAL DESCRIPTION: Colorless, amorphous powder.

Molecular Wt.: \_\_\_\_\_ Melting Pt.: decomposes over 200°C Boiling Pt.: \_\_\_\_\_

Density: (Solid) 1.329 g/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: 175° F (O.C.) Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: \_\_\_\_\_

Ethanol: \_\_\_\_\_ Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: Not considered toxic. Details not known.

OTHER HAZARDS: Slight fire hazard when exposed to heat or flame, or by reaction with oxidizing materials. Poly vinyl alcohol is a slight explosion hazard when exposed to flame in the form of dust.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool place away from heat flame and oxidizing materials.

## PROPANOL

1 - PROPANOL

CHEMICAL FORMULA:  $\text{CH}_3\text{CH}_2\text{CH}_2\text{OH}$

GENERAL DESCRIPTION: Clear, odorless liquid with an alcohol like odor. Also called n-propyl alcohol and ethyl carbinol.

Molecular Wt.: 60.09      Melting Pt.: -127°C      Boiling Pt.: 97.19°C

Density: (Liquid) 0.8044 g/cc @ 20°C (Gas) 2.07 g/l

Vapor Pressure: 10 mm @ 14.7°C

Flash Pt.: 59°F (C.C.)      Autoignition Temperature: 700°F

Explosive Limits in Air (Wt%):	Lower	2.1%	Upper	13.5
--------------------------------	-------	------	-------	------

Solubility:

Hot Water: Infinitely sol. Cold Water: Ethanol: Inf. sol.

Other: Infinitely soluble in ether

DOT Classification:

Coast Guard Classification:

2 - PROPANOL

CHEMICAL FORMULA:  $\text{CH}_3 - \overset{\text{CH}_3}{\underset{|}{\text{CH}}} - \text{OH}$

GENERAL DESCRIPTION: Clear colorless liquid. Also called dimethylcarbinol, sec-propyl alcohol, isopropanol and iso-propyl alcohol

Molecular Wt.: 60.09      Melting Pt.: -88.5 -89.5°C Boiling Pt.: 82.3°C

Density: (Liquid) 0.7854 g/cc @ 20°C (Gas) 2.07 g/l

Vapor Pressure: 33.0 mm @ 20° C

Flash Pt.: 53°F Autoignition Temperature: 750°F

Explosive Limits in Air (Wt%):	Lower	2.0%	Upper	12%
--------------------------------	-------	------	-------	-----

Solubility:

Hot Water: Inf. soluble      Cold Water: Inf. sol.      Ethanol: Inf. sol.

Other: Infinitely soluble in ether

DOT Classification: Flammable liquid

Coast Guard Classification:

MCA Warning Label

TOXICOLOGY: Isopropyl alcohol is a local irritant. It produces a narcotic effect in high concentration.

It produces a mild irritation to the eyes, nose and throat at concentration levels of 400 ppm.

The tentative Threshold Limit Value for n-propyl alcohol is 200 ppm (510 mgm/M<sup>3</sup>) in air.

The Booz-Allen Ratings are:

	<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
1-Propanol	1	1	1	1	2	U	2	1	1
2-Propanol	2	2	1	1	2	U	2	1	2

OTHER HAZARDS: Propyl alcohol is a fire and explosion hazard when exposed to heat and flame. It can react vigorously with oxidizing materials.

HANDLING, STORAGE, TRANSPORTATION: Avoid eye and skin contact and breathing of vapors. Store in a cool well ventilated area away from heat, flame and oxidizing materials.

PROPARGYL ALCOHOL

CHEMICAL FORMULA:  $\text{CH}\equiv\text{CCH}_2\text{OH}$

GENERAL DESCRIPTION: A moderately volatile liquid with a geranium-like odor. IUC Name: 2-propyn-1-ol. Also called ethynylcarbinol, acetylenylcarbinol and propiolic alcohol.

Molecular Wt.: 56.06 Melting Pt.:  $-17^\circ\text{C}$  Boiling Pt.:  $115^\circ\text{C}$

Density: (Liquid) 0.9715 g/cc @  $20^\circ\text{F}$  (Gas) 1.93 g/l

Vapor Pressure: 11.6 mm @  $20^\circ\text{C}$

Flash Pt.:  $97^\circ\text{F}$  (O.C.) Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:  
Hot Water: Soluble Cold Water: Soluble Ethanol: Infinitely  
Other: Infinitely soluble in ether

DOT Classification:

Coast Guard Classification:

TOXICOLOGY: Very toxic by ingestion, inhalation and absorption through the skin.

OTHER HAZARDS: Moderate fire hazard when exposed to heat or flames. It can react with oxidizing materials.

HANDLING, STORAGE, TRANSPORTATION: Wear protective equipment when handling. In case of contact wash with soap and water. Remove all contaminated clothing and wash before reuse.

Store in a cool well ventilated place away from heat or flame.

## RADIUM-226

CHEMICAL FORMULA:  ${}_{88}^{226}\text{Ra}$

GENERAL DESCRIPTION: Radium is a silver-white radioactive metal. It is one of the most hazardous radionuclides.

Atomic Wt.: 226      Melting Pt.: 700°C      Boiling Pt.: 1737° C

Density (Solid): 5 g/cc

Half-life: 1602 years

Type of Decay: Alpha

Specific Power:  $1.3 \times 10^{-4}$  watts/gm      Specific Activity: 0.99 curies/gm

Solubility:

Cold Water: Reacts and evolves H<sub>2</sub>O      Hot Water: Reacts and evolves H<sub>2</sub>O

Others: Reacts with acid

DOT Classification: Transport group 1, radionuclide

### DECAY CHAIN:

<u>Nuclide</u>	<u>Name</u>	<u>Half-Life</u>	<u>Major Radiation</u>
${}_{88}^{226}\text{Ra}$	Radium-226	1602 years	Alpha and gamma
$\downarrow$ ${}_{86}^{222}\text{Rn}$	Radon-222	3.8 days	Alpha and gamma
$\downarrow$ ${}_{84}^{218}\text{Po}$	Polonium-218	3.5 minutes	Alpha
$\downarrow$ ${}_{82}^{214}\text{Pb}$	Lead-214	26.8 minutes	Beta and gamma
$\downarrow$ ${}_{83}^{214}\text{Bi}$	Bismuth-214	19.7 minutes	Alpha, beta, and gamma
$\downarrow$ ${}_{84}^{214}\text{Po}$	Polonium-214	64 micro seconds	Alpha
$\downarrow$ ${}_{82}^{210}\text{Pb}$	Lead-210	21 years	Beta and gamma
$\downarrow$ ${}_{83}^{210}\text{Bi}$	Bismuth-210	5 days	Beta
$\downarrow$ ${}_{84}^{210}\text{Po}$	Polonium-210	138 days	Alpha
$\downarrow$ ${}_{82}^{206}\text{Pb}$	Lead-206	Stable	

MANUFACTURE: Radium-226 is a daughter of uranium-238 and occurs naturally in the earth's surface.

USES: Radium-226 is used in timepieces, electron tubes, record player brushes, gauges, fire detectors, and in various self-luminous products. It is used in medicine for the treatment of tumors, superficial skin lesions, lymphoid tissue and other diseases. It is used at 2,300 facilities.

**TOXICOLOGY:** The ingestion of the luminous dial paint prepared from radium caused the death of many early dial painters.

**RADIATION HAZARD:** Radium-226 is one of the most hazardous radioactive materials known. It replaces calcium in the bone structure and is a source of irradiation to the blood forming organs. This along with its long half-life and high radiation energies puts it in the highest radiotoxicity group.

The effects of radiation exposure is primarily dependent on the amount of radiation and the portion of the body affected. The effects of whole-body gamma radiation exposure are: (1) 5 to 25 rads, minimal dose detectable by chromosome analysis or other specialized analysis, but not by hemogram; (2) 50 to 75 rads, minimal acute dose readily detectable in a specific individual (e.g., one who presents himself as a possible exposure case); (3) 75 to 125 rads, minimal acute dose likely to produce vomiting in about 10 percent of people so exposed; (4) 150 to 200 rads, acute dose likely to produce transient disability and clear hematological changes in a majority of people so exposed; (5) 30 rads, median lethal dose for single short exposure. These effects are for a single large dose of radiation or a series of substantial doses in a short interval of time to the total body. The dose delivered to the bone following the inhalation of 1 microcurie of radium-226 is 300 rem. The dose delivered to the bone following the injection of 1 microcurie into the body via a wound is 1,000 rem.

Standards for prolonged exposure over a 50-year period have defined the single dose limit in terms of the maximum permissible dose accumulated in a period of 13 weeks. The whole body exposure limit is 3 rem per quarter for a radiation worker and the accumulated dose limit is  $5(N - 18)$ , where N is the individual's age in years. Limits for the thyroid, bone, and other organs have also been defined. Values of the total body burden for each radionuclide required to produce the maximum permissible dose rates defined above have been compiled. For radium-226 the critical organ is the bone and the maximum permissible body burden is 0.1 microcuries.

**OTHER HAZARDS:** The fire and explosive hazard is moderate.

**HANDLING, STORAGE, TRANSPORTATION:** Radium 226 is hazardous to man by inhalation, ingestion or direct radiation exposure. Great care should be exercised in handling it. Excessive exposure to personnel should be avoided.

Special procedures and adequate radiation shielding are required in handling it. To detect and control personnel exposure to radiation, everyone working with radium 226 should wear dosimetry devices which directly indicate the dose. Other devices used for this purpose are the film badge and the thermoluminescent dosimeters.

Specially constructed containers in controlled areas should be used for storing large quantities. They should be protected by both a primary and a secondary containment barrier. Special monitoring systems and proper warning signs should be located in the storage area. Stored radium-266 should

be vented to prevent the build-up of radon gas.

DISPOSAL/REUSE: For the safe release of radium-226 to the environment, the following Permissible Concentrations should not be exceeded:

MAXIMUM PERMISSABLE CONCENTRATIONS

<u>FORM</u>	<u>Concentrations in Air</u> (microcuries/milliliter)	<u>Concentration in Water</u> (microcuries/milliliter)
Soluble	$3 \times 10^{-12}$	$3 \times 10^{-8}$
Insoluble	$2 \times 10^{-12}$	$3 \times 10^{-5}$

The release may be limited even further, if a suitable sample of the population is exposed to one-third concentrations in air or water as specified above.

The release in a sanitary sewage system is limited to 0.1 microcuries of radium-226. Radium is exempt from ACE control and regulation and control is a state function. Some states require licensing for possession and use and in others no license is required. Therefore, the disposal, transportation and use of radium in some uses is not subject to the above regulations.

EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Land burial	Not Satisfactory. It has an extremely long half-life and a high radio-toxicity
Near-surface solid storage	Satisfactory
Salt Deposits	satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Radium-226 is a candidate for a National Disposal Site due to its large commercial use and high health hazard.

## SILICA

CHEMICAL FORMULA:  $\text{SiO}_2$

GENERAL DESCRIPTION: Colorless crystalline solid. Also called silicon dioxide, silicic anhydride, cristobalite, quartz, lechatelierite, tridymite.

It also exists in amorphous form as opal, silica gel and fused silica

Molecular Wt.: 60.08      Melting Pt.: 1610°C      Boiling Pt.: 2230°C

Density: (Solid) 2.64-2.66 g/cc      (Gas)

Vapor Pressure:

Flash Pt.:      Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower      Upper

Solubility:

Hot Water: Insoluble      Cold Water: Insoluble

Ethanol: Insoluble      Other: Soluble in HF

DOT Classification:

Coast Guard Classification:

MANUFACTURE: Occurs plentifully in nature as sand, quartz, flint, chalcedony, opal, agate and infusorial earth.

USES: In the manufacture of glass, ceramics, enamels, refractories, abrasives, concrete, bricks, building stones, water glass, and soluble silicates, silicon and its alloys, silicon carbide, silicon-based chemicals and the silicones. As a desiccant, an adsorbent or a catalyst.

TOXICOLOGY: Prolonged inhalation may result in a diffuse fibrosis known and silicosis. This fibrosis may continue to develop for several years after exposure is terminated. This condition is indicated by shortness of breath, and a limitation of chest expansion. There may be a dry cough with increasing susceptibility to tuberculosis. Further progress of the disease results in more severe shortness of breath and cough, marked fatigue, extreme dyspnea and cyanosis, loss of appetite, pleuritic pain and total incapacity to work. If tuberculosis does not supervene, the conditions may eventually cause death from either cardiac failure or destruction of lung tissue with resultant anoxemia.

The Threshold Limit Values and Lethal Dose are:

TLV

Lethal Dose

-

or  $\text{LD}_{50}$ : 3160 mg/kg, rat

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	1	1	U	U	U	1	1	1



OTHER HAZARDS: None

HANDLING, STORAGE, TRANSPORTATION: In handling silica, avoid breathing silica dust.

DISPOSAL: The Provisional Limits and safe disposal of silica into the environment are:

<u>Silica as a Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.1 mg/M <sup>3</sup>	0.01 TLV for Si
Water and Soil	-	-

EVALUATION OF WASTE MANAGEMENT:

<u>DISPOSAL METHODS</u>	<u>EVALUATION</u>
Landfill	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES:

Silica is not a candidate for National Disposal Sites

## SILICON TETRACHLORIDE

CHEMICAL FORMULA:  $\text{SiCl}_4$

GENERAL DESCRIPTION: Colorless, fuming liquid with a suffocating odor. Also called silicon chloride.

Molecular Wt.: 169.90 Melting Pt.: -70°C Boiling Pt.: 57.57°C

Density: (Liquid) 1.483 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Decomposes Cold Water: Decomposes Ethanol: Decomposes

Other: \_\_\_\_\_

DOT Classification: Corrosive liquid, white label

Coast Guard Classification: Corrosive liquid, white label

IATA Classification: Corrosive liquid, white label

1 liter (passenger) 5 liters (cargo)

MANUFACTURE: By reacting silicon carbide with chlorine gas.

USES: In producing smoke screens (fumed silica) in warfare, in the manufacture of high purity silicon, in the synthesis of silicon esters and in making special glass for the electronic industry.

TOXICOLOGY: Basically non-toxic, but is irritating to the eyes and respiratory tract. The Lethal Concentration for silicon tetra chloride is 1h LC<sub>50</sub>: 8000 ppm, rat.

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	3	U	U	2	2	2

OTHER HAZARDS: Silicon tetrachloride emits toxic fumes of hydrochloric acid when heated to decomposition. It will also react with water or steam to produce toxic and corrosive fumes.

HANDLING, STORAGE, TRANSPORTATION: Silicon tetrachloride should be handled carefully. Contact with skin and inhalation of the fumes should be avoided. It should be kept away from heat. The container should be kept tightly closed.

DISPOSAL/REUSE: For the safe disposal of silicon tetrachloride the following Provisional Limits are recommended.

<u>SiCl<sub>4</sub> as a Contaminant in</u>	<u>Maximum Exposure Limit</u>	<u>Basis for Recommendation</u>
Air	0.1 mg/M <sup>3</sup> as Si	0.01 TLV for Si
	<u>Provisional Limit</u>	
Water and Soil	0.50 ppm	Stokinger and Woodward Method

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### DISPOSAL METHOD

Neutralization with soda ash-slaked lime solution. The neutral solution of sodium or calcium chloride is discharged after dilution.

##### EVALUATION

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Waste streams containing silicon tetrachloride can be adequately treated at the site of generation and are not considered candidates for National Disposal Sites.

## SILVER CHLORIDE

CHEMICAL FORMULA: AgCl

GENERAL DESCRIPTION: White crystalline powder.

Molecular Wt.: 143.34 Melting Pt.: 455°C Boiling Pt.: 1550°C

Density: (Solid) 5.561 g/cc (Gas)

Vapor Pressure: 1 mm @ 912°C

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 0.0021g/100 ml@100°C Cold Water: Insoluble

Ethanol: Other: Soluble in NH4OH, Na2S2O3 & KCN

DOT Classification:

Coast Guard Classification:

TOXICOLOGY: Silver compounds absorbed into the circulation and then deposited in various body tissues may produce a generalized greyish pigmentation of the skin and mucous membranes, a condition known as argyria. The introduction of fine particles of silver through breaks of the skin produces a local pigmentation at the site of the injury. Once deposited there is no known method by which the silver can be eliminated. The pigmentation is permanent. There are no constitutional symptoms and no physical disability. The Threshold Limit Value for silver is 0.01 mg/M<sup>3</sup>.

OTHER HAZARDS. Chlorides, when heated to decomposition or on contact with acid or acid fumes, evolve highly toxic chloride fumes.

SODIUM FERROCYANIDE

CHEMICAL FORMULA:  $\text{Na}_4\text{Fe}(\text{CN})_6 \cdot \text{H}_2\text{O}$

GENERAL DESCRIPTION: Pale yellow crystalline solid. Also called yellow prussiate of soda.

Molecular Wt.: 484.11 Melting Pt.: Boiling Pt.:

Density: (Solid) 1.458 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 156.5 g/100 ml @ 98°C Cold Water: 31.58 g/100 ml @ 31.85°C

Ethanol: Insoluble Other:

DOT Classification:

Coast Guard Classification:

USE: As a food and drinking water additive for animals and for the treatment of food producing animals. Permitted in food for human consumption.

## SODIUM FLUORIDE

CHEMICAL FORMULA:  $\text{NaF}$

GENERAL DESCRIPTION: Colorless crystalline solid. Also called villiaumite.

Molecular Wt.: 42.00 Melting Pt.: 993°C Boiling Pt.: 1704°C

Density: (Solid) 2.78 g/cc (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 5 g/100 ml @ 100°C Cold Water: 4 g/100 ml @ 0°C

Ethanol: Very slightly soluble Other:

DOT Classification:

Coast Guard Classification:

MCA Warning Label

MANUFACTURE: By reacting soda ash with 40 percent hydrofluoric acid.

USES: As an insecticide, in other pesticide formulations, in the fluoridation of water, in soldering and metallurgical fluxes, in the manufacture of rimmed steel, in electroplating, as a constituent of vitreous enamel and opal glass mixes, in heat treating salts, for pickling stainless steel, as a disinfectant in breweries and distilleries, as a glue and paste adhesive, preservative, in the manufacture of coated papers.

Sodium fluoride solution is applied topically to the teeth as a 2 percent solution for prevention of dental cavities.

TOXICOLOGY: All alkali and ammonium fluorides can cause both acute and chronic poisoning. It causes extreme nausea and vomiting, perspiration, salivation, burning, cramp-like abdominal pains, diarrhea, dehydration and thirst, muscle weakness, hemorrhagic gastroenteritis, central nervous depression, cyanosis, shock, weak and thready pulse, shallow unlabored respiration, weak heart tones, paralysis of the muscles of deglutation, carpopedal spasm, spasm of the extremities and in extreme cases, death. Chronic contact can cause a crippling disease known as crippling fluorosis.

In animals fluoride poisoning can cause loss of appetite and starvation and in general the same effects as in man. Chronic effects are dental lesions, hypertosis, lameness, loss of appetite, decreased milk production and diminution in reproduction.

In plants fluoride poisoning causes necrosis, where injured portions of the leaves die and become discolored, diminution in the growth or yield of fruit or seeds, changes in physiological activities, metabolic activities and cellular structure, and deposit or accumulation of fluoride in the plant with

increasingly higher concentration of fluoride in the tissues.

The Threshold Limit Value (TLV) for fluoride dust is 2.5 mg/M<sup>3</sup>. The Federal Water Pollution Control Administration Water Quality Criteria recommends permissible limit criteria for fluoride in drinking water ranging from 0.8 mg/l to 1.7 mg/l, for average daily maximum temperature ranging from 50 to 90.5°F and recommends that water for livestock use contain less than 2.4 mg/l of fluoride ion. It also indicates a quality requirement of a maximum of 1 mg/l of fluoride ion in water intended for use by the canned, dried and frozen fruit and vegetable industry.

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	3	3	2	2	1	1

OTHER HAZARDS: Sodium fluoride and all ammonium and alkali fluorides are toxic to all life; yeast, other microorganisms, plant life, both harmful and beneficial, insects, fish and all higher vertebrates.

HANDLING, STORAGE, TRANSPORTATION: Care must be exercised when handling sodium fluoride to prevent contact with the skin or eyes, and to avoid ingestion of dust by inhalation or other means. Food should not be handled near any of the soluble fluorides. In case of contact the skin and eyes should be flushed thoroughly and medical attention obtained. Contaminated clothing should be removed and washed before re-use.

Sodium fluoride is shipped in screw cap bottles for quantities up to 5 lbs; for quantities from 5 lbs. to 400 lbs., polyethylene bag-lined drums or fiber drums are used. The containers should carry a "poison" warning label containing information on treatment and antidotes. The containers should be stored in a cool, dry area, and should be kept tightly closed.

In the disposal of sodium fluoride waste, the following Provisional Limits should be considered:

<u>NaF as a Contaminant</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
in Air	0.025 mg/M <sup>3</sup> as F	0.01 TLV
in Water and Soil	0.6-1.7 ppm (mg/l) as F	Drinking Water Standard

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

Two stage addition of lime slurry to waste containing tin and fluoride from plating.  
Discharge of fluoride stripped liquid to sewers.

#### EVALUATION

Satisfactory

DISPOSAL METHODS

EVALUATION

Dilution and reaction with slaked lime and soda ash and then neutralization with HCl, further dilution and discharge to sewers of the liquid and the sludge is added to landfill.

Satisfactory

Venting of fumes to the atmosphere.

Undesirable due to the pollution of the environment.

Direct discharge to sewers

Undesirable due to the pollution of the environment.

APPLICABILITY TO NATIONAL DISPOSAL SITES: Sodium fluoride is not considered a candidate waste stream constituent for National Disposal Sites. The above satisfactory procedures are not hazardous nor costly and are practical for waste generation site use.



## SODIUM HYPOCHLORITE

CHEMICAL FORMULA: NaOCl

GENERAL DESCRIPTION: Exists only in aqueous solution. Usually contains some sodium hydroxide. Strongly basic.

Molecular Wt.: 74.45 Melting Pt.: d Boiling Pt.: d

Density: (Liquid) --- (Gas) ---

Vapor Pressure: ---

Flash Pt.: --- Autoignition Temperature: ---

Explosive Limits in Air (Wt%): Lower --- Upper ---

Solubility:

Hot Water: d Cold Water: Soluble Ethanol: --

Other: ---

DOT Classification: ---

Coast Guard Classification: ---

MANUFACTURE: Reaction between sodium hydroxide solution and gaseous chlorine; electrolysis of a salt solution.

USES: Disinfectant and deodorant in dairies, creameries, water supply and sewage disposal; bleaching agent for cotton, linen, jute, paper pulp and oranges.

TOXICOLOGY: Not particularly toxic. No TLV established. Irritating to skin and mucous membranes.

OTHER HAZARDS: Oxidizing material. Contact with combustible material should be avoided. May ignite or explode when contaminated with organics or reducing agents.

HANDLING, STORAGE TRANSPORTATION: Avoid contact with reducing agents. Avoid exposure to heat. Skin contact should be avoided.

DISPOSAL/REUSE: Usually not processed for reuse, due to danger involved.

Provisional Limits for Disposal:

<u>Environment</u>	<u>Provisional Limit</u>	<u>Basis For Recommendation</u>
In Air	0.02 mg/M <sup>3</sup>	0.01 TLV for NaOH
Water and Soil	0.01 ppm (mg/l)	Stokinger and Woodward Method

EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHOD

EVALUATION

Reduction by adding to large volume of

Satisfactory

DISPOSAL METHOD

EVALUATION

reducing agent. Release to sewer or stream

Open burning

Not satisfactory, liberates HCl, NO<sub>x</sub>.

Incinerator burning in gas flame. Vent scrubber

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Satisfactory on site disposal.  
Not a candidate for disposal at a National Disposal Site.

## SODIUM MONOXIDE

CHEMICAL FORMULA:  $\text{Na}_2\text{O}$

GENERAL DESCRIPTION: White-grey, deliquescent, crystalline solid. Also called sodium oxide.

Molecular Wt.: 61.99      Melting Pt.: 920°C      Boiling Pt.: 1275°C

Density: (Solid) 2.27 g/cc      (Gas) (sublimes)

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Decomposes      Cold Water: Decomposes

Ethanol: Decomposes      Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: Hazardous material

MANUFACTURE: By controlled burning of sodium in air at temperatures less than 160°C

USES: No commercial use known.

TOXICOLOGY: Sodium monoxide is dangerous due to its caustic property. A Threshold Limit Value (TLV) has not been reported for this material, but NaOH which forms vigorously on contact of  $\text{Na}_2\text{O}$  with moisture or human tissue, has a TLV of 2 mg/M3. The hydroxide is caustic in concentrated form, but neutralization with acid renders it harmless.

The Booz-Allen Ratings are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
2	3	3	2	3	U	1	2	2

OTHER HAZARDS: No other hazards known.

HANDLING, STORAGE, TRANSPORTATION: Sodium monoxide should be stored in cool dry, well-ventilated and preferably fire-resistant areas. Containers should be kept off of the floor, and away from any possible contact with water, combustibles and organic or readily oxidizable materials. Sodium monoxide being a strong caustic should be handled, loaded and shipped in the same manner as sodium hydroxide.

DISPOSAL/REUSE: For the safe disposal of sodium monoxide into the environment the following Provisional Limits are recommended:

<u>Sodium Monoxide as a Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.02 mg/M <sup>3</sup> as NaOH	Provisional Limit for NaOH
Water and Soil	0.01 ppm as NaOH	Provisional Limit for NaOH

EVALUATION OF WASTE MANAGEMENT PRACTICES:

DISPOSAL METHOD

EVALUATION

Neutralized with H<sub>2</sub>SO<sub>4</sub> in settling ponds  
and discharged into rivers

Satisfactory

When Na<sub>2</sub>O is in streams containing Na metal, it is treated the same as the metal which is dumped into the ocean in perforated drums or burned mixed with kerosene in a closed chemical reactor

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Since sodium monoxide waste is adequately handled at the industrial level, it is not considered a candidate for disposal at National Disposal Sites.

# SODIUM NITRITE

CHEMICAL FORMULA:  $\text{NaNO}_2$

GENERAL DESCRIPTION: Yellowish or white crystalline solid. It oxidizes upon exposure to air. Also called diozotizing salt.

Molecular Wt.: 69.01 Melting Pt.:  $271^\circ\text{C}$  Boiling Pt.:  $320^\circ\text{C}$   
Density: (Solid) 2.168 g/cc (Gas) (decomposes)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 163 g/100 ml @  $100^\circ\text{C}$  Cold Water: 72 g/100 ml @  $0^\circ\text{C}$

Ethanol: Slightly soluble Other: 0.3 g/100 ml in ether @  $20^\circ\text{C}$

DOT Classification: Oxidizing material, yellow label

Coast Guard Classification: Oxidizing material, yellow label

MANUFACTURE: By oxidizing into NO and passing the NO into a soda ash solution. The nitrate formed is separated by crystallization in lead lined equipment.

USES: In making dyes, in the preparation of nitric oxide, in pickling metal, in medicine, in rust proofing, in cutting oils and as food preservatives.

TOXICOLOGY: It is not highly toxic. In high concentrations in water it is irritating to skin and mucous membranes. No Threshold Limit Values have been recommended. The Lethal Dose is reported as "or LD<sub>50</sub> 480 mg/kg rat".

The Booz-Allen Ratings are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
3	3	1	2	3	U	U	U	U

OTHER HAZARDS: Sodium nitrite is both a reducing agent and an oxidizing agent. It is a fire hazard when in contact with organic or other easily oxidized material and is corrosive to most metals.

HANDLING, STORAGE, TRANSPORTATION: May be handled or stored as strong solutions in lead-lined containers.

DISPOSAL/REUSE: When in sufficient quantity,  $\text{NaNO}_2$  can be reprocessed for reuse. The Recommended Provisional Limits are:

<u>Sodium Nitrite in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.02* mg/M <sup>3</sup>	0.01 TLV*
Water and Soil	0.10* mg/l	Stokinger and Woodward Method

\* Estimated

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### DISPOSAL METHOD

Dilution of the waste with large amounts of water containing soda ash and then adding calcium hypochlorite. Then neutralization with HCl, diluted and discharged to sewer or stream. Any sludge is added to Class 2 type landfill.

##### EVALUATION

Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: This material has been classed as a probable waste stream constituent for municipal disposal and is not considered a candidate for treatment at a National Disposal Site.

## SODIUM SULFATE

CHEMICAL FORMULA:  $\text{Na}_2\text{SO}_4$

GENERAL DESCRIPTION: White odorless crystals or powder.

Molecular Wt.: 142.06 Melting Pt.: 888°C Boiling Pt.: \_\_\_\_\_

Density: (Solid) 2.67 g/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility: \_\_\_\_\_

Hot Water: \_\_\_\_\_ Soluble Cold Water: \_\_\_\_\_ Soluble

Ethanol: \_\_\_\_\_ Insoluble Other: \_\_\_\_\_ Soluble in glycerin

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

OTHER HAZARDS: When heated to decomposition sodium sulfate emits highly toxic fumes of oxides of sulfur.

TOXICOLOGY: Unknown.

## SODIUM SULFITE

CHEMICAL FORMULA:  $\text{Na}_2\text{SO}_3$

GENERAL DESCRIPTION: White crystalline powder.

Molecular Wt.: 126.05 Melting Pt.: decomposes Boiling Pt.: \_\_\_\_\_

Density: (Solid) 2.633 g/cc @ 15.4°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: 28.3 g/100 ml @ 80°C Cold Water: 12.54 g/100 ml @ 0°C

Ethanol: Slightly soluble Other: \_\_\_\_\_

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

MANUFACTURE: The most important commercial manufacturing process is the reaction of sulfur dioxide with a solution of soda ash. Another commercial source of sodium sulfite is as a byproduct from the preparation of phenol by the fusion of sodium benzene sulfonate with sodium hydroxide. Sodium sulfite is also recovered from paper mill cellulose waste liquors.

USES: It is used to bleach wool and silk and as an "antichlor" after bleaching yarns, textiles and paper, as a preservative for foodstuff and to prevent raw sugar solutions from coloring upon evaporation. It is also used in photography, medicine and to remove oxygen from boiler water.

TOXICITY: Sodium sulfite is not highly toxic. High concentrations are irritating to the skin and mucous membranes. No Threshold Limit Values have been established.

The Booz-Allen Ratings are:

HUMAN			ECOLOGICAL			EXPLOSION		
Air	Water	Land	Air	Water	Land	Air	Water	Land
2	2	1	2	2	U	2	2	2

OTHER HAZARDS: Sodium sulfite is corrosive to most metals.

HANDLING, STORAGE, TRANSPORTATION: Strong solutions of sodium sulfite can be handled and stored in lead lined equipment.

DISPOSAL/REUSE: Industrially contaminated material when in sufficient quantity can be reprocessed for reuse.

For safe disposal of sodium sulfite into the environment, the following Provisional Limits are recommended:



<u>Contaminant in</u>	<u>Provisional Limit</u>	<u>Basis for Recommendation</u>
Air	0.02* mg/M <sup>3</sup>	0.01* TLV
Water and Soil	0.01* mg/l	Stokinger and Woodward Method

\*Estimated

#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

##### DISPOSAL METHODS

##### EVALUATION

Dilution with large volumes of water followed by reaction with soda ash, calcium hypochlorite and HCl then discharge into the sewer system. Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Waste treatment for sodium sulfite can be handled adequately locally and is not considered to be a candidate for treatment at National Disposal Sites.

STANNIC OXIDE

CHEMICAL FORMULA:  $\text{SnO}_2$

GENERAL DESCRIPTION: White crystalline solid. Also called cassiterite.

Molecular Wt.: 150.70 Melting Pt.:  $1127^\circ\text{C}$  d Boiling Pt.: \_\_\_\_\_

Density: (Solid) 6.95 g/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Insoluble Cold Water: Insoluble

Ethanol: \_\_\_\_\_ Other: Decomposes in KOH & NaOH

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: The dust of tin oxides have been known to cause pneumoconiosis which is usually benign.

## SULFURIC ACID

CHEMICAL FORMULA:  $\text{H}_2\text{SO}_4$

GENERAL DESCRIPTION: Colorless, corrosive, oily liquid. Also called oil of vitriol and dipping acid.

Molecular Wt.: 98.98 Melting Pt.: 10.36°C (100) Boiling Pt.: 338°C (98.3%)

Density: (Liquid) 1.834 g/cc (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Infinitely Cold Water: Infinitely Ethanol: Decomposes

Other: \_\_\_\_\_

DOT Classification: Corrosive liquid, white label

Coast Guard Classification: \_\_\_\_\_

MCA Warning Label

IATA Classification: Corrosive liquid, white label;  
1 liter (passenger) 5 liters (cargo)

### MANUFACTURE:

USES: (1) 44% of the  $\text{H}_2\text{SO}_4$  produced in the U.S. is used to manufacture superphosphate and phosphate-type fertilizers.

(2) 21% is used in the chemical industry.

(3) 10% is used in the petroleum industry.

(4) Other major uses are in the manufacture of titanium pigments, steel pickling, rayon, dyes, detergents, etc.

TOXICOLOGY: Sulfuric acid is very corrosive to all body tissues. Contact with eyes may result in total loss of vision and skin contact may produce severe necrosis. Inhalation of concentrated vapor may cause serious lung damage. Ingestion may cause severe injury and death.

The Threshold Limit Values (TLV) and Lethal Doses are:

#### TLV

1.0 mg/M<sup>3</sup>

#### Lethal Dose or Concentration

ih LC<sub>50</sub>: 500 mg/M<sup>3</sup>, rat  
or LD<sub>50</sub>: 2.40 mg/kg, rat

The Booz-Allen Ratings are:

<u>HUMAN</u>			<u>ECOLOGICAL</u>			<u>EXPLOSION</u>		
<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>	<u>Air</u>	<u>Water</u>	<u>Land</u>
3	3	3	2	3	U	2	2	2

OTHER HAZARDS: Sulfuric acid is a powerful oxidizing agent and can ignite upon contact with combustibles. It also has a strong affinity for water, generating much heat in mixing.

HANDLING, STORAGE, TRANSPORTATIONS: Corrosive materials such as sulfuric acid must be handled carefully. Contact with the skin and inhalation should be avoided. It should be kept away from feed and food products. Sulfuric acid should be kept tightly closed.

DISPOSAL/REUSE: For the safe disposal of  $H_2SO_4$  into the environment the following Provisional Limits are recommended.

<u>H<sub>2</sub>SO<sub>4</sub> as a Contaminant</u>	<u>Maximum Exposure Limit</u>	<u>Basis for Recommendation</u>
in Air	0.01 mg/M <sup>3</sup>	0.01 TLV
Water and Soil	0.05 ppm (mg/l)	Stokinger and Woodward Method


#### EVALUATION OF WASTE MANAGEMENT PRACTICES:

<u>DISPOSAL METHOD</u>	<u>EVALUATION</u>
Regeneration	Best choice when economically feasible
Neutralization with soda ash-slaked lime solution. The calcium sulfate is then removed by filtration.	Satisfactory

APPLICABILITY TO NATIONAL DISPOSAL SITES: Sulfuric acid as a waste stream constituent is not considered to be a candidate for disposal at a National Disposal Site.

TEREPHTHALIC ACID

CHEMICAL FORMULA:  $C_6H_4(COOH)_2$  /



GENERAL DESCRIPTION: White crystalline solid. IUC Name: 1,4 benzenedicarboxylic acid. Also called p-phthalic acid, TPA, and benzene-p-dicarboxylic acid.

Molecular Wt.: 166.13 Melting Pt.: Sublimes Boiling Pt.: Sublimes

Density: (Solid) 1.510 g/cc (Gas) /approx 300°C

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 0.0016 g/100 ml Cold Water:

Ethanol: Very slightly soluble Other: Very slightly soluble in ether and chloroform. Soluble in alkali.

Coast Guard Classification:

DOT Classification:

# THORIUM-230

CHEMICAL FORMULA:  ${}_{90}^{230}\text{Th}$

GENERAL DESCRIPTION: Gray radioactive solid  
 Atomic Wt.: 23 Melting Pt.: 1845°C Boiling Pt.: 4500°C  
 Density: (Solid) 11.2 g/cc (Gas)  
 Type of Decay: Alpha Half-Life:  $8 \times 10^4$  years  
 Flash Pt.: Autoignition Temperature:  
 Explosive Limits in Air (Wt%): Lower Upper  
 Solubility:  
     Hot Water: Insoluble Cold Water: Insoluble  
     Ethanol: Other: Soluble in HCl, H<sub>2</sub>SO<sub>4</sub>, and  
     aqua regia. Slightly soluble in HNO<sub>3</sub>.  
 DOT Classification: Flammable solid, yellow label, 25 pounds  
 Coast Guard Classification: Flammable solid, yellow label  
 IATA Classification: Flammable solid, yellow label  
     Not acceptable (passenger), 12 kilograms (cargo)  
 Decays to radioactive radium-226 by emitting alpha particles.

OTHER HAZARDS: Moderate, in the form of dust, when exposed to heat or flame or by chemical reaction with oxidizers.

HANDLING, STORAGE, TRANSPORTATION: Avoid, inhalation, ingestion or radiation exposure.

DISPOSAL/REUSE: For the safe disposal of Thorium-230 into the environment the following Permissible Concentrations should not be exceeded:


## MAXIMUM PERMISSABLE CONCENTRATIONS

<u>Form</u>	<u>Concentrations in Air</u> <u>micorcuries/millileter</u>	<u>Concentration in Water</u> <u>microcuries/millileter</u>
Soluble	$8 \times 10^{-14}$	$2 \times 10^{-5}$
Insoluble	$3 \times 10^{-13}$	$3 \times 10^{-5}$

## TOLUENEDIAMINE

### 2, 4-TOLUENEDIAMINE

CHEMICAL FORMULA:  $\text{CH}_3\text{C}_6\text{H}_3(\text{NH}_2)_2$ ,



GENERAL DESCRIPTION: Colorless crystalline solid. Also called tolyenediamine, 2,4-diaminotoluene and 2,4-toluylenediamine.

Molecular Wt.: 122.17      Melting Pt.: 99°C      Boiling Pt.: 280°C

Density: (Solid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: 1 mm @ 106.5°C

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Soluble      Cold Water: Soluble

Ethanol: Very soluble      Other: Very soluble in ether


DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

IATA Classification: Poison B, poison label  
25 kilograms (passenger) 95 kilograms (cargo)

### 2, 5-TOLUENEDIAMINE

CHEMICAL FORMULA:  $\text{CH}_3\text{C}_6\text{H}_4(\text{NH}_2)_2$ ,



GENERAL DESCRIPTION: Colorless crystalline solid. Also called, 2,5-toluylenediamine, 2,5-diaminotoluene and 2,5 toluylenediamine.

Molecular Wt.: 122.17      Melting Pt.: 64°C      Boiling Pt.: 274°C

Density: (Solid) \_\_\_\_\_ (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: \_\_\_\_\_ Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: Very soluble      Cold Water: Very soluble

Ethanol: Very soluble      Other: Very soluble in ether

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: These materials can have a toxic effect upon the liver, causing fatty degeneration. They are though to be irritant. Upon contact with the skin they can cause irritations and blisters. 2,5-Toluenediamine can also be toxic to the central nervous system, produce jaundice by its


action on the liver and spleen and produce anemia. It can also produce permanent injury to the eye.

OTHER HAZARDS: They are moderate fire hazards when heated they emit highly toxic fumes.

HANDLING, STORAGE, TRANSPORTATION: Store in a cool, well ventilated area away from heat and flames. Avoid contact with the skin or eyes. Avoid inhalation and ingestion.



para -TOLUIC ACID



GENERAL DESCRIPTION: White crystalline solid. Also called para-methylbenzoic acid.

Molecular Wt.: 136.14 Melting Pt.: 179.6°C Boiling Pt.: 275°C

Density: (Solid) (Gas)

Vapor Pressure:

Flash Pt.: Autoignition Temperature:

Explosive Limits in Air (Wt%): Lower Upper

Solubility:

Hot Water: 1.26 g/100 ml @ 100°C Cold Water: 0.034 g/100 ml

Ethanol: Very soluble Other: Very soluble in ether

DOT Classification:

Coast Guard Classification:

## URANIUM

CHEMICAL FORMULA: U

GENERAL DESCRIPTION: Silver white or black crystals. There are four natural isotopes; U232, U234, U235 and U238 and four artificial isotopes; U230, U233, U236 and U240

Atomic Wt.: 238.07 Melting Pt.: Approximately 1133°C Boiling Pt.: Ignites

Density (Solid) 18.7 g/cc

Solubility:

Cold Water: Insoluble Hot Water: Insoluble Ethanol: Insoluble

Other: Soluble in acid, insoluble in alkali

The radioactive decay of the isotopes are:

<u>Isotope</u>	<u>Half-life</u>	<u>Emission Particle</u>	<u>Radiation Energy Level and Intensity</u>	<u>Decays to</u>
U230	29 days	alpha	5.8-5.9 MeV	Th-226
U232	74 years	alpha	5.3 MeV	Th-228
		gamma	0.06 MeV	
U233	$1.6 \times 10^5$ years	alpha	4.8 MeV	Th-229
U234	$2.5 \times 10^5$ years	alpha	4.7-4.8 MeV	Th-230
U235	$7 \times 10^8$ years	alpha	4.3-4.6 MeV	Th-231
U236	$2.4 \times 10^7$ years	alpha	4.5 MeV	Th-232
U238	$4.5 \times 10^9$ years	alpha	4.2 MeV	Th-234
U240	14 hours	beta	0.36 MeV	Np-249

DOT Classification: Poison D, radioactive materials, red label.

IATA Classification: Radioactive material, red label  
2000 millicuries (passenger and cargo)

TOXICOLOGY: The high chemical toxicity of uranium and its salts is largely shown in kidney damage and acute necrotic arterial lesions. Relatively large amounts tend to be taken in due to the rapid passage of soluble uranium compounds through the body. The highly toxic effect of insoluble compounds is largely due to lung irritation by inhaled particles.

This material is transferred from the lungs of animals quite slowly.

OTHER HAZARDS: A fire hazard in the form of a solid or dust when exposed to heat or flame and an explosion hazard when the dust is exposed to flame.

HANDLING, STORAGE, TRANSPORTATION: Avoid inhaling the dust, ingestion or exposure to radiation. Store away from fire and flame in a way to prevent exposure to personnel.

DISPOSAL/REUSE: For the safe release of uranium into the environment the

following Permissible Maximum Concentrations should not be exceeded:

MAXIMUM PERMISSIBLE CONCENTRATIONS

<u>Isotope</u>	<u>Form</u>	<u>Concentrations in Air</u> <u>(microcuries/millileter)</u>	<u>Concentration in Water</u> <u>(microcuries/millileter)</u>
Uranium 230	Soluble	$1 \times 10^{-11}$	$5 \times 10^{-6}$
	Insoluble	$4 \times 10^{-12}$	$5 \times 10^{-6}$
Uranium 232	Soluble	$3 \times 10^{-12}$	$3 \times 10^{-5}$
	Insoluble	$9 \times 10^{-13}$	$3 \times 10^{-5}$
Uranium 233	Soluble	$2 \times 10^{-11}$	$3 \times 10^{-5}$
	Insoluble	$4 \times 10^{-12}$	$3 \times 10^{-5}$
Uranium 234	Soluble	$2 \times 10^{-11}$	$3 \times 10^{-5}$
	Insoluble	$4 \times 10^{-12}$	$3 \times 10^{-5}$
Uranium 235	Soluble	$2 \times 10^{-11}$	$3 \times 10^{-5}$
	Insoluble	$4 \times 10^{-12}$	$3 \times 10^{-5}$
Uranium 236	Soluble	$2 \times 10^{-11}$	$3 \times 10^{-5}$
	Insoluble	$4 \times 10^{-12}$	$3 \times 10^{-5}$
Uranium 238	Soluble	$3 \times 10^{-12}$	$4 \times 10^{-5}$
	Insoluble	$5 \times 10^{-12}$	$4 \times 10^{-5}$
Uranium 240	Soluble	$8 \times 10^{-9}$	$3 \times 10^{-5}$
	Insoluble	$6 \times 10^{-9}$	$3 \times 10^{-5}$
Uranium (nat)	Soluble	$3 \times 10^{-12}$	$2 \times 10^{-5}$
	Insoluble	$2 \times 10^{-12}$	$2 \times 10^{-5}$

## VALERIC ACID

CHEMICAL FORMULA:  $\text{CH}_3(\text{CH}_2)_3\overset{\text{O}}{\underset{\text{OH}}{\text{C}}}$

GENERAL DESCRIPTION: Colorless liquid. Unpleasant odor. IUC Name: Penta-noic acid.

Molecular Wt.: 102.13 Melting Pt.: -34.5°C Boiling Pt.: 187°C

Density: (Liquid) 0.942 g/cc @ 20°C (Gas) \_\_\_\_\_

Vapor Pressure: \_\_\_\_\_

Flash Pt.: 205°F (O.C.) Autoignition Temperature: \_\_\_\_\_

Explosive Limits in Air (Wt%): Lower \_\_\_\_\_ Upper \_\_\_\_\_

Solubility:

Hot Water: \_\_\_\_\_ Cold Water: 3.7 g/100 ml @ 16°C

Ethanol: Infinitely Other: Infinitely soluble in ether

DOT Classification: \_\_\_\_\_

Coast Guard Classification: \_\_\_\_\_

TOXICOLOGY: Probably a moderate toxic and high irritant based on animal ex-periments.

OTHER HAZARDS: Fire hazard when exposed to heat and flame and can react with oxidizing materials.

HANDLING, STORAGE, TRANSPORTATION: Avoid breathing of fumes and skin con-tact. Store in a cool well ventilated area, away from heat, flames and ox-idizing materials.

## SECTION XI

### APPENDIX C

#### REFERENCES CITED

1. Booz, Allen - Applied Research, Inc., Hazardous Waste Materials: Hazardous Effects and Disposal Methods, U. S. Environmental Protection Agency, Washington, D.C., Vol. 1, Sec. 4, 48 pp, 1973.
2. Hodgman, C. D., et al, Handbook of Chemistry and Physics, Chemical Rubber Publishing Co., Cleveland, 41st Ed., 3472 pp, 1968.
3. Sax, N. I., Dangerous Properties of Industrial Materials, Reinhold Publishing Corp., New York, 3rd Ed., 1251 pp, 1968.
4. Ottinger, R. S., et al, Recommended Methods of Reduction, Neutralization, Recovery or Disposal of Hazardous Waste, U. S. Environmental Protection Agency, EPA - 670/2/73-053 f, Washington, D. C., Vols. 6-13, 1973.

<b>TECHNICAL REPORT DATA</b> <i>(Please read Instructions on the reverse before completing)</i>		
1. REPORT NO. EPA-600/2-77-029b	2.	3. RECIPIENT'S ACCESSION NO.
4. TITLE AND SUBTITLE REVIEW AND ASSESSMENT OF DEEP-WELL INJECTION OF HAZARDOUS WASTE Volume II - Appendices A, B, & C	5. REPORT DATE June 1977 (Issuing Date)	6. PERFORMING ORGANIZATION CODE
7. AUTHOR(S) Louis R. Reeder, James H. Cobbs, John W. Field, Jr., William D. Finley, Steven C. Vokurka, and Bernard N. Rolfe	8. PERFORMING ORGANIZATION REPORT NO.	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Louis R. Reeder and Associates 5200 South Yale Tulsa, Oklahoma 74135	10. PROGRAM ELEMENT NO. 1DC618, (SOS 2, Task 02)	11. CONTRACT/GRANT NO. 68-03-2013
12. SPONSORING AGENCY NAME AND ADDRESS Cin., OH Municipal Environmental Research Laboratory-- Office of Research and Development U.S. Environmental Research Cincinnati, Ohio 45268	13. TYPE OF REPORT AND PERIOD COVERED Final Report	14. SPONSORING AGENCY CODE EPA/600/14
15. SUPPLEMENTARY NOTES See also Volumes I, III, & IV, EPA-600/2-77-029a,c,&d Project Officer: Carlton C. Wiles, 684-7881		
16. ABSTRACT This four volume report is a review and assessment of the adequacy of deep-well waste injection systems to receive hazardous wastes and to define what effects that these wastes will have upon the environment when injected into subsurface reservoirs. All aspects of deep-well injection systems have been touched upon.  A comprehensive bibliography, chemical waste profiles, deep-well inventory, case histories, microbiological research, deep-well and hazardous waste research, legal aspects and an inventory of statutes and regulations governing waste injection are discussed in the text and detailed in the appendices.		
17. KEY WORDS AND DOCUMENT ANALYSIS		
a. DESCRIPTORS	b. IDENTIFIERS/OPEN ENDED TERMS	c. COSATI Field/Group
Waste Disposal Deep-Wells Hazardous Materials Industrial Wastes	Industrial Waste Disposal Underground Disposal Deep-Well Disposal Waste Disposal Wells Hazardous Waste Injection	13B
18. DISTRIBUTION STATEMENT  RELEASE TO PUBLIC	19. SECURITY CLASS (This Report) UNCLASSIFIED	21. NO. OF PAGES 316
	20. SECURITY CLASS (This page) UNCLASSIFIED	22. PRICE