

Technical Report

Heavy-Duty Engine Testing Report

Correlation Testing of The European EMA  
Round Robin Engine (Daimler-Benz OM 366 A)

By

Thomas M. Baines

December, 1987

Notice

Technical Reports do not necessarily represent final EPA decisions or positions. They are intended to present technical analysis of issues using data which are currently available. The purpose in the release of such reports is to facilitate the exchange of technical information and to inform the public of technical developments which may form the basis for a final EPA decision, position or regulatory action.

Standards Development and Support Branch  
Emission Control Technology Division  
Office of Mobile Sources  
Office of Air and Radiation  
U.S. Environmental Protection Agency

Correlation Testing of the European  
EMA Round Robin  
Engine (Daimler-Benz OM 366A)

## I. Introduction

The Environmental Protection Agencies' Selective Enforcement Audit (SEA) program requires correlation testing to take place between EPA's MVEL heavy duty (HD) engine testing facility and that of the manufacturer who produces engines for sale in the United States. There are five European manufacturers of HD engines that participate in the U.S. market and have their own HD testing facility in Europe. These manufacturers are members of the Engine Manufacturers Association (EMA) and are referred to as "European EMA" members.

In order to comply with the SEA program's facility correlation requirement, the European EMA members organized a round robin testing program. They decided to test a Daimler-Benz OM 366A engine, and to focus the program on gathering simple cold start/hot start Federal Test Procedure data. (Such a program contrasts with the U.S. EMA/CRC/EPA program wherein various test procedure questions were addressed in each laboratories' test plans.)

The D-B OM 366A engine was selected in part because it did not require a charge air cooler system, which is cumbersome to transport and set up at various facilities, and partly because this particular engine had been tested once already at the EPA/MVEL.

The engine was circulated among the five European EMA laboratories in the spring and early summer of 1987. It was then shipped to the EPA/MVEL in mid summer, 1987. The engine was tested at the MVEL in the first weeks of September, 1987 and was subsequently returned to Daimler-Benz. (This engine may be used for a second round of testing among the European EMA laboratories.) The purpose of this report is to present and discuss the results of the EPA testing of the D-B OM 366A. The comparisons will be with the most recent D-B testing. The comparison with the results observed in the other four European EMA laboratories will be presented in a different report. Some limited comparisons will be made to the previous EPA and D-B test program which was reported in EPA report EPA-AA-SDSB-86-02.

## II. Engine Test Procedures and Fuels

The 1984 Daimler-Benz OM 366A is an in-line, 6 cylinder, direct injection, turbocharged, four-stroke per cycle diesel engine. It is rated at 171 hp at 2600 rpm. The engine was

tested at the MVEL facility with all normal Federal Test Procedures adhered to. Three cold start and six hot start transient tests were run as well as two sets of four steady state modes. Copies of the individual transient test and steady state test results are included in the Appendix. Phillips DOE reference Fuel (lot G-668) was used during the test, and a copy of the fuel analysis is included in the Appendix. Dilution tunnel flow rate was 3000 CFM, and inlet fuel temperature was limited to 110°F. The shut down procedure employed was fuel pump shut off and simultaneous dynamometer dial-down.

### III. Test Results

The initial part of testing HD engines is to map the wide open throttle torque characteristics of the engine as a function of speed. This data is then used to denormalize the engine operating cycle to form the engine reference cycle. One way to compare this process between laboratories is to look at the subsequent integrated reference brake horsepower-hour figure. If both labs have the same map results (which can be indicated by the engine performance values of idle speed, peak torque, peak torque speed and rated power) then both labs should have the same integrated reference brake horsepower-hour figure, provided of course, the denormalization process was done correctly.

The engine performance test results (see Table 1) measured at MVEL show close agreement to results previously obtained with this engine (see EPA-AA-SDSB-86-02), and in addition, are in good agreement with current Daimler-Benz results in the areas of rated power, maximum torque speed, and maximum torque output of this engine. In the previous correlation testing, integrated reference horsepower results between EPA and Daimler-Benz were in very good agreement, in line with the rest of the engine performance results. Daimler-Benz results for the current cycle of correlation tests shows a 3.4 percent increase in integrated reference horsepower from previous D-B results and is 4.2 percent higher than the current EPA integrated reference horsepower. This is unexpected and not understood considering the consistency in the engine performance data.

The transient emissions data are presented in Tables 2, 3 and 4, which contain the composite, cold start, and hot start data, respectively. The repeatability of the EPA data is generally very good with coefficients of variation (COV) well within the expected values. The only exception to this is the COV for particulate which is about seven percent. This is at the high end of what is usually expected for particulate emissions.

As for comparisons between laboratories, the composite data will be emphasized, as it is representative of the whole data set. The HC levels measured at MVEL were an average of 0.98 g/BHP-hr. The D-B HC values were about 11 percent higher than this, or 1.09 g/BHP-hr. When EPA previously tested this engine, the HC values were significantly higher than either the current EPA values or the D-B HC value. The reasons for this variability are not understood at this time.

With regard to the other emissions, there was very good agreement between labs in NOx values. The CO, particulate and BSFC values were all higher at the D-B lab than the MVEL and the magnitude of the difference between labs was near the upper limit of what one would expect for these measurements. In other words, the agreement on these values is marginal but probably acceptable.

#### IV. Conclusions

In summary, EPA tested the Daimler-Benz OM 366A engine for correlation with results from five European EMA laboratories. The comparisons discussed in the report are with D-B data. The conclusions from this work are:

1. Average composite transient test results were, in g/BHP-hr, 0.98 HC, 2.42 CO, 7.82 NOx, 0.44 PM, and 0.400 lb/BHP-hr BSFC.

2. There was close agreement between the EPA and D-B laboratories on engine performance data, and differences are minimal when compared to the same data from the previous testing of this engine by the same two facilities. EPA's data for integrated reference BHP-hr changed by -1.2 percent from the previous test to this one, but Daimler-Benz had a change of +3.4 percent. This change is not expected considering the close agreement of all other performance data and is unexplained.

3. In comparing emissions between the two labs, the following conclusions were reached:

- HC values from this engine appear quite variable as previous EPA testing had results much higher than D-B. Current testing shows D-B results to be about 11 percent higher than EPA. The reasons for this are not known.
- NOx correlation between labs was excellent (less than 1 percent difference).
- CO, particulate and BSFC values were all higher at D-B than at EPA and in magnitude were at the upper limit of what would be considered good lab-to-lab correlation.

Table 1

Table of Engine Performance Data from Testing of the  
Daimler-Benz OM 366A Correlation Engine

<u>Lab</u>	Curb Idle, <u>RPM</u>	Max. Power <u>BHP</u>	Max. Speed, <u>RPM</u>	Max. Torque Point Speed, <u>RPM</u>	Torque, Ft.-lb.	Integrated Reference Horsepower, <u>BHP-hr</u>
EPA	600	171	2583	1556	403	10.845
D-B	600	171	2600	1560	408	11.30

Table 2

Table of Composite Transient Test Emission  
Results From the European EMA Round  
Robin Correlation Engine (D-B OM 366A)

<u>Test No.</u>	<u>Emissions, q/BHP-Hr</u>				<u>BSFC, lb/BHP-Hr</u>
	<u>HC</u>	<u>CO</u>	<u>NOx</u>	<u>Part</u>	
3690					
3691	0.99	2.50	7.66	0.44	0.387
3694					
3695	1.01	2.41	8.10	0.47	0.412
3699					
3700	<u>0.94</u>	<u>2.34</u>	<u>7.69</u>	<u>0.41</u>	<u>0.402</u>
$\bar{X}$	0.98	2.42	7.82	0.44	0.400
(S/ $\bar{X}$ )100	3.8	3.3	3.2	6.8	3.1
D-B $\bar{X}$	1.09	2.60	7.75	0.48	0.413
<u>% Difference Relative to EPA</u>					
	+11.2	+7.4	-.9	+9.1	+3.3

Table 3

Table of Cold Start Emission Results  
from the European EMA Round Robin  
Correlation Engine (D-B OM 366A)

<u>Test No.</u>	Emissions, g/BHP-Hr				<u>BSFC,</u> <u>lb/BHP-Hr</u>
	<u>HC</u>	<u>CO</u>	<u>NOx</u>	<u>Part</u>	
3690	1.25	3.04	8.07	0.51	0.390
3694	1.27	3.10	8.60	0.50	0.427
3699	<u>1.27</u>	<u>3.27</u>	<u>7.95</u>	<u>0.48</u>	<u>0.418</u>
$\bar{X}$	1.26	3.14	8.21	0.50	0.412
(S/ $\bar{X}$ )100	1.1	3.8	4.2	3.1	4.7
D-B $\bar{X}$	1.30	3.25	7.81	0.57	0.428
<u>% Difference Relative to EPA</u>					
	+2.8	+3.5	-4.8	+14.0	+3.9

\*3 tests

Table 4

Table of Hot Start Emission Results  
from the European EMA Round Robin  
Correlation Engine (D-B OM 366A)

<u>Test No.</u>	<u>Emissions, g/BHP-Hr</u>				<u>BSFC, lb/BHP-Hr</u>
	<u>HC</u>	<u>CO</u>	<u>NOx</u>	<u>Part</u>	
3691	0.95	2.41	7.59	0.43	0.387
3692	1.01	2.29	7.68	0.47	0.384
3693	0.99	2.17	7.43	0.47	0.377
3695	0.97	2.30	8.02	0.46	0.409
3696	0.97	2.35	8.14	0.43	0.408
3697	0.98	2.27	8.01	0.40	0.408
3700	0.88	2.19	7.65	0.40	0.399
3701	0.97	2.29	7.75	0.40	0.398
3702	<u>0.87</u>	<u>2.22</u>	<u>7.85</u>	<u>0.40</u>	<u>0.395</u>
$\bar{X}$	0.95	2.28	7.79	0.43	0.396
(S/ $\bar{X}$ )100	4.8	3.3	3.0	7.2	2.9
D-B $\bar{X}$	1.05	2.45	7.69	0.47	0.406
<u>% Difference Relative to EPA</u>					
	+10.1	+7.5	-1.3	+9.3	+2.5

\*3 tests

Appendix Contents

EPA Map Data

EPA Transient Test Summary Sheets

EPA Steady State Summary Table

Fuel Analysis

Daimler-Benz Data

    Engine Set-up Data

    Transient Test Results

    Steady State Test Results (4-Mode)

    Smoke Results

    Steady State Test Results (8-Modes)

Data Points From Mapping of the  
D-B OM 366 A European Round Robin  
Engine on July 30, 1987 at  
the EPA-MVEL  
Speed in RPM  
Torque in ft-lb

THERE ARE ( 302 ) MAPPING DATA POINTS:

554.	202.0	922.	339.2	1291.	378.8	1661.	400.4	2031.	375.2	2400.	357.2
558.	207.6	929.	336.8	1299.	380.8	1670.	401.6	2037.	375.2	2408.	357.2
561.	220.0	937.	334.4	1306.	381.6	1677.	402.0	2046.	375.6	2415.	357.6
566.	226.8	945.	334.0	1315.	381.6	1683.	402.0	2053.	374.8	2423.	356.0
582.	234.0	952.	334.8	1321.	384.4	1691.	402.4	2061.	374.4	2430.	355.6
592.	240.4	958.	334.4	1328.	384.8	1697.	399.6	2068.	374.4	2437.	355.2
598.	248.8	965.	334.8	1335.	386.4	1704.	397.2	2075.	374.4	2445.	354.8
605.	252.0	974.	336.4	1343.	386.8	1711.	395.6	2083.	375.2	2451.	355.2
615.	254.0	981.	337.2	1351.	388.0	1721.	393.6	2090.	374.0	2460.	354.4
620.	257.2	989.	339.2	1360.	391.6	1727.	390.8	2096.	373.6	2467.	354.0
629.	258.8	996.	339.2	1366.	390.4	1736.	388.8	2104.	373.2	2473.	353.2
635.	261.6	1003.	339.6	1374.	390.0	1741.	388.0	2112.	374.4	2479.	352.4
641.	263.6	1009.	340.4	1381.	392.0	1749.	385.6	2119.	373.6	2488.	351.2
648.	264.8	1018.	340.4	1388.	393.2	1756.	384.8	2126.	374.0	2496.	351.6
657.	267.6	1025.	340.0	1394.	393.2	1764.	384.4	2134.	372.8	2504.	351.2
664.	270.0	1033.	339.8	1404.	391.6	1771.	386.8	2142.	371.6	2512.	351.6
671.	271.6	1040.	339.6	1411.	392.8	1780.	386.4	2150.	371.2	2520.	351.2
677.	273.6	1047.	341.2	1416.	392.4	1786.	387.2	2156.	370.0	2527.	350.8
688.	274.4	1055.	342.0	1423.	393.2	1794.	384.0	2163.	368.4	2534.	350.0
693.	275.6	1062.	342.0	1432.	394.0	1801.	382.4	2170.	367.6	2540.	349.6
700.	277.2	1069.	342.8	1439.	394.8	1809.	382.8	2178.	367.6	2549.	348.4
708.	278.4	1077.	342.4	1448.	395.6	1816.	382.4	2185.	366.4	2557.	348.4
715.	281.2	1084.	343.2	1454.	396.0	1824.	382.0	2194.	366.0	2563.	348.0
721.	282.8	1091.	342.8	1462.	397.6	1831.	380.8	2200.	365.2	2570.	347.6
729.	284.4	1097.	342.4	1467.	398.0	1838.	380.4	2207.	364.4	2577.	345.6
737.	286.0	1106.	342.8	1476.	398.8	1846.	379.6	2214.	364.0	2585.	345.6
748.	289.2	1113.	343.2	1484.	398.4	1853.	380.0	2223.	363.6	2593.	345.6
752.	290.4	1120.	344.0	1492.	400.0	1860.	380.0	2230.	363.6	2601.	342.4
760.	292.8	1129.	344.8	1499.	400.8	1868.	378.4	2238.	363.6	2609.	342.4
766.	293.6	1136.	345.6	1506.	402.0	1876.	378.0	2244.	364.0	2615.	341.6
775.	295.2	1144.	346.4	1512.	401.6	1881.	376.8	2252.	362.8	2623.	341.2
781.	297.2	1151.	347.6	1521.	401.6	1890.	375.6	2260.	362.4	2629.	340.0
790.	299.2	1158.	349.2	1527.	402.0	1897.	375.6	2268.	362.4	2637.	338.8
797.	302.4	1166.	350.8	1536.	402.0	1904.	374.8	2273.	362.0	2644.	336.8
806.	304.8	1174.	352.4	1543.	402.4	1913.	374.4	2281.	360.8	2651.	336.4
810.	305.2	1180.	354.0	1550.	402.8	1919.	373.6	2289.	360.4	2659.	334.4
818.	307.6	1189.	355.6	1556.	402.8	1926.	373.6	2297.	360.4	2666.	330.4
825.	309.6	1194.	357.6	1565.	402.8	1935.	373.2	2303.	360.8	2673.	325.2
832.	312.8	1202.	358.8	1572.	399.6	1941.	373.2	2311.	360.8	2680.	318.4
841.	315.6	1210.	361.6	1579.	399.2	1951.	373.6	2318.	360.8	2688.	310.0
848.	318.4	1217.	363.6	1587.	399.2	1958.	374.0	2327.	360.0	2694.	301.2
857.	323.2	1225.	364.8	1594.	398.4	1965.	373.6	2334.	360.8	2699.	290.4
864.	326.0	1233.	366.4	1602.	398.0	1970.	374.8	2341.	362.8	2707.	276.4
870.	327.2	1240.	369.6	1608.	398.8	1978.	374.4	2347.	361.6	2715.	276.4
878.	329.6	1247.	370.4	1616.	400.0	1986.	374.0	2356.	360.4	2723.	259.2
885.	331.6	1254.	372.0	1624.	400.4	1995.	374.0	2365.	359.2	2731.	246.8
892.	333.2	1262.	374.8	1632.	400.8	2002.	374.8	2369.	359.2	2738.	237.2
901.	335.2	1269.	375.2	1638.	400.4	2009.	374.8	2378.	359.2	2747.	224.4
907.	336.8	1277.	376.8	1645.	400.8	2015.	376.0	2384.	359.2	2753.	213.6
913.	338.4	1284.	377.6	1654.	401.6	2023.	375.6	2393.	358.0	2756.	204.8
									2758.	202.0	
									2759.	196.0	

<COMMENT> MAX POWER: 170.6 HP @ 2593. RPM.

<COMMENT> RATED SPEED: 2583. RPM.

WANT A CALCOMP PLOT OF THE MAPPING CURVE? (Y/N) • (DEFLT = N): Y

HD-873690  
200 OM366A84SEACORR1 1  
CS D1CS

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 07-31-87 TIME: 14:53:16 HD-873690

TEST NUMBER: HD-873690  
TEST DATE/TIME: 7-31-87 8: 7

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.00 "HG  
DRY BULB TEMPERATURE: 78.50 F  
ABSOLUTE HUMIDITY: 64.52 GRAINS H2O / LB. DRY AIR

<u>EMISSION RESULTS</u>	<u>CS</u>	<u>HS</u>	<u>WTD TEST</u>	<u>CYCLE STATISTICS</u>	<u>CS</u>	<u>HS</u>
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	3.96	0.00		NUMBER	1176	0
EXHAUST+BKG, GM	17.00	0.00		SLOPE	1.00397	0.00000
NET, GM/BHP-HR	1.248	0.000	1.248	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	-8.152	0.000
BACKGROUND, PPM	0.25	0.00		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	33.26	0.00		STD ERROR	11.987	0.000
NET, GM/BHP-HR	3.04	0.00	3.04	(LIMIT: 100 RPM)		
R-SQUARE					0.99979	0.00000
(LIMIT: 0.97)				TORQUE		
NOX (INTEGRATED)				NUMBER	983	0
BACKGROUND, PPM	0.26	0.00		SLOPE	1.00795	0.00000
EXHAUST+BKG, GM	90.17	0.00		(LIMIT: 0.77/0.83-1.03)		
NET, GM/BHP-HR	8.071	0.000	8.071	Y-INTERCEPT	-3.033	0.000
(LIMIT: +-15 FT-LBS)				STD ERROR	3.792%	0.000%
CO2 (BAG)				(LIMIT: 13% MAX ENG TQ)		
BACKGROUND, PPM	0.040	0.000		R-SQUARE	0.98397	0.00000
EXHAUST+BKG, GM	7132.58	0.00		(LIMIT: 0.85/0.88)		
NET, GM/BHP-HR	555.6	0.0	555.6	POWER		
PARTICULATE				NUMBER	982	0
SECONDARY TARE, GM	0.159824	0.000000		SLOPE	1.01365	0.00000
SECONDARY PART, GM	0.160052	0.000000		(LIMIT: 0.87/0.89-1.03)		
PRIMARY TARE, GM	0.155473	0.000000		Y-INTERCEPT	-1.196	0.000
PRIMARY PART, GM	0.159136	0.000000		(LIMIT: +-5 BHP)		
TOTAL, GM/BHP-HR	0.51	0.00	0.51	STD ERROR	3.261%	0.000%
FUEL CONSUMPTION				(LIMIT: 8%)		
LBS/CARBON BALANCE	4.211	0.000	4.211	R-SQUARE	0.98787	0.00000
LBS/BHP-HR	0.390	0.000	0.390	(LIMIT: 0.91)		
LBS/MEASURED	4.476	0.0		WORK		
BRAKE HORSEPOWER-HOUR	10.783	0.000		ACTUAL	10.783	0.000
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	10.845	0.000
				% DIFFERENCE	-0.57%	0.00%

HD-873691  
200 OM366A84SEACORR1 1  
HS D1HS

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 07-31-87 TIME: 14:33:36 HD-873691

TEST NUMBER: HD-873691  
TEST DATE/TIME: 7-31-87 9:33

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG  
DRY BULB TEMPERATURE: 79.00 F  
ABSOLUTE HUMIDITY: 56.72 GRAINS H2O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	0.00		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	14.12		SLOPE	0.00000	1.00422
NET, GM/BHP-HR	0.000	0.949	0.949	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-8.506
BACKGROUND, PPM	0.00	0.00		(LIMIT: +/-50 RPM)		
EXHAUST+BKG, GM	0.00	26.06		STD ERROR	0.000	11.750
NET, GM/BHP-HR	0.00	2.41	2.41	(LIMIT: 100 RPM)		
NOX (INTEGRATED)				R-SQUARE	0.00000	0.99980
BACKGROUND, PPM	0.00	0.00		(LIMIT: 0.97)		
EXHAUST+BKG, GM	0.00	86.66		TORQUE		
NET, GM/BHP-HR	0.000	7.587	7.587	NUMBER	0	989
CO2 (BAG)				SLOPE	0.00000	1.00725
BACKGROUND, PPM	0.000	0.000		(LIMIT: 0.77/0.83-1.03)		
EXHAUST+BKG, GM	0.00	7051.15		Y-INTERCEPT	0.000	-2.533
NET, GM/BHP-HR	0.0	553.2	553.2	(LIMIT: +/-15 FT-LBS)		
PARTICULATE				STD ERROR	0.000%	3.767%
SECONDARY TARE, GM	0.000000	0.147306		(LIMIT: 13% MAX ENG TQ)		
SECONDARY PART, GM	0.000000	0.147417		R-SQUARE	0.00000	0.98442
PRIMARY TARE, GM	0.000000	0.143940		(LIMIT: 0.85/0.88)		
PRIMARY PART, GM	0.000000	0.147225		POWER		
TOTAL, GM/BHP-HR	0.00	0.43	0.43	NUMBER	0	988
FUEL CONSUMPTION				SLOPE	0.00000	1.01440
LBS/CARBON BALANCE	0.000	4.188	4.188	(LIMIT: 0.87/0.89-1.03)		
LBS/BHP-HR	0.000	0.387	0.387	Y-INTERCEPT	0.000	-1.157
LBS/MEASURED	0.0	4.404		(LIMIT: +/-5 BHP)		
BRAKE HORSEPOWER-HOUR	0.000	10.809		STD ERROR	0.000%	3.281%
				R-SQUARE	0.00000	0.98802
				(LIMIT: 0.91)		
				WORK		
				ACTUAL	0.000	10.809
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.33%

HD-873692  
200 OM366A84SEACORR1 1  
DIHS

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 07-31-87 TIME: 16:28:26 HD-873692

TEST NUMBER: HD-873692  
TEST DATE/TIME: 7-31-87 10:13

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG  
DRY BULB TEMPERATURE: 77.50 F  
ABSOLUTE HUMIDITY: 63.96 GRAINS H2O / LB. DRY AIR

<u>EMISSION RESULTS</u>	<u>CS</u>	<u>HS</u>	<u>WTD TEST</u>	<u>CYCLE STATISTICS</u>	<u>CS</u>	<u>HS</u>
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	3.73		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	14.18		SLOPE	0.00000	1.00439
NET, GM/BHP-HR	0.000	1.005	1.005	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-8.554
BACKGROUND, PPM	0.00	0.00		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	0.00	24.70		STD ERROR	0.000	11.921
NET, GM/BHP-HR	0.00	2.29	2.29	(LIMIT: 100 RPM)		
R-SQUARE				R-SQUARE	0.00000	0.99979
(LIMIT: 0.97)				(LIMIT: 0.97)		
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.00	0.51		NUMBER	0	989
EXHAUST+BKG, GM	0.00	86.77		SLOPE	0.00000	1.00844
NET, GM/BHP-HR	0.000	7.679	7.679	(LIMIT: 0.77/0.83-1.03)		
CO2 (BAG)				Y-INTERCEPT	0.000	-3.118
BACKGROUND, PPM	0.000	0.037		(LIMIT: +-15 FT-LBS)		
EXHAUST+BKG, GM	0.00	6978.35		STD ERROR	0.000%	3.750%
NET, GM/BHP-HR	0.0	547.8	547.8	(LIMIT: 13% MAX ENG TQ)		
PARTICULATE				R-SQUARE	0.00000	0.98460
SECONDARY TARE, GM	0.000000	0.154690		(LIMIT: 0.85/0.88)		
SECONDARY PART, GM	0.000000	0.154920		POWER		
PRIMARY TARE, GM	0.000000	0.149568		NUMBER	0	988
PRIMARY PART, GM	0.000000	0.152887		SLOPE	0.00000	1.01355
TOTAL, GM/BHP-HR	0.00	0.47	0.47	(LIMIT: 0.87/0.89-1.03)		
FUEL CONSUMPTION				Y-INTERCEPT	0.000	-1.224
LBS/CARBON BALANCE	0.000	4.141	4.141	(LIMIT: +-5 BHP)		
LBS/BHP-HR	0.000	0.384	0.384	STD ERROR	0.000%	3.281%
LBS/MEASURED	0.0	4.404		(R-SQUARE)	0.00000	0.98799
BRAKE HORSEPOWER-HOUR	0.000	10.793		(LIMIT: 8%)		
				(R-SQUARE)	0.00000	0.98799
				(LIMIT: 0.91)		
WORK						
				ACTUAL	0.000	10.793
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.48%

HD-873693  
200 OM366A84SEACORR1 1  
HS DIHS

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 07-31-87 TIME: 16:28:32 HD-873693

TEST NUMBER: HD-873693  
TEST DATE/TIME: 7-31-87 10:54

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG  
DRY BULB TEMPERATURE: 77.00 F  
ABSOLUTE HUMIDITY: 55.42 GRAINS H2O / LB. DRY AIR

<u>EMISSION RESULTS</u>	<u>CS</u>	<u>HS</u>	<u>WTD TEST</u>	<u>CYCLE STATISTICS</u>	<u>CS</u>	<u>HS</u>
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	3.96		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	14.25		SLOPE	0.00000	1.00379
NET, GM/BHP-HR	0.000	0.993	0.993	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-8.008
BACKGROUND, PPM	0.00	0.49		(LIMIT: +/-50 RPM)		
EXHAUST+BKG, GM	0.00	24.37		STD ERROR	0.000	11.969
NET, GM/BHP-HR	0.00	2.17	2.17	(LIMIT: 100 RPM)		
R-SQUARE				R-SQUARE	0.00000	0.99979
(LIMIT: 0.97)				(LIMIT: 0.97)		
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.00	1.02		NUMBER	0	989
EXHAUST+BKG, GM	0.00	87.31		SLOPE	0.00000	1.00693
NET, GM/BHP-HR	0.000	7.430	7.430	(LIMIT: 0.77/0.83-1.03)		
CO2 (BAG)				Y-INTERCEPT	0.000	-2.882
BACKGROUND, PPM	0.000	0.037		(LIMIT: +/-15 FT-LBS)		
EXHAUST+BKG, GM	0.00	6878.87		STD ERROR	0.000%	3.758%
NET, GM/BHP-HR	0.0	538.4	538.4	(LIMIT: 13% MAX ENG TQ)		
R-SQUARE				R-SQUARE	0.00000	0.98449
(LIMIT: 0.85/0.88)				(LIMIT: 0.85/0.88)		
PARTICULATE				POWER		
SECONDARY TARE, GM	0.000000	0.158636		NUMBER	0	988
SECONDARY PART, GM	0.000000	0.158848		SLOPE	0.00000	1.01251
PRIMARY TARE, GM	0.000000	0.148620		(LIMIT: 0.87/0.89-1.03)		
PRIMARY PART, GM	0.000000	0.151926		Y-INTERCEPT	0.000	-1.181
TOTAL, GM/BHP-HR	0.00	0.47	0.47	(LIMIT: +/-5 BHP)		
FUEL CONSUMPTION				STD ERROR	0.000%	3.284%
LBS/CARBON BALANCE	0.000	4.069	4.069	(LIMIT: 8%)		
LBS/BHP-HR	0.000	0.377	0.377	R-SQUARE	0.00000	0.98795
LBS/MEASURED	0.0	4.404		(LIMIT: 0.91)		
BRAKE HORSEPOWER-HOUR	0.000	10.792		WORK		
				ACTUAL	0.000	10.792
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.49%

A 6

HD-873694  
200 OM366A84SEACORR1 1  
CS CSD2

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:19:08 HD-873694

TEST NUMBER: HD-873694  
TEST DATE/TIME: 8- 5-87 8:12

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.00 "HG  
DRY BULB TEMPERATURE: 78.00 F  
ABSOLUTE HUMIDITY: 65.85 GRAINS H<sub>2</sub>O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	2.61	0.00		NUMBER	1176	0
EXHAUST+BKG, GM	16.05	0.00		SLOPE	1.00506	0.00000
NET, GM/BHP-HR	1.272	0.000	1.272	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	-7.776	0.000
BACKGROUND, PPM	0.00	0.00		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	33.44	0.00		STD ERROR	11.958	0.000
NET, GM/BHP-HR	3.10	0.00	3.10	(LIMIT: 100 RPM)		
				R-SQUARE	0.99979	0.00000
NOX (INTEGRATED)				(LIMIT: 0.97)		
BACKGROUND, PPM	0.26	0.00		TORQUE		
EXHAUST+BKG, GM	95.78	0.00		NUMBER	980	0
NET, GM/BHP-HR	8.602	0.000	8.602	SLOPE	1.01534	0.00000
CO <sub>2</sub> (BAG)				(LIMIT: 0.77/0.83-1.03)		
BACKGROUND, PPM	0.034	0.000		Y-INTERCEPT	-4.402	0.000
EXHAUST+BKG, GM	7521.38	0.00		(LIMIT: +-15 FT-LBS)		
NET, GM/BHP-HR	607.6	0.0	607.6	STD ERROR	3.749%	0.000%
				(LIMIT: 13% MAX ENG TQ)		
PARTICULATE				R-SQUARE	0.98442	0.00000
SECONDARY TARE, GM	0.154596	0.000000		(LIMIT: 0.85/0.88)		
SECONDARY PART, GM	0.154652	0.000000		POWER		
PRIMARY TARE, GM	0.151457	0.000000		NUMBER	979	0
PRIMARY PART, GM	0.155264	0.000000		SLOPE	1.01723	0.00000
TOTAL, GM/BHP-HR	0.50	0.00	0.50	(LIMIT: 0.87/0.89-1.03)		
FUEL CONSUMPTION				Y-INTERCEPT	-1.321	0.000
LBS/CARBON BALANCE	4.602	0.000	4.602	(LIMIT: +-5 BHP)		
LBS/BHP-HR	0.427	0.000	0.427	STD ERROR	3.284%	0.000%
LBS/MEASURED	4.618	0.0		(LIMIT: 8%)		
BRAKE HORSEPOWER-HOUR	10.789	0.000		R-SQUARE	0.98769	0.00000
				(LIMIT: 0.91)		
WORK				WORK		
				ACTUAL	10.789	0.000
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	10.845	0.000
				% DIFFERENCE	-0.52%	0.00%

HD-873695  
200 OM366A84SEACORR1 1  
HS HSD2

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:19:24 HD-873695

TEST NUMBER: HD-873695  
TEST DATE/TIME: 8- 5-87 9: 3  
MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.00 "HG  
DRY BULB TEMPERATURE: 77.50 F  
ABSOLUTE HUMIDITY: 59.52 GRAINS H2O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	3.36		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	13.44		SLOPE	0.00000	1.00445
NET, GM/BHP-HR	0.000	0.966	0.966	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-7.842
BACKGROUND, PPM	0.00	0.25		(LIMIT: +50 RPM)		
EXHAUST+BKG, GM	0.00	25.37		STD ERROR	0.000	11.702
NET, GM/BHP-HR	0.00	2.30	2.30	(LIMIT: 100 RPM)		
R-SQUARE					0.00000	0.99980
(LIMIT: 0.97)				TORQUE		
NOX (INTEGRATED)				NUMBER	0	988
BACKGROUND, PPM	0.00	0.51		SLOPE	0.00000	1.00895
EXHAUST+BKG, GM	0.00	91.67		(LIMIT: 0.77/0.83-1.03)		
NET, GM/BHP-HR	0.000	8.019	8.019	Y-INTERCEPT	0.000	-3.003
CO2 (BAG)				(LIMIT: +15 FT-LBS)		
BACKGROUND, PPM	0.000	0.035		STD ERROR	0.000%	3.756%
EXHAUST+BKG, GM	0.00	7342.91		(LIMIT: 13% MAX ENG TQ)		
NET, GM/BHP-HR	0.0	584.5	584.5	R-SQUARE	0.00000	0.98454
PARTICULATE				(LIMIT: 0.85/0.88)		
SECONDARY TARE, GM	0.000000	0.159875		POWER		
SECONDARY PART, GM	0.000000	0.160150		NUMBER	0	987
PRIMARY TARE, GM	0.000000	0.163171		SLOPE	0.00000	1.01455
PRIMARY PART, GM	0.000000	0.1666357		(LIMIT: 0.87/0.89-1.03)		
TOTAL, GM/BHP-HR	0.00	0.46	0.46	Y-INTERCEPT	0.000	-1.185
FUEL CONSUMPTION				(LIMIT: +5 BHP)		
LBS/CARBON BALANCE	0.000	4.420	4.420	STD ERROR	0.000%	3.268%
LBS/BHP-HR	0.000	0.409	0.409	(LIMIT: 8%)		
LBS/MEASURED	0.0	4.476		R-SQUARE	0.00000	0.98812
BRAKE HORSEPOWER-HOUR	0.000	10.808		(LIMIT: 0.91)		
WORK				ACTUAL	0.000	10.808
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.34%

A  
8

HD-873696  
200 OM366A84SEACORR1 1  
HS HSD2

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-10-87 TIME: 08:28:58 HD-873696

TEST NUMBER: HD-873696  
TEST DATE/TIME: 8- 5-87 9:42

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.00 "HG  
DRY BULB TEMPERATURE: 77.00 F  
ABSOLUTE HUMIDITY: 62.72 GRAINS H<sub>2</sub>O / LB. DRY AIR

<u>EMISSION RESULTS</u>	<u>CS</u>	<u>HS</u>	<u>WTD TEST</u>	<u>CYCLE STATISTICS</u>	<u>CS</u>	<u>HS</u>
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	3.36		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	13.45		SLOPE	0.00000	1.00373
NET, GM/BHP-HR	0.000	0.967	0.967	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-7.468
BACKGROUND, PPM	0.00	0.00		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	0.00	25.40		STD ERROR	0.000	11.832
NET, GM/BHP-HR	0.00	2.35	2.35	(LIMIT: 100 RPM)		
				R-SQUARE	0.00000	0.99979
				(LIMIT: 0.97)		
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.00	0.26		NUMBER	0	985
EXHAUST+BKG, GM	0.00	91.47		SLOPE	0.00000	1.00929
NET, GM/BHP-HR	0.000	8.141	8.141	(LIMIT: 0.77/0.83-1.03)		
				Y-INTERCEPT	0.000	-2.987
				(LIMIT: +-15 FT-LBS)		
CO <sub>2</sub> (BAG)				STD ERROR	0.000%	3.725%
BACKGROUND, PPM	0.000	0.037		(LIMIT: 13% MAX ENG TQ)		
EXHAUST+BKG, GM	0.00	7362.77		R-SQUARE	0.00000	0.98466
NET, GM/BHP-HR	0.0	582.8	582.8	(LIMIT: 0.85/0.88)		
PARTICULATE				POWER		
SECONDARY TARE, GM	0.000000	0.166481		NUMBER	0	984
SECONDARY PART, GM	0.000000	0.166595		SLOPE	0.00000	1.01414
PRIMARY TARE, GM	0.000000	0.166450		(LIMIT: 0.87/0.89-1.03)		
PRIMARY PART, GM	0.000000	0.169742		Y-INTERCEPT	0.000	-1.174
TOTAL, GM/BHP-HR	0.00	0.43	0.43	(LIMIT: +-5 BHP)		
				STD ERROR	0.000%	3.281%
FUEL CONSUMPTION				(LIMIT: 8%)		
LBS/CARBON BALANCE	0.000	4.404	4.404	R-SQUARE	0.00000	0.98790
LBS/BHP-HR	0.000	0.408	0.408	(LIMIT: 0.91)		
LBS/MEASURED	0.0	4.476		WORK		
BRAKE HORSEPOWER-HOUR	0.000	10.798		ACTUAL	0.000	10.798
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.43%

A 6

HD-873697  
200 OM366A84SEACORR1 1  
HS HSD2

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:19:45 HD-873697

TEST NUMBER: HD-873697  
TEST DATE/TIME: 8- 5-87 10:22

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.00 "HG  
DRY BULB TEMPERATURE: 77.50 F  
ABSOLUTE HUMIDITY: 61.88 GRAINS H2O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	0.00		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	13.48		SLOPE	0.00000	1.00446
NET, GM/BHP-HR	0.000	0.982	0.982	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-8.174
BACKGROUND, PPM	0.00	0.00		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	0.00	24.53		STD ERROR	0.000	11.921
NET, GM/BHP-HR	0.00	2.27	2.27	(LIMIT: 100 RPM)		
R-SQUARE				R-SQUARE	0.00000	0.99979
(LIMIT: 0.97)				(LIMIT: 0.97)		
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.00	0.00		NUMBER	0	988
EXHAUST+BKG, GM	0.00	90.27		SLOPE	0.00000	1.01076
NET, GM/BHP-HR	0.000	8.012	8.012	(LIMIT: 0.77/0.83-1.03)		
CO2 (BAG)				Y-INTERCEPT	0.000	-3.450
BACKGROUND, PPM	0.000	0.000		(LIMIT: +-15 FT-LBS)		
EXHAUST+BKG, GM	0.00	7364.38		STD ERROR	0.000%	3.725%
NET, GM/BHP-HR	0.0	582.3	582.3	(LIMIT: 13% MAX ENG TQ)		
R-SQUARE				R-SQUARE	0.00000	0.98484
(LIMIT: 0.85/0.88)				(LIMIT: 0.85/0.88)		
PARTICULATE				POWER		
SECONDARY TARE, GM	0.000000	0.158591		NUMBER	0	987
SECONDARY PART, GM	0.000000	0.158680		SLOPE	0.00000	1.01570
PRIMARY TARE, GM	0.000000	0.162416		(LIMIT: 0.87/0.89-1.03)		
PRIMARY PART, GM	0.000000	0.165466		Y-INTERCEPT	0.000	-1.245
TOTAL, GM/BHP-HR	0.00	0.40	0.40	(LIMIT: +-5 BHP)		
FUEL CONSUMPTION				STD ERROR	0.000%	3.267%
LBS/CARBON BALANCE	0.000	4.403	4.403	(LIMIT: 8%)		
LBS/BHP-HR	0.000	0.408	0.408	R-SQUARE	0.00000	0.98816
LBS/MEASURED	0.0	4.404		(LIMIT: 0.91)		
BRAKE HORSEPOWER-HOUR	0.000	10.803		WORK		
				ACTUAL	0.000	10.803
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.39%

A 10

HD-873699  
200 OM366A84SEACORR1 1  
CS D3CS

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:19:54 HD-873699

TEST NUMBER: HD-873699  
TEST DATE/TIME: 8- 6-87 8:45

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG  
DRY BULB TEMPERATURE: 74.00 F  
ABSOLUTE HUMIDITY: 48.22 GRAINS H2O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	3.88	0.00		NUMBER	1176	0
EXHAUST+BKG, GM	17.25	0.00		SLOPE	1.00432	0.00000
NET, GM/BHP-HR	1.271	0.000	1.271	(LIMIT: 0.97-1.03)		
(CO) (BAG)				Y-INTERCEPT	-6.188	0.000
BACKGROUND, PPM	0.25	0.00		(LIMIT: +/-50 RPM)		
EXHAUST+BKG, GM	35.84	0.00		STD ERROR	11.903	0.000
NET, GM/BHP-HR	3.27	0.00	3.27	(LIMIT: 100 RPM)		
R-SQUARE				R-SQUARE	0.99979	0.00000
(LIMIT: 0.97)				(LIMIT: 0.97)		
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.51	0.00		NUMBER	984	0
EXHAUST+BKG, GM	93.44	0.00		SLOPE	1.00416	0.00000
NET, GM/BHP-HR	7.947	0.000	7.947	(LIMIT: 0.77/0.83-1.03)		
Y-INTERCEPT				Y-INTERCEPT	-2.229	0.000
(LIMIT: +/-15 FT-LBS)				STD ERROR	3.886%	0.000%
CO2 (BAG)				(LIMIT: 13% MAX ENG TQ)		
BACKGROUND, PPM	0.036	0.000		R-SQUARE	0.98308	0.00000
EXHAUST+BKG, GM	7485.08	0.00		(LIMIT: 0.85/0.88)		
NET, GM/BHP-HR	595.5	0.0	595.5	POWER		
PARTICULATE				NUMBER	983	0
SECONDARY TARE, GM	0.168294	0.000000		SLOPE	1.01382	0.00000
SECONDARY PART, GM	0.168450	0.000000		(LIMIT: 0.87/0.89-1.03)		
PRIMARY TARE, GM	0.163520	0.000000		Y-INTERCEPT	-1.106	0.000
PRIMARY PART, GM	0.167144	0.000000		(LIMIT: +/-5 BHP)		
TOTAL, GM/BHP-HR	0.48	0.00	0.48	STD ERROR	3.311%	0.000%
FUEL CONSUMPTION				(LIMIT: 8%)		
LBS/CARBON BALANCE	4.524	0.000	4.524	R-SQUARE	0.98755	0.00000
LBS/BHP-HR	0.418	0.000	0.418	(LIMIT: 0.91)		
LBS/MEASURED	4.547	0.0		WORK		
BRAKE HORSEPOWER-HOUR	10.812	0.000		ACTUAL	10.812	0.000
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	10.845	0.000
				% DIFFERENCE	-0.30%	0.00%

HD-873700  
200 OM366A84SEACORR1 1  
HS D3H1

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:20:04 HD-873700

TEST NUMBER: HD-873700  
TEST DATE/TIME: 8- 6-87 9:31

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG  
DRY BULB TEMPERATURE: 73.50 F  
ABSOLUTE HUMIDITY: 46.95 GRAINS H2O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	0.00		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	13.83		SLOPE	0.00000	1.00331
NET, GM/BHP-HR	0.000	0.884	0.884	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-5.289
BACKGROUND, PPM	0.00	0.00		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	0.00	23.70		STD ERROR	0.000	11.797
NET, GM/BHP-HR	0.00	2.19	2.19	(LIMIT: 100 RPM)		
R-SQUARE				(R-SQUARE)	0.00000	0.99979
(LIMIT: 0.97)				TORQUE		
NOX (INTEGRATED)				NUMBER	0	989
BACKGROUND, PPM	0.00	0.00		SLOPE	0.00000	1.00190
EXHAUST+BKG, GM	0.00	90.48		(LIMIT: 0.77/0.83-1.03)		
NET, GM/BHP-HR	0.000	7.650	7.650	Y-INTERCEPT	0.000	-1.281
CO2 (BAG)				(LIMIT: +-15 FT-LBS)		
BACKGROUND, PPM	0.000	0.000		STD ERROR	0.000%	3.795%
EXHAUST+BKG, GM	0.00	7255.95		(LIMIT: 13% MAX ENG TQ)		
NET, GM/BHP-HR	0.0	570.0	570.0	R-SQUARE	0.00000	0.98404
PARTICULATE				(LIMIT: 0.85/0.88)		
SECONDARY TARE, GM	0.000000	0.165280		POWER		
SECONDARY PART, GM	0.000000	0.165401		NUMBER	0	988
PRIMARY TARE, GM	0.000000	0.166074		SLOPE	0.00000	1.01330
PRIMARY PART, GM	0.000000	0.169113		(LIMIT: 0.87/0.89-1.03)		
TOTAL, GM/BHP-HR	0.00	0.40	0.40	Y-INTERCEPT	0.000	-1.020
FUEL CONSUMPTION				(LIMIT: +-5 BHP)		
LBS/CARBON BALANCE	0.000	4.321	4.321	STD ERROR	0.000%	3.301%
LBS/BHP-HR	0.000	0.399	0.399	(LIMIT: 8%)		
LBS/MEASURED	0.0	4.333		R-SQUARE	0.00000	0.98785
(LIMIT: 0.91)				WORK		
BRAKE HORSEPOWER-HOUR	0.000	10.837		ACTUAL	0.000	10.837
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.07%

A 12

HD-873701  
200 OM366A84SEACORR1 1  
HS D3H2

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:20:14 HD-873701

TEST NUMBER: HD-873701  
TEST DATE/TIME: 8- 6-87 10: 0

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG  
DRY BULB TEMPERATURE: 73.50 F  
ABSOLUTE HUMIDITY: 46.77 GRAINS H2O / LB. DRY AIR

<u>EMISSION RESULTS</u>	<u>CS</u>	<u>HS</u>	<u>WTD TEST</u>	<u>CYCLE STATISTICS</u>	<u>CS</u>	<u>HS</u>
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	4.63		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	14.65		SLOPE	0.00000	1.00407
NET, GM/BHP-HR	0.000	0.970	0.970	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-7.405
BACKGROUND, PPM	0.00	0.49		(LIMIT: +-50 RPM)		
EXHAUST+BKG, GM	0.00	25.59		STD ERROR	0.000	11.937
NET, GM/BHP-HR	0.00	2.29	2.29	(LIMIT: 100 RPM)		
R-SQUARE				(LIMIT: 0.97)	0.00000	0.99979
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.00	0.51		NUMBER	0	989
EXHAUST+BKG, GM	0.00	91.34		SLOPE	0.00000	1.00571
NET, GM/BHP-HR	0.000	7.751	7.751	(LIMIT: 0.77/0.83-1.03)		
CO2 (BAG)				Y-INTERCEPT	0.000	-2.636
BACKGROUND, PPM	0.000	0.036		(LIMIT: +-15 FT-LBS)		
EXHAUST+BKG, GM	0.00	7188.09		STD ERROR	0.000%	3.794%
NET, GM/BHP-HR	0.0	568.2	568.2	(LIMIT: 13% MAX ENG TQ)		
R-SQUARE				(LIMIT: 0.85/0.88)	0.00000	0.98416
PARTICULATE				POWER		
SECONDARY TARE, GM	0.000000	0.163824		NUMBER	0	988
SECONDARY PART, GM	0.000000	0.163951		SLOPE	0.00000	1.01309
PRIMARY TARE, GM	0.000000	0.164306		(LIMIT: 0.87/0.89-1.03)		
PRIMARY PART, GM	0.000000	0.167281		Y-INTERCEPT	0.000	-1.177
TOTAL, GM/BHP-HR	0.00	0.40	0.40	(LIMIT: +-5 BHP)		
FUEL CONSUMPTION				STD ERROR	0.000%	3.316%
LBS/CARBON BALANCE	0.000	4.293	4.293	(LIMIT: 8%)		
LBS/BHP-HR	0.000	0.398	0.398	R-SQUARE	0.00000	0.98773
LBS/MEASURED	0.0	4.333		(LIMIT: 0.91)		
BRAKE HORSEPOWER-HOUR	0.000	10.794		WORK		
				ACTUAL	0.000	10.794
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	-0.47%

A 13

HD-873702  
200 OM366A84SEACORR1 1  
HS D3H3

HEAVY DUTY DIESEL TRANSIENT ENGINE TEST  
DIESEL SUMMARY REPORT

DATE: 08-07-87 TIME: 14:20:23 HD-873702

TEST NUMBER: HD-873702  
TEST DATE/TIME: 8- 6-87 10:39

MANUFACTURER: MERCEDES BENZ  
ENGINE ID: 200 OM366A84SEACORR1 1

AMBIENT DATA

BAROMETER (DRY): 29.10 "HG

DRY BULB TEMPERATURE: 74.00 F

ABSOLUTE HUMIDITY: 47.31 GRAINS H2O / LB. DRY AIR

EMISSION RESULTS	CS	HS	WTD TEST	CYCLE STATISTICS	CS	HS
HC (INTEGRATED)				SPEED		
BACKGROUND, PPM	0.00	0.00		NUMBER	0	1176
EXHAUST+BKG, GM	0.00	13.73		SLOPE	0.00000	1.00362
NET, GM/BHP-HR	0.000	0.874	0.874	(LIMIT: 0.97-1.03)		
CO (BAG)				Y-INTERCEPT	0.000	-6.515
BACKGROUND, PPM	0.00	0.00		(LIMIT: +50 RPM)		
EXHAUST+BKG, GM	0.00	25.03		STD ERROR	0.000	11.966
NET, GM/BHP-HR	0.00	2.22	2.22	(LIMIT: 100 RPM)		
R-SQUARE				(LIMIT: 0.97)	0.00000	0.99979
NOX (INTEGRATED)				TORQUE		
BACKGROUND, PPM	0.00	0.00		NUMBER	0	989
EXHAUST+BKG, GM	0.00	92.01		SLOPE	0.00000	0.99282
NET, GM/BHP-HR	0.000	7.847	7.847	(LIMIT: 0.77/0.83-1.03)		
CO2 (BAG)				Y-INTERCEPT	0.000	0.504
BACKGROUND, PPM	0.000	0.000		(LIMIT: +15 FT-LBS)		
EXHAUST+BKG, GM	0.00	7108.05		STD ERROR	0.000%	3.930%
NET, GM/BHP-HR	0.0	565.3	565.3	(LIMIT: 13% MAX ENG TQ)	0.00000	0.98258
PARTICULATE				R-SQUARE		
SECONDARY TARE, GM	0.000000	0.166293		(LIMIT: 0.85/0.88)		
SECONDARY PART, GM	0.000000	0.166418		POWER		
PRIMARY TARE, GM	0.000000	0.166231		NUMBER	0	988
PRIMARY PART, GM	0.000000	0.169284		SLOPE	0.00000	1.00990
TOTAL, GM/BHP-HR	0.00	0.40	0.40	(LIMIT: 0.87/0.89-1.03)		
FUEL CONSUMPTION				Y-INTERCEPT	0.000	-0.858
LBS/CARBON BALANCE	0.000	4.290	4.290	STD ERROR	0.000%	3.350%
LBS/BHP-HR	0.000	0.395	0.395	(LIMIT: 8%)		
LBS/MEASURED	0.0	4.333		R-SQUARE	0.00000	0.98741
BRAKE HORSEPOWER-HOUR	0.000	10.846		(LIMIT: 0.91)		
WORK				ACTUAL	0.000	10.846
				(LIMIT: -15%-5% REF BHP-HR)		
				REFERENCE	0.000	10.845
				% DIFFERENCE	0.00%	0.01%

A 14

Table A-1

Table of Steady State Values from  
the European EMA Round Robin  
Correlation Engine (D-B OM 366A)

Engine Speed RPM	Engine Torque, Ft.-lb	Fuel Rate, lb/hr		Emissions, g/BHP-Hr**					Part
		Measured	C.Bal*	HC	CO	NOx	CO <sub>2</sub>		
2600	307.0	56.46	56.07	.35	.63	9.54	531.15	.25	
1600	395.8	41.90	41.10	.22	1.60	10.84	489.29	.39	
1600	105.5	12.76	12.80	1.43	2.97	6.82	566.37	.26	
572	0	1.06	1.06	(21.97)	(39.65)	(24.77)	(1394.75)	(9.06)	

\*Carbon Balance

\*\*The 572 RPM, 0 Ft-lb (idle) mode data are in g/hr.

**ENGINEERING OPERATIONS DIVISION**  
**Fuel Analysis Report**  
**Diesel Test Fuel**

Supplier: Phillips Chemical Lot G-668

Proposed Use(s): Certification and Heavy Duty Engine Testing

Quantity: 2000 gallon

Location: Tank 5

Date placed in service:

4/3/87

Expected date of exhaustion: 5/16/88

Item	Method	Procurement Specifications	CFR 86.113-82 (if different)	Official EOD Values
Distillation	ASTM D 86			
Initial Boiling Point (°F)		345-375	340-400	351
10% recovered Point (°F)		400-440	400-460	422
50% recovered Point (°F)		495-525	470-540	505
90% recovered Point (°F)		580-610	550-610	593
End Point (°F)		630-660	580-660	641
Sulfur (wt%)	ASTM D 2622	0.2-0.4	0.2-0.5	0.34
Flashpoint (°F)	ASTM D 93	130 Min.	154	154
Viscosity @ 40 °C (centistokes)	ASTM D 445	2.2-3.2	2.0-3.2	2.52
HC Composition	ASTM D 1319			
Olefins (vol%)		(a)		1.9
Aromatics (vol%)		29 Min.	27 Min.	30.3
Saturates (vol%)		(a)		67.8
Cetane Number	ASTM D 613	43-47	42-50	43.0
Cetane Index	ASTM D 976	43-47	(a)	46.2
Oxidation Stability (mg/100ml)	ASTM D 2274	1.5 Max.	(a)	<0.3
Particulate matter (mg/l)	ASTM D 2276	15 Max.	(a)	<2.5
Weight Fraction Carbon	ASTM D 3343	(a)		0.8689
Net Heat of Combustion (BTU/lb)	ASTM D 3338	(a)		18384
Gravity (°API)	ASTM D 287	33-36	33-37	34.9
Fuel Economy Numerator (grams carbon/gallon)		2750-2806	(a)	2791

(a) No requirements or not addressed

Prepared by: \_\_\_\_\_

Date: \_\_\_\_\_

Validated by: \_\_\_\_\_

Date: \_\_\_\_\_

Quality Control: \_\_\_\_\_

Date: \_\_\_\_\_

## CORRELATION ENGINE FOR EMA EUROPEAN ROUND-ROBIN

## ENGINE SET-UP AND DESCRIPTIVE DATA

( 1) Engine Manufacturer:	Daimler-Benz AG
( 2) Engine Type:	OM 366 A
( 3) Displacement:	5.96 l
( 4) Model Year:	1984
( 5) Identification Number:	366.959-10-10205
( 6) Fuel Type:	2D
( 7) Rec.Oil Type:	SAE 15W40 (3.7 - 4.2 gal)
( 8) Curb Idle Speed:	600+-50
( 9) Max.Idle Torque:	320 Nm
(10) High Idle Speed:	2900 RPM
(11) Max.Safe Operating Speed:	2950 RPM
(12) Max.Power:	128 (171 HP)/2600 RPM
(13) Max.Torque:	555 Nm (408 ft-lbs)/1560 RPM
(14) Fuel Consumption at Max.Power:	28.6 kg/h (63.1 lbs/hr)
(15) Fuel Consumption at Max.Torque:	18.8 kg/h (41.4 lbs/hr)
(16) Injection Timing:	17 deg BTDC
(17) Exhaust Pipe Configuration:	86 mm Inside Diameter
(18) Length of Exhaust System:	3.5 m
(19) Inlet Depression:	2.0 kPa (7.9 in Water) (1)
(20) Exhaust Backpressure:	6.0 kPa (1.8 in Mercury) (2)
(21) Hours of Operation:	559 hrs
(22) Rec.Start-up Procedure:	Production Type Starter
(23) Cranking Speed:	180 RPM at 20 deg C

(1) Set with Restrictor Valve 2.85 m from Intake Manifold

(2) Set with Restrictor Valve 3.00 m from Turbocharger

## DBAG TEST RESULTS OF OM 366 A CORRELATION ENGINE

## A. TRANSIENT CYCLE

Cycle Type	HC	NOX	CO	PM	BSFC	Eg/BHP-hr]
Cold 1	1.33	7.56	3.36	0.61	190.7	
Hot 1	1.09	7.54	2.56	0.50	183.6	
Hot 2	1.08	7.62	2.56	0.49	183.6	
Hot 3	1.05	7.65	2.38	0.47	182.3	
Cold 2	1.28	7.91	3.23	0.57	195.5	
Hot 4	1.06	7.72	2.48	0.43	186.2	
Hot 5	1.00	7.75	2.54	0.47	185.1	
Hot 6	1.04	7.66	2.38	0.46	182.5	
Cold 3	1.29	7.97	3.16	0.54	196.5	
Hot 7	1.03	7.96	2.45	0.47	189.3	
Hot 8	1.05	7.61	2.36	0.45	182.0	
Hot 9	1.04	7.70	2.36	0.45	182.1	
Average Cold	1.30	7.81	3.25	0.57	194.2	
Average Hot	1.05	7.69	2.45	0.47	184.1	
Weighted Average	1.09	7.71	2.57	0.48	185.5	
2s (P=95%)	0.06	0.24	0.18	0.04	4.8	
COV (2s)	5.0%	3.2%	7.0%	9.2%	2.6%	

CVS Flow Rate: 1469 SCFM  
 Average DF: 27.31  
 Average Intake Air Temperature: 74.3 deg F  
 Average Humidity: 51.1 gr/lb  
 Idle Speed: 600 RPM  
 Reference Cycle Work: 11.30 BHP-hr  
 Measuring Ranges:  
 HC 100 ppm (Cold); 50 ppm (Hot)  
 NOX 500 ppm  
 CO 500 ppm  
 CO2 2.5 %

## B. 4-MODE STEADY STATE TEST

Mode	HC	NOX	CO	PM	BSFC	Eg/BHP-hr]
1 (2600/90%)	0.43	9.99	0.57	0.19	164.7	Eg/BHP-hr]
2 (1600/WOT)	0.24	10.92	1.49	0.36	153.7	Eg/BHP-hr]
3 (1600/27%)	2.29	7.02	3.21	0.34	176.8	Eg/BHP-hr]
4 ( 600/0% )	27.83	32.13	40.10	7.57		Eg/hr]

## C. SMOKE CYCLE

Test Number	A	B	C	%
1	9.6	3.5	19.5	
2	9.6	3.5	20.0	
3	8.7	3.2	17.6	
4	8.6	2.9	17.3	
5	7.6	2.7	15.9	
Average	8.8	3.1	18.0	
2s (P=95%)	1.6	0.8	3.4	
COV (2s)	18.6%	24.2%	19.6%	

## D. STEADY STATE TEST

Speed [RPM]	Power [HP]	Torque [ft-lbs]	BSFC [lbs/BHP-hr]	Air Flow [CFM]	Smoke [ESZ]	Inl. Dep. [in H2O]	Exh. Backp. [in Hg]
2600	173.4	350	0.363	371.5	1.1	8.0	1.80
2340	163.2	366	0.353	337.8	1.2	6.4	1.45
2080	148.2	374	0.346	294.4	1.4	4.8	1.09
1820	133.8	386	0.340	248.1	1.7	3.6	0.77
1560	120.6	405	0.344	199.1	2.4	2.4	0.74
1370	103.9	399	0.345	171.4	2.4	1.6	0.53
1170	83.3	374	0.346	138.9	2.9	0.8	0.35
910	60.1	347	0.362	97.0	3.8	0.4	0.21