

Air

---



# **APTI Course 450 Source Sampling for Particulate Pollutants**

## **Student Workbook**




# **APTI Course 450 Source Sampling for Particulate Pollutants**

## **Student Workbook**

**Northrop Services, Inc.**  
**P. O. Box 12313**  
**Research Triangle Park, NC 27709**

Under Contract No.  
68-02-2374  
EPA Project Officer  
R. E. Townsend

**United States Environmental Protection Agency**  
**Office of Air, Noise, and Radiation**  
**Office of Air Quality Planning and Standards**  
**Research Triangle Park, NC 27711**



## **Notice**

**This is not an official policy and standards document. The opinions, findings, and conclusions are those of the authors and not necessarily those of the Environmental Protection Agency. Every attempt has been made to represent the present state of the art as well as subject areas still under evaluation. Any mention of products or organizations does not constitute endorsement by the United States Environmental Protection Agency.**

## **Availability of Copies of This Document**

This document is issued by the Manpower and Technical Information Branch, Control Programs Development Division, Office of Air Quality Planning and Standards, USEPA. It is for use in training courses presented by the EPA Air Pollution Training Institute and others receiving contractual or grant support from the Institute.

Schools or governmental air pollution control agencies establishing training programs may receive single copies of this document, free of charge, from the Air Pollution Training Institute, USEPA, MD-20, Research Triangle Park, NC 27711. Others may obtain copies, for a fee, from the National Technical Information Service, 5825 Port Royal Road, Springfield, VA 22161.



**AIR POLLUTION TRAINING INSTITUTE  
MANPOWER AND TECHNICAL INFORMATION BRANCH  
CONTROL PROGRAMS DEVELOPMENT DIVISION  
OFFICE OF AIR QUALITY PLANNING AND STANDARDS**



*The Air Pollution Training Institute (1) conducts training for personnel working on the development and improvement of state, and local governmental, and EPA air pollution control programs, as well as for personnel in industry and academic institutions; (2) provides consultation and other training assistance to governmental agencies, educational institutions, industrial organizations, and others engaged in air pollution training activities; and (3) promotes the development and improvement of air pollution training programs in educational institutions and state, regional, and local governmental air pollution control agencies. Much of the program is now conducted by an on-site contractor, Northrop Services, Inc.*

*One of the principal mechanisms utilized to meet the Institute's goals is the intensive short term technical training course. A full-time professional staff is responsible for the design, development, and presentation of these courses. In addition the services of scientists, engineers, and specialists from other EPA programs, governmental agencies, industries, and universities are used to augment and reinforce the Institute staff in the development and presentation of technical material.*

*Individual course objectives and desired learning outcomes are delineated to meet specific program needs through training. Subject matter areas covered include air pollution source studies, atmospheric dispersion, and air quality management. These courses are presented in the Institute's resident classrooms and laboratories and at various field locations.*

*R. Alan Schueler*

R. Alan Schueler  
Program Manager  
Northrop Services, Inc.

*James A. Jahoke*  
James A. Jahoke  
Technical Director  
Northrop Services, Inc.

*Jean J. Schueneman*

Jean J. Schueneman  
Chief, Manpower & Technical  
Information Branch

# TABLE OF CONTENTS

<b>Major Course Goals</b> .....	1
<b>Course Objectives</b> .....	3
<b>Introduction</b> .....	5
<b>Lecture 1: Welcome, Registration, and Pre-test</b> .....	7
<b>Lecture 2: Introduction to Source Sampling</b> .....	9
Nomenclature .....	10
Emission Rate .....	14
Gas Physics .....	16
<b>Lecture 3: EPA Method 5 Sampling Train</b> .....	17
Schematic Diagram .....	18
<b>Lecture 4: Discussion of Laboratory Exercises</b> .....	19
Traverse Point Determination .....	21
Pitot Tube Calibration .....	24
Wet Bulb-Dry Bulb Technique .....	27
Orifice Meter Calibration .....	33
Determination of Velocity and Flow Rates .....	37
Data Summary .....	40
<b>Lecture 5 &amp; 6: Isokinetic Source Sampling and Isokinetic Rate Equations</b> .....	43
Isokinetic Sampling .....	45
Isokinetic Rate Equation .....	51
Lecture Problem .....	53
Nomograph .....	55
Homework Problem .....	57
<b>Lecture 7: Review of Reference Methods 1-4</b> .....	61
Lab Exercise .....	66
Dry Molecular Weight Determination .....	70
<b>Lecture 8: Calculation and Interpretation of Percent Isokinetic</b> .....	71
<b>Lecture 9: Sampling Train Configuration: Definition of a Particulate</b> .....	77
<b>Lecture 10: Discussion of Source Sampling Exercises</b> .....	79
Laboratory Exercises .....	90
Particulate Field Data Sheet .....	90
Source Test Data Summary Sheet .....	92
<b>Lecture 11: Concentration Correction and Problem Session</b> .....	97
<b>Lecture 12: Literature Sources</b> .....	103
<b>Lecture 13: The F-Factor Method</b> .....	107

<b>Lecture 14: Calculation Review</b> . . . . .	111
<b>Lecture 15: Error Analysis</b> . . . . .	115
<b>Lecture 16: Source Sampling Quality Assurance and Safety on Site</b> . . . . .	117
<b>Lecture 17: Particle Sizing Using a Cascade Impactor</b> . . . . .	121
<b>Lecture 18: Transmissometers</b> . . . . .	125
<b>Appendix A: Sample Data Sheets</b> . . . . .	135
Method 5 — Source Test Data Sheets . . . . .	137
Meter Console Calibration . . . . .	141
Nozzle Calibration . . . . .	142
Temperature Calibration . . . . .	143
Particulate Field Data . . . . .	145
Laboratory Analysis Data Particulate Source Sample . . . . .	147
Orsat Field Data . . . . .	148
Sample Label . . . . .	149
<b>Appendix B: Source Sampling Calculations</b> . . . . .	151
<b>Appendix C: Problems</b> . . . . .	161
Problems with Solutions . . . . .	163
Additional Problems . . . . .	175

# Major Course Goals

The major goal of Course #450, "Source Sampling for Particulate Pollutants", is to provide the student with a basic understanding of the theory and experimental methods involved in isokinetic sampling, the foundation of EPA Method 5.

Knowledge of isokinetic sampling, serving as the core of the course material, will then be amplified with lectures, problem sessions and lecture-demonstrations in order to present the many facets of particulate sampling. Upon completion of the course, the student should be able to design and plan a source test, perform all of the calculations involved in reporting a mass emission rate, and understand problems of error and quality assurance. The student should also become conversant with the methods of particle sizing and transmissometry. He should attain an awareness of the problems involved in source sampling and be able to recognize what constitutes difficult experimental situations, a good test, good data, and a good final report.

# Course Objectives

On completion of this course the student should be able to:

- Define symbols and common source sampling terms used in source sampling for particulate pollutants.
- Recognize, interpret and apply sections of the *Federal Register* pertinent to source sampling for particulate pollutants.
- Understand the construction, operation and calibration of component parts of the *Federal Register* Method 5 sampling train.
- Recognize the advantages and disadvantages of the nomograph and its uses in the establishment of the isokinetic sampling rate.
- Understand the “working” isokinetic rate equation and its derivation.
- Define isokinetic sampling and illustrate why it is important in sample extraction.
- Apply *Federal Register* Methods 1 through 4 in preparation for a particulate sampling test.
- Understand the construction, evaluation, standardization and orientation of the “S Type” pitot tube and its application to source sampling.
- Calculate the “Percent Isokinetic” value for a source test, and interpret the effect of over or under—isokinetic values on the source test results.
- Understand the quality assurance programs involved in source sampling dealing with nozzle sizing, orifice meter calibration, nomograph standardization and sample recovery.
- List the steps involved in conducting a source test, including completion of pre-test and post-test forms. The student should be able to recognize potential problem areas in preparing and conducting a source test.
- Properly assemble, leak check, conduct and recover a Method 5 sample according to *Federal Register*, August 18, 1977.
- Apply *Federal Register* Method 3 gas analysis in formulating the stack gas molecular weight and % excess air.
- Explain the principles behind the operation of particles sizing devices for sources and name some of those devices being tested by EPA.
- Define the terms opacity, transmittance and transmissometer.
- Recognize the relationship between optical density and particulate concentration.



# Introduction

The determination of particulate emissions from a stationary source requires the measurement of several source variables. The stack gas emitted from an incineration or process stack is a mixture of a number of gas components and particulates. The temperature and moisture content of the gases vary from source to source. The volume of gases emitted varies according to the size and type of the plant. It is not possible to sample all the gases and particulates emitted from a source in a given time period, therefore, a system was developed that would extract a representative sample while monitoring pertinent stack variables. The data from this representative sample is used in calculating an average particulate concentration in the stack gas. This concentration is calculated on the basis of standard gas temperature and pressure. The data are then utilized in calculating the emissions in terms of lbs/10<sup>6</sup> Btu Heat Input.

The Air Pollution Training Institute has developed Course 450 to instruct engineers, chemists, and technicians in particulate sampling methods. The sampling techniques and calculations used in the EPA Method 5 source sampling system are demonstrated and practiced for student comprehension. Students completing the 450 course with an understanding of the lecture, laboratory, and text materials should be able to conduct a Method 5 particulate determination at a stationary source.

This workbook is designed to provide the student with a guide to the lecture materials and laboratory exercises. Incorporated in this workbook the student will find reproductions of selected visual materials, lecture problems and data reporting forms. Lecture and laboratory sessions are presented in order of their expected presentation. Space is provided for additional notation by the student of lecture material as presented by the instructor.

# **Lecture 1**

## **WELCOME, REGISTRATION AND PRETEST**

### **Lesson Objectives:**

- To allow students to introduce themselves to the class; to determine the actual level of job experience in the class (the number of stack tests in which each student has participated) and to complete the pretest.


# Lecture 2

## INTRODUCTION TO SOURCE SAMPLING

### Lesson Objectives:

The student will be able to:

- Locate the goals and objectives of the course.
- Define the symbols and common source sampling terms used in the course.
- Recognize the basic features of the EPA Method 5 sampling train.
- Write the expressions for pollutant mass rate and emission rate, using symbols for stack gas concentration, stack gas volumetric flowrate, and heat input rate.
- Recognize the pitot tube equation on sight and understand the relative importance of the parameters in the equation.
- Write the ideal gas law equation and be able to describe the effects of changing pressure and temperature on a gas volume.
- Recognize the form of an ideal gas law correction equation.
- Recognize the importance of Bernoulli's principle in source sampling.



**EPA Method 5 particulate sampling train**

# Nomenclature

$A_n$	—	sampling nozzle cross-sectional area
$A_s$	—	stack cross-sectional area
$a$	—	mean particle projected area
$B_{wm}$	—	percent moisture present in gas at meter
$B_{ws}$	—	percent moisture present in stack gas
$C_p$	—	pitot tube calibration coefficient
$C_{p(std)}$	—	standard pitot-static tube calibration coefficient
$c_s$	—	particulate concentration in stack gas mass/volume
$c_{ws}$	—	particulate concentration on a wet basis mass/wet volume
$c_{s12}$	—	particulate concentration corrected to 12% CO <sub>2</sub>
$c_{s50}$	—	particulate concentration corrected to 50% excess air
$D_E$	—	equivalent diameter
$D_H$	—	hydraulic diameter
$D_n$	—	source sampling nozzle diameter
$E$	—	emission rate mass/heat Btu input
$e$	—	base of natural logarithms ( $\ln 10 = 2.302585$ )
%EA	—	percent excess air
$F_c$	—	F-factor using $c_s$ and CO <sub>2</sub> on wet or dry basis
$F_d$	—	F-factor using $c_s$ and O <sub>2</sub> on a dry basis
$F_w$	—	F-factor using $c_{ws}$ and O <sub>2</sub> on a wet basis
$F_o$	—	miscellaneous F-factor for checking orsat data
$\Delta H@$	—	pressure drop across orifice meter for 0.75 CFM flow rate at standard conditions
$\Delta H$	—	pressure drop across orifice meter
$j$	—	equal area centroid
$K_p$	—	pitot tube equation dimensional constant

$$\text{Metric Units} = 34.97 \text{ m/sec.} \left[ \frac{\text{g/g mole (mm Hg)}}{(^{\circ}\text{K})(\text{mm H}_2\text{O})} \right]^{1/2}$$

$$\text{English Units} = 85.49 \text{ ft./sec.} \left[ \frac{\text{lb/lb mole (in. Hg)}}{(^{\circ}\text{R})(\text{in. H}_2\text{O})} \right]^{1/2}$$

L	—	length of duct cross-section at sampling site
$l'$	—	path length
$L_1$	—	plume exit diameter
$L_2$	—	stack diameter
m	—	mass
$M_d$	—	dry stack gas molecular weight
$M_s$	—	wet stack gas molecular weight
n	—	number of particles
$N_{Re}$	—	Reynolds number
$O_1$	—	plume opacity at exit
$O_2$	—	in stack plume opacity
$P_{atm}$	—	atmospheric pressure
$P_b$	—	barometric pressure ( $P_b = P_{atm}$ )
$P_m$	—	absolute pressure at the meter
pmr	—	Pollutant mass rate
$P_s$	—	absolute pressure in the stack
$P_{std}$	—	standard absolute pressure Metric Units = 760 mm Hg English Units = 29.92 in. Hg
$\Delta p$	—	gas velocity pressure
$\Delta P_{(std)}$	—	standard velocity pressure read by the standard pitot tube
$\Delta P_{test}$	—	gas velocity pressure read by the type "S" pitot tube
q	—	particle extinction coefficient
$Q_s$	—	stack gas volumetric flow rate corrected to standard conditions
R	—	Gas law constant, $21.83 \frac{(\text{in. Hg})(\text{ft.}^3)}{(\text{lb} - \text{mole})(^\circ\text{R})}$
t	—	temperature ( $^\circ\text{Fahrenheit}$ or $^\circ\text{Celsius}$ )
$T_m$	—	absolute temperature at the meter Metric Units = $^\circ\text{C} + 273 = ^\circ\text{K}$ English Units = $^\circ\text{F} + 460 = ^\circ\text{R}$
$T_s$	—	absolute temperature of stack gas
$T_{std}$	—	standard absolute temperature Metric Units = $20^\circ\text{C} + 273 = 293^\circ\text{K}$ English Units = $68^\circ\text{F} + 460 = 528^\circ\text{R}$
$V_m$	—	volume metered at actual conditions
$V_{mstd}$	—	volume metered corrected to standard conditions
v.p.	—	water vapor pressure
$v_s$	—	stack gas velocity
Volume $\text{H}_2\text{O}$	—	Metric units = $0.00134 \text{ m}^3/\text{ml} \times \text{ml } \text{H}_2\text{O}$ English units = $0.0472 \text{ ft.}^3/\text{ml} \times \text{ml } \text{H}_2\text{O}$
W	—	width of the duct cross-section at the sampling site
$\theta$	—	time in minutes

# Subscripts


atm	—	atmospheric
ave	—	average
b	—	barometric
d	—	dry gas basis
f	—	final
g	—	gage
i	—	initial
m	—	at meter
n	—	at nozzle
p	—	of pitot tube
s	—	at stack
SCF	—	standard cubic feet
std	—	standard conditions
w	—	wet basis

## NOTES:

### III. EMISSION RATE

#### Methods of monitoring source emissions


#### POLLUTANT MASS RATE



$$V_{\text{nozzle}} = V_{\text{stack}}$$

ISOKINETIC CONDITION



$$v_s = K_p C_p \sqrt{\frac{T_s \Delta p}{M_s P_s}}$$

PITOT TUBE EQUATION

Emissions in terms of  
lbs / 10<sup>6</sup> Btu heat input

$$E = \frac{c_s \bar{Q}_s}{\bar{Q}_H}$$

## **GAS PHYSICS**

### **Ideal Gas Law**

#### **Volume Correction**

$$V_{\text{corr}} = V_s \frac{P_s T_{\text{std}}}{P_{\text{std}} T_s}$$

#### **Bernoulli's Principle**

$$\frac{1}{2} \rho \Delta v^2 + \rho g \Delta h + \Delta p = 0$$

# **Lecture 3**

## **EPA METHOD 5 SAMPLING TRAIN**

### **Lesson Objectives:**

The student will be able to:

- List the construction and calibration requirements for the Method 5 Sampling Nozzle.
- List the nozzle, probe, pitot tube, and thermocouple placement requirements to minimize aerodynamic interferences.
- List the approved construction materials for the nozzle probe, pitot tube, and probe liner.
- Describe the probe locking system for preventing misalignment in the gas stream.
- Describe the advantages and disadvantages of various types of sample cases and glassware.
- List the advantages and disadvantages of various materials used in constructing umbilical lines.
- Describe the advantages of magnehelic gages for pressure measurements and list the requirements for using these gages in an EPA Method 5 Sampling System.
- Compare the cost effectiveness of the nomograph and calculator.




Figure 3-1. EPA Method 5 particulate sampling train

1. Sampling nozzle
2. Sampling probe sheath
3. Heated sample probe liner
4. Cyclone assembly (proposed regulations do not require this cyclone)
5. Out of stack filter assembly
6. Heated filter compartment maintained  $120^{\circ}\text{C} \pm 14^{\circ}\text{C}$  ( $248^{\circ}\text{F} \pm 25^{\circ}\text{F}$ ) (or temperature specified in 40CFR subpart)
7. Impinger case
8. First impinger filled with  $\text{H}_2\text{O}$  (100 ml)
9. Greenburg-Smith (or modified Greenburg-Smith) impinger filled with  $\text{H}_2\text{O}$  (100 ml)
10. Third impinger – dry
11. Fourth impinger – filled with  $\text{H}_2\text{O}$  absorption media (200-300 gm)
12. Impinger exit gas thermometer
13. Check valve to prevent back pressure
14. Umbilical cord – vacuum line
15. Pressure gage
16. Coarse adjustment valve
17. Leak free pump
18. By-pass valve
19. Dry gas meter with inlet and outlet dry gas meter thermometer
20. Orifice meter with manometer
21. Type S pitot tube with manometer
22. Stack temperature sensor

# **Lecture 4**

## **DISCUSSION OF LABORATORY EXERCISES**

### **Lesson Objectives:**

The student will be able to:

- List the procedures for applying reference Method 1 at circular and rectangular stacks.
- List the steps involved in performing an “S” type pitot tube calibration.
- Describe the procedures for wet bulb dry bulb moisture estimation.
- Calibrate the meter console orifice meter when the dry gas meter has been calibrated against a reference volume standard.

## **I. REFERENCE METHOD I**

### **A. Laminar Gas Flow**

### **B. Flow Disturbance**

### **C. Procedures**

## II. Lab Exercises

### 1. TRAVERSE POINT DETERMINATION

#### a. Minimum number of traverse points:

- (1) Measure the inside dimensions of the duct at the sampling site. Record this data in table I.
- (2) Calculate the duct equivalent diameter according to the equation.

$$D_{Eq} = \frac{2(LW)}{L+W}$$

where:

$D_{Eq}$  = the equivalent diameter of the duct

$L$  = the length of the duct cross-section at the sampling site

$W$  = the width of the duct cross-section at the sampling site.

- (3) Measure the distance from the sampling site to the nearest downstream flow disturbance (distance A in figure I) and from the site to the nearest upstream flow disturbance (distance B in figure I).
- (4) Divide these distances by the equivalent diameter of the duct.
- (5) Determine the corresponding number of traverse points for each distance from Figure I. This number must be a multiple of two.
- (6) Select the higher of these two numbers. This is the minimum number of traverse points that must be used.
- (7) Record all data in Table I.




Figure I. Minimum number of traverse points.

TABLE I  
NUMBER OF TRAVERSE POINTS

L= \_\_\_\_\_

W= \_\_\_\_\_

D<sub>Eq</sub>= \_\_\_\_\_

Distance A = \_\_\_\_\_ and in equivalent diameters \_\_\_\_\_

Distance B = \_\_\_\_\_ and in equivalent diameters \_\_\_\_\_

Number of traverse points required by distance A \_\_\_\_\_


Number of traverse points required by distance B \_\_\_\_\_

Required number of traverse points \_\_\_\_\_



b. Traverse point location.

- (1) Divide the duct cross-section into as many equal rectangular areas as there are traverse points. Maintain the length-to-width ratio of these areas between 1.0 and 2.0. Use the rectangle below for diagramming.
- (2) Locate a traverse point at the center of each individual area.



L/W ratio=\_\_\_\_\_

Duct cross-section lay-out

## 2. PITOT TUBE CALIBRATION

### 1. Determination of the Type S Pitot Tube Coefficient, $C_p$

In this exercise you will calibrate the Type S pitot tube used for velocity measurement against a standard pitot tube.




Figure 2

#### Procedure

- Set-up, level and zero the inclined manometer.
- Be sure that one tube of the type S pitot tube is labeled "A" and the other is labeled "B".
- Place an arbitrary mark on the pitot tube such that when the mark is placed at the outside edge of the duct, the tip of the pitot tube is near the center of the duct.
- Connect the pitot tube to the manometer as shown in Figure 2.
- Insert the pitot tube into the duct until the mark is at the outside edge of the duct wall.
- Align the pitot tube so that the tube labeled "A" faces directly into the flow stream.

- g. Record (in Table 2) the velocity pressure indicated by the manometer.
- h. Place a mark on the standard pitot tube such that when the mark is placed at the outside edge of the duct wall, the tip of the pitot tube is in exactly the same location in the duct as the Type S pitot tube was.
- i. Connect the pitot tube to the manometer as shown in Figure 2.
- j. Insert the tube into the duct until the mark is at the outside edge of the duct wall.
- k. Align the tube so that it faces directly into the flow stream.
- l. Record (in Table 2) the velocity head indicated by the manometer.
- m. Determine the pitot tube coefficient according to the equation

$$C_p = C_p \text{ (standard)} \sqrt{\frac{\Delta p \text{ (standard)}}{\Delta p \text{ (Type S)}}}$$

Assume the  $C_p \text{ (standard)}$  is 0.99.

- n. Transfer this coefficient to Table 2.

# CALIBRATION OF "S" TYPE PITOT TUBE

Probe-Type "S" Pitot Tube: ID. No. \_\_\_\_\_

NBS Standard Pitot-Static Tube  $C_p = 0.99$

Barometric Pressure \_\_\_\_\_ Duct Gas Temperature \_\_\_\_\_

Date \_\_\_\_\_ Calibration Operator(s) \_\_\_\_\_

TABLE #2

S-Type Pitot Tube Coefficient Data

	Legs A, B of "S" Type Pitot Tube	Standard Pitot- Static Tube $\Delta p$ in. $H_2O$	"S" Type Pitot Tube $\Delta p$ in. $H_2O$	$C_{p \text{ Test}}$ Leg A	$C_{p \text{ Test}}$ Leg B
Test 1	A				
	B				
Test 2	A				
	B				
Test 3	A				
	B				
				$\overline{C_p}$	


$$C_{p \text{ Test}} = \left[ \frac{\Delta p_{\text{std}}}{\Delta p_{\text{Test}}} \right]^{\frac{1}{2}} C_{p \text{ std}}$$

### 3. WET BULB-DRY BULB TECHNIQUE

The determination of stack gas moisture content can be easily accomplished by either of four sampling techniques:


- Condensation (Federal Register Method 4)
- Adsorption (modified Federal Register Method 4)
- Wet Bulb-Dry Bulb
- Nomograph

The Federal Register Method 4 procedure for moisture determination in flue gas requires a sampling train composed of a heated probe, midget impingers and a silica gel tube. The flue gas is extracted from the source at a sampling rate of  $0.75 \text{ ft}^3/\text{min}$  or at a rate proportional to the stack gas velocity. The amount of moisture in the flue gas is determined gravimetrically and volumetrically from the impinger system/silica gel tube to give a final moisture determination.



Federal Register  
Method 4  
Sampling Train

Another method of determining moisture content of the flue gas relies on adsorption of the gas stream onto a desiccant (i.e. silica gel).



Modified Method 4

The amount of collected water is determined by the weight difference of the dessicant before and after sampling corrected to standard conditions employing the following two equations:

$$\text{Equation (1): } B_{ws} = \frac{V_{wc}}{V_{wc} + V_{mc}}$$

where  $B_{ws}$  = Proportion by volume of water vapor in the gas stream, dimensionless

$V_{wc}$  = The volume of water vapor collected at standard conditions,  $\text{ft}^3$

$V_{mc}$  = Dry Gas volume through the meter at standard conditions,  $\text{ft}^3$

The volume of water vapor collected at standard conditions,  $V_{wc}$ , is given in the following equation:

$$\text{Equation (2): } V_{wc} = 0.0472 \text{ ft}^3/\text{gram} (V_f - V_i)$$

where  $V_f$  = Final weight of M4 Tube, grams

$V_i$  = Initial weight of M4 Tube, grams

0.0472 = The number of cubic feet that 1 gram of water would occupy in the vapor state at standard conditions.

The dry gas volume of sample pulled through the meter at standard conditions can be calculated from the following equation:

$$V_{mc} = V_m Y \frac{P_m T_{std}}{P_{std} T_m}$$

where

$V_m$  = Dry gas volume measured by meter,  $\text{ft}^3$

$P_m$  = Barometric pressure at gas meter, in. Hg.

$P_{\text{std}}$  = Pressure at standard conditions, 29.91 in. Hg.


$T_{\text{std}}$  = Absolute temperature at standard conditions,  $528^\circ \text{R}$

$T_m$  = Absolute temperature at meter ( $F + 460$ ), R

$Y$  = Dry gas meter correction factor, dimensionless

Both of the above methods require some form of extracting the flue gas from the source, hence involving considerable time and effort. For approximate determination, the latter two methods serve equally well in stack gas moisture determination.

In the wet bulb/dry bulb technique, two mercury in glass thermometers are required to measure flue gas temperature. One thermometer, dry bulb, is inserted into the stack and allowed to reach equilibrium. This temperature is recorded as the dry bulb temperature. The other thermometer is covered with a cotton wick saturated with distilled water. It is also inserted into the stack and allowed to reach equilibrium. The dry bulb rapidly reaches equilibrium, while the wet bulb rises to equilibrium, levels off, and then rises again once the wick is dry. The inflection point at which the temperature reaches equilibrium is considered the wet bulb temperature.



Wet Bulb/Dry Bulb  
Moisture Determination

At temperatures below  $212^\circ\text{F}$ , wet and dry bulb temperatures may be measured in the flue gas without worry of sulfuric acid mist being present and raising the dew point substantially. However, above  $212^\circ\text{F}$ , erroneous results may be obtained due to rapid drying of the wet bulb wick.

Moisture content can be calculated, using the wet bulb/dry bulb technique, from the following equation:

$$B_{ws} = \frac{V.P.}{P_{abs}} \quad \text{Moisture Equation}$$

where:  $V.P.$  = Vapor pressure of  $H_2O$   
 $= S.V.P. - (3.67 \times 10^{-4}) (P_{abs}) (T_d - T_w) \left( 1 + \frac{t_w - 32}{1571} \right)$

$S.V.P.$  = Saturated  $H_2O$  vapor pressure at wet bulb temperature (inches of Hg) taken from table on page 31.

$P_{abs}$  = Absolute pressure of stack gas

$t_d$  = Temperature of dry bulb measurement, °F

$t_w$  = Temperature of wet bulb inflection point, °F

To determine approximate moisture in a stack gas, perform the wet bulb/dry bulb technique and fill in the following equation:

$$V.P. = \text{_____ in. Hg} - \left[ 3.67 \times 10^{-4} (\text{_____ in. Hg}) (\text{_____ } ^\circ\text{F} - \text{_____ } ^\circ\text{F}) \left( 1 + \frac{\text{_____ } ^\circ\text{F} - 32^\circ\text{F}}{1571} \right) \right]$$

$$B_{ws} = \frac{\text{_____ in. Hg}}{\text{_____ in. Hg}} = \text{_____} \times 100 = \text{_____} \%$$

Another method for determining approximate moisture in the flue gas is by the use of a nomograph. The nomograph has been mathematically constructed to solve various equations when known process information is supplied. While nomographs may not be as accurate as actual analysis they do provide a useful approximate moisture figure needed in solving the isokinetic ratio equation. To properly use the nomograph, determine the wet bulb/dry bulb temperatures and proceed with the following steps:

- (1) Calculate wet bulb depression

$$t_d - t_{wet} = \text{depression, } ^\circ\text{F}$$

- (2) On the line from stack absolute pressure to wet bulb depression temperature, mark pivot line #1.




**Wet Bulb  
Temp.  
Deg. F.**

	0	1	2	3	4	5	6	7	8	9
— — — 20	.0126	.0119	.0112	.0106	.0100	.0095	.0089	.0084	.0080	.0075
— — — 10	.0222	.0209	.0199	.0187	.0176	.0168	.0158	.0150	.0142	.0134
— — —	.0376	.0359	.0339	.0324	.0306	.0289	.0275	.0250	.0247	.0233
0	.0376	.0398	.0417	.0463	.0441	.0489	.0517	.0541	.0571	.0598
10	.0631	.0660	.0696	.0728	.0768	.0810	.0846	.0892	.0932	.0982
20	.1025	.1080	.1127	.1186	.1248	.1302	.1370	.1429	.1502	.1567
30	.1647	.1716	.1803	.1878	.1955	.2035	.2118	.2203	.2292	.2382
40	.2478	.2576	.2677	.2782	.2891	.3004	.3120	.3240	.3364	.3493
50	.3626	.3764	.3906	.4052	.4203	.4359	.4520	.4586	.4858	.5035
60	.5218	.5407	.5601	.5802	.6009	.6222	.6442	.6669	.6903	.7144
70	.7392	.7648	.7912	.8183	.8462	.8750	.9046	.9352	.9666	.9989
80	1.032	1.066	1.102	1.138	1.175	1.213	1.253	1.293	1.335	1.378
90	1.422	1.467	1.513	1.561	1.610	1.660	1.712	1.765	1.819	1.875
100	1.932	1.991	2.052	2.114	2.178	2.243	2.310	2.379	2.449	2.521
110	2.596	2.672	2.749	2.829	2.911	2.995	3.081	3.169	3.259	3.351
120	3.446	3.543	3.642	3.744	3.848	3.954	4.063	4.174	4.289	4.406
130	4.525	4.647	4.772	4.900	5.031	5.165	5.302	5.442	5.585	5.732
140	5.881	6.034	6.190	6.330	6.513	6.680	6.850	7.024	7.202	7.384
150	7.569	7.759	7.952	8.150	8.351	8.557	8.767	8.981	9.200	9.424
160	9.652	9.885	10.12	10.36	10.61	10.86	11.12	11.38	11.65	11.92
170	12.20	12.48	12.77	13.07	13.37	13.67	13.98	14.30	14.62	14.96
180	15.29	15.63	15.98	16.34	16.70	17.07	17.44	17.82	18.21	18.61
190	10.01	19.42	19.84	20.27	20.70	21.14	21.50	22.05	22.52	22.99
200	23.47	23.96	24.46	24.97	25.48	26.00	26.53	27.07	27.62	28.18
210	28.75	29.33	29.92	30.52	31.13	31.75	32.38	33.02	33.67	34.33
220	35.00	35.68	36.37	37.07	37.78	38.50	39.24	39.99	40.75	41.52
230	42.31	43.11	43.92	44.74	45.57	46.41	47.37	48.14	49.03	49.93
240	50.84	51.76	52.70	53.65	54.62	55.60	56.60	57.61	58.63	59.67
250	60.72	61.79	62.88	63.98	65.10	66.23	67.38	68.54	69.72	70.92
260	72.13	74.36	74.61	75.88	77.17	78.46	79.78	81.11	82.46	83.83
270	85.22	86.63	88.06	89.51	90.97	92.45	93.96	95.49	97.03	98.61
280	100.2	101.8	103.4	105.0	106.7	108.4	110.1	111.8	113.6	115.4
290	117.2	119.0	120.8	122.7	124.6	126.5	128.4	130.4	132.4	134.4
300	136.4	138.5	140.6	142.7	144.8	147.0	149.2	151.4	153.6	155.9
310	158.2	160.5	162.8	165.2	167.6	170.0	172.5	175.0	177.5	180.0
320	182.6	185.2	187.8	190.4	193.1	195.8	198.5	201.3	204.1	206.9
330	209.8	212.7	215.6	218.6	221.6	224.6	227.7	230.8	233.9	237.1
340	240.3	243.5	246.8	250.1	253.4	256.7	260.1	263.6	267.1	270.6
350	274.1	277.7	281.3	284.9	288.6	292.3	296.1	299.9	303.8	307.7
360	311.6	315.5	319.5	323.5	327.6	331.7	335.9	340.1	344.4	348.7
370	353.0	357.4	361.8	366.2	370.7	375.2	379.8	384.4	389.1	393.8
380	398.6	403.4	408.2	413.1	418.1	423.1	428.1	433.1	438.2	443.4
390	448.6	453.9	459.2	464.6	470.0	475.5	481.0	486.2	492.2	497.9
400	503.6	509.3	515.1	521.0	526.9	532.9	538.9	545.0	551.1	557.3

**S.V.P. (Saturated H<sub>2</sub>O vapor pressure wet bulb temperature—inches of mercury)**

- (3) On the line from the pivot line #1 mark and the  $t_w$ , mark on pivot line #2.
- (4) On the line from the stack absolute pressure through the mark on pivot line #2 read %  $H_2O$  on scale M.

Percent Moisture in Flue Gas  
Nomograph Technique



In conclusion, we have discussed four methods for determining moisture in the stack gas: condensation, adsorption, wet bulb-dry bulb and the nomograph. The method you select will depend upon your sampling parameters and degree of accuracy.

#### 4. CALIBRATION OF THE ORIFICE METER

The orifice meter is a thin flat plate with a sharp-edged hole concentric with the axis of the diameter of the pipe in which it is located. A pressure differential is created across the orifice plate as gases flow through the concentric hole. This pressure differential is directly related to the flow rate through the orifice. A properly constructed orifice meter will locate the orifice plate at least 8 pipe diameters upstream and 2 pipe diameters downstream of any disturbances to the gas flow. The pressure differential across the plate is best measured by "Radius Taps" located 1 pipe diameter upstream and 1/2 pipe diameter downstream of the orifice plate. Improperly positioned pressure taps may not give a true representation of the gas flow rate. Calibration of the orifice meter is essential and should be performed on a regular basis.

##### EXERCISE

- The exercise is directed at establishing a flow rate through the orifice of 0.75cfm of dry air ( $M_d=29\text{g/mole}$ ) at  $68^{\circ}\text{F}$  29.92in. Hg. (STP). The pressure differential for this flow rate is designated  $\Delta H_0$ .

- The flow rate through the orifice is calculated in the equation

$$Q_m = K_m \left[ \frac{T_m \Delta H}{P_m M_m} \right]^{1/2}$$

$\Delta H$  = Pressure differential in.  $H_2O$

$K_m$  = Proportionality factor

$Q_m$  = Volumetric gas flow rate (cfm)

$T_m = t_m (^{\circ}F) + 460$

$P_m$  = Absolute pressure at the meter

$M_m$  = Molecular weight of gas flowing through orifice

2. Solving this equation for  $\Delta H$

$$\Delta H = \left[ \frac{Q_m}{K_m} \right]^2 \frac{P_m M_m}{T_m}$$

3. Substituting terms given for  $\Delta H_{\theta}$

$$\Delta H_{\theta} = \left[ \frac{0.75 \text{ cfm}}{K_m} \right]^2 \frac{(29.92 \text{ in.Hg.}) (29 \text{ g/mole})}{528^{\circ}R} = \frac{0.9244}{K_m^2}$$

. Laboratory procedures - Record data in the appropriate spaces on the form provided.

1. Turn on sampling meter console.
2. Close coarse valve and turn fine adjust valve all the way counter-clockwise.
3. Level and zero orifice manometer.
4. Partially open coarse valve using it and fine adjust to establish orifice  $\Delta H$ .
5. Read DGM dial and simultaneously start stopwatch. Allow 2 minutes to pass maintaining proper  $\Delta H$  the entire period.

6. Simultaneously close course valve and stop the watch.
7. Record final DGM reading and other data and repeat procedure for other  $\Delta H$ .
8. For the higher flow rates, it may be necessary to cut off the pump while leaving the valves set, read the DGM, then simultaneously start the pump and the watch.
9. Perform calculations as illustrated on the orifice meter calibration form.

TABLE IV  
Orifice Meter Calibration

Operator(s) \_\_\_\_\_ Date \_\_\_\_\_  
 Meter Console No. \_\_\_\_\_ DGM No. \_\_\_\_\_  
 Barometric Pressure ( $P_m$ ) \_\_\_\_\_ in.Hg. DGM Correction Factor (DGMCF) \_\_\_\_\_

$\Delta H$ in $H_2O$	$V_1$ Initial DGM Dial Reading	$\theta$ Minutes	$V_2$ Final DGM Dial Reading	$Q_m$ (CFM)	$t_m$ ( $^{\circ}F$ )	$K_m$
0.25						
0.5						
1.0						
2.0						
4.0						
6.0						
Average ( $\bar{K}_m$ )						

$$Q_m = \frac{(V_2 - V_1) \times \text{DGMCF}}{\theta(\text{minutes})}$$

$$K_m = Q_m \left[ \frac{P_m M_m}{T_m \Delta H} \right]^{1/2}$$

$$\Delta H_{\theta} = \frac{0.9244}{(\bar{K}_m)^2}$$

## 5. DETERMINATION OF GAS STREAM VELOCITY AND VOLUMETRIC FLOW RATE

The volumetric flow rate of a gas stream can now be determined. It is the velocity of the stream multiplied by the cross-sectional area through which it is flowing. The cross-sectional area can be determined by conventional means using diameter or circumference data for circular stacks and length and width data for rectangular stacks. Velocity, then, becomes the basic parameter necessary for volumetric flow rate calculation.

The velocity of a gas stream is determined by using a pitot tube. The pitot tube equation can be written as

$$v_s = K_p C_p (\sqrt{\Delta p_{ave}}) \sqrt{\frac{T_s}{P_s M_s}}$$

where:

$v_s$  = velocity of the gas stream, ft /sec

$T_s$  = absolute temperature, °R (°F + 460)

$P_s$  = absolute pressure, in. Hg

$M_s$  = molecular weight of the gas, lb /lb -mole

$\Delta p$  = velocity pressure, in. H<sub>2</sub>O

$K_p$  = constant:  $85.49 \sqrt{\frac{\text{ft}^2 \text{ in. Hg lbs /lb -mole}}{\text{sec}^2 \text{ in. H}_2\text{O } ^\circ\text{R}}}$  for the  
above dimensions

$C_p$  = pitot tube coefficient, dimensionless.

The volumetric flow rate of a gas stream is calculated according to the equations: Actual Stack Gas Volumetric Flow Rate

$$Q_a = v_s A$$

Stack Gas Volumetric Flow Rate corrected to standard conditions

$$Q_s = 3600 \text{ sec/hr } (1-B_{ws}) v_s A \left( \frac{T_{std}}{T_s} \right) \left( \frac{P_s}{P_{std}} \right)$$

where:

$Q_a$  = the volumetric flow rate of the gas stream at actual conditions in cubic feet per hour (acfh)

$Q_s$  = the volumetric flow rate of the gas stream on a dry basis at standard conditions in cubic feet per hour (scfh)

3600 = conversion factor (3600 sec /hr )

$B_{ws}$  = the moisture fraction by volume of the gas stream (dimensionless)

$v_s$  = the velocity of the gas stream at the sampling site (ft /sec )

$A$  = the cross-sectional area of the gas stream at the sampling site (ft<sup>2</sup>)

$T_{std}$  = the absolute temperature at standard conditions (528° R)

$T_s$  = the average, absolute temperature of the gas stream (°R)

$P_s$  = the average, absolute pressure of the gas stream (in. Hg)

$P_{std}$  = the absolute pressure at standard conditions (29.92 in. Hg).

In order to calculate the velocity,  $v_s$ , and the volumetric flow rate,  $Q_s$ , you must measure  $C_p, T_s$ ,  $\Delta p$ ,  $P_s$ ,  $M_s$ , and  $A$ . You will notice that in order to determine the molecular weight,  $M_s$ , there are two steps--the determination of the molecular weight ( $M_d$ ) of the gas stream on a dry basis and the determination of the moisture content ( $B_{ws}$ ) of the gas stream.



## Procedures:

Determine the following:

1. Pitot tube coefficient ( $C_p$ ).
2. Velocity pressure ( $\Delta p$ ).
3. Molecular weight ( $M_d$ ).
4. Stack pressure ( $P_s$ ).
5. Stack temperature ( $T_s$ ).
6. Moisture fraction ( $B_{ws}$ ).

When you have conducted the exercises and made the appropriate calculations, transfer the data to Table III and calculate the velocity.

For this exercise, assume a  $M_d$  of 29.0 and a  $B_{ws}$  as determined in wet bulb-dry bulb lab.

TABLE III

### VELOCITY AND VOLUMETRIC FLOW RATE CALCULATIONS

A = \_\_\_\_\_

$K_p$  = 85.49 \_\_\_\_\_

$C_p$  = \_\_\_\_\_

$(\sqrt{\Delta p})_{ave}$  \_\_\_\_\_ (in.  $H_2O$ )<sup>1/2</sup>

$T_s$  = \_\_\_\_\_ °R

$P_s$  = \_\_\_\_\_ in. Hg

$M_d$  = \_\_\_\_\_ lb/lb-mole

$B_{ws}$  = \_\_\_\_\_ moisture fraction

$M_s = M_d (1 - B_{ws}) + 18 B_{ws} =$  \_\_\_\_\_

$$v_s = K_p C_p (\sqrt{\Delta p})_{ave} \sqrt{\frac{T_s}{P_s M_s}} = \underline{\hspace{2cm}}$$

$$Q_s = 3600 \text{ sec/hr} (1 - B_{ws}) v_s A \left( \frac{T_{std}}{T_s} \right) \left( \frac{P_s}{P_{std}} \right) = \underline{\hspace{2cm}}$$

Name \_\_\_\_\_

Group no. \_\_\_\_\_

Date \_\_\_\_\_

### DATA SUMMARY

1. Stack diameter \_\_\_\_\_
2. Equivalent diameter ( $D_E$ ) \_\_\_\_\_
3. Number of sampling points required \_\_\_\_\_
4. Standard pitot tube  $C_p$  \_\_\_\_\_
5. Type S pitot tube  $C_p$  \_\_\_\_\_
6. Barometric pressure ( $P_b$ ) \_\_\_\_\_
7. Absolute stack pressure ( $P_s$ ) \_\_\_\_\_
8. Meter temperature ( $T_m$ ) \_\_\_\_\_
9. Stack temperature ( $T_s$ ) \_\_\_\_\_
10. % Moisture in stack gas \_\_\_\_\_
11. Dry molecular weight of stack gas ( $M_d$ ) \_\_\_\_\_
12. Wet molecular weight of stack gas ( $M_s$ ) \_\_\_\_\_
13. Average gas velocity ( $v_s$ ) \_\_\_\_\_
14. Average stack volumetric flow rate  
    Actual ( $Q_a$ ) \_\_\_\_\_  
    Standard ( $Q_s$ ) \_\_\_\_\_
15. Meter console no. \_\_\_\_\_  $\Delta H$  @ \_\_\_\_\_

Name \_\_\_\_\_

Group no. \_\_\_\_\_

Date \_\_\_\_\_

### DATA SUMMARY

1. Stack diameter \_\_\_\_\_
2. Equivalent diameter ( $D_E$ ) \_\_\_\_\_
3. Number of sampling points required \_\_\_\_\_
4. Standard pitot tube  $C_p$  \_\_\_\_\_
5. Type S pitot tube  $C_p$  \_\_\_\_\_
6. Barometric pressure ( $P_b$ ) \_\_\_\_\_
7. Absolute stack pressure ( $P_s$ ) \_\_\_\_\_
8. Meter temperature ( $T_m$ ) \_\_\_\_\_
9. Stack temperature ( $T_s$ ) \_\_\_\_\_
10. % Moisture in stack gas \_\_\_\_\_
11. Dry molecular weight of stack gas ( $M_d$ ) \_\_\_\_\_
12. Wet molecular weight of stack gas ( $M_s$ ) \_\_\_\_\_
13. Average gas velocity ( $v_s$ ) \_\_\_\_\_
14. Average stack volumetric flow rate  
    Actual ( $Q_a$ ) \_\_\_\_\_  
    Standard ( $Q_s$ ) \_\_\_\_\_
15. Meter console no. \_\_\_\_\_  $\Delta H @$  \_\_\_\_\_

This sheet is to be handed in Wednesday morning.

# Lectures 5 & 6

## ISOKINETIC SOURCE SAMPLING AND ISOKINETIC RATE EQUATIONS

### Lesson Objectives:

The student will be able to:

- Define isokinetic sampling.
- Illustrate why isokinetic sampling is necessary when sampling for particulate emissions.
- State how the particulate concentration given by the Method 5 train will change when the sampling is performed overisokinetically .
- State how the particulate concentration given by the Method 5 train will change when the sampling is performed underisokinetically .
- Recall the basic equation for establishing the isokinetic rate,  $\Delta H = K \Delta p$
- Explain that gas passing through the sampling train undergoes changes of moisture content, temperature, and pressure.
- Explain that the isokinetic rate equation is derived from the requirement that  $v_n$  must equal  $v_s$ , and that one obtains the final expression by substituting the pitot tube equation and orifice meter equation and by making proper corrections for pressure, temperature, and moisture content.
- Recognize the fact that a separate equation exists for the determination of the nozzle diameter.
- Calculate the value of  $D_n$ , the nozzle diameter, given the appropriate input data, using a calculator or a slide rule.

- Calculate the value of  $K$  and  $\Delta H$ , given the appropriate input data, using a calculator or a slide rule.
- Calculate values of  $D_n$ ,  $K$ , and  $\Delta H$  using a source sampling nomograph.
- State the assumptions of the source sampling nomograph.
- Check the accuracy of the source sampling nomograph and recognize the effect of errors in computed  $\Delta H$  values on test results.

## ISOKINETIC SAMPLING

Isokinetic sampling conditions exist when the velocity of the gases entering the probe nozzle tip ( $v_n$ ) is exactly equal to the velocity of the approaching stack gases ( $v_s$ ), that is  $v_n = v_s$ . The percent isokinetic is defined as:


$$\% \text{ isokinetic} = \frac{v_n}{v_s} \times 100$$

and is equal to 100% only when  $v_n = v_s$ . When  $v_n \neq v_s$  (anisokinetic conditions), sample concentrations can be biased due to the inertial effects of particles.

If the gas-flow streamlines are disturbed as in anisokinetic conditions:

1. Large particles tend to move in the same initial direction.
2. Small particles tend to follow the streamlines.
3. Intermediate particles are somewhat deflected.

As an example, assume that we have a large particle of 6 mass units and a small particle of .03 mass units. Consider the following situations:




Therefore:

$$\text{mass/minute} = 4 \times 6 + 4 \times .03 = 24.1 \frac{\text{mass units}}{\text{minute}}$$

$$C_n = \frac{24.1}{1} \frac{\text{m.u./min}}{\text{ft}^3/\text{min}} = 24.1 \frac{\text{m.u.}}{\text{ft}^3}$$

## 200% ISOKINETIC



Assume:  $v_n = 2v_s$

$Q_n = 2 \text{ cfm}$


4 large and 8 small particles collected/minute

Therefore:

$$\text{mass/minute} = 4 \times 6 + 8 \times .03 = 24.2 \text{ m.u./minute}$$

$$C_n = \frac{24.2}{2} \frac{\text{m.u./min}}{\text{ft}^3/\text{min}} = 12.1 \frac{\text{m.u.}}{\text{ft}^3}$$

## 50% ISOKINETIC



Assume:  $v_n = 1/2 v_s$

$Q_n = 1/2 \text{ cfm}$

4 large and 2 small particles collected/minute

Therefore:

$$\text{mass/minute} = 4 \times 6 + 2 \times .03 = 24.1 \text{ m.u./minute}$$

$$C_n = \frac{24.1}{1/2} \frac{\text{m.u./min}}{\text{ft}^3/\text{min}} = 48.2 \frac{\text{m.u.}}{\text{ft}^3}$$

The criteria of what particle sizes constitute large, intermediate, and small particles is a function of the particle density stack velocity, gas viscosity, and nozzle diameter. Various studies have been made to determine this relationship. The following are some references.

1. S. Badzioch, "Correction for Anisokinetic Sampling of Gas-borne Dust Particles" J. Inst. Fuel, 106-110 (March 1960).
2. W.C.L. Hemeon and G.F. Haines, Jr., "The Magnitude of Errors in Stack Dust Sampling" Air Repair 4, 159-164 (November 1954).
3. H.H. Watson, "Errors Due to Anisokinetic Sampling of Aerosols" Ind. Hyg. Quart., 21-25 (March 1954).
4. S. Badzioch, "Collection of Gas-borne Dust Particles by Means of an Aspirated Sampling Nozzle", Brit. J. Appl. Phys. 10, 26-32 (January 1959).
5. V. Vitols, "Theoretical Limits of Errors Due to Anisokinetic Sampling of Particulate Matter" J. APCA 16, 79-84 (February 1966).



$$\Delta H = K \Delta p$$

SIMPLIFIED  
ISOKINETIC  
RATE EQUATION

$$Q_n = A_n v_n = A_n v_s = \frac{\pi D_n^2}{4} v_s$$

NOZZLE TIP VOLUMETRIC FLOW RATE

$$Q_m = K_m \sqrt{\frac{T_m \Delta H}{P_m M_m}}$$

ORIFICE METER EQUATION

T and P CORRECTION  
FOR DRY GAS STREAM

$$Q_n = \frac{P_m}{P_s} \frac{T_s}{T_m} Q_m$$

$$n_s (1 - B_{ws}) = n_m (1 - B_{wm})$$

MOISTURE CORRECTION

$$Q_n = \frac{1 - B_{wm}}{1 - B_{ws}} \frac{T_s}{T_m} \frac{P_m}{P_s} Q_m$$

FLOW RATE CORRECTED FOR T, P & MOISTURE

$$Q_n = \frac{(1 - B_{wm}) T_s P_m}{(1 - B_{ws}) T_m P_s} K_m \sqrt{\frac{T_m \Delta H}{P_m M_m}}$$

RELATION OF FLOW RATE AT NOZZLE  
TO METER FLOW RATE

$$\frac{\pi D_n^2}{4} v_s = \frac{(1 - B_{wm}) T_s P_m}{(1 - B_{ws}) T_m P_s} K_m \sqrt{\frac{T_m \Delta H}{P_m M_m}}$$

$$v_s = K_p c_p \sqrt{\frac{T_s \Delta p}{P_s M_s}}$$

PITOT TUBE EQUATION

$$\frac{\pi D_n^2}{4} K_p C_p \sqrt{\frac{T_s \Delta p}{P_s M_s}} = \frac{(1 - B_{wm})}{(1 - B_{ws})} \frac{T_s P_m}{T_m P_s} K_m \sqrt{\frac{T_m \Delta H}{P_m M_m}}$$

$$\Delta H = \left\{ D_n^4 \left( \frac{\pi K_p C_p}{4 K_m} \right)^2 \frac{(1 - B_{ws})^2}{(1 - B_{wm})^2} \frac{M_m}{M_s} \frac{T_m P_s}{T_s P_m} \right\} \Delta p$$

SOLVING FOR  $\Delta H$

$$M_m = M_d(1 - B_{wm}) + 18 B_{wm}$$

$$M_s = M_d(1 - B_{ws}) + 18 B_{ws}$$

MOISTURE RELATIONSHIPS

$$\Delta H = \left\{ D_n^4 \left( \frac{\pi K_p C_p}{4 K_m} \right)^2 \frac{(1 - B_{ws})^2}{(1 - B_{wm})^2} \left[ \frac{M_d(1 - B_{wm}) + 18 B_{wm}}{M_d(1 - B_{ws}) + 18 B_{ws}} \right] \frac{T_m P_s}{T_s P_m} \right\} \Delta p$$

#### ISOKINETIC RATE EQUATION

$\Delta H_{@}$  IS DEFINED AS THE ORIFICE PRESSURE DIFFERENTIAL THAT GIVES 0.75 CFM OF AIR AT 68° F AND 29.92" Hg.

$$\Delta H = \frac{Q_m^2 P_m M_m}{K_m^2 T_m}$$

$$\Delta H_{@} = \frac{(.75 \text{cfm})^2 (29.92'' \text{ Hg}) (29.0)}{(460 + 68) K_m^2}$$

$$\Delta H_{@} = \frac{.9244}{K_m^2}$$

### SIMPLIFYING

$$\text{ASSUME } B_{wm} = 0$$

$$\text{LET } \Delta H_{@} = \frac{.9244}{(K_m)^2}$$

$$\text{AND } K_p = 85.49$$

### ISOKINETIC RATE EQUATION – WORKING FORM

$$\Delta H = \left\{ 846.72 D_n^4 \Delta H_{@} C_p^2 (1 - B_{ws})^2 \frac{M_d}{M_s} \frac{T_m}{T_s} \frac{P_s}{P_m} \right\} \Delta p$$

$$D_n = \sqrt{\left( \frac{.0358 Q_m P_m}{T_m C_p (1 - B_{ws})} \right) \sqrt{\frac{T_s M_s}{P_s (\Delta p)}}}$$

### NOZZLE DIAMETER SELECTION

## ISOKINETIC $\Delta H$ LECTURE PROBLEM

Given the following information use the isokinetic  $\Delta H$  equation to find a  $K$  factor for setting isokinetic rate through the sampling train:

$$Q_m = 0.75 \text{ CFM}$$

$$\Delta H_{@} = 1.85$$

$$\text{Pitot tube } C_p = 0.85$$

$$t_m = 80^\circ\text{F}$$

$$P_m = 30.0 \text{ in. Hg}$$

$$P_s = 29.6 \text{ in. Hg}$$

$$B_{wm} = 0$$


$$B_{ws} = 0.12$$

$$t_s = 280^\circ\text{F}$$


$$M_d = 29 \text{ lb/lb-mole}$$

$$\text{Average } \Delta p = 0.80 \text{ in. H}_2\text{O}$$

You will need to find  $M_s$  then solve the equations for nozzle diameter and  $K$ .



DRAW LINE FROM  $\Delta H_a$  TO  $t_m$  TO OBTAIN POINT A ON REF. 1.  
 DRAW LINE FROM POINT A TO  $\% H_2O$  AND READ B ON REF. 2.  
 DRAW LINE FROM POINT B TO  $P_s/P_m$ .





## SOURCE SAMPLING NOMOGRAPH CALIBRATION DATA

**Form A. Correct the C-Factor obtained in normal operation of the nomograph for  $C_p \neq 0.85$  by:**

$$\text{C-Factor (Adjusted)} = (\text{C-Factor Nomograph}) \frac{(\text{Pitot Tube } C_p)^2}{(0.85)^2}$$

Nomograph ID. No.	Nomograph C-Factor	Pitot $C_p$	$\frac{(C_p)^2}{(0.85)^2}$	Adjusted C-Factor

**Form B. Correct the Nomograph C-Factor for  $M_d \neq 29$  lb/lb-mole**

$$\text{C-Factor (Adjusted)} = (\text{C-Factor Nomograph}) \frac{1-B_{ws} + 18 B_{ws}/29}{1-B_{ws} + 18 B_{ws}/M_d}$$

Nomograph ID. No.	Nomograph C-Factor	Stack Gas Dry Molecular Weight ( $M_d$ )	Adjusted C-Factor

**Form C. Scale Alignment (Check all Nomographs)**

	Step 1	Step 2	Step 3		
	Set marker on and tighten pivot	Set one end of marker on	$\Delta H$ should read	Nomograph ID. No. _____ actual $\Delta H$ reading	Nomograph ID. No. _____ actual $\Delta H$ reading
Alignment Test 1	$\Delta H = 0.1$ $\Delta p = 0.001$	$\Delta p = 0.01$ $\Delta p = 0.1$	1.0 10.0		
Alignment Test 2	$\Delta H = 10.0$ $\Delta p = 10.0$	$\Delta p = 1.0$ $\Delta p = 0.1$	1.0 .1		
Alignment Test 3	$\Delta H = 1.0$ $\Delta p = 0.1$	$\Delta p = 1.0$ $\Delta p = 0.01$	10.0 .1		

**Form D. Nomograph Accuracy\***

Meter Console $\Delta H @$	Meter $t_m$ °F	Stack Gas $B_{ws} \times 100$	$P_s$	$P_m$	Stack $t_s$ °F	$\Delta p$	Nomograph C-Factor	Calculated Nozzle $D_n$	Nomograph $\Delta H$	Calculated $\Delta H$
1.84*	70	5	29.92	29.92	1000	1.00				
1.00	140	10	29.92	29.92	300	2.00				
2.00*	100	30	35.9	29.92	500	2.00				

\*Assume  $Q_m = 0.75$ ;  $C_p = 0.85$ ;  $B_{wm} = 0$ ;  $M_d = 29.0$

**Forms for source sampling nomograph calibration.**

Name \_\_\_\_\_

Nomograph No. \_\_\_\_\_

### Homework Problem Setting the Isokinetic Sampling Rate

This problem gives practice in obtaining the isokinetic sampling rate using two methods—the nomograph method and the calculation method. Using the data given in Table 1, fill in the boxes of Table 2 for problems 1, 2, and 3.

Note the following:

1. Assume  $B_{wm} = 0$  for all problems. Assume  $Q_m = .75$ .
2. In problem 3, correct the nomograph C factor for different  $C_p$  and for different  $M_d$ .
3. Remember that  $M_s = M_d(1 - B_{ws}) + 18 B_{ws}$ .
4. Equations for  $D_n$  and  $\Delta H$  are page 52 of the workbook.

#### Table 1

Problem Number	$\Delta H @$	$C_p$	$t_m$	$t_s$	$P_s$	$P_m$	$B_{ws}$	$M_d$	$\tilde{\Delta p}$
1.	1.84	.85	70	1000	29.92	29.92	.05	29.0	1.0
2.	1.00	.85	140	300	29.92	29.92	.10	29.0	2.0
3.	2.00	.80	100	500	29.70	31.9	.30	26.2	.75

#### Table 2

Problem Number	$M_s$	$D_n$ (calc.)	K (calc.)	C (nomo.)	$D_n$ (nomo.)	$\Delta H$ if $\Delta p = 1.0$ (nomo.)	$\Delta H$ if $\Delta p = 1.0$ (calc.)	$\Delta H$ if $\Delta p = 1.3$ (nomo.)	$\Delta H$ if $\Delta p = 1.3$ (calc.)	$\Delta H$ if $\Delta p = .8$ (nomo.)	$\Delta H$ if $\Delta p = .8$ (calc.)
1.											
2.											
3.											

Name \_\_\_\_\_

Nomograph No. \_\_\_\_\_

**HAND IN SHEET**  
**Homework Problem**  
**Setting the Isokinetic Sampling Rate**

This problem gives practice in obtaining the isokinetic sampling rate using two methods—the nomograph method and the calculation method. Using the data given in Table 1, fill in the boxes of Table 2 for problems 1, 2, and 3.

Note the following:

1. Assume  $B_{wm} = 0$  for all problems. Assume  $Q_m = .75$ .
2. In problem 3, correct the nomograph C factor for different  $C_p$  and for different  $M_d$ .
3. Remember that  $M_s = M_d(1 - B_{ws}) + 18 B_{ws}$ .
4. Equations for  $D_n$  and  $\Delta H$  are page 52 of the workbook.

**Table 1**

Problem Number	$\Delta H_{@}$	$C_p$	$t_m$	$t_s$	$P_s$	$P_m$	$B_{ws}$	$M_d$	$\tilde{\Delta p}$
1.	1.84	.85	70	1000	29.92	29.92	.05	29.0	1.0
2.	1.00	.85	140	300	29.92	29.92	.10	29.0	2.0
3.	2.00	.80	100	500	29.70	31.9	.30	26.2	.75

**Table 2**

Problem Number	$M_s$	$D_n$ (calc.)	K (calc.)	C (nomo.)	$D_n$ (nomo.)	$\Delta H$ if $\Delta p = 1.0$ (nomo.)	$\Delta H$ if $\Delta p = 1.0$ (calc.)	$\Delta H$ if $\Delta p = 1.3$ (nomo.)	$\Delta H$ if $\Delta p = 1.3$ (calc.)	$\Delta H$ if $\Delta p = .8$ (nomo.)	$\Delta H$ if $\Delta p = .8$ (calc.)
1.											
2.											
3.											

(To be handed in Wednesday morning)


# Lecture 7


## REVIEW OF REFERENCE METHODS 1-4

### Lesson Objectives:



The student will be able to:

- Fully describe and perform RM1 procedures.
- List all Federal Register requirements for pitot tube calibration, construction, and use.
- Describe RM4 procedures for moisture determination.
- Use RM4 equations for calculation of  $B_{ws}$ .
- List the procedures for RM3 gas analysis.
- Calculate and mathematically define.
  - a.  $M_d$
  - b.  $M_s$
  - c. %Excess air







**A. BOTTOM VIEW: SHOWING MINIMUM PITOT-NOZZLE SEPARATION**





or

**PROPER THERMOCOUPLE PLACEMENT TO MINIMIZE INTERFERENCE**





**CALIBRATION DUCT**

NOTES:



# **VELOCITY ERROR VS YAW ANGLE FOR AN S-TYPE PITOT TUBE**






## LABORATORY EXERCISE

### GAS ANALYSIS DETERMINATION FOR CARBON DIOXIDE, EXCESS AIR, AND DRY MOLECULAR WEIGHT

The orsat gas analyzer is used to determine the composition of the stack gas when  $\text{CO}_2$ ,  $\text{O}_2$ ,  $\text{CO}$ , and  $\text{N}_2$  are the principle gas constituents. An integrated Tedlar bag sample is taken of the stack gas and a known volume of the gas is analyzed in the orsat. The composition of the gas is determined on a percent by volume basis. This is accomplished by successive removal of  $\text{CO}_2$ ,  $\text{O}_2$ , and  $\text{CO}$  with  $\text{N}_2$  calculated by difference. The data are defined by Dalton's Law of Partial Pressure and the Ideal Gas Law as the mole fraction of each constituent gas. The vapor pressure of  $\text{H}_2\text{O}$  in the orsat analyzer is constant, therefore, all data are given on a dry basis. An outline of the procedure is presented here. Please read the Federal Register for complete understanding.

#### I. Integrated Bag Sample

- A. The sampling set up is diagrammed below. A sample rate proportional to the stack gas velocity is arbitrarily set, such that the evacuated bag will be approximately 2/3 full after the allotted sampling time.



B. This apparatus will be assembled for the student and be in operation.

1. Inspect all aspects of this apparatus for complete understanding.
2. Proceed to Orsat when bag is filled.

## II. Orsat Analysis

A. Level the analysis solutions to the mark on the analysis bottle using the burette leveling bottle.

1. Turn burette stopcock to vent and raise leveling bottle.
  - a. red burette solution (saturated  $\text{Na}_2\text{SO}_4$  with  $\text{H}_2\text{SO}_4$  to make it acidic and methyl orange indicator) will fill burette.
  - b. close the stopcock.
  - c. Crimp leveling bottle tubing with the palm of your hand.
2. Open burette stopcock and the stopcock of the  $\text{CO}_2$  bubbler bottle so that gas can enter each container.
  - a. Slowly release leveling bottle tubing crimp while lowering the bottle.
  - b. The  $\text{CO}_2$  absorbing solution (42% KOH) will rise in the bubbler.
  - c. Raise  $\text{CO}_2$  solution to the reference mark on the small diameter pipette very slowly (use the palm of your hand to make a tubing crimp as a regulator).  
Do not mix solutions.
  - d. Close stopcock to  $\text{CO}_2$  bubbler leave burette stopcock open to pipette gas to other bubblers.

3. Repeat procedure for other bubblers.
  - a.  $O_2$  (46% KOH and pyrogalllic acid)
  - b. CO (CuCl in solution with hydrogen and copper ions to prevent oxidation to  $Cu^{++}$   $Cl^-$ .)
- B. Leak test the burette and analysis bottles
  1. Close stopcocks after bringing analysis solutions in each bottle to reference mark.
  2. Level burette solution at mid-scale. Close stopcock and record reading.
  3. Allow analyzer to stand 4 minutes then note level of each solution.
  4. For any solution that has fallen from the mark, regrease the stopcock and check for location(s) of leak. Repeat leak test until analyzer holds marks for 4 minutes.
- C. Analyze gas sample
  1. Record all information on the Orsat Field Data Sheet
  2. Fill the burette with 100cc of gas from the integrated bag sample.
  3. Determine the percent by volume in the following sequence :  
 $CO_2$ ,  $O_2$ , CO.
    - a. Open the  $CO_2$  stopcock to the burette.
    - b. Let the gas mix by bubbling through the  $CO_2$  bottle three times using the leveling bottle to move the gas back and forth through the liquid.
    - c. Bring  $CO_2$  solution back to the reference mark and close the stopcock. Do not mix solutions.

- d. Read burette by leveling solution in burette and solution in leveling bottle (both at atmospheric pressure)
- e. Repeat 1 pass only to assure all  $\text{CO}_2$  has been scrubbed out and record the constant readings.
- f. Repeat all procedures for  $\text{O}_2$  ( $\approx 10$  passes) and  $\text{CO}$  ( $\approx 3$  passes)

# Dry molecular weight determination

Plant

Comments:

Date

Sampling time (24 hr clock)

Sampling location

Sample type (bag, integrated, continuous)

Analytical method

Ambient temperature

Operator

Run Gas	1 Reading		2 Reading		3 Reading		Average net Volume	Multiplier	Molecular weight of stack gas (dry basis) $M_d$ (lb/lb-mole)
	Actual	Net	Actual	Net	Actual	Net			
CO <sub>2</sub>								.44	
O <sub>2</sub> (net is actual O <sub>2</sub> reading minus actual CO <sub>2</sub> reading)								.32	
CO (net is actual CO reading minus actual O <sub>2</sub> reading)								.28	
N <sub>2</sub> (net is 100 minus actual CO reading)								.28	
Total									

$$M_d = .44(\%CO_2) + .32(\%O_2) + .28(\%CO + \%N_2)$$

# Lecture 8

## CALCULATION AND INTERPRETATION OF % ISOKINETIC

### Lesson Objectives:

The student will be able to:

- Locate the equations for %I in the Federal Register and in the course workbook.
- Explain how the %I expression is derived.
- Explain the relative importance of the variables in the %I expression and point out which ones should be closely checked on the source test report.
- Illustrate the effect of underisokinetic sampling on the measured pmr, relative to the true pmr.
- Illustrate the effect of overisokinetic sampling on the measured pmr, relative to the true pmr.
- Evaluate whether a source test should be rejected or accepted, based upon the value of the % isokinetic and whether the emission rate value is above or below the standard.

**DERIVATION  
of the  
ISOKINETIC  
VARIATION  
EQUATION**

$$\% \text{ Isokinetic Variation} = \frac{v_n}{v_s} \times 100$$

$v_n$  = velocity of gas through nozzle

$v_s$  = stack gas velocity

From the equation  
of continuity

$$v_n = \frac{Q_n}{A_n}$$

$Q_n$  FROM COLLECTED DATA

$$Q_n = \frac{V_{sw} + V_{\text{meter corrected}}}{\theta}$$

where  $\theta$  = SAMPLING TIME  
PERIOD

$$V_{\text{Orifice Corrected}} = \left( \frac{T_s}{P_s} \frac{(P_b + \frac{\Delta H}{13.6})}{T_m} \right) V_m$$



Correction of Metered Volume to Volume at Stack Conditions  
Correction for Water Collected in Impingers

$$V_{1c} \rho_{H_2O} = m_{H_2O}$$

$$P_s V_{sw} = \frac{m}{M} RT_s$$

$$\text{and } V_{sw} = m_{H_2O} \frac{RT_s}{M_{H_2O} P_s}$$

$$V_{sw} = V_{1c} \rho_{H_2O} \frac{RT_s}{M_{H_2O} P_s} = \text{The volume of water vapor at stack conditions}$$

SUBSTITUTING INTO  $Q_n$

$$Q_n = \frac{T_s}{P_s} \left[ V_{1c} K_3 + \frac{V_m}{T_m} \left( P_b + \frac{\Delta H}{13.6} \right) \right]$$

$\theta$

WHERE  $K_3 = \frac{\rho_{H_2O} R}{M_{H_2O}} = .00267 \frac{\text{in Hg ft}^3}{\text{ml } ^\circ R}$

**DERIVATION OF % I**

$$\% I = \frac{v_n}{v_s} 100 = \frac{Q_n}{v_s A_n} 100$$

**SUBSTITUTING,**

$$\% I = \frac{\frac{T_s}{P_s} \left[ K_3 V_{1c} + \frac{V_m}{T_m} \left( P_b + \frac{\Delta H}{13.6} \right) \right]}{A_n \theta v_s} 100$$

**% I FR EXPRESSION**


$$\% I = \frac{100 T_s \left[ V_{1c} K_3 + \frac{V_m}{T_m} \left( P_b + \frac{\Delta H}{13.6} \right) \right]}{60 \theta v_s P_s A_n}$$

% I FR Expression  
from intermediate data

$$\% I = K_4 \frac{T_s V_m(\text{std})}{P_s v_s A_n \theta (1-B_{ws})}$$

K = 0.09450  
for English units

$$\overline{pmr}_s = \frac{m_n}{V_n} A_s \bar{v}_s$$



# **Lecture 9**





## **SAMPLING TRAIN CONFIGURATION: DEFINITION OF A PARTICULATE**

### **Lesson Objectives:**

The student will be able to:

- Write the Federal Register definition of a particulate given in the NSPS regulations.
- Describe the sampling train parameters effecting the definition of a particulate.
- Define “particulate” for the sampling train configurations given on page 78 of the workbook.

# Sampling Train Configurations



# Lecture 10

## DISCUSSION OF SOURCE SAMPLING EXERCISE


### Lesson Objectives:


The student will be able to:

- List the steps involved in designing a stack test.
- List the information necessary in a pre-survey of the stack test site.
- Recall the planning steps for a stack test.
- Recall a usable report writing format.
- Describe the basic procedures for performing an EPA Method 5 test including filling out data forms and making calculations.

...

## Planning and performing a stack test.







## I. PRELIMINARY MEASUREMENTS AND SETUP OF THE SAMPLING TRAIN

Using the data collected during the Monday afternoon lab session, determine the following parameters:

- Determination of equivalent diameter and traverse points
- Stack gas velocity and volumetric flow rate
- Moisture content of flue gas
- Stack gas temperature and molecular weight

The above parameters must be determined in order to pick the correct nozzle size and to set the nomograph. Incorrect selection of nozzle size may result in not being able to maintain isokinetic sampling rate, thereby voiding the sample.

## II. SAMPLING

The on-site sampling includes making a final selection of proper nozzle size, setting the nomograph or calculator, making an initial leak-check, inserting the probe into the stack, sealing the port, sampling isokinetically while traversing, recording the data and making a final leak-check of the sampling system.

However, due to the sampling port locations in the test section, cooperation is required with the group directly located across from your own test port. Referring back to Figure 3, we see that ports 1 and 2 of each module lie on the same centerline. Thus, in order for a traverse to be done without interfering with one another, the group located at port 1 should start their traverse with the first traverse point closest to the facility inside wall. Simultaneously, the group located at port 2 should start with the furthestest traverse point from the inside wall. Thus, while one group is traversing toward the opposite wall, the other group is returning to that wall.

### III. SOURCE TEST

Good organization of the sampling team will make the source test much easier, save time and improve the quality of the data. Each sample team member should have a specific task at the site. The flow chart provided is a brief outline of procedures. The entire experiment is outlined in the two-part flow chart you have received. The procedures involved are described below.

#### Description of Procedures

##### A. Assemble the Sampling Train

###### 1. Inspect the sampling nozzle

- The nozzle should be perfectly round and of uniform diameter throughout. Any out-of-round nozzles should be rounded or replaced.
- The round nozzle diameter should be precisely measured with a micrometer to three decimal places.

###### 2. Inspect the sampling probe\*

- Remove swagelock union and determine the presence of asbestos string ( $T_s > 350^\circ\text{F}$ ) or rubber o-ring seals and a compression seal spacer.
- Inspect the end of the probe glass liner for cracks and chips.
- Make certain a small diameter hole is drilled in the probe sheath (allows pressure equalization)
- Remove the liner and check the glass liner heater connections for frayed wires.
- Inspect the condition, alignment, and attachment of the pitot tube.
- Reassemble and position in sample case.

\*NOTE: These steps have already been done for you. They are included here for you to follow when you are on your own.

### 3. Sample Case

- Check the thermometers
- Inspect the electrical connections for the umbilical cord, probe, and filter heater.
- Be certain the sampling probe attachment is in proper order for the sampling.
- Close ice compartment drain plug.

### 4. Glassware\*

- Be sure the glass impingers are clean
- Grease all joint surfaces-for the ball joint type glassware - inspecting all pieces for cracks or chips.
- Fill the impingers:
  1. Measure 100 ml of distilled water into each of the first two impingers.
  2. The third impinger is left empty.
  3. Place approximately 200 g of preweighted indicating silica gel into the fourth impinger.

The first, third and fourth impingers are modified Greenburg-Smith while the second impinger is a standard Greenburg-Smith design. Place the impingers into the sampling box and assemble the sampling train using the appropriate U-tubes.


\*NOTE: These steps have been done prior to laboratory exercise.

### 5. Load Filter

- The preweighed filter is removed from its sealed container and placed in the filter holder. Make sure that the filter is centered correctly in the holder with the sample side toward the probe. The filter holder should be tightened until the two halves are secure.
- Attach the probe to the filter holder, being sure not to apply excessive torque to the glass components.

## B. Leak Test the Assembled Sampling Train

1. Test the completely assembled sampling train at 15in. on the Vacuum Gage.
  - Be certain the valves on the RAC Meter Console are "out"
  - Turn on the console pump
  - Turn on probe heater and filter box temperature switches, allow to reach operating temperature.
  - Turn fine adjust valve fully counter-clockwise
  - Seal nozzle opening with duct tape or rubber stopper
  - Open coarse adjust valve slowly until fully counter-clockwise
  - Slowly turn fine adjust valve clockwise until vacuum reaches 15" Hg. on gage. If you over shoot 15" Hg. do not turn fine adjust valve back, simply read and record at vacuum on gage.



- Note DGM dial pointer. If the pointer does not move for 15 seconds the leak test is good. If it continues to move, time the leak using a stopwatch. 0.02CFM is the maximum acceptable leak rate
  - Any leak greater than 0.02CFM must be prevented.
  - Slowly release vacuum at the nozzle before closing coarse adjust valve.
2. Track down any leaks by successive back tracking leak checks-- Disconnect filter and test the system back from the first impinger, etc.
  3. Record the leak rate

C. Calculate Sampling Points on Traverse Following Method 1 Guidelines and Mark Probe From Center of Pitot Orifice Back to Sample Case.

Set up nomograph and calculators.

1. Use the data from the Monday laboratory for stack temperature and average  $\Delta p$ .
2. Each laboratory group is to set up at least one calculator and at least one nomograph in order to obtain  $\Delta H$  values.

D. Fill Out Data Sheets

1. Label time intervals for each sampling point
2. Record the initial DGM reading
3. Fill out all data blanks

E. Isokinetic Sampling

1. Place ice in the condenser section of the sampling train. Turn on the probe heater and filter box temperature switches. Check to insure proper operation. Allow to reach operating temperature.
2. Fill out the appropriate information on the "Particulate Data" sheet. This should include date, time, test time at each point and DGM reading. Once all information has been recorded, the test can begin.
3. Move the sampling train to the first traverse point with the nozzle pointing directly into the gas stream. Seal the port and immediately start the pump, noting time and DGM reading.
  - Determine and calculate the proper  $\Delta H$  using the calculator or nomograph. Check to see that the nomograph and calculator values agree.
  - Adjust  $\Delta H$  using coarse and fine valve.
  - Maintain isokinetic conditions during the entire sampling period by observing  $\Delta p$  and setting  $\Delta H$  through the use of the nomograph or calculator. Adjust the sampling rate at each traverse point by adjusting the coarse and fine valves. When significant changes in stack conditions are observed, compensating adjustments in flow rate should be made. Three conditions would account for realigning nomograph or calculator:

1. Stack gas temperature varies by more than 25°F.
  2.  $t_m$  (average temperature of meter) varies by more than 11°F.
  3. Significant changes in moisture content ( $B_{ws}$ ).
- At each traverse point, the following information should be observed and recorded on the field data sheet: stack temperature ( $t_s$ ), velocity pressure head ( $\Delta p$ ), orifice pressure differential ( $\Delta H$ ), gas temperature at dry gas meter ( $t_{m_{avg}}$ ), sample box temperature, condenser temperature and probe temperature. The time period at each traverse point must be long enough to obtain a total sampling period representative of the process being monitored. The time at each traverse point must be sufficient to obtain a total sample volume of at least 30 DSCF.

Fifteen seconds before the end of sampling at the first traverse point, move the probe and sample container assembly to the next point. Allow a short time period to stabilize the  $\Delta p$  reading. Adjust  $\Delta H$  to the corresponding isokinetic rate and record on data sheet. Repeat this procedure for each additional traverse point.

#### F. Test Completion

1. At the completion of the test, close the coarse control valve on the meter, remove the probe from the stack and turn off the pump. Remove the probe carefully from the stack to insure that the nozzle does not scrape dust from the inside of the port. Seal the port. Keep the probe elevated to insure loss of sample does not occur. Record all proper information on the field log sheet. This should include final DGM reading, stop time, probe temperature and meter box temperature.
2. Perform a post leak check on the sample train following the same procedure as in the pretest. Record final leak rate on data sheet.

#### G. Sample Recovery

1. Disassemble sampling train
  - Disassemble filter holder and seal until ready to clean
  - When probe has reached ambient temperature, seal at both ends until ready to clean.

#### IV. ANALYTICAL RECOVERY

During sample recovery, care must be taken to prevent loss or contamination of the sample.

- Filter Holder - Care must be taken when removing the filter from its holder. Be sure that extraneous dirt does not become a part of the sampling run. Place the filter into its original container, seal, label and record filter number on the data sheet.
- Silica Gel - Transfer the silica gel from the fourth impinger to its original preweighed container. The use of a funnel to transfer the silica gel would be most helpful. Once it has been transferred, label and seal properly.
- Condenser - Measure the total volume of condensation (+ 1 ml) transferring the contents of the first three impingers into a graduated cylinder. Record on the data log sheet.
- Acetone Wash-Front Half - Wash all internal surfaces of the sampling train from the nozzle tip up to the backside of the filter holder with acetone. Determine the volume to the nearest ml and transfer to a labeled container. A brush with a handle as long as the probe may be used to dislodge particulate matter from the inside of the probe. Include this with the acetone washings.

#### V. ANALYTICAL ANALYSIS

Record the necessary data on the "Laboratory Analysis Data" sheet concerning sample identification and sample integrity. Proper procedure indicates desiccating both for 24 hours in a desiccator, then weighing to a constant weight. However, the time period for this course is restrictive, therefore, weigh the filter without desiccating. For proper analysis, please refer to The Federal Register, Vol. 42, No. 160, August 18, 1977.

- Silica Gel - Weigh the spent silica gel to the nearest 0.5g using a balance. Record the final weight on the "Data" sheet.
- Filter - Weight the filter to the nearest 0.1 mg using a balance. Record the final weight on the "Data sheet".
- Probe Wash - Submit your probe wash to the instructor. He will evaporate the sample and have it weighed for you. The data will be supplied to you Thursday morning.

## VI. CALCULATIONS

Complete the "Source Test Data Summary" worksheet found in the workbook. This should include information obtained during Monday's and Wednesday's laboratory sessions.

Note: It will be necessary to defer the calculation of  $C_s$ , pmr, and E, the Emission Rate, until after you have received the weight of the particulate contribution from the nozzle and probe. The instructor will provide this data to you Thursday morning.



*Very Important—Fill in all Blanks*

Fyrite no. \_\_\_\_\_ Date rebuilt \_\_\_\_\_

 $\Delta p_{avg}$ , in. H<sub>2</sub>O \_\_\_\_\_

Leak rate@15 in. Hg Pre-test\_\_\_\_\_ Post-test\_\_\_\_\_

[illegible]

Comments: \_\_\_\_\_

Test observers: \_\_\_\_\_

*continued*

[illegible]

Comments: \_\_\_\_\_

Test observers: \_\_\_\_\_

Name \_\_\_\_\_  
Group No. \_\_\_\_\_

### SOURCE TEST DATA SUMMARY

1. Total number of sampling points \_\_\_\_\_
2. Total test time \_\_\_\_\_ minutes
3. Stack cross-sectional area \_\_\_\_\_ sq. ft.
4. Orsat analysis  
    %CO<sub>2</sub> \_\_\_\_\_  
    %O<sub>2</sub> \_\_\_\_\_  
    %N<sub>2</sub> \_\_\_\_\_  
    B<sub>ws</sub> \_\_\_\_\_  
    M<sub>d</sub> \_\_\_\_\_ lb/lb-mole  
    M<sub>s</sub> \_\_\_\_\_ lb/lb-mole
5. Average stack gas temperature \_\_\_\_\_ °F + 460 = \_\_\_\_\_ °R
6. Barometric pressure (P<sub>b</sub>) \_\_\_\_\_ in. Hg
7. Absolute stack pressure (P<sub>s</sub>) \_\_\_\_\_ in. Hg
8. Stack gas velocity data  
    Pitot tube C<sub>p</sub> = \_\_\_\_\_  
    Average Δp \_\_\_\_\_ in. H<sub>2</sub>O  
    Average velocity (v<sub>s</sub>) \_\_\_\_\_ ft/sec
9. Average stack gas dry standard volumetric flow rate (Q<sub>s</sub>) \_\_\_\_\_ DSCFH
10. Sampling nozzle diameter \_\_\_\_\_ inches
11. Particulate catch weight \_\_\_\_\_ mg
12. Meter console volume  
    Volume metered (V<sub>m</sub>) \_\_\_\_\_ CF  
    Standard volume metered (V<sub>mstd</sub>) \_\_\_\_\_ DSCF
13. Particulate concentration (c<sub>s</sub>) \_\_\_\_\_ grains/ DSCF
14. %Isokinetic \_\_\_\_\_
15. Pollutant mass rate at standard conditions \_\_\_\_\_ lb/hr
16. Emission rate \_\_\_\_\_ lb/10<sup>6</sup>Btu  
    (Use F-factor for propane)


Name \_\_\_\_\_

Group No. \_\_\_\_\_

### SOURCE TEST DATA SUMMARY

1. Total number of sampling points \_\_\_\_\_
2. Total test time \_\_\_\_\_ minutes
3. Stack cross-sectional area \_\_\_\_\_ sq. ft.
4. Orsat analysis
  - %CO<sub>2</sub> \_\_\_\_\_
  - %O<sub>2</sub> \_\_\_\_\_
  - %N<sub>2</sub> \_\_\_\_\_
  - B<sub>ws</sub> \_\_\_\_\_
  - M<sub>d</sub> \_\_\_\_\_ lb/lb-mole
  - M<sub>s</sub> \_\_\_\_\_ lb/lb-mole
5. Average stack gas temperature \_\_\_\_\_ °F + 460 = \_\_\_\_\_ °R
6. Barometric pressure (P<sub>b</sub>) \_\_\_\_\_ in. Hg
7. Absolute stack pressure (P<sub>s</sub>) \_\_\_\_\_ in. Hg
8. Stack gas velocity data
  - Pitot tube C<sub>p</sub> = \_\_\_\_\_
  - Average Δp \_\_\_\_\_ in. H<sub>2</sub>O
  - Average velocity (v<sub>s</sub>) \_\_\_\_\_ ft/sec
9. Average stack gas dry standard volumetric flow rate (Q<sub>s</sub>) \_\_\_\_\_ DSCFH
10. Sampling nozzle diameter \_\_\_\_\_ inches
11. Particulate catch weight \_\_\_\_\_ mg
12. Meter console volume
  - Volume metered (V<sub>m</sub>) \_\_\_\_\_ CF
  - Standard volume metered (V<sub>mstd</sub>) \_\_\_\_\_ DSCF
13. Particulate concentration (c<sub>s</sub>) \_\_\_\_\_ grains/ DSCF
14. %Isokinetic \_\_\_\_\_
15. Pollutant mass rate at standard conditions \_\_\_\_\_ lb/hr
16. Emission rate \_\_\_\_\_ lb/10<sup>6</sup>Btu  
(Use F-factor for propane)

# Source test outline.



# Lecture 11

## CONCENTRATION CORRECTION AND PROBLEM SESSION

### Lesson Objectives:

The student will be able to:

- Discuss the relationships that exist in fossil fuel-fired boilers between excess air, % O<sub>2</sub>, and % CO<sub>2</sub>.
- Define excess air.
- Correct a particulate concentration to standard temperature and pressure.
- Correct a particulate concentration to 50% excess air using two methods.
- Correct a particulate concentration to 12% CO<sub>2</sub>.
- Correct a particulate concentration to 6% O<sub>2</sub>.

## I. CONCENTRATION CORRECTION

### CONCENTRATION CORRECTION

$$c_{s_{\text{corr}}} = c_s \frac{P_{\text{std}} T_s}{P_s T_{\text{std}}}$$

### % EXCESS AIR

$$\% \text{ EA.} = \frac{\text{Volume Excess Air}}{\text{Theoretical Volume required for complete combustion}} \times 100$$

$$\% \text{ EA.} = \frac{\% \text{ O}_2 - .5(\% \text{ CO})}{.264(\% \text{ N}_2) - [\% \text{ O}_2 - .5(\% \text{ CO})]} \times 100$$

### 50% Excess Air Correction for $C_s$

Given % EA

$$c_{s50} = \frac{c_s [100 + \% \text{ EA}]}{150}$$

### 50% Excess Air Correction from Orsat Data

$$c_{s50} = \frac{c_s}{1 - \left[ \frac{1.5(\%O_2) - .133(\%N_2) - .75(\%CO)}{21} \right]}$$

### CORRECTING CONCENTRATION to 12% CO<sub>2</sub>

$$c_{s12} = c_s \frac{12}{\%CO_2}$$

### CORRECTING CONCENTRATION TO 6% OXYGEN

$$c_{s6\%O_2} = \frac{c_s (20.9 - 6.0)}{20.9 - \%O_2}$$



## II. PROBLEM SESSION

Several problems are presented to help in understanding the use of these concentration corrections and give you practice. Examples of the calculations are given in Problem I.

### Problem I

Source tests were performed at a facility burning residual oil on two different occasions. The fuel feed rate was 10 gallons oil/Hr. for both tests, however, the % Excess Air varied to insure good combustion. Given the following Test data calculate the corrected pollutant concentration in grains (gr /ft <sup>3</sup>) for each condition shown in the table provided.

Test Number	% EA	Orsat Analysis				Q <sub>S</sub> DSCF/min	PMR gr /min	c <sub>S</sub> gr /DSCF	C̄ <sub>S12</sub>	C <sub>B50</sub>	
		%CO <sub>2</sub>	%O <sub>2</sub>	%CO	%N <sub>2</sub>					From	
										% EA	Raw Orsat Data
1A	10	13.3	2.2	0	84.5	14,300	10,000				
1B		9.7	7.1	0.2	83.0	19,400	10,000				

### Example Calculations

#### Test Number 1A

1. Average pollutant concentration (c<sub>S</sub>)

$$c_S = \frac{PMR}{\bar{Q}_S} = \frac{1 \times 10^4 \text{ gr /min}}{1.43 \times 10^4 \text{ DSCF/min}} = 0.699 \text{ gr /DSCF}$$

2. Average pollutant concentration corrected to 12% CO<sub>2</sub> in duct gas

$$(c_{s12})$$

$$c_{s12} = c_s \frac{12}{\%CO_2} = 0.699 \text{ gr /DSCF} \frac{12}{13.3} = 0.631 \text{ gr /DSCF}$$

3. Average pollutant concentration corrected to 50% EA ( $c_{s50}$ )

a. Using known % EA

$$c_{s50} = c_s \frac{100 + \% EA}{150} = 0.699 \text{ gr /DSCF} \frac{100 + 10}{150} = 0.513 \text{ gr /DSCF}$$

b. Using raw orsat data

$$c_{s50} = \frac{c_s}{1 - \frac{1.5(\%O_2) - 0.133(\%N_2) - 0.75(\%CO)}{21}}$$

$$c_{s50} = \frac{0.699 \text{ gr /DSCF}}{1 - \frac{1.5(2.2) - 0.133(84.3) - 0.75(0)}{21}} = 0.507 \text{ gr /DSCF}$$

Record the data calculated in the examples then calculate concentrations for Test 1B.

### Problem II

A coal fired boiler burns coal at a rate of 100 lb/Hr. Two source tests at the facility yielded the following data. Make all calculations and complete the Table.

Test Number	Z EA	Orsat Analysis				Q <sub>g</sub> DSCF/min	PMR gr /min	C <sub>g</sub> gr /DSCF	C̄ <sub>g12</sub>	C <sub>g50</sub>	
		ZCO <sub>2</sub>	ZO <sub>2</sub>	ZCO	ZN <sub>2</sub>					From	
										Z EA	Raw Orsat Data
2A		12.1	7.1	0.3	80.5	18,000	13,000				
2B	100	9.1	10.6	0.8	80.3	24,000	13,000				

# **Lecture 12**

## **LITERATURE SOURCES**

### **Lesson Objectives:**

The student will be able to:

- Recall at least three types of sources from which information on source sampling methodology may be found (books, periodicals, newsletters, EPA publications).
- List the most important periodicals and professional organizations that transmit source sampling information.
- Tell how to receive assistance in obtaining EPA publications; and computerized literature searches.

# **LITERATURE SOURCES**

## **A. Books**

## **B. Periodicals**

**C. EPA Publications**

**D. Newsletters**

**E. Others.**

# **Lecture 13**

## **THE F-FACTOR METHOD**

### **Lesson Objectives:**

The student will be able to:

- Define the F-factor used in EPA Method 5 calculations.
- Discuss how the F-factor can give a value for the emission rate.
- Describe the requirements for using the F-factor in the EPA Method 5 test for new FFFSGs.
- Recall alternate F-factor methods.
- Use F-factors for cross-checking Orsat and combustion data.

$$F_d = \frac{\text{Volume of theoretical dry combustion product burned/lb}}{10^6 \text{ Btu/lb Heating value of fuel combusted}}$$

$$E = c_s F_d \left[ \frac{20.9}{20.9 - \% O_2} \right]$$

#### F FACTORS FOR VARIOUS FUELS

<u>FUEL TYPE</u>	<u><math>F_d</math> dscf/10<sup>6</sup>Btu</u>	<u><math>F_c</math> scf/10<sup>6</sup>Btu</u>	<u><math>F_w</math> wscf/10<sup>6</sup>Btu</u>	<u><math>F_o</math></u>
BITUMINOUS COAL	9820	1810	10680	1.140
OIL	9220	1430	10360	1.3461
NATURAL GAS	8740	1040	10650	1.79
WOOD	9280	1840	—	1.5

$$F_c = \frac{\text{Volume of theoretical CO}_2 \text{ generated by combustion / lb}}{10^6 \text{ Btu/lb heating value of fuel combusted}}$$

### **F<sub>c</sub> FACTOR METHOD**

$$E = c_s F_c \left( \frac{100}{\% \text{CO}_2} \right)$$

### **Alternate F Factor Method using wet basis data**

$$E = c_{ws} F_d \left[ \frac{20.9}{20.9 (1 - B_{ws}) - \%O_{2w}} \right]$$

**B<sub>ws</sub>** = fractional moisture content  
of stack gas

### **Wet F Factor Method**

$$E = c_{ws} F_w \left[ \frac{20.9}{20.9 (1 - B_{wa}) - \%O_{2w}} \right]$$

**B<sub>wa</sub>** = fractional moisture content  
in air



### Use of F factors for cross checks

$$F_{d(\text{calc})} = \frac{Q_{sd}}{Q_H} \left( \frac{20.9 - \% O_2}{20.9} \right)$$

$$F_{w(\text{calc})} = \frac{Q_{sw}}{Q_H} \left[ \frac{20.9(1 - B_{wa}) - \% O_{2w}}{20.9} \right]$$

$$F_{c(\text{calc})} = \frac{Q_{sw}}{Q_H} \left( \frac{\% CO_{2w}}{100} \right)$$

$F_O$  factor

$$F_O = \frac{20.9 F_d}{100 F_c}$$

$$F_O = \frac{20.9 - \% O_{2d}}{\% CO_{2d}}$$

### Correcting for Incomplete Combustion

$$(\% CO_2)_{\text{adj}} = \% CO_2 + \% CO$$

$$(\% O_2)_{\text{adj}} = \% O_2 - .5(\% CO)$$

# **Lecture 14**

## **CALCULATION REVIEW**

### **Lesson Objectives:**

The student will be able to:

- List the clean-up procedures for the RM5 sampling train.
- Make all calculations for an RM5 stack test.
- Distinguish the difference between sampling precision and sampling accuracy.
- Answer all questions on the pre-test.

### Class Data Summary

Group	No. sample pt.	Time min.	A <sub>s</sub> ft <sup>2</sup>	A <sub>n</sub> ft <sup>2</sup>	B <sub>ws</sub>	M <sub>s</sub> lb/lb-mole	P <sub>s</sub> in. Hg	v <sub>s</sub> ft/sec	Q <sub>s</sub> DSCFH	V <sub>m</sub> std	%I	c <sub>s</sub> gr/ft <sup>3</sup>	PMR lb/hr	E lbs/ 10 <sup>6</sup> Btu
1														
2														
3														
4														
5														
6														
7														
8														

# **Lecture 15**


## **ERROR ANALYSIS**

### **Lesson Objectives:**

The student will be able to:

- Explain the difference between precision and accuracy.
- List and describe three categories of error. (systematic, random, illegitimate)
- Discuss the relative precision of EPA reference methods 2-5.
- Use the concepts of this lecture and not misapply the terminology in discussions of source sampling results.


# ERROR ANALYSIS




## PRECISION AND ACCURACY

*Precision refers to  
Reproducibility*

*Accuracy refers to  
Correctness*



**A** PRECISION IS GOOD  
BUT ACCURACY IS POOR



**B** BOTH PRECISION AND  
ACCURACY ARE GOOD

- 1 SYSTEMATIC ERRORS
- 2 RANDOM ERRORS
- 3 ILLEGITIMATE ERRORS

# **Lecture 16**

## **SOURCE SAMPLING QUALITY ASSURANCE AND SAFETY ON SITE**

### **Lesson Objectives:**

The student will be able to:

- Recall the important aspects of an accident analysis program.
- List the 10 causes of accidents.
- List some personal safety equipment for a source sampler.
- List the important items necessary to assure good quality test data.

## QUALITY ASSURANCE CHECK LIST

1. \_\_\_\_\_
2. \_\_\_\_\_
3. \_\_\_\_\_
4. \_\_\_\_\_
5. \_\_\_\_\_
6. \_\_\_\_\_
7. \_\_\_\_\_
8. \_\_\_\_\_
9. \_\_\_\_\_
10. \_\_\_\_\_
11. \_\_\_\_\_
12. \_\_\_\_\_
13. \_\_\_\_\_
14. \_\_\_\_\_
15. \_\_\_\_\_
16. \_\_\_\_\_
17. \_\_\_\_\_
18. \_\_\_\_\_
19. \_\_\_\_\_
20. \_\_\_\_\_

## **CAUSES OF ACCIDENTS**

1. Poor instructions
2. Poor planning
3. Improper design
4. Proper equipment not provided
5. Failure to follow instructions
6. Neglect or improper use of equipment
7. Faulty equipment
8. Untrained personnel
9. Uncooperative personnel
10. Unpredictable outside agents



# Lecture 17

## PARTICULATE SIZING USING A CASCADE IMPACTOR


### Lesson Objectives:

The student will be able to:

- Describe the equation of continuity for a flowing ideal fluid.
- List several particle properties and give the most important property.
- Define effective particle size.
- Define particle aerodynamic diameter.
- Describe the relationship between particle diameter and its physical properties.
- List several methods of determining particle diameter other than inertial sizing.
- Recognize the importance of a cascade impactor.
- Define the  $D_{50}$  for an impactor collection stage.
- Describe the sampling procedures used for an in-stack cascade impactor.

## NOTES:

## INERTIAL PARTICLE COLLECTOR




# Lecture 18

## TRANSMISSOMETERS

### Lesson Objectives:

The student will be able to:

- Define the terms opacity, transmittance, and transmissometer.
- Express the relationship between opacity and transmittance.
- Recognize the proper expression for optical density.
- Discuss the EPA requirements for the design and performance of transmissometers placed on sources regulated by NSPS.
- Define the meaning of photopic and give at least two reasons why light in the photopic region is to be used in transmissometer design.
- Explain that optical density is proportional to grain loading and discuss the advantages and limitations of correlating optical density to grain loading.
- List several uses of opacity monitors.



**OPACITY** IS THE PERCENTAGE OF  
VISIBLE LIGHT ATTENUATED DUE TO  
THE ABSORPTION AND SCATTERING OF  
LIGHT BY PARTICULATE MATTER IN  
FLUE GAS.

$$\underline{\underline{\% \text{ OPACITY} = 100\% - \% \text{ TRANSMITTANCE}}}$$

#### BEER BOUGERT RELATIONSHIP

$$T = e^{-naql}$$

$T$  = Fraction of light transmitted  
(Transmittance)

$q$  = Particle extinction coefficient

$n$  = Number of particles  
per unit volume


$l$  = Length of effluent path


$a$  = Mean particle projected area

$e$  = Base of natural logarithm

$$\text{Optical Density} = \log_{10} \frac{1}{1 - \text{Opacity}}$$

- Optical density is a measure of the ability of an aerosol to attenuate light.
- Optical density is proportional to both path length and particulate concentration.





#### VENDORS OF SINGLE – PASS TRANSMISSOMETERS

Cost Range \$800 - \$ 4,000

Bailey Meter

Cleveland Controls, Inc.

De - Tec - Tronic Corp.

Reliance Instrument Manufacturing

HABCO

Leeds & Northrop

Photomation, Inc.

Preferred Utilities Manufacturing

Electronics Corp. of America

Robert H. Wagner

#### VENDORS OF DOUBLE – PASS TRANSMISSOMETERS

Cost Range \$8,000 – \$ 16,000

Environmental Data Corp.

Research Appliance Co.

Dynatron Inc.

Esterline Angus

Lear Siegler



Contraves - Goerz Corp.

Datatest, Inc.

Anderson - 2000


# OPACITY MONITOR SPECIFICATIONS

SPECTRAL RESPONSE ——— PHOTOPIC  
 ANGLE OF VIEW ——— 5%  
 ANGLE OF PROJECTION ——— 5%  
 CALIBRATION ERROR ——— < 3% OPACITY







## PARTICLE SIZE EFFECTS



## ANGLE OF PROJECTION







## TRANSMISSOMETER APPLICATIONS

1. Installation to satisfy EPA continuous opacity monitoring requirements.
2. Installation for process performance data - - maintenance and repair indicator, process improvement
3. Installation for control equipment operation - - ESP tuning, broken bag detector.
4. Correlation with particulate concentration.
5. Maintenance of a continuous emissions record.

**LIGNITE  
FIRED  
BOILER  
EMISSIONS**  
  
(standard  
conditions)




# CEMENT KILN EMISSIONS



# BITUMINOUS COAL FIRED BOILER EMISSIONS

(standard  
conditions)



# Appendix

# **Appendix A**

## **Sample Data Sheets**

## METHOD 5—SOURCE TEST DATA SHEETS

### Preliminary Survey—Source Sampling Site

Date \_\_\_\_\_ Survey investigator \_\_\_\_\_

Plant name \_\_\_\_\_ City \_\_\_\_\_ State \_\_\_\_\_

Previous test(s) by: \_\_\_\_\_ Reports available \_\_\_\_\_

Plant contacts \_\_\_\_\_ Title \_\_\_\_\_ Phone \_\_\_\_\_

\_\_\_\_\_ Title \_\_\_\_\_ Phone \_\_\_\_\_

\_\_\_\_\_ Title \_\_\_\_\_ Phone \_\_\_\_\_

Complete directions to plant from point of origin \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Local accommodations: nearest motel \_\_\_\_\_ miles

Restaurants \_\_\_\_\_

Nearest hospital \_\_\_\_\_ Phone \_\_\_\_\_

Rental cars and vans available \_\_\_\_\_

### Plant Operation and Process Description

Description of process \_\_\_\_\_

\_\_\_\_\_

Description of control equipment \_\_\_\_\_

\_\_\_\_\_

### Schematic Drawing of Process Operation (Note location of sampling)

Sites and control equipment:

Sampling sites	Anticipated constituents of stack gas
1. _____	_____
2. _____	_____
3. _____	_____
4. _____	_____
5. _____	_____

Process fuel type(s) \_\_\_\_\_ Feed rate \_\_\_\_\_  
 Process raw material(s) \_\_\_\_\_ Consumption rate(s) \_\_\_\_\_  
 Process production rate(s) \_\_\_\_\_  
 Samples to be taken of: \_\_\_\_\_  
 Plant operation: Continuous \_\_\_\_\_ Batch \_\_\_\_\_  
 Shift changes and breaks \_\_\_\_\_  
 Plant facilities: Entrance requirements \_\_\_\_\_ Food \_\_\_\_\_ Restrooms \_\_\_\_\_  
 First aid \_\_\_\_\_ Safety equipment \_\_\_\_\_ Compressed air source \_\_\_\_\_  
 Laboratory \_\_\_\_\_ Equipment available \_\_\_\_\_  
 Reagents \_\_\_\_\_ Ice \_\_\_\_\_

### Sampling Site and Stack Information

Sampling site	Type Pollutant emissions	Duct dimensions	Duct construction material	No. of sample ports	Port dimension	Diameters straight run to ports	Duct gas temp. °F	Duct gas velocity ft /sec	Average $\Delta p$ in. H <sub>2</sub> O in duct	% $\Delta p$ in gas	Stack pressure in. Hg

Sketch of duct to be sampled with port locations and all dimensions

**Sketch of sampling site including all dimensions**

Access to work area	Work area (locate electrical outlets)
Electrical outlets available _____ 1. Voltage _____ 2. Extension cords needed, _____ ft 3. Adapters _____	

Recommended modifications to sampling site \_\_\_\_\_

Sampling method suggested \_\_\_\_\_

Equipment needed: Sample probe length \_\_\_\_\_ Nozzles \_\_\_\_\_

Glassware \_\_\_\_\_ Sample case: Horizontal traverse \_\_\_\_\_ Vertical \_\_\_\_\_

No. of needed sample cases \_\_\_\_\_ Meter consoles \_\_\_\_\_ Probes \_\_\_\_\_ Filter assemblies \_\_\_\_\_

Special equipment: \_\_\_\_\_

Reagents needed \_\_\_\_\_

**Safety at Site**

Condition descrip- tion	Sampling site(s) general	Ladders	Scaffolds	Platforms	Lighting	Ventila- tion	Chemical hazard protection	Warning system
Good								
Adequate								
Poor								
Intolerable								



### Personnel Safety Equipment

Item	Safety glasses	Full face shields	Hard hats	Safety shoes	Safety belts	Hearing protection	Respiratory equipment			Fire extinguishers	Chemical protection garments	Heat protecting garments	Asbestos aprons, gloves
							Purifying type	Self contained	Air supplied				
Needed at site													
Available at plant													
Must be brought by sample team													

Description of additional safety equipment recommended: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Comments: \_\_\_\_\_

\_\_\_\_\_

## METER CONSOLE CALIBRATION

Name \_\_\_\_\_ Date \_\_\_\_\_

Console no. \_\_\_\_\_ Dry gas meter no. \_\_\_\_\_ Dry gas meter correction factor \_\_\_\_\_

Wet test meter no. \_\_\_\_\_ Correction factor \_\_\_\_\_

Barometric pressure,  $P_b$  \_\_\_\_\_ in. Hg Previous calibration and date \_\_\_\_\_

Orifice manometer setting, $\Delta H$ , in. H <sub>2</sub> O	Gas volume wet test meter $V_w$ , ft <sup>3</sup>	Gas volume dry gas meter $V_d$ , ft <sup>3</sup>	Temperature				Time $\theta$ min	$\gamma$	$\Delta H@$
			Wet test		Dry gas meter				
			Meter $t_w$ , °F	Inlet $t_{di}$ , °F	Outlet $t_{do}$ , °F	Average $t_d$ , °F			
0.5	5								
1.0	5								
2.0	10								
4.0	10								
6.0	10								
8.0	10								
Average									

### Calculations

$\Delta H$	$\frac{\Delta H}{13.6}$	$\gamma$	$\Delta H@$
		$\frac{V_w P_b (t_d + 460)}{V_d \left( P_b + \frac{\Delta H}{13.6} \right) (t_w + 460)}$	$\frac{0.0317 \Delta H}{P_b (t_d + 460)} \left[ \frac{(t_w + 460)\theta}{V_w} \right]^2$
0.5	0.0368		
1.0	0.0737		
2.0	0.147		
4.0	0.294		
6.0	0.431		
8.0	0.588		

$\gamma$  = Ratio of accuracy of wet test meter to dry test meter. Tolerance =  $\pm 0.02$ .

$\Delta H@$  = Orifice pressure differential that gives 0.75 cfm of air at 68°F and 29.92 inches of mercury, in. H<sub>2</sub>O. Tolerance =  $\pm 0.15$  inches.

Orifice  $\Delta H@$  should fall between 1.59 - 2.09 inches, or modification may be necessary for some sampling situations.

Form for meter console calibration

## NOZZLE CALIBRATION

Date \_\_\_\_\_ Calibrated by \_\_\_\_\_

Nozzle identifi- cation #	D <sub>1</sub> , in.	D <sub>2</sub> , in.	D <sub>3</sub> , in.	ΔD, in.	D <sub>avg</sub>

where:

D<sub>1</sub>, 2, 3, = nozzle diameter measured on a different diameter, in. Tolerance = measure within 0.001 in.

ΔD = maximum difference in any two measurements, in. Tolerance = 0.004 in.

D<sub>avg</sub> = average of D<sub>1</sub>, D<sub>2</sub>, and D<sub>3</sub>.

Nozzle calibration data.

# TEMPERATURE CALIBRATION

Name \_\_\_\_\_ Date \_\_\_\_\_

Barometric Pressure \_\_\_\_\_ Land Elevation \_\_\_\_\_

## ICE BATH

Hg in Glass Thermometer Temperature				Corrected Hg in Glass Temperature				Temperature Device _____ Identification No. _____ Temperature			
°C	°K	°F	°R	°C	°K	°F	°R	°C	°K	°F	°R

## BOILING WATER BATH

Hg in Glass Temperature				Corrected Temperature				Device _____ No. _____			
°C	°K	°F	°R	°C	°K	°F	°R	°C	°K	°F	°R

## MINERAL OIL BATH

Point	Hg in Glass Temperature				Corrected Temperature				Device _____ No. _____			
	°C	°K	°F	°R	°C	°K	°F	°R	°C	°K	°F	°R
1												
2												
3												
4												

Form for temperature calibration.

# **Method 1—Sample and Velocity Traverses for Stationary Sources** **Sample Site Selection and Minimum Number of Traverse Points**

Plant \_\_\_\_\_ Location \_\_\_\_\_ Date \_\_\_\_\_

Sampling location \_\_\_\_\_

Sample team operator(s) \_\_\_\_\_

Sketch of stack geometry (including distances from sample site to any disturbances)

Interior duct cross-section dimension \_\_\_\_\_ ft

Sampling port diameter \_\_\_\_\_ in.

Sampling port nipple length \_\_\_\_\_ in.

Stack cross-sectional area \_\_\_\_\_ ft<sup>2</sup>

Sampling site: diameter downstream of disturbance \_\_\_\_\_ Diameters upstream \_\_\_\_\_

Minimum number of sampling points \_\_\_\_\_ Individual point sample time \_\_\_\_\_

Total test time \_\_\_\_\_

Comments:

## **Sketch of Stack Cross-Section Showing Sample Ports and all Dimensions**

Sample point number	Circular stack % diameter	Distance from sample port opening in.
1.		
2.		
3.		
4.		
5.		
6.		
7.		
8.		
9.		
10.		
11.		
12.		

*Very Important—Fill in all Blanks*

Fyrite no. \_\_\_\_\_ Date rebuilt \_\_\_\_\_

 $\Delta p_{avg}$ , in. H<sub>2</sub>O \_\_\_\_\_

Leak rate@15 in. Hg Pre-test\_\_\_\_\_ Post-test\_\_\_\_\_

[illegible]

Comments:

Test observers: \_\_\_\_\_

**continued**

[illegible]

Comments: \_\_\_\_\_

Test observers: \_\_\_\_\_

*continued*

# Laboratory Analysis Data Particulate Source Sample

Analysis date(s) \_\_\_\_\_ Analytical chemist \_\_\_\_\_  
 Plant sampled \_\_\_\_\_ Location \_\_\_\_\_  
 Sampling location \_\_\_\_\_ Sampling date(s) \_\_\_\_\_  
 Sample run no. \_\_\_\_\_ Sampling case no. \_\_\_\_\_  
 Sample labels: H<sub>2</sub>O \_\_\_\_\_ Silica gel \_\_\_\_\_ Filter \_\_\_\_\_ Probe \_\_\_\_\_  
 Impinger rinse \_\_\_\_\_ Dry particulate \_\_\_\_\_ Other \_\_\_\_\_  
 Analysis performed \_\_\_\_\_  
 Reference method \_\_\_\_\_ Analytical sample temp. \_\_\_\_\_  
 Comments: \_\_\_\_\_

<b>Moisture Data</b> Final volume H <sub>2</sub> O in impingers _____ ml Initial volume H <sub>2</sub> O in impingers _____ ml Volume H <sub>2</sub> O condensed _____ ml Final weight silica gel _____ gm Initial weight silica gel _____ gm		<b>Total Moisture</b> H <sub>2</sub> O Condensed _____ ml H <sub>2</sub> O Absorbed _____ ml H <sub>2</sub> O Total _____ ml	
<b>Particulate Data</b> CH <sub>3</sub> -CH <sub>2</sub> -O-CH <sub>2</sub> -CH <sub>3</sub> / CHCl <sub>3</sub> extract Flask no. _____ Final weight _____ mg Initial weight _____ mg Organic fraction _____ mg		<b>Total Particulate Sampled</b> Organic fraction _____ mg Inorganic fraction _____ mg Front half particulates _____ mg	
<b>Extracted H<sub>2</sub>O Flask No.</b> _____ Final weight _____ mg Initial weight _____ mg Inorganic fraction _____ mg <b>Filter Flask No.</b> _____ Final weight _____ mg Initial weight _____ mg Filter and particulates _____ mg Filter no. _____ Tare weight _____ mg Particulates _____ mg Dry particulates and probe _____ mg Front half particulates _____ mg		<b>Total Particulates</b> Run No. _____  _____ mg	



## Orsat Field Data

Orsat identification no. \_\_\_\_\_ Date reagents added \_\_\_\_\_  
Checked by \_\_\_\_\_  
Plant location \_\_\_\_\_ Sampling date \_\_\_\_\_  
Operator(s) \_\_\_\_\_  
Sampling location \_\_\_\_\_ Average fyrite CO<sub>2</sub> \_\_\_\_\_  
Moisture content of stack gas (B<sub>ws</sub>) \_\_\_\_\_ Fuel used \_\_\_\_\_  
Fuel feed rate \_\_\_\_\_ Combustion source description \_\_\_\_\_  
Process production rate \_\_\_\_\_ Steam production rate \_\_\_\_\_  
Comments: \_\_\_\_\_

Test no.	Sample time		Analysis time	Burette readings		
	Start	Stop		CO <sub>2</sub>	O <sub>2</sub>	CO

Component	Mole fraction = %composition
CO <sub>2</sub>	
O <sub>2</sub> - CO <sub>2</sub>	
CO - O <sub>2</sub>	
100 - CO = N <sub>2</sub>	

Dry molecular weight of stack gas ( $M_d$ ) =  $\sum M_x B_x$

$$M_d = .44 (\text{---} \% \text{CO}_2) + .32 (\text{---} \% \text{O}_2) + .28 (\text{---} \% \text{CO}) + .28 (\text{---} \% \text{N}_2) = \text{---} \text{ gm/m}$$

Wet molecular weight of stack gas ( $M_s$ ) =  $M_d(1 - B_{ws}) + 18 \text{ gm/m}(B_{ws})$

$$M_s = (\text{---} \text{ gm/m}) (1 - \text{---}) + 18 \text{ gm/m} (\text{---}) = \text{---} \text{ gm/m}$$

$$\% \text{ Excess air in the duct } (\% \text{EA}) = \left[ \frac{\% \text{O}_2 - 0.5(\% \text{CO})}{(0.264)(\% \text{N}_2) - (\% \text{O}_2) + 0.5(\% \text{CO})} \right] \times 100$$

$$\% \text{ EA} = \left[ \frac{(\text{---} \% \text{O}_2) - 0.5(\text{---} \% \text{CO})}{(0.264)(\text{---} \% \text{N}_2) - (\text{---} \% \text{O}_2) + 0.5(\text{---} \% \text{CO})} \right] \times 100 = \text{---} \%$$

Plant: _____	City: _____	Remarks: _____ _____ _____
Site: _____	Sam. type: _____	
Date: _____	Run no: _____	
Front rinse <input type="checkbox"/>	Front filter <input type="checkbox"/> Front solu <input type="checkbox"/>	
Back rinse <input type="checkbox"/>	Back filter <input type="checkbox"/> Back solu <input type="checkbox"/>	
Solution: _____	Level marked _____	
Volume: Initial _____	Final _____	
Clean up by: _____		

Example sample label

# **Appendix B**

## **Source Sampling Calculations**

# Source Sampling Calculations

This section presents the equations used for source sampling calculations. These equations are divided into two parts—equipment calibration, and source test calculations. Gaseous source test equations are included to aid the source sampler performing both particulate and gaseous emissions tests. The purpose of the section is to give the reader a quick reference to necessary mathematical expressions used in source testing experiments.

## EQUIPMENT CALIBRATION EQUATIONS

### Stausscheibe (Type S) Pitot Tube Calibration

Calibration Coefficient ( $C_p$ )

$$(Eq. 6-1) \quad C_{p(s)} = C_{p(std)} \sqrt{\frac{\Delta p_{std}}{\Delta p_s}}$$

Deviation from Average  $C_p$  (Leg A or B of Type S tube)

$$(Eq. 6-2) \quad Deviation = C_{p(std)} - C_p$$

Average deviation from the mean  $\delta$  (Leg A or B)

$$(Eq. 6-3) \quad \delta = \frac{\sum_{i=1}^3 |C_{p(s)} - \bar{C}_{p(A \text{ or } B)}|}{3}$$

### Sampling Probe Calibration Developed by Experiment and Graphed for Each Probe Length

#### Test Meter Calibration Using Spirometer

Spirometer volume (temperature and pressure correction not necessary for ambient conditions)

$$(Eq. 6-4) \quad [Spirometer \text{ displacement (cm)}] \times [liters/cm] = \text{liters volume}$$

Convert liters to cubic feet ( $ft^3$ )

Test Meter Correction Factor

$$(Eq. 6-5) \quad \frac{Spirometer \text{ Standard } ft^3}{Test \text{ meter } ft^3} = Test \text{ meter correction factor}$$

Correct Volume

$$(Eq. 6-6) \quad [Test\ meter\ volume] \times [Test\ meter\ correction\ factor] = correct\ volume$$

### Orifice Meter Calibration Using Test Meter

Test meter volumetric flowrate ( $Q_m$ ) in cubic feet per minute

$$(Eq. 6-7) \quad Q_m = [Test\ meter\ (V_f) - Test\ Meter\ V_i] \times [Test\ meter\ correction\ factor]$$

where

$$Q_m = \text{cubic feet per minute}$$

Proportionality Factor ( $K_m$ )

$$(Eq. 6-8) \quad K_m = Q_m \sqrt{\frac{P_m M_m}{T_m \Delta H}}$$

Orifice meter  $\Delta H@$

$$(Eq. 6-9) \quad 1. \quad \text{English units } \Delta H@ = \frac{0.9244}{K_m^2}$$

where

$$Q_m = 0.75 \text{ cfm at } 68^\circ\text{F and } 29.92 \text{ in. Hg}$$

$$(Eq. 6-9) \quad 2. \quad \text{Metric units } \Delta H@ = \frac{0.3306}{K_m^2}$$

where

$$Q_m = 0.021 \text{ m}^3/\text{min at } 760 \text{ mm Hg and } 20^\circ\text{C}$$

### Sampling Meter Console Calibration

Ratio of the accuracy of Console Gas Meter Calibration Test Meter ( $\gamma$ ).

Tolerance  $1 \pm 0.02$

$$(Eq. 6-10) \quad \gamma = \frac{V_T T_m P_b}{V_m T_t \left( P_b + \frac{\Delta H}{13.6} \right)}$$

Meter Console Orifice Meter Calibration ( $\Delta H@$ )

$$(Eq. 6-11) \quad 1. \quad \Delta H@ = \frac{K \Delta H}{P_b T_m} \left[ \frac{T_T \theta}{V_T} \right]^2$$

where

$$K = 0.0317 \text{ English units} \\ = 0.0012 \text{ metric units}$$

$$(Eq. 6-12) \quad 2. \quad \Delta H@ = \frac{0.9244}{\bar{K}_m^2}$$

## Source Sampling Nomograph Calibration

### Isokinetic $\Delta H$ Equation

$$(Eq. 6-13) \quad \text{Isokinetic } \Delta H = 846.72 D_n^4 \Delta H @ C_p^2 \frac{T_m P_s}{T_s P_m} (1 - B_{ws})^2 \left( \frac{M_d}{M_s} \right) (\Delta p) \quad \text{English units}$$

### Sampling Nozzle Equation

$$(Eq. 6-14) \quad D_n = \sqrt{\frac{0.0358 Q_m P_m}{T_m C_p (1 - B_{ws})}} \sqrt{\frac{T_s M_s}{P_s (\Delta p)}} \quad \text{English units}$$

### Adjusted C-Factor ( $C_p$ )

$$(Eq. 6-15) \quad C\text{-Factor}_{adjusted} = C_{factor} \left[ \frac{C_p}{0.85} \right]^2$$

### Adjusted C-Factor ( $M_d \neq 29$ )

$$(Eq. 6-15) \quad C\text{-Factor}_{adjusted} = C_{factor} \frac{1 - B_{ws} + 18 B_{ws}/29}{1 - B_{ws} + 18 B_{ws}/M_d}$$

## SOURCE SAMPLING CALCULATIONS

### Method 1—Site Selection

#### Equal Area Equation (circular ducts)

$$(Eq. 6-16) \quad P = 50 \left[ 1 - \sqrt{\frac{2j-1}{2n}} \right]$$

#### Equivalent Diameter for a Rectangular Duct

$$(Eq. 6-17) \quad D_E = \frac{2(\text{length})(\text{width})}{\text{length} + \text{width}}$$

### Method 2—Gas Velocity and Volumetric Flow Rate

#### Average Stack Gas Velocity

$$(Eq. 6-18) \quad \bar{v}_s = K_p C_p \sqrt{\frac{T_s}{P_s M_s}} (\sqrt{\Delta p})_{average}$$

#### Average Dry Stack Gas Volumetric Flow Rate at Standard Conditions ( $\bar{Q}_s$ )

$$(Eq. 6-19) \quad \bar{Q}_s = 3600 (1 - B_{ws}) \bar{v}_s A_s \left[ \frac{T_{std}}{P_{std}} \right] \frac{P_s}{T_s}$$

### Method 3—Orsat Analysis

Stack Gas Dry Molecular Weight

$$(Eq. 6-20) \quad M_d = \sum M_x B_x = 0.44(\%CO_2) + 0.32(\%O_2) + 0.28(\%N_2 + \%CO)$$

Stack Gas Wet Molecular Weight

$$(Eq. 6-21) \quad M_s = M_d(1 - B_{ws}) + 18 B_{ws}$$

Percent Excess Air (%EA)

$$(Eq. 6-22) \quad \%EA = \frac{(\%O_2) - 0.05(\%CO)}{0.264 (\%N_2) - (\%O_2) + 0.5(\%CO)} \times 100$$

### Method 4—Reference Moisture Content of a Stack Gas

Volume Water Vapor Condensed at Standard Conditions ( $V_{wc}$ )

$$(Eq. 6-23) \quad V_{wc} = \frac{(ml H_2O)_w R T_{std}}{P_{std} M_w} = K_1 (V_f - V_i)$$

where

$$K_1 = 0.001333 \text{ m}^3/\text{ml for metric units} \\ = 0.04707 \text{ ft.}^3/\text{ml for English units}$$

Silica Gel

$$(Eq. 6-24) \quad K_2 = (W_f - W_i) = V_{w_{SG}}$$

where

$$K_2 = 0.001335 \text{ m}^3/\text{gm for metric units} \\ = 0.04715 \text{ ft.}^3/\text{gm for English units}$$

Gas Volume at Standard Conditions

$$(Eq. 6-25) \quad V_{m(std)} = V_m Y_m \left( \frac{T_{std}}{P_{std}} \right) \left( \frac{P_b + \frac{\Delta H}{13.6}}{T_m} \right)$$

Moisture Content

$$(Eq. 6-26) \quad B_{ws} = \frac{V_{wc} + V_{w_{SG}}}{V_{wc} + V_{w_{SG}} + V_{m(std)}}$$

### Method 5—Particulate Emissions Testing

Dry Gas Volume Metered at Standard Conditions

Leak Rate Adjustment

$$(Eq. 6-27) \quad V_m = [V_m - (L_1 - L_a)\theta - \sum_{i=2}^N (L_i - L_a)\theta_i - (L_p - L_a)\theta_p]$$

## Standard Dry Volume at Sampling Meter

$$(Eq. 6-28) \quad V_{m(std)} = V_m Y_m \left( \frac{T_{std}}{P_{std}} \right) \left( \frac{P_b + \frac{\Delta H}{13.6}}{T_m} \right)$$

## Isokinetic Variation

### Raw Data

$$(Eq. 6-29) \quad \%I = \frac{100 T_s [K_3 V_{lc} + (V_m/T_m) (P_b + \Delta H/13.6)]}{60 \theta_s v_s P_s A_n}$$

where

$$K_3 = 0.003454 \frac{mm \text{ Hg } m^3}{ml \text{ } ^\circ K}$$

$$= 0.002669 \frac{in. \text{ Hg } ft.^3}{ml \text{ } ^\circ R}$$

Note: This equation includes a correction for the pressure differential across the dry gas meter measured by the orifice meter — average sampling run  $\Delta H$  readings.

### Intermediate Data

$$(Eq. 6-30) \quad \%I = 100 \frac{T_s V_{m(std)} P_{std}}{T_{std} \bar{v}_s \theta A_n P_s 60 (1 - B_{ws})}$$

## Method 8 —Sulfuric Acid Mist and Sulfur Dioxide Emissions Testing

Dry volume metered at standard conditions (see equations in previous sections of this outline)

### Sulfur Dioxide concentration

$$(Eq. 6-31) \quad c_{SO} = K_3 \frac{N(V_t - V_{tb}) \left( \frac{V_{solution}}{V_{aliquot}} \right)}{V_{m(std)}}$$

where

$$K_3 = 0.03203 \text{ g/meq for metric units}$$

$$= 7.061 \times 10^{-5} \text{ lb/meq for English units}$$

### Sulfuric acid mist (including sulfur trioxide) concentration

$$(Eq. 6-32) \quad c_{H_2SO_4} = K_2 \frac{N(V_t - V_{tb}) \left( \frac{V_{solution}}{V_{aliquot}} \right)}{V_{m(std)}}$$



where

$$K_2 = 0.04904 \text{ g/meq for metric units} \\ = 1.08 \times 10^{-4} \text{ lb/meq for English units}$$

Isokinetic Variation

Raw Data

$$(Eq. 6-33) \quad \%I = 100 \frac{T_s [K_4 V_{lc} + (V_m/T_m)(P_b + \Delta H/13.6)]}{60\theta A_n v_s P_s}$$

where

$$K_4 = 0.003464 \text{ mm Hg} - m^3/ml - ^\circ K \\ = 0.002676 \text{ in Hg} - ft^3/ml - ^\circ R$$

### Concentration Correction Equations

Concentration Correction to 12%  $CO_2$

$$(Eq. 6-34) \quad c_{s12} = c_s \left[ \frac{12}{\%CO_2} \right]$$

Concentration Correction to 50% Excess Air Concentration

$$(Eq. 6-35) \quad c_{s50} = \left[ \frac{100 + \%EA}{150} \right]$$

Correction to 50% Excess Air Using Raw Orsat Data

$$(Eq. 6-36) \quad c_{s50} = \frac{c_s}{1 - \left[ \frac{(1.5)(\%O_2) - (0.133)(\%N_2) - 0.75(\%CO)}{21} \right]}$$

### F-Factor Equations

$F_c$  Factor

$$(Eq. 6-37) \quad E = F_c c_s \left( \frac{100}{\%CO_2} \right)$$

Used when measuring  $c_s$  and  $CO_2$  on a wet or dry basis.

$F_d$  Factor

When measuring  $O_{2d}$  and  $c_s$  on a dry basis

$$(Eq. 6-38) \quad E = F_d c_{sd} \left[ \frac{20.9}{20.9 - \%O_{2d}} \right]$$

When measuring  $O_{2d}$  and  $c_s$  on a wet basis

$$(Eq. 6-39) \quad E = F_d c_{ws} \left[ \frac{20.9}{20.9(1 - B_{ws}) - \frac{\%O_{2w}}{1 - B_{ws}}} \right]$$

$F_w$  Factor

- When measuring  $c_s$  and  $O_2$  on a wet basis
- $B_{wa}$  = moisture content of ambient air
- Cannot be used after a wet scrubber

$$(Eq. 6-40) \quad E = F_w c_{ws} \left[ \frac{20.9}{20.9(1 - B_{wa}) - \%O_{2w}} \right]$$

$F_o$  Factor

1. Miscellaneous factor for checking Orsat data

$$(Eq. 6-41) \quad F_o = \frac{20.9}{100} \frac{F_d}{F_c} = \frac{20.9 - \%O_{2d}}{\%CO_{2d}} \left( \begin{array}{l} O_2 \text{ and } CO_2 \text{ measured} \\ \text{on dry basis} \end{array} \right)$$

### Opacity Equations

% Opacity

$$(Eq. 6-42) \quad \% \text{ Opacity} = 100 - \% \text{ Transmittance}$$

Optical Density

$$(Eq. 6-43) \quad \text{Optical Density} = \log_{10} \left[ \frac{1}{1 - \text{Opacity}} \right]$$

$$(Eq. 6-44) \quad \text{Optical Density} = \log_{10} \left[ \frac{1}{\text{Transmittance}} \right]$$

Transmittance

$$(Eq. 6-45) \quad \text{Transmittance} = e^{-naql}$$

Plume Opacity Correction

$$(Eq. 6-46) \quad \log(1 - O_1) = (L_1/L_2) \log(1 - O_2)$$

# **Appendix C**


## **Problems**

# **PROBLEMS WITH SOLUTIONS**

## SAMPLE SITE SELECTION

### Problem 1.

The diagram below is a sketch of a duct to be sampled using the EPA Method 5 Sampling Train. Using Method 1 guidelines calculate the equivalent diameter of the duct, select the best sampling site, sample port entry number, and sampling point number (the plant will weld on threaded 3" diameter, 6" long steel pipe nipples as Sample ports. Determine the sampling time at each test point and total test time. Sketch out all work with dimensions.



## 1. Equivalent Diameter

$$2. \quad \frac{231'' \text{ total duct dimension to exit}}{D_F = 30.8} = 7.5 \text{ diameter total}$$

4. Chart indicates 24 or more sample points.

6. Minimum time/point 2.5 minutes. total test time = 62.5 minutes.  
(Note: 3 minutes/point would be easiest).

## 7. Sketch of Sampling Site Cross-section.



Sample Point	Distance from 6" Long Nipple Opening
1	$2.5" + 6" = 8.5"$
2	$7.5" + 6" = 13.5"$
3	$12.5" + 6" = 18.5"$
4	$17.5" + 6" = 23.5"$
5	$22.5" + 6" = 28.5"$

Problem 2.

An "S" type pitot tube was used with an assumed  $C_p = 0.85$  for performing a source test. Laboratory calibration of the tube showed that for the conditions at the source the actual  $C_p = 0.80$ . Explain all the ramifications of this error given the data below.

$$B_{ws} = 7\%$$

$$M_s = 30.01 \text{ lb/lbmole}$$

$$P_s = 30.04 \text{ in. Hg}$$

$$\Delta p = 1.2 \text{ in H}_2\text{O}$$

$$\theta = 60 \text{ minutes}$$

$$T_s^{\circ}R = 700$$

$$V_{m(\text{std})} = 45.25 \text{ SCF}$$

$$\text{Particulate Concentration} = .2 \text{ grains/DSCF}$$

$$A_s = 20 \text{ ft.}^2$$

## A. Velocity

$$1. \quad C_p = 0.85$$

$$v_s = 85.49 (0.85) \left[ \frac{700 (1.2)}{30.04 (30.0)} \right]^{\frac{1}{2}} = 70.16 \text{ ft./sec}$$

$$2. \quad C_p = 0.80$$

$$v_s = 85.4 (.8) \left[ \frac{700 (1.2)}{30.04 (30.0)} \right]^{\frac{1}{2}} = 66.03 \text{ ft./sec}$$

5.88% error

## B. Volumetric Flow Rate

$$1. \quad C_p = 0.85$$

$$Q_s = 3600 (1-0.07)(70.16)(20)(17.65) \left( \frac{30.04}{700} \right) = 3,558,000 \text{ SCFH}$$

$$2. \quad C_p = 0.80$$

$$Q_s = 3600 (1-0.007)(66.03)(20)(17.65) \left( \frac{30.04}{700} \right) = 3,348,000 \text{ SCFH}$$

5.90% error

## C. Isokinetic Flow Rate

### 1. Nozzle Velocity

$$a. \quad C_p = 0.85$$

Nozzle velocity ( $v_n$ ) > stack gas velocity

Overisokinetic

$$b. \quad C_p = 0.80 \quad v_n = v_s = \text{isokinetic}$$

### 2. Overisokinetic Condition

a. Biased sample with small particles

b. 0.2 gr/SCF < real concentration



### Problem 3.

#### Stack Gas Velocity

An "S" type pitot tube with a  $C_p = 0.84$  was used to take a stack gas velocity reading in an oil fired power plant duct. The circular duct had a diameter of 10ft. The  $\Delta p$  measured in the duct was 0.5 in.  $H_2O$ . The average stack gas temperature was  $300^\circ F$ . The wet molecular weight of the gas was 30.0 gm/mole. Moisture content was 6%  $H_2O$ . Absolute stack pressure was 30.0 in. Hg. Calculate the average gas velocity in feet/second. Calculate the volumetric flow rate in standard cubic feet/hour.

#### 1. Average Stack Gas Velocity

$$a. \quad v_s = K_p C_p \left[ \frac{(T_s) \Delta p}{P_s M_s} \right]^{1/2}$$

b.

$$v_s = 85.49 \left[ \frac{(760^\circ)(0.5)}{(30.0)(30.0)} \right]^{1/2} (.84)^{1/2}$$
$$= 46.7 \text{ ft/sec}$$

#### 2. Average Stack Gas Volumetric Flow Rate (Dry SCFH)

$$a. \quad Q_s = 3600 \text{ sec./hr. } (1 - B_{ws})(v_s)(\text{Area}) \left[ \frac{528^\circ R}{T_s^\circ R} \right] \frac{P_s}{29.92 \text{ in. Hg.}}$$

$$b. \quad Q_s = 3600 \text{ sec./hr. } (1 - 0.06)(46.7 \text{ ft./sec.}) \pi (5 \text{ ft.})^2$$

$$\left[ \frac{528^\circ R}{760^\circ R} \right] \frac{30.0 \text{ in. Hg.}}{29.92 \text{ in. Hg.}} = 8,646,000 \text{ SCFH}$$

What would be the volumetric flow rate of the stack gas exiting the duct in the above problem in actual cubic feet/hour at stack conditions?

$$a. \quad Q_a = (\bar{v}_s \text{ ft./sec.}) \times (\text{Area}) \times 3600 \text{ sec./hr.}$$

$$b. \quad Q_a = (46.7 \text{ ft./sec.}) \pi (5\text{ft.})^2 \times 3600 \text{ sec./hr.} \\ = 13,204,000 \text{ ACFH}$$

#### Problem 4.

##### Molecular Weight of a Stack Gas

An integrated bag sample of the stack gas in coal fired power plant duct was analyzed by orsat. The orsat indicated readings for  $\text{CO}_2$  - 14.2;  $\text{O}_2$  - 21.4; and  $\text{CO}$  - 21.4.\* The moisture content of the stack gas was 7%  $\text{H}_2\text{O}$  vapor. What is the molecular weight of the gas?

#### 1. Stack Gas Constituents

$$\text{CO}_2 = 14.2\% \text{ by volume}$$

$$\text{O}_2 = 21.4 - 14.2 = 7.2\% \text{ by volume}$$

$$\text{CO} = 21.4 - 21.4 = 0\%$$

$$\text{N}_2 = 100 - 21.4 = 78.6\% \text{ by volume}$$

$$\text{H}_2\text{O} = 7\%$$

#### 2. Dry Molecular Weight of Gas

$$M_{\text{dry}} = \sum M_x B_x \quad \begin{array}{l} M_x = \text{Molecular weight} \\ \text{component} \end{array} \quad \begin{array}{l} B_x = \text{Mole fraction} \\ \text{expressed as \% by} \\ \text{volume} \end{array}$$

\*Note: Orsat analysis readings indicate a direct % reading for  $\text{CO}_2$  and additive readings for  $\text{O}_2$  and  $\text{CO}$ . Therefore in the problem above:

$$\text{CO}_2 = 14.2\% \text{ by volume (read directly)}$$

$$\text{O}_2 = \text{O}_2 - \text{CO}_2 = 21.4 - 14.2 = 7.2\% \text{ by volume}$$

$$\text{CO} = \text{O}_2 - \text{CO} = 21.4 - 21.4 = 0\% \text{ CO by volume}$$

$$\begin{aligned}
 M_{\text{dry}} &= 44\text{lb/lb-mole}(\% \text{CO}_2) + 32\text{lb/lb-mole}(\% \text{O}_2) + 28\text{lb/lb-mole}(\% \text{CO}) \\
 &\quad + 28\text{lb/lb-mole}(\% \text{N}_2) \\
 &= 44(.142) + 32(.072) + 28(0) + 28(.786) \\
 &= 6.248 + 2.304 + 0 + 22.008 \\
 &= 30.560\text{lb/lb-mole}
 \end{aligned}$$

### 3. Wet Molecular Weight of Gas

$$\begin{aligned}
 M_s &= M_{\text{dry}} (1 - B_{ws}) + 18(B_{ws}) \quad B_{ws} = \% \text{H}_2\text{O vapor in stack gas} \\
 &= 30.560\text{lb/lb-mole} (1 - 0.07) + 18\text{lb/lb-mole} (0.07) \\
 &= 28.421 + 1.26 \\
 &= 29.681\text{lb/lb-mole}
 \end{aligned}$$

## Problem 5.

### Moisture Content of a Stack Gas

Reference Method 4 for determination of the moisture content of a stack gas was completed at a coal fired power plant duct. From the following data calculate the % H<sub>2</sub>O present in the stack gas.

$$V_{\text{metered}} = 1.258 \text{ CF}$$

$$\text{Test Time} = 20 \text{ minutes}$$

$$t_m \text{ } ^\circ\text{F} = 80$$

$$t_s \text{ } ^\circ\text{F} = 250$$

$$P_m = 30.25 \text{ in. Hg.}$$

$$\text{H}_2\text{O Volume collected in the Impingers} = 2.6 \text{ ml}$$

$$\text{H}_2\text{O Weight increase in Silica Gel} = 2.4 \text{ gm.}$$

### 1. Volume Metered at Standard Conditions.

$$V_{m(std)}^* = V_m \left[ \frac{T_{std}}{P_{std}} \right] \frac{P_m}{T_m}$$

$$V_{m(std)} = 1.258 \text{ CF} \left[ \frac{528^\circ\text{R}}{29.92 \text{ in.Hg.}} \right] \frac{30.25 \text{ in.Hg.}}{540^\circ\text{R}} = 1.244 \text{ SCF}$$

2. H<sub>2</sub>O Condensed Converted to Standard Cubic Volume of H<sub>2</sub>O Vapor

a. Impinger (V<sub>WC</sub>)

$$2.6 \text{ ml} \times 0.04707 \text{ SCF/ml} = .12238 \text{ SCF}$$

b. Silica Gel (V<sub>Sg</sub>)

$$2.4 \text{ m.} \times 0.04715 \text{ SCF/ml} = .11316$$

3. (B<sub>WS</sub>) Moisture Content

$$B_{WS} = \frac{V_{WC} + V_{Sg}}{V_{WC} + V_{Sg} + V_{m(std)}} \times 100 = \frac{0.236}{0.236 + 1.244} = 15.95\%$$

#### Problem 6.

##### Percent Isokinetic

A 1 hour long source test conducted at an oil fired steam generation facility provided the following information:

Average Stack Temperature = 300°F

Average Stack Gas Velocity = 50.0 ft./sec.

Volume Sampled at Meter Conditions = 40 cubic feet

Average Temperature at the Meter = 70°F

Static Pressure in the Stack = +0.2 in. H<sub>2</sub>O

Barometric Pressure = 30.26 in. Hg.

Average Pressure Differential Across the Orifice = 1.5 in. H<sub>2</sub>O

\*Note: V<sub>m</sub> = Volume at meter X Dry Gas Meter Correction Factor (DGMCF)

In this example assume DGMCF = 1

H<sub>2</sub>O Collected in the impingers = 100 ml

Sampling Nozzle Diameter = 0.250 inches

What is the % isokinetic for this source test?

a. % Isokinetic from Raw Data

$$\%I = 100 \times \frac{T_s \cdot R \left[ K(\text{Volume H}_2\text{O}) + (V_m/T_m) (P_b + \frac{\Delta H}{13.6}) \right]}{\bar{V}_s \cdot 60\text{sec./min.} (0\text{min.}) P_s (\text{Nozzle Area})}$$

b. % I

$$\%I = 100 \times \frac{760^\circ R \left[ \left( 0.00267 \frac{\text{in.Hg} \cdot \text{ft.}^3}{\text{ml} \cdot ^\circ R} \right) (100\text{ml}) + \frac{40\text{ft.}^3}{530^\circ R} \left( 30.26\text{in.Hg} + \frac{1.5\text{in. H}_2\text{O}}{13.6} \right) \right]}{(50\text{ft./sec.}) 60\text{sec./min.} (60\text{min.}) \left( 30.26\text{in. Hg} + \frac{0.2\text{in. H}_2\text{O}}{13.6} \right) (0.0003408 \text{ ft}^2)}$$

The 1 hour second stack test at the same facility gave intermediate data as follows:

% H<sub>2</sub>O in Stack Gas = 6.5

Volume metered at Standard Conditions = 38.8DSCF

Static Pressure in the Stack = 0.25 in. H<sub>2</sub>O

Barometric Pressure = 30.30 in. Hg.

Nozzle Diameter = 0.248 inches

Average Velocity = 49.8 ft./sec.

Average Stack Temperature = 296°F

What is the percent isokinetic for this source test?

$$\% I = 100 \times \frac{T_s V_m(\text{std}) P_{\text{std}}}{T_{\text{std}} V_s P_s \cdot 0\text{min.} (60\text{sec./min.}) (\text{Nozzle Area}) (1-B_{ws})}$$

b. % Isokinetic

$$\% I = .100 \times \frac{760^{\circ}R (38.8\text{ft.}^3) (29.92\text{in. Hg.})}{(528^{\circ}R) (30.30 + \frac{0.25}{13.6}) (49.8\text{ft./sec.}) (1-0.06) (3600) (0.0003352\text{ft.}^2)}$$
$$= 97.05$$


# **ADDITIONAL PROBLEMS**

## ADDITIONAL PROBLEMS

### BACKGROUND

During a recent presite survey at a wood waste boiler in Pactolus, North Carolina, the following information was obtained concerning emission description and emission information from the exhaust of the boiler:

a) Sketch



b) Information

% Moisture in Stack Gas ( $B_{ws}$ ): 7.0 %  
Stack gas Temperature ( $t_s$ ): 303°F  
Average  $\Delta p$ : 0.15 " H<sub>2</sub>O  
 $C_p$ : 0.845  
Orsat Data: CO<sub>2</sub>: 14.2 %  
                  O<sub>2</sub>: 5.0 %  
                  CO: 0.0 %  
Absolute Stack Gas Pressure: 30.3 " Hg  
Stack Diameter: 16"  
Stack Configuration: Circular

### PROBLEM 1.

With the assistance of Federal Register Method 1 as outlined in Vol. 42, No. 160, Aug. 18, 1977, complete the following table for a particulate traverse.



TABLE #1

Sample Point Number	Circular Stack % Diameter	Distance From Sample Port Opening in.
1.		
2.		
3.		
4.		
5.		
6.		
7.		
8.		
9.		
10.		
11.		
12.		

PROBLEM 2. Determine the following parameters:

Average Stack Gas Velocity ( $\bar{v}_s$ ): ft/sec  
 Average Stack Gas Volumetric Flow Rate ( $\bar{Q}_s$ ): DSCFH  
 Actual Stack Gas Volumetric Flow Rate ( $Q_a$ ): ACFH

PROBLEM 3. During a recent visit to a fertilizer plant, the following information was obtained concerning emissions from the drying operation:

Stack Temperature ( $t_s$ ): 300°F  
 Per Cent Moisture in Flue Gas ( $B_{ws}$ ): 12%  
 Per Cent  $O_2$  in Flue Gas: 2%  
 Per Cent  $CO_2$  in Flue Gas: 17%  
 Per Cent  $CO$  in Flue Gas: nil  
 Barometric Pressure: 30.1 " Hg  
 Pressure of Stack: -15.0 "  $H_2O$   
 $C_p$ : 0.842  
 $\Delta p$ : 2.5 "  $H_2O$

From the above information, determine the average stack gas velocity ( $\bar{v}_s$ ).

Problem 4.

Given the following calculate ( $B_{ws}$ ) moisture content of the stack gas

$H_2O$  collected in the impingers = 75 ml

$H_2O$  collected in the silica gel = 25 gms

Volume metered = 40.20 cubic feet

$P_m$  = 30.0 in. Hg

$t_m$  = 100°F

Answers:

$$V_{m_{std}} = 37.99 \text{ SCF}$$

$$V_{wc_{std}} = 3.54 \text{ ft}^3$$

$$V_{sg_{std}} = 1.18 \text{ ft}^3$$

$$B_{ws} = 11.03\%$$

Problem 5.

Given the following information determine the "S" type Pitot tube  $C_p$ , Dry Molecular Weight of the Stack Gas ( $M_d$ ) and Wet Molecular Weight ( $M_s$ ), Stack Gas Velocity, and Volumetric Flow Rate.

Pitot Tube Data:

$$C_{p_{std}} = 0.99$$

$$\Delta p_{\text{std}} = 0.31 \text{ in. H}_2\text{O}$$

$$\Delta p_{\text{Test}} = 0.42 \text{ in. H}_2\text{O}$$

#### Orsat Analysis

$$\text{CO}_2 = 13\%$$

$$\text{O}_2 = 6\%$$

$$\text{CO} = 1\%$$

$$\text{N}_2 = 79\%$$

#### Stack Data

$$(t_s)_{\text{avg}} = 350^\circ\text{F}$$

$$(\Delta p_{\text{avg}}) = 0.59 \text{ in. H}_2\text{O} \quad \text{Note: this equals } (\sqrt{\Delta p_{\text{ave}}})^2$$

$$P_s = 29.00 \text{ in. Hg}$$

$$B_{\text{ws}} = 10\%$$

$$A_s = 1200 \text{ ft.}^2$$

Answers:

$$C_p = 0.851$$

$$M_d = 30.041\text{b}/1\text{b-mole}$$

$$M_s = 28.841\text{b}/1\text{b-mole}$$

$$v_s = 54.98 \text{ ft/sec}$$

$$Q_s = 1.35 \times 10^8 \text{ dscfh}$$

#### Problem 6.

Using the given information calculate the Concentration of Particulate in the Gas Stream ( $c_s$ ), Moisture Content ( $B_{\text{ws}}$ ), and % Isokinetic for the test

Volume metered = 50 ft<sup>3</sup>

$p_v = 29.5 \text{ in. Hg.}$

$\Delta H = 1.5 \text{ in. H}_2\text{O}$

$t_m = 100^\circ\text{F}$

$t_s = 300^\circ\text{F}$

$\theta = 60 \text{ minutes}$

$v_s = 48.0 \text{ ft./sec.}$

$P_s = 29.00 \text{ in. Hg.}$

$A_n = 0.0003408 \text{ ft.}^2$

Total H<sub>2</sub>O collected (condenser and silica) = 100 ml

Particulate Catch ( $M_n$ ) = 100 mg

Answers:

$V_{m_{\text{std}}} = 46.64 \text{ ft.}^3$

$B_{ws} = 9.186\%$

$c_s = 0.033 \text{ gr./DSCF}$

$\%I = 129.7\%$

# **TECHNICAL REPORT DATA**

*(Please read Instructions on the reverse before completing)*

1. REPORT NO. EPA-450/2-79-007		2.		3. RECIPIENT'S ACCESSION NO.	
4. TITLE AND SUBTITLE APTI Course 450 Source Sampling for Particulate Pollutants Student Workbook				5. REPORT DATE December 1979	
				6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S)				8. PERFORMING ORGANIZATION REPORT NO.	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Northrop Services, Inc. P. O. Box 12313 Research Triangle Park, NC 27709				10. PROGRAM ELEMENT NO. B18A2C	
				11. CONTRACT/GRANT NO. 68-02-2374	
12. SPONSORING AGENCY NAME AND ADDRESS U.S. Environmental Protection Agency Manpower and Technical Information Branch Research Triangle Park, NC 27711				13. TYPE OF REPORT AND PERIOD COVERED Student Workbook	
				14. SPONSORING AGENCY CODE	
15. SUPPLEMENTARY NOTES EPA Project Officer for this workbook is R. E. Townsend, EPA, MD-17, ERC, RTP, NC					
16. ABSTRACT This workbook is used in conjunction with Course #450, "Source Sampling for Particulate Pollutants", as designed and presented by the EPA Air Pollution Training Institute (APTI). The workbook includes course objectives, lecture aides, calculation problems, and instructions for the course laboratory exercises. Tables of nomenclature, source sampling forms, and representations of selected course visual materials are given to aide the student in his understanding of EPA Federal reference method 5 for sampling particulate matter from stationary sources. The workbook is not meant to stand on its own, but is to be used with the course manual, EPA-450/2-79-006 during the lecture and laboratory sessions of the training course. An instructor's manual (EPA 450/2-80-003) entitled "Source Sampling for Particulate Pollutants" is also available for use in presenting the training course.					
17. KEY WORDS AND DOCUMENT ANALYSIS					
a. DESCRIPTORS		b. IDENTIFIERS/OPEN ENDED TERMS		c. COSATI Field/Group	
Gas Sampling Collection Filtered Particle Sampling Air Pollution Measurement Dust Calibrating		Stack Sampling Particle Measurement		14B 14D	
18. DISTRIBUTION STATEMENT available from NTIS address		19. SECURITY CLASS (This Report) Unclassified		21. NO. OF PAGES 187	
		20. SECURITY CLASS (This page) Unclassified		22. PRICE	