

EPA-600/4-77-007  
JANUARY 1977

Environmental Monitoring Series

# DETERMINATION OF HYDROGEN SULFIDE IN REFINERY FUEL GASES



Environmental Monitoring and Support Laboratory  
Office of Research and Development  
U.S. Environmental Protection Agency  
Research Triangle Park, North Carolina 27711

## **RESEARCH REPORTING SERIES**

Research reports of the Office of Research and Development, U.S. Environmental Protection Agency, have been grouped into five series. These five broad categories were established to facilitate further development and application of environmental technology. Elimination of traditional grouping was consciously planned to foster technology transfer and a maximum interface in related fields. The five series are:

1. Environmental Health Effects Research
2. Environmental Protection Technology
3. Ecological Research
4. Environmental Monitoring
5. Socioeconomic Environmental Studies

This report has been assigned to the ENVIRONMENTAL MONITORING series. This series describes research conducted to develop new or improved methods and instrumentation for the identification and quantification of environmental pollutants at the lowest conceivably significant concentrations. It also includes studies to determine the ambient concentrations of pollutants in the environment and/or the variance of pollutants as a function of time or meteorological factors.

DETERMINATION OF HYDROGEN SULFIDE IN REFINERY FUEL GASES

BY

Joseph E. Knoll and M. Rodney Midgett  
Quality Assurance Branch  
Environmental Monitoring and Support Laboratory  
Research Triangle Park, North Carolina 27711

ENVIRONMENTAL MONITORING AND SUPPORT LABORATORY  
OFFICE OF RESEARCH AND DEVELOPMENT  
U.S. ENVIRONMENTAL PROTECTION AGENCY  
RESEARCH TRIANGLE PARK, NORTH CAROLINA 27711

## DISCLAIMER

This report has been reviewed by the Environmental Monitoring and Support Laboratory, U.S. Environmental Protection Agency, and approved for publication. Mention of trade names or commercial products does not constitute endorsement or recommendation for use.

## ABSTRACT

EPA Test Method 11 has been evaluated. In this study, the cadmium hydroxide/cadmium sulfate gas absorbing solution was found to be an efficient collector of thiols. Since thiols are iodimetrically active and often found present together with hydrogen sulfide in refinery fuel gases, they cause a serious interference in the method. The same problem was found to exist when several other gas absorbing solutions were studied. These included neutral cadmium sulfate, neutral zinc acetate, as well as buffered cadmium acetate, cadmium formate and zinc acetate solutions. Large interferences occurred when thiols were simultaneously present with hydrogen sulfide and coprecipitation took place. Further investigation produced an absorbing solution that is essentially free from thiol interference. This has been achieved using 0.16M  $\text{CdSO}_4$  solution, adjusted to pH 3.9 with  $\text{H}_2\text{SO}_4$ , which is effective for the collection of  $\text{H}_2\text{S}$  in the 70-700  $\text{mg}/\text{m}^3$  range, in the presence of up to 1800  $\text{mg}/\text{m}^3$  of  $\text{CH}_3\text{SH}$ .<sup>2</sup>

Sulfur dioxide in the 1300  $\text{mg}/\text{m}^3$  range was found to be effectively removed by the single midget impinger of 3 percent  $\text{H}_2\text{O}_2$  specified in Method 11. Less than 0.2% of the  $\text{H}_2\text{S}$  was removed by this reagent and interferences resulting from its evaporative entrainment were negligible. The peroxide solution also was shown to serve as a physical trap for other unwanted substances.

Compatibility of the absorbing solutions under study with iodimetric measurement was shown and cadmium sulfide precipitates aged for ten days did not differ from freshly prepared samples when analyzed.

Further studies were also made employing other substances often present in refinery fuel gases. No measurable interference resulted from the presence of carbon oxysulfide, dimethyl sulfoxide, ethene or thiophene. Acetaldehyde and acetone were observed to interfere at the 24000 and 48000  $\text{mg}/\text{m}^3$  level, respectively. The former substance was largely removed by the air flush procedure and the latter substance was trapped, to a large extent, in the peroxide solution.





A revised version of the test method is presented.

This report covers a period from January 1, 1974 to December 31, 1975 and work was accomplished as of December 31, 1975.

## CONTENTS

Abstract . . . . .	iii
Figures . . . . .	vi
Tables . . . . .	vii
Acknowledgments . . . . .	viii
1. Introduction . . . . .	1
2. Conclusions . . . . .	2
3. Experimental . . . . .	4
4. Results and Discussion . . . . .	6
References . . . . .	15
Appendices	
A. Method for the determination of hydrogen sulfide emissions from petroleum refinery fuel gases . . . . .	.16
B. Chemical processes relevant to Method 11 . . . . .	.28

## FIGURES

<u>Number</u>		<u>Page</u>
1	H <sub>2</sub> S Absorption Flow Apparatus . . . . .	3
2	Collection efficiency of H <sub>2</sub> S and CH <sub>3</sub> SH in zinc acetate solutions at various pH values. (  , H <sub>2</sub> S collection efficiency,  , CH <sub>3</sub> SH collection efficiency.) . . . . .	7
3	Collection efficiency of H <sub>2</sub> S and CH <sub>3</sub> SH in cadmium sulfate solution at various concentrations. (  , H <sub>2</sub> S collection efficiency,  , CH <sub>3</sub> SH collection efficiency.) . . . . .	8
4	H <sub>2</sub> S Sampling Train . . . . .	27

## TABLES

<u>Number</u>		<u>Page</u>
1	Interference Levels of Methanethiol in Hydrogen Sulfide Measurements . . . . .	9
2	Test of Removal of SO <sub>2</sub> Interference by 3% H <sub>2</sub> O <sub>2</sub> Solution .	12
3	Entrainment of Peroxide . . . . .	13
4	Sulfide Recovery as Percent of Added Na <sub>2</sub> S . . . . .	14



#### ACKNOWLEDGMENTS

The authors wish to thank Drs. J. B. Clements, W. J. Mitchell, and Mr. F. P. Scaringelli of this Agency, and Dr. G. W. Scheil of Midwest Research Institute for helpful discussions during the course of this research.

## SECTION 1

### INTRODUCTION

In view of the increasing national concern about toxic sulfur compounds in the atmosphere, the U.S. Environmental Protection Agency (EPA) has issued regulations that deal with the emission of sulfur dioxide into the atmosphere from the combustion of petroleum refinery fuel gases and process gases that contain hydrogen sulfide. In March 1974, a standard was promulgated that limited the emission of sulfur gases from fuel gas combustion devices by specifying that the fuel gas combusted contain no more than 230 mg/dscm of  $\text{H}_2\text{S}$ , or optionally, that the gases resulting from the combustion of fuel gas be treated in a manner which limits the release of  $\text{SO}_2$  into the atmosphere. The applicable performance test method for  $\text{H}_2\text{S}$ , designated EPA Method 11,<sup>2</sup> utilizes an alkaline  $\text{CdSO}_4$  solution to collect  $\text{H}_2\text{S}$ , which is later regenerated and measured iodimetrically. Other methods have also been developed for the analysis of gases containing  $\text{H}_2\text{S}$ , and recently the literature has been reviewed.<sup>3</sup> Two iodimetric procedures that have also been widely employed are the ASTM Method D2385-65-T,<sup>4</sup> which uses  $\text{CdSO}_4$  and a method which uses  $\text{Zn}(\text{C}_2\text{H}_3\text{O}_2)_2$ .<sup>5</sup>

In recognition of the acute need for accurate techniques, EPA's Environmental Monitoring and Support Laboratory (EMSL) has been given the task of evaluating the standardizing test procedures in current use. This task has included the investigation of interferences in Method 11. Iodometry is not specific for  $\text{H}_2\text{S}$ ; other substances that are often found present in refinery gases are also iodimetrically active. Among these, for example is  $\text{SO}_2$  and Method 11 includes a  $\text{H}_2\text{O}_2$  solution for the removal of  $\text{SO}_2$  from the gas under analysis, prior to its passage through the  $\text{H}_2\text{S}$  absorption solution.

Recent attention to the fact that thiols may also be important constituents of refinery fuel gases, prompted the present study which is mainly concerned with the elimination of interferences resulting from these substances. To this end, collection efficiencies of  $\text{H}_2\text{S}$  and  $\text{CH}_3\text{SH}$  were measured in several reagents, and the effects of varying concentration and pH were determined. Serious levels of interferences were found in all three of the methods cited above,<sup>2,4,5</sup> but a useful  $\text{H}_2\text{S}$  absorbing medium was developed. Some information was also obtained on the efficacy of removal of  $\text{SO}_2$  by the  $\text{H}_2\text{O}_2$  absorbing solution. And further, since entrained  $\text{H}_2\text{O}_2$  may itself interfere in subsequent analytical processes, a study was also made of the minimum quantity transported as a result of evaporation and its fate in the  $\text{H}_2\text{S}$  absorbing solution. Interferences resulting from several other substances commonly found in fuel gases were also briefly considered. These data are presented below.

## SECTION 2

### CONCLUSIONS

This investigation has produced an absorbing solution that is essentially free from thiol interferences for use in the measurement of  $\text{H}_2\text{S}$  in refinery gases. This has been achieved using 0.16 M  $\text{CdSO}_4$  solution adjusted to pH 3.0 with  $\text{H}_2\text{SO}_4$ , which is effective for the collection of  $\text{H}_2\text{S}$  in the 70-700  $\text{mg}/\text{m}^3$  range, in the presence of up to 1,800  $\text{mg}/\text{m}^3$  of  $\text{CH}_3\text{SH}$ . Recommendation of this solution as a substitute for the collecting medium now employed in EPA Method 11 is planned. (A revised version of the method is contained in Appendix A of this report.)

Serious thiol interferences were uncovered when neutral cadmium sulfate<sup>4</sup>, alkaline cadmium sulfate (current EPA Method 11),<sup>2</sup> neutral zinc acetate<sup>5</sup> as well as when buffered cadmium acetate, cadmium formate and zinc acetate solutions were used.

Sulfur dioxide in the 1,300  $\text{mg}/\text{m}^3$  range is effectively removed by a single impinger of 3 percent  $\text{H}_2\text{O}_2$ . Interferences caused by the evaporative entrainment of the latter compound are negligible.

No measurable interference resulted from the presence of carbon oxysulfide, ethene, dimethyl sulfoxide, or thiophene. Acetaldehyde and acetone were observed to interfere at the 2,400 and 48,000  $\text{mg}/\text{m}^3$  level, respectively.

Equations pertaining to the relevant chemical processes are tabulated in Appendix B.




Figure 1. H<sub>2</sub>S absorption flow apparatus.

### SECTION 3

#### EXPERIMENTAL

Since refinery fuel gases consist of mixtures of light hydrocarbons which cannot easily be duplicated in the laboratory,  $C_2H_6$  was selected as a diluent to prepare feed gases containing the sulfur compounds of interest. Hydrogen sulfide/ethane, methanethiol/nitrogen, sulfur dioxide/ethane mixed gases and ethane gas for further dilution obtained from a commercial supplier, were employed. The gas cylinders used were connected to the laboratory gas dilution system (shown in Figure 1) by means of 1/4" I.D. stainless steel tubing and joined with stainless steel Swagelock connectors. In each case, the gas passed through a Hoke Type 1335g4Y metering valve and into a Dwyer 1 to 9 l/min rotometer-type flow meter. The three gas inputs connected into the manifold through a T-joint and the combined gases passed through two, 200 ml mixing chambers. A second T-joint afforded symmetrical sampling ports to which the sampling trains could be connected and duplicate samples withdrawn. The system was operated slightly above atmospheric pressure and exhausted through a Hastings Model ALF-2KX Flow Meter, which was used to monitor flow and compute dilution factors. The sampling trains are described in Appendix A.

Cadmium sulfate/cadmium hydroxide, cadmium acetate, cadmium formate, cadmium sulfate/sulfuric acid and zinc acetate absorbing solutions were prepared from analytical grade reagents. Buffered absorbing solutions were prepared by mixing appropriate quantities of salt and acid and determining pH with a pH meter. Collection efficiencies of  $H_2S$  and  $CH_3SH$  were measured in these solutions over a range of pH values, employing gas streams containing diluted  $H_2S$  and  $CH_3SH$  (separately) and mixtures of  $H_2S$  and  $CH_3SH$ .

The gas sampling and analytical procedures described in Method 11<sup>2</sup> were followed, except as noted below. In practice, feed gas passed through a midjet bubbler containing 15 ml of 3 percent  $H_2O_2$  solution and then through three midjet impingers, each containing 15 ml of the absorbing solution under investigation. The gas was collected for 10 minutes at a flow rate of approximately one l/min, which was followed by a 15 minute air flush at the same flow rate. This is typical of the procedure followed in practical stack sampling. Impingers containing the absorbed sulfur compounds were extracted with acid-iodine solution and analyzed iodimetrically. An identical impinger extraction procedure was followed when measuring reagent blanks. In some instances, the contents of the hydrogen peroxide-containing impinger was analyzed for sulfate by the barium thorin method.

Possible interferences resulting from the vaporization and collection of  $\text{H}_2\text{O}_2$  were studied by passing 28.3 liters of air through 15 ml of 30 percent  $\text{H}_2\text{O}_2$  solution (cooled to  $0^\circ\text{C}$ ) and then through three impingers containing acid  $\text{CdSO}_4$  solution. The latter were then analyzed by the Method 11 procedure, which was modified as follows: Several drops of 1.0 N ammonium molybdate were added along with the acid-iodine solution to catalyze the reaction of peroxide with iodide ion. Though this reaction goes nearly to completion under the prevailing analytical conditions, the addition of catalyst was made to avoid variations resulting from incompleteness of reaction.

Interferences from substances other than thiols of sulfur dioxide were investigated as follows: Gases were introduced pure or diluted with nitrogen into the sampling train at a flow rate of 1 l/min for 10 minutes, followed by a 15 minute air flush at 1 l/min. Liquid substances were introduced directly into the  $\text{CdSO}_4$  absorbing solution and analyzed iodimetrically. When a significant analytical difference resulted, an atmosphere of the substance in question was generated by passing nitrogen gas through the liquid at  $0^\circ\text{C}$  and estimating gas phase concentrations from the vapor pressure. Approximately 10 liters of the resulting mixture were sampled, followed by a 15 liter air flush. When large quantities of active materials were collected, the recovered absorbing solution was diluted prior to analysis.

## SECTION 4

### RESULTS AND DISCUSSION

Several reagents were studied as absorption media for  $\text{H}_2\text{S}$  to determine suitability for use in the quantitative collection and separation of  $\text{H}_2\text{S}$  from thiols. Collection efficiencies of  $\text{H}_2\text{S}$  and  $\text{CH}_3\text{SH}$  were measured at various pH values. Figure 2 shows results obtained using zinc acetate/acetic acid solutions. Over the pH range of approximately 5 to 6, the collection efficiency of  $\text{H}_2\text{S}$  is near unity while that of  $\text{CH}_3\text{SH}$  is essentially negligible. However, when  $\text{Zn}(\text{C}_2\text{H}_3\text{O}_2)_2$  solutions buffered in this pH range were employed for the measurement of gas streams containing mixtures of  $\text{H}_2\text{S}$  and  $\text{CH}_3\text{SH}$ , considerable thiol was collected along with the  $\text{H}_2\text{S}$ , apparently as a result of the coprecipitation of  $\text{ZnS}$  and mercaptide. These data are shown in Table 1 along with the results of similar measurements made employing alkaline cadmium sulfate (EPA Method 11), buffered cadmium acetate, and cadmium formate solutions. The levels of interference encountered are unacceptably large for any of these reagents to be employed for the collection and separation of  $\text{H}_2\text{S}$  from thiols. Further these results demonstrate that unbuffered zinc acetate (pH 6.6) takes up large quantities of thiols, even when  $\text{H}_2\text{S}$  is absent. Since this reagent is occasionally employed in source sampling tests, potentially large thiol interferences must be expected from its use.

Collection efficiencies of  $\text{H}_2\text{S}$  and  $\text{CH}_3\text{SH}$  in neutral cadmium sulfate solutions were also measured and are shown in Figure 3. Neutral  $\text{CdSO}_4$  has been previously studied, and the ASTM Method (D2385-65-T) employs 0.57 M  $\text{CdSO}_4$  to separate  $\text{H}_2\text{S}$  from  $\text{CH}_3\text{SH}$  when concentrations of the latter compound do not exceed 23 mg/m<sup>3</sup>. However, in the  $\text{CH}_3\text{SH}$  range employed in the present study (0 - 900 mg/m<sup>3</sup>), significant  $\text{CH}_3\text{SH}$  collection was observed at that  $\text{CdSO}_4$  concentration, even in the absence of  $\text{H}_2\text{S}$ . Therefore, the ASTM Method does not work at these high thiol levels.

A study was also made of  $\text{CdSO}_4/\text{H}_2\text{SO}_4$  solutions for the absorption of  $\text{H}_2\text{S}$  from  $\text{CH}_3\text{SH}-\text{H}_2\text{S}$  feed gas mixtures. Table 1 lists results obtained using 0.16 M  $\text{CdSO}_4$  at several pH values, which show that thiol interference decreases with decreasing pH and at pH 3.0 does not exceed 4 percent of the  $\text{H}_2\text{S}$  concentration under analysis. The use of 0.16 M  $\text{CdSO}_4$  was also found to have additional advantages. It is sufficiently concentrated to assure essentially quantitative  $\text{H}_2\text{S}$  collection at pH 3.0 while at the same time providing some buffering against the acidity produced during  $\text{CdS}$  formation. Sulfate ions have only a weak buffer capacity, but at the concentration and pH employed, it is sufficient to assure that the pH of the absorbing solution is not reduced below the value at which  $\text{H}_2\text{S}$  absorption becomes inefficient, provided that the quantity of  $\text{H}_2\text{S}$  collected does not exceed 0.3 millimoles.




Figure 2. Collection efficiency of  $\text{H}_2\text{S}$  and  $\text{CH}_3\text{SH}$  in zinc acetate solutions at various pH values.






Figure 3. Collection efficiency of H<sub>2</sub>S and CH<sub>3</sub>SH in cadmium sulfate solution at various concentrations.

TABLE 1. INTERFERENCE LEVELS OF METHANETHIOL IN HYDROGEN SULFIDE MEASUREMENTS

Reagent	Absorbing Solution		Feed Gas Composition mg H <sub>2</sub> S/m <sup>3</sup>		Quantity Detected as mg H <sub>2</sub> S/m <sup>3</sup>	Excess as Percent of Added CH <sub>3</sub> SH
	M	pH	H <sub>2</sub> S	CH <sub>3</sub> SH <sup>a</sup>		
CdSO <sub>4</sub> /Cd(OH) <sub>2</sub>	0.017	7.2	0	329 <sup>b</sup>	391	118
Cd(OAc) <sub>2</sub> /HOAc	0.04	4.2	172	279	323	54
Cd(OOCH) <sub>2</sub> /HOOCH	0.04	3.5	153	295	202	17
CdSO <sub>4</sub> /H <sub>2</sub> SO <sub>4</sub>	0.16	4.0	333	129	346	10
CdSO <sub>4</sub> /H <sub>2</sub> SO <sub>4</sub>	0.16	3.3	333	129	342	7
CdSO <sub>4</sub> /H <sub>2</sub> SO <sub>4</sub>	0.16	3.0	106	308	110	1
CdSO <sub>4</sub> /H <sub>2</sub> SO <sub>4</sub>	0.16	3.0	333	129	337	3
Zn(OAc) <sub>2</sub> /HOAc	0.08	5.4	355	147	382	19
Zn(OAc) <sub>2</sub>	0.09	6.6	106	308	317	69

<sup>a</sup>CH<sub>3</sub>SH concentrations are listed as equivalent mg of H<sub>2</sub>S/m<sup>3</sup> at 20°C and 1 atm., and may be converted to mg CH<sub>3</sub>SH/m<sup>3</sup> values by multiplying by 2.82.

<sup>b</sup>Value specified by compressed gas supplier.

The results shown in Table 2 indicate that 3percent  $\text{H}_2\text{O}_2$  solutions are effective for the removal of  $\text{SO}_2$  interferences in  $\text{H}_2\text{S}$  measurements. Values measured after  $\text{SO}_2$  removal are statistically equivalent to the concentration of  $\text{H}_2\text{S}$  introduced into the feed gas. (The latter quantity had been determined by substituting an equivalent amount of  $\text{C}_2\text{H}_6$  diluent gas for the  $\text{SO}_2/\text{C}_2\text{H}_6$  employed.) A small but statistically significant quantity of  $\text{SO}_2$  remains, after passage through  $\text{H}_2\text{O}_2$  in gas streams where  $\text{H}_2\text{S}$  is absent. Marked  $\text{SO}_2$  interferences result when the peroxide absorbing solution is omitted. In further studies, barium-thorin analysis of  $\text{H}_2\text{O}_2$  solutions after passage of  $\text{H}_2\text{S}$ -containing feed gases showed that less than 0.2 percent of the quantity of  $\text{H}_2\text{S}$  sampled had been converted to sulfate by the peroxide.

No evidence was found that entrained peroxide is destroyed after it has been collected by acid cadmium sulfate solution. The quantity evaporated from 3 percent peroxide solution was too small to measure accurately, but could be detected. To test for these effects, a more concentrated solution was employed. Entrained peroxide from a 30 percent  $\text{H}_2\text{O}_2$  solution was collected in acid  $\text{CdSO}_4$  solution and measured iodimetrically.<sup>2</sup> Results are listed in Table 3 and are compared with a theoretical value. The latter quantity is the quantity of  $\text{H}_2\text{O}_2$  that would completely saturate a volume equal to the volume of gas passed through the peroxide solution during a typical sampling run (28.3l), at the temperature ( $0^\circ\text{C}$ ) and concentration of interest. This value was determined, employing values of the vapor pressure (0.272 mm) and activity coefficient (0.513) of  $\text{H}_2\text{O}_2$ , calculated from equations given by Scatchard et.al.<sup>9</sup> The measured results are approximately 40 percent of the calculated value; it is therefore possible that complete saturation of the gas stream may not have taken place during the sampling process. However, if the results of these observations are extrapolated, peroxide equivalent to approximately  $-4 \text{ mg } \text{H}_2\text{S}/\text{m}^3$  must be expected to be entrained by evaporation from the 3 percent  $\text{H}_2\text{O}_2$  solution employed in Method 11. This quantity is less than 2 percent of the applicable standard and of the same order of magnitude as the reagent blank and standard deviations, examples of which are given in Table 2. However, much larger interferences will result if portions of the hydrogen peroxide solution are transferred into the  $\text{H}_2\text{S}$  collecting impingers, so that caution must be exercised during sampling to avoid this occurrence.

No detectible iodometric measurement resulted from sampling carbon oxysulfide (20 percent in  $\text{N}_2$ ), undiluted ethene, dimethyl sulfoxide, ethanolamine or thiophene. Acetaldehyde and acetone react with iodine and produce unstable titration endpoints. However, the sampling process did not result in the complete collection of these compounds in the absorbing solution subjected to analysis. Acetone vapor was largely retained in the peroxide solution while some acetaldehyde was removed by the air flush. Based on the quantities actually measured, acetaldehyde at  $2,400 \text{ mg}/\text{m}^3$  and acetone at  $48,000 \text{ mg}/\text{m}^3$  concentrations would be required to produce an interference level equivalent to 10 percent of the applicable  $\text{H}_2\text{S}$  standard. The foregoing compounds were studied as examples of substances that might be found in refinery process gases.

Method 11 was further investigated by adding measured quantities of sodium sulfide to the absorbing solution. The resulting mixture containing CdS precipitate was then analyzed iodimetrically. These measurements enabled us to study the completeness of sulfide recovery in the analytical part of the method, i.e., in that part that includes processes such as the conversion of CdS to free  $H_2S$ , its partial escape into the gas phase, its reabsorption and its subsequent reaction with iodine. It separated out those effects that might have resulted from sampling. Some information about the aging of CdS precipitate also resulted from this investigation. These results are listed in Table 4. The quantities of sulfide employed corresponded to that which would have resulted from feed gases of from 85-280 mg  $H_2S/m^3$ . Recoveries differ from 100 percent by amounts that do not exceed 3 percent for all but one determination. The latter corresponded to an  $H_2S$  concentration that was only a third of the value of the promulgated standard. Table 4 also contains the results of the measurement of samples that were aged for ten days. No appreciable difference between aged and unaged samples could be found. The foregoing served as a check on the compatibility of the absorbing solution with iodimetric measurements and to show the absence of problems resulting from the time interval between sampling and analysis.

TABLE 2. TEST OF REMOVAL OF  $\text{SO}_2$  INTERFERENCE BY 3%  $\text{H}_2\text{O}_2$  SOLUTION

Sample	Feed Gas Composition mg $\text{H}_2\text{S}/\text{m}^3$ <sup>a</sup>		Iodimetrically Active Materials Found, mg $\text{H}_2\text{S}/\text{m}^3$	
	$\text{H}_2\text{S}$	$\text{SO}_2$ <sup>b</sup>	$\text{H}_2\text{O}_2$ Employed <sup>c</sup>	$\text{H}_2\text{O}_2$ Omitted
1	0	176	4.5	178
2	0	176	4.5	174
3	234	176	239	280
4	234	176	243	263
5	234	318	232	340
6	234	318	239	317

<sup>a</sup>

Standard deviations of  $\text{H}_2\text{S}$  values in Runs 3-6,  $\text{SO}_2$  in Runs 1-4 and  $\text{SO}_2$  in Runs 5 and 6 were 5, 2 and 6 mg  $\text{H}_2\text{S}/\text{m}^3$ , respectively.

<sup>b</sup>

$\text{SO}_2$  concentrations are listed as equivalent mg of  $\text{H}_2\text{S}/\text{m}^3$  at 20°C and 1 atm., and may be converted to the corresponding mg of  $\text{SO}_2/\text{m}^3$  values by multiplying by 1.88.

<sup>c</sup>

Average Reagent Blank: 12 mg  $\text{H}_2\text{S}/\text{m}^3$ ; std. dev. 3.

TABLE 3. ENTRAINMENT OF PEROXIDE<sup>a</sup>

<u>Run</u>	<u>Iodometrically Active Materials Detected Micromoles H<sub>2</sub>O<sub>2</sub></u>
1	20.5
2	31.0
3	25.9
4	28.4
mean	26.5 $\pm$ 4.5 <sup>b</sup>
theoretical	65.1

<sup>a</sup>  
From 30% H<sub>2</sub>O<sub>2</sub> solution at 0°C.

<sup>b</sup>  
Standard Deviation.

<sup>c</sup>  
Calculated using following constants: volume 28.3 l; vapor pressure, 0.272 mm; mole fraction, 0.3; activity coefficient, 0.513.

TABLE 4. SULFIDE RECOVERY AS PERCENT OF ADDED  $\text{Na}_2\text{S}$

$\text{Na}_2\text{S}$ taken millimoles	Sulfide measured millimoles	Percent recovery
0.1885	0.1940	102.9
0.1885	0.1933	102.5
0.0943	0.0954	101.1
0.0566	0.0612	108.1
0.1885	0.1829	97.0
0.1885 <sup>a</sup>	0.1829	97.0
0.1885 <sup>a</sup>	0.1839	97.6

<sup>a</sup>  
Samples aged for ten days.

## SECTION V

### REFERENCES

1. Federal Register, 39(47):9308-9323, March 8, 1974.
2. Ibid., pp. 9321-9323.
3. Kniebes, D. V., "Sulfur-Containing Gases," in The Analytical Chemistry of Sulfur and its Compounds, Part I, J. H. Karchmer, pp. 145-181, Wiley-Interscience, N. Y., 1970.
4. Annual Book of ASTM Standards, Part 24, D2385-65T, American Society for Testing and Materials, Philadelphia, Pa., 1974.
5. Wilson, A. J., "New Test Methods Submitted by the South Coast Air Basin Technical Advisory Committee," Stack Sampling News, 3(4):2-6, 1975.
6. Federal Register, 36(247):24890-28891, December 23, 1971.
7. Riensenfield, F. C., and Orbach, H. K., Petroleum Engineer, 25, c-32, c-34, c-38, June 1953.
8. Scott, W. W., "Standard Methods of Chemical Analysis" Vol. II, Fifth Ed., 2180, D. Van Nostrand Co., N. Y., 1939
9. Scatchard, G., Kavanagh, G. M., and Ticknor, L. B., J. Am. Chem. Soc., 74:3715, 1952.



APPENDIX A

METHOD FOR THE DETERMINATION OF HYDROGEN SULFIDE EMISSIONS  
FROM PETROLEUM REFINERY FUEL GASES

DISCLAIMER

This method has been assembled from available information based upon extensive laboratory and field evaluations followed by interlaboratory collaborative testing. However, it does not represent an official EPA position at this time.

## 1.0 Principle and Applicability

### 1.1 Principle

Hydrogen sulfide ( $\text{H}_2\text{S}$ ) is collected from a source in a series of midget impingers and absorbed in pH 3.0 cadmium sulfate solution to form cadmium sulfide ( $\text{CdS}$ ). The latter compound is then measured iodometrically. An impinger containing hydrogen peroxide is included to remove  $\text{SO}_2$  as an interfering species.

### 1.2 Applicability

This method is applicable for the determination of hydrogen sulfide emissions from stationary sources only when specified by the test procedures for determining compliance with the new source performance standards.

## 2.0 Range and Sensitivity

The limit of detection is approximately  $8 \text{ mg/m}^3$  (6 ppm). The maximum of the range is  $740 \text{ mg/m}^3$  (520 ppm).

## 3.0 Interferences

Any compound that reduces iodine or oxidizes iodide ion will interfere in this procedure, provided it is collected in the cadmium sulfate impingers. Sulfur dioxide in concentrations of up to  $2,600 \text{ mg/m}^3$  is eliminated by the hydrogen peroxide solution. Thiols coprecipitate with hydrogen sulfide. In the absence of  $\text{H}_2\text{S}$ , only traces of thiols are collected. When methane- and ethane-thiols at a total level of  $300 \text{ mg/m}^3$  are present in addition to  $\text{H}_2\text{S}$ , the results vary from 2% low at an  $\text{H}_2\text{S}$  concentration of  $400 \text{ mg/m}^3$  to 14% high at an  $\text{H}_2\text{S}$  concentration of  $100 \text{ mg/m}^3$ . Carbon oxysulfide of 20% does not interfere. Certain carbonyl-containing compounds react with iodine and produce recurring end points. However, acetaldehyde and acetone at concentrations of 1 and 3%, respectively, do not interfere.

Entrained hydrogen peroxide produces a negative interference equivalent to 100% of that of an equimolar quantity of hydrogen sulfide. Avoid the ejection of hydrogen peroxide into the cadmium sulfate impingers.

## 4.0 Precision and Accuracy

Collaborative testing has shown the within-laboratory coefficient of variation to be 2.2% and the overall coefficient of variation to be 5.0%. The method bias was shown to be -4.8% when only  $\text{H}_2\text{S}$  was present.

In the presence of the interferences cited in 3.0 above, the bias was positive at low  $\text{H}_2\text{S}$  concentrations and negative at higher concentrations. At  $230 \text{ mg H}_2\text{S/m}^3$ , the level of the compliance standard, the bias was +2.7%. Thiols had no effect on the precision.

## 5.0 Apparatus

### 5.1 Sampling Train

5.1.1 Sampling line - Six to 7 mm (1/4 in.) Teflon\* tubing to connect sampling train to sampling valve. Depending on sampling stream pressure, a pressure-reduction regulator may be required just prior to the Teflon sampling line.

If significant amounts of water or amine are present in the sample stream, a corrosion-resistant cold trap should be used immediately after the sample tap. The trap should not be operated below  $0^\circ\text{C}$  to avoid condensation of  $\text{C}_3$  or  $\text{C}_4$  hydrocarbons.

5.1.2 Impingers - Five midjet impingers, each with 30 ml capacity. The internal diameter of the impinger tip must be  $1.00 \text{ mm} \pm 0.05 \text{ mm}$ . The impinger tip must be positioned 4 to 6 mm from the bottom of the impinger.

5.1.3 Glass or Teflon connecting tubing for the impingers.

5.1.4 Ice bath container - To maintain absorbing solution at a low temperature.

5.1.5 Silica gel drying tube - To protect pump and dry gas meter.

5.1.6 Sampling valve - Needle valve or equivalent to adjust gas flow rate. Stainless steel or other corrosion-resistant material.

5.1.7 Dry gas meter - Sufficiently accurate to measure sample volume to within 1% and calibrated with a wet test meter over the range of flow rates used in sampling. Gas volume for one dial revolution must not be more than 10 liters. The gas meter should have a gas petcock or equivalent on the outlet connector which can be closed during the leak test.

5.1.8 Flow meter - Rotameter or equivalent, to measure a 0.5 to 2.0 liters/min (1 to 4 CFH) flow rate.

---

\* Mention of trade names of specific products does not constitute endorsement by the Environmental Protection Agency.

5.1.9 Graduated cylinder - 25 ml size.

5.1.10 Barometer - To measure atmospheric pressure to within  $\pm 2.5$  mm (0.1 in.) Hg.

5.1.11 U-Tube manometer - 0-30 cm water column. For leak check procedure.

5.1.12 Rubber squeeze bulb - To pressurize train for leak check.

5.1.13 Tee, pinchclamp, and connecting tubing - For leak check.

5.1.14 Vacuum pump - Required for air purge.

5.1.15 Needle valve or orifice - To set air purge flow to 1 liter/min.

5.1.16 Tube packed with activated carbon - To filter air during purge.

5.1.17 Volumetric flask - One 1,000 ml.

5.1.18 Volumetric pipette - One 15 ml.

## 5.2 Sample Recovery

5.2.1 Sample container - Iodine flask, glass-stoppered; 500 ml size.

5.2.2 Pipette - 50 ml volumetric type.

5.2.3 Graduated cylinders - One each 25 and 250 ml.

5.2.4 Flasks - 125 ml, Erlenmeyer.

5.2.5 Wash bottle.

5.2.6 Volumetric flasks - Three 1,000 ml.

## 5.3 Analysis

5.3.1 Flask - 500 ml glass-stoppered iodine flask.

5.3.2 Burette - 50 ml.

5.3.3 Flask - 125 ml Erlenmeyer

5.3.4 Pipettes, volumetric - One 25 ml; two each 50 and 100 ml.

5.3.5 Volumetric flasks - One 1,000 ml; two 500 ml.

5.3.6 Graduated cylinders - One each 10 and 100 ml.

## 6.0 Reagents

Unless otherwise indicated, it is intended that all reagents conform to the specifications established by the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available. Otherwise, use best available grade.

### 6.1 Sampling

6.1.1 Cadmium sulfate absorbing solution - Dissolve 41.0 g of  $3\text{CdSO}_4 \cdot 8\text{H}_2\text{O}$  and 15.0 ml of 0.1 M sulfuric acid in a 1-liter volumetric flask that contains approximately 3/4 liter of deionized distilled water. Dilute to volume with deionized water. Mix thoroughly. pH should be  $3.0 \pm 0.1$ . Add 10 drops of Dow-Corning Antifoam B.\* Shake well before use. If Antifoam B is not used, the alternate acidified iodine extraction procedure must be used.

6.1.2 Hydrogen peroxide, 3% - Dilute 30% hydrogen peroxide to 3% as needed. Prepare fresh daily.

6.1.3 Water - Deionized, distilled, to conform to ASTM specifications D1193-72, Type 3.

### 6.2 Sample Recovery

6.2.1 Hydrochloric acid solution (HCl), 3 M - Add 240 ml of concentrated HCl (specific gravity 1.19) to 500 ml of deionized, distilled water in a 1-liter volumetric flask. Dilute to 1 liter with deionized water. Mix thoroughly.

6.2.2 Iodine solution, 0.1 N - Dissolve 24 g of potassium iodide (KI) in 30 ml of deionized, distilled water. Add 12.7 g of resublimed iodine ( $\text{I}_2$ ) to the potassium iodide solution. Shake the mixture until the iodine is completely dissolved. If possible, let the solution stand overnight in the dark. Slowly dilute the solution to 1 liter with deionized, distilled water, with swirling. Filter the solution if it is cloudy. Store solution in a brown-glass reagent bottle.

---

\* Mention of trade names of specific products does not constitute endorsement by the Environmental Protection Agency.

6.2.3 Standard iodine solution, 0.01 N - Pipette 100.0 ml of the 0.1 N iodine solution into a 1 liter volumetric flask and dilute to volume with deionized, distilled water. Standardize daily as in Section 8.1. This solution must be protected from light. Reagent bottles and flasks must be kept tightly stoppered.

### 6.3 Analysis

6.3.1 Sodium thiosulfate solution, standard 0.1 N - Dissolve 24.8 g of sodium thiosulfate pentahydrate ( $\text{Na}_2\text{S}_2\text{O}_3 \cdot 5\text{H}_2\text{O}$ ) or 15.8 g of anhydrous sodium thiosulfate ( $\text{Na}_2\text{S}_2\text{O}_3$ ), in 1 liter of deionized, distilled water and add 0.01 g of anhydrous sodium carbonate ( $\text{Na}_2\text{CO}_3$ ) and 0.4 ml of chloroform ( $\text{CHCl}_3$ ) to stabilize. Mix thoroughly by shaking or by aerating with nitrogen for approximately 15 min and store in a glass-stoppered, reagent bottle. Standardize as in Section 8.2 below.

6.3.2 Sodium thiosulfate solution, standard 0.01 N - Pipette 50.0 ml of the standard 0.1 N thiosulfate solution into a volumetric flask and dilute to 500 ml with distilled water.

6.3.3 Starch indicator solution - Suspend 10 g of soluble starch in 100 ml of deionized, distilled water and add 15 g of potassium hydroxide (KOH) pellets. Stir until dissolved, dilute with 900 ml of deionized distilled water and let stand for 1 hr. Neutralize the alkali with concentrated hydrochloric acid, using an indicator paper similar to Alkacid test ribbon, then add 2 ml of glacial acetic acid as a preservative.

(Note 1: Test starch indicator solution for decomposition by titrating with 0.01 N iodine solution 4 ml of starch solution in 200 ml of distilled water that contains 1 g potassium iodide. If more than 4 drops of the 0.01 N iodine solution are required to obtain the blue color, a fresh solution must be prepared.)

## 7.0 Procedure

### 7.1 Sampling

7.1.1 Assemble the sampling train as shown in Figure 1, connecting the five midjet impingers in series. Place 15 ml of 3% hydrogen peroxide solution in the first impinger. Leave the second impinger empty. Place 15 ml of the cadmium sulfate absorbing solution in the third, fourth, and fifth impingers. Place the impinger assembly in an ice bath container and place crushed ice around the impingers. Add more ice during the run, if needed.

7.1.2 Connect the rubber bulb and manometer to first impinger, as shown in Figure 1. Close the petcock on the dry gas meter outlet. Pressurize the train to 30-cm water pressure with the bulb and close off tubing connected to rubber bulb. Train must hold a 30-cm water pressure with not more than a 1 cm drop in pressure in a 1-min interval. Stopcock grease is acceptable for sealing ground glass joints.

7.1.3 Purge the connecting line between the sampling valve and the first impinger. Close valve and connect the sample line to the train. Open the petcock on the dry gas meter outlet. Record the initial reading on the dry gas meter.

7.1.4 Open the sampling valve and then adjust the valve to obtain a rate of approximately 1 liter/min. Maintain a constant flow rate during the test. Record the meter temperature.

7.1.5 Sample for at least 10 min. At the end of the sampling time, close the sampling valve and record the final volume and temperature readings.

7.1.6 Disconnect the impinger train from the sampling line. Connect the charcoal tube and the pump, as shown in Figure 1. Purge the train with clean ambient air for 15 min to ensure that all  $H_2S$  is removed from the hydrogen peroxide. For sample recovery, cap the open ends and remove to a clean area that is away from sources of heat. The area should be well lighted, but not exposed to direct sunlight.

## 7.2 Sample Recovery

7.2.1 Discard the contents of the hydrogen peroxide impinger. Carefully rinse the contents of the third, fourth, and fifth impingers into a 500 ml iodine flask.

(Note 2: The impingers normally have only a thin film of cadmium sulfide remaining after a water rinse. If Antifoam B was not used or if significant quantities of yellow cadmium sulfide remain in the impingers, the alternate recovery procedure must be used.)

7.2.2 Pipette exactly 50 ml of 0.01 N iodine solution into a 125-ml Erlenmeyer flask. Add 10 ml of 3 M HCl to the solution. Quantitatively rinse the acidified iodine into the iodine flask. Stopper the flask immediately and shake briefly.

7.2.2 (Alternate) Extract the remaining cadmium sulfide from the third, fourth, and fifth impingers using the acidified iodine solution. Immediately after pouring the acidified iodine into an impinger, stopper it and shake for a few moments, then transfer the liquid to the iodine flask.

Do not transfer any rinse portion from one impinger to another; transfer it directly to the iodine flask. Once the acidified iodine solution has been poured into any glassware containing cadmium sulfide, the container must be tightly stoppered at all times except when adding more solution, and this must be done as quickly and carefully as possible. After adding any acidified iodine solution to the iodine flask, allow a few minutes for absorption of the  $H_2S$  before adding any further rinses. Repeat the iodine extraction until all cadmium sulfide is removed from the impingers. Extract that part of the connecting glassware that contains visible cadmium sulfide.

Quantitatively rinse all of the iodine from the impingers, connectors, and the beaker into the iodine flask using deionized, distilled water. Stopper the flask and shake briefly.

7.2.3 Allow to stand about 30 min in the dark for absorption of the  $H_2S$  into the iodine, then complete the titration analysis as in Section 7.3.

(Note 3: CAUTION! Iodine evaporates from acidified iodine solutions.

Samples to which acidified iodine have been added may not be stored, but must be analyzed in the time schedule stated above in 7.2.3.)

7.2.4 Prepare a blank by adding 45 ml of cadmium sulfate absorbing solution to an iodine flask. Pipette exactly 50 ml of 0.01 iodine solution into a 125-ml Erlenmeyer flask. Add 10 ml of 3 M HCl. Follow the same impinger extracting and quantitative rinsing procedure carried out in sample analysis. Stopper the flask, shake briefly, let stand 30 min in the dark, and titrate with the samples.

(Note 4: The blank must be handled by exactly the same procedure as that used for the samples.)

### 7.3 Analysis

(Note 5: Titration analyses should be conducted at the sample-cleanup area in order to prevent loss of iodine from the sample. Titration should never be made in direct sunlight.)

7.3.1 Using 0.01 N sodium thiosulfate solution, rapidly titrate samples in iodine flasks using gentle mixing, until solution is light yellow. Add 4 ml of starch indicator solution and continue titrating slowly until the blue color just disappears. Record  $V_t$ , the volume of sodium thiosulfate solution used (ml).

7.3.2 Titrate the blanks in the same manner as the samples. Run blanks each day until replicate values agree within 0.05 ml. Average the replicate titration values which agree within 0.05 ml.



## 8.0 Calibration and Standards

8.1 Standardize the 0.01 N iodine solution daily as follows: Pipette 25 ml of the iodine solution into a 125-ml Erlenmeyer flask. Add 2 ml of 3 M HCl. Titrate rapidly with standard 0.01 N thiosulfate solution until the solution is light yellow, using gentle mixing. Add four drops of starch indicator solution and continue titrating slowly until the blue color just disappears. Record  $V_t$ , the volume of thiosulfate solution used (ml). Repeat until replicate values agree within 0.05 ml. Average the replicate titration values which agree within 0.05 ml and calculate the exact normality of the iodine solution using Equation 9.1. Repeat the standardization daily.

8.2 Standardize the 0.1 N thiosulfate solution as follows: Oven-dry potassium dichromate ( $K_2Cr_2O_7$ ) at 180 to 200°C. Weigh to the nearest milligram, 2 g of potassium dichromate into a 500 ml volumetric flask, dissolve in deionized, distilled water and dilute to exactly 500 ml. In a 500 ml iodine flask, dissolve approximately 3 g of potassium iodide (KI) in 45 ml of deionized, distilled water, then add 10 ml of 3 M hydrochloric acid solution. Pipette 50 ml of the dichromate solution into this mixture. Gently swirl the solution once and allow it to stand in the dark for 5 min. Dilute the solution with 100 to 200 ml of deionized distilled water, washing down the sides of the flask with part of the water. Titrate with 0.1 N thiosulfate until the solution is light yellow. Add 4 ml of starch indicator and continue titrating slowly to a green end point. Record  $V_t$ , the volume of thiosulfate solution used (ml). Repeat until replicate analyses agree within 0.05 ml. Calculate the normality using Equation 9.2. Repeat the standardization each week.

## 9.0 Calculations

Carry out calculations retaining at least one extra decimal figure beyond that of the acquired data. Round off results only after the final calculation.

### 9.1 Normality of the Standard Iodine Solution.

$$N_I = \frac{N_T V_T}{V_I}$$

where  $N_I$  = normality of iodine, g-eq/liter;  
 $V_I$  = volume of iodine used, ml;  
 $N_T$  = normality of sodium thiosulfate, g-eq/liter; and  
 $V_T$  = volume of sodium thiosulfate used, ml.

## 9.2 Normality of the Standard Thiosulfate Solution.

$$N_T = 2.04 \frac{W}{V_T}$$

where  $W$  = weight of  $K_2Cr_2O_7$  used, g;  
 $V_T$  = volume of  $Na_2S_2O_3$  used, ml;  
 $N_T$  = normality of standard thiosulfate solution, g-eq/liter; and  
 2.04 = conversion factor.

$$= \frac{(6 \text{ eq } I_2/\text{mole } K_2Cr_2O_7) (1,000 \text{ ml/liter})}{(294.2 \text{ g } K_2Cr_2O_7/\text{mole}) (10 \text{ aliquot factor})}$$

9.3 Dry Gas Volume - Correct the sample volume measured by the dry gas meter to standard conditions (20°C) and 760 mm Hg.

$$V_{mstd} = V_m \left( \frac{T_{std}}{T_m} \right) \left( \frac{P_{bar}}{P_{std}} \right)$$

where  $V_{mstd}$  = volume at standard conditions of gas sample through the dry gas meter, standard liters;  
 $V_m$  = volume of gas sample through the dry gas meter (meter conditions), liters;  
 $T_{std}$  = absolute temperature at standard conditions, 293 K;  
 $T_m$  = average dry gas meter temperature, °K;  
 $P_{bar}$  = barometric pressure at the orifice meter, mm Hg; and  
 $P_{std}$  = absolute pressure at standard conditions, 760 mm Hg.

9.4 Concentration of  $H_2S$  - Calculate the concentration of  $H_2S$  in the gas stream at standard conditions using equation:

$$C_{H_2S} = \frac{K[(V_I N_I - V_T N_T) \text{ sample} - (V_I N_I - V_T N_T) \text{ blank}]}{V_{mstd}}$$

where (metric units):

$C_{H_2S}$  = concentration of  $H_2S$  at standard conditions, mg/dscm;  
 $K$  = conversion factor =  $17.0 \times 10^3$

$$= \frac{(34.07 \text{ g/mole } H_2S) (1,000 \text{ liters/m}^3) (1,000 \text{ mg/g})}{(1,000 \text{ ml/liter}) (2H_2S \text{ eq/mole})}$$

$V_I$  = volume of standard iodine solution, ml;  
 $N_I$  = normality of standard iodine solution, g-eq/liter;  
 $V_T$  = volume of standard sodium thiosulfate solution, ml;  
 $N_T$  = normality of standard sodium thiosulfate solution,  
g-eq/liter; and  
 $V_{mstd}$  = dry gas volume at standard conditions, liters.

## 10.0 Stability

The absorbing solution is stable for at least 1 month. Sample recovery and analysis should begin within 1 hr of sampling to minimize oxidation of the acidified cadmium sulfide. Once iodine has been added to the sample, the remainder of the analysis procedure must be completed according to Sections 7.2.2, 7.2.3, and 7.3.

## 11.0 References

- 11.1 "Determination of Hydrogen Sulfide, Ammoniacal Cadmium Chloride Method, API Method 772-54." In: Manual on Disposal of Refinery Wastes, Vol. V: Sampling and Analysis of Waste Gases and Particulate Matter, American Petroleum Institute, Washington, D.C., 1954.
- 11.2 Tentative Method of Determination of Hydrogen Sulfide and Mercaptan Sulfur in Natural Gas, Natural Gas Processors Association, Tulsa, Oklahoma, NGPA Publication No. 2265-65, 1965.
- 11.3 Knoll, J. E., M. R. Midgett, "Determination of Hydrogen Sulfide in Refinery Fuel Gases," Environmental Monitoring Series, Office of Research and Development, U.S. EPA, NC 27711.
- 11.4 Scheil, G. W., and M. C. Sharp, "Standardization of Method 11 at a Petroleum Refinery," Midwest Research Institute Draft Report for U.S. EPA, Office of Research and Development, RTP, NC 27711, EPA Contract No. 68-02-1098, August 1976.





Figure 4 -  $H_2S$  Sampling Train

APPENDIX B  
CHEMICAL PROCESSES RELEVANT TO METHOD 11


## Appendix II. Chemical Processes Relevant to Method 11.

The following are the reactions pertinent to the processes discussed in the main body of this report.


### Sample analysis:




### Standardization:



### Sulfur dioxide removal:



### Interference :



**TECHNICAL REPORT DATA**  
(Please read Instructions on the reverse before completing)

1. REPORT NO.		2.	3. RECIPIENT'S ACCESSION NO.	
4. TITLE AND SUBTITLE DETERMINATION OF HYDROGEN SULFIDE IN REFINERY FUEL GASES			5. REPORT DATE	
			6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S) Joseph E. Knoll and M. Rodney Midgett			8. PERFORMING ORGANIZATION REPORT NO.	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Quality Assurance Branch Environmental Monitoring and Support Laboratory U.S. Environmental Protection Agency Research Triangle Park, North Carolina 27711			10. PROGRAM ELEMENT NO. 1HD621	
			11. CONTRACT/GRANT NO.	
12. SPONSORING AGENCY NAME AND ADDRESS Environmental Monitoring and Support Laboratory Office of Research and Development U.S. Environmental Protection Agency Research Triangle Park, North Carolina 27711			13. TYPE OF REPORT AND PERIOD COVERED Final Report	
			14. SPONSORING AGENCY CODE EPA-ORD	
15. SUPPLEMENTARY NOTES				
16. ABSTRACT <p>Several widely employed test methods for the iodimetric measurement of hydrogen sulfide in refinery fuel gases are shown to suffer from serious thiol interferences. An absorbing solution consisting of 0.16 M cadmium sulfate/sulfuric acid at pH 3.0<sub>3</sub> is shown to be effective for the collection of hydrogen sulfide in the 70-700 mg/m<sup>3</sup> range and to be essentially free from interference by up to 1800 mg/m<sup>3</sup> of methane-thiol. When combined with a single 3 percent hydrogen peroxide impinger, sulfur dioxide interferences of up to 1,300 mg/m<sup>3</sup> are also removed. No measureable interference results from the presence of carbon oxysulfide, ethene, dimethyl sulfoxide, or thiophene. Acetaldehyde and acetone are observed to interfere at the 2,400 and 48,000 mg/m<sup>3</sup> level, respectively. It is proposed that the absorption solution described here be substituted for the cadmium hydroxide/cadmium sulfate mixture used in the EPA test method (Method 11) for determining the hydrogen sulfide content of refinery fuel gases.</p>				
17. KEY WORDS AND DOCUMENT ANALYSIS				
a. DESCRIPTORS		b. IDENTIFIERS/OPEN ENDED TERMS		c. COSATI Field/Group
Air pollution Hydrogen sulfide		Iodimetric measurement Refinery fuel gases Thiols		13b
18. DISTRIBUTION STATEMENT Release to Public		19. SECURITY CLASS (This Report) Unclassified		21. NO. OF PAGES 37
		20. SECURITY CLASS (This page) Unclassified		22. PRICE