

EPA-600/D-84-265
October 1984

Guidelines for Decontaminating Buildings, Structures,
and Equipment at Superfund Sites

M. P. Esposito, J. McArdle, and J. S. Greber
PEDCo Environmental, Inc.
Cincinnati, Ohio

R. Clark
Battelle Columbus Laboratories
Columbus, Ohio

EPA Contract 68-03-3190

EPA Project Officer
Naomi P. Barkley

MUNICIPAL ENVIRONMENTAL RESEARCH LABORATORY
OFFICE OF RESEARCH AND DEVELOPMENT
U.S. ENVIRONMENTAL PROTECTION AGENCY
CINCINNATI, OHIO 45268

TECHNICAL REPORT DATA (Please read Instructions on the reverse before completing)		
1 REPORT NO. EPA-600/D-84-265	2.	3 RECIPIENT'S ACCESSION NO PB85 120996
4 TITLE AND SUBTITLE Guidelines for Decontaminating Buildings, Structures and Equipment at Superfund Sites	5. REPORT DATE October 1984	
	6. PERFORMING ORGANIZATION CODE	
7 AUTHOR(S) M. P. Esposito, J. McArdle, J. S. Greber, and R. Clark*	8. PERFORMING ORGANIZATION REPORT NO.	
9 PERFORMING ORGANIZATION NAME AND ADDRESS PEDCo Environmental, Inc. *Battelle Columbus 11499 Chester Road Laboratories Cincinnati, Ohio 45246 Columbus, OH	10. PROGRAM ELEMENT NO. TE371A	
	11 CONTRACT/GRANT NO 68-03-3190	
12 SPONSORING AGENCY NAME AND ADDRESS Municipal Environmental Research Laboratory--Cin., OH Office of Research and Development U.S. Environmental Protection Agency Cincinnati, Ohio 45268	13. TYPE OF REPORT AND PERIOD COVERED Interim - 9/83-6/84	
	14. SPONSORING AGENCY CODE EPA/600/14-	
15 SUPPLEMENTARY NOTES Naomi P. Barkley, Project Officer 513/684-7875		
16 ABSTRACT <p>This paper identifies contaminants most likely to occur in buildings and structures or on removal equipment at remedial sites. Steps for developing a general decontamination strategy are enumerated. The paper also announces a User's Guide or handbook that will be published by the U.S. EPA as the final product of Contract 68-03-3190.</p> <p>Additional research needs concerning building decontamination are identified and the need for documentation and verification of methods currently in use is stressed.</p>		
17. KEY WORDS AND DOCUMENT ANALYSIS		
a. DESCRIPTORS	b. IDENTIFIERS/OPEN ENDED TERMS	c. COSATI Field/Group
18 DISTRIBUTION STATEMENT RELEASE TO PUBLIC	19 SECURITY CLASS (This Report) UNCLASSIFIED	21 NO OF PAGES 15
	20 SECURITY CLASS (This page) UNCLASSIFIED	22 PRICE

NOTICE

This document has been reviewed in accordance with U.S. Environmental Protection Agency policy and approved for publication. Mention of trade names or commercial products does not constitute endorsement or recommendation for use.

GUIDELINES FOR DECONTAMINATING BUILDINGS, STRUCTURES, AND
EQUIPMENT AT SUPERFUND SITES

M. P. Esposito, J. McArdle, and J.S. Greber
PEDCo Environmental, Inc.
Cincinnati, Ohio

R. Clark
Battelle Columbus Laboratories
Columbus, Ohio

PURPOSE OF STUDY

The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA), the Superfund legislation, established a dual-phase program for responding to environmental problems caused by hazardous substances. The "removal program" involves cleanup or other actions that are taken in response to emergency conditions, or on a short-term or temporary basis. The "remedial program" involves response actions that tend to be long-term in nature and that permanently remedy problem sites.

To be eligible for cleanup under Superfund, a site must be included on the National Priorities List (NPL). As of this writing, 406 sites appear on the NPL, which was promulgated by the U.S. Environmental Protection Agency (EPA) on September 8, 1983. Currently, the EPA is proposing the addition of 133 new sites to the list.

As the number of sites on the NPL grows and as removal and remedial activities at Superfund sites accelerate, the task of decontaminating buildings, structures, and construction equipment will become increasingly important. These items often represent large capital

investments, and the costs of dismantling and disposing of such structures in a secure landfill can be very expensive. The objective of an effective decontamination program, therefore, is to return contaminated buildings, structures, and equipment to active, productive status.

This study had as its goal the development of a general guide for government personnel, cleanup contractors, and other individuals responsible for planning and executing decontamination activities at Superfund sites.

TECHNICAL APPROACH

As an initial part of the study (begun in the fall, 1983), a survey of ongoing decontamination activities at 50 Superfund sites across the country, which were thought to have potentially contaminated buildings, structures, and equipment, was conducted in order to gather information on 1) the types of contaminants of most concern and 2) the methods currently being proposed or used for decontamination of the buildings, structures, and equipment in place at these sites. Contractors and numerous other individuals with direct experience in both Superfund and non-Superfund related programs involving decontamination of dioxins, explosives, PCB's, and other toxic wastes from buildings and equipment were contacted. In addition, a thorough search of published literature for information on decontamination methods was conducted through computerized search services.

From these surveys, a decontamination data base containing state-of-the-art information on specific cleanup methods and their applications, as well as guidelines for developing site-specific cleanup strategies, was developed.

RESULTS

The 1983 survey of building/equipment decontamination practices at Superfund sites revealed that the contaminants of most concern at these sites include asbestos, acids and alkalis, dioxins, explosives, heavy metals, cyanides, low-level ionizing radiation, organic solvents, pesticides, and PCB's. The methods used to remove these substances from buildings, structures, and equipment are few in number and rarely documented in detail. For example, it is common practice to steam clean equipment such as backhoes, bulldozers, and drilling augers, but testing to verify that the contaminants of concern have been adequately removed is generally not performed. Contaminated buildings and structures are seldom cleaned and returned to active use. More often, they are closed and barricaded to prevent further entry and exposure until sometime in the future when a solution regarding their disposition can be found. Some buildings are torn down and buried in landfills. Contaminated underground structures such as tanks, sumps, and sewers are sometimes filled in place with concrete to prevent their reuse.

Because these findings clearly pointed to the need for basic guidance material on decontamination methods, the remainder of the project was devoted to developing a manual, or user's guide, for this purpose. The handbook which was developed presents general guidelines for developing a rationale and strategy (summarized in Figure 1) for dealing with the prospect of decontamination, including guidance and information for selecting the least-costly method(s) that are technologically feasible and that will effectively reduce contamination to predetermined levels. Steps in the process include 1) determining the nature and extent of contamination, 2) developing and implementing a




Figure 1. Flow diagram illustrating sequence of steps for developing a decontamination strategy.

site-specific decontamination plan, and 3) evaluating decontamination effectiveness. Step 1 consists of a) querying former employees, b) searching old business records, inspection reports, and news stories c) conducting a visual site inspection, and d) collecting and analyzing samples from the contaminated surfaces or structures. Step 2 is further broken down into the following activities: a) identifying the future intended use of buildings, structures, and equipment; b) establishing decontamination target levels for the contaminants present; c) identifying and evaluating potential decontamination methods; d) selecting the most appropriate method(s) for achieving the decontamination target levels; e) determining worker health and safety requirements (training, medical surveillance, personal protective equipment, site safety); f) writing the site decontamination plan; g) estimating costs; and h) hiring the contractor and initiating cleanup. Step 3 involves a) reinspecting the site for evidence of residual contamination, b) collecting and analyzing samples from the decontaminated area, and c) determining whether the target levels for residual contamination have been reached. This step can also include repeating, and if necessary, modifying the decontamination procedures until satisfactory results are obtained. Descriptions of actual building decontamination efforts at both Superfund and non-Superfund sites are included as case studies.

The manual contains process descriptions for 21 decontamination methodologies including both traditional and developmental techniques (asbestos abatement, absorption, demolition, dismantling, dusting/vacuuming/wiping, encapsulation, gritblasting, hydroblasting/water-washing, painting/coating, scarification, RadKleen, solvent washing,

steam cleaning, vapor-phase solvent extraction, acid etching, bleaching, flaming, drilling and spalling, K-20, microbial degradation, and photochemical degradation), and describes their potential applicability to various combinations of contaminants and materials. Potential cleanup methods are identified in a two-dimensional matrix (see Table 1) matching contaminants (asbestos, acids, alkalis, dioxins, explosives, heavy metals and cyanides, low-level radiation, organic solvents, pesticides, PCB's, and all contaminants in liquid form) with materials/surfaces (all wall, ceiling, and floor surfaces; glass; plastic; metal; wood; brick; concrete; aluminum; and equipment and auxiliary structures). Finally, the manual describes safeguards for protecting the health and safety of decontamination workers during site operations. Topics covered include personnel training, medical surveillance, personal protective equipment, and site safety.

CONCLUSIONS AND RECOMMENDATIONS FOR ADDITIONAL RESEARCH

As a result of this paper study, it has become clear that all future owners of decontaminated buildings and structures on Superfund sites should be advised of the nature of the contamination that was present, the cleanup methods used, and levels of any residual contaminants. Ensuring the transfer of such information from one site owner to the next will require a method for permanently recording this information. Regulations requiring the addition of such information to the property deed, as is required in the deed of all RCRA-permitted facilities, may be a workable solution.

The handbook which was developed will provide much of the guidance needed by site cleanup personnel for decontaminating buildings,

TABLE 1. POTENTIAL DECONTAMINATION METHODS FOR VARIOUS CONTAMINANT/MATERIAL COMBINATIONS^a

Material/surface	Contaminant										
	Asbestos	Acids	Alkalis	Dioxins	Explosives	Heavy metals and cyanide	Low-level radiation	Organic solvents	Pesticides	PCB's	All contaminants in liquid form
All wall, ceiling, and floor surfaces	1,3,4,5	3,4,6,9,16	3,4,6,9	3,4,5,6,9,21	3,4,6,9,13	3,4,5,6,8,9,16	3,4,5,6,9	3,4,6,9	3,4,6,9,13	3,4,5,6,9	2
Glass	1,3,4,5	3,4,6,9,16	3,4,6,9	3,4,5,6,9,21	8,16	3,4,5,6,8,9,16	8	3,4,6,9	16	3,4,5,6,9	1
Plastic	1,3,4,5	3,4,6,9,16	15	15	8,15,16	15	8,15	15	15,16	15	2
Metal	1,3,4,5	7	7,15	7,15	7,8,15,16,17	7,15	7,8,15	7,15	7,15,16	7,15	1
Wood	1,3,4,5	7	7,15	7,15	7,15,16,20	7,15	7,15	7,15	7,15,16,20	7,15,19	1
Brick	1,3,4,5	7	7,15	7,15	7,8,15,17,20	7,15	7,8,15	7,15	7,15,20	7,15,19	2
Concrete	1,3,4,5	7,10,18	7,10,15,18	7,10,15,18	7,8,10,15,16,17,18,20	7,10,15,18	5,7,8,10,15,17,18	7,10,15,18	7,10,15,18,19,20	7,10,15,18,19	2
Equipment and auxiliary structures (bulldozers, electrical transformers and capacitors, sumps, ventilation ducts, etc.)	1,5	4,6,11,12,13	4,6,11,12,13	4,5,6,11,12,13,21	4,6,8,11,12,13,17	4,5,6,7,8,11,12,13	4,6,8,11,12,13	4,6,11,12,13	4,6,11,12,13	4,5,6,11,12,13,14	1

Key for decontamination methods

- | | | | |
|-----------------------------|-------------------------------|------------------------------------|-------------------------------|
| 1. Asbestos abatement | 7. Abrasive gritblasting | 12. Solvent washing | 17. Flaming |
| 2. Adsorption | 8. Hydroblasting/waterwashing | 13. Steam cleaning | 18. Drilling and spalling |
| 3. Demolition | 9. Painting/coating | 14. Vapor-phase solvent extraction | 19. 8-20 coating |
| 4. Dismantling | 10. Scarification | 15. Acid etching | 20. Microbial degradation |
| 5. Dusting/vacuuming/wiping | 11. Radkleen | 16. Bleaching | 21. Photochemical degradation |
| 6. Encapsulation | | | |

^a Each cell in the matrix represents a specific contaminant/substrate combination and contains numbers corresponding to decontamination methods that either have been used in the specific interaction, or have the potential for such use, based on available information in the published literature. Each methodology can be used alone or in conjunction with one or more of the other procedures.

structures, and equipment. However, additional research is needed to bridge gaps in the state of the art in four key information areas. First, and perhaps most importantly, sampling methods for determining the type and degree of contamination existing on building/structure/equipment surfaces, both before and after cleanup efforts, are poorly developed, documented, and verified. Similarly, subsurface sampling techniques (such as corings) for determining the depth of contamination in porous substances (such as concrete or wood floors) have not been adequately developed and documented. Although "wipe tests" are often referred to in site records, the actual methodology used is rarely described in enough detail to allow simulation or reproduction by others, and the technique itself is known to be inadequate for quantitatively transferring contaminants from surfaces to wipes or swabs. Additional research in this area is badly needed.

Second, many of the decontamination techniques described in the manual were developed specifically by the U.S. Army's Installation Restoration Program. Their applicability to contaminant/material combinations encountered at Superfund sites has not been fully explored. Even where decontamination techniques are indicated for certain contaminant/material combinations, the more detailed methodology descriptions should be consulted for any future work that may be required before the methods are selected.

Third, the effectiveness of many decontamination methods currently in use has not been verified and documented. For example, the degree to which steam cleaning removes dioxin-contaminated soil particles from drilling augers has not been established. Decontamination

methods that have not previously been applied to specific contaminant/substrate combinations but show a strong potential applicability should be validated in pilot investigations. Additions/deletions to the matrix should be made accordingly. New decontamination technologies that become available also should be evaluated and added to the matrix.

Fourth, a formal, systematic approach for determining acceptable levels of contaminants remaining in and on building and equipment surfaces does not currently exist. As a result, guidance on the "how clean is clean?" issue and the establishment of target levels could not be included in this manual and must continue to be addressed on a case-by-case basis.

ACKNOWLEDGMENTS

This work was funded by the U.S. Environmental Protection Agency Municipal Environmental Research Laboratory, Solid and Hazardous Waste Research Division, Cincinnati, Ohio under Contract No. 68-03-3190. Ms. Naomi P. Barkley was the Project Officer. Others contributing to the work were Ann Crone and Mike Hessling of PEDCo, and Ann Langham, Cindy McCandlish, Scott Brown, and John B. Hallowell of Battelle.

SELECTED BIBLIOGRAPHY

Act II - How Clean is Clean? Hazardous Waste Report, 5(9):13, 1983.

Battelle Columbus Laboratories. Final Report on Evaluation of Encapsulants for Sprayed-on Asbestos-Containing Materials in Buildings. Prepared for U.S. Environmental Protection Agency under Contract No. 68-03-2552, 1979.

Battelle Columbus Laboratories. Final Report on Evaluation of Encapsulants for Sprayed-On Asbestos-Containing Materials in Buildings. U.S. Environmental Protection Agency, Industrial Environmental Research Laboratory, Cincinnati, Ohio. 1979.

Benecke, P., et al. Development of Novel Decontamination and Inerting Techniques for Explosives-Contaminated Facilities. Phase I - Identification and Evaluation of Concepts. Vols. 1 and 2. DRXTH-TE-CR-83a11, July 1983.

Bromley, J., D. C. Wilson, and E. T. Smith. Remedial Measures Following Accidental Release of Dioxin. *Chemosphere*, 12(4/5):687-703, 1983.

CH₂M Hill. Hazardous Waste Site Investigation Training Course Guide. November 1983.

Crosby, D. G. Methods of Photochemical Degradation of Halogenated Dioxins in View of Environmental Reclamation. In: *Accidental Exposure to Dioxins. Human Health Aspects*. Academic Press, Inc., New York, 1983.

Dempsey, K. B. Biotechnology Aids Disposal. *Plants, Sites and Parks*, September/October 1982, pp. 1-8+.

Di Domenico, A., et al. Accidental Release of 2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD) at Seveso, Italy. I. Sensitivity and Specificity of Analytical Procedures Adopted for TCDD Analysis. *Ecotoxicology and Environmental Safety*, 4:283-297, 1980.

Di Domenico, A., et al. Accidental Release of 2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD) at Seveso, Italy: III. Monitoring of Residual TCDD Levels in Reclaimed Buildings. *Ecotoxicology and Environmental Safety*, 4:321-326, 1980.

Di Domenico, A., et al. Accidental Release of 2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD) at Seveso: Assessment of Environmental Contamination and of Effectiveness of Decontamination Treatments. *CODATA Bulletin*, 29:53-59, 1978.

Furhman, D. Decontamination Operations at Gateway Army Ammunition Plant. DRXTH-AS-CR-83250, November 1983.

Ghezzi, I. Potential 2,3,7,8-Tetrachlorodibenzo-p-dioxin Exposure of Seveso Decontamination Workers. *Scandinavian Journal of Work Environment and Health*, 8(Suppl. 1):176-179, 1982.

Haines, R.V., and W. W. Kelley. Frankford Arsenal Decontamination/Cleanup Operation - Cleanup and Demolition of the 400 Area. Rockwell International. Pub. No. N505TI000054, November 1980.

Hawthorne, S. H. Solvent Decontamination of PCB Electrical Equipment. In: *IEEE Conference Proceedings*, Vol. IA-18, July 1982.

Johnson, W. R. Frankford Arsenal Decontamination/Cleanup Operation - Standing Operating Procedures for Cleanup of Heavy Metals and Explosive Residues and Radiological Contamination of Buildings at Frankford Arsenal. Rockwell International. Pub. No. N5050P000009, April 1980.

Johnson, W. R. Frankford Arsenal Decontamination/Cleanup Operation - Standing Operating Procedures for Cleanup of Heavy Metals and Explosive Residues From Buildings at Frankford Arsenal. Rockwell International. Pub. No. N5050P000014, August 1980.

Jones, W. E. Engineering and Development Support of General Decon Technology for the U.S. Army's Installation Restoration Program. Task 5, Facility Decontamination. Defense Technical Information Center, Alexandria, Virginia. Pub. No. 49-5002-0005, July 1982.

Marion, W. J., and Thomas, S. Decommissioning Handbook. DOE/EV/10128-1, November 1980.

Natale, A., and H. Levins. Asbestos Removal and Control. An Insiders Guide to the Business. Sourcefinders, Voorhees, New Jersey, 1984.

New York State Office of General Services. The Binghamton State Office Building Clean-up: A Progress Report Update. Albany, New York. January 1983.

Noe, L. Reclamation of the TCDD-Contaminated Seveso Area. In: Accidental Exposure to Dioxins. Human Health Aspects. Academic Press, Inc., New York, 1983.

Personal communication from V. G. Rose, Pacific Gas and Electric Company, San Francisco, California, to S. Brown, Battelle Columbus Laboratories, Columbus, Ohio, on April 17, 1984.

Pocchiari, F. 2,3,7,8-Tetrachlorodibenzo-p-dioxin Decontamination. In: Chlorinated Phenoxy Acids and Their Dioxins. Mode of Action, Health Risks and Environmental Effects. Ecological Bulletin, 27:67-70, 1978.

Rockwell International. Final Report for the Frankford Arsenal Decontamination/Cleanup Program. DRXTH-FE-CR-800, December 1980.

Roos, K. S., and P. A. Scofield. Health and Safety Considerations: Superfund Hazardous Waste Sites. In: National Conference on Management of Uncontrolled Hazardous Waste Sites, Washington, D.C., October 31 - November 2, 1983. Hazardous Materials Control Research Institute, Silver Spring, Maryland, 1983.

State of Georgia. Department of Natural Resources, Environmental Protection Division. Luminous Superfund Project Report: Remedial Action for the Removal of Ra-226 Contamination at the Luminous Processes, Inc. Site in Clarke County, Georgia. August 1982.

Strahl, H. Frankford Arsenal Decontamination/Cleanup Operation - Standing Operating Procedures for Cleanup of Explosive Residues From Buildings at Frankford Arsenal. Rockwell International. Pub. No. N505P000018, October 1980.

Tuttle, R. J. Frankford Arsenal Decontamination/Cleanup Operation - Cleanness Criteria for Release for Unrestricted Use. Rockwell International. Pub. No. N505SRR000002, October 1980.

Tuttle, R. J. Frankford Arsenal Decontamination/Cleanup Operation - Radiological Inspection for Release for Unrestricted Use. Rockwell International. Pub. No. N505SRR000004, December 1980.

U.S. Environmental Protection Agency (Region III). Federal On-Scene Coordinator's Report. Chemical Metals Industries, Inc., Baltimore, Maryland. Immediate Removal Project. Philadelphia. Undated.

U.S. Environmental Protection Agency. Guidance for Controlling Friable Asbestos-Containing Material in Buildings. EPA-560/5-83-002, March 1983.

U.S. Environmental Protection Agency, Office of Emergency and Remedial Response, Hazardous Response Support Division. Interim Standard Operating Safety Guides. Revised September 1982.

U.S. Environmental Protection Agency, Region VII. CERCLA Fund Request for Immediate Removal: Sontag Road Area Superfund Site (Draft). July 22, 1983.

Wolfe, H. R., et al. Some Problems Related to Cleanup of Parathion-Contaminated Surfaces Following Spillage. In: Proceedings of the 1976 National Conference on Control of Hazardous Material Spills. EPA-600/5-76-002, 1976.