

# 2019 SmartWay Rail Carrier Partner Tool: Technical Documentation

**U.S. Version 2.0.18 (Data Year 2018)**



# **2019 SmartWay Rail Carrier Partner Tool:**

# **Technical Documentation**

**U.S. Version 2.0.18  
(Data Year 2018)**

Transportation and Climate Division  
Office of Transportation and Air Quality  
U.S. Environmental Protection Agency

EPA-420-B-19-017  
March 2019

# Table of Contents






1.0	DATA SOURCES .....	1
2.0	EMISSION ESTIMATION .....	2
3.0	ACTIVITY INPUT VALIDATION .....	11
	REFERENCES .....	13
	APPENDIX A: LOCOMOTIVE EMISSION FACTORS .....	A-1
	APPENDIX B: SURROGATE LOCOMOTIVE DATA .....	B-1
	APPENDIX C: DERIVATION OF NATIONAL AVERAGE G/KW-HR EMISSION FACTORS .....	C-1

## List of Tables

Table 1. Example Operation Hour Allocation by Tier Level .....	3
Table 2. Emission Factors by Tier Level and Unit Type.....	3
Table 3. Emission Factors by Engine Tier Only .....	5
Table 4. National Average Railcar Volume Data (Tool Defaults).....	7
Table 5. 2011 R1 Activity Data and Rail Tool Validation Ranges.....	12
Table A-1. Line Haul Locomotive Emission Factors (grams per gal).....	A-1
Table A-2. Small Line-haul Locomotive Emission Factors (grams per gal).....	A-1
Table A-3. Yard Locomotive Emission Factors (grams per gal).....	A-1
Table B-1. Fuel Usage Surrogates .....	B-1
Table B-2. Surrogates for Estimating Annual Miles and Ton-Miles .....	B-2
Table C-1. Electric Generation Mix (From Annual Energy Outlook 2016) .....	C-1
Table C-2. Power Plant Emissions: in Grams per kWh of Electricity Available at Power Plant Gate.....	C-1
Table C-3. Power Plant Emissions: Grams per kWh of Electricity Available at User Sites (wall outlets).....	C-1

## 1.0 Data Sources

The technical approach recommended for the SmartWay railroad model was developed to encourage railroad participation by providing methods to calculate emissions, fuel consumption, and comparison metrics based, to the extent possible, based on data the participating railroad companies have on hand and provide annually to the Department of Transportation's Federal Railroad Administration (FRA). For example, the approach presented uses data elements that Class 1 railway companies submit in their annual R-1 reports. Class I Railroad companies can use their most recent R-1 data for this SmartWay Tool. The relevant data reported annually to the FRA's R-1 forms include:

-  Power Unit Information – Form 710
-  Locomotive Unit Miles – Form 755, lines 8-14
-  Railcar Miles – Form 755, line 30
-  Fuel Consumption by Fuel Type and Unit Type – Form 750, lines 1-3
-  Ton-Mile Data – Form 755, lines 104, 110, 113





As Class 2 and 3 railroads do not need to provide detailed information to the FRA, in order for them to participate in the SmartWay Program they need to develop and submit the required data specific for their operations. Where a Class 2 or 3 railroad company does not have all of the required information, surrogate data are provided in the Appendix B of this report that may be useful to develop some of the basic data required for the Tool.

## 2.0 Emission Estimation

Regardless of the locomotive class, the SmartWay Rail Tool was designed to calculate CO<sub>2</sub> performance metrics based on fuel consumption estimates, and NO<sub>x</sub> and PM emissions based on tier-specific engine operation information.

In the SmartWay Rail Tool, the data for line-haul (including short line-haul and passenger rail) and yard operations are handled separately, even though many of the data elements are the same. Line-haul and yard operations are sufficiently different that they require separate emission factors associated with the different duty cycles. If operational surrogates are needed, then these should be compiled specific to either line-haul or yard operations.

The specific Rail Tool calculation outputs include:

-  total mass emissions (CO<sub>2</sub>, NO<sub>x</sub>, PM<sub>10</sub> and PM<sub>2.5</sub>)
-  g/ton-mile (gross, revenue, non-revenue)
-  g/railcar-mile (just total miles)
-  g/truck-equivalent-mile (just total miles)

The following presents the calculation procedures used to estimate these performance metrics.

### 1. Calculating mass emissions (total grams)

- a. CO<sub>2</sub><sup>1</sup>
  - i. Diesel fuel: grams of CO<sub>2</sub> = total gallons diesel (freight + passenger + switching) x 10,180 g CO<sub>2</sub>/gallon.
  - ii. Biodiesel: The Tool uses the biodiesel blend percentage to interpolate between regular diesel and 100% biodiesel fuel factors, with 100% biodiesel = 9,460 g/gallon. Therefore 20% biodiesel (B20) has a fuel factor of 10,180 – (10,180 – 9,460) x (20/100) = 10,036 g CO<sub>2</sub>/gallon
  - iii. LNG: grams of CO<sub>2</sub> = total gallons LNG (freight + passenger + switching) x 4,394 g CO<sub>2</sub>/gallon.
  - iv. CNG: If input in cubic feet, grams of CO<sub>2</sub> = total cubic feet (freight + passenger + switching) x 57.8. If CNG input is in equivalent gallons, the Tool multiplies total gallons by 7,030 g CO<sub>2</sub>/gallon.
  - v. Electric: grams of CO<sub>2</sub> = total kWh x 607 g CO<sub>2</sub>/kWhr. See **Appendix C** for details.

---

<sup>1</sup> With the exception of the electricity factors, the source of the fuel-based CO<sub>2</sub> factors are discussed in the SmartWay Truck Tool Technical Documentation.

- b. NO<sub>x</sub> and PM
  - vi. Diesel - Data Input Methods 2 and 4 (inputs differentiated by line haul and switcher)
    - 1) The Tool first calculates the proportion of hrs/units by Tier level.
      - a) The following provides an example for line haul units:

**Table 1. Example Operation Hour Allocation by Tier Level**

Tier Level	Hrs	Fraction
<b>Non-Tier -</b>	3,000	0.15
<b>0</b>	0	0
<b>0+</b>	1,000	0.05
<b>1</b>	2,000	0.1
<b>1+</b>	5,000	0.25
<b>2</b>	0	0
<b>2+</b>	4,000	0.2
<b>3</b>	5,000	0.25
<b>4</b>	0	0
<b>Total</b>	<b>20,000</b>	<b>1.00</b>

- b) The Tool repeats this calculation for the switcher distribution
- c) The Tool then calculates weighted average fuel factors for NO<sub>x</sub> and PM, using the following table.<sup>2</sup>

**Table 2. Emission Factors by Tier Level and Unit Type**

Engine Tier	Unit Type	g/gal		
		NO <sub>x</sub>	PM <sub>10</sub>	PM <sub>2.5</sub>
<b>Non-tier</b>	Line-Haul/Passenger	270.40	6.66	6.46
	Switcher	264.48	6.69	6.49
<b>Tier 0</b>	Line-Haul/Passenger	178.88	6.66	6.46
	Switcher	191.52	6.69	6.49
<b>Tier 0 +</b>	Line-Haul/Passenger	149.76	4.16	4.04
	Switcher	161.12	3.50	3.40

<sup>2</sup> EPA 2009, Emission Factors for Locomotives.  
<https://nepis.epa.gov/Exe/ZyNET.exe/P100500B.TXT?ZyActionD=ZyDocument&Client=EPA&Index=2006+Thru+2010&Docs=&Query=&Time=&EndTime=&SearchMethod=1&TocRestrict=n&Toc=&TocEntry=&QField=&QFieldYear=&QFieldMonth=&QFieldDay=&IntQFieldOp=0&ExtQFieldOp=0&XmlQuery=&File=D%3A%5Czfiles%5Cindex%20Data%5C06thru0%5CTxt%5C00000010%5CP100500B.txt&User=ANONYMOUS&Password=anonymous&SortMethod=h%7C-&MaximumDocuments=1&FuzzyDegree=0&ImageQuality=r75g8/r75g8/x150y150q16/i425&Display=hpfr&DefSeekPage=x&SearchBack=ZyActionL&Back=ZyActionS&BackDesc=Results%20page&MaximumPages=1&ZyEntry=1&SeekPage=x&ZyPURL>

**Table 2. Emission Factors by Tier Level and Unit Type**

Engine Tier	Unit Type	g/gal		
		NO <sub>x</sub>	PM <sub>10</sub>	PM <sub>2.5</sub>
Tier 1	Line-Haul/Passenger	139.36	6.66	6.46
	Switcher	150.48	6.54	6.34
Tier 1 +	Line-Haul/Passenger	139.36	4.16	4.04
	Switcher	150.48	3.50	3.40
Tier 2	Line-Haul/Passenger	102.96	3.74	3.63
	Switcher	110.96	2.89	2.80
Tier 2+	Line-Haul/Passenger	102.96	1.66	1.61
	Switcher	110.96	1.67	1.62
Tier 3	Line-Haul/Passenger	102.96	1.66	1.61
	Switcher	68.40	1.22	1.18
Tier 4	Line-Haul/Passenger	20.80	0.31	0.30
	Switcher	15.20	0.23	0.22

i) Example calculation for the weighted NO<sub>x</sub> factor for line-haul case above:

$$\text{Weighted average} = 270.4 \times 0.15 + 178.88 \times 0.0 + 149.76 \times 0.05 + 139.36 \times 0.1 + 139.36 \times 0.25 + 102.96 \times 0.0 + 102.96 \times 0.1 + 102.96 \times 0.25 = \mathbf{132.86 \text{ g/gal NO}_x}$$

ii) The Tool repeats these calculations for PM<sub>10/2.5</sub>

iii) All calculations are then repeated for switchers

- 2) The Tool multiplies gallons of (freight + passenger) diesel by weighted average fuel factors for line-haul/passenger category.
  - 3) The Tool multiplies gallons of switcher diesel by weighted average fuel factors for switchers.
  - 4) The Tool sums grams for line-haul/passenger and switchers to obtain total tons for NO<sub>x</sub>, PM<sub>10</sub> and PM<sub>2.5</sub>.
- ii. Diesel - Data Input Methods 1 and 3 (inputs NOT differentiated by line haul and switcher)
- 1) The Tool uses Table 2 to calculate the weighted average fuel factors<sup>3</sup>

<sup>3</sup> The factors in Table 2 are calculated by weighting the line haul/passenger and switcher values from Table 1 by the national average relative fuel consumption levels for these categories (0.925 and 0.075, respectively). National average values were obtained from 2010 R-1 reports.



**Table 3. Emission Factors by Engine Tier Only**

Engine Tier	g/gal		
	NO <sub>x</sub>	PM <sub>10</sub>	PM <sub>2.5</sub>
<b>Non-Tier</b>	269.96	6.66	6.46
<b>Tier 0</b>	179.83	6.66	6.46
<b>Tier 0+</b>	150.61	4.11	3.99
<b>Tier 1</b>	140.19	6.65	6.45
<b>Tier 1+</b>	140.19	4.11	3.99
<b>Tier 2</b>	103.56	3.68	3.57
<b>Tier 2+</b>	103.56	1.66	1.61
<b>Tier 3</b>	100.37	1.63	1.58
<b>Tier 4</b>	20.38	0.31	0.30

- 2) The Tool follows the same process as for Data Input Methods 2 and 4, but there is no need to sum across unit types (step 4 above).

iii. Biodiesel –

- 1) Biodiesel NO<sub>x</sub> and PM<sub>10/2.5</sub> emissions are calculated by applying an adjustment factor to diesel emissions. Therefore the first is to multiply the biodiesel gallons by the diesel fuel factors as described above to calculate an unadjusted estimate for grams of NO<sub>x</sub>, PM<sub>10</sub> and PM<sub>2.5</sub>.
- 2) Next the Tool calculates adjustment factors based on % biodiesel blend specified – see Truck Tool Technical Documentation for references.
  - a) % change in emissions =  $\{ \text{expla} \times (\text{vol}\% \text{ biodiesel}) \} - 1 \times 100\%$

Where a = 0.0009794 for NO<sub>x</sub>, and a = -0.006384 for PM<sub>10/2.5</sub>

- b) The Tool applies the adjustment factor to the unadjusted grams of NO<sub>x</sub> and PM<sub>10/2.5</sub> calculated above. In general PM emissions are somewhat lower than diesel emissions, while NO<sub>x</sub> emissions increase slightly.

iv. LNG – <sup>4</sup>

- 1) The Tool first sums total gallons of LNG across line-haul, passenger, and switchers
- 2) The Tool then multiplies total gallons by 20.3 g/gal to obtain grams NO<sub>x</sub>; and by 1.35 g/gal to obtain PM<sub>10</sub>. The Tool multiplies the gallons value by 1.31 to obtain PM<sub>2.5</sub>. See Appendix A regarding the source of these fuel-based factors.

<sup>4</sup> LNG, CNG, and Electricity factors do not vary with engine tier. Therefore the Tool does not calculate weighted averages based on tier level distributions, but simply uses the gallons and/or kWh amounts from the Operations screen.

v. CNG –

- 1) The Tool converts cubic feet of CNG to gallons if necessary with 1 standard cubic foot of CNT = 0.00823 equivalent gallons.
- 2) The Tool sums total gallons of CNG across line-haul, passenger, and switchers
- 3) The Tool multiplies total gallons by 20.3 g/gal to obtain grams NO<sub>x</sub>; and by 1.35 g/gal to obtain PM<sub>10</sub>. The Tool multiplies the gallons value by 1.31 to obtain PM<sub>2.5</sub>. See Appendix A regarding the source of these fuel-based factors.

vi. Electricity –

- 1) The Tool sums total kWh of electricity across line-haul, passenger, and switchers
- 2) The Tool then multiplies total kWh by 0.400 to obtain grams NO<sub>x</sub>; by 0.091 for grams PM<sub>10</sub>; and by 0.037 for grams PM<sub>2.5</sub>. See Appendix C for details.

2. **Calculate g/ton-mile for each pollutant (three types of “ton-miles”)**

- a. Grams per gross ton-mile: the Tool divides the grams of each pollutant (fleet total) by gross ton miles entered on Operations screen.
- b. Grams per revenue ton-mile: the Tool divides the grams of each pollutant (fleet total) by revenue ton miles entered on Operations screen.<sup>5</sup>
- c. Grams per non-revenue ton-mile: the Tool divides the grams of each pollutant (fleet total) by non-revenue ton miles entered on Operations screen.

3. **Calculate g/railcar-mile for each pollutant<sup>6</sup>**

- a. The Tool divides the grams of each pollutant by total railcar miles entered

4. **Calculate g/truck-equivalent-mile**

- a. Since rail operators do not provide railcar type/volume information, a national default value of 6,091 cubic feet per car is assumed for all carriers – see the **Shipper Tool Technical Documentation** for details.
- b. Calculate the “truckload equivalents” factor (TE): divide the national average railcar volume by 3,780 cubic feet.<sup>7</sup>
- c. g/truck-equivalent-mile = g/railcar-mile / TE, and is calculated for each pollutant.

---

<sup>5</sup> Value reported in SmartWay Public Bin Export Report.

<sup>6</sup> Ibid.

<sup>7</sup> Truck industry average freight volume is 2.78 TEU = 3,780 cubic feet (see Shipper Tool Technical Documentation).

**Table 4. National Average Railcar Volume Data (Tool Defaults)**

Type in Tool	Railcar Type	Cubic Feet	Source/Assumption <i>Key:</i> Norfolk Southern (NS), Union Pacific (UP), Burlington Northern Santa Fe (BNSF), CSX Transportation (CSX), Guide to Railcars (GTRC), Chicago Rail Car Leasing (CRCL), Union Tank Car Company (UTCC), U.S Department of Agriculture (USDA)
<b>Box-Plain 50' + Box Equipped</b>	Boxcar 50 ft and longer including equipped boxcars	7,177	Based on the average of the following boxcar types: <u>50ft</u> assumed to be 5694 [reflecting the average of 5355 (NS), 5431 (UP), 5238 (CSX), 6175 (BNSF), 6269 (GTRC)]. <u>60ft</u> assumed to be 6,648 [reflecting the average of 6618 (NS), 6389 (UP), 6085 (CSX), 7500 (BNSF)]. <u>50ft high cube</u> assumed to be 6,304 [reflecting the average of 6339 (NS) and 6269 (CSX)]. <u>60 ft high cube</u> assumed to be 6917 [reflecting the average of 7499 (NS), 6646 (CSX), and 6607 (GTRC)]. <u>86ft</u> assumed to be 9999 (NS). <u>Autoparts</u> assumed to be 7499 (NS).
<b>Box-Plain 40'</b>	Boxcar 40ft	4,555	Based on estimate of 50ft boxcar volume described above. Assumed 40ft length would result in 20% reduction in volume.
<b>Flat TOFC/COFC Flat General Service Flat all other</b>	Flat car – all types except for multi-level	6,395	Based on the average of the following flat car types: <u>60ft</u> assumed to be 6739 (BNSF). <u>89ft</u> assumed to be 9372(BNSF). <u>Coil</u> assumed to be 3387(NS). <u>Covered coil</u> assumed to be 5294 [reflecting the average of 8328 (NS) and 2260 (BNSF)]. <u>Centerbeam</u> assumed to be 6546 [reflecting the average of 5857 (UP) and 7236 (BNSF)]. <u>Bulkhead</u> assumed to be 7030 (BNSF).
<b>Flat Multi level</b>	Multi-level flat car	13,625	Based on the average of the following multi-level flat car types: <u>Unilevel</u> (that carry very large cargo, such as <u>vehicles/tractors</u> ) assumed to be 12183 (NS). <u>Bi-level</u> assumed to be 14381(NS). <u>Tri-level</u> assumed to be 14313 (based on average of 15287 (NS) and 13339 (BNSF)).
	Flat Car – all types-including multi-level	7,428	Based on the average volumes of the flatcar types described above including multi-level as a single flat car type.
<b>Gondola Plain Gondola Equipped</b>	Gondola – all types Including equipped	5,190	Based on the average of the following gondola car types: <u>52-53ft</u> assumed to be 2626 [based on average of 2665 (NS), 2743 (CSX), 2400 (BNSF), and 2697(CRLC)].

**Table 4. National Average Railcar Volume Data (Tool Defaults)**

Type in Tool	Railcar Type	Cubic Feet	Source/Assumption <i>Key:</i> Norfolk Southern (NS), Union Pacific (UP), Burlington Northern Santa Fe (BNSF), CSX Transportation (CSX), Guide to Railcars (GTRC), Chicago Rail Car Leasing (CRCL), Union Tank Car Company (UTCC), U.S Department of Agriculture (USDA)
			<p><u>60-66ft</u> assumed to be 3372 [based on average of 3281 (NS), 3242 (CSX), 3350 (BNSF), CRCL-3670, and 3366 (GTRC)].</p> <p><u>Municipal Waste</u> assumed to be 7999 (NS).</p> <p><u>Woodchip</u> assumed to be 7781 [based on average of 7862 (NS) and 7700 (CRCL)].</p> <p><u>Coal</u> assumed to be 4170 [based on average of 3785 (NS) and 4556 (BNSF)].</p>
<b>Refrigerator Mechanical</b> <b>Refrigerated non-mechanical</b>	Refrigerated - Mechanical /non-Mechanical	6,202	Based on the average of the following refrigerated car types: <u>48-72ft</u> assumed to be 6963 [based on average of 6043 (UP) and 7883 (BNSF)]. <u>50ft</u> assumed to be 5167(GTRC). <u>40-90 ft</u> assumed to be 6476 [based on average of 6952 (UP) and 6000 (BNSF)].
<b>Hopper Open Top-General Service</b>	Open Top Hopper	4,220	Based on the average of the following open top hopper car types: <u>42ft</u> assumed to be 3000 (UP). <u>54ft</u> assumed to be 3700 (UP). <u>60ft</u> assumed to be 5188 [based on average of 5125 (UP) and 5250 (GTRC)]. <u>45ft+</u> assumed to be 4105 [based on average of 4500 (UP) and 3710 (BNSF)]. <u>Woodchip</u> assumed to be 7075 [based on average of 7525 (NS), 5999 (UP), and 7700 (CRCL)]. <u>Small Aggregate</u> assumed to be 2252 [based on average of 2150 (NS), 2106 (BNSF), and 2500 (CRCL)].
<b>Hopper Covered</b>	Covered Top Hopper	4,188	Based on the average of the following covered top hopper car types: <u>45ft</u> assumed to be 5250 (GTRC). <u>Aggregate</u> assumed to be 2575 [based on average of 2150 (NS) and 3000 (CRCL)]. <u>Small Cube Gravel</u> assumed to be 2939 [based on average of 2655 (NS), 3100 (CSX), and 3063 (BNSF)]. <u>Med-Large Cube Ores and Sand</u> assumed to be 4169 [based on average of 3750 (NS) and 4589 (BNSF)]. <u>Jumbo</u> assumed to be 5147 [based on average of 4875 (NS), 4462 (CSX), 5175 (BNSF), and 6075 (CRCL)]. <u>Pressure Differential (flour)</u> assumed to be 5050 [based on average of 5124 (NS) and 4975 (CRCL)].

**Table 4. National Average Railcar Volume Data (Tool Defaults)**

Type in Tool	Railcar Type	Cubic Feet	Source/Assumption <i>Key:</i> Norfolk Southern (NS), Union Pacific (UP), Burlington Northern Santa Fe (BNSF), CSX Transportation (CSX), Guide to Railcars (GTRC), Chicago Rail Car Leasing (CRCL), Union Tank Car Company (UTCC), U.S Department of Agriculture (USDA)
<b>Tank under 22,000 gallons</b>	Tank Cars under 22,000 gallons	2,314	Assumes 1 gallon=0.1337 cubic foot (USDA). Based on small tank car average volume of 17304 gallons, which is the average of the following currently manufactured tank car volume design capacities of 13470, 13710, 15100, 15960, 16410, 17300, 19900, 20000, 20590, and 20610 gallons (GTRC).
<b>Tank over 22,000 gallons</b>	Tank Cars over 22,000 gallons	3,857	Assumes 1 gallon=0.1337 (USDA). Based on large tank car volume of 28851 gallons, which is the average of the following currently manufactured tank car volume design capacities of 23470, 25790, 27200, 28700, 30000, 33000, and 33800 gallons (GTRC).
<b>All other cars Work Equip &amp; company Freight No payment car-miles</b>	All Other Cars	5,014	Based on average volume presented above for each of the nine railcar types (all flatcars are represented by the line item that includes multi-level flatcars - 7428).

**References**

Burlington Northern Santa Fe Railway (BNSF), Available at: <http://www.bnsf.com/customers/how-can-i-ship/individual-railcar/#%23subtabs-3>

CSX Transportation (CSXT), Customer Equipment. Available at: <https://www.csx.com/index.cfm/customers/resources/equipment/>

Norfolk Southern Railway Company (NS), Customer Equipment. Available at: <http://www.nscorp.com/content/nscorp/en/shipping-tools/equipment-guide/merchandise-equipment.html>

Union Pacific Railroad (UP), Customer Equipment, Car Types. Available at: <http://www.uprr.com/customers/equip-resources/cartypes/index.shtml>

Chicago Rail Car Leasing (CRCL), Rail Car Types. Available at: <https://www.crdx.com/railcars>

Surface Transportation Board (STB), Industry Data, Economic Data and Statistical Reports, Class 1 Annual Report Financial Form R-1. Available at [http://www.stb.dot.gov/stb/industry/econ\\_reports.html](http://www.stb.dot.gov/stb/industry/econ_reports.html)

United States Department of Agriculture, Economic Research Service, 20005-4788, June 1992, Agricultural Handbook Number 697, Washington, DC. Available at: <https://www.ers.usda.gov/publications/pub-details/?pubid=41881>



Union Tank Car Company, Chicago, IL, Basic Design Specifications. Available at: <https://www.utlx.com/>

## 3.0 Activity Input Validation

SmartWay has developed general validation criteria based on 2011 R-1 report data in order to perform range checks on Partner activity inputs. These range checks are simply intended to identify unreasonable data entries only. Table 4 summarizes the R-1 data used for each Class 1 Rail Line, as well as the range check values derived from the carrier-specific data. Range check values are displayed in bold.

Maximum acceptable values for fuel use, ton-miles, car-miles, and unit miles for Class 1 operators were set equal to three times the rail-line specific maximum shown in the table. Similarly, minimum acceptable values for Class 1 operators were set equal to one tenth for fuel use, ton-miles, car-miles, and unit miles. Maximum acceptable values for Class 2 and 3 operators were set at one tenth of the Class 1 maximum value.

SmartWay will re-evaluate validation ranges to make them more precise, comprehensive, and consistent as Rail Partner data is collected in the future.

**Table 5. 2011 R1 Activity Data and Rail Tool Validation Ranges**

Rail Line	Total Fuel Use (gallons diesel oil)	Gross ton miles total (thousands)	Revenue Freight ton miles (thousands)	Non revenue Freight ton miles (thousands)	Total freight car miles (thousands)	Total Locomotive unit miles	Locomotive Train switching unit miles	Locomotive Yard switching unit miles
<b>BNSF</b>	1,340,634,000	1,200,654,478	648,431,637	6,117,197	11,316,277	495,865,213	2,161,568	14,323,105
<b>CSX</b>	500,735,225	456,207,620	228,394,651	1,216,165	4,789,143	186,017,342	6,557,484	14,352,854
<b>GTC</b>	124,776,076	105,195,469	51,253,084	518,201	1,241,217	31,375,934	2,686,536	4,714,915
<b>KCSR</b>	64,833,378	55,889,957	30,485,863	1,338,343	628,431	23,846,725	516,654	26,504,929
<b>NS</b>	473,887,662	392,056,820	191,712,562	1,267,931	4,327,021	170,767,368	7,042,003	14,060,355
<b>Soo</b>	72,442,000	70,325,676	34,581,354	333,090	807,927	27,407,979	2,686,353	2,577,600
<b>UP</b>	1,117,851,152	1,072,705,764	544,397,317	5,485,720	11,012,608	424,786,444	12,635,406	19,169,964
<b>Class 1 max</b>	4,021,902,000	3,601,963,434	1,945,294,911	18,351,591	33,948,831	1,487,595,639	37,906,218	79,514,787
<b>Class 1 min</b>	6,483,338	5,588,996	3,048,586	33,309	62,843	2,384,673	51,665	257,760
<b>Class 2/3 max</b>	134,063,400	120,065,448	64,843,164	611,720	1,131,628	49,586,521	1,263,541	2,650,493
<b>Class 2/3 min</b>	> 0	> 0	> 0	> 0	> 0	> 0	> 0	> 0



## References

### **California Air Resource Board**

*Rail Yard Agreement*, Sacramento California 2007.

### **U.S. Department of Transportation**

Bureau of Transportation Statistics, *Freight in America*, January 2006.

### **U.S. Department of Transportation**

Surface Transportation Board, Form R-1

### **United States Code of Federal Regulations**

Title 40 Section Chapter 1, Subchapter Q, Part 600.113, Fuel Economy Calculations

### **U.S. Environmental Protection Agency**

Regulatory Support Document: Locomotive Emission Standards Final Rule, 1997.

### **U.S. Environmental Protection Agency**

2009 Locomotive Emission Factor Study, Ann Arbor, MI.2009.

### **U.S. Environmental Protection Agency**

MARKAL Input Data for non-Light Duty Vehicles, Research Triangle Park, NC 2009

# Appendix A: Locomotive Emission Factors

## A-1. FUEL-BASED EMISSION FACTORS

**Table A-1. Line Haul Locomotive Emission Factors (grams per gal)**

Pollutant	NO <sub>x</sub>	PM <sub>10</sub>	CO <sub>2</sub>
<b>Diesel</b>	270.40 <sup>2</sup>	6.66 <sup>2</sup>	10,180
<b>Biodiesel (B-20)</b>	173 <sup>1</sup>	7.88 <sup>1</sup>	9,460 <sup>4</sup>
<b>CNG</b>			7,030 <sup>4</sup>
<b>LNG</b>	20.3 <sup>3</sup>	1.35 <sup>3</sup>	3,865 <sup>4</sup>

1. MARKAL data (2009)
2. EPA Locomotive Emission Factors (2009)
3. ARB Rail Yard Agreement (2007) in terms of diesel equivalents
4. 40 CFR 600.113

**Table A-2. Small Line-haul Locomotive Emission Factors (grams per gal)**

Small Line Haul	Emission Factor
	g/gal
<b>NO<sub>x</sub></b>	236.60
<b>PM<sub>10</sub></b>	5.82
<b>CO<sub>2</sub></b>	10,180

Uncontrolled yard locomotive emission factors were obtained from EPA's Locomotive Emission Factors (2009).

**Table A-3. Yard Locomotive Emission Factors (grams per gal)**

Yard	Emission Factor
	g/gal
<b>NO<sub>x</sub></b>	264.48
<b>PM<sub>10</sub></b>	6.69
<b>CO<sub>2</sub></b>	10,180

Uncontrolled yard locomotive emission factors were obtained from EPA's Locomotive Emission Factors (2009). All emission factors listed here reflect uncontrolled (i.e., pre-Tier 0) emission levels.

# Appendix B: Surrogate Locomotive Data

## SURROGATE DATA FOR EMISSION ESTIMATION

Data provided in the R-1 reports have been compiled and evaluated to identify useful surrogates that may help Partners gap-fill missing data. Because the data is from Class I operations, it may be biased to larger operations.

## SURROGATES FOR CALCULATING FUEL CONSUMPTION

The basic approach allows for emission calculations that roughly approximate emissions using reported total annual fuel consumption. If annual fuel consumption data are unknown, surrogate data, such as locomotive population, miles traveled, annual ton-miles or TEU-miles, can be used to provide an estimate for line-haul locomotive fuel consumption, as noted in the following table.

**Table B-1. Fuel Usage Surrogates**

Line Haul Surrogate Data Options in Absence of Annual Fuel Usage	Number of Locomotives	Total Annual Locomotive Miles	Total Annual Ton Miles Freight Transported	Total Annual TEU mile Equivalents
<b>Multiplication Factor for estimating Annual Fuel Usage (gal/yr)</b>	132,800 (gal/yr*locomotive)	2.44 (gal/locomotive miles)	0.002 (gal/ton miles freight transported)	0.053 (gal/TEU-mile Equivalents)

Values used to develop the surrogates were derived from the Bureau of Transportation Statistics 2012 National Transportation Statistics Table 4-17 ([http://www.bts.gov/publications/national\\_transportation\\_statistics/html/table\\_04\\_17.html](http://www.bts.gov/publications/national_transportation_statistics/html/table_04_17.html))

When using the basic approach to estimate yard locomotive emissions, the number of locomotives can be applied to the fuel consumption factors noted in the following equation to estimate annual fuel usage:

$$\text{Yard Fuel Use (gal/yr)} = 195,451 \text{ (gal/yr*yard locomotive)} \times \text{Number of Yard Locomotives}$$

## SURROGATES FOR METRIC COMPARISONS

The railroad model is designed to apply calculated emissions to a variety of operational parameters. This allows the derivation of metrics that can be used as a reference point to evaluate a Partner's environmental performance relative to others.

In instances where the necessary information has not been provided, surrogate data presented in Table B-2, may be used to estimate total miles traveled or the total annual ton-miles, based on the number of active line-haul locomotives in the Partner's fleet.

**Table B-2. Surrogates for Estimating Annual Miles and Ton-Miles**

Metric for Which Surrogate Data is Needed	Total Annual Train Miles Traveled	Total Annual Ton Miles
<b>Multiplication Factor for Estimating Train miles or ton-miles based on the Number of Locomotives</b>	54,400 (miles/yr*locomotive)	63,744,000 (ton-miles/yr*locomotive)

# Appendix C: Derivation of National Average g/kW-hr Emission Factors

FROM ARGONNE GREET MODEL Version 2016. <http://greet.es.anl.gov/>

**Table C-1. Electric Generation Mix (From Annual Energy Outlook 2016)**

	U.S. Mix
Residual oil	0.7%
Natural gas	32.9%
Coal	33.5%
Nuclear power	19.7%
Biomass	1.0%
Others	12.2%

Others = Hydro, Wind, Geothermal, Solar PV etc.  
Electric Transmission and Distribution Loss = 8.0%

**Table C-2. Power Plant Emissions: in Grams per kWh of Electricity Available at Power Plant Gate**

	GREET Calculated Emission Factors				
	By Fuel Type Plants (Stationary and Transportation)				
	4.3	0.41	0.49		0.366
PM <sub>10</sub>	0.18	0.01379	0.16	2.08	0.083
PM <sub>2.5</sub>	0.13	0.01344	0.062	0.61	0.034
CO <sub>2</sub>	950	440	960	1,530	559
CO <sub>2</sub> in burnt biomass from atmosphere				-750	

Assumes no emissions from nuclear power plants or "Others"

**Table C-3. Power Plant Emissions: Grams per kWh of Electricity Available at User Sites (wall outlets)**

	Total delivered based on US electric generation mix
NO <sub>x</sub>	0.40
PM <sub>10</sub>	0.091
PM <sub>2.5</sub>	0.037
CO <sub>2</sub>	607

Total power plant gate emissions/(1-electric transmission and distribution loss)



For more information:

U. S. Environmental Protection Agency  
Office of Transportation and Air Quality  
1200 Pennsylvania Ave. NW  
Washington, DC 20460  
(734) 214-4333

[www.epa.gov/transportation-air-pollution-and-climate-change](http://www.epa.gov/transportation-air-pollution-and-climate-change)

U. S. Environmental Protection Agency  
National Vehicle and Fuel Emissions Laboratory  
2565 Plymouth Rd.  
Ann Arbor, MI 48105  
(734) 214-4200

[www.epa.gov/aboutepa/about-national-vehicle-and-fuel-emissions-laboratory-nvfel](http://www.epa.gov/aboutepa/about-national-vehicle-and-fuel-emissions-laboratory-nvfel)